

NVIDIA Performance Primitives (NPP)

Version 4.0

February 11, 2011

Contents

1	NVIDIA Performance Primitives	1
1.1	What is NPP?	1
1.2	Documentation	1
1.3	Technical Specifications	1
1.4	Files	2
1.4.1	Header Files	2
1.4.2	Library Files	2
1.5	Supported NVIDIA Hardware	2
2	General API Conventions	3
2.1	Memory Management	4
2.2	Function Naming	4
2.3	Integer Result Scaling	4
3	Signal-Processing Specific API Conventions	7
3.1	Signal Data	8
3.1.1	Parameter Names for Signal Data	8
3.1.1.1	Source Signal Pointer	8
3.1.1.2	Destination Signal Pointer	8
3.1.1.3	In-Place Signal Pointer	8
3.1.2	Signal Data Alignment Requirements	9
3.1.3	Signal Data Related Error Codes	9
3.2	Signal Length	9
3.2.1	Length Related Error Codes	9
4	Imaging-Processing Specific API Conventions	11
4.1	Function Naming	12
4.2	Image Data	12
4.2.1	Line Step	13

4.2.2	Parameter Names for Image Data	13
4.2.2.1	Passing Source-Image Data	13
4.2.2.2	Passing Destination-Image Data	14
4.2.2.3	Passing In-Place Image Data	14
4.2.3	Image Data Alignment Requirements	14
4.2.4	Image Data Related Error Codes	15
4.3	Region-of-Interest (ROI)	15
4.3.1	ROI Related Error Codes	15
5	Module Index	17
5.1	Modules	17
6	Data Structure Index	19
6.1	Data Structures	19
7	Module Documentation	21
7.1	NPP Core	21
7.1.1	Detailed Description	21
7.1.2	Function Documentation	22
7.1.2.1	nppGetGpuComputeCapability	22
7.1.2.2	nppGetGpuName	22
7.1.2.3	nppGetGpuNumSMs	22
7.1.2.4	nppGetLibVersion	22
7.1.2.5	nppGetMaxThreadsPerBlock	22
7.1.2.6	nppGetStream	22
7.1.2.7	nppSetStream	23
7.2	NPP Type Definitions and Constants	24
7.2.1	Define Documentation	27
7.2.1.1	NPP_MAX_16S	27
7.2.1.2	NPP_MAX_16U	27
7.2.1.3	NPP_MAX_32S	27
7.2.1.4	NPP_MAX_32U	27
7.2.1.5	NPP_MAX_64S	27
7.2.1.6	NPP_MAX_8S	27
7.2.1.7	NPP_MAX_8U	28
7.2.1.8	NPP_MAXABS_32F	28
7.2.1.9	NPP_MAXABS_64F	28
7.2.1.10	NPP_MIN_16S	28

7.2.1.11	NPP_MIN_16U	28
7.2.1.12	NPP_MIN_32S	28
7.2.1.13	NPP_MIN_32U	28
7.2.1.14	NPP_MIN_64S	28
7.2.1.15	NPP_MIN_8S	28
7.2.1.16	NPP_MIN_8U	28
7.2.1.17	NPP_MINABS_32F	28
7.2.1.18	NPP_MINABS_64F	29
7.2.2	Enumeration Type Documentation	29
7.2.2.1	NppCmpOp	29
7.2.2.2	NppGpuComputeCapability	29
7.2.2.3	NppHintAlgorithm	29
7.2.2.4	NppiAxis	29
7.2.2.5	NppiInterpolationMode	30
7.2.2.6	NppRoundMode	30
7.2.2.7	NppStatus	30
7.3	Basic NPP Data Types	32
7.3.1	Typedef Documentation	33
7.3.1.1	Npp16s	33
7.3.1.2	Npp16u	33
7.3.1.3	Npp32f	33
7.3.1.4	Npp32s	33
7.3.1.5	Npp32u	33
7.3.1.6	Npp64f	33
7.3.1.7	Npp64s	33
7.3.1.8	Npp64u	33
7.3.1.9	Npp8s	33
7.3.1.10	Npp8u	33
7.4	NPP Image Processing	34
7.4.1	Function Documentation	73
7.4.1.1	nppiAbsDiff_32f_C1R	73
7.4.1.2	nppiAbsDiff_32s_C1R	73
7.4.1.3	nppiAbsDiff_8u_AC4R	74
7.4.1.4	nppiAbsDiff_8u_C1R	74
7.4.1.5	nppiAbsDiff_8u_C4R	75
7.4.1.6	nppiAbsDiffC_32f_C1R	75

7.4.1.7	nppiAdd_32f_C1R	75
7.4.1.8	nppiAdd_32s_C1R	76
7.4.1.9	nppiAdd_8u_AC4RSfs	76
7.4.1.10	nppiAdd_8u_C1RSfs	77
7.4.1.11	nppiAdd_8u_C4RSfs	77
7.4.1.12	nppiAddC_32f_C1R	77
7.4.1.13	nppiAddC_32fc_C1R	78
7.4.1.14	nppiColorTwist32f_8u_AC4R	78
7.4.1.15	nppiColorTwist32f_8u_C3R	79
7.4.1.16	nppiColorTwist32f_8u_P3R	79
7.4.1.17	nppiCompare_32f_C1R	79
7.4.1.18	nppiCompare_8u_AC4R	80
7.4.1.19	nppiCompare_8u_C4R	80
7.4.1.20	nppiConvert_16s32f_C1R	81
7.4.1.21	nppiConvert_16s32s_C1R	81
7.4.1.22	nppiConvert_16s8u_AC4R	82
7.4.1.23	nppiConvert_16s8u_C1R	82
7.4.1.24	nppiConvert_16s8u_C4R	82
7.4.1.25	nppiConvert_16u32f_C1R	83
7.4.1.26	nppiConvert_16u32s_C1R	83
7.4.1.27	nppiConvert_16u8u_AC4R	83
7.4.1.28	nppiConvert_16u8u_C1R	84
7.4.1.29	nppiConvert_16u8u_C4R	84
7.4.1.30	nppiConvert_32f16s_C1R	85
7.4.1.31	nppiConvert_32f16u_C1R	85
7.4.1.32	nppiConvert_32f8u_C1R	85
7.4.1.33	nppiConvert_8u16s_AC4R	86
7.4.1.34	nppiConvert_8u16s_C1R	86
7.4.1.35	nppiConvert_8u16s_C4R	87
7.4.1.36	nppiConvert_8u16u_AC4R	87
7.4.1.37	nppiConvert_8u16u_C1R	87
7.4.1.38	nppiConvert_8u16u_C4R	88
7.4.1.39	nppiConvert_8u32f_C1R	88
7.4.1.40	nppiCopy_16s_AC4R	88
7.4.1.41	nppiCopy_16s_C1R	89
7.4.1.42	nppiCopy_16s_C4R	89

7.4.1.43	nppiCopy_16u_AC4R	89
7.4.1.44	nppiCopy_16u_C1R	90
7.4.1.45	nppiCopy_16u_C4R	90
7.4.1.46	nppiCopy_32f_AC4R	90
7.4.1.47	nppiCopy_32f_C1R	91
7.4.1.48	nppiCopy_32f_C4R	91
7.4.1.49	nppiCopy_32s_AC4R	91
7.4.1.50	nppiCopy_32s_C1R	92
7.4.1.51	nppiCopy_32s_C4R	92
7.4.1.52	nppiCopy_8u_AC4R	92
7.4.1.53	nppiCopy_8u_C1R	93
7.4.1.54	nppiCopy_8u_C4R	93
7.4.1.55	nppiCopyConstBorder_32s_C1R	93
7.4.1.56	nppiCopyConstBorder_8u_AC4R	94
7.4.1.57	nppiCopyConstBorder_8u_C1R	94
7.4.1.58	nppiCopyConstBorder_8u_C4R	95
7.4.1.59	nppiDCTQuantFwd8x8LS_JPEG_8u16s_C1R	95
7.4.1.60	nppiDCTQuantInv8x8LS_JPEG_16s8u_C1R	96
7.4.1.61	nppiDilate_8u_C1R	96
7.4.1.62	nppiDilate_8u_C4R	97
7.4.1.63	nppiDiv_32f_C1R	97
7.4.1.64	nppiDiv_32s_C1R	98
7.4.1.65	nppiDiv_8u_AC4RSfs	98
7.4.1.66	nppiDiv_8u_C1RSfs	98
7.4.1.67	nppiDiv_8u_C4RSfs	99
7.4.1.68	nppiDivC_32f_C1R	99
7.4.1.69	nppiDivC_32fc_C1R	100
7.4.1.70	nppiErode_8u_C1R	100
7.4.1.71	nppiErode_8u_C4R	101
7.4.1.72	nppiEvenLevelsHost_32s	101
7.4.1.73	nppiExp_32f_C1R	101
7.4.1.74	nppiFilter_8u_C1R	102
7.4.1.75	nppiFilter_8u_C4R	102
7.4.1.76	nppiFilterBox_8u_C1R	103
7.4.1.77	nppiFilterBox_8u_C4R	103
7.4.1.78	nppiFilterColumn_8u_C1R	104

7.4.1.79	<code>nppiFilterColumn_8u_C4R</code>	104
7.4.1.80	<code>nppiFilterMax_8u_C1R</code>	105
7.4.1.81	<code>nppiFilterMax_8u_C4R</code>	105
7.4.1.82	<code>nppiFilterMin_8u_C1R</code>	106
7.4.1.83	<code>nppiFilterMin_8u_C4R</code>	106
7.4.1.84	<code>nppiFilterRow_8u_C1R</code>	107
7.4.1.85	<code>nppiFilterRow_8u_C4R</code>	107
7.4.1.86	<code>nppiFree</code>	108
7.4.1.87	<code>nppiGetAffineBound</code>	108
7.4.1.88	<code>nppiGetAffineQuad</code>	108
7.4.1.89	<code>nppiGetAffineTransform</code>	109
7.4.1.90	<code>nppiGetPerspectiveBound</code>	109
7.4.1.91	<code>nppiGetPerspectiveQuad</code>	110
7.4.1.92	<code>nppiGetPerspectiveTransform</code>	110
7.4.1.93	<code>nppiGraphcut_32s8u</code>	110
7.4.1.94	<code>nppiGraphcutGetSize</code>	111
7.4.1.95	<code>nppiHistogramEven_16s_AC4R</code>	112
7.4.1.96	<code>nppiHistogramEven_16s_C1R</code>	112
7.4.1.97	<code>nppiHistogramEven_16s_C4R</code>	113
7.4.1.98	<code>nppiHistogramEven_16u_AC4R</code>	113
7.4.1.99	<code>nppiHistogramEven_16u_C1R</code>	114
7.4.1.100	<code>nppiHistogramEven_16u_C4R</code>	114
7.4.1.101	<code>nppiHistogramEven_8u_AC4R</code>	114
7.4.1.102	<code>nppiHistogramEven_8u_C1R</code>	115
7.4.1.103	<code>nppiHistogramEven_8u_C4R</code>	115
7.4.1.104	<code>nppiHistogramEvenGetBufferSize_16s_AC4R</code>	116
7.4.1.105	<code>nppiHistogramEvenGetBufferSize_16s_C1R</code>	116
7.4.1.106	<code>nppiHistogramEvenGetBufferSize_16s_C4R</code>	116
7.4.1.107	<code>nppiHistogramEvenGetBufferSize_16u_AC4R</code>	117
7.4.1.108	<code>nppiHistogramEvenGetBufferSize_16u_C1R</code>	117
7.4.1.109	<code>nppiHistogramEvenGetBufferSize_16u_C4R</code>	117
7.4.1.110	<code>nppiHistogramEvenGetBufferSize_8u_AC4R</code>	118
7.4.1.111	<code>nppiHistogramEvenGetBufferSize_8u_C1R</code>	118
7.4.1.112	<code>nppiHistogramEvenGetBufferSize_8u_C4R</code>	118
7.4.1.113	<code>nppiHistogramRange_16s_AC4R</code>	118
7.4.1.114	<code>nppiHistogramRange_16s_C1R</code>	119

7.4.1.115 nppiHistogramRange_16s_C4R	119
7.4.1.116 nppiHistogramRange_16u_AC4R	120
7.4.1.117 nppiHistogramRange_16u_C1R	120
7.4.1.118 nppiHistogramRange_16u_C4R	121
7.4.1.119 nppiHistogramRange_32f_AC4R	121
7.4.1.120 nppiHistogramRange_32f_C1R	122
7.4.1.121 nppiHistogramRange_32f_C4R	122
7.4.1.122 nppiHistogramRange_8u_AC4R	122
7.4.1.123 nppiHistogramRange_8u_C1R	123
7.4.1.124 nppiHistogramRange_8u_C4R	123
7.4.1.125 nppiHistogramRangeGetBufferSize_16s_AC4R	124
7.4.1.126 nppiHistogramRangeGetBufferSize_16s_C1R	124
7.4.1.127 nppiHistogramRangeGetBufferSize_16s_C4R	124
7.4.1.128 nppiHistogramRangeGetBufferSize_16u_AC4R	125
7.4.1.129 nppiHistogramRangeGetBufferSize_16u_C1R	125
7.4.1.130 nppiHistogramRangeGetBufferSize_16u_C4R	125
7.4.1.131 nppiHistogramRangeGetBufferSize_32f_AC4R	125
7.4.1.132 nppiHistogramRangeGetBufferSize_32f_C1R	126
7.4.1.133 nppiHistogramRangeGetBufferSize_32f_C4R	126
7.4.1.134 nppiHistogramRangeGetBufferSize_8u_AC4R	126
7.4.1.135 nppiHistogramRangeGetBufferSize_8u_C1R	127
7.4.1.136 nppiHistogramRangeGetBufferSize_8u_C4R	127
7.4.1.137 nppiLn_32f_C1R	127
7.4.1.138 nppiLUT_Linear_8u_AC4R	128
7.4.1.139 nppiLUT_Linear_8u_C1R	128
7.4.1.140 nppiLUT_Linear_8u_C3R	129
7.4.1.141 nppiMagnitude_32fc32f_C1R	129
7.4.1.142 nppiMagnitudeSqr_32fc32f_C1R	129
7.4.1.143 nppiMalloc_16s_C1	130
7.4.1.144 nppiMalloc_16s_C2	130
7.4.1.145 nppiMalloc_16s_C4	130
7.4.1.146 nppiMalloc_16u_C1	131
7.4.1.147 nppiMalloc_16u_C2	131
7.4.1.148 nppiMalloc_16u_C3	131
7.4.1.149 nppiMalloc_16u_C4	132
7.4.1.150 nppiMalloc_32f_C1	132

7.4.1.151	nppiMalloc_32f_C2	132
7.4.1.152	nppiMalloc_32f_C3	132
7.4.1.153	nppiMalloc_32f_C4	133
7.4.1.154	nppiMalloc_32s_C1	133
7.4.1.155	nppiMalloc_32s_C3	133
7.4.1.156	nppiMalloc_32s_C4	134
7.4.1.157	nppiMalloc_8u_C1	134
7.4.1.158	nppiMalloc_8u_C2	134
7.4.1.159	nppiMalloc_8u_C3	134
7.4.1.160	nppiMalloc_8u_C4	135
7.4.1.161	nppiMean_StdDev_8u_C1R	135
7.4.1.162	nppiMinMax_8u_C1R	135
7.4.1.163	nppiMinMax_8u_C4R	136
7.4.1.164	nppiMinMaxGetBufferSize_8u_C1R	136
7.4.1.165	nppiMinMaxGetBufferSize_8u_C4R	136
7.4.1.166	nppiMirror_8u_C1R	137
7.4.1.167	nppiMirror_8u_C4R	137
7.4.1.168	nppiMul_32f_C1R	138
7.4.1.169	nppiMul_32s_C1R	138
7.4.1.170	nppiMul_8u_AC4RSfs	138
7.4.1.171	nppiMul_8u_C1RSfs	139
7.4.1.172	nppiMul_8u_C4RSfs	139
7.4.1.173	nppiMulC_32f_C1R	140
7.4.1.174	nppiMulC_32fc_C1R	140
7.4.1.175	nppiNormDiff_Inf_8u_C1R	141
7.4.1.176	nppiNormDiff_L1_8u_C1R	141
7.4.1.177	nppiNormDiff_L2_8u_C1R	141
7.4.1.178	nppiQuantFwdRawTableInit_JPEG_8u	142
7.4.1.179	nppiQuantFwdTableInit_JPEG_8u16u	142
7.4.1.180	nppiQuantInvTableInit_JPEG_8u16u	142
7.4.1.181	nppiRectStdDev_32s32f_C1R	142
7.4.1.182	nppiReductionGetBufferHostSize_8u_C1R	143
7.4.1.183	nppiReductionGetBufferHostSize_8u_C4R	143
7.4.1.184	nppiResize_8u_C1R	143
7.4.1.185	nppiResize_8u_C4R	144
7.4.1.186	nppiRGBToYCbCr420_8u_C3P3R	145

7.4.1.187 nppiRGBToYCbCr422_8u_C3C2R	145
7.4.1.188 nppiRGBToYCbCr_8u_AC4R	145
7.4.1.189 nppiRGBToYCbCr_8u_C3R	146
7.4.1.190 nppiRGBToYCbCr_8u_P3R	146
7.4.1.191 nppiRotate_8u_C1R	146
7.4.1.192 nppiRotate_8u_C4R	147
7.4.1.193 nppiSet_16s_AC4MR	148
7.4.1.194 nppiSet_16s_AC4R	148
7.4.1.195 nppiSet_16s_C1MR	148
7.4.1.196 nppiSet_16s_C1R	149
7.4.1.197 nppiSet_16s_C2R	149
7.4.1.198 nppiSet_16s_C4CR	149
7.4.1.199 nppiSet_16s_C4MR	150
7.4.1.200 nppiSet_16s_C4R	150
7.4.1.201 nppiSet_16u_AC4MR	151
7.4.1.202 nppiSet_16u_AC4R	151
7.4.1.203 nppiSet_16u_C1MR	151
7.4.1.204 nppiSet_16u_C1R	152
7.4.1.205 nppiSet_16u_C2R	152
7.4.1.206 nppiSet_16u_C4CR	152
7.4.1.207 nppiSet_16u_C4MR	153
7.4.1.208 nppiSet_16u_C4R	153
7.4.1.209 nppiSet_32f_AC4MR	154
7.4.1.210 nppiSet_32f_AC4R	154
7.4.1.211 nppiSet_32f_C1MR	154
7.4.1.212 nppiSet_32f_C1R	155
7.4.1.213 nppiSet_32f_C4CR	155
7.4.1.214 nppiSet_32f_C4MR	155
7.4.1.215 nppiSet_32f_C4R	156
7.4.1.216 nppiSet_32s_AC4MR	156
7.4.1.217 nppiSet_32s_AC4R	157
7.4.1.218 nppiSet_32s_C1MR	157
7.4.1.219 nppiSet_32s_C1R	157
7.4.1.220 nppiSet_32s_C4CR	158
7.4.1.221 nppiSet_32s_C4MR	158
7.4.1.222 nppiSet_32s_C4R	158

7.4.1.223 nppiSet_8u_AC4MR	159
7.4.1.224 nppiSet_8u_AC4R	159
7.4.1.225 nppiSet_8u_C1MR	160
7.4.1.226 nppiSet_8u_C1R	160
7.4.1.227 nppiSet_8u_C4CR	160
7.4.1.228 nppiSet_8u_C4MR	161
7.4.1.229 nppiSet_8u_C4R	161
7.4.1.230 nppiSetDefaultQuantTable	161
7.4.1.231 nppiSqrIntegral_8u32s32f_C1R	162
7.4.1.232 nppiSub_32f_C1R	162
7.4.1.233 nppiSub_32s_C1R	163
7.4.1.234 nppiSub_8u_AC4RSfs	163
7.4.1.235 nppiSub_8u_C1RSfs	163
7.4.1.236 nppiSub_8u_C4RSfs	164
7.4.1.237 nppiSubC_32f_C1R	164
7.4.1.238 nppiSubC_32fc_C1R	165
7.4.1.239 nppiSum_8u_C1R	165
7.4.1.240 nppiSum_8u_C4R	165
7.4.1.241 nppiSumWindowColumn_8u32f_C1R	166
7.4.1.242 nppiSumWindowRow_8u32f_C1R	166
7.4.1.243 nppiSwapChannels_8u_C4IR	167
7.4.1.244 nppiThreshold_32f_C1R	167
7.4.1.245 nppiThreshold_8u_AC4R	168
7.4.1.246 nppiTranspose_8u_C1R	168
7.4.1.247 nppiWarpAffine_16u_AC4R	168
7.4.1.248 nppiWarpAffine_16u_C1R	169
7.4.1.249 nppiWarpAffine_16u_C3R	170
7.4.1.250 nppiWarpAffine_16u_C4R	170
7.4.1.251 nppiWarpAffine_16u_P3R	170
7.4.1.252 nppiWarpAffine_16u_P4R	170
7.4.1.253 nppiWarpAffine_32f_AC4R	171
7.4.1.254 nppiWarpAffine_32f_C1R	171
7.4.1.255 nppiWarpAffine_32f_C3R	172
7.4.1.256 nppiWarpAffine_32f_C4R	172
7.4.1.257 nppiWarpAffine_32f_P3R	172
7.4.1.258 nppiWarpAffine_32f_P4R	172

7.4.1.259 nppiWarpAffine_32s_AC4R	173
7.4.1.260 nppiWarpAffine_32s_C1R	173
7.4.1.261 nppiWarpAffine_32s_C3R	174
7.4.1.262 nppiWarpAffine_32s_C4R	174
7.4.1.263 nppiWarpAffine_32s_P3R	174
7.4.1.264 nppiWarpAffine_32s_P4R	174
7.4.1.265 nppiWarpAffine_8u_AC4R	175
7.4.1.266 nppiWarpAffine_8u_C1R	175
7.4.1.267 nppiWarpAffine_8u_C3R	176
7.4.1.268 nppiWarpAffine_8u_C4R	176
7.4.1.269 nppiWarpAffine_8u_P3R	176
7.4.1.270 nppiWarpAffine_8u_P4R	177
7.4.1.271 nppiWarpAffineBack_16u_AC4R	177
7.4.1.272 nppiWarpAffineBack_16u_C1R	177
7.4.1.273 nppiWarpAffineBack_16u_C3R	178
7.4.1.274 nppiWarpAffineBack_16u_C4R	178
7.4.1.275 nppiWarpAffineBack_16u_P3R	179
7.4.1.276 nppiWarpAffineBack_16u_P4R	179
7.4.1.277 nppiWarpAffineBack_32f_AC4R	179
7.4.1.278 nppiWarpAffineBack_32f_C1R	179
7.4.1.279 nppiWarpAffineBack_32f_C3R	180
7.4.1.280 nppiWarpAffineBack_32f_C4R	180
7.4.1.281 nppiWarpAffineBack_32f_P3R	181
7.4.1.282 nppiWarpAffineBack_32f_P4R	181
7.4.1.283 nppiWarpAffineBack_32s_AC4R	181
7.4.1.284 nppiWarpAffineBack_32s_C1R	181
7.4.1.285 nppiWarpAffineBack_32s_C3R	182
7.4.1.286 nppiWarpAffineBack_32s_C4R	182
7.4.1.287 nppiWarpAffineBack_32s_P3R	183
7.4.1.288 nppiWarpAffineBack_32s_P4R	183
7.4.1.289 nppiWarpAffineBack_8u_AC4R	183
7.4.1.290 nppiWarpAffineBack_8u_C1R	183
7.4.1.291 nppiWarpAffineBack_8u_C3R	184
7.4.1.292 nppiWarpAffineBack_8u_C4R	185
7.4.1.293 nppiWarpAffineBack_8u_P3R	185
7.4.1.294 nppiWarpAffineBack_8u_P4R	185

7.4.1.295 nppiWarpAffineQuad_16u_AC4R	185
7.4.1.296 nppiWarpAffineQuad_16u_C1R	185
7.4.1.297 nppiWarpAffineQuad_16u_C3R	186
7.4.1.298 nppiWarpAffineQuad_16u_C4R	187
7.4.1.299 nppiWarpAffineQuad_16u_P3R	187
7.4.1.300 nppiWarpAffineQuad_16u_P4R	187
7.4.1.301 nppiWarpAffineQuad_32f_AC4R	187
7.4.1.302 nppiWarpAffineQuad_32f_C1R	187
7.4.1.303 nppiWarpAffineQuad_32f_C3R	188
7.4.1.304 nppiWarpAffineQuad_32f_C4R	188
7.4.1.305 nppiWarpAffineQuad_32f_P3R	189
7.4.1.306 nppiWarpAffineQuad_32f_P4R	189
7.4.1.307 nppiWarpAffineQuad_32s_AC4R	189
7.4.1.308 nppiWarpAffineQuad_32s_C1R	189
7.4.1.309 nppiWarpAffineQuad_32s_C3R	190
7.4.1.310 nppiWarpAffineQuad_32s_C4R	190
7.4.1.311 nppiWarpAffineQuad_32s_P3R	190
7.4.1.312 nppiWarpAffineQuad_32s_P4R	191
7.4.1.313 nppiWarpAffineQuad_8u_AC4R	191
7.4.1.314 nppiWarpAffineQuad_8u_C1R	191
7.4.1.315 nppiWarpAffineQuad_8u_C3R	192
7.4.1.316 nppiWarpAffineQuad_8u_C4R	192
7.4.1.317 nppiWarpAffineQuad_8u_P3R	192
7.4.1.318 nppiWarpAffineQuad_8u_P4R	193
7.4.1.319 nppiWarpPerspective_16u_AC4R	193
7.4.1.320 nppiWarpPerspective_16u_C1R	193
7.4.1.321 nppiWarpPerspective_16u_C3R	194
7.4.1.322 nppiWarpPerspective_16u_C4R	194
7.4.1.323 nppiWarpPerspective_16u_P3R	195
7.4.1.324 nppiWarpPerspective_16u_P4R	195
7.4.1.325 nppiWarpPerspective_32f_AC4R	195
7.4.1.326 nppiWarpPerspective_32f_C1R	195
7.4.1.327 nppiWarpPerspective_32f_C3R	196
7.4.1.328 nppiWarpPerspective_32f_C4R	196
7.4.1.329 nppiWarpPerspective_32f_P3R	197
7.4.1.330 nppiWarpPerspective_32f_P4R	197

7.4.1.331 nppiWarpPerspective_32s_AC4R	197
7.4.1.332 nppiWarpPerspective_32s_C1R	197
7.4.1.333 nppiWarpPerspective_32s_C3R	198
7.4.1.334 nppiWarpPerspective_32s_C4R	198
7.4.1.335 nppiWarpPerspective_32s_P3R	199
7.4.1.336 nppiWarpPerspective_32s_P4R	199
7.4.1.337 nppiWarpPerspective_8u_AC4R	199
7.4.1.338 nppiWarpPerspective_8u_C1R	199
7.4.1.339 nppiWarpPerspective_8u_C3R	200
7.4.1.340 nppiWarpPerspective_8u_C4R	201
7.4.1.341 nppiWarpPerspective_8u_P3R	201
7.4.1.342 nppiWarpPerspective_8u_P4R	201
7.4.1.343 nppiWarpPerspectiveBack_16u_AC4R	201
7.4.1.344 nppiWarpPerspectiveBack_16u_C1R	201
7.4.1.345 nppiWarpPerspectiveBack_16u_C3R	203
7.4.1.346 nppiWarpPerspectiveBack_16u_C4R	203
7.4.1.347 nppiWarpPerspectiveBack_16u_P3R	203
7.4.1.348 nppiWarpPerspectiveBack_16u_P4R	203
7.4.1.349 nppiWarpPerspectiveBack_32f_AC4R	203
7.4.1.350 nppiWarpPerspectiveBack_32f_C1R	204
7.4.1.351 nppiWarpPerspectiveBack_32f_C3R	205
7.4.1.352 nppiWarpPerspectiveBack_32f_C4R	205
7.4.1.353 nppiWarpPerspectiveBack_32f_P3R	205
7.4.1.354 nppiWarpPerspectiveBack_32f_P4R	205
7.4.1.355 nppiWarpPerspectiveBack_32s_AC4R	205
7.4.1.356 nppiWarpPerspectiveBack_32s_C1R	206
7.4.1.357 nppiWarpPerspectiveBack_32s_C3R	207
7.4.1.358 nppiWarpPerspectiveBack_32s_C4R	207
7.4.1.359 nppiWarpPerspectiveBack_32s_P3R	207
7.4.1.360 nppiWarpPerspectiveBack_32s_P4R	207
7.4.1.361 nppiWarpPerspectiveBack_8u_AC4R	207
7.4.1.362 nppiWarpPerspectiveBack_8u_C1R	208
7.4.1.363 nppiWarpPerspectiveBack_8u_C3R	209
7.4.1.364 nppiWarpPerspectiveBack_8u_C4R	209
7.4.1.365 nppiWarpPerspectiveBack_8u_P3R	209
7.4.1.366 nppiWarpPerspectiveBack_8u_P4R	209

7.4.1.367	nppiWarpPerspectiveQuad_16u_AC4R	210
7.4.1.368	nppiWarpPerspectiveQuad_16u_C1R	210
7.4.1.369	nppiWarpPerspectiveQuad_16u_C3R	211
7.4.1.370	nppiWarpPerspectiveQuad_16u_C4R	211
7.4.1.371	nppiWarpPerspectiveQuad_16u_P3R	211
7.4.1.372	nppiWarpPerspectiveQuad_16u_P4R	211
7.4.1.373	nppiWarpPerspectiveQuad_32f_AC4R	212
7.4.1.374	nppiWarpPerspectiveQuad_32f_C1R	212
7.4.1.375	nppiWarpPerspectiveQuad_32f_C3R	213
7.4.1.376	nppiWarpPerspectiveQuad_32f_C4R	213
7.4.1.377	nppiWarpPerspectiveQuad_32f_P3R	213
7.4.1.378	nppiWarpPerspectiveQuad_32f_P4R	213
7.4.1.379	nppiWarpPerspectiveQuad_32s_AC4R	213
7.4.1.380	nppiWarpPerspectiveQuad_32s_C1R	214
7.4.1.381	nppiWarpPerspectiveQuad_32s_C3R	214
7.4.1.382	nppiWarpPerspectiveQuad_32s_C4R	215
7.4.1.383	nppiWarpPerspectiveQuad_32s_P3R	215
7.4.1.384	nppiWarpPerspectiveQuad_32s_P4R	215
7.4.1.385	nppiWarpPerspectiveQuad_8u_AC4R	215
7.4.1.386	nppiWarpPerspectiveQuad_8u_C1R	215
7.4.1.387	nppiWarpPerspectiveQuad_8u_C3R	216
7.4.1.388	nppiWarpPerspectiveQuad_8u_C4R	217
7.4.1.389	nppiWarpPerspectiveQuad_8u_P3R	217
7.4.1.390	nppiWarpPerspectiveQuad_8u_P4R	217
7.4.1.391	nppiYCbCr420ToRGB_8u_P3C3R	217
7.4.1.392	nppiYCbCr420ToYCbCr411_8u_P3P2R	218
7.4.1.393	nppiYCbCr420ToYCbCr422_8u_P3R	218
7.4.1.394	nppiYCbCr422ToRGB_8u_C2C3R	218
7.4.1.395	nppiYCbCr422ToYCbCr411_8u_P3R	219
7.4.1.396	nppiYCbCr422ToYCbCr420_8u_P3R	219
7.4.1.397	nppiYCbCrToRGB_8u_AC4R	219
7.4.1.398	nppiYCbCrToRGB_8u_C3R	220
7.4.1.399	nppiYCbCrToRGB_8u_P3R	220
7.5	NPP Signal Processing	221
7.5.1	Function Documentation	258
7.5.1.1	npps10Log10_32s_ISfs	258

7.5.1.2	npps10Log10_32s_Sfs	258
7.5.1.3	nppsAbs_16s	259
7.5.1.4	nppsAbs_16s_I	259
7.5.1.5	nppsAbs_32f	259
7.5.1.6	nppsAbs_32f_I	259
7.5.1.7	nppsAbs_32s	260
7.5.1.8	nppsAbs_32s_I	260
7.5.1.9	nppsAbs_64f	260
7.5.1.10	nppsAbs_64f_I	260
7.5.1.11	nppsAdd_16s	261
7.5.1.12	nppsAdd_16s32f	261
7.5.1.13	nppsAdd_16s32s_I	261
7.5.1.14	nppsAdd_16s_I	262
7.5.1.15	nppsAdd_16s_ISfs	262
7.5.1.16	nppsAdd_16s_Sfs	262
7.5.1.17	nppsAdd_16sc_ISfs	263
7.5.1.18	nppsAdd_16sc_Sfs	263
7.5.1.19	nppsAdd_16u	263
7.5.1.20	nppsAdd_16u_ISfs	264
7.5.1.21	nppsAdd_16u_Sfs	264
7.5.1.22	nppsAdd_32f	264
7.5.1.23	nppsAdd_32f_I	265
7.5.1.24	nppsAdd_32fc	265
7.5.1.25	nppsAdd_32fc_I	265
7.5.1.26	nppsAdd_32s_ISfs	265
7.5.1.27	nppsAdd_32s_Sfs	266
7.5.1.28	nppsAdd_32sc_ISfs	266
7.5.1.29	nppsAdd_32sc_Sfs	267
7.5.1.30	nppsAdd_32u	267
7.5.1.31	nppsAdd_64f	267
7.5.1.32	nppsAdd_64f_I	268
7.5.1.33	nppsAdd_64fc	268
7.5.1.34	nppsAdd_64fc_I	268
7.5.1.35	nppsAdd_64s_Sfs	268
7.5.1.36	nppsAdd_8u16u	269
7.5.1.37	nppsAdd_8u_ISfs	269

7.5.1.38	nppsAdd_8u_Sfs	270
7.5.1.39	nppsAddC_16s_ISfs	270
7.5.1.40	nppsAddC_16s_Sfs	270
7.5.1.41	nppsAddC_16sc_ISfs	271
7.5.1.42	nppsAddC_16sc_Sfs	271
7.5.1.43	nppsAddC_16u_ISfs	271
7.5.1.44	nppsAddC_16u_Sfs	272
7.5.1.45	nppsAddC_32f	272
7.5.1.46	nppsAddC_32f_I	272
7.5.1.47	nppsAddC_32fc	273
7.5.1.48	nppsAddC_32fc_I	273
7.5.1.49	nppsAddC_32s_ISfs	273
7.5.1.50	nppsAddC_32s_Sfs	274
7.5.1.51	nppsAddC_32sc_ISfs	274
7.5.1.52	nppsAddC_32sc_Sfs	274
7.5.1.53	nppsAddC_64f	275
7.5.1.54	nppsAddC_64f_I	275
7.5.1.55	nppsAddC_64fc	275
7.5.1.56	nppsAddC_64fc_I	276
7.5.1.57	nppsAddC_8u_ISfs	276
7.5.1.58	nppsAddC_8u_Sfs	276
7.5.1.59	nppsAddProduct_16s32s_Sfs	277
7.5.1.60	nppsAddProduct_16s_Sfs	277
7.5.1.61	nppsAddProduct_32f	277
7.5.1.62	nppsAddProduct_32fc	278
7.5.1.63	nppsAddProduct_32s_Sfs	278
7.5.1.64	nppsAddProduct_64f	278
7.5.1.65	nppsAddProduct_64fc	279
7.5.1.66	nppsAddProductC_16s_ISfs	279
7.5.1.67	nppsAddProductC_16s_Sfs	280
7.5.1.68	nppsAddProductC_16sc_ISfs	280
7.5.1.69	nppsAddProductC_16sc_Sfs	280
7.5.1.70	nppsAddProductC_16u_ISfs	281
7.5.1.71	nppsAddProductC_16u_Sfs	281
7.5.1.72	nppsAddProductC_32f	281
7.5.1.73	nppsAddProductC_32f_I	282

7.5.1.74	nppsAddProductC_32s_ISfs	282
7.5.1.75	nppsAddProductC_32s_Sfs	282
7.5.1.76	nppsAddProductC_32sc_ISfs	283
7.5.1.77	nppsAddProductC_32sc_Sfs	283
7.5.1.78	nppsAddProductC_8u_ISfs	283
7.5.1.79	nppsAddProductC_8u_Sfs	284
7.5.1.80	nppsAnd_16u	284
7.5.1.81	nppsAnd_16u_I	284
7.5.1.82	nppsAnd_32u	285
7.5.1.83	nppsAnd_32u_I	285
7.5.1.84	nppsAnd_8u	285
7.5.1.85	nppsAnd_8u_I	286
7.5.1.86	nppsAndC_16u	286
7.5.1.87	nppsAndC_16u_I	286
7.5.1.88	nppsAndC_32u	286
7.5.1.89	nppsAndC_32u_I	287
7.5.1.90	nppsAndC_8u	287
7.5.1.91	nppsAndC_8u_I	287
7.5.1.92	nppsArctan_32f	288
7.5.1.93	nppsArctan_32f_I	288
7.5.1.94	nppsArctan_64f	288
7.5.1.95	nppsArctan_64f_I	288
7.5.1.96	nppsCauchy_32f_I	289
7.5.1.97	nppsCauchyD_32f_I	289
7.5.1.98	nppsCauchyDD2_32f_I	289
7.5.1.99	nppsCopy_16s	289
7.5.1.100	nppsCopy_16sc	290
7.5.1.101	nppsCopy_32f	290
7.5.1.102	nppsCopy_32fc	290
7.5.1.103	nppsCopy_32s	291
7.5.1.104	nppsCopy_32sc	291
7.5.1.105	nppsCopy_64fc	291
7.5.1.106	nppsCopy_64s	291
7.5.1.107	nppsCopy_64sc	292
7.5.1.108	nppsCopy_8u	292
7.5.1.109	nppsCubrt_32f	292

7.5.1.110 nppsCubrt_32s16s_Sfs	293
7.5.1.111 nppsDiv_16s_ISfs	293
7.5.1.112 nppsDiv_16s_Sfs	293
7.5.1.113 nppsDiv_16sc_ISfs	294
7.5.1.114 nppsDiv_16sc_Sfs	294
7.5.1.115 nppsDiv_16u_ISfs	294
7.5.1.116 nppsDiv_16u_Sfs	295
7.5.1.117 nppsDiv_32f	295
7.5.1.118 nppsDiv_32f_I	295
7.5.1.119 nppsDiv_32fc	296
7.5.1.120 nppsDiv_32fc_I	296
7.5.1.121 nppsDiv_32s16s_Sfs	296
7.5.1.122 nppsDiv_32s_ISfs	297
7.5.1.123 nppsDiv_32s_Sfs	297
7.5.1.124 nppsDiv_64f	297
7.5.1.125 nppsDiv_64f_I	298
7.5.1.126 nppsDiv_64fc	298
7.5.1.127 nppsDiv_64fc_I	298
7.5.1.128 nppsDiv_8u_ISfs	298
7.5.1.129 nppsDiv_8u_Sfs	299
7.5.1.130 nppsDiv_Round_16s_ISfs	299
7.5.1.131 nppsDiv_Round_16s_Sfs	300
7.5.1.132 nppsDiv_Round_16u_ISfs	300
7.5.1.133 nppsDiv_Round_16u_Sfs	300
7.5.1.134 nppsDiv_Round_8u_ISfs	301
7.5.1.135 nppsDiv_Round_8u_Sfs	301
7.5.1.136 nppsDivC_16s_ISfs	301
7.5.1.137 nppsDivC_16s_Sfs	302
7.5.1.138 nppsDivC_16sc_ISfs	302
7.5.1.139 nppsDivC_16sc_Sfs	302
7.5.1.140 nppsDivC_16u_ISfs	303
7.5.1.141 nppsDivC_16u_Sfs	303
7.5.1.142 nppsDivC_32f	303
7.5.1.143 nppsDivC_32f_I	304
7.5.1.144 nppsDivC_32fc	304
7.5.1.145 nppsDivC_32fc_I	304

7.5.1.146	nppsDivC_32s_ISfs	304
7.5.1.147	nppsDivC_32s_Sfs	305
7.5.1.148	nppsDivC_32sc_ISfs	305
7.5.1.149	nppsDivC_32sc_Sfs	306
7.5.1.150	nppsDivC_64f	306
7.5.1.151	nppsDivC_64f_I	306
7.5.1.152	nppsDivC_64fc	307
7.5.1.153	nppsDivC_64fc_I	307
7.5.1.154	nppsDivC_8u_ISfs	307
7.5.1.155	nppsDivC_8u_Sfs	308
7.5.1.156	nppsDivCRev_16s	308
7.5.1.157	nppsDivCRev_16s_I	308
7.5.1.158	nppsDivCRev_16u	309
7.5.1.159	nppsDivCRev_16u_I	309
7.5.1.160	nppsDivCRev_32f	309
7.5.1.161	nppsDivCRev_32f_I	310
7.5.1.162	nppsDivCRev_32s	310
7.5.1.163	nppsDivCRev_32s_I	310
7.5.1.164	nppsDivCRev_64f	310
7.5.1.165	nppsDivCRev_64f_I	311
7.5.1.166	nppsDivCRev_8u	311
7.5.1.167	nppsDivCRev_8u_I	311
7.5.1.168	nppsExp_16s_ISfs	312
7.5.1.169	nppsExp_16s_Sfs	312
7.5.1.170	nppsExp_32f	312
7.5.1.171	nppsExp_32f64f	312
7.5.1.172	nppsExp_32f_I	313
7.5.1.173	nppsExp_32s_ISfs	313
7.5.1.174	nppsExp_32s_Sfs	313
7.5.1.175	nppsExp_64f	314
7.5.1.176	nppsExp_64f_I	314
7.5.1.177	nppsExp_64s_ISfs	314
7.5.1.178	nppsExp_64s_Sfs	314
7.5.1.179	nppsFree	315
7.5.1.180	nppsIntegral_32s	315
7.5.1.181	nppsIntegralGetBufferSize_32s	315

7.5.1.182 nppsLn_16s_ISfs	315
7.5.1.183 nppsLn_16s_Sfs	315
7.5.1.184 nppsLn_32f	316
7.5.1.185 nppsLn_32f_I	316
7.5.1.186 nppsLn_32s16s_Sfs	316
7.5.1.187 nppsLn_32s_ISfs	316
7.5.1.188 nppsLn_32s_Sfs	317
7.5.1.189 nppsLn_64f	317
7.5.1.190 nppsLn_64f32f	317
7.5.1.191 nppsLn_64f_I	318
7.5.1.192 nppsLShiftC_16s	318
7.5.1.193 nppsLShiftC_16s_I	318
7.5.1.194 nppsLShiftC_16u	318
7.5.1.195 nppsLShiftC_16u_I	319
7.5.1.196 nppsLShiftC_32s	319
7.5.1.197 nppsLShiftC_32s_I	319
7.5.1.198 nppsLShiftC_32u	320
7.5.1.199 nppsLShiftC_32u_I	320
7.5.1.200 nppsLShiftC_8u	320
7.5.1.201 nppsLShiftC_8u_I	321
7.5.1.202 nppsMalloc_16s	321
7.5.1.203 nppsMalloc_16sc	321
7.5.1.204 nppsMalloc_16u	321
7.5.1.205 nppsMalloc_32f	322
7.5.1.206 nppsMalloc_32fc	322
7.5.1.207 nppsMalloc_32s	322
7.5.1.208 nppsMalloc_32sc	322
7.5.1.209 nppsMalloc_32u	323
7.5.1.210 nppsMalloc_64f	323
7.5.1.211 nppsMalloc_64fc	323
7.5.1.212 nppsMalloc_64s	323
7.5.1.213 nppsMalloc_64sc	324
7.5.1.214 nppsMalloc_8u	324
7.5.1.215 nppsMax_16s	324
7.5.1.216 nppsMax_32f	324
7.5.1.217 nppsMax_32s	325

7.5.1.218 nppsMax_64f	325
7.5.1.219 nppsMin_16s	325
7.5.1.220 nppsMin_32f	326
7.5.1.221 nppsMin_32s	326
7.5.1.222 nppsMin_64f	326
7.5.1.223 nppsMinMax_16s	327
7.5.1.224 nppsMinMax_16u	327
7.5.1.225 nppsMinMax_32f	327
7.5.1.226 nppsMinMax_32s	328
7.5.1.227 nppsMinMax_32u	328
7.5.1.228 nppsMinMax_64f	328
7.5.1.229 nppsMinMax_8u	329
7.5.1.230 nppsMinMaxGetBufferSize_16s	329
7.5.1.231 nppsMinMaxGetBufferSize_16u	329
7.5.1.232 nppsMinMaxGetBufferSize_32f	329
7.5.1.233 nppsMinMaxGetBufferSize_32s	330
7.5.1.234 nppsMinMaxGetBufferSize_32u	330
7.5.1.235 nppsMinMaxGetBufferSize_64f	330
7.5.1.236 nppsMinMaxGetBufferSize_8u	330
7.5.1.237 nppsMul_16s	331
7.5.1.238 nppsMul_16s32f	331
7.5.1.239 nppsMul_16s32s_Sfs	331
7.5.1.240 nppsMul_16s_I	332
7.5.1.241 nppsMul_16s_ISfs	332
7.5.1.242 nppsMul_16s_Sfs	332
7.5.1.243 nppsMul_16sc_ISfs	333
7.5.1.244 nppsMul_16sc_Sfs	333
7.5.1.245 nppsMul_16u16s_Sfs	333
7.5.1.246 nppsMul_16u_ISfs	334
7.5.1.247 nppsMul_16u_Sfs	334
7.5.1.248 nppsMul_32f	334
7.5.1.249 nppsMul_32f32fc	335
7.5.1.250 nppsMul_32f32fc_I	335
7.5.1.251 nppsMul_32f_I	335
7.5.1.252 nppsMul_32fc	336
7.5.1.253 nppsMul_32fc_I	336

7.5.1.254 nppsMul_32s32sc_ISfs	336
7.5.1.255 nppsMul_32s32sc_Sfs	337
7.5.1.256 nppsMul_32s_ISfs	337
7.5.1.257 nppsMul_32s_Sfs	337
7.5.1.258 nppsMul_32sc_ISfs	338
7.5.1.259 nppsMul_32sc_Sfs	338
7.5.1.260 nppsMul_64f	338
7.5.1.261 nppsMul_64f_I	339
7.5.1.262 nppsMul_64fc	339
7.5.1.263 nppsMul_64fc_I	339
7.5.1.264 nppsMul_8u16u	339
7.5.1.265 nppsMul_8u_ISfs	340
7.5.1.266 nppsMul_8u_Sfs	340
7.5.1.267 nppsMul_Low_32s_Sfs	341
7.5.1.268 nppsMulC_16s_ISfs	341
7.5.1.269 nppsMulC_16s_Sfs	341
7.5.1.270 nppsMulC_16sc_ISfs	342
7.5.1.271 nppsMulC_16sc_Sfs	342
7.5.1.272 nppsMulC_16u_ISfs	342
7.5.1.273 nppsMulC_16u_Sfs	343
7.5.1.274 nppsMulC_32f	343
7.5.1.275 nppsMulC_32f16s_Sfs	343
7.5.1.276 nppsMulC_32f_I	344
7.5.1.277 nppsMulC_32fc	344
7.5.1.278 nppsMulC_32fc_I	344
7.5.1.279 nppsMulC_32s_ISfs	344
7.5.1.280 nppsMulC_32s_Sfs	345
7.5.1.281 nppsMulC_32sc_ISfs	345
7.5.1.282 nppsMulC_32sc_Sfs	346
7.5.1.283 nppsMulC_64f	346
7.5.1.284 nppsMulC_64f64s_ISfs	346
7.5.1.285 nppsMulC_64f_I	347
7.5.1.286 nppsMulC_64fc	347
7.5.1.287 nppsMulC_64fc_I	347
7.5.1.288 nppsMulC_8u_ISfs	347
7.5.1.289 nppsMulC_8u_Sfs	348

7.5.1.290 nppsMulC_Low_32f16s	348
7.5.1.291 nppsNormalize_16s_Sfs	349
7.5.1.292 nppsNormalize_16sc_Sfs	349
7.5.1.293 nppsNormalize_32f	349
7.5.1.294 nppsNormalize_32fc	350
7.5.1.295 nppsNormalize_64f	350
7.5.1.296 nppsNormalize_64fc	350
7.5.1.297 nppsNot_16u	351
7.5.1.298 nppsNot_16u_I	351
7.5.1.299 nppsNot_32u	351
7.5.1.300 nppsNot_32u_I	351
7.5.1.301 nppsNot_8u	352
7.5.1.302 nppsNot_8u_I	352
7.5.1.303 nppsOr_16u	352
7.5.1.304 nppsOr_16u_I	352
7.5.1.305 nppsOr_32u	353
7.5.1.306 nppsOr_32u_I	353
7.5.1.307 nppsOr_8u	353
7.5.1.308 nppsOr_8u_I	354
7.5.1.309 nppsOrC_16u	354
7.5.1.310 nppsOrC_16u_I	354
7.5.1.311 nppsOrC_32u	354
7.5.1.312 nppsOrC_32u_I	355
7.5.1.313 nppsOrC_8u	355
7.5.1.314 nppsOrC_8u_I	355
7.5.1.315 nppsReductionGetBufferSize_16s	356
7.5.1.316 nppsReductionGetBufferSize_16s_Sfs	356
7.5.1.317 nppsReductionGetBufferSize_16sc	356
7.5.1.318 nppsReductionGetBufferSize_16sc_Sfs	356
7.5.1.319 nppsReductionGetBufferSize_16u	357
7.5.1.320 nppsReductionGetBufferSize_32f	357
7.5.1.321 nppsReductionGetBufferSize_32fc	357
7.5.1.322 nppsReductionGetBufferSize_32s	358
7.5.1.323 nppsReductionGetBufferSize_32s_Sfs	358
7.5.1.324 nppsReductionGetBufferSize_32sc	358
7.5.1.325 nppsReductionGetBufferSize_32u	358

7.5.1.326 nppsReductionGetBufferSize_64f	359
7.5.1.327 nppsReductionGetBufferSize_64fc	359
7.5.1.328 nppsReductionGetBufferSize_64s	359
7.5.1.329 nppsReductionGetBufferSize_8u	360
7.5.1.330 nppsRShiftC_16s	360
7.5.1.331 nppsRShiftC_16s_I	360
7.5.1.332 nppsRShiftC_16u	360
7.5.1.333 nppsRShiftC_16u_I	361
7.5.1.334 nppsRShiftC_32s	361
7.5.1.335 nppsRShiftC_32s_I	361
7.5.1.336 nppsRShiftC_32u	362
7.5.1.337 nppsRShiftC_32u_I	362
7.5.1.338 nppsRShiftC_8u	362
7.5.1.339 nppsRShiftC_8u_I	363
7.5.1.340 nppsSet_16s	363
7.5.1.341 nppsSet_16sc	363
7.5.1.342 nppsSet_32f	363
7.5.1.343 nppsSet_32fc	364
7.5.1.344 nppsSet_32s	364
7.5.1.345 nppsSet_32sc	364
7.5.1.346 nppsSet_64f	365
7.5.1.347 nppsSet_64fc	365
7.5.1.348 nppsSet_64s	365
7.5.1.349 nppsSet_64sc	365
7.5.1.350 nppsSet_8u	366
7.5.1.351 nppsSqr_16s_ISfs	366
7.5.1.352 nppsSqr_16s_Sfs	366
7.5.1.353 nppsSqr_16sc_ISfs	367
7.5.1.354 nppsSqr_16sc_Sfs	367
7.5.1.355 nppsSqr_16u_ISfs	367
7.5.1.356 nppsSqr_16u_Sfs	367
7.5.1.357 nppsSqr_32f	368
7.5.1.358 nppsSqr_32f_I	368
7.5.1.359 nppsSqr_32fc	368
7.5.1.360 nppsSqr_32fc_I	369
7.5.1.361 nppsSqr_64f	369

7.5.1.362 nppsSqr_64f_I	369
7.5.1.363 nppsSqr_64fc	369
7.5.1.364 nppsSqr_64fc_I	370
7.5.1.365 nppsSqr_8u_ISfs	370
7.5.1.366 nppsSqr_8u_Sfs	370
7.5.1.367 nppsSqrt_16s_ISfs	370
7.5.1.368 nppsSqrt_16s_Sfs	371
7.5.1.369 nppsSqrt_16sc_ISfs	371
7.5.1.370 nppsSqrt_16sc_Sfs	371
7.5.1.371 nppsSqrt_16u_ISfs	372
7.5.1.372 nppsSqrt_16u_Sfs	372
7.5.1.373 nppsSqrt_32f	372
7.5.1.374 nppsSqrt_32f_I	372
7.5.1.375 nppsSqrt_32fc	373
7.5.1.376 nppsSqrt_32fc_I	373
7.5.1.377 nppsSqrt_32s16s_Sfs	373
7.5.1.378 nppsSqrt_64f	374
7.5.1.379 nppsSqrt_64f_I	374
7.5.1.380 nppsSqrt_64fc	374
7.5.1.381 nppsSqrt_64fc_I	374
7.5.1.382 nppsSqrt_64s16s_Sfs	375
7.5.1.383 nppsSqrt_64s_ISfs	375
7.5.1.384 nppsSqrt_64s_Sfs	375
7.5.1.385 nppsSqrt_8u_ISfs	376
7.5.1.386 nppsSqrt_8u_Sfs	376
7.5.1.387 nppsSub_16s	376
7.5.1.388 nppsSub_16s32f	377
7.5.1.389 nppsSub_16s_I	377
7.5.1.390 nppsSub_16s_ISfs	377
7.5.1.391 nppsSub_16s_Sfs	378
7.5.1.392 nppsSub_16sc_ISfs	378
7.5.1.393 nppsSub_16sc_Sfs	378
7.5.1.394 nppsSub_16u_ISfs	379
7.5.1.395 nppsSub_16u_Sfs	379
7.5.1.396 nppsSub_32f	379
7.5.1.397 nppsSub_32f_I	380

7.5.1.398 nppsSub_32fc	380
7.5.1.399 nppsSub_32fc_I	380
7.5.1.400 nppsSub_32s_ISfs	380
7.5.1.401 nppsSub_32s_Sfs	381
7.5.1.402 nppsSub_32sc_ISfs	381
7.5.1.403 nppsSub_32sc_Sfs	382
7.5.1.404 nppsSub_64f	382
7.5.1.405 nppsSub_64f_I	382
7.5.1.406 nppsSub_64fc	383
7.5.1.407 nppsSub_64fc_I	383
7.5.1.408 nppsSub_8u_ISfs	383
7.5.1.409 nppsSub_8u_Sfs	384
7.5.1.410 nppsSubC_16s_ISfs	384
7.5.1.411 nppsSubC_16s_Sfs	384
7.5.1.412 nppsSubC_16sc_ISfs	385
7.5.1.413 nppsSubC_16sc_Sfs	385
7.5.1.414 nppsSubC_16u_ISfs	385
7.5.1.415 nppsSubC_16u_Sfs	386
7.5.1.416 nppsSubC_32f	386
7.5.1.417 nppsSubC_32f_I	386
7.5.1.418 nppsSubC_32fc	387
7.5.1.419 nppsSubC_32fc_I	387
7.5.1.420 nppsSubC_32s_ISfs	387
7.5.1.421 nppsSubC_32s_Sfs	388
7.5.1.422 nppsSubC_32sc_ISfs	388
7.5.1.423 nppsSubC_32sc_Sfs	388
7.5.1.424 nppsSubC_64f	389
7.5.1.425 nppsSubC_64f_I	389
7.5.1.426 nppsSubC_64fc	389
7.5.1.427 nppsSubC_64fc_I	390
7.5.1.428 nppsSubC_8u_ISfs	390
7.5.1.429 nppsSubC_8u_Sfs	390
7.5.1.430 nppsSubCRev_16s_ISfs	391
7.5.1.431 nppsSubCRev_16s_Sfs	391
7.5.1.432 nppsSubCRev_16sc_ISfs	391
7.5.1.433 nppsSubCRev_16sc_Sfs	392

7.5.1.434 nppsSubCRev_16u_ISfs	392
7.5.1.435 nppsSubCRev_16u_Sfs	392
7.5.1.436 nppsSubCRev_32f	393
7.5.1.437 nppsSubCRev_32f_I	393
7.5.1.438 nppsSubCRev_32fc	393
7.5.1.439 nppsSubCRev_32fc_I	394
7.5.1.440 nppsSubCRev_32s_ISfs	394
7.5.1.441 nppsSubCRev_32s_Sfs	394
7.5.1.442 nppsSubCRev_32sc_ISfs	395
7.5.1.443 nppsSubCRev_32sc_Sfs	395
7.5.1.444 nppsSubCRev_64f	395
7.5.1.445 nppsSubCRev_64f_I	396
7.5.1.446 nppsSubCRev_64fc	396
7.5.1.447 nppsSubCRev_64fc_I	396
7.5.1.448 nppsSubCRev_8u_ISfs	396
7.5.1.449 nppsSubCRev_8u_Sfs	397
7.5.1.450 nppsSum_16s32s_Sfs	397
7.5.1.451 nppsSum_16s_Sfs	398
7.5.1.452 nppsSum_16sc32sc_Sfs	398
7.5.1.453 nppsSum_16sc_Sfs	398
7.5.1.454 nppsSum_32f	399
7.5.1.455 nppsSum_32fc	399
7.5.1.456 nppsSum_32s_Sfs	399
7.5.1.457 nppsSum_64f	400
7.5.1.458 nppsSum_64fc	400
7.5.1.459 nppsXor_16u	400
7.5.1.460 nppsXor_16u_I	401
7.5.1.461 nppsXor_32u	401
7.5.1.462 nppsXor_32u_I	401
7.5.1.463 nppsXor_8u	401
7.5.1.464 nppsXor_8u_I	402
7.5.1.465 nppsXorC_16u	402
7.5.1.466 nppsXorC_16u_I	402
7.5.1.467 nppsXorC_32u	403
7.5.1.468 nppsXorC_32u_I	403
7.5.1.469 nppsXorC_8u	403

7.5.1.470	nppsXorC_8u_I	404
7.5.1.471	nppsZero_16s	404
7.5.1.472	nppsZero_16sc	404
7.5.1.473	nppsZero_32f	404
7.5.1.474	nppsZero_32fc	405
7.5.1.475	nppsZero_32s	405
7.5.1.476	nppsZero_32sc	405
7.5.1.477	nppsZero_64f	405
7.5.1.478	nppsZero_64fc	406
7.5.1.479	nppsZero_64s	406
7.5.1.480	nppsZero_64sc	406
7.5.1.481	nppsZero_8u	406
8	Data Structure Documentation	407
8.1	Npp16sc Struct Reference	407
8.1.1	Detailed Description	407
8.1.2	Field Documentation	407
8.1.2.1	im	407
8.1.2.2	re	407
8.2	Npp32fc Struct Reference	408
8.2.1	Detailed Description	408
8.2.2	Field Documentation	408
8.2.2.1	im	408
8.2.2.2	re	408
8.3	Npp32sc Struct Reference	409
8.3.1	Detailed Description	409
8.3.2	Field Documentation	409
8.3.2.1	im	409
8.3.2.2	re	409
8.4	Npp64fc Struct Reference	410
8.4.1	Detailed Description	410
8.4.2	Field Documentation	410
8.4.2.1	im	410
8.4.2.2	re	410
8.5	Npp64sc Struct Reference	411
8.5.1	Detailed Description	411
8.5.2	Field Documentation	411

8.5.2.1	im	411
8.5.2.2	re	411
8.6	NppiHaarBuffer Struct Reference	412
8.6.1	Field Documentation	412
8.6.1.1	haarBuffer	412
8.6.1.2	haarBufferSize	412
8.7	NppiHaarClassifier_32f Struct Reference	413
8.7.1	Field Documentation	413
8.7.1.1	classifiers	413
8.7.1.2	classifierSize	413
8.7.1.3	classifierStep	413
8.7.1.4	counterDevice	413
8.7.1.5	numClassifiers	413
8.8	NppiPoint Struct Reference	414
8.8.1	Detailed Description	414
8.8.2	Field Documentation	414
8.8.2.1	x	414
8.8.2.2	y	414
8.9	NppiRect Struct Reference	415
8.9.1	Detailed Description	415
8.9.2	Field Documentation	415
8.9.2.1	height	415
8.9.2.2	width	415
8.9.2.3	x	415
8.9.2.4	y	415
8.10	NppiSize Struct Reference	416
8.10.1	Detailed Description	416
8.10.2	Field Documentation	416
8.10.2.1	height	416
8.10.2.2	width	416
8.11	NppLibraryVersion Struct Reference	417
8.11.1	Field Documentation	417
8.11.1.1	build	417
8.11.1.2	major	417
8.11.1.3	minor	417

Chapter 1

NVIDIA Performance Primitives

1.1 What is NPP?

NVIDIA NPP is a library of functions for performing CUDA accelerated processing. The initial set of functionality in the library focuses on imaging and video processing and is widely applicable for developers in these areas. NPP will evolve over time to encompass more of the compute heavy tasks in a variety of problem domains. The NPP library is written to maximize flexibility, while maintaining high performance.

NPP can be used in one of two ways:

- A stand-alone library for adding GPU acceleration to an application with minimal effort. Using this route allows developers to add GPU acceleration to their applications in a matter of hours.
- A cooperative library for interoperating with a developer's GPU code efficiently.

Either route allows developers to harness the massive compute resources of NVIDIA GPUs, while simultaneously reducing development times.

1.2 Documentation

- [General API Conventions](#)
- [Signal-Processing Specific API Conventions](#)
- [Imaging-Processing Specific API Conventions](#)

1.3 Technical Specifications

Supported Platforms:

- Microsoft Windows 7 (64-bit and 32-bit)
- Microsoft Windows Vista (64-bit and 32-bit)
- Microsoft Windows XP (64-bit and 32-bit)
- Linux (Centos & Ubuntu) (64-bit and 32-bit)
- Mac OS X

1.4 Files

NPP is comprised of the following files:

1.4.1 Header Files

- [npp.h](#)
- [nppcore.h](#)
- [nppdefs.h](#)
- [nppi.h](#)
- [npps.h](#)
- [nppversion.h](#)

All those header files are located in the CUDA Toolkit's

`/include/`

directory.

1.4.2 Library Files

On the Windows platform the NPP stub library is found in the CUDA Toolkit's library directory:

`/lib/npp.lib`

The matching DLL is located in the CUDA Toolkit's binary directory:

```
/bin/npp32_32_7.dll    // Dynamic library for 32-bit Windows.  
/bin/npp64_32_7.dll    // Dynamic library for 64-bit Windows.
```

On Linux and Mac platforms the dynamic libraries are located in the lib directory

```
/lib/libnpp32.so.3.2.9  // NPP 32-bit dynamic library for Linux  
/lib/libnpp64.so.3.2.9  // NPP 64-bit dynamic library for Linux  
  
/lib/libnpp32.3.2.dylib // NPP 32-bit dynamic library for Mac  
/lib/libnpp64.3.2.dylib // NPP 64-bit dynamic library for Mac
```

1.5 Supported NVIDIA Hardware

NPP runs on all CUDA capable NVIDIA hardware. For details please see http://www.nvidia.com/object/cuda_learn_products.html

Chapter 2

General API Conventions

2.1 Memory Management

The design of all the NPP functions follows the same guidelines as other NVIDIA CUDA libraries like cuFFT and cuBLAS. That is that all pointer arguments in those APIs are device pointers.

This convention enables the individual developer to make smart choices about memory management that minimize the number of memory transfers. It also allows the user the maximum flexibility regarding which of the various memory transfer mechanisms offered by the CUDA runtime is used, e.g. synchronous or asynchronous memory transfers, zero-copy and pinned memory, etc.

The most basic steps involved in using NPP for processing data is as follows:

1. Transfer input data from the host to device using

```
cudaMemcpy(...)
```

2. Process data using one or several NPP functions or custom CUDA kernels

3. Transfer the result data from the device to the host using

```
cudaMemcpy(...)
```

Throughout NPP there are a number of functions that require the use of host pointers. E.g. various `<Primitiv>GetBufferSize(...)` functions. Those functions compute the minimum size of (scratch memory) buffer that some primitives require. This buffer size is returned via a host pointer. Since these buffers are allocated via CUDA runtime functions, it would make no sense to place those size values in device memory by default.

2.2 Function Naming

Since NPP is a C API and therefore does not allow for function overloading for different data-types the NPP naming convention addresses the need to differentiate between different flavors of the same algorithm or primitive function but for various data types. This disambiguation of different flavors of a primitive is done via a suffix containing data type and other disambiguating information.

In addition to the flavor suffix, all NPP functions are prefixed with by the letters "npp". Primitives belonging to NPP's image-processing module add the letter "i" to the npp prefix, i.e. are prefixed by "nppi". Similarly signal-processing primitives are prefixed with "npps".

The general naming scheme is:

```
npp<module info><PrimitiveName>_<data-type info>[_<additional flavor info>](<parameter list>)
```

The data-type information uses the same names as the [Basic NPP Data Types](#). For example the data-type information "8u" would imply that the primitive operates on [Npp8u](#) data.

If a primitive consumes different type data from what it produces, both types will be listed in the order of consumed to produced data type.

Details about the "additional flavor information" is provided for each of the NPP modules, since each problem domain uses different flavor information suffixes.

2.3 Integer Result Scaling

NPP signal processing and imaging primitives often operate on integer data. This integer data is a usually a fixed point fractional representation of some physical magnitue (e.g. luminance). Because of this fixed-

point nature of the representation many numerical operations (e.g. addition or multiplication) tend produce results exceeding the original fixed-point range if treated as regular integers.

In cases where the results exceed the original range, these functions clamp the result values back to the valid range. E.g. the maximum positive value for a 16-bit unsigned integer is 32767. A multiplication operation of $4 * 10000 = 40000$ would exceed this range. The result would be clamped to be 32767.

To avoid the level of lost information due to clamping most integer primitives allow for result scaling. Primitives with result scaling have the "Sfs" suffix in their name and provide a parameter "nScaleFactor" that controls the amount of scaling. Before the results of an operation are clamped to the valid output-data range by multiplying them with $2^{-nScaleFactor}$.

Example: The primitive `nppsSqr_8u_Sfs()` computes the square of 8-bit unsigned sample values in a signal (1D array of values). The maximum value of a 8-bit value is 255. The square of $255^2 = 65025$ which would be clamped to 255 if no result scaling is performed. In order to map the maximum value of 255 to 255 in the result, one would specify an integer result scaling factor of 8, i.e. multiply each result with $2^{-8} = \frac{1}{2^8} = \frac{1}{256}$. The final result for a signal value of 255 being squared and scaled would be:

$$255^2 \cdot 2^{-8} = 254.00390625$$

which would be rounded to a final result of 254.

A medium gray value of 128 would result in

$$128^2 \cdot 2^{-8} = 64$$

Chapter 3

Signal-Processing Specific API Conventions

3.1 Signal Data

Signal data is passed to and from NPPS primitives via a pointer to the signal's data type.

The general idea behind this fairly low-level way of passing signal data is ease-of-adoption into existing software projects:

- Passing the data pointer rather than a higher-level signal struct allows for easy adoption by not requiring a specific signal representation (that could include total signal size offset, or other additional information). This avoids awkward packing and unpacking of signal data from the host application to an NPP specific signal representation.

3.1.1 Parameter Names for Signal Data

There are three general cases of image-data passing throughout NPP detailed in the following sections.

Those are signals consumed by the algorithm.

3.1.1.1 Source Signal Pointer

The source signal data is generally passed via a pointer named

`pSrc`

The source signal pointer is generally defined constant, enforcing that the primitive does not change any image data pointed to by that pointer. E.g.

```
nppsPrimitive_32s(const Npp32s * pSrc, ...)
```

In case the primitive consumes multiple signals as inputs the source pointers are numbered like this:

`pSrc1, pSrc2, ...`

3.1.1.2 Destination Signal Pointer

The destination signal data is generally passed via a pointer named

`pDst`

In case the primitive consumes multiple signals as inputs the source pointers are numbered like this:

`pDst1, pDst2, ...`

3.1.1.3 In-Place Signal Pointer

In the case of in-place processing, source and destination are served by the same pointer and thus pointers to in-place signal data are called:

`pSrcDst`

3.1.2 Signal Data Alignment Requirements

NPP requires signal sample data to be naturally aligned, i.e. any pointer

```
NppType * p;
```

to a sample in a signal needs to fulfill:

```
assert(p % sizeof(p) == 0);
```

3.1.3 Signal Data Related Error Codes

All NPPI primitives operating on signal data validate the signal-data pointer for proper alignment and test that the point is not null.

Failed validation results in one of the following error codes being returned and the primitive not being executed:

- [NPP_NULL_POINTER_ERROR](#) is returned if the image-data pointer is 0 (NULL).
- [NPP_ALIGNMENT_ERROR](#) if the signal-data pointer address is not a multiple of the signal's data-type size.

3.2 Signal Length

The vast majority of NPPS functions take a

```
nLength
```

parameter that tells the primitive how many of the signal's samples starting from the given data pointer are to be processed.

3.2.1 Length Related Error Codes

All NPPS primitives taking a length parameter validate this input.

Failed validation results in the following error code being returned and the primitive not being executed:

- [NPP_SIZE_ERROR](#) is returned if the length is negative.

Chapter 4

Imaging-Processing Specific API Conventions

4.1 Function Naming

Image processing related functions use a number of suffixes to indicate various different flavors of a primitive beyond just different data types. The flavor suffix uses the following abbreviations:

- "A" if the image is a 4 channel image this indicates the result alpha channel is not affected by the primitive.
- "Cn" the image consists of n channel packed pixels, where n can be 1, 2, 3 or 4.
- "Pn" the image consists of n separate image planes, where n can be 1, 2, 3 or 4.
- "C" (following the channel information) indicates that the primitive only operates on one of the color channels, the "channel-of-interest". All other output channels are not affected by the primitive.
- "I" indicates that the primitive works "in-place". In this case the image-data pointer is usually named "pSrcDst" to indicate that the image data serves as source and destination at the same time.
- "M" indicates "masked operation". These types of primitives have an additional "mask image" as input. Each pixel in the destination image corresponds to a pixel in the mask image. Only pixels with a corresponding non-zero mask pixel are being processed.
- "R" indicates the primitive operates only on a rectangular "region-of-interest" or "ROI". All ROI primitives take an additional input parameter of type [NppiSize](#), which specifies the width and height of the rectangular region that the primitive should process. For details on how primitives operate on ROIs see: [Region-of-Interest \(ROI\)](#).
- "Sfs" indicates the result values are processed by fixed scaling and saturation before they're written out.

The suffixes above always appear in alphabetical order. E.g. a 4 channel primitive not affecting the alpha channel with masked operation, in place and with scaling/saturation and ROI would have the postfix: "AC4IMRSfs".

4.2 Image Data

Image data is passed to and from NPPI primitives via a pair of parameters:

1. A pointer to the image's underlying data type.
2. A line step in bytes (also sometimes called line stride).

The general idea behind this fairly low-level way of passing image data is ease-of-adoption into existing software projects:

- Passing a raw pointer to the underlying pixel data type, rather than structured (by color) channel pixel data allows usage of the function in a wide variety of situations avoiding risky type cast or expensive image data copies.
- Passing the data pointer and line step individually rather than a higher-level image struct again allows for easy adoption by not requiring a specific image representation and thus avoiding awkward packing and unpacking of image data from the host application to an NPP specific image representation.

4.2.1 Line Step

The line step (also called "line stride" or "row step") allows lines of oddly sized images to start on well-aligned addresses by adding a number of unused bytes at the ends of the lines. This type of line padding has been common practice in digital image processing for a long time and is not particular to GPU image processing.

The line step is the number of bytes in a line **including the padding**. An other way to interpret this number is to say that it is the number of bytes between the first pixel of successive rows in the image, or generally the number of bytes between two neighboring pixels in any column of pixels.

The general reason for the existence of the line step it is that uniformly aligned rows of pixel enable optimizations of memory-access patterns.

Even though all functions in NPP will work with arbitrarily aligned images, best performance can only be achieved with well aligned image data. Any image data allocated with the NPP image allocators or the 2D memory allocators in the CUDA runtime, is well aligned.

Particularly on older CUDA capable GPUs it is likely that the performance decrease for misaligned data is substantial (orders of magnitude).

All image data passed to NPPI primitives requires a line step to be provided. It is important to keep in mind that this line step is always specified in terms of bytes, not pixels.

4.2.2 Parameter Names for Image Data

There are three general cases of image-data passing throughout NPP detailed in the following sections.

4.2.2.1 Passing Source-Image Data

Those are images consumed by the algorithm.

4.2.2.1.1 Source-Image Pointer

The source image data is generally passed via a pointer named

```
pSrc
```

The source image pointer is generally defined constant, enforcing that the primitive does not change any image data pointed to by that pointer. E.g.

```
nppiPrimitive_32s_C1R(const Npp32s * pSrc, ...)
```

In case the primitive consumes multiple images as inputs the source pointers are numbered like this:

```
pSrc1, pSrc2, ...
```

4.2.2.1.2 Source-Image Line Step

The source-image line step is the number of bytes between successive rows in the image. The source-image line step parameter is

```
nSrcStep
```

or in the case of multiple source images

```
nSrcStep1, nSrcStep2, ...
```

4.2.2.2 Passing Destination-Image Data

Those are images produced by the algorithm.

4.2.2.2.1 Destination-Image Pointer

The destination image data is generally passed via a pointer named

```
pDst
```

In case the primitive consumes multiple images as inputs the source pointers are numbered like this:

```
pDst1, pDst2, ...
```

4.2.2.2.2 Destination-Image Line Step

The destination-image line step parameter is

```
nDstStep
```

or in the case of multiple destination images

```
nDstStep1, nDstStep2, ...
```

4.2.2.3 Passing In-Place Image Data

4.2.2.3.1 In-Place Image Pointer

In the case of in-place processing, source and destination are served by the same pointer and thus pointers to in-place image data are called:

```
pSrcDst
```

4.2.2.3.2 In-Place Line Step

The in-place nSrcDstStep

4.2.3 Image Data Alignment Requirements

NPP requires pixel data to adhere to certain alignment constraints: For 2 and 4 channel images the following alignment requirement holds: `data_pointer % (#channels * sizeof(channel type)) == 0`. E.g. a 4 channel image with underlying type [Npp8u](#) (8-bit unsigned) would require all pixels to fall on addresses that are multiples of 4 (4 channels * 1 byte size).

As a logical consequence of all pixels being aligned to their natural size the image line steps of 2 and 4 channel images also need to be multiples of the pixel size.

1 and 3 channel images only require that pixel pointers are aligned to the underlying data type, i.e. `pData % sizeof(data type) == 0`. And consequentially line steps are also held to this requirement.

4.2.4 Image Data Related Error Codes

All NPPI primitives operating on image data validate the image-data pointer for proper alignment and test that the point is not null. They also validate the line stride for proper alignment and guard against the step being less or equal to 0. Failed validation results in one of the following error codes being returned and the primitive not being executed:

- [NPP_STEP_ERROR](#) is returned if the data step is 0 or negative.
- [NPP_NOT_EVEN_STEP_ERROR](#) is returned if the line step is not a multiple of the pixel size for 2 and 4 channel images.
- [NPP_NULL_POINTER_ERROR](#) is returned if the image-data pointer is 0 (NULL).
- [NPP_ALIGNMENT_ERROR](#) if the image-data pointer address is not a multiple of the pixel size for 2 and 4 channel images.

4.3 Region-of-Interest (ROI)

In practice processing a rectangular sub-region of an image is often more common than processing complete images. The vast majority of NPP's image-processing primitives allow for processing of such sub regions also referred to as regions-of-interest or ROIs.

All primitives supporting ROI processing are marked by a "R" in their name suffix. Where possible, the ROI a primitive operates on is passed as a single [NppiSize](#) struct, which provides the width and height of the ROI. This raises the obvious question how the primitive knows where in the image this rectangle of (width, height) is located. The "start pixel" of the ROI is implicitly given by the image-data pointer. I.e. instead of explicitly passing a pixel coordinate for the upper-right corner of the ROI the primitive's user needs to perform the necessary offset computation on the image data pointers, such that the pointers passed to the primitive thus point to the start of the ROI.

In practice this means that for an image (pSrc, nSrcStep) and the start-pixel of the ROI being given by (xROI, yROI), one would pass

`pSrcOffset = pSrc + yROI * nSrcStep + xROI * PixelSize;`

as the image-data source to the primitive. PixelSize is typically computed as

`PixelSize = NumberOfColorChannels * sizeof(PixelDataType).`

E.g. for a primitive like [nppiSet_16s_C4R\(\)](#) we would have

- `NumberOfColorChannels == 4;`
- `sizeof(Npp16s) == 2;`
- and thus `PixelSize = 4 * 2 = 8;`

4.3.1 ROI Related Error Codes

All NPPI primitives operating on ROIs of image data validate the ROI size and image's step size. Failed validation results in one of the following error codes being returned and the primitive not being executed:

- [NPP_SIZE_ERROR](#) is returned if either the ROI width or ROI height are negative.
- [NPP_STEP_ERROR](#) is returned if the ROI width exceeds the image's line step. In mathematical terms $(\text{widthROI} * \text{PixelSize}) > \text{nLinStep}$ indicates an error.

Chapter 5

Module Index

5.1 Modules

Here is a list of all modules:

NPP Core	21
NPP Type Definitions and Constants	24
Basic NPP Data Types	32
NPP Image Processing	34
NPP Signal Processing	221

Chapter 6

Data Structure Index

6.1 Data Structures

Here are the data structures with brief descriptions:

Npp16sc (Complex Number This struct represents a short complex number)	407
Npp32fc (Complex Number This struct represents a single floating-point complex number) . . .	408
Npp32sc (Complex Number This struct represents a signed int complex number)	409
Npp64fc (Complex Number This struct represents a double floating-point complex number) . .	410
Npp64sc (Complex Number This struct represents a long long complex number)	411
NppiHaarBuffer	412
NppiHaarClassifier_32f	413
NppiPoint (2D Point)	414
NppiRect (2D Rectangle This struct contains position and size information of a rectangle in two space)	415
NppiSize (2D Size This struct typically represents the size of a a rectangular region in two space)	416
NppLibraryVersion	417

Chapter 7

Module Documentation

7.1 NPP Core

Basic functions for library management, in particular library version and device property query functions.

Functions

- `const NppLibraryVersion * nppGetLibVersion ()`
Get the NPP library version.
- `NppGpuComputeCapability nppGetGpuComputeCapability ()`
What CUDA compute model is supported by the default CUDA device?
- `int nppGetGpuNumSMs ()`
Get the number of Streaming Multiprocessors (SM) on the default CUDA device.
- `int nppGetMaxThreadsPerBlock ()`
Get the maximum number of threads per block on the default CUDA device.
- `const char * nppGetGpuName ()`
Get the name of the default CUDA device.
- `cudaStream_t nppGetStream ()`
Get the NPP CUDA stream.
- `void nppSetStream (cudaStream_t hStream)`
Set the NPP CUDA stream.

7.1.1 Detailed Description

Basic functions for library management, in particular library version and device property query functions.

7.1.2 Function Documentation

7.1.2.1 NppGpuComputeCapability nppGetGpuComputeCapability ()

What CUDA compute model is supported by the default CUDA device?

Before trying to call any NPP functions, the user should make a call this function to ensure that the current machine has a CUDA capable device.

Returns:

An enum value representing if a CUDA capable device was found and what level of compute capabilities it supports.

7.1.2.2 const char* nppGetGpuName ()

Get the name of the default CUDA device.

Returns:

Name string of the graphics-card/compute device in a system.

7.1.2.3 int nppGetGpuNumSMs ()

Get the number of Streaming Multiprocessors (SM) on the default CUDA device.

Returns:

Number of SMs of the default CUDA device.

7.1.2.4 const NppLibraryVersion* nppGetLibVersion ()

Get the NPP library version.

Returns:

A struct containing separate values for major and minor revision and build number.

7.1.2.5 int nppGetMaxThreadsPerBlock ()

Get the maximum number of threads per block on the default CUDA device.

Returns:

Maximum number of threads per block on the default CUDA device.

7.1.2.6 cudaStream_t nppGetStream ()

Get the NPP CUDA stream.

NPP enables concurrent device tasks via a global stream state variable. The NPP stream by default is set to stream 0, i.e. non-concurrent mode. A user can set the NPP stream to any valid CUDA stream. All CUDA commands issued by NPP (e.g. kernels launched by the NPP library) are then issued to that NPP stream.

7.1.2.7 void nppSetStream (cudaStream_t *hStream*)

Set the NPP CUDA stream.

See also:

[nppGetStream\(\)](#)

7.2 NPP Type Definitions and Constants

Data Structures

- struct [NppLibraryVersion](#)
- struct [NppiPoint](#)
2D Point
- struct [NppiSize](#)
2D Size This struct typically represents the size of a rectangular region in two space.
- struct [NppiRect](#)
2D Rectangle This struct contains position and size information of a rectangle in two space.
- struct [NppiHaarClassifier_32f](#)
- struct [NppiHaarBuffer](#)

Modules

- [Basic NPP Data Types](#)

Defines

- #define [NPP_MIN_8U](#) (0)
Minimum 8-bit unsigned integer.
- #define [NPP_MAX_8U](#) (255)
Maximum 8-bit unsigned integer.
- #define [NPP_MIN_16U](#) (0)
Minimum 16-bit unsigned integer.
- #define [NPP_MAX_16U](#) (65535)
Maximum 16-bit unsigned integer.
- #define [NPP_MIN_32U](#) (0)
Minimum 32-bit unsigned integer.
- #define [NPP_MAX_32U](#) (4294967295)
Maximum 32-bit unsigned integer.
- #define [NPP_MIN_8S](#) (-128)
Minimum 8-bit signed integer.
- #define [NPP_MAX_8S](#) (127)
Maximum 8-bit signed integer.
- #define [NPP_MIN_16S](#) (-32768)
Minimum 16-bit signed integer.

- #define `NPP_MAX_16S` (32767)
Maximum 16-bit signed integer.
- #define `NPP_MIN_32S` (-2147483648)
Minimum 32-bit signed integer.
- #define `NPP_MAX_32S` (2147483647)
Maximum 32-bit signed integer.
- #define `NPP_MAX_64S` (9223372036854775807LL)
Minimum 64-bit signed integer.
- #define `NPP_MIN_64S` (-9223372036854775808LL)
Maximum 64-bit signed integer.
- #define `NPP_MINABS_32F` (1.175494351e-38f)
Smallest positive 32-bit floating point value.
- #define `NPP_MAXABS_32F` (3.402823466e+38f)
Largest positive 32-bit floating point value.
- #define `NPP_MINABS_64F` (2.2250738585072014e-308)
Smallest positive 64-bit floating point value.
- #define `NPP_MAXABS_64F` (1.7976931348623158e+308)
Largest positive 64-bit floating point value.

Enumerations

- enum `NppiInterpolationMode` {
`NPPI_INTER_UNDEFINED` = 0,
`NPPI_INTER_NN` = 1,
`NPPI_INTER_LINEAR` = 2,
`NPPI_INTER_CUBIC` = 4,
`NPPI_INTER_SUPER` = 8,
`NPPI_INTER_LANCZOS` = 16,
`NPPI_SMOOTH_EDGE` = (1 << 31) }
Filtering methods.
- enum `NppStatus` {
`NPP_NOT_SUPPORTED_MODE_ERROR` = -9999,
`NPP_ROUND_MODE_NOT_SUPPORTED_ERROR` = -213,
`NPP_RESIZE_NO_OPERATION_ERROR` = -50,
`NPP_NOT_SUFFICIENT_COMPUTE_CAPABILITY` = -27,
`NPP_BAD_ARG_ERROR` = -26,

```

NPP_LUT_NUMBER_OF_LEVELS_ERROR = -25,
NPP_TEXTURE_BIND_ERROR = -24,
NPP_COEFF_ERROR = -23,
NPP_RECT_ERROR = -22,
NPP_QUAD_ERROR = -21,
NPP_WRONG_INTERSECTION_ROI_ERROR = -20,
NPP_NOT_EVEN_STEP_ERROR = -19,
NPP_INTERPOLATION_ERROR = -18,
NPP_RESIZE_FACTOR_ERROR = -17,
NPP_HAAR_CLASSIFIER_PIXEL_MATCH_ERROR = -16,
NPP_MEMFREE_ERR = -15,
NPP_MEMSET_ERR = -14,
NPP_MEMCPY_ERROR = -13,
NPP_MEM_ALLOC_ERR = -12,
NPP_HISTO_NUMBER_OF_LEVELS_ERROR = -11,
NPP_MIRROR_FLIP_ERR = -10,
NPP_INVALID_INPUT = -9,
NPP_ALIGNMENT_ERROR = -8,
NPP_STEP_ERROR = -7,
NPP_SIZE_ERROR = -6,
NPP_POINTER_ERROR = -5,
NPP_NULL_POINTER_ERROR = -4,
NPP_CUDA_KERNEL_EXECUTION_ERROR = -3,
NPP_NOT_IMPLEMENTED_ERROR = -2,
NPP_ERROR = -1,
NPP_NO_ERROR = 0,
NPP_SUCCESS = NPP_NO_ERROR,
NPP_WARNING = 1,
NPP_WRONG_INTERSECTION_QUAD_WARNING = 2,
NPP_MISALIGNED_DST_ROI_WARNING = 3,
NPP_AFFINE_QUAD_INCORRECT_WARNING = 4,
NPP_DOUBLE_SIZE_WARNING = 5,
NPP_ODD_ROI_WARNING = 6 }

```

Error Status Codes.

- enum NppGpuComputeCapability {


```

NPP_CUDA_UNKNOWN_VERSION = -1,
NPP_CUDA_NOT_CAPABLE,
NPP_CUDA_1_0,
NPP_CUDA_1_1,
NPP_CUDA_1_2,
NPP_CUDA_1_3,
NPP_CUDA_2_0 }

```

- enum `NppiAxis` {
 `NPP_HORIZONTAL_AXIS`,
 `NPP_VERTICAL_AXIS`,
 `NPP_BOTH_AXIS` }
- enum `NppCmpOp` {
 `NPP_CMP_LESS`,
 `NPP_CMP_LESS_EQ`,
 `NPP_CMP_EQ`,
 `NPP_CMP_GREATER_EQ`,
 `NPP_CMP_GREATER` }
- enum `NppRoundMode` {
 `NPP_RND_ZERO`,
 `NPP_RND_NEAR`,
 `NPP_RND_FINANCIAL` }
- enum `NppHintAlgorithm` {
 `nppAlgHintNone`,
 `nppAlgHintFast`,
 `nppAlgHintAccurate` }

7.2.1 Define Documentation

7.2.1.1 `#define NPP_MAX_16S (32767)`

Maximum 16-bit signed integer.

7.2.1.2 `#define NPP_MAX_16U (65535)`

Maximum 16-bit unsigned integer.

7.2.1.3 `#define NPP_MAX_32S (2147483647)`

Maximum 32-bit signed integer.

7.2.1.4 `#define NPP_MAX_32U (4294967295)`

Maximum 32-bit unsigned integer.

7.2.1.5 `#define NPP_MAX_64S (9223372036854775807LL)`

Minimum 64-bit signed integer.

7.2.1.6 `#define NPP_MAX_8S (127)`

Maximum 8-bit signed integer.

7.2.1.7 #define NPP_MAX_8U (255)

Maximum 8-bit unsigned integer.

7.2.1.8 #define NPP_MAXABS_32F (3.402823466e+38f)

Largest positive 32-bit floating point value.

7.2.1.9 #define NPP_MAXABS_64F (1.7976931348623158e+308)

Largest positive 64-bit floating point value.

7.2.1.10 #define NPP_MIN_16S (-32768)

Minimum 16-bit signed integer.

7.2.1.11 #define NPP_MIN_16U (0)

Minimum 16-bit unsigned integer.

7.2.1.12 #define NPP_MIN_32S (-2147483648)

Minimum 32-bit signed integer.

7.2.1.13 #define NPP_MIN_32U (0)

Minimum 32-bit unsigned integer.

7.2.1.14 #define NPP_MIN_64S (-9223372036854775808LL)

Maximum 64-bit signed integer.

7.2.1.15 #define NPP_MIN_8S (-128)

Minimum 8-bit signed integer.

7.2.1.16 #define NPP_MIN_8U (0)

Minimum 8-bit unsigned integer.

7.2.1.17 #define NPP_MINABS_32F (1.175494351e-38f)

Smallest positive 32-bit floating point value.

7.2.1.18 #define NPP_MINABS_64F (2.2250738585072014e-308)

Smallest positive 64-bit floating point value.

7.2.2 Enumeration Type Documentation**7.2.2.1 enum NppCmpOp**

Enumerator:

NPP_CMP_LESS

NPP_CMP_LESS_EQ

NPP_CMP_EQ

NPP_CMP_GREATER_EQ

NPP_CMP_GREATER

7.2.2.2 enum NppGpuComputeCapability

Enumerator:

NPP_CUDA_UNKNOWN_VERSION Indicates that the compute-capability query failed.

NPP_CUDA_NOT_CAPABLE Indicates that no CUDA capable device was found on machine.

NPP_CUDA_1_0 Indicates that CUDA 1.0 capable device is default device on machine.

NPP_CUDA_1_1 Indicates that CUDA 1.1 capable device.

NPP_CUDA_1_2 Indicates that CUDA 1.2 capable device.

NPP_CUDA_1_3 Indicates that CUDA 1.3 capable device.

NPP_CUDA_2_0 Indicates that CUDA 2.0 or better is default device on machine.

7.2.2.3 enum NppHintAlgorithm

Enumerator:

nppAlgHintNone

nppAlgHintFast

nppAlgHintAccurate

7.2.2.4 enum NppiAxis

Enumerator:

NPP_HORIZONTAL_AXIS

NPP_VERTICAL_AXIS

NPP_BOTH_AXIS

7.2.2.5 enum NppiInterpolationMode

Filtering methods.

Enumerator:

NPPI_INTER_UNDEFINED
NPPI_INTER_NN Nearest neighbor filtering.
NPPI_INTER_LINEAR Linear interpolation.
NPPI_INTER_CUBIC Cubic interpolation.
NPPI_INTER_SUPER Super sampling.
NPPI_INTER_LANCZOS Lanczos filtering.
NPPI_SMOOTH_EDGE Smooth edge filtering.

7.2.2.6 enum NppRoundMode

Enumerator:

NPP_RND_ZERO
NPP_RND_NEAR
NPP_RND_FINANCIAL

7.2.2.7 enum NppStatus

Error Status Codes.

Almost all NPP function return error-status information using these return codes. Negative return codes indicate errors, positive return codes indicate warnings, a return code of 0 indicates success.

Enumerator:

NPP_NOT_SUPPORTED_MODE_ERROR
NPP_ROUND_MODE_NOT_SUPPORTED_ERROR
NPP_RESIZE_NO_OPERATION_ERROR
NPP_NOT_SUFFICIENT_COMPUTE_CAPABILITY
NPP_BAD_ARG_ERROR
NPP_LUT_NUMBER_OF_LEVELS_ERROR
NPP_TEXTURE_BIND_ERROR
NPP_COEFF_ERROR
NPP_RECT_ERROR
NPP_QUAD_ERROR
NPP_WRONG_INTERSECTION_ROI_ERROR
NPP_NOT_EVEN_STEP_ERROR
NPP_INTERPOLATION_ERROR
NPP_RESIZE_FACTOR_ERROR
NPP_HAAR_CLASSIFIER_PIXEL_MATCH_ERROR

NPP_MEMFREE_ERR

NPP_MEMSET_ERR

NPP_MEMCPY_ERROR

NPP_MEM_ALLOC_ERR

NPP_HISTO_NUMBER_OF_LEVELS_ERROR

NPP_MIRROR_FLIP_ERR

NPP_INVALID_INPUT

NPP_ALIGNMENT_ERROR

NPP_STEP_ERROR Step is less or equal zero.

NPP_SIZE_ERROR

NPP_POINTER_ERROR

NPP_NULL_POINTER_ERROR

NPP_CUDA_KERNEL_EXECUTION_ERROR

NPP_NOT_IMPLEMENTED_ERROR

NPP_ERROR

NPP_NO_ERROR Error free operation.

NPP_SUCCESS Successful operation (same as ***NPP_NO_ERROR***).

NPP_WARNING

NPP_WRONG_INTERSECTION_QUAD_WARNING

NPP_MISALIGNED_DST_ROI_WARNING Speed reduction due to uncoalesced memory accesses warning.

NPP_AFFINE_QUAD_INCORRECT_WARNING Indicates that the quadrangle passed to one of affine warping functions doesn't have necessary properties. First 3 vertices are used, the fourth vertex discarded.

NPP_DOUBLE_SIZE_WARNING Indicates that in case of 422/411/420 sampling the ROI width/height was modified for proper processing.

NPP_ODD_ROI_WARNING Indicates that for 422/411/420 sampling the ROI width/height was forced to even value.

7.3 Basic NPP Data Types

Data Structures

- struct [Npp16sc](#)
Complex Number This struct represents a short complex number.
- struct [Npp32sc](#)
Complex Number This struct represents a signed int complex number.
- struct [Npp32fc](#)
Complex Number This struct represents a single floating-point complex number.
- struct [Npp64sc](#)
Complex Number This struct represents a long long complex number.
- struct [Npp64fc](#)
Complex Number This struct represents a double floating-point complex number.

Typedefs

- typedef unsigned char [Npp8u](#)
8-bit unsigned chars
- typedef signed char [Npp8s](#)
8-bit signed chars
- typedef unsigned short [Npp16u](#)
16-bit unsigned integers
- typedef short [Npp16s](#)
16-bit signed integers
- typedef unsigned int [Npp32u](#)
32-bit unsigned integers
- typedef int [Npp32s](#)
32-bit signed integers
- typedef unsigned long long [Npp64u](#)
64-bit unsigned integers
- typedef long long [Npp64s](#)
64-bit signed integers
- typedef float [Npp32f](#)
32-bit (IEEE) floating-point numbers

- typedef double [Npp64f](#)
64-bit floating-point numbers

7.3.1 Typedef Documentation

7.3.1.1 typedef short Npp16s

16-bit signed integers

7.3.1.2 typedef unsigned short Npp16u

16-bit unsigned integers

7.3.1.3 typedef float Npp32f

32-bit (IEEE) floating-point numbers

7.3.1.4 typedef int Npp32s

32-bit signed integers

7.3.1.5 typedef unsigned int Npp32u

32-bit unsigned integers

7.3.1.6 typedef double Npp64f

64-bit floating-point numbers

7.3.1.7 typedef long long Npp64s

64-bit signed integers

7.3.1.8 typedef unsigned long long Npp64u

64-bit unsigned integers

7.3.1.9 typedef signed char Npp8s

8-bit signed chars

7.3.1.10 typedef unsigned char Npp8u

8-bit unsigned chars

7.4 NPP Image Processing

Functions

- `NppStatus nppiSqrIntegral_8u32s32f_C1R` (`Npp8u *pSrc`, `int nSrcStep`, `Npp32s *pDst`, `int nDstStep`, `Npp32f *pSqr`, `int nSqrStep`, `NppiSize srcROI`, `Npp32s val`, `Npp32f valSqr`, `Npp32s integral-ImageNewHeight`)

SqrIntegral Transforms an image to integral and integral of pixel squares representation.

- `NppStatus nppiRectStdDev_32s32f_C1R` (`const Npp32s *pSrc`, `int nSrcStep`, `const Npp32f *pSqr`, `int nSqrStep`, `Npp32f *pDst`, `int nDstStep`, `NppiSize oSizeROI`, `NppiRect rect`)

RectStdDev Computes the standard deviation of integral images.

Image-Memory Allocation

ImageAllocator methods for 2D arrays of data.

The allocators have width and height parameters to specify the size of the image data being allocated. They return a pointer to the newly created memory and return the numbers of bytes between successive lines.

All allocators return memory with line strides that are beneficial for performance. It is not mandatory to use these allocators. Any valid CUDA device-memory pointers can be used by the NPP primitives and there are no restrictions on line strides.

- `Npp8u * nppiMalloc_8u_C1` (`int nWidthPixels`, `int nHeightPixels`, `int *pStepBytes`)
8-bit unsigned image memory allocator.
- `Npp8u * nppiMalloc_8u_C2` (`int nWidthPixels`, `int nHeightPixels`, `int *pStepBytes`)
2 channel 8-bit unsigned image memory allocator.
- `Npp8u * nppiMalloc_8u_C3` (`int nWidthPixels`, `int nHeightPixels`, `int *pStepBytes`)
3 channel 8-bit unsigned image memory allocator.
- `Npp8u * nppiMalloc_8u_C4` (`int nWidthPixels`, `int nHeightPixels`, `int *pStepBytes`)
4 channel 8-bit unsigned image memory allocator.
- `Npp16u * nppiMalloc_16u_C1` (`int nWidthPixels`, `int nHeightPixels`, `int *pStepBytes`)
16-bit unsigned image memory allocator.
- `Npp16u * nppiMalloc_16u_C2` (`int nWidthPixels`, `int nHeightPixels`, `int *pStepBytes`)
2 channel 16-bit unsigned image memory allocator.
- `Npp16u * nppiMalloc_16u_C3` (`int nWidthPixels`, `int nHeightPixels`, `int *pStepBytes`)
3 channel 16-bit unsigned image memory allocator.
- `Npp16u * nppiMalloc_16u_C4` (`int nWidthPixels`, `int nHeightPixels`, `int *pStepBytes`)
4 channel 16-bit unsigned image memory allocator.
- `Npp16s * nppiMalloc_16s_C1` (`int nWidthPixels`, `int nHeightPixels`, `int *pStepBytes`)
16-bit signed image memory allocator.

- `Npp16s * nppiMalloc_16s_C2` (int nWidthPixels, int nHeightPixels, int *pStepBytes)
2 channel 16-bit signed image memory allocator.
- `Npp16s * nppiMalloc_16s_C4` (int nWidthPixels, int nHeightPixels, int *pStepBytes)
4 channel 16-bit signed image memory allocator.
- `Npp32s * nppiMalloc_32s_C1` (int nWidthPixels, int nHeightPixels, int *pStepBytes)
32-bit signed image memory allocator.
- `Npp32s * nppiMalloc_32s_C3` (int nWidthPixels, int nHeightPixels, int *pStepBytes)
3 channel 32-bit signed image memory allocator.
- `Npp32s * nppiMalloc_32s_C4` (int nWidthPixels, int nHeightPixels, int *pStepBytes)
4 channel 32-bit signed image memory allocator.
- `Npp32f * nppiMalloc_32f_C1` (int nWidthPixels, int nHeightPixels, int *pStepBytes)
32-bit floating point image memory allocator.
- `Npp32f * nppiMalloc_32f_C2` (int nWidthPixels, int nHeightPixels, int *pStepBytes)
2 channel 32-bit floating point image memory allocator.
- `Npp32f * nppiMalloc_32f_C3` (int nWidthPixels, int nHeightPixels, int *pStepBytes)
3 channel 32-bit floating point image memory allocator.
- `Npp32f * nppiMalloc_32f_C4` (int nWidthPixels, int nHeightPixels, int *pStepBytes)
4 channel 32-bit floating point image memory allocator.
- `void nppiFree` (void *pData)
Free method for any 2D allocated memory.

Image-Memory Set

Set methods for images of various types.

Images are passed to these primitives via a pointer to the image data (first pixel in the ROI) and a step-width, i.e. the number of bytes between successive lines. The size of the area to be set (region-of-interest, ROI) is specified via a `NppiSize` struct. In addition to the image data and ROI, all methods have a parameter to specify the value being set. In case of single channel images this is a single value, in case of multi-channel, an array of values is passed.

- `NppStatus nppiSet_8u_C1R` (Npp8u nValue, Npp8u *pDst, int nDstStep, NppiSize oSizeROI)
8-bit unsigned image set.
- `NppStatus nppiSet_8u_C1MR` (Npp8u nValue, Npp8u *pDst, int nDstStep, NppiSize oSizeROI, const Npp8u *pMask, int nMaskStep)
Masked 8-bit unsigned image set.
- `NppStatus nppiSet_8u_C4R` (const Npp8u aValues[4], Npp8u *pDst, int nDstStep, NppiSize oSizeROI)

4 channel 8-bit unsigned image set.

- `NppStatus nppiSet_8u_C4MR` (const `Npp8u` aValues[4], `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` *pMask, int nMaskStep)

Masked 4 channel 8-bit unsigned image set.

- `NppStatus nppiSet_8u_AC4R` (const `Npp8u` aValues[3], `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)

4 channel 8-bit unsigned image set method, not affecting Alpha channel.

- `NppStatus nppiSet_8u_AC4MR` (const `Npp8u` aValues[3], `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` *pMask, int nMaskStep)

Masked 4 channel 8-bit unsigned image set method, not affecting Alpha channel.

- `NppStatus nppiSet_8u_C4CR` (`Npp8u` nValue, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)

4 channel 8-bit unsigned image set affecting only single channel.

- `NppStatus nppiSet_16u_C1R` (`Npp16u` nValue, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)

16-bit unsigned image set.

- `NppStatus nppiSet_16u_C1MR` (`Npp16u` nValue, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` *pMask, int nMaskStep)

Masked 16-bit unsigned image set.

- `NppStatus nppiSet_16u_C2R` (const `Npp16u` aValues[2], `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)

2 channel 16-bit unsigned image set.

- `NppStatus nppiSet_16u_C4R` (const `Npp16u` aValues[4], `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)

4 channel 16-bit unsigned image set.

- `NppStatus nppiSet_16u_C4MR` (const `Npp16u` aValues[4], `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` *pMask, int nMaskStep)

Masked 4 channel 16-bit unsigned image set.

- `NppStatus nppiSet_16u_AC4R` (const `Npp16u` aValues[3], `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)

4 channel 16-bit unsigned image set method, not affecting Alpha channel.

- `NppStatus nppiSet_16u_AC4MR` (const `Npp16u` aValues[3], `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` *pMask, int nMaskStep)

Masked 4 channel 16-bit unsigned image set method, not affecting Alpha channel.

- `NppStatus nppiSet_16u_C4CR` (`Npp16u` nValue, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)

4 channel 16-bit unsigned image set affecting only single channel.

- `NppStatus nppiSet_16s_C1R` (`Npp16s` nValue, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI)

16-bit image set.

- **NppStatus nppiSet_16s_C1MR** (**Npp16s** nValue, **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI, const **Npp8u** *pMask, int nMaskStep)
Masked 16-bit image set.
- **NppStatus nppiSet_16s_C2R** (const **Npp16s** aValues[2], **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI)
2 channel 16-bit image set.
- **NppStatus nppiSet_16s_C4R** (const **Npp16s** aValues[4], **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI)
4 channel 16-bit image set.
- **NppStatus nppiSet_16s_C4MR** (const **Npp16s** aValues[4], **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI, const **Npp8u** *pMask, int nMaskStep)
Masked 4 channel 16-bit image set.
- **NppStatus nppiSet_16s_AC4R** (const **Npp16s** aValues[3], **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI)
4 channel 16-bit image set method, not affecting Alpha channel.
- **NppStatus nppiSet_16s_AC4MR** (const **Npp16s** aValues[3], **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI, const **Npp8u** *pMask, int nMaskStep)
Masked 4 channel 16-bit image set method, not affecting Alpha channel.
- **NppStatus nppiSet_16s_C4CR** (**Npp16s** nValue, **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI)
4 channel 16-bit unsigned image set affecting only single channel.
- **NppStatus nppiSet_32s_C1R** (**Npp32s** nValue, **Npp32s** *pDst, int nDstStep, **NppiSize** oSizeROI)
32-bit image set.
- **NppStatus nppiSet_32s_C1MR** (**Npp32s** nValue, **Npp32s** *pDst, int nDstStep, **NppiSize** oSizeROI, const **Npp8u** *pMask, int nMaskStep)
Masked 32-bit image set.
- **NppStatus nppiSet_32s_C4R** (const **Npp32s** aValues[4], **Npp32s** *pDst, int nDstStep, **NppiSize** oSizeROI)
4 channel 32-bit image set.
- **NppStatus nppiSet_32s_C4MR** (const **Npp32s** aValues[4], **Npp32s** *pDst, int nDstStep, **NppiSize** oSizeROI, const **Npp8u** *pMask, int nMaskStep)
Masked 4 channel 32-bit image set.
- **NppStatus nppiSet_32s_AC4R** (const **Npp32s** aValues[3], **Npp32s** *pDst, int nDstStep, **NppiSize** oSizeROI)
4 channel 16-bit image set method, not affecting Alpha channel.
- **NppStatus nppiSet_32s_AC4MR** (const **Npp32s** aValues[3], **Npp32s** *pDst, int nDstStep, **NppiSize** oSizeROI, const **Npp8u** *pMask, int nMaskStep)
Masked 4 channel 16-bit image set method, not affecting Alpha channel.
- **NppStatus nppiSet_32s_C4CR** (**Npp32s** nValue, **Npp32s** *pDst, int nDstStep, **NppiSize** oSizeROI)

4 channel 32-bit unsigned image set affecting only single channel.

- **NppStatus nppiSet_32f_C1R** (**Npp32f** nValue, **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)
32-bit floating point image set.
- **NppStatus nppiSet_32f_C1MR** (**Npp32f** nValue, **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI, const **Npp8u** *pMask, int nMaskStep)
Masked 32-bit floating point image set.
- **NppStatus nppiSet_32f_C4R** (const **Npp32f** aValues[4], **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)
4 channel 32-bit floating point image set.
- **NppStatus nppiSet_32f_C4MR** (const **Npp32f** aValues[4], **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI, const **Npp8u** *pMask, int nMaskStep)
Masked 4 channel 32-bit floating point image set.
- **NppStatus nppiSet_32f_AC4R** (const **Npp32f** aValues[3], **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)
4 channel 32-bit floating point image set method, not affecting Alpha channel.
- **NppStatus nppiSet_32f_AC4MR** (const **Npp32f** aValues[3], **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI, const **Npp8u** *pMask, int nMaskStep)
Masked 4 channel 32-bit floating point image set method, not affecting Alpha channel.
- **NppStatus nppiSet_32f_C4CR** (**Npp32f** nValue, **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)
4 channel 32-bit floating point image set affecting only single channel.

Image-Memory Copy

Copy methods for images of various types.

Images are passed to these primitives via a pointer to the image data (first pixel in the ROI) and a step-width, i.e. the number of bytes between successive lines. The size of the area to be copied (region-of-interest, ROI) is specified via a **NppiSize** struct.

- **NppStatus nppiCopy_8u_C1R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
8-bit unsigned image copy.
- **NppStatus nppiCopy_8u_C4R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
4 channel 8-bit unsigned image copy.
- **NppStatus nppiCopy_8u_AC4R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
4 channel 8-bit unsigned image copy, not affecting Alpha channel.
- **NppStatus nppiCopy_16u_C1R** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI)

16-bit unsigned image copy.

- `NppStatus nppiCopy_16u_C4R` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)

4 channel 16-bit unsigned image copy.

- `NppStatus nppiCopy_16u_AC4R` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)

4 channel 16-bit unsigned image copy, not affecting Alpha channel.

- `NppStatus nppiCopy_16s_C1R` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI)

16-bit image copy.

- `NppStatus nppiCopy_16s_C4R` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI)

4 channel 16-bit image copy.

- `NppStatus nppiCopy_16s_AC4R` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI)

4 channel 16-bit image copy, not affecting Alpha.

- `NppStatus nppiCopy_32s_C1R` (const `Npp32s` *pSrc, int nSrcStep, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)

32-bit image copy.

- `NppStatus nppiCopy_32s_C4R` (const `Npp32s` *pSrc, int nSrcStep, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)

4 channel 32-bit image copy.

- `NppStatus nppiCopy_32s_AC4R` (const `Npp32s` *pSrc, int nSrcStep, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)

4 channel 32-bit image copy, not affecting Alpha.

- `NppStatus nppiCopy_32f_C1R` (const `Npp32f` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI)

32-bit floating point image copy.

- `NppStatus nppiCopy_32f_C4R` (const `Npp32f` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI)

4 channel 32-bit floating point image copy.

- `NppStatus nppiCopy_32f_AC4R` (const `Npp32f` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI)

4 channel 32-bit floating point image copy, not affecting Alpha.

Bit-Depth Conversion

Convert bit-depth up and down.

The integer conversion methods do not involve any scaling. Conversions that reduce bit-depth saturate values exceeding the reduced range to the range's maximum/minimum value. When converting from floating-point values to integer values, a rounding mode can be specified. After rounding to integer values the values get saturated to the destination data type's range.

- `NppStatus nppiConvert_8u16u_C1R` (const `Npp8u` *pSrc, int nSrcStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
8-bit unsigned to 16-bit unsigned conversion.
- `NppStatus nppiConvert_16u8u_C1R` (const `Npp16u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
16-bit unsigned to 8-bit unsigned conversion.
- `NppStatus nppiConvert_8u16u_C4R` (const `Npp8u` *pSrc, int nSrcStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
4 channel 8-bit unsigned to 16-bit unsigned conversion.
- `NppStatus nppiConvert_16u8u_C4R` (const `Npp16u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
4 channel 16-bit unsigned to 8-bit unsigned conversion.
- `NppStatus nppiConvert_8u16u_AC4R` (const `Npp8u` *pSrc, int nSrcStep, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
4 channel 8-bit unsigned to 16-bit unsigned conversion, not affecting Alpha.
- `NppStatus nppiConvert_16u8u_AC4R` (const `Npp16u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
4 channel 16-bit unsigned to 8-bit unsigned conversion, not affecting Alpha.
- `NppStatus nppiConvert_8u16s_C1R` (const `Npp8u` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI)
8-bit unsigned to 16-bit signed conversion.
- `NppStatus nppiConvert_16s8u_C1R` (const `Npp16s` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
4 channel 16-bit signed to 8-bit unsigned conversion.
- `NppStatus nppiConvert_8u16s_C4R` (const `Npp8u` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI)
4 channel 8-bit unsigned to 16-bit signed conversion.
- `NppStatus nppiConvert_16s8u_C4R` (const `Npp16s` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
4 channel 16-bit signed to 8-bit unsigned conversion, not affecting Alpha.
- `NppStatus nppiConvert_8u16s_AC4R` (const `Npp8u` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI)
4 channel 8-bit unsigned to 16-bit signed conversion, not affecting Alpha.
- `NppStatus nppiConvert_16s8u_AC4R` (const `Npp16s` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)

4 channel 16-bit signed to 8-bit unsigned conversion, not affecting Alpha.

- **NppStatus** **nppiConvert_16s32f_C1R** (const **Npp16s** *pSrc, int nSrcStep, **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)

16-bit signed to 32-bit floating point conversion.

- **NppStatus** **nppiConvert_32f16s_C1R** (const **Npp32f** *pSrc, int nSrcStep, **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppRoundMode** eRoundMode)

32-bit floating point to 16-bit conversion.

- **NppStatus** **nppiConvert_8u32f_C1R** (const **Npp8u** *pSrc, int nSrcStep, **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)

8-bit unsigned to 32-bit floating point conversion.

- **NppStatus** **nppiConvert_16u32f_C1R** (const **Npp16u** *pSrc, int nSrcStep, **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)

16-bit unsigned to 32-bit floating point conversion.

- **NppStatus** **nppiConvert_32f16u_C1R** (const **Npp32f** *pSrc, int nSrcStep, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppRoundMode** eRoundMode)

32-bit floating point to 16-bit unsigned conversion.

- **NppStatus** **nppiConvert_32f8u_C1R** (const **Npp32f** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppRoundMode** eRoundMode)

32-bit floating point to 8-bit unsigned conversion.

- **NppStatus** **nppiConvert_16u32s_C1R** (const **Npp16u** *pSrc, int nSrcStep, **Npp32s** *pDst, int nDstStep, **NppiSize** oSizeROI)

16-bit unsigned to 32-bit signed conversion.

- **NppStatus** **nppiConvert_16s32s_C1R** (const **Npp16s** *pSrc, int nSrcStep, **Npp32s** *pDst, int nDstStep, **NppiSize** oSizeROI)

16-bit to 32-bit conversion.

Copy Const Border

Methods for copying images and padding borders with a constant, user-specifiable color.

- **NppStatus** **nppiCopyConstBorder_8u_C1R** (const **Npp8u** *pSrc, int nSrcStep, **NppiSize** oSrcSizeROI, **Npp8u** *pDst, int nDstStep, **NppiSize** oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth, **Npp8u** nValue)

8-bit unsigned image copy with constant border color.

- **NppStatus** **nppiCopyConstBorder_8u_C4R** (const **Npp8u** *pSrc, int nSrcStep, **NppiSize** oSrcSizeROI, **Npp8u** *pDst, int nDstStep, **NppiSize** oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth, const **Npp8u** aValue[4])

4-channel 8-bit unsigned image copy with constant border color.

- **NppStatus nppiCopyConstBorder_8u_AC4R** (const **Npp8u** *pSrc, int nSrcStep, **NppiSize** oSrcSizeROI, **Npp8u** *pDst, int nDstStep, **NppiSize** oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth, const **Npp8u** aValue[3])

4 channel 8-bit unsigned image copy with constant border color.

- **NppStatus nppiCopyConstBorder_32s_C1R** (const **Npp32s** *pSrc, int nSrcStep, **NppiSize** oSrcSizeROI, **Npp32s** *pDst, int nDstStep, **NppiSize** oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth, **Npp32s** nValue)

32-bit image copy with constant border color.

Image Transpose

Methods for transposing images of various types.

Like matrix transpose, image transpose is a mirror along the image's diagonal (upper-left to lower-right corner).

- **NppStatus nppiTranspose_8u_C1R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oROI)

8-bit image transpose.

Image Color Channel Swap

Methods for exchanging the color channels of an image.

The methods support arbitrary permutations of the original channels, including replication.

- **NppStatus nppiSwapChannels_8u_C4IR** (**Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, const int aDstOrder[4])

4 channel 8-bit unsigned swap channels, in-place.

Arithmetic with Constant Values

Methods performing image arithmetic with the second operand being a constant rather than an image.

- **NppStatus nppiAddC_32f_C1R** (const **Npp32f** *pSrc, int nSrcStep, **Npp32f** nValue, **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)

32-bit floating point image add constant.

- **NppStatus nppiSubC_32f_C1R** (const **Npp32f** *pSrc, int nSrcStep, **Npp32f** nValue, **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)

32-bit floating point image subtract constant.

- **NppStatus nppiMulC_32f_C1R** (const **Npp32f** *pSrc, int nSrcStep, **Npp32f** nValue, **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)

32-bit floating point image multiply constant.

- **NppStatus nppiDivC_32f_C1R** (const **Npp32f** *pSrc, int nSrcStep, **Npp32f** nValue, **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)
32-bit floating point image divide by constant.
- **NppStatus nppiAbsDiffC_32f_C1R** (const **Npp32f** *pSrc, int nSrcStep, **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI, **Npp32f** nValue)
32-bit floating point image absolute difference from constant.
- **NppStatus nppiAddC_32fc_C1R** (const **Npp32fc** *pSrc, int nSrcStep, **Npp32fc** nValue, **Npp32fc** *pDst, int nDstStep, **NppiSize** oSizeROI)
32-bit complex floating point image add constant.
- **NppStatus nppiSubC_32fc_C1R** (const **Npp32fc** *pSrc, int nSrcStep, **Npp32fc** nValue, **Npp32fc** *pDst, int nDstStep, **NppiSize** oSizeROI)
32-bit complex floating point image subtract constant.
- **NppStatus nppiMulC_32fc_C1R** (const **Npp32fc** *pSrc, int nSrcStep, **Npp32fc** nValue, **Npp32fc** *pDst, int nDstStep, **NppiSize** oSizeROI)
32-bit complex floating point image multiply constant.
- **NppStatus nppiDivC_32fc_C1R** (const **Npp32fc** *pSrc, int nSrcStep, **Npp32fc** nValue, **Npp32fc** *pDst, int nDstStep, **NppiSize** oSizeROI)
32-bit complex floating point image divide by constant.

Image Addition

Methods for adding two images.

- **NppStatus nppiAdd_8u_C1RSfs** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
8-bit unsigned image add.
- **NppStatus nppiAdd_8u_C4RSfs** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
4 channel 8-bit unsigned image add.
- **NppStatus nppiAdd_8u_AC4RSfs** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
4 channel 8-bit unsigned image add, not affecting Alpha.
- **NppStatus nppiAdd_32f_C1R** (const **Npp32f** *pSrc1, int nSrc1Step, const **Npp32f** *pSrc2, int nSrc2Step, **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)
32-bit floating point image add.
- **NppStatus nppiAdd_32s_C1R** (const **Npp32s** *pSrc1, int nSrc1Step, const **Npp32s** *pSrc2, int nSrc2Step, **Npp32s** *pDst, int nDstStep, **NppiSize** oSizeROI)
32-bit image add.

Image Subtraction

Methods for subtracting one image from another.

- `NppStatus nppiSub_8u_C1RSfs` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
8-bit unsigned image subtraction.
- `NppStatus nppiSub_8u_C4RSfs` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
4 channel 8-bit unsigned image subtraction.
- `NppStatus nppiSub_8u_AC4RSfs` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
4 channel 8-bit unsigned image subtraction, not affecting Alpha.
- `NppStatus nppiSub_32f_C1R` (const `Npp32f` *pSrc1, int nSrc1Step, const `Npp32f` *pSrc2, int nSrc2Step, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI)
32-bit floating point image subtraction.
- `NppStatus nppiSub_32s_C1R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` *pSrc2, int nSrc2Step, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
32-bit image subtraction.

Image Multiplication

Methods for multiplying two images.

- `NppStatus nppiMul_8u_C1RSfs` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
8-bit unsigned image multiplication.
- `NppStatus nppiMul_8u_C4RSfs` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
4 channel 8-bit unsigned image multiplication.
- `NppStatus nppiMul_8u_AC4RSfs` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
4 channel 8-bit unsigned image multiplication, not affecting Alpha.
- `NppStatus nppiMul_32f_C1R` (const `Npp32f` *pSrc1, int nSrc1Step, const `Npp32f` *pSrc2, int nSrc2Step, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI)
4 channel 32-bit floating point image multiplication.
- `NppStatus nppiMul_32s_C1R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` *pSrc2, int nSrc2Step, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
4 channel 32-bit image multiplication.

Image Division

Methods for dividing one image by another.

- **NppStatus** **nppiDiv_8u_C1RSfs** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
8-bit unsigned image division.
- **NppStatus** **nppiDiv_8u_C4RSfs** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
4 channel 8-bit unsigned image division.
- **NppStatus** **nppiDiv_8u_AC4RSfs** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
4 channel 8-bit unsigned image division, not affecting Alpha.
- **NppStatus** **nppiDiv_32f_C1R** (const **Npp32f** *pSrc1, int nSrc1Step, const **Npp32f** *pSrc2, int nSrc2Step, **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)
32-bit floating point image division.
- **NppStatus** **nppiDiv_32s_C1R** (const **Npp32s** *pSrc1, int nSrc1Step, const **Npp32s** *pSrc2, int nSrc2Step, **Npp32s** *pDst, int nDstStep, **NppiSize** oSizeROI)
32-bit image division.

Image Absolute Difference Methods

Per-pixel absolute difference methods.

- **NppStatus** **nppiAbsDiff_8u_C1R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
8-bit unsigned absolute difference.
- **NppStatus** **nppiAbsDiff_8u_C4R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
4 channel 8-bit unsigned absolute difference.
- **NppStatus** **nppiAbsDiff_8u_AC4R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
4 channel 8-bit unsigned absolute difference, not affecting Alpha.
- **NppStatus** **nppiAbsDiff_32f_C1R** (const **Npp32f** *pSrc1, int nSrc1Step, const **Npp32f** *pSrc2, int nSrc2Step, **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)
32-bit floating point absolute difference.
- **NppStatus** **nppiAbsDiff_32s_C1R** (const **Npp32s** *pSrc1, int nSrc1Step, const **Npp32s** *pSrc2, int nSrc2Step, **Npp32s** *pDst, int nDstStep, **NppiSize** oSizeROI)
32-bit absolute difference.

Other Image Arithmetic

- **NppStatus nppiLn_32f_C1R** (const **Npp32f** *pSrc, int nSrcStep, **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)
32-bit floating point logarithm.
- **NppStatus nppiExp_32f_C1R** (const **Npp32f** *pSrc, int nSrcStep, **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)
32-bit floating point exponentiation.

Image Threshold Methods

Threshold pixels.

- **NppStatus nppiThreshold_32f_C1R** (const **Npp32f** *pSrc, int nSrcStep, **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI, **Npp32f** nThreshold, **NppCmpOp** eComparisonOperation)
32-bit floating point threshold.
- **NppStatus nppiThreshold_8u_AC4R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, const **Npp8u** aThresholds[3], **NppCmpOp** eComparisonOperation)
4 channel 8-bit unsigned image threshold, not affecting Alpha.

Image Compare Methods

Compare the pixels of two images and create a binary result image.

In case of multi-channel image types, the condition must be fulfilled for all channels, otherwise the comparison is considered false. The "binary" result image is of type 8u_C1. False is represented by 0, true by NPP_MAX_8U.

- **NppStatus nppiCompare_8u_C4R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppCmpOp** eComparisonOperation)
4 channel 8-bit unsigned image compare.
- **NppStatus nppiCompare_8u_AC4R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppCmpOp** eComparisonOperation)
4 channel 8-bit unsigned image compare, not affecting Alpha.
- **NppStatus nppiCompare_32f_C1R** (const **Npp32f** *pSrc1, int nSrc1Step, const **Npp32f** *pSrc2, int nSrc2Step, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppCmpOp** eComparisonOperation)
32-bit floating point image compare.

Mean_StdDev

Computes the mean and standard deviation of image pixel values

- **NppStatus nppiMean_StdDev_8u_C1R** (const **Npp8u** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp64f** *pMean, **Npp64f** *pStdDev)

8-bit unsigned mean standard deviation.

NormDiff

Norm of pixel differences between two images.

- `NppStatus nppiNormDiff_L1_8u_C1R` (const `Npp8u` *pSrc1, int nSrcStep1, const `Npp8u` *pSrc2, int nSrcStep2, `NppiSize` oSizeROI, `Npp64f` *pRetVal)

8-bit unsigned L1 norm of pixel differences.

- `NppStatus nppiNormDiff_L2_8u_C1R` (const `Npp8u` *pSrc1, int nSrcStep1, const `Npp8u` *pSrc2, int nSrcStep2, `NppiSize` oSizeROI, `Npp64f` *pRetVal)

8-bit unsigned L2 norm of pixel differences.

- `NppStatus nppiNormDiff_Inf_8u_C1R` (const `Npp8u` *pSrc1, int nSrcStep1, const `Npp8u` *pSrc2, int nSrcStep2, `NppiSize` oSizeROI, `Npp64f` *pRetVal)

8-bit unsigned Infinity Norm of pixel differences.

1D Linear Filter

1D mask Linear Convolution Filter, with rescaling, for 8 bit images.

- `NppStatus nppiFilterColumn_8u_C1R` (const `Npp8u` *pSrc, `Npp32s` nSrcStep, `Npp8u` *pDst, `Npp32s` nDstStep, `NppiSize` oROI, const `Npp32s` *pKernel, `Npp32s` nMaskSize, `Npp32s` nAnchor, `Npp32s` nDivisor)

8-bit unsigned 1D (column) image convolution.

- `NppStatus nppiFilterColumn_8u_C4R` (const `Npp8u` *pSrc, `Npp32s` nSrcStep, `Npp8u` *pDst, `Npp32s` nDstStep, `NppiSize` oROI, const `Npp32s` *pKernel, `Npp32s` nMaskSize, `Npp32s` nAnchor, `Npp32s` nDivisor)

4 channel 8-bit unsigned 1D (column) image convolution.

- `NppStatus nppiFilterRow_8u_C1R` (const `Npp8u` *pSrc, `Npp32s` nSrcStep, `Npp8u` *pDst, `Npp32s` nDstStep, `NppiSize` oROI, const `Npp32s` *pKernel, `Npp32s` nMaskSize, `Npp32s` nAnchor, `Npp32s` nDivisor)

8-bit unsigned 1D (row) image convolution.

- `NppStatus nppiFilterRow_8u_C4R` (const `Npp8u` *pSrc, `Npp32s` nSrcStep, `Npp8u` *pDst, `Npp32s` nDstStep, `NppiSize` oROI, const `Npp32s` *pKernel, `Npp32s` nMaskSize, `Npp32s` nAnchor, `Npp32s` nDivisor)

4 channel 8-bit unsigned 1D (row) image convolution.

1D Window Sum

1D mask Window Sum for 8 bit images.

- `NppStatus nppiSumWindowColumn_8u32f_C1R` (const `Npp8u` *pSrc, `Npp32s` nSrcStep, `Npp32f` *pDst, `Npp32s` nDstStep, `NppiSize` oROI, `Npp32s` nMaskSize, `Npp32s` nAnchor)
8-bit unsigned 1D (column) sum to 32f.
- `NppStatus nppiSumWindowRow_8u32f_C1R` (const `Npp8u` *pSrc, `Npp32s` nSrcStep, `Npp32f` *pDst, `Npp32s` nDstStep, `NppiSize` oROI, `Npp32s` nMaskSize, `Npp32s` nAnchor)
8-bit unsigned 1D (row) sum to 32f.

2D Morphology Filter

Image dilate and erod operations.

- `NppStatus nppiDilate_8u_C1R` (const `Npp8u` *pSrc, `Npp32s` nSrcStep, `Npp8u` *pDst, `Npp32s` nDstStep, `NppiSize` oSizeROI, const `Npp8u` *pMask, `NppiSize` oMaskSize, `NppiPoint` oAnchor)
8-bit unsigned image dilation.
- `NppStatus nppiDilate_8u_C4R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp8u` *pMask, `NppiSize` oMaskSize, `NppiPoint` oAnchor)
4 channel 8-bit unsigned image dilation.
- `NppStatus nppiErode_8u_C1R` (const `Npp8u` *pSrc, `Npp32s` nSrcStep, `Npp8u` *pDst, `Npp32s` nDstStep, `NppiSize` oSizeROI, const `Npp8u` *pMask, `NppiSize` oMaskSize, `NppiPoint` oAnchor)
8-bit unsigned image erosion.
- `NppStatus nppiErode_8u_C4R` (const `Npp8u` *pSrc, `Npp32s` nSrcStep, `Npp8u` *pDst, `Npp32s` nDstStep, `NppiSize` oSizeROI, const `Npp8u` *pMask, `NppiSize` oMaskSize, `NppiPoint` oAnchor)
4 channel 8-bit unsigned image erosion.

Convolution (2D Masks)

General purpose 2D convolution filters.

- `NppStatus nppiFilter_8u_C1R` (const `Npp8u` *pSrc, `Npp32s` nSrcStep, `Npp8u` *pDst, `Npp32s` nDstStep, `NppiSize` oSizeROI, const `Npp32s` *pKernel, `NppiSize` oKernelSize, `NppiPoint` oAnchor, `Npp32s` nDivisor)
8-bit unsigned convolution filter.
- `NppStatus nppiFilter_8u_C4R` (const `Npp8u` *pSrc, `Npp32s` nSrcStep, `Npp8u` *pDst, `Npp32s` nDstStep, `NppiSize` oSizeROI, const `Npp32s` *pKernel, `NppiSize` oKernelSize, `NppiPoint` oAnchor, `Npp32s` nDivisor)
4 channel 8-bit unsigned convolution filter.

2D Linear Fixed Filters

2D linear fixed filters for 8 bit images.

- `NppStatus nppiFilterBox_8u_C1R` (const `Npp8u` *pSrc, `Npp32s` nSrcStep, `Npp8u` *pDst, `Npp32s` nDstStep, `NppiSize` oSizeROI, `NppiSize` oMaskSize, `NppiPoint` oAnchor)
8-bit unsigned box filter.
- `NppStatus nppiFilterBox_8u_C4R` (const `Npp8u` *pSrc, `Npp32s` nSrcStep, `Npp8u` *pDst, `Npp32s` nDstStep, `NppiSize` oSizeROI, `NppiSize` oMaskSize, `NppiPoint` oAnchor)
4 channel 8-bit unsigned box filter.

Image Rank Filters

Min, Median, and Max image filters.

- `NppStatus nppiFilterMax_8u_C1R` (const `Npp8u` *pSrc, `Npp32s` nSrcStep, `Npp8u` *pDst, `Npp32s` nDstStep, `NppiSize` oSizeROI, `NppiSize` oMaskSize, `NppiPoint` oAnchor)
8-bit unsigned maximum filter.
- `NppStatus nppiFilterMax_8u_C4R` (const `Npp8u` *pSrc, `Npp32s` nSrcStep, `Npp8u` *pDst, `Npp32s` nDstStep, `NppiSize` oSizeROI, `NppiSize` oMaskSize, `NppiPoint` oAnchor)
4 channel 8-bit unsigned maximum filter.
- `NppStatus nppiFilterMin_8u_C1R` (const `Npp8u` *pSrc, `Npp32s` nSrcStep, `Npp8u` *pDst, `Npp32s` nDstStep, `NppiSize` oSizeROI, `NppiSize` oMaskSize, `NppiPoint` oAnchor)
8-bit unsigned minimum filter.
- `NppStatus nppiFilterMin_8u_C4R` (const `Npp8u` *pSrc, `Npp32s` nSrcStep, `Npp8u` *pDst, `Npp32s` nDstStep, `NppiSize` oSizeROI, `NppiSize` oMaskSize, `NppiPoint` oAnchor)
4 channel 8-bit unsigned minimum filter.

Image Linear Transforms

Linear image transforms, like Fourier and DCT transformations.

- `NppStatus nppiMagnitude_32fc32f_C1R` (const `Npp32fc` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI)
32-bit floating point complex to 32-bit floating point magnitude.
- `NppStatus nppiMagnitudeSqr_32fc32f_C1R` (const `Npp32fc` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI)
32-bit floating point complex to 32-bit floating point squared magnitude.

Histogram

- `NppStatus nppiEvenLevelsHost_32s` (`Npp32s` *hpLevels, int nLevels, `Npp32s` nLowerLevel, `Npp32s` nUpperLevel)
Compute levels with even distribution.

- [NppStatus nppiHistogramEvenGetBufferSize_8u_C1R](#) ([NppiSize](#) oSizeROI, int nLevels, int *hpBufferSize)
Scratch-buffer size for nppiHistogramEven_8u_C1R.
- [NppStatus nppiHistogramEven_8u_C1R](#) (const [Npp8u](#) *pSrc, int nSrcStep, [NppiSize](#) oSizeROI, [Npp32s](#) *pHist, int nLevels, [Npp32s](#) nLowerLevel, [Npp32s](#) nUpperLevel, [Npp8u](#) *pBuffer)
8-bit unsigned histogram with evenly distributed bins.
- [NppStatus nppiHistogramEvenGetBufferSize_8u_C4R](#) ([NppiSize](#) oSizeROI, int nLevels[4], int *hpBufferSize)
Scratch-buffer size for nppiHistogramEven_8u_C4R.
- [NppStatus nppiHistogramEven_8u_C4R](#) (const [Npp8u](#) *pSrc, int nSrcStep, [NppiSize](#) oSizeROI, [Npp32s](#) *pHist[4], int nLevels[4], [Npp32s](#) nLowerLevel[4], [Npp32s](#) nUpperLevel[4], [Npp8u](#) *pBuffer)
4 channel 8-bit unsigned histogram with evenly distributed bins.
- [NppStatus nppiHistogramEvenGetBufferSize_8u_AC4R](#) ([NppiSize](#) oSizeROI, int nLevels[3], int *hpBufferSize)
Scratch-buffer size for nppiHistogramEven_8u_AC4R.
- [NppStatus nppiHistogramEven_8u_AC4R](#) (const [Npp8u](#) *pSrc, int nSrcStep, [NppiSize](#) oSizeROI, [Npp32s](#) *pHist[3], int nLevels[3], [Npp32s](#) nLowerLevel[3], [Npp32s](#) nUpperLevel[3], [Npp8u](#) *pBuffer)
4 channel (alpha as the last channel) 8-bit unsigned histogram with evenly distributed bins.
- [NppStatus nppiHistogramEvenGetBufferSize_16u_C1R](#) ([NppiSize](#) oSizeROI, int nLevels, int *hpBufferSize)
Scratch-buffer size for nppiHistogramEven_16u_C1R.
- [NppStatus nppiHistogramEven_16u_C1R](#) (const [Npp16u](#) *pSrc, int nSrcStep, [NppiSize](#) oSizeROI, [Npp32s](#) *pHist, int nLevels, [Npp32s](#) nLowerLevel, [Npp32s](#) nUpperLevel, [Npp8u](#) *pBuffer)
16-bit unsigned histogram with evenly distributed bins.
- [NppStatus nppiHistogramEvenGetBufferSize_16u_C4R](#) ([NppiSize](#) oSizeROI, int nLevels[4], int *hpBufferSize)
Scratch-buffer size for nppiHistogramEven_16u_C4R.
- [NppStatus nppiHistogramEven_16u_C4R](#) (const [Npp16u](#) *pSrc, int nSrcStep, [NppiSize](#) oSizeROI, [Npp32s](#) *pHist[4], int nLevels[4], [Npp32s](#) nLowerLevel[4], [Npp32s](#) nUpperLevel[4], [Npp8u](#) *pBuffer)
4 channel 16-bit unsigned histogram with evenly distributed bins.
- [NppStatus nppiHistogramEvenGetBufferSize_16u_AC4R](#) ([NppiSize](#) oSizeROI, int nLevels[3], int *hpBufferSize)
Scratch-buffer size for nppiHistogramEven_16u_AC4R.
- [NppStatus nppiHistogramEven_16u_AC4R](#) (const [Npp16u](#) *pSrc, int nSrcStep, [NppiSize](#) oSizeROI, [Npp32s](#) *pHist[3], int nLevels[3], [Npp32s](#) nLowerLevel[3], [Npp32s](#) nUpperLevel[3], [Npp8u](#) *pBuffer)
4 channel (alpha as the last channel) 16-bit unsigned histogram with evenly distributed bins.

- `NppStatus nppiHistogramEvenGetBufferSize_16s_C1R` (`NppiSize` oSizeROI, `int` nLevels, `int` *hpBufferSize)
Scratch-buffer size for nppiHistogramEven_16s_C1R.
- `NppStatus nppiHistogramEven_16s_C1R` (`const Npp16s` *pSrc, `int` nSrcStep, `NppiSize` oSizeROI, `Npp32s` *pHist, `int` nLevels, `Npp32s` nLowerLevel, `Npp32s` nUpperLevel, `Npp8u` *pBuffer)
16-bit signed histogram with evenly distributed bins.
- `NppStatus nppiHistogramEvenGetBufferSize_16s_C4R` (`NppiSize` oSizeROI, `int` nLevels[4], `int` *hpBufferSize)
Scratch-buffer size for nppiHistogramEven_16s_C4R.
- `NppStatus nppiHistogramEven_16s_C4R` (`const Npp16s` *pSrc, `int` nSrcStep, `NppiSize` oSizeROI, `Npp32s` *pHist[4], `int` nLevels[4], `Npp32s` nLowerLevel[4], `Npp32s` nUpperLevel[4], `Npp8u` *pBuffer)
4 channel 16-bit signed histogram with evenly distributed bins.
- `NppStatus nppiHistogramEvenGetBufferSize_16s_AC4R` (`NppiSize` oSizeROI, `int` nLevels[3], `int` *hpBufferSize)
Scratch-buffer size for nppiHistogramEven_16s_AC4R.
- `NppStatus nppiHistogramEven_16s_AC4R` (`const Npp16s` *pSrc, `int` nSrcStep, `NppiSize` oSizeROI, `Npp32s` *pHist[3], `int` nLevels[3], `Npp32s` nLowerLevel[3], `Npp32s` nUpperLevel[3], `Npp8u` *pBuffer)
4 channel (alpha as the last channel) 16-bit signed histogram with evenly distributed bins.
- `NppStatus nppiHistogramRangeGetBufferSize_8u_C1R` (`NppiSize` oSizeROI, `int` nLevels, `int` *hpBufferSize)
Scratch-buffer size for nppiHistogramRange_8u_C1R.
- `NppStatus nppiHistogramRange_8u_C1R` (`const Npp8u` *pSrc, `int` nSrcStep, `NppiSize` oSizeROI, `Npp32s` *pHist, `const Npp32s` *pLevels, `int` nLevels, `Npp8u` *pBuffer)
8-bit unsigned histogram with bins determined by pLevels array.
- `NppStatus nppiHistogramRangeGetBufferSize_8u_C4R` (`NppiSize` oSizeROI, `int` nLevels[4], `int` *hpBufferSize)
Scratch-buffer size for nppiHistogramRange_8u_C4R.
- `NppStatus nppiHistogramRange_8u_C4R` (`const Npp8u` *pSrc, `int` nSrcStep, `NppiSize` oSizeROI, `Npp32s` *pHist[4], `const Npp32s` *pLevels[4], `int` nLevels[4], `Npp8u` *pBuffer)
4 channel 8-bit unsigned histogram with bins determined by pLevels.
- `NppStatus nppiHistogramRangeGetBufferSize_8u_AC4R` (`NppiSize` oSizeROI, `int` nLevels[3], `int` *hpBufferSize)
Scratch-buffer size for nppiHistogramRange_8u_AC4R.
- `NppStatus nppiHistogramRange_8u_AC4R` (`const Npp8u` *pSrc, `int` nSrcStep, `NppiSize` oSizeROI, `Npp32s` *pHist[3], `const Npp32s` *pLevels[3], `int` nLevels[3], `Npp8u` *pBuffer)
4 channel (alpha as a last channel) 8-bit unsigned histogram with bins determined by pLevels.

- [NppStatus nppiHistogramRangeGetBufferSize_16u_C1R](#) ([NppiSize](#) oSizeROI, int nLevels, int *hpBufferSize)
Scratch-buffer size for nppiHistogramRange_16u_C1R.
- [NppStatus nppiHistogramRange_16u_C1R](#) (const [Npp16u](#) *pSrc, int nSrcStep, [NppiSize](#) oSizeROI, [Npp32s](#) *pHist, const [Npp32s](#) *pLevels, int nLevels, [Npp8u](#) *pBuffer)
16-bit unsigned histogram with bins determined by pLevels array.
- [NppStatus nppiHistogramRangeGetBufferSize_16u_C4R](#) ([NppiSize](#) oSizeROI, int nLevels[4], int *hpBufferSize)
Scratch-buffer size for nppiHistogramRange_16u_C4R.
- [NppStatus nppiHistogramRange_16u_C4R](#) (const [Npp16u](#) *pSrc, int nSrcStep, [NppiSize](#) oSizeROI, [Npp32s](#) *pHist[4], const [Npp32s](#) *pLevels[4], int nLevels[4], [Npp8u](#) *pBuffer)
4 channel 16-bit unsigned histogram with bins determined by pLevels.
- [NppStatus nppiHistogramRangeGetBufferSize_16u_AC4R](#) ([NppiSize](#) oSizeROI, int nLevels[3], int *hpBufferSize)
Scratch-buffer size for nppiHistogramRange_16u_AC4R.
- [NppStatus nppiHistogramRange_16u_AC4R](#) (const [Npp16u](#) *pSrc, int nSrcStep, [NppiSize](#) oSizeROI, [Npp32s](#) *pHist[3], const [Npp32s](#) *pLevels[3], int nLevels[3], [Npp8u](#) *pBuffer)
4 channel (alpha as a last channel) 16-bit unsigned histogram with bins determined by pLevels.
- [NppStatus nppiHistogramRangeGetBufferSize_16s_C1R](#) ([NppiSize](#) oSizeROI, int nLevels, int *hpBufferSize)
Scratch-buffer size for nppiHistogramRange_16s_C1R.
- [NppStatus nppiHistogramRange_16s_C1R](#) (const [Npp16s](#) *pSrc, int nSrcStep, [NppiSize](#) oSizeROI, [Npp32s](#) *pHist, const [Npp32s](#) *pLevels, int nLevels, [Npp8u](#) *pBuffer)
16-bit signed histogram with bins determined by pLevels array.
- [NppStatus nppiHistogramRangeGetBufferSize_16s_C4R](#) ([NppiSize](#) oSizeROI, int nLevels[4], int *hpBufferSize)
Scratch-buffer size for nppiHistogramRange_16s_C4R.
- [NppStatus nppiHistogramRange_16s_C4R](#) (const [Npp16s](#) *pSrc, int nSrcStep, [NppiSize](#) oSizeROI, [Npp32s](#) *pHist[4], const [Npp32s](#) *pLevels[4], int nLevels[4], [Npp8u](#) *pBuffer)
4 channel 16-bit signed histogram with bins determined by pLevels.
- [NppStatus nppiHistogramRangeGetBufferSize_16s_AC4R](#) ([NppiSize](#) oSizeROI, int nLevels[3], int *hpBufferSize)
Scratch-buffer size for nppiHistogramRange_16s_AC4R.
- [NppStatus nppiHistogramRange_16s_AC4R](#) (const [Npp16s](#) *pSrc, int nSrcStep, [NppiSize](#) oSizeROI, [Npp32s](#) *pHist[3], const [Npp32s](#) *pLevels[3], int nLevels[3], [Npp8u](#) *pBuffer)
4 channel (alpha as a last channel) 16-bit signed histogram with bins determined by pLevels.
- [NppStatus nppiHistogramRangeGetBufferSize_32f_C1R](#) ([NppiSize](#) oSizeROI, int nLevels, int *hpBufferSize)
Scratch-buffer size for nppiHistogramRange_32f_C1R.

- **NppStatus nppiHistogramRange_32f_C1R** (const **Npp32f** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp32s** *pHist, const **Npp32f** *pLevels, int nLevels, **Npp8u** *pBuffer)
32-bit float histogram with bins determined by pLevels array.
- **NppStatus nppiHistogramRangeGetBufferSize_32f_C4R** (**NppiSize** oSizeROI, int nLevels[4], int *hpBufferSize)
Scratch-buffer size for nppiHistogramRange_32f_C4R.
- **NppStatus nppiHistogramRange_32f_C4R** (const **Npp32f** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp32s** *pHist[4], const **Npp32f** *pLevels[4], int nLevels[4], **Npp8u** *pBuffer)
4 channel 32-bit float histogram with bins determined by pLevels.
- **NppStatus nppiHistogramRangeGetBufferSize_32f_AC4R** (**NppiSize** oSizeROI, int nLevels[3], int *hpBufferSize)
Scratch-buffer size for nppiHistogramRange_32f_AC4R.
- **NppStatus nppiHistogramRange_32f_AC4R** (const **Npp32f** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp32s** *pHist[3], const **Npp32f** *pLevels[3], int nLevels[3], **Npp8u** *pBuffer)
4 channel (alpha as a last channel) 32-bit float histogram with bins determined by pLevels.

JPEG DCT, Quantization and Level Shift Functions

Jpeg standard defines a flow of level shift, DCT and quantization for forward JPEG transform and inverse level shift, IDCT and de-quantization for inverse JPEG transform.

This group has the functions for both forward and inverse functions.

- **NppStatus nppiQuantFwdRawTableInit_JPEG_8u** (**Npp8u** *pQuantRawTable, int nQualityFactor)
Converts regular quantization tables with the quality factor.
- **NppStatus nppiQuantFwdTableInit_JPEG_8u16u** (const **Npp8u** *pQuantRawTable, **Npp16u** *pQuantFwdRawTable)
Converts raw quantization table to a forward quantization table.
- **NppStatus nppiQuantInvTableInit_JPEG_8u16u** (const **Npp8u** *pQuantRawTable, **Npp16u** *pQuantFwdRawTable)
Converts raw quantization table to an inverse quantization table.
- **NppStatus nppiSetDefaultQuantTable** (**Npp8u** *pQuantRawTable, int tableIndex)
Fills out the quantization table with either luminance and chrominance tables for JPEG.
- **NppStatus nppiDCTQuantInv8x8LS_JPEG_16s8u_C1R** (**Npp16s** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, const **Npp16u** *pQuantInvTable, **NppiSize** oSizeROI)
Inverse DCT, de-quantization and level shift part of the JPEG decoding.
- **NppStatus nppiDCTQuantFwd8x8LS_JPEG_8u16s_C1R** (**Npp8u** *pSrc, int nSrcStep, **Npp16s** *pDst, int nDstStep, const **Npp16u** *pQuantFwdTable, **NppiSize** oSizeROI)
Forward DCT, quantization and level shift part of the JPEG encoding.

Sum

Sum of 8 bit images.

- **NppStatus** **nppiReductionGetBufferHostSize_8u_C1R** (const **NppiSize** &oSizeROI, int *hpBufferSize)
Scratch-buffer size for nppiSum_8u_C1R.
- **NppStatus** **nppiReductionGetBufferHostSize_8u_C4R** (const **NppiSize** &oSizeROI, int *hpBufferSize)
Scratch-buffer size for nppiSum_8u_C4R.
- **NppStatus** **nppiSum_8u_C1R** (const **Npp8u** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp8u** *pDeviceBuffer, **Npp64f** *pSum)
8-bit unsigned image sum.
- **NppStatus** **nppiSum_8u_C4R** (const **Npp8u** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp8u** *pDeviceBuffer, **Npp64f** aSum[4])
4 channel 8-bit unsigned image sum.

MinMax

Minimum and maximum of 8-bit images.

- **NppStatus** **nppiMinMaxGetBufferSize_8u_C1R** (const **NppiSize** &oSizeROI, int *hpBufferSize)
Scratch-buffer size for nppiMinManx_8u_C1R.
- **NppStatus** **nppiMinMax_8u_C1R** (const **Npp8u** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp8u** *pMin, **Npp8u** *pMax, **Npp8u** *pDeviceBuffer)
8-bit unsigned pixel minimum and maximum.
- **NppStatus** **nppiMinMaxGetBufferSize_8u_C4R** (const **NppiSize** &oSizeROI, int *hpBufferSize)
Scratch-buffer size for nppiMinManx_8u_C4R.
- **NppStatus** **nppiMinMax_8u_C4R** (const **Npp8u** *pSrc, int nSrcStep, **NppiSize** oSizeROI, **Npp8u** aMin[4], **Npp8u** aMax[4], **Npp8u** *pDeviceBuffer)
4 channel 8-bit unsigned pixel minimum and maximum.

Resize

Resizes 8 bit images.

Handles C1 and C4 images.

- **NppStatus** **nppiResize_8u_C1R** (const **Npp8u** *pSrc, **NppiSize** srcSize, int nSrcStep, **NppiRect** srcROI, **Npp8u** *pDst, int nDstStep, **NppiSize** dstROISize, double xFactor, double yFactor, int interpolation)
8-bit unsigned image resize.

- `NppStatus nppiResize_8u_C4R` (const `Npp8u` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcROI, `Npp8u` *pDst, int nDstStep, `NppiSize` dstROISize, double xFactor, double yFactor, int interpolation)

4 channel 8-bit unsigned image resize.

Rotate

Rotates an image around the origin (0,0) and then shifts it.

- `NppStatus nppiRotate_8u_C1R` (const `Npp8u` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcROI, `Npp8u` *pDst, int nDstStep, `NppiRect` dstROI, double angle, double xShift, double yShift, int interpolation)

8-bit unsigned image rotate.

- `NppStatus nppiRotate_8u_C4R` (const `Npp8u` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcROI, `Npp8u` *pDst, int nDstStep, `NppiRect` dstROI, double angle, double xShift, double yShift, int interpolation)

4 channel 8-bit unsigned image rotate.

Mirror

Mirrors images horizontally, vertically and diagonally.

- `NppStatus nppiMirror_8u_C1R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oROI, `NppiAxis` flip)

8-bit unsigned image mirror.

- `NppStatus nppiMirror_8u_C4R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oROI, `NppiAxis` flip)

4 channel 8-bit unsigned image mirror.

RGBToYCbCr

RGB to YCbCr color conversion.

- `NppStatus nppiRGBToYCbCr_8u_C3R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)

3 channel 8-bit unsigned packed RGB to packed YCbCr color conversion.

- `NppStatus nppiRGBToYCbCr422_8u_C3C2R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)

3 channel 8-bit unsigned RGB to 2 channel chroma packed YCbCr422 color conversion.

- `NppStatus nppiRGBToYCbCr420_8u_C3P3R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` **pDst, int nDstStep[3], `NppiSize` oSizeROI)

3 channel 8-bit unsigned packed RGB to planar YCbCr420 color conversion.

- `NppStatus nppiRGBToYCbCr_8u_P3R` (const `Npp8u` *const *pSrc, int nSrcStep, `Npp8u` **pDst, int nDstStep, `NppiSize` oSizeROI)

3 channel planar 8-bit unsigned RGB to YCbCr color conversion.

- `NppStatus nppiRGBToYCbCr_8u_AC4R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)

4 channel 8-bit unsigned RGB to YCbCr color conversion, ignoring Alpha.

YCbCrToRGB

YCbCr to RGB color conversion.

- `NppStatus nppiYCbCrToRGB_8u_C3R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)

3 channel 8-bit unsigned packed YCbCr to RGB color conversion.

- `NppStatus nppiYCbCrToRGB_8u_P3R` (const `Npp8u` *const *pSrc, int nSrcStep, `Npp8u` **pDst, int nDstStep, `NppiSize` oSizeROI)

3 channel 8-bit unsigned planar YCbCr to RGB color conversion.

- `NppStatus nppiYCbCrToRGB_8u_AC4R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)

4 channel 8-bit unsigned packed YCbCr to RGB color conversion, not affecting Alpha.

- `NppStatus nppiYCbCr422ToRGB_8u_C2C3R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)

2 channel 8-bit unsigned YCbCr422 to 3 channel packed RGB color conversion.

- `NppStatus nppiYCbCr420ToRGB_8u_P3C3R` (const `Npp8u` *const *pSrc, int nSrcStep[3], `Npp8u` **pDst, int nDstStep, `NppiSize` oSizeROI)

3 channel 8-bit unsigned planar YCbCr420 to packed RGB color conversion.

Sample Pattern Conversion.

- `NppStatus nppiYCbCr422ToYCbCr420_8u_P3R` (const `Npp8u` *const *pSrc, int nSrcStep[3], `Npp8u` **pDst, int nDstStep[3], `NppiSize` oSizeROI)

3 channel 8-bit unsigned planar YCbCr:422 to YCbCr:420 resampling.

- `NppStatus nppiYCbCr422ToYCbCr411_8u_P3R` (const `Npp8u` *const *pSrc, int nSrcStep[3], `Npp8u` **pDst, int nDstStep[3], `NppiSize` oSizeROI)

3 channel 8-bit unsigned planar YCbCr:422 to YCbCr:411 resampling.

- `NppStatus nppiYCbCr420ToYCbCr422_8u_P3R` (const `Npp8u` *const *pSrc, int nSrcStep[3], `Npp8u` **pDst, int nDstStep[3], `NppiSize` oSizeROI)

3 channel 8-bit unsigned planar YCbCr:420 to YCbCr:422 resampling.

- `NppStatus nppiYCbCr420ToYCbCr411_8u_P3P2R` (const `Npp8u` *const *pSrc, int aSrcStep[3], `Npp8u` *pDstY, int nDstYStep, `Npp8u` *pDstCbCr, int nDstCbCrStep, `NppiSize` oSizeROI)

3 channel 8-bit unsigned planar YCbCr:420 to YCbCr:411 resampling.

Color Processing

Color manipulation functions.

- `NppStatus nppiColorTwist32f_8u_C3R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp32f` twist[3][4])

3 channel 8-bit unsigned color twist.

- `NppStatus nppiColorTwist32f_8u_P3R` (const `Npp8u` *const *pSrc, int nSrcStep, `Npp8u` **pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp32f` twist[3][4])

3 channel planar 8-bit unsigned color twist.

- `NppStatus nppiColorTwist32f_8u_AC4R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp32f` twist[3][4])

4 channel 8-bit unsigned color twist, not affecting Alpha.

- `NppStatus nppiLUT_Linear_8u_C1R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp32s` *pValues, const `Npp32s` *pLevels, int nLevels)

8-bit unsigned look-up-table color conversion.

- `NppStatus nppiLUT_Linear_8u_C3R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp32s` *pValues[3], const `Npp32s` *pLevels[3], int nLevels[3])

3 channel 8-bit unsigned look-up-table color conversion.

- `NppStatus nppiLUT_Linear_8u_AC4R` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, const `Npp32s` *pValues[4], const `Npp32s` *pLevels[4], int nLevels[4])

4 channel 8-bit unsigned look-up-table color conversion, not affecting Alpha.

Affine warping, affine transform calculation

Affine warping of an image is the transform of image pixel positions, defined by the following formulas:

$$X_{new} = C_{00} * x + C_{01} * y + C_{02} \quad Y_{new} = C_{10} * x + C_{11} * y + C_{12} \quad C = \begin{bmatrix} C_{00} & C_{01} & C_{02} \\ C_{10} & C_{11} & C_{12} \end{bmatrix}$$

That is, any pixel with coordinates (X_{new}, Y_{new}) in the transformed image is sourced from coordinates (x, y) in the original image.

The mapping C is completely specified by 6 values $C_{ij}, i = \overline{0,1}, j = \overline{0,2}$. The transform maps parallel lines to parallel lines and preserves ratios of distances of points to lines. Implementation specific properties are discussed in each function's documentation.

- `NppStatus nppiGetAffineTransform` (`NppiRect` srcRoi, const double quad[4][2], double coeffs[2][3])

Calculates affine transform coefficients given source rectangular ROI and its destination quadrangle projection.

- **NppStatus nppiGetAffineQuad** (**NppiRect** srcRoi, double quad[4][2], const double coeffs[2][3])
Calculates affine transform projection of given source rectangular ROI.
- **NppStatus nppiGetAffineBound** (**NppiRect** srcRoi, double bound[2][2], const double coeffs[2][3])
Calculates bounding box of the affine transform projection of the given source rectangular ROI.
- **NppStatus nppiWarpAffine_8u_C1R** (const **Npp8u** *pSrc, **NppiSize** srcSize, int nSrcStep, **NppiRect** srcRoi, **Npp8u** *pDst, int nDstStep, **NppiRect** dstRoi, const double coeffs[2][3], int interpolation)
Affine transform of an image (8bit unsigned integer, single channel).
- **NppStatus nppiWarpAffine_8u_C3R** (const **Npp8u** *pSrc, **NppiSize** srcSize, int nSrcStep, **NppiRect** srcRoi, **Npp8u** *pDst, int nDstStep, **NppiRect** dstRoi, const double coeffs[2][3], int interpolation)
Affine transform of an image (8bit unsigned integer, three channels).
- **NppStatus nppiWarpAffine_8u_C4R** (const **Npp8u** *pSrc, **NppiSize** srcSize, int nSrcStep, **NppiRect** srcRoi, **Npp8u** *pDst, int nDstStep, **NppiRect** dstRoi, const double coeffs[2][3], int interpolation)
Affine transform of an image (8bit unsigned integer, four channels).
- **NppStatus nppiWarpAffine_8u_AC4R** (const **Npp8u** *pSrc, **NppiSize** srcSize, int nSrcStep, **NppiRect** srcRoi, **Npp8u** *pDst, int nDstStep, **NppiRect** dstRoi, const double coeffs[2][3], int interpolation)
Affine transform of an image (8bit unsigned integer, four channels RGBA).
- **NppStatus nppiWarpAffine_8u_P3R** (const **Npp8u** *pSrc[3], **NppiSize** srcSize, int nSrcStep, **NppiRect** srcRoi, **Npp8u** *pDst[3], int nDstStep, **NppiRect** dstRoi, const double coeffs[2][3], int interpolation)
Affine transform of an image (8bit unsigned integer, three planes).
- **NppStatus nppiWarpAffine_8u_P4R** (const **Npp8u** *pSrc[4], **NppiSize** srcSize, int nSrcStep, **NppiRect** srcRoi, **Npp8u** *pDst[4], int nDstStep, **NppiRect** dstRoi, const double coeffs[2][3], int interpolation)
Affine transform of an image (8bit unsigned integer, four planes).
- **NppStatus nppiWarpAffineBack_8u_C1R** (const **Npp8u** *pSrc, **NppiSize** srcSize, int nSrcStep, **NppiRect** srcRoi, **Npp8u** *pDst, int nDstStep, **NppiRect** dstRoi, const double coeffs[2][3], int interpolation)
Inverse affine transform of an image (8bit unsigned integer, single channel).
- **NppStatus nppiWarpAffineBack_8u_C3R** (const **Npp8u** *pSrc, **NppiSize** srcSize, int nSrcStep, **NppiRect** srcRoi, **Npp8u** *pDst, int nDstStep, **NppiRect** dstRoi, const double coeffs[2][3], int interpolation)
Inverse affine transform of an image (8bit unsigned integer, three channels).
- **NppStatus nppiWarpAffineBack_8u_C4R** (const **Npp8u** *pSrc, **NppiSize** srcSize, int nSrcStep, **NppiRect** srcRoi, **Npp8u** *pDst, int nDstStep, **NppiRect** dstRoi, const double coeffs[2][3], int interpolation)
Inverse affine transform of an image (8bit unsigned integer, four channels).
- **NppStatus nppiWarpAffineBack_8u_AC4R** (const **Npp8u** *pSrc, **NppiSize** srcSize, int nSrcStep, **NppiRect** srcRoi, **Npp8u** *pDst, int nDstStep, **NppiRect** dstRoi, const double coeffs[2][3], int interpolation)

Inverse affine transform of an image (8bit unsigned integer, four channels RGBA).

- `NppStatus nppiWarpAffineBack_8u_P3R` (const `Npp8u` *pSrc[3], `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp8u` *pDst[3], int nDstStep, `NppiRect` dstRoi, const double coeffs[2][3], int interpolation)

Inverse affine transform of an image (8bit unsigned integer, three planes).

- `NppStatus nppiWarpAffineBack_8u_P4R` (const `Npp8u` *pSrc[4], `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp8u` *pDst[4], int nDstStep, `NppiRect` dstRoi, const double coeffs[2][3], int interpolation)

Inverse affine transform of an image (8bit unsigned integer, four planes).

- `NppStatus nppiWarpAffineQuad_8u_C1R` (const `Npp8u` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, const double srcQuad[4][2], `Npp8u` *pDst, int nDstStep, `NppiRect` dstRoi, const double dstQuad[4][2], int interpolation)

Affine transform of an image (8bit unsigned integer, single channel).

- `NppStatus nppiWarpAffineQuad_8u_C3R` (const `Npp8u` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, const double srcQuad[4][2], `Npp8u` *pDst, int nDstStep, `NppiRect` dstRoi, const double dstQuad[4][2], int interpolation)

Affine transform of an image (8bit unsigned integer, three channels).

- `NppStatus nppiWarpAffineQuad_8u_C4R` (const `Npp8u` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, const double srcQuad[4][2], `Npp8u` *pDst, int nDstStep, `NppiRect` dstRoi, const double dstQuad[4][2], int interpolation)

Affine transform of an image (8bit unsigned integer, four channels).

- `NppStatus nppiWarpAffineQuad_8u_AC4R` (const `Npp8u` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, const double srcQuad[4][2], `Npp8u` *pDst, int nDstStep, `NppiRect` dstRoi, const double dstQuad[4][2], int interpolation)

Affine transform of an image (8bit unsigned integer, four channels RGBA).

- `NppStatus nppiWarpAffineQuad_8u_P3R` (const `Npp8u` *pSrc[3], `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, const double srcQuad[4][2], `Npp8u` *pDst[3], int nDstStep, `NppiRect` dstRoi, const double dstQuad[4][2], int interpolation)

Affine transform of an image (8bit unsigned integer, three planes).

- `NppStatus nppiWarpAffineQuad_8u_P4R` (const `Npp8u` *pSrc[4], `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, const double srcQuad[4][2], `Npp8u` *pDst[4], int nDstStep, `NppiRect` dstRoi, const double dstQuad[4][2], int interpolation)

Affine transform of an image (8bit unsigned integer, four planes).

- `NppStatus nppiWarpAffine_16u_C1R` (const `Npp16u` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp16u` *pDst, int nDstStep, `NppiRect` dstRoi, const double coeffs[2][3], int interpolation)

Affine transform of an image (16bit unsigned integer, single channel).

- `NppStatus nppiWarpAffine_16u_C3R` (const `Npp16u` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp16u` *pDst, int nDstStep, `NppiRect` dstRoi, const double coeffs[2][3], int interpolation)

Affine transform of an image (16bit unsigned integer, three channels).

- `NppStatus nppiWarpAffine_16u_C4R` (const `Npp16u` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp16u` *pDst, int nDstStep, `NppiRect` dstRoi, const double coeffs[2][3], int interpolation)

Affine transform of an image (16bit unsigned integer, four channels).

- `NppStatus nppiWarpAffine_16u_AC4R` (const `Npp16u` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp16u` *pDst, int nDstStep, `NppiRect` dstRoi, const double coeffs[2][3], int interpolation)

Affine transform of an image (16bit unsigned integer, four channels RGBA).

- `NppStatus nppiWarpAffine_16u_P3R` (const `Npp16u` *pSrc[3], `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp16u` *pDst[3], int nDstStep, `NppiRect` dstRoi, const double coeffs[2][3], int interpolation)

Affine transform of an image (16bit unsigned integer, three planes).

- `NppStatus nppiWarpAffine_16u_P4R` (const `Npp16u` *pSrc[4], `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp16u` *pDst[4], int nDstStep, `NppiRect` dstRoi, const double coeffs[2][3], int interpolation)

Affine transform of an image (16bit unsigned integer, four planes).

- `NppStatus nppiWarpAffineBack_16u_C1R` (const `Npp16u` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp16u` *pDst, int nDstStep, `NppiRect` dstRoi, const double coeffs[2][3], int interpolation)

Inverse affine transform of an image (16bit unsigned integer, single channel).

- `NppStatus nppiWarpAffineBack_16u_C3R` (const `Npp16u` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp16u` *pDst, int nDstStep, `NppiRect` dstRoi, const double coeffs[2][3], int interpolation)

Inverse affine transform of an image (16bit unsigned integer, three channels).

- `NppStatus nppiWarpAffineBack_16u_C4R` (const `Npp16u` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp16u` *pDst, int nDstStep, `NppiRect` dstRoi, const double coeffs[2][3], int interpolation)

Inverse affine transform of an image (16bit unsigned integer, four channels).

- `NppStatus nppiWarpAffineBack_16u_AC4R` (const `Npp16u` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp16u` *pDst, int nDstStep, `NppiRect` dstRoi, const double coeffs[2][3], int interpolation)

Inverse affine transform of an image (16bit unsigned integer, four channels RGBA).

- `NppStatus nppiWarpAffineBack_16u_P3R` (const `Npp16u` *pSrc[3], `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp16u` *pDst[3], int nDstStep, `NppiRect` dstRoi, const double coeffs[2][3], int interpolation)

Inverse affine transform of an image (16bit unsigned integer, three planes).

- `NppStatus nppiWarpAffineBack_16u_P4R` (const `Npp16u` *pSrc[4], `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp16u` *pDst[4], int nDstStep, `NppiRect` dstRoi, const double coeffs[2][3], int interpolation)

Inverse affine transform of an image (16bit unsigned integer, four planes).

- `NppStatus nppiWarpAffineQuad_16u_C1R` (const `Npp16u` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, const double srcQuad[4][2], `Npp16u` *pDst, int nDstStep, `NppiRect` dstRoi, const double dstQuad[4][2], int interpolation)

Affine transform of an image (16bit unsigned integer, single channel).

- `NppStatus nppiWarpAffineQuad_16u_C3R` (const `Npp16u` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, const double srcQuad[4][2], `Npp16u` *pDst, int nDstStep, `NppiRect` dstRoi, const double dstQuad[4][2], int interpolation)

Affine transform of an image (16bit unsigned integer, three channels).

- `NppStatus nppiWarpAffineQuad_16u_C4R` (const `Npp16u` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, const double srcQuad[4][2], `Npp16u` *pDst, int nDstStep, `NppiRect` dstRoi, const double dstQuad[4][2], int interpolation)

Affine transform of an image (16bit unsigned integer, four channels).

- `NppStatus nppiWarpAffineQuad_16u_AC4R` (const `Npp16u` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, const double srcQuad[4][2], `Npp16u` *pDst, int nDstStep, `NppiRect` dstRoi, const double dstQuad[4][2], int interpolation)

Affine transform of an image (16bit unsigned integer, four channels RGBA).

- `NppStatus nppiWarpAffineQuad_16u_P3R` (const `Npp16u` *pSrc[3], `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, const double srcQuad[4][2], `Npp16u` *pDst[3], int nDstStep, `NppiRect` dstRoi, const double dstQuad[4][2], int interpolation)

Affine transform of an image (16bit unsigned integer, three planes).

- `NppStatus nppiWarpAffineQuad_16u_P4R` (const `Npp16u` *pSrc[4], `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, const double srcQuad[4][2], `Npp16u` *pDst[4], int nDstStep, `NppiRect` dstRoi, const double dstQuad[4][2], int interpolation)

Affine transform of an image (16bit unsigned integer, four planes).

- `NppStatus nppiWarpAffine_32f_C1R` (const `Npp32f` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp32f` *pDst, int nDstStep, `NppiRect` dstRoi, const double coeffs[2][3], int interpolation)

Affine transform of an image (32bit float, single channel).

- `NppStatus nppiWarpAffine_32f_C3R` (const `Npp32f` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp32f` *pDst, int nDstStep, `NppiRect` dstRoi, const double coeffs[2][3], int interpolation)

Affine transform of an image (32bit float, three channels).

- `NppStatus nppiWarpAffine_32f_C4R` (const `Npp32f` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp32f` *pDst, int nDstStep, `NppiRect` dstRoi, const double coeffs[2][3], int interpolation)

Affine transform of an image (32bit float, four channels).

- `NppStatus nppiWarpAffine_32f_AC4R` (const `Npp32f` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp32f` *pDst, int nDstStep, `NppiRect` dstRoi, const double coeffs[2][3], int interpolation)

Affine transform of an image (32bit float, four channels RGBA).

- `NppStatus nppiWarpAffine_32f_P3R` (const `Npp32f *pSrc[3]`, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp32f *pDst[3]`, int nDstStep, `NppiRect` dstRoi, const double coeffs[2][3], int interpolation)

Affine transform of an image (32bit float, three planes).

- `NppStatus nppiWarpAffine_32f_P4R` (const `Npp32f *pSrc[4]`, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp32f *pDst[4]`, int nDstStep, `NppiRect` dstRoi, const double coeffs[2][3], int interpolation)

Affine transform of an image (32bit float, four planes).

- `NppStatus nppiWarpAffineBack_32f_C1R` (const `Npp32f *pSrc`, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp32f *pDst`, int nDstStep, `NppiRect` dstRoi, const double coeffs[2][3], int interpolation)

Inverse affine transform of an image (32bit float, single channel).

- `NppStatus nppiWarpAffineBack_32f_C3R` (const `Npp32f *pSrc`, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp32f *pDst`, int nDstStep, `NppiRect` dstRoi, const double coeffs[2][3], int interpolation)

Inverse affine transform of an image (32bit float, three channels).

- `NppStatus nppiWarpAffineBack_32f_C4R` (const `Npp32f *pSrc`, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp32f *pDst`, int nDstStep, `NppiRect` dstRoi, const double coeffs[2][3], int interpolation)

Inverse affine transform of an image (32bit float, four channels).

- `NppStatus nppiWarpAffineBack_32f_AC4R` (const `Npp32f *pSrc`, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp32f *pDst`, int nDstStep, `NppiRect` dstRoi, const double coeffs[2][3], int interpolation)

Inverse affine transform of an image (32bit float, four channels RGBA).

- `NppStatus nppiWarpAffineBack_32f_P3R` (const `Npp32f *pSrc[3]`, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp32f *pDst[3]`, int nDstStep, `NppiRect` dstRoi, const double coeffs[2][3], int interpolation)

Inverse affine transform of an image (32bit float, three planes).

- `NppStatus nppiWarpAffineBack_32f_P4R` (const `Npp32f *pSrc[4]`, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp32f *pDst[4]`, int nDstStep, `NppiRect` dstRoi, const double coeffs[2][3], int interpolation)

Inverse affine transform of an image (32bit float, four planes).

- `NppStatus nppiWarpAffineQuad_32f_C1R` (const `Npp32f *pSrc`, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, const double srcQuad[4][2], `Npp32f *pDst`, int nDstStep, `NppiRect` dstRoi, const double dstQuad[4][2], int interpolation)

Affine transform of an image (32bit float, single channel).

- `NppStatus nppiWarpAffineQuad_32f_C3R` (const `Npp32f *pSrc`, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, const double srcQuad[4][2], `Npp32f *pDst`, int nDstStep, `NppiRect` dstRoi, const double dstQuad[4][2], int interpolation)

Affine transform of an image (32bit float, three channels).

- `NppStatus nppiWarpAffineQuad_32f_C4R` (const `Npp32f` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, const double srcQuad[4][2], `Npp32f` *pDst, int nDstStep, `NppiRect` dstRoi, const double dstQuad[4][2], int interpolation)

Affine transform of an image (32bit float, four channels).

- `NppStatus nppiWarpAffineQuad_32f_AC4R` (const `Npp32f` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, const double srcQuad[4][2], `Npp32f` *pDst, int nDstStep, `NppiRect` dstRoi, const double dstQuad[4][2], int interpolation)

Affine transform of an image (32bit float, four channels RGBA).

- `NppStatus nppiWarpAffineQuad_32f_P3R` (const `Npp32f` *pSrc[3], `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, const double srcQuad[4][2], `Npp32f` *pDst[3], int nDstStep, `NppiRect` dstRoi, const double dstQuad[4][2], int interpolation)

Affine transform of an image (32bit float, three planes).

- `NppStatus nppiWarpAffineQuad_32f_P4R` (const `Npp32f` *pSrc[4], `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, const double srcQuad[4][2], `Npp32f` *pDst[4], int nDstStep, `NppiRect` dstRoi, const double dstQuad[4][2], int interpolation)

Affine transform of an image (32bit float, four planes).

- `NppStatus nppiWarpAffine_32s_C1R` (const `Npp32s` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp32s` *pDst, int nDstStep, `NppiRect` dstRoi, const double coeffs[2][3], int interpolation)

Affine transform of an image (32bit signed integer, single channel).

- `NppStatus nppiWarpAffine_32s_C3R` (const `Npp32s` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp32s` *pDst, int nDstStep, `NppiRect` dstRoi, const double coeffs[2][3], int interpolation)

Affine transform of an image (32bit signed integer, three channels).

- `NppStatus nppiWarpAffine_32s_C4R` (const `Npp32s` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp32s` *pDst, int nDstStep, `NppiRect` dstRoi, const double coeffs[2][3], int interpolation)

Affine transform of an image (32bit signed integer, four channels).

- `NppStatus nppiWarpAffine_32s_AC4R` (const `Npp32s` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp32s` *pDst, int nDstStep, `NppiRect` dstRoi, const double coeffs[2][3], int interpolation)

Affine transform of an image (32bit signed integer, four channels RGBA).

- `NppStatus nppiWarpAffine_32s_P3R` (const `Npp32s` *pSrc[3], `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp32s` *pDst[3], int nDstStep, `NppiRect` dstRoi, const double coeffs[2][3], int interpolation)

Affine transform of an image (32bit signed integer, three planes).

- `NppStatus nppiWarpAffine_32s_P4R` (const `Npp32s` *pSrc[4], `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp32s` *pDst[4], int nDstStep, `NppiRect` dstRoi, const double coeffs[2][3], int interpolation)

Affine transform of an image (32bit signed integer, four planes).

- `NppStatus nppiWarpAffineBack_32s_C1R` (const `Npp32s` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp32s` *pDst, int nDstStep, `NppiRect` dstRoi, const double coeffs[2][3], int interpolation)

Inverse affine transform of an image (32bit signed integer, single channel).

- `NppStatus nppiWarpAffineBack_32s_C3R` (const `Npp32s` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp32s` *pDst, int nDstStep, `NppiRect` dstRoi, const double coeffs[2][3], int interpolation)

Inverse affine transform of an image (32bit signed integer, three channels).

- `NppStatus nppiWarpAffineBack_32s_C4R` (const `Npp32s` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp32s` *pDst, int nDstStep, `NppiRect` dstRoi, const double coeffs[2][3], int interpolation)

Inverse affine transform of an image (32bit signed integer, four channels).

- `NppStatus nppiWarpAffineBack_32s_AC4R` (const `Npp32s` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp32s` *pDst, int nDstStep, `NppiRect` dstRoi, const double coeffs[2][3], int interpolation)

Inverse affine transform of an image (32bit signed integer, four channels RGBA).

- `NppStatus nppiWarpAffineBack_32s_P3R` (const `Npp32s` *pSrc[3], `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp32s` *pDst[3], int nDstStep, `NppiRect` dstRoi, const double coeffs[2][3], int interpolation)

Inverse affine transform of an image (32bit signed integer, three planes).

- `NppStatus nppiWarpAffineBack_32s_P4R` (const `Npp32s` *pSrc[4], `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp32s` *pDst[4], int nDstStep, `NppiRect` dstRoi, const double coeffs[2][3], int interpolation)

Inverse affine transform of an image (32bit signed integer, four planes).

- `NppStatus nppiWarpAffineQuad_32s_C1R` (const `Npp32s` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, const double srcQuad[4][2], `Npp32s` *pDst, int nDstStep, `NppiRect` dstRoi, const double dstQuad[4][2], int interpolation)

Affine transform of an image (32bit signed integer, single channel).

- `NppStatus nppiWarpAffineQuad_32s_C3R` (const `Npp32s` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, const double srcQuad[4][2], `Npp32s` *pDst, int nDstStep, `NppiRect` dstRoi, const double dstQuad[4][2], int interpolation)

Affine transform of an image (32bit signed integer, three channels).

- `NppStatus nppiWarpAffineQuad_32s_C4R` (const `Npp32s` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, const double srcQuad[4][2], `Npp32s` *pDst, int nDstStep, `NppiRect` dstRoi, const double dstQuad[4][2], int interpolation)

Affine transform of an image (32bit signed integer, four channels).

- `NppStatus nppiWarpAffineQuad_32s_AC4R` (const `Npp32s` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, const double srcQuad[4][2], `Npp32s` *pDst, int nDstStep, `NppiRect` dstRoi, const double dstQuad[4][2], int interpolation)

Affine transform of an image (32bit signed integer, four channels RGBA).

- **NppStatus** **nppiWarpAffineQuad_32s_P3R** (const **Npp32s** *pSrc[3], **NppiSize** srcSize, int nSrcStep, **NppiRect** srcRoi, const double srcQuad[4][2], **Npp32s** *pDst[3], int nDstStep, **NppiRect** dstRoi, const double dstQuad[4][2], int interpolation)

Affine transform of an image (32bit signed integer, three planes).

- **NppStatus** **nppiWarpAffineQuad_32s_P4R** (const **Npp32s** *pSrc[4], **NppiSize** srcSize, int nSrcStep, **NppiRect** srcRoi, const double srcQuad[4][2], **Npp32s** *pDst[4], int nDstStep, **NppiRect** dstRoi, const double dstQuad[4][2], int interpolation)

Affine transform of an image (32bit signed integer, four planes).

Perspective warping, perspective transform calculation

Perspective warping of an image is the transform of image pixel positions, defined by the following formulas:

$$X_{new} = \frac{C_{00} * x + C_{01} * y + C_{02}}{C_{20} * x + C_{21} * y + C_{22}} \quad Y_{new} = \frac{C_{10} * x + C_{11} * y + C_{12}}{C_{20} * x + C_{21} * y + C_{22}} \quad C = \begin{bmatrix} C_{00} & C_{01} & C_{02} \\ C_{10} & C_{11} & C_{12} \\ C_{20} & C_{21} & C_{22} \end{bmatrix}$$

That is, any pixel of the transformed image with coordinates (X_{new}, Y_{new}) has a preimage with coordinates (x, y) .

The mapping C is fully defined by 8 values $C_{ij}, (i, j) = \overline{0, 2}$, except of C_{22} , which is a normalizer. The transform has a property of mapping any convex quadrangle to a convex quadrangle, which is used in a group of functions **nppiWarpPerspectiveQuad**. The NPPI implementation of perspective transform has some issues which are discussed in each function's documentation.

- **NppStatus** **nppiGetPerspectiveTransform** (**NppiRect** srcRoi, const double quad[4][2], double coeffs[3][3])

Calculates perspective transform coefficients given source rectangular ROI and its destination quadrangle projection.

- **NppStatus** **nppiGetPerspectiveQuad** (**NppiRect** srcRoi, double quad[4][2], const double coeffs[3][3])

Calculates perspective transform projection of given source rectangular ROI.

- **NppStatus** **nppiGetPerspectiveBound** (**NppiRect** srcRoi, double bound[2][2], const double coeffs[3][3])

Calculates bounding box of the perspective transform projection of the given source rectangular ROI.

- **NppStatus** **nppiWarpPerspective_8u_C1R** (const **Npp8u** *pSrc, **NppiSize** srcSize, int nSrcStep, **NppiRect** srcRoi, **Npp8u** *pDst, int nDstStep, **NppiRect** dstRoi, const double coeffs[3][3], int interpolation)

Perspective transform of an image (8bit unsigned integer, single channel).

- **NppStatus** **nppiWarpPerspective_8u_C3R** (const **Npp8u** *pSrc, **NppiSize** srcSize, int nSrcStep, **NppiRect** srcRoi, **Npp8u** *pDst, int nDstStep, **NppiRect** dstRoi, const double coeffs[3][3], int interpolation)

Perspective transform of an image (8bit unsigned integer, three channels).

- `NppStatus nppiWarpPerspective_8u_C4R` (const `Npp8u` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp8u` *pDst, int nDstStep, `NppiRect` dstRoi, const double coeffs[3][3], int interpolation)

Perspective transform of an image (8bit unsigned integer, four channels).

- `NppStatus nppiWarpPerspective_8u_AC4R` (const `Npp8u` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp8u` *pDst, int nDstStep, `NppiRect` dstRoi, const double coeffs[3][3], int interpolation)

Perspective transform of an image (8bit unsigned integer, four channels RGBA).

- `NppStatus nppiWarpPerspective_8u_P3R` (const `Npp8u` *pSrc[3], `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp8u` *pDst[3], int nDstStep, `NppiRect` dstRoi, const double coeffs[3][3], int interpolation)

Perspective transform of an image (8bit unsigned integer, three planes).

- `NppStatus nppiWarpPerspective_8u_P4R` (const `Npp8u` *pSrc[4], `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp8u` *pDst[4], int nDstStep, `NppiRect` dstRoi, const double coeffs[3][3], int interpolation)

Perspective transform of an image (8bit unsigned integer, four planes).

- `NppStatus nppiWarpPerspectiveBack_8u_C1R` (const `Npp8u` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp8u` *pDst, int nDstStep, `NppiRect` dstRoi, const double coeffs[3][3], int interpolation)

Inverse perspective transform of an image (8bit unsigned integer, single channel).

- `NppStatus nppiWarpPerspectiveBack_8u_C3R` (const `Npp8u` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp8u` *pDst, int nDstStep, `NppiRect` dstRoi, const double coeffs[3][3], int interpolation)

Inverse perspective transform of an image (8bit unsigned integer, three channels).

- `NppStatus nppiWarpPerspectiveBack_8u_C4R` (const `Npp8u` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp8u` *pDst, int nDstStep, `NppiRect` dstRoi, const double coeffs[3][3], int interpolation)

Inverse perspective transform of an image (8bit unsigned integer, four channels).

- `NppStatus nppiWarpPerspectiveBack_8u_AC4R` (const `Npp8u` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp8u` *pDst, int nDstStep, `NppiRect` dstRoi, const double coeffs[3][3], int interpolation)

Inverse perspective transform of an image (8bit unsigned integer, four channels RGBA).

- `NppStatus nppiWarpPerspectiveBack_8u_P3R` (const `Npp8u` *pSrc[3], `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp8u` *pDst[3], int nDstStep, `NppiRect` dstRoi, const double coeffs[3][3], int interpolation)

Inverse perspective transform of an image (8bit unsigned integer, three planes).

- `NppStatus nppiWarpPerspectiveBack_8u_P4R` (const `Npp8u` *pSrc[4], `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp8u` *pDst[4], int nDstStep, `NppiRect` dstRoi, const double coeffs[3][3], int interpolation)

Inverse perspective transform of an image (8bit unsigned integer, four planes).

- `NppStatus nppiWarpPerspectiveQuad_8u_C1R` (const `Npp8u` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, const double srcQuad[4][2], `Npp8u` *pDst, int nDstStep, `NppiRect` dstRoi, const double dstQuad[4][2], int interpolation)

Perspective transform of an image (8bit unsigned integer, single channel).

- `NppStatus nppiWarpPerspectiveQuad_8u_C3R` (const `Npp8u` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, const double srcQuad[4][2], `Npp8u` *pDst, int nDstStep, `NppiRect` dstRoi, const double dstQuad[4][2], int interpolation)

Perspective transform of an image (8bit unsigned integer, three channels).

- `NppStatus nppiWarpPerspectiveQuad_8u_C4R` (const `Npp8u` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, const double srcQuad[4][2], `Npp8u` *pDst, int nDstStep, `NppiRect` dstRoi, const double dstQuad[4][2], int interpolation)

Perspective transform of an image (8bit unsigned integer, four channels).

- `NppStatus nppiWarpPerspectiveQuad_8u_AC4R` (const `Npp8u` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, const double srcQuad[4][2], `Npp8u` *pDst, int nDstStep, `NppiRect` dstRoi, const double dstQuad[4][2], int interpolation)

Perspective transform of an image (8bit unsigned integer, four channels RGBA).

- `NppStatus nppiWarpPerspectiveQuad_8u_P3R` (const `Npp8u` *pSrc[3], `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, const double srcQuad[4][2], `Npp8u` *pDst[3], int nDstStep, `NppiRect` dstRoi, const double dstQuad[4][2], int interpolation)

Perspective transform of an image (8bit unsigned integer, three planes).

- `NppStatus nppiWarpPerspectiveQuad_8u_P4R` (const `Npp8u` *pSrc[4], `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, const double srcQuad[4][2], `Npp8u` *pDst[4], int nDstStep, `NppiRect` dstRoi, const double dstQuad[4][2], int interpolation)

Perspective transform of an image (8bit unsigned integer, four planes).

- `NppStatus nppiWarpPerspective_16u_C1R` (const `Npp16u` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp16u` *pDst, int nDstStep, `NppiRect` dstRoi, const double coeffs[3][3], int interpolation)

Perspective transform of an image (16bit unsigned integer, single channel).

- `NppStatus nppiWarpPerspective_16u_C3R` (const `Npp16u` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp16u` *pDst, int nDstStep, `NppiRect` dstRoi, const double coeffs[3][3], int interpolation)

Perspective transform of an image (16bit unsigned integer, three channels).

- `NppStatus nppiWarpPerspective_16u_C4R` (const `Npp16u` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp16u` *pDst, int nDstStep, `NppiRect` dstRoi, const double coeffs[3][3], int interpolation)

Perspective transform of an image (16bit unsigned integer, four channels).

- `NppStatus nppiWarpPerspective_16u_AC4R` (const `Npp16u` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp16u` *pDst, int nDstStep, `NppiRect` dstRoi, const double coeffs[3][3], int interpolation)

Perspective transform of an image (16bit unsigned integer, four channels RGBA).

- `NppStatus nppiWarpPerspective_16u_P3R` (const `Npp16u` *pSrc[3], `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp16u` *pDst[3], int nDstStep, `NppiRect` dstRoi, const double coeffs[3][3], int interpolation)

Perspective transform of an image (16bit unsigned integer, three planes).

- `NppStatus nppiWarpPerspective_16u_P4R` (const `Npp16u` *pSrc[4], `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp16u` *pDst[4], int nDstStep, `NppiRect` dstRoi, const double coeffs[3][3], int interpolation)

Perspective transform of an image (16bit unsigned integer, four planes).

- `NppStatus nppiWarpPerspectiveBack_16u_C1R` (const `Npp16u` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp16u` *pDst, int nDstStep, `NppiRect` dstRoi, const double coeffs[3][3], int interpolation)

Inverse perspective transform of an image (16bit unsigned integer, single channel).

- `NppStatus nppiWarpPerspectiveBack_16u_C3R` (const `Npp16u` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp16u` *pDst, int nDstStep, `NppiRect` dstRoi, const double coeffs[3][3], int interpolation)

Inverse perspective transform of an image (16bit unsigned integer, three channels).

- `NppStatus nppiWarpPerspectiveBack_16u_C4R` (const `Npp16u` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp16u` *pDst, int nDstStep, `NppiRect` dstRoi, const double coeffs[3][3], int interpolation)

Inverse perspective transform of an image (16bit unsigned integer, four channels).

- `NppStatus nppiWarpPerspectiveBack_16u_AC4R` (const `Npp16u` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp16u` *pDst, int nDstStep, `NppiRect` dstRoi, const double coeffs[3][3], int interpolation)

Inverse perspective transform of an image (16bit unsigned integer, four channels RGBA).

- `NppStatus nppiWarpPerspectiveBack_16u_P3R` (const `Npp16u` *pSrc[3], `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp16u` *pDst[3], int nDstStep, `NppiRect` dstRoi, const double coeffs[3][3], int interpolation)

Inverse perspective transform of an image (16bit unsigned integer, three planes).

- `NppStatus nppiWarpPerspectiveBack_16u_P4R` (const `Npp16u` *pSrc[4], `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp16u` *pDst[4], int nDstStep, `NppiRect` dstRoi, const double coeffs[3][3], int interpolation)

Inverse perspective transform of an image (16bit unsigned integer, four planes).

- `NppStatus nppiWarpPerspectiveQuad_16u_C1R` (const `Npp16u` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, const double srcQuad[4][2], `Npp16u` *pDst, int nDstStep, `NppiRect` dstRoi, const double dstQuad[4][2], int interpolation)

Perspective transform of an image (16bit unsigned integer, single channel).

- `NppStatus nppiWarpPerspectiveQuad_16u_C3R` (const `Npp16u` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, const double srcQuad[4][2], `Npp16u` *pDst, int nDstStep, `NppiRect` dstRoi, const double dstQuad[4][2], int interpolation)

Perspective transform of an image (16bit unsigned integer, three channels).

- `NppStatus nppiWarpPerspectiveQuad_16u_C4R` (const `Npp16u` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, const double srcQuad[4][2], `Npp16u` *pDst, int nDstStep, `NppiRect` dstRoi, const double dstQuad[4][2], int interpolation)

Perspective transform of an image (16bit unsigned integer, four channels).

- `NppStatus nppiWarpPerspectiveQuad_16u_AC4R` (const `Npp16u` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, const double srcQuad[4][2], `Npp16u` *pDst, int nDstStep, `NppiRect` dstRoi, const double dstQuad[4][2], int interpolation)

Perspective transform of an image (16bit unsigned integer, four channels RGBA).

- `NppStatus nppiWarpPerspectiveQuad_16u_P3R` (const `Npp16u` *pSrc[3], `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, const double srcQuad[4][2], `Npp16u` *pDst[3], int nDstStep, `NppiRect` dstRoi, const double dstQuad[4][2], int interpolation)

Perspective transform of an image (16bit unsigned integer, three planes).

- `NppStatus nppiWarpPerspectiveQuad_16u_P4R` (const `Npp16u` *pSrc[4], `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, const double srcQuad[4][2], `Npp16u` *pDst[4], int nDstStep, `NppiRect` dstRoi, const double dstQuad[4][2], int interpolation)

Perspective transform of an image (16bit unsigned integer, four planes).

- `NppStatus nppiWarpPerspective_32f_C1R` (const `Npp32f` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp32f` *pDst, int nDstStep, `NppiRect` dstRoi, const double coeffs[3][3], int interpolation)

Perspective transform of an image (32bit float, single channel).

- `NppStatus nppiWarpPerspective_32f_C3R` (const `Npp32f` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp32f` *pDst, int nDstStep, `NppiRect` dstRoi, const double coeffs[3][3], int interpolation)

Perspective transform of an image (32bit float, three channels).

- `NppStatus nppiWarpPerspective_32f_C4R` (const `Npp32f` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp32f` *pDst, int nDstStep, `NppiRect` dstRoi, const double coeffs[3][3], int interpolation)

Perspective transform of an image (32bit float, four channels).

- `NppStatus nppiWarpPerspective_32f_AC4R` (const `Npp32f` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp32f` *pDst, int nDstStep, `NppiRect` dstRoi, const double coeffs[3][3], int interpolation)

Perspective transform of an image (32bit float, four channels RGBA).

- `NppStatus nppiWarpPerspective_32f_P3R` (const `Npp32f` *pSrc[3], `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp32f` *pDst[3], int nDstStep, `NppiRect` dstRoi, const double coeffs[3][3], int interpolation)

Perspective transform of an image (32bit float, three planes).

- `NppStatus nppiWarpPerspective_32f_P4R` (const `Npp32f` *pSrc[4], `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp32f` *pDst[4], int nDstStep, `NppiRect` dstRoi, const double coeffs[3][3], int interpolation)

Perspective transform of an image (32bit float, four planes).

- **NppStatus nppiWarpPerspectiveBack_32f_C1R** (const **Npp32f** *pSrc, **NppiSize** srcSize, int nSrcStep, **NppiRect** srcRoi, **Npp32f** *pDst, int nDstStep, **NppiRect** dstRoi, const double coeffs[3][3], int interpolation)

Inverse perspective transform of an image (32bit float, single channel).

- **NppStatus nppiWarpPerspectiveBack_32f_C3R** (const **Npp32f** *pSrc, **NppiSize** srcSize, int nSrcStep, **NppiRect** srcRoi, **Npp32f** *pDst, int nDstStep, **NppiRect** dstRoi, const double coeffs[3][3], int interpolation)

Inverse perspective transform of an image (32bit float, three channels).

- **NppStatus nppiWarpPerspectiveBack_32f_C4R** (const **Npp32f** *pSrc, **NppiSize** srcSize, int nSrcStep, **NppiRect** srcRoi, **Npp32f** *pDst, int nDstStep, **NppiRect** dstRoi, const double coeffs[3][3], int interpolation)

Inverse perspective transform of an image (32bit float, four channels).

- **NppStatus nppiWarpPerspectiveBack_32f_AC4R** (const **Npp32f** *pSrc, **NppiSize** srcSize, int nSrcStep, **NppiRect** srcRoi, **Npp32f** *pDst, int nDstStep, **NppiRect** dstRoi, const double coeffs[3][3], int interpolation)

Inverse perspective transform of an image (32bit float, four channels RGBA).

- **NppStatus nppiWarpPerspectiveBack_32f_P3R** (const **Npp32f** *pSrc[3], **NppiSize** srcSize, int nSrcStep, **NppiRect** srcRoi, **Npp32f** *pDst[3], int nDstStep, **NppiRect** dstRoi, const double coeffs[3][3], int interpolation)

Inverse perspective transform of an image (32bit float, three planes).

- **NppStatus nppiWarpPerspectiveBack_32f_P4R** (const **Npp32f** *pSrc[4], **NppiSize** srcSize, int nSrcStep, **NppiRect** srcRoi, **Npp32f** *pDst[4], int nDstStep, **NppiRect** dstRoi, const double coeffs[3][3], int interpolation)

Inverse perspective transform of an image (32bit float, four planes).

- **NppStatus nppiWarpPerspectiveQuad_32f_C1R** (const **Npp32f** *pSrc, **NppiSize** srcSize, int nSrcStep, **NppiRect** srcRoi, const double srcQuad[4][2], **Npp32f** *pDst, int nDstStep, **NppiRect** dstRoi, const double dstQuad[4][2], int interpolation)

Perspective transform of an image (32bit float, single channel).

- **NppStatus nppiWarpPerspectiveQuad_32f_C3R** (const **Npp32f** *pSrc, **NppiSize** srcSize, int nSrcStep, **NppiRect** srcRoi, const double srcQuad[4][2], **Npp32f** *pDst, int nDstStep, **NppiRect** dstRoi, const double dstQuad[4][2], int interpolation)

Perspective transform of an image (32bit float, three channels).

- **NppStatus nppiWarpPerspectiveQuad_32f_C4R** (const **Npp32f** *pSrc, **NppiSize** srcSize, int nSrcStep, **NppiRect** srcRoi, const double srcQuad[4][2], **Npp32f** *pDst, int nDstStep, **NppiRect** dstRoi, const double dstQuad[4][2], int interpolation)

Perspective transform of an image (32bit float, four channels).

- **NppStatus nppiWarpPerspectiveQuad_32f_AC4R** (const **Npp32f** *pSrc, **NppiSize** srcSize, int nSrcStep, **NppiRect** srcRoi, const double srcQuad[4][2], **Npp32f** *pDst, int nDstStep, **NppiRect** dstRoi, const double dstQuad[4][2], int interpolation)

Perspective transform of an image (32bit float, four channels RGBA).

- `NppStatus nppiWarpPerspectiveQuad_32f_P3R` (const `Npp32f` *pSrc[3], `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, const double srcQuad[4][2], `Npp32f` *pDst[3], int nDstStep, `NppiRect` dstRoi, const double dstQuad[4][2], int interpolation)

Perspective transform of an image (32bit float, three planes).

- `NppStatus nppiWarpPerspectiveQuad_32f_P4R` (const `Npp32f` *pSrc[4], `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, const double srcQuad[4][2], `Npp32f` *pDst[4], int nDstStep, `NppiRect` dstRoi, const double dstQuad[4][2], int interpolation)

Perspective transform of an image (32bit float, four planes).

- `NppStatus nppiWarpPerspective_32s_C1R` (const `Npp32s` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp32s` *pDst, int nDstStep, `NppiRect` dstRoi, const double coeffs[3][3], int interpolation)

Perspective transform of an image (32bit signed integer, single channel).

- `NppStatus nppiWarpPerspective_32s_C3R` (const `Npp32s` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp32s` *pDst, int nDstStep, `NppiRect` dstRoi, const double coeffs[3][3], int interpolation)

Perspective transform of an image (32bit signed integer, three channels).

- `NppStatus nppiWarpPerspective_32s_C4R` (const `Npp32s` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp32s` *pDst, int nDstStep, `NppiRect` dstRoi, const double coeffs[3][3], int interpolation)

Perspective transform of an image (32bit signed integer, four channels).

- `NppStatus nppiWarpPerspective_32s_AC4R` (const `Npp32s` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp32s` *pDst, int nDstStep, `NppiRect` dstRoi, const double coeffs[3][3], int interpolation)

Perspective transform of an image (32bit signed integer, four channels RGBA).

- `NppStatus nppiWarpPerspective_32s_P3R` (const `Npp32s` *pSrc[3], `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp32s` *pDst[3], int nDstStep, `NppiRect` dstRoi, const double coeffs[3][3], int interpolation)

Perspective transform of an image (32bit signed integer, three planes).

- `NppStatus nppiWarpPerspective_32s_P4R` (const `Npp32s` *pSrc[4], `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp32s` *pDst[4], int nDstStep, `NppiRect` dstRoi, const double coeffs[3][3], int interpolation)

Perspective transform of an image (32bit signed integer, four planes).

- `NppStatus nppiWarpPerspectiveBack_32s_C1R` (const `Npp32s` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp32s` *pDst, int nDstStep, `NppiRect` dstRoi, const double coeffs[3][3], int interpolation)

Inverse perspective transform of an image (32bit signed integer, single channel).

- `NppStatus nppiWarpPerspectiveBack_32s_C3R` (const `Npp32s` *pSrc, `NppiSize` srcSize, int nSrcStep, `NppiRect` srcRoi, `Npp32s` *pDst, int nDstStep, `NppiRect` dstRoi, const double coeffs[3][3], int interpolation)

Inverse perspective transform of an image (32bit signed integer, three channels).

- **NppStatus nppiWarpPerspectiveBack_32s_C4R** (const **Npp32s** *pSrc, **NppiSize** srcSize, int nSrcStep, **NppiRect** srcRoi, **Npp32s** *pDst, int nDstStep, **NppiRect** dstRoi, const double coeffs[3][3], int interpolation)

Inverse perspective transform of an image (32bit signed integer, four channels).

- **NppStatus nppiWarpPerspectiveBack_32s_AC4R** (const **Npp32s** *pSrc, **NppiSize** srcSize, int nSrcStep, **NppiRect** srcRoi, **Npp32s** *pDst, int nDstStep, **NppiRect** dstRoi, const double coeffs[3][3], int interpolation)

Inverse perspective transform of an image (32bit signed integer, four channels RGBA).

- **NppStatus nppiWarpPerspectiveBack_32s_P3R** (const **Npp32s** *pSrc[3], **NppiSize** srcSize, int nSrcStep, **NppiRect** srcRoi, **Npp32s** *pDst[3], int nDstStep, **NppiRect** dstRoi, const double coeffs[3][3], int interpolation)

Inverse perspective transform of an image (32bit signed integer, three planes).

- **NppStatus nppiWarpPerspectiveBack_32s_P4R** (const **Npp32s** *pSrc[4], **NppiSize** srcSize, int nSrcStep, **NppiRect** srcRoi, **Npp32s** *pDst[4], int nDstStep, **NppiRect** dstRoi, const double coeffs[3][3], int interpolation)

Inverse perspective transform of an image (32bit signed integer, four planes).

- **NppStatus nppiWarpPerspectiveQuad_32s_C1R** (const **Npp32s** *pSrc, **NppiSize** srcSize, int nSrcStep, **NppiRect** srcRoi, const double srcQuad[4][2], **Npp32s** *pDst, int nDstStep, **NppiRect** dstRoi, const double dstQuad[4][2], int interpolation)

Perspective transform of an image (32bit signed integer, single channel).

- **NppStatus nppiWarpPerspectiveQuad_32s_C3R** (const **Npp32s** *pSrc, **NppiSize** srcSize, int nSrcStep, **NppiRect** srcRoi, const double srcQuad[4][2], **Npp32s** *pDst, int nDstStep, **NppiRect** dstRoi, const double dstQuad[4][2], int interpolation)

Perspective transform of an image (32bit signed integer, three channels).

- **NppStatus nppiWarpPerspectiveQuad_32s_C4R** (const **Npp32s** *pSrc, **NppiSize** srcSize, int nSrcStep, **NppiRect** srcRoi, const double srcQuad[4][2], **Npp32s** *pDst, int nDstStep, **NppiRect** dstRoi, const double dstQuad[4][2], int interpolation)

Perspective transform of an image (32bit signed integer, four channels).

- **NppStatus nppiWarpPerspectiveQuad_32s_AC4R** (const **Npp32s** *pSrc, **NppiSize** srcSize, int nSrcStep, **NppiRect** srcRoi, const double srcQuad[4][2], **Npp32s** *pDst, int nDstStep, **NppiRect** dstRoi, const double dstQuad[4][2], int interpolation)

Perspective transform of an image (32bit signed integer, four channels RGBA).

- **NppStatus nppiWarpPerspectiveQuad_32s_P3R** (const **Npp32s** *pSrc[3], **NppiSize** srcSize, int nSrcStep, **NppiRect** srcRoi, const double srcQuad[4][2], **Npp32s** *pDst[3], int nDstStep, **NppiRect** dstRoi, const double dstQuad[4][2], int interpolation)

Perspective transform of an image (32bit signed integer, three planes).

- **NppStatus nppiWarpPerspectiveQuad_32s_P4R** (const **Npp32s** *pSrc[4], **NppiSize** srcSize, int nSrcStep, **NppiRect** srcRoi, const double srcQuad[4][2], **Npp32s** *pDst[4], int nDstStep, **NppiRect** dstRoi, const double dstQuad[4][2], int interpolation)

Perspective transform of an image (32bit signed integer, four planes).

Image Labeling Techniques

- **NppStatus nppiGraphcutGetSize** (NppiSize size, int *pBufSize)
Calculates the size of the temporary buffer for graph-cut labeling.
- **NppStatus nppiGraphcut_32s8u** (Npp32s *pTerminals, Npp32s *pLeftTransposed, Npp32s *pRightTransposed, Npp32s *pTop, Npp32s *pBottom, int nStep, int nTransposedStep, NppiSize size, Npp8u *pLabel, int nLabelStep, Npp8u *pBuffer)
Graphcut of a flow network (32bit signed integer edge capacities).

7.4.1 Function Documentation

7.4.1.1 NppStatus nppiAbsDiff_32f_C1R (const Npp32f *pSrc1, int nSrc1Step, const Npp32f *pSrc2, int nSrc2Step, Npp32f *pDst, int nDstStep, NppiSize oSizeROI)

32-bit floating point absolute difference.

Compute abs(sourcePixel1 - sourcePixel2).

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.2 NppStatus nppiAbsDiff_32s_C1R (const Npp32s *pSrc1, int nSrc1Step, const Npp32s *pSrc2, int nSrc2Step, Npp32s *pDst, int nDstStep, NppiSize oSizeROI)

32-bit absolute difference.

Compute abs(sourcePixel1 - sourcePixel2).

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.3 NppStatus nppiAbsDiff_8u_AC4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

4 channel 8-bit unsigned absolute difference, not affecting Alpha.

Compute abs(sourcePixel1 - sourcePixel2).

Parameters:

pSrc1 [Source-Image Pointer](#).

nSrc1Step [Source-Image Line Step](#).

pSrc2 [Source-Image Pointer](#).

nSrc2Step [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.4 NppStatus nppiAbsDiff_8u_C1R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

8-bit unsigned absolute difference.

Compute abs(sourcePixel1 - sourcePixel2).

Parameters:

pSrc1 [Source-Image Pointer](#).

nSrc1Step [Source-Image Line Step](#).

pSrc2 [Source-Image Pointer](#).

nSrc2Step [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.5 NppStatus nppiAbsDiff_8u_C4R (const Npp8u * *pSrc1*, int *nSrc1Step*, const Npp8u * *pSrc2*, int *nSrc2Step*, Npp8u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

4 channel 8-bit unsigned absolute difference.

Compute $\text{abs}(\text{sourcePixel1} - \text{sourcePixel2})$.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.6 NppStatus nppiAbsDiffC_32f_C1R (const Npp32f * *pSrc*, int *nSrcStep*, Npp32f * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, Npp32f *nValue*)

32-bit floating point image absolute difference from constant.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nValue Constant.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.7 NppStatus nppiAdd_32f_C1R (const Npp32f * *pSrc1*, int *nSrc1Step*, const Npp32f * *pSrc2*, int *nSrc2Step*, Npp32f * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

32-bit floating point image add.

Add the pixel values of corresponding pixels in the ROI and write them to the output image.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.8 NppStatus nppiAdd_32s_C1R (const Npp32s * *pSrc1*, int *nSrc1Step*, const Npp32s * *pSrc2*, int *nSrc2Step*, Npp32s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

32-bit image add.

Add the pixel values of corresponding pixels in the ROI and write them to the output image.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.9 NppStatus nppiAdd_8u_AC4RSfs (const Npp8u * *pSrc1*, int *nSrc1Step*, const Npp8u * *pSrc2*, int *nSrc2Step*, Npp8u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

4 channel 8-bit unsigned image add, not affecting Alpha.

Add the pixel values of corresponding pixels in the ROI and write them to the output image.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Result pixel values are scaled by $2^{-(nScaleFactor)}$ and then clamped to [0,255] range.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.10 NppStatus nppiAdd_8u_C1RSfs (const Npp8u * *pSrc1*, int *nSrc1Step*, const Npp8u * *pSrc2*, int *nSrc2Step*, Npp8u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

8-bit unsigned image add.

Add the pixel values of corresponding pixels in the ROI and write them to the output image.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Result pixel values are scaled by $2^{(-nScaleFactor)}$ and then clamped to [0,255] range.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.11 NppStatus nppiAdd_8u_C4RSfs (const Npp8u * *pSrc1*, int *nSrc1Step*, const Npp8u * *pSrc2*, int *nSrc2Step*, Npp8u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

4 channel 8-bit unsigned image add.

Add the pixel values of corresponding pixels in the ROI and write them to the output image.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Result pixel values are scaled by $2^{(-nScaleFactor)}$ and then clamped to [0,255] range.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.12 NppStatus nppiAddC_32f_C1R (const Npp32f * *pSrc*, int *nSrcStep*, Npp32f *nValue*, Npp32f * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

32-bit floating point image add constant.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nValue Constant.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.13 **NppStatus nppiAddC_32fc_C1R** (const Npp32fc * *pSrc*, int *nSrcStep*, Npp32fc *nValue*, Npp32fc * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

32-bit complex floating point image add constant.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nValue Constant.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.14 **NppStatus nppiColorTwist32f_8u_AC4R** (const Npp8u * *pSrc*, int *nSrcStep*, Npp8u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, const Npp32f *twist*[3][4])

4 channel 8-bit unsigned color twist, not affecting Alpha.

An input color twist matrix with floating-point pixel values is applied with in ROI. Alpha channel is the last channel and is not processed.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
twist The color twist matrix with floating-point pixel values.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.15 `NppStatus nppiColorTwist32f_8u_C3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp32f twist[3][4])`

3 channel 8-bit unsigned color twist.

An input color twist matrix with floating-point pixel values is applied within ROI.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

twist The color twist matrix with floating-point pixel values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.16 `NppStatus nppiColorTwist32f_8u_P3R (const Npp8u *const * pSrc, int nSrcStep, Npp8u ** pDst, int nDstStep, NppiSize oSizeROI, const Npp32f twist[3][4])`

3 channel planar 8-bit unsigned color twist.

An input color twist matrix with floating-point pixel values is applied within ROI.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

twist The color twist matrix with floating-point pixel values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.17 `NppStatus nppiCompare_32f_C1R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppCmpOp eComparisonOperation)`

32-bit floating point image compare.

Compare pSrc1's pixels with corresponding pixels in pSrc2.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eComparisonOperation Specifies the comparison operation to be used in the pixel comparison.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.18 NppStatus nppiCompare_8u_AC4R (const Npp8u *pSrc1, int nSrc1Step, const Npp8u *pSrc2, int nSrc2Step, Npp8u *pDst, int nDstStep, NppiSize oSizeROI, NppCmpOp eComparisonOperation)

4 channel 8-bit unsigned image compare, not affecting Alpha.

Compare pSrc1's pixels with corresponding pixels in pSrc2.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eComparisonOperation Specifies the comparison operation to be used in the pixel comparison.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.19 NppStatus nppiCompare_8u_C4R (const Npp8u *pSrc1, int nSrc1Step, const Npp8u *pSrc2, int nSrc2Step, Npp8u *pDst, int nDstStep, NppiSize oSizeROI, NppCmpOp eComparisonOperation)

4 channel 8-bit unsigned image compare.

Compare pSrc1's pixels with corresponding pixels in pSrc2.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eComparisonOperation Specifies the comparison operation to be used in the pixel comparison.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.20 NppStatus nppiConvert_16s32f_C1R (const Npp16s * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

16-bit singedto 32-bit floating point conversion.

For detailed documentation see [nppiConverte_8u16u_C1R\(\)](#).

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.21 NppStatus nppiConvert_16s32s_C1R (const Npp16s * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

16-bit to 32-bit conversion.

For detailed documentation see [nppiConvert_8u16u_C1R\(\)](#).

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.22 **NppStatus nppiConvert_16s8u_AC4R** (const Npp16s * *pSrc*, int *nSrcStep*, Npp8u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

4 channel 16-bit signed to 8-bit unsigned conversion, not affecting Alpha.

For detailed documentation see [nppiConvert_8u16u_C1R\(\)](#).

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.23 **NppStatus nppiConvert_16s8u_C1R** (const Npp16s * *pSrc*, int *nSrcStep*, Npp8u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

4 channel 16-bit signed to 8-bit unsigned conversion.

For detailed documentation see [nppiConvert_8u16u_C1R\(\)](#).

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.24 **NppStatus nppiConvert_16s8u_C4R** (const Npp16s * *pSrc*, int *nSrcStep*, Npp8u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

4 channel 16-bit signed to 8-bit unsigned conversion, not affecting Alpha.

For detailed documentation see [nppiConvert_8u16u_C1R\(\)](#).

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

oSizeROI [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.25 NppStatus nppiConvert_16u32f_C1R (const Npp16u * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

16-bit unsigned to 32-bit floating point conversion.

For detailed documentation see [nppiConverte_8u16u_C1R\(\)](#).

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.26 NppStatus nppiConvert_16u32s_C1R (const Npp16u * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

16-bit unsigned to 32-bit signed conversion.

For detailed documentation see [nppiConverte_8u16u_C1R\(\)](#).

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.27 NppStatus nppiConvert_16u8u_AC4R (const Npp16u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

4 channel 16-bit unsigned to 8-bit unsigned conversion, not affecting Alpha.

For detailed documentation see [nppiConvert_8u16u_C1R\(\)](#).

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.28 NppStatus nppiConvert_16u8u_C1R (const Npp16u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

16-bit unsigned to 8-bit unsigned conversion.

For detailed documentation see [nppiConvert_8u16u_C1R\(\)](#).

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.29 NppStatus nppiConvert_16u8u_C4R (const Npp16u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

4 channel 16-bit unsigned to 8-bit unsigned conversion.

For detailed documentation see [nppiConvert_8u16u_C1R\(\)](#).

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.30 NppStatus nppiConvert_32f16s_C1R (const Npp32f * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode eRoundMode)

32-bit floating point to 16-bit conversion.

For detailed documentation see nppiConverte_8u16u_C1R().

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eRoundMode Flag specifying how fractional float values are rounded to integer values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.31 NppStatus nppiConvert_32f16u_C1R (const Npp32f * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode eRoundMode)

32-bit floating point to 16-bit unsigned conversion.

For detailed documentation see nppiConverte_8u16u_C1R().

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eRoundMode Flag specifying how fractional float values are rounded to integer values.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.32 NppStatus nppiConvert_32f8u_C1R (const Npp32f * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode eRoundMode)

32-bit floating point to 8-bit unsigned conversion.

For detailed documentation see nppiConverte_8u16u_C1R().

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

eRoundMode Flag specifying how fractional float values are rounded to integer values.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.33 NppStatus nppiConvert_8u16s_AC4R (const Npp8u * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI)

4 channel 8-bit unsigned to 16-bit signed conversion, not affecting Alpha.

For detailed documentation see [nppiConverte_8u16u_C1R\(\)](#).

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.34 NppStatus nppiConvert_8u16s_C1R (const Npp8u * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI)

8-bit unsigned to 16-bit signed conversion.

For detailed documentation see [nppiConvert_8u16u_C1R\(\)](#).

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.35 NppStatus nppiConvert_8u16s_C4R (const Npp8u * *pSrc*, int *nSrcStep*, Npp16s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

4 channel 8-bit unsigned to 16-bit signed conversion.

For detailed documentation see [nppiConvert_8u16u_C1R\(\)](#).

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.36 NppStatus nppiConvert_8u16u_AC4R (const Npp8u * *pSrc*, int *nSrcStep*, Npp16u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

4 channel 8-bit unsigned to 16-bit unsigned conversion, not affecting Alpha.

For detailed documentation see [nppiConvert_8u16u_C1R\(\)](#).

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.37 NppStatus nppiConvert_8u16u_C1R (const Npp8u * *pSrc*, int *nSrcStep*, Npp16u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

8-bit unsigned to 16-bit unsigned conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.38 NppStatus nppiConvert_8u16u_C4R (const Npp8u * *pSrc*, int *nSrcStep*, Npp16u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

4 channel 8-bit unsigned to 16-bit unsigned conversion.

For detailed documentation see [nppiConvert_8u16u_C1R\(\)](#).

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.39 NppStatus nppiConvert_8u32f_C1R (const Npp8u * *pSrc*, int *nSrcStep*, Npp32f * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

8-bit unsigned to 32-bit floating point conversion.

For detailed documentation see [nppiConvert_8u16u_C1R\(\)](#).

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.40 NppStatus nppiCopy_16s_AC4R (const Npp16s * *pSrc*, int *nSrcStep*, Npp16s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

4 channel 16-bit image copy, not affecting Alpha.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.41 NppStatus nppiCopy_16s_C1R (const Npp16s * *pSrc*, int *nSrcStep*, Npp16s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

16-bit image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.42 NppStatus nppiCopy_16s_C4R (const Npp16s * *pSrc*, int *nSrcStep*, Npp16s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

4 channel 16-bit image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.43 NppStatus nppiCopy_16u_AC4R (const Npp16u * *pSrc*, int *nSrcStep*, Npp16u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

4 channel 16-bit unsigned image copy, not affecting Alpha channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.44 NppStatus nppiCopy_16u_C1R (const Npp16u * *pSrc*, int *nSrcStep*, Npp16u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

16-bit unsigned image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.45 NppStatus nppiCopy_16u_C4R (const Npp16u * *pSrc*, int *nSrcStep*, Npp16u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

4 channel 16-bit unsigned image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.46 NppStatus nppiCopy_32f_AC4R (const Npp32f * *pSrc*, int *nSrcStep*, Npp32f * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

4 channel 32-bit floating point image copy, not affecting Alpha.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.47 NppStatus nppiCopy_32f_C1R (const Npp32f * *pSrc*, int *nSrcStep*, Npp32f * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

32-bit floating point image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.48 NppStatus nppiCopy_32f_C4R (const Npp32f * *pSrc*, int *nSrcStep*, Npp32f * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

4 channel 32-bit floating point image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.49 NppStatus nppiCopy_32s_AC4R (const Npp32s * *pSrc*, int *nSrcStep*, Npp32s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

4 channel 32-bit image copy, not affecting Alpha.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.50 NppStatus nppiCopy_32s_C1R (const Npp32s * *pSrc*, int *nSrcStep*, Npp32s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

32-bit image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.51 NppStatus nppiCopy_32s_C4R (const Npp32s * *pSrc*, int *nSrcStep*, Npp32s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

4 channel 32-bit image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.52 NppStatus nppiCopy_8u_AC4R (const Npp8u * *pSrc*, int *nSrcStep*, Npp8u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

4 channel 8-bit unsigned image copy, not affecting Alpha channel.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.53 NppStatus nppiCopy_8u_C1R (const Npp8u * *pSrc*, int *nSrcStep*, Npp8u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

8-bit unsigned image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.54 NppStatus nppiCopy_8u_C4R (const Npp8u * *pSrc*, int *nSrcStep*, Npp8u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

4 channel 8-bit unsigned image copy.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.55 NppStatus nppiCopyConstBorder_32s_C1R (const Npp32s * *pSrc*, int *nSrcStep*, NppiSize *oSrcSizeROI*, Npp32s * *pDst*, int *nDstStep*, NppiSize *oDstSizeROI*, int *nTopBorderHeight*, int *nLeftBorderWidth*, Npp32s *nValue*)

32-bit image copy with constant border color.

See [nppiCopyConstBorder_8u_C1R\(\)](#) for detailed documentation.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
oSrcSizeROI Size of the source region-of-interest.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

oDstSizeROI Size of the destination region-of-interest.

nTopBorderHeight Height of top border.

nLeftBorderWidth Width of left border.

nValue Border luminance value.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.56 `NppStatus nppiCopyConstBorder_8u_AC4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp8u * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth, const Npp8u aValue[3])`

4 channel 8-bit unsigned image copy with constant border color.

See [nppiCopyConstBorder_8u_C1R\(\)](#) for detailed documentation.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSizeROI Size of the source region-of-interest.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstSizeROI Size of the destination region-of-interest.

nTopBorderHeight Height of top border.

nLeftBorderWidth Width of left border.

aValue Vector of the RGB values of the border pixels. Because this method does not affect the destination image's alpha channel, only three components of the border color are needed.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.57 `NppStatus nppiCopyConstBorder_8u_C1R (const Npp8u * pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp8u * pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth, Npp8u nValue)`

8-bit unsigned image copy width constant border color.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSizeROI Size of the source region of pixels.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstSizeROI Size (width, height) of the destination region, i.e. the region that gets filled with data from the source image (inner part) and constant border color (outer part).

nTopBorderHeight Height (in pixels) of the top border. The height of the border at the bottom of the destination ROI is implicitly defined by the size of the source ROI: $nBottomBorderHeight = oDstSizeROI.height - nTopBorderHeight - oSrcSizeROI.height$.

nLeftBorderWidth Width (in pixels) of the left border. The width of the border at the right side of the destination ROI is implicitly defined by the size of the source ROI: $nRightBorderWidth = oDstSizeROI.width - nLeftBorderWidth - oSrcSizeROI.width$.

nValue The pixel value to be set for border pixels.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.58 NppStatus nppiCopyConstBorder_8u_C4R (const Npp8u *pSrc, int nSrcStep, NppiSize oSrcSizeROI, Npp8u *pDst, int nDstStep, NppiSize oDstSizeROI, int nTopBorderHeight, int nLeftBorderWidth, const Npp8u aValue[4])

4channel 8-bit unsigned image copy with constant border color.

See [nppiCopyConstBorder_8u_C1R\(\)](#) for detailed documentation.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSrcSizeROI Size of the source region-of-interest.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oDstSizeROI Size of the destination region-of-interest.

nTopBorderHeight Height of top border.

nLeftBorderWidth Width of left border.

aValue Vector of the RGBA values of the border pixels to be set.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.59 NppStatus nppiDCTQuantFwd8x8LS_JPEG_8u16s_C1R (Npp8u *pSrc, int nSrcStep, Npp16s *pDst, int nDstStep, const Npp16u *pQuantFwdTable, NppiSize oSizeROI)

Forward DCT, quantization and level shift part of the JPEG encoding.

Input is expected in 8x8 macro blocks and output is expected to be in 64x1 macro blocks.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

pQuantFwdTable Forward quantization tables for JPEG encoding.

oSizeROI Region-of-Interest (ROI).

Returns:

Error codes:

- **NPP_SIZE_ERROR** For negative input height/width or not a multiple of 8 width/height.
- **NPP_STEP_ERROR** If input image width is not multiple of 8 or does not match ROI.
- **NPP_NULL_POINTER_ERROR** If the destination pointer is NULL.

7.4.1.60 `NppStatus nppiDCTQuantInv8x8LS_JPEG_16s8u_C1R(Npp16s * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, const Npp16u * pQuantInvTable, NppiSize oSizeROI)`

Inverse DCT, de-quantization and level shift part of the JPEG decoding.

Input is expected in 64x1 macro blocks and output is expected to be in 8x8 macro blocks.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

pQuantInvTable Inverse quantization tables for JPEG decoding.

oSizeROI Region-of-Interest (ROI).

Returns:

Error codes:

- **NPP_SIZE_ERROR** For negative input height/width or not a multiple of 8 width/height.
- **NPP_STEP_ERROR** If input image width is not multiple of 8 or does not match ROI.
- **NPP_NULL_POINTER_ERROR** If the destination pointer is NULL.

7.4.1.61 `NppStatus nppiDilate_8u_C1R(const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI, const Npp8u * pMask, NppiSize oMaskSize, NppiPoint oAnchor)`

8-bit unsigned image dilation.

Dilation computes the output pixel as the maximum pixel value of the pixels under the mask. Pixels whose corresponding mask values are zero do not participate in the maximum search.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI [Region-of-Interest \(ROI\)](#).

pMask Pointer to the start address of the mask array

oMaskSize Width and Height mask array.

oAnchor X and Y offsets of the mask origin frame of reference w.r.t the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.62 `NppStatus nppiDilate_8u_C4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, NppiSize oMaskSize, NppiPoint oAnchor)`

4 channel 8-bit unsigned image dilation.

Dilation computes the output pixel as the maximum pixel value of the pixels under the mask. Pixels whose corresponding mask values are zero do not participate in the maximum search.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pMask Pointer to the start address of the mask array

oMaskSize Width and Height mask array.

oAnchor X and Y offsets of the mask origin frame of reference w.r.t the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.63 `NppStatus nppiDiv_32f_C1R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

32-bit floating point image division.

Divide pixels in pSrc2 by pSrc1's pixels.

Parameters:

pSrc1 [Source-Image Pointer](#).

nSrc1Step [Source-Image Line Step](#).

pSrc2 [Source-Image Pointer](#).

nSrc2Step [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.64 **NppStatus nppiDiv_32s_C1R** (const Npp32s * *pSrc1*, int *nSrc1Step*, const Npp32s * *pSrc2*, int *nSrc2Step*, Npp32s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

32-bit image division.

Divide pixels in *pSrc2* by *pSrc1*'s pixels.

Parameters:

pSrc1 [Source-Image Pointer](#).
nSrc1Step [Source-Image Line Step](#).
pSrc2 [Source-Image Pointer](#).
nSrc2Step [Source-Image Line Step](#).
pDst [Destination-Image Pointer](#).
nDstStep [Destination-Image Line Step](#).
oSizeROI [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.65 **NppStatus nppiDiv_8u_AC4RSfs** (const Npp8u * *pSrc1*, int *nSrc1Step*, const Npp8u * *pSrc2*, int *nSrc2Step*, Npp8u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

4 channel 8-bit unsigned image division, not affecting Alpha.

Divide pixels in *pSrc2* by *pSrc1*'s pixels.

Parameters:

pSrc1 [Source-Image Pointer](#).
nSrc1Step [Source-Image Line Step](#).
pSrc2 [Source-Image Pointer](#).
nSrc2Step [Source-Image Line Step](#).
pDst [Destination-Image Pointer](#).
nDstStep [Destination-Image Line Step](#).
oSizeROI [Region-of-Interest \(ROI\)](#).
nScaleFactor Result pixel values are scaled by $2^{(-nScaleFactor)}$ and then clamped to [0,255] range.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.66 **NppStatus nppiDiv_8u_C1RSfs** (const Npp8u * *pSrc1*, int *nSrc1Step*, const Npp8u * *pSrc2*, int *nSrc2Step*, Npp8u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

8-bit unsigned image division.

Divided pixels in *pSrc2* by *pSrc1*'s pixels.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Result pixel values are scaled by $2^{(-nScaleFactor)}$ and then clamped to [0,255] range.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.67 `NppStatus nppiDiv_8u_C4RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

4 channel 8-bit unsigned image division.

Divide pixels in pSrc2 by pSrc1's pixels.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Result pixel values are scaled by $2^{(-nScaleFactor)}$ and then clamped to [0,255] range.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.68 `NppStatus nppiDivC_32f_C1R (const Npp32f * pSrc, int nSrcStep, Npp32f nValue, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

32-bit floating point image divide by constant.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
nValue Constant.
pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.69 `NppStatus nppiDivC_32fc_C1R (const Npp32fc * pSrc, int nSrcStep, Npp32fc nValue, Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)`

32-bit complex floating point image divide by constant.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nValue Constant.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.70 `NppStatus nppiErode_8u_C1R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI, const Npp8u * pMask, NppiSize oMaskSize, NppiPoint oAnchor)`

8-bit unsigned image erosion.

Erosion computes the output pixel as the minimum pixel value of the pixels under the mask. Pixels whose corresponding mask values are zero do not participate in the maximum search.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pMask Pointer to the start address of the mask array

oMaskSize Width and Height mask array.

oAnchor X and Y offsets of the mask origin frame of reference w.r.t the source pixel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.71 NppStatus nppiErode_8u_C4R (const Npp8u * *pSrc*, Npp32s *nSrcStep*, Npp8u * *pDst*, Npp32s *nDstStep*, NppiSize *oSizeROI*, const Npp8u * *pMask*, NppiSize *oMaskSize*, NppiPoint *oAnchor*)

4 channel 8-bit unsigned image erosion.

Erosion computes the output pixel as the minimum pixel value of the pixels under the mask. Pixels whose corresponding mask values are zero do not participate in the maximum search.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pMask Pointer to the start address of the mask array

oMaskSize Width and Height mask array.

oAnchor X and Y offsets of the mask origin frame of reference w.r.t the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.72 NppStatus nppiEvenLevelsHost_32s (Npp32s * *hpLevels*, int *nLevels*, Npp32s *nLowerLevel*, Npp32s *nUpperLevel*)

Compute levels with even distribution.

Parameters:

hpLevels A host pointer to array which receives the levels being computed. The array needs to be of size *nLevels*.

nLevels The number of levels being computed. *nLevels* must be at least 2, otherwise an NPP_HISTO_NUMBER_OF_LEVELS_ERROR error is returned.

nLowerLevel Lower boundary value of the lowest level.

nUpperLevel Upper boundary value of the greatest level.

Returns:

Error code.

7.4.1.73 NppStatus nppiExp_32f_C1R (const Npp32f * *pSrc*, int *nSrcStep*, Npp32f * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

32-bit floating point exponentiation.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.74 `NppStatus nppiFilter_8u_C1R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI, const Npp32s * pKernel, NppiSize oKernelSize, NppiPoint oAnchor, Npp32s nDivisor)`

8-bit unsigned convolution filter.

Pixels under the mask are multiplied by the respective weights in the mask and the results are summed. Before writing the result pixel the sum is scaled back via division by nDivisor.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.
oKernelSize Width and Height of the rectangular kernel.
oAnchor X and Y offsets of the kernel origin frame of reference w.r.t the source pixel.
nDivisor The factor by which the convolved summation from the Filter operation should be divided. If equal to the sum of coefficients, this will keep the maximum result value within full scale.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.75 `NppStatus nppiFilter_8u_C4R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI, const Npp32s * pKernel, NppiSize oKernelSize, NppiPoint oAnchor, Npp32s nDivisor)`

4 channel 8-bit unsigned convolution filter.

Pixels under the mask are multiplied by the respective weights in the mask and the results are summed. Before writing the result pixel the sum is scaled back via division by nDivisor.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

oKernelSize Width and Height of the rectangular kernel.

oAnchor X and Y offsets of the kernel origin frame of reference w.r.t the source pixel.

nDivisor The factor by which the convolved summation from the Filter operation should be divided. If equal to the sum of coefficients, this will keep the maximum result value within full scale.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.76 `NppStatus nppiFilterBox_8u_C1R (const Npp8u *pSrc, Npp32s nSrcStep, Npp8u *pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)`

8-bit unsigned box filter.

Computes the average pixel values of the pixels under a rectangular mask.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Avg operation.

oAnchor X and Y offsets of the kernel origin frame of reference w.r.t the source pixel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.77 `NppStatus nppiFilterBox_8u_C4R (const Npp8u *pSrc, Npp32s nSrcStep, Npp8u *pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)`

4 channel 8-bit unsigned box filter.

Computes the average pixel values of the pixels under a rectangular mask.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI [Region-of-Interest \(ROI\)](#).

oMaskSize Width and Height of the neighborhood region for the local Avg operation.

oAnchor X and Y offsets of the kernel origin frame of reference w.r.t the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.78 `NppStatus nppiFilterColumn_8u_C1R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oROI, const Npp32s * pKernel, Npp32s nMaskSize, Npp32s nAnchor, Npp32s nDivisor)`

8-bit unsigned 1D (column) image convolution.

Apply convolution filter with user specified 1D column of weights. Result pixel is equal to the sum of the products between the kernel coefficients (pKernel array) and corresponding neighboring column pixel values in the source image defined by nKernelDim and nAnchorY, divided by nDivisor.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oROI [Region-of-Interest \(ROI\)](#).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor Y offset of the kernel origin frame of reference w.r.t the source pixel.

nDivisor The factor by which the convolved summation from the Filter operation should be divided. If equal to the sum of coefficients, this will keep the maximum result value within full scale.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.79 `NppStatus nppiFilterColumn_8u_C4R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oROI, const Npp32s * pKernel, Npp32s nMaskSize, Npp32s nAnchor, Npp32s nDivisor)`

4 channel 8-bit unsigned 1D (column) image convolution.

Apply convolution filter with user specified 1D column of weights. Result pixel is equal to the sum of the products between the kernel coefficients (pKernel array) and corresponding neighboring column pixel values in the source image defined by nKernelDim and nAnchorY, divided by nDivisor.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor Y offset of the kernel origin frame of reference w.r.t the source pixel.

nDivisor The factor by which the convolved summation from the Filter operation should be divided. If equal to the sum of coefficients, this will keep the maximum result value within full scale.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.80 NppStatus nppiFilterMax_8u_C1R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)

8-bit unsigned maximum filter.

Result pixel value is the maximum of pixel values under the rectangular mask region.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

oMaskSize Width and Height of the neighborhood region for the local Max operation.

oAnchor X and Y offsets of the kernel origin frame of reference w.r.t the source pixel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.81 NppStatus nppiFilterMax_8u_C4R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)

4 channel 8-bit unsigned maximum filter.

Result pixel value is the maximum of pixel values under the rectangular mask region.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI [Region-of-Interest \(ROI\)](#).

oMaskSize Width and Height of the neighborhood region for the local Max operation.

oAnchor X and Y offsets of the kernel origin frame of reference w.r.t the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.82 NppStatus nppiFilterMin_8u_C1R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)

8-bit unsigned minimum filter.

Result pixel value is the minimum of pixel values under the rectangular mask region.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

oMaskSize Width and Height of the neighborhood region for the local Max operation.

oAnchor X and Y offsets of the kernel origin frame of reference w.r.t the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.83 NppStatus nppiFilterMin_8u_C4R (const Npp8u * pSrc, Npp32s nSrcStep, Npp8u * pDst, Npp32s nDstStep, NppiSize oSizeROI, NppiSize oMaskSize, NppiPoint oAnchor)

4 channel 8-bit unsigned minimum filter.

Result pixel value is the minimum of pixel values under the rectangular mask region.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

oMaskSize Width and Height of the neighborhood region for the local Max operation.

oAnchor X and Y offsets of the kernel origin frame of reference w.r.t the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.84 **NppStatus nppiFilterRow_8u_C1R** (const Npp8u * *pSrc*, Npp32s *nSrcStep*, Npp8u * *pDst*, Npp32s *nDstStep*, NppiSize *oROI*, const Npp32s * *pKernel*, Npp32s *nMaskSize*, Npp32s *nAnchor*, Npp32s *nDivisor*)

8-bit unsigned 1D (row) image convolution.

Apply general linear Row convolution filter, with rescaling, in a 1D mask region around each source pixel for 1-channel 8 bit/pixel images. Result pixel is equal to the sum of the products between the kernel coefficients (*pKernel* array) and corresponding neighboring row pixel values in the source image defined by *iKernelDim* and *iAnchorX*, divided by *iDivisor*.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oROI [Region-of-Interest \(ROI\)](#).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor X offset of the kernel origin frame of reference w.r.t the source pixel.

nDivisor The factor by which the convolved summation from the Filter operation should be divided. If equal to the sum of coefficients, this will keep the maximum result value within full scale.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.85 **NppStatus nppiFilterRow_8u_C4R** (const Npp8u * *pSrc*, Npp32s *nSrcStep*, Npp8u * *pDst*, Npp32s *nDstStep*, NppiSize *oROI*, const Npp32s * *pKernel*, Npp32s *nMaskSize*, Npp32s *nAnchor*, Npp32s *nDivisor*)

4 channel 8-bit unsigned 1D (row) image convolution.

Apply general linear Row convolution filter, with rescaling, in a 1D mask region around each source pixel for 1-channel 8 bit/pixel images. Result pixel is equal to the sum of the products between the kernel coefficients (*pKernel* array) and corresponding neighboring row pixel values in the source image defined by *iKernelDim* and *iAnchorX*, divided by *iDivisor*.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oROI [Region-of-Interest \(ROI\)](#).

pKernel Pointer to the start address of the kernel coefficient array. Coefficients are expected to be stored in reverse order.

nMaskSize Length of the linear kernel array.

nAnchor X offset of the kernel origin frame of reference w.r.t the source pixel.

nDivisor The factor by which the convolved summation from the Filter operation should be divided. If equal to the sum of coefficients, this will keep the maximum result value within full scale.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.86 void nppiFree (void * *pData*)

Free method for any 2D allocated memory.

This method should be used to free memory allocated with any of the nppiMalloc_<modifier> methods.

Parameters:

pData A pointer to memory allocated using nppiMalloc_<modifier>.

7.4.1.87 NppStatus nppiGetAffineBound (NppiRect *srcRoi*, double *bound*[2][2], const double *coeffs*[2][3])

Calculates bounding box of the affine transform projection of the given source rectangular ROI.

Parameters:

srcRoi Source ROI

bound Bounding box of the transformed source ROI

coeffs Affine transform coefficients

Returns:

Error codes:

- [NPP_SIZE_ERROR](#) Indicates an error condition if any image dimension has zero or negative value
- [NPP_RECT_ERROR](#) Indicates an error condition if width or height of the intersection of the *srcRoi* and source image is less than or equal to 1
- [NPP_COEFF_ERROR](#) Indicates an error condition if coefficient values are invalid

7.4.1.88 NppStatus nppiGetAffineQuad (NppiRect *srcRoi*, double *quad*[4][2], const double *coeffs*[2][3])

Calculates affine transform projection of given source rectangular ROI.

Parameters:

srcRoi Source ROI

quad Destination quadrangle

coeffs Affine transform coefficients

Returns:

Error codes:

- [NPP_SIZE_ERROR](#) Indicates an error condition if any image dimension has zero or negative value
- [NPP_RECT_ERROR](#) Indicates an error condition if width or height of the intersection of the *srcRoi* and source image is less than or equal to 1
- [NPP_COEFF_ERROR](#) Indicates an error condition if coefficient values are invalid

7.4.1.89 NppStatus nppiGetAffineTransform (NppiRect *srcRoi*, const double *quad*[4][2], double *coeffs*[2][3])

Calculates affine transform coefficients given source rectangular ROI and its destination quadrangle projection.

Parameters:

srcRoi Source ROI

quad Destination quadrangle

coeffs Affine transform coefficients

Returns:

Error codes:

- [NPP_SIZE_ERROR](#) Indicates an error condition if any image dimension has zero or negative value
- [NPP_RECT_ERROR](#) Indicates an error condition if width or height of the intersection of the *srcRoi* and source image is less than or equal to 1
- [NPP_COEFF_ERROR](#) Indicates an error condition if coefficient values are invalid
- [NPP_AFFINE_QUAD_INCORRECT_WARNING](#) Indicates a warning when *quad* does not conform to the transform properties. Fourth vertex is ignored, internally computed coordinates are used instead

7.4.1.90 NppStatus nppiGetPerspectiveBound (NppiRect *srcRoi*, double *bound*[2][2], const double *coeffs*[3][3])

Calculates bounding box of the perspective transform projection of the given source rectangular ROI.

Parameters:

srcRoi Source ROI

bound Bounding box of the transformed source ROI

coeffs Perspective transform coefficients

Returns:

Error codes:

- [NPP_SIZE_ERROR](#) Indicates an error condition if any image dimension has zero or negative value
- [NPP_RECT_ERROR](#) Indicates an error condition if width or height of the intersection of the *srcRoi* and source image is less than or equal to 1
- [NPP_COEFF_ERROR](#) Indicates an error condition if coefficient values are invalid

7.4.1.91 **NppStatus nppiGetPerspectiveQuad** (NppiRect *srcRoi*, double *quad*[4][2], const double *coeffs*[3][3])

Calculates perspective transform projection of given source rectangular ROI.

Parameters:

srcRoi Source ROI
quad Destination quadrangle
coeffs Perspective transform coefficients

Returns:

Error codes:

- [NPP_SIZE_ERROR](#) Indicates an error condition if any image dimension has zero or negative value
- [NPP_RECT_ERROR](#) Indicates an error condition if width or height of the intersection of the *srcRoi* and source image is less than or equal to 1
- [NPP_COEFF_ERROR](#) Indicates an error condition if coefficient values are invalid

7.4.1.92 **NppStatus nppiGetPerspectiveTransform** (NppiRect *srcRoi*, const double *quad*[4][2], double *coeffs*[3][3])

Calculates perspective transform coefficients given source rectangular ROI and its destination quadrangle projection.

Parameters:

srcRoi Source ROI
quad Destination quadrangle
coeffs Perspective transform coefficients

Returns:

Error codes:

- [NPP_SIZE_ERROR](#) Indicates an error condition if any image dimension has zero or negative value
- [NPP_RECT_ERROR](#) Indicates an error condition if width or height of the intersection of the *srcRoi* and source image is less than or equal to 1
- [NPP_COEFF_ERROR](#) Indicates an error condition if coefficient values are invalid

7.4.1.93 **NppStatus nppiGraphcut_32s8u** (Npp32s * *pTerminals*, Npp32s * *pLeftTransposed*, Npp32s * *pRightTransposed*, Npp32s * *pTop*, Npp32s * *pBottom*, int *nStep*, int *nTransposedStep*, NppiSize *size*, Npp8u * *pLabel*, int *nLabelStep*, Npp8u * *pBuffer*)

Graphcut of a flow network (32bit signed integer edge capacities).

The function computes the minimal cut (graphcut) of a 2D regular 4-connected graph. The inputs are the capacities of the horizontal (in transposed form), vertical and terminal (source and sink) edges. The capacities to source and sink are stored as capacity differences in the terminals array (*terminals*(x) =

source(x) - sink(x)). The implementation assumes that the edge capacities for boundary edges that would connect to nodes outside the specified domain are set to 0 (for example left(0,*) == 0). If this is not fulfilled the computed labeling may be wrong! The computed binary labeling is encoded as unsigned 8bit values (0 / 255).

See also:

[nppiGraphcutGetSize](#)

Parameters:

pTerminals Pointer to differences of terminal edge capacities (terminal(x) = source(x) - sink(x))

pLeftTransposed Pointer to transposed left edge capacities (left(0,*) must be 0)

pRightTransposed Pointer to transposed right edge capacities (right(width-1,*) must be 0)

pTop Pointer to top edge capacities (top(*,0) must be 0)

pBottom Pointer to bottom edge capacities (bottom(*,height-1) must be 0)

nStep Step in bytes between any pair of sequential rows of edge capacities

nTransposedStep Step in bytes between any pair of sequential rows of transposed edge capacities

size Graph size

pLabel Pointer to destination label image

nLabelStep Step in bytes between any pair of sequential rows of label image

pBuffer Pointer to the temporary buffer

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.94 NppStatus nppiGraphcutGetSize (NppiSize size, int * pBufSize)

Calculates the size of the temporary buffer for graph-cut labeling.

See also:

[nppiGraphcut_32s8u](#)

Parameters:

size Graph size

pBufSize Pointer to variable that returns the size of the temporary buffer.

Returns:

NPP_SUCCESS Indicates no error. Any other value indicates an error or a warning

NPP_SIZE_ERROR Indicates an error condition if any image dimension has zero or negative value

NPP_NULL_POINTER_ERROR Indicates an error condition if pBufSize pointer is NULL

7.4.1.95 `NppStatus nppiHistogramEven_16s_AC4R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp32s * pHist[3], int nLevels[3], Npp32s nLowerLevel[3], Npp32s nUpperLevel[3], Npp8u * pBuffer)`

4 channel (alpha as the last channel) 16-bit signed histogram with evenly distributed bins.

Alpha channel is ignored during histogram computation.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pHist Array of pointers which are receiving computed histograms per color channel. Array pointed by pHist[i] be of size nLevels[i]-1.

nLevels Array containing number of levels per color channel.

nLowerLevel Array containing lower-level of lowest bin per color channel.

nUpperLevel Array containing upper-level of highest bin per color channel.

pBuffer Pointer to appropriately sized (nppiHistogramEvenGetBufferSize_16s_AC4R) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.96 `NppStatus nppiHistogramEven_16s_C1R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp32s * pHist, int nLevels, Npp32s nLowerLevel, Npp32s nUpperLevel, Npp8u * pBuffer)`

16-bit signed histogram with evenly distributed bins.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pHist Pointer to array that receives the computed histogram. The array must be of size nLevels-1.

nLevels Number of levels.

nLowerLevel Lower boundary of lowest level bin.

nUpperLevel Upper boundary of highest level bin.

pBuffer Pointer to appropriately sized (nppiHistogramEvenGetBufferSize_16s_C1R) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.97 `NppStatus nppiHistogramEven_16s_C4R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp32s * pHist[4], int nLevels[4], Npp32s nLowerLevel[4], Npp32s nUpperLevel[4], Npp8u * pBuffer)`

4 channel 16-bit signed histogram with evenly distributed bins.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pHist Array of pointers which are receiving computed histograms per color channel. Array pointed by pHist[i] be of size nLevels[i]-1.

nLevels Array containing number of levels per color channel.

nLowerLevel Array containing lower-level of lowest bin per color channel.

nUpperLevel Array containing upper-level of highest bin per color channel.

pBuffer Pointer to appropriately sized (`nppiHistogramEvenGetBufferSize_16s_C4R`) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.98 `NppStatus nppiHistogramEven_16u_AC4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp32s * pHist[3], int nLevels[3], Npp32s nLowerLevel[3], Npp32s nUpperLevel[3], Npp8u * pBuffer)`

4 channel (alpha as the last channel) 16-bit unsigned histogram with evenly distributed bins.

Alpha channel is ignored during histogram computation.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pHist Array of pointers which are receiving computed histograms per color channel. Array pointed by pHist[i] be of size nLevels[i]-1.

nLevels Array containing number of levels per color channel.

nLowerLevel Array containing lower-level of lowest bin per color channel.

nUpperLevel Array containing upper-level of highest bin per color channel.

pBuffer Pointer to appropriately sized (`nppiHistogramEvenGetBufferSize_16u_AC4R`) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.99 NppStatus nppiHistogramEven_16u_C1R (const Npp16u * *pSrc*, int *nSrcStep*, NppiSize *oSizeROI*, Npp32s * *pHist*, int *nLevels*, Npp32s *nLowerLevel*, Npp32s *nUpperLevel*, Npp8u * *pBuffer*)

16-bit unsigned histogram with evenly distributed bins.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pHist Pointer to array that receives the computed histogram. The array must be of size *nLevels*-1.

nLevels Number of levels.

nLowerLevel Lower boundary of lowest level bin.

nUpperLevel Upper boundary of highest level bin.

pBuffer Pointer to appropriately sized (nppiHistogramEvenGetBufferSize_16u_C1R) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.100 NppStatus nppiHistogramEven_16u_C4R (const Npp16u * *pSrc*, int *nSrcStep*, NppiSize *oSizeROI*, Npp32s * *pHist*[4], int *nLevels*[4], Npp32s *nLowerLevel*[4], Npp32s *nUpperLevel*[4], Npp8u * *pBuffer*)

4 channel 16-bit unsigned histogram with evenly distributed bins.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pHist Array of pointers which are receiving computed histograms per color channel. Array pointed by *pHist*[*i*] be of size *nLevels*[*i*]-1.

nLevels Array containing number of levels per color channel.

nLowerLevel Array containing lower-level of lowest bin per color channel.

nUpperLevel Array containing upper-level of highest bin per color channel.

pBuffer Pointer to appropriately sized (nppiHistogramEvenGetBufferSize_16u_C4R) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.101 NppStatus nppiHistogramEven_8u_AC4R (const Npp8u * *pSrc*, int *nSrcStep*, NppiSize *oSizeROI*, Npp32s * *pHist*[3], int *nLevels*[3], Npp32s *nLowerLevel*[3], Npp32s *nUpperLevel*[3], Npp8u * *pBuffer*)

4 channel (alpha as the last channel) 8-bit unsigned histogram with evenly distributed bins.

Alpha channel is ignored during histogram computation.

Parameters:

pSrc [Source-Image Pointer](#).
nSrcStep [Source-Image Line Step](#).
oSizeROI [Region-of-Interest \(ROI\)](#).
pHist Array of pointers which are receiving computed histograms per color channel. Array pointed by *pHist[i]* be of size *nLevels[i]*-1.
nLevels Array containing number of levels per color channel.
nLowerLevel Array containing lower-level of lowest bin per color channel.
nUpperLevel Array containing upper-level of highest bin per color channel.
pBuffer Pointer to appropriately sized (`nppiHistogramEvenGetBufferSize_8u_AC4R`) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.102 `NppStatus nppiHistogramEven_8u_C1R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp32s * pHist, int nLevels, Npp32s nLowerLevel, Npp32s nUpperLevel, Npp8u * pBuffer)`

8-bit unsigned histogram with evenly distributed bins.

Parameters:

pSrc [Source-Image Pointer](#).
nSrcStep [Source-Image Line Step](#).
oSizeROI [Region-of-Interest \(ROI\)](#).
pHist Pointer to array that receives the computed histogram. The array must be of size *nLevels*-1.
nLevels Number of levels.
nLowerLevel Lower boundary of lowest level bin.
nUpperLevel Upper boundary of highest level bin.
pBuffer Pointer to appropriately sized (`nppiHistogramEvenGetBufferSize_8u_C1R`) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.103 `NppStatus nppiHistogramEven_8u_C4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp32s * pHist[4], int nLevels[4], Npp32s nLowerLevel[4], Npp32s nUpperLevel[4], Npp8u * pBuffer)`

4 channel 8-bit unsigned histogram with evenly distributed bins.

Parameters:

pSrc [Source-Image Pointer](#).
nSrcStep [Source-Image Line Step](#).
oSizeROI [Region-of-Interest \(ROI\)](#).

pHist Array of pointers which are receiving computed histograms per color channel. Array pointed by *pHist[i]* be of size *nLevels[i]-1*.

nLevels Array containing number of levels per color channel.

nLowerLevel Array containing lower-level of lowest bin per color channel.

nUpperLevel Array containing upper-level of highest bin per color channel.

pBuffer Pointer to appropriately sized (*npPiHistogramEvenGetBufferSize_8u_C4R*) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.104 NppStatus npPiHistogramEvenGetBufferSize_16s_AC4R (NppiSize *oSizeROI*, int *nLevels*[3], int * *hpBufferSize*)

Scratch-buffer size for *npPiHistogramEven_16s_AC4R*.

Parameters:

oSizeROI ROI size.

nLevels Array containing number of levels per color channel.

hpBufferSize Host pointer where required buffer size is returned.

Returns:

Error Code.

7.4.1.105 NppStatus npPiHistogramEvenGetBufferSize_16s_C1R (NppiSize *oSizeROI*, int *nLevels*, int * *hpBufferSize*)

Scratch-buffer size for *npPiHistogramEven_16s_C1R*.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

nLevels Number of levels in the histogram.

hpBufferSize Host pointer where required buffer size is returned.

Returns:

Error Code.

7.4.1.106 NppStatus npPiHistogramEvenGetBufferSize_16s_C4R (NppiSize *oSizeROI*, int *nLevels*[4], int * *hpBufferSize*)

Scratch-buffer size for *npPiHistogramEven_16s_C4R*.

Parameters:

oSizeROI ROI size.

nLevels Array containing number of levels per color channel.

hpBufferSize Host pointer where required buffer size is returned.

Returns:

Error Code.

7.4.1.107 NppStatus nppiHistogramEvenGetBufferSize_16u_AC4R (NppiSize *oSizeROI*, int *nLevels*[3], int * *hpBufferSize*)

Scratch-buffer size for nppiHistogramEven_16u_AC4R.

Parameters:

oSizeROI ROI size.

nLevels Array containing number of levels per color channel.

hpBufferSize Host pointer where required buffer size is returned.

Returns:

Error Code.

7.4.1.108 NppStatus nppiHistogramEvenGetBufferSize_16u_C1R (NppiSize *oSizeROI*, int *nLevels*, int * *hpBufferSize*)

Scratch-buffer size for nppiHistogramEven_16u_C1R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

nLevels Number of levels in the histogram.

hpBufferSize Host pointer where required buffer size is returned.

Returns:

Error Code.

7.4.1.109 NppStatus nppiHistogramEvenGetBufferSize_16u_C4R (NppiSize *oSizeROI*, int *nLevels*[4], int * *hpBufferSize*)

Scratch-buffer size for nppiHistogramEven_16u_C4R.

Parameters:

oSizeROI ROI size.

nLevels Array containing number of levels per color channel.

hpBufferSize Host pointer where required buffer size is returned.

Returns:

Error Code.

7.4.1.110 NppStatus nppiHistogramEvenGetBufferSize_8u_AC4R (NppiSize *oSizeROI*, int *nLevels*[3], int * *hpBufferSize*)

Scratch-buffer size for nppiHistogramEven_8u_AC4R.

Parameters:

oSizeROI ROI size.

nLevels Array containing number of levels per color channel.

hpBufferSize Host pointer where required buffer size is returned.

Returns:

Error Code.

7.4.1.111 NppStatus nppiHistogramEvenGetBufferSize_8u_C1R (NppiSize *oSizeROI*, int *nLevels*, int * *hpBufferSize*)

Scratch-buffer size for nppiHistogramEven_8u_C1R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

nLevels Number of levels in the histogram.

hpBufferSize Host pointer where required buffer size is returned.

Returns:

Error Code.

7.4.1.112 NppStatus nppiHistogramEvenGetBufferSize_8u_C4R (NppiSize *oSizeROI*, int *nLevels*[4], int * *hpBufferSize*)

Scratch-buffer size for nppiHistogramEven_8u_C4R.

Parameters:

oSizeROI ROI size.

nLevels Array containing number of levels per color channel.

hpBufferSize Host pointer where required buffer size is returned.

Returns:

Error Code.

7.4.1.113 NppStatus nppiHistogramRange_16s_AC4R (const Npp16s * *pSrc*, int *nSrcStep*, NppiSize *oSizeROI*, Npp32s * *pHist*[3], const Npp32s * *pLevels*[3], int *nLevels*[3], Npp8u * *pBuffer*)

4 channel (alpha as a last channel) 16-bit signed histogram with bins determined by *pLevels*.

Alpha channel is ignored during the histograms computations.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pHist Array of pointers which are receiving the computed histograms per color channel. Array pointed by pHist[i] must be of size nLevels[i]-1.

nLevels Array containing number of levels per color channel.

pLevels Array containing pointers to level-arrays per color channel. Array pointed by pLevel[i] must be of size nLevels[i].

pBuffer Pointer to appropriately sized (nppiHistogramRangeGetBufferSize_16_AC4R) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.114 `NppStatus nppiHistogramRange_16s_C1R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp32s * pHist, const Npp32s * pLevels, int nLevels, Npp8u * pBuffer)`

16-bit signed histogram with bins determined by pLevels array.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pHist Pointer to array that receives the computed histogram. The array must be of size nLevels-1.

pLevels Pointer to array containing the level sizes of the bins. The array must be of size nLevels.

nLevels Number of levels in histogram.

pBuffer Pointer to appropriately sized (nppiHistogramRangeGetBufferSize_16_C1R) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.115 `NppStatus nppiHistogramRange_16s_C4R (const Npp16s * pSrc, int nSrcStep, NppiSize oSizeROI, Npp32s * pHist[4], const Npp32s * pLevels[4], int nLevels[4], Npp8u * pBuffer)`

4 channel 16-bit signed histogram with bins determined by pLevels.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pHist Array of pointers which are receiving the computed histograms per color channel. Array pointed by *pHist[i]* must be of size *nLevels[i]*-1.

nLevels Array containing number of levels per color channel.

pLevels Array containing pointers to level-arrays per color channel. Array pointed by *pLevel[i]* must be of size *nLevels[i]*.

pBuffer Pointer to appropriately sized (`npPiHistogramRangeGetBufferSize_16s_C4R`) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.116 `NppStatus npPiHistogramRange_16u_AC4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp32s * pHist[3], const Npp32s * pLevels[3], int nLevels[3], Npp8u * pBuffer)`

4 channel (alpha as a last channel) 16-bit unsigned histogram with bins determined by *pLevels*.

Alpha channel is ignored during the histograms computations.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pHist Array of pointers which are receiving the computed histograms per color channel. Array pointed by *pHist[i]* must be of size *nLevels[i]*-1.

nLevels Array containing number of levels per color channel.

pLevels Array containing pointers to level-arrays per color channel. Array pointed by *pLevel[i]* must be of size *nLevels[i]*.

pBuffer Pointer to appropriately sized (`npPiHistogramRangeGetBufferSize_16u_AC4R`) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.117 `NppStatus npPiHistogramRange_16u_C1R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp32s * pHist, const Npp32s * pLevels, int nLevels, Npp8u * pBuffer)`

16-bit unsigned histogram with bins determined by *pLevels* array.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pHist Pointer to array that receives the computed histogram. The array must be of size *nLevels*-1.

pLevels Pointer to array containing the level sizes of the bins. The array must be of size *nLevels*.

nLevels Number of levels in histogram.

pBuffer Pointer to appropriately sized (nppiHistogramRangeGetBufferSize_16u_C1R) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.118 `NppStatus nppiHistogramRange_16u_C4R (const Npp16u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp32s * pHist[4], const Npp32s * pLevels[4], int nLevels[4], Npp8u * pBuffer)`

4 channel 16-bit unsigned histogram with bins determined by pLevels.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pHist Array of pointers which are receiving the computed histograms per color channel. Array pointed by pHist[i] must be of size nLevels[i]-1.

nLevels Array containing number of levels per color channel.

pLevels Array containing pointers to level-arrays per color channel. Array pointed by pLevel[i] must be of size nLevels[i].

pBuffer Pointer to appropriately sized (nppiHistogramRangeGetBufferSize_16u_C4R) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.119 `NppStatus nppiHistogramRange_32f_AC4R (const Npp32f * pSrc, int nSrcStep, NppiSize oSizeROI, Npp32s * pHist[3], const Npp32f * pLevels[3], int nLevels[3], Npp8u * pBuffer)`

4 channel (alpha as a last channel) 32-bit float histogram with bins determined by pLevels.

Alpha channel is ignored during the histograms computations.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pHist Array of pointers which are receiving the computed histograms per color channel. Array pointed by pHist[i] must be of size nLevels[i]-1.

nLevels Array containing number of levels per color channel.

pLevels Array containing pointers to level-arrays per color channel. Array pointed by pLevel[i] must be of size nLevels[i].

pBuffer Pointer to appropriately sized (nppiHistogramRangeGetBufferSize_32f_AC4R) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.120 **NppStatus nppiHistogramRange_32f_C1R** (const Npp32f * *pSrc*, int *nSrcStep*, NppiSize *oSizeROI*, Npp32s * *pHist*, const Npp32f * *pLevels*, int *nLevels*, Npp8u * *pBuffer*)

32-bit float histogram with bins determined by *pLevels* array.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pHist Pointer to array that receives the computed histogram. The array must be of size *nLevels*-1.

pLevels Pointer to array containing the level sizes of the bins. The array must be of size *nLevels*.

nLevels Number of levels in histogram.

pBuffer Pointer to appropriately sized (`nppiHistogramRangeGetBufferSize_32f_C1R`) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.121 **NppStatus nppiHistogramRange_32f_C4R** (const Npp32f * *pSrc*, int *nSrcStep*, NppiSize *oSizeROI*, Npp32s * *pHist*[4], const Npp32f * *pLevels*[4], int *nLevels*[4], Npp8u * *pBuffer*)

4 channel 32-bit float histogram with bins determined by *pLevels*.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pHist Array of pointers which are receiving the computed histograms per color channel. Array pointed by *pHist*[*i*] must be of size *nLevels*[*i*]-1.

nLevels Array containing number of levels per color channel.

pLevels Array containing pointers to level-arrays per color channel. Array pointed by *pLevel*[*i*] must be of size *nLevels*[*i*].

pBuffer Pointer to appropriately sized (`nppiHistogramRangeGetBufferSize_32f_C4R`) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.122 **NppStatus nppiHistogramRange_8u_AC4R** (const Npp8u * *pSrc*, int *nSrcStep*, NppiSize *oSizeROI*, Npp32s * *pHist*[3], const Npp32s * *pLevels*[3], int *nLevels*[3], Npp8u * *pBuffer*)

4 channel (alpha as a last channel) 8-bit unsigned histogram with bins determined by *pLevels*.

Alpha channel is ignored during the histograms computations.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pHist Array of pointers which are receiving the computed histograms per color channel. Array pointed by pHist[i] must be of size nLevels[i]-1.

nLevels Array containing number of levels per color channel.

pLevels Array containing pointers to level-arrays per color channel. Array pointed by pLevel[i] must be of size nLevels[i].

pBuffer Pointer to appropriately sized (nppiHistogramRangeGetBufferSize_8u_AC4R) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.123 `NppStatus nppiHistogramRange_8u_C1R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp32s * pHist, const Npp32s * pLevels, int nLevels, Npp8u * pBuffer)`

8-bit unsigned histogram with bins determined by pLevels array.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pHist Pointer to array that receives the computed histogram. The array must be of size nLevels-1.

pLevels Pointer to array containing the level sizes of the bins. The array must be of size nLevels.

nLevels Number of levels in histogram.

pBuffer Pointer to appropriately sized (nppiHistogramRangeGetBufferSize_8u_C1R) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.124 `NppStatus nppiHistogramRange_8u_C4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp32s * pHist[4], const Npp32s * pLevels[4], int nLevels[4], Npp8u * pBuffer)`

4 channel 8-bit unsigned histogram with bins determined by pLevels.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pHist Array of pointers which are receiving the computed histograms per color channel. Array pointed by pHist[i] must be of size nLevels[i]-1.

nLevels Array containing number of levels per color channel.

pLevels Array containing pointers to level-arrays per color channel. Array pointed by *pLevel[i]* must be of size *nLevels[i]*.

pBuffer Pointer to appropriately sized (`nppiHistogramRangeGetBufferSize_8u_C4R`) scratch buffer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.125 NppStatus nppiHistogramRangeGetBufferSize_16s_AC4R (NppiSize *oSizeROI*, int *nLevels*[3], int * *hpBufferSize*)

Scratch-buffer size for `nppiHistogramRange_16s_AC4R`.

Parameters:

oSizeROI ROI size.

nLevels Array containing number of levels per color channel.

hpBufferSize Host pointer where required buffer size is returned.

Returns:

Error Code.

7.4.1.126 NppStatus nppiHistogramRangeGetBufferSize_16s_C1R (NppiSize *oSizeROI*, int *nLevels*, int * *hpBufferSize*)

Scratch-buffer size for `nppiHistogramRange_16s_C1R`.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

nLevels Number of levels in the histogram.

hpBufferSize Host pointer where required buffer size is returned.

Returns:

Error Code.

7.4.1.127 NppStatus nppiHistogramRangeGetBufferSize_16s_C4R (NppiSize *oSizeROI*, int *nLevels*[4], int * *hpBufferSize*)

Scratch-buffer size for `nppiHistogramRange_16s_C4R`.

Parameters:

oSizeROI ROI size.

nLevels Array containing number of levels per color channel.

hpBufferSize Host pointer where required buffer size is returned.

Returns:

Error Code.

7.4.1.128 NppStatus nppiHistogramRangeGetBufferSize_16u_AC4R (NppiSize *oSizeROI*, int *nLevels*[3], int * *hpBufferSize*)

Scratch-buffer size for nppiHistogramRange_16u_AC4R.

Parameters:

oSizeROI ROI size.

nLevels Array containing number of levels per color channel.

hpBufferSize Host pointer where required buffer size is returned.

Returns:

Error Code.

7.4.1.129 NppStatus nppiHistogramRangeGetBufferSize_16u_C1R (NppiSize *oSizeROI*, int *nLevels*, int * *hpBufferSize*)

Scratch-buffer size for nppiHistogramRange_16u_C1R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

nLevels Number of levels in the histogram.

hpBufferSize Host pointer where required buffer size is returned.

Returns:

Error Code.

7.4.1.130 NppStatus nppiHistogramRangeGetBufferSize_16u_C4R (NppiSize *oSizeROI*, int *nLevels*[4], int * *hpBufferSize*)

Scratch-buffer size for nppiHistogramRange_16u_C4R.

Parameters:

oSizeROI ROI size.

nLevels Array containing number of levels per color channel.

hpBufferSize Host pointer where required buffer size is returned.

Returns:

Error Code.

7.4.1.131 NppStatus nppiHistogramRangeGetBufferSize_32f_AC4R (NppiSize *oSizeROI*, int *nLevels*[3], int * *hpBufferSize*)

Scratch-buffer size for nppiHistogramRange_32f_AC4R.

Parameters:

oSizeROI ROI size.
nLevels Array containing number of levels per color channel.
hpBufferSize Host pointer where required buffer size is returned.

Returns:

Error Code.

7.4.1.132 NppStatus nppiHistogramRangeGetBufferSize_32f_C1R (NppiSize *oSizeROI*, int *nLevels*, int * *hpBufferSize*)

Scratch-buffer size for nppiHistogramRange_32f_C1R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).
nLevels Number of levels in the histogram.
hpBufferSize Host pointer where required buffer size is returned.

Returns:

Error Code.

7.4.1.133 NppStatus nppiHistogramRangeGetBufferSize_32f_C4R (NppiSize *oSizeROI*, int *nLevels*[4], int * *hpBufferSize*)

Scratch-buffer size for nppiHistogramRange_32f_C4R.

Parameters:

oSizeROI ROI size.
nLevels Array containing number of levels per color channel.
hpBufferSize Host pointer where required buffer size is returned.

Returns:

Error Code.

7.4.1.134 NppStatus nppiHistogramRangeGetBufferSize_8u_AC4R (NppiSize *oSizeROI*, int *nLevels*[3], int * *hpBufferSize*)

Scratch-buffer size for nppiHistogramRange_8u_AC4R.

Parameters:

oSizeROI ROI size.
nLevels Array containing number of levels per color channel.
hpBufferSize Host pointer where required buffer size is returned.

Returns:

Error Code.

7.4.1.135 NppStatus nppiHistogramRangeGetBufferSize_8u_C1R (NppiSize *oSizeROI*, int *nLevels*, int * *hpBufferSize*)

Scratch-buffer size for nppiHistogramRange_8u_C1R.

Parameters:

oSizeROI [Region-of-Interest \(ROI\)](#).

nLevels Number of levels in the histogram.

hpBufferSize Host pointer where required buffer size is returned.

Returns:

Error Code.

7.4.1.136 NppStatus nppiHistogramRangeGetBufferSize_8u_C4R (NppiSize *oSizeROI*, int *nLevels*[4], int * *hpBufferSize*)

Scratch-buffer size for nppiHistogramRange_8u_C4R.

Parameters:

oSizeROI ROI size.

nLevels Array containing number of levels per color channel.

hpBufferSize Host pointer where required buffer size is returned.

Returns:

Error Code.

7.4.1.137 NppStatus nppiLn_32f_C1R (const Npp32f * *pSrc*, int *nSrcStep*, Npp32f * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

32-bit floating point logarithm.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.138 `NppStatus nppiLUT_Linear_8u_AC4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp32s * pValues[4], const Npp32s * pLevels[4], int nLevels[4])`

4 channel 8-bit unsigned look-up-table color conversion, not affecting Alpha.

The LUT is derived from a set of user defined mapping points through linear interpolation. Alpha channel is the last channel and is not processed.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Double pointer to an [4] of arrays of user defined OUTPUT values per CHANNEL

pLevels Double pointer to an [4] of arrays of user defined INPUT values per CHANNEL

nLevels A [4] array of user defined input/output mapping points (levels) per CHANNEL

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2.

7.4.1.139 `NppStatus nppiLUT_Linear_8u_C1R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp32s * pValues, const Npp32s * pLevels, int nLevels)`

8-bit unsigned look-up-table color conversion.

The LUT is derived from a set of user defined mapping points through linear interpolation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Pointer to an array of user defined OUTPUT values

pLevels Pointer to an array of user defined INPUT values

nLevels Number of user defined input/output mapping points (levels)

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_LUT_NUMBER_OF_LEVELS_ERROR](#) if the number of levels is less than 2.

7.4.1.140 `NppStatus nppiLUT_Linear_8u_C3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp32s * pValues[3], const Npp32s * pLevels[3], int nLevels[3])`

3 channel 8-bit unsigned look-up-table color conversion.

The LUT is derived from a set of user defined mapping points through linear interpolation.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pValues Double pointer to an [3] of arrays of user defined OUTPUT values per CHANNEL

pLevels Double pointer to an [3] of arrays of user defined INPUT values per CHANNEL

nLevels A [3] array of user defined input/output mapping points (levels) per CHANNEL

Returns:

Image Data Related Error Codes, ROI Related Error Codes

- `NPP_LUT_NUMBER_OF_LEVELS_ERROR` if the number of levels is less than 2.

7.4.1.141 `NppStatus nppiMagnitude_32fc32f_C1R (const Npp32fc * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

32-bit floating point complex to 32-bit floating point magnitude.

Converts complex-number pixel image to single channel image computing the result pixels as the magnitude of the complex values.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.142 `NppStatus nppiMagnitudeSqr_32fc32f_C1R (const Npp32fc * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

32-bit floating point complex to 32-bit floating point squared magnitude.

Converts complex-number pixel image to single channel image computing the result pixels as the squared magnitude of the complex values.

The squared magnitude is an intermediate result of magnitude computation and can thus be computed faster than actual magnitude. If magnitudes are required for sorting/comparing only, using this function instead of `nppiMagnitude_32fc32f_C1R` can be a worthwhile performance optimization.

Parameters:

pSrc [Source-Image Pointer](#).
nSrcStep [Source-Image Line Step](#).
pDst [Destination-Image Pointer](#).
nDstStep [Destination-Image Line Step](#).
oSizeROI [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.143 Npp16s* nppiMalloc_16s_C1 (int nWidthPixels, int nHeightPixels, int * pStepBytes)

16-bit signed image memory allocator.

Parameters:

nWidthPixels Image width.
nHeightPixels Image height.
pStepBytes [Line Step](#).

Returns:

Pointer to new image data. NULL pointer indicates allocation failure.

7.4.1.144 Npp16s* nppiMalloc_16s_C2 (int nWidthPixels, int nHeightPixels, int * pStepBytes)

2 channel 16-bit signed image memory allocator.

Parameters:

nWidthPixels Image width.
nHeightPixels Image height.
pStepBytes [Line Step](#).

Returns:

Pointer to new image data. NULL pointer indicates allocation failure.

7.4.1.145 Npp16s* nppiMalloc_16s_C4 (int nWidthPixels, int nHeightPixels, int * pStepBytes)

4 channel 16-bit signed image memory allocator.

Parameters:

nWidthPixels Image width.

nHeightPixels Image height.

pStepBytes [Line Step](#).

Returns:

Pointer to new image data. NULL pointer indicates allocation failure.

7.4.1.146 Npp16u* nppiMalloc_16u_C1 (int *nWidthPixels*, int *nHeightPixels*, int * *pStepBytes*)

16-bit unsigned image memory allocator.

Parameters:

nWidthPixels Image width.

nHeightPixels Image height.

pStepBytes [Line Step](#).

Returns:

Pointer to new image data. NULL pointer indicates allocation failure.

7.4.1.147 Npp16u* nppiMalloc_16u_C2 (int *nWidthPixels*, int *nHeightPixels*, int * *pStepBytes*)

2 channel 16-bit unsigned image memory allocator.

Parameters:

nWidthPixels Image width.

nHeightPixels Image height.

pStepBytes [Line Step](#).

Returns:

Pointer to new image data. NULL pointer indicates allocation failure.

7.4.1.148 Npp16u* nppiMalloc_16u_C3 (int *nWidthPixels*, int *nHeightPixels*, int * *pStepBytes*)

3 channel 16-bit unsigned image memory allocator.

Parameters:

nWidthPixels Image width.

nHeightPixels Image height.

pStepBytes [Line Step](#).

Returns:

Pointer to new image data. NULL pointer indicates allocation failure.

7.4.1.149 Npp16u* nppiMalloc_16u_C4 (int *nWidthPixels*, int *nHeightPixels*, int * *pStepBytes*)

4 channel 16-bit unsigned image memory allocator.

Parameters:

nWidthPixels Image width.

nHeightPixels Image height.

pStepBytes [Line Step](#).

Returns:

Pointer to new image data. NULL pointer indicates allocation failure.

7.4.1.150 Npp32f* nppiMalloc_32f_C1 (int *nWidthPixels*, int *nHeightPixels*, int * *pStepBytes*)

32-bit floating point image memory allocator.

Parameters:

nWidthPixels Image width.

nHeightPixels Image height.

pStepBytes [Line Step](#).

Returns:

Pointer to new image data. NULL pointer indicates allocation failure.

7.4.1.151 Npp32f* nppiMalloc_32f_C2 (int *nWidthPixels*, int *nHeightPixels*, int * *pStepBytes*)

2 channel 32-bit floating point image memory allocator.

Parameters:

nWidthPixels Image width.

nHeightPixels Image height.

pStepBytes [Line Step](#).

Returns:

Pointer to new image data. NULL pointer indicates allocation failure.

7.4.1.152 Npp32f* nppiMalloc_32f_C3 (int *nWidthPixels*, int *nHeightPixels*, int * *pStepBytes*)

3 channel 32-bit floating point image memory allocator.

Parameters:

nWidthPixels Image width.

nHeightPixels Image height.

pStepBytes [Line Step](#).

Returns:

Pointer to new image data. NULL pointer indicates allocation failure.

7.4.1.153 Npp32f* nppiMalloc_32f_C4 (int *nWidthPixels*, int *nHeightPixels*, int * *pStepBytes*)

4 channel 32-bit floating point image memory allocator.

Parameters:

nWidthPixels Image width.

nHeightPixels Image height.

pStepBytes [Line Step](#).

Returns:

Pointer to new image data. NULL pointer indicates allocation failure.

7.4.1.154 Npp32s* nppiMalloc_32s_C1 (int *nWidthPixels*, int *nHeightPixels*, int * *pStepBytes*)

32-bit signed image memory allocator.

Parameters:

nWidthPixels Image width.

nHeightPixels Image height.

pStepBytes [Line Step](#).

Returns:

Pointer to new image data. NULL pointer indicates allocation failure.

7.4.1.155 Npp32s* nppiMalloc_32s_C3 (int *nWidthPixels*, int *nHeightPixels*, int * *pStepBytes*)

3 channel 32-bit signed image memory allocator.

Parameters:

nWidthPixels Image width.

nHeightPixels Image height.

pStepBytes [Line Step](#).

Returns:

Pointer to new image data. NULL pointer indicates allocation failure.

7.4.1.156 Npp32s* nppiMalloc_32s_C4 (int *nWidthPixels*, int *nHeightPixels*, int * *pStepBytes*)

4 channel 32-bit signed image memory allocator.

Parameters:

nWidthPixels Image width.

nHeightPixels Image height.

pStepBytes [Line Step](#).

Returns:

Pointer to new image data. NULL pointer indicates allocation failure.

7.4.1.157 Npp8u* nppiMalloc_8u_C1 (int *nWidthPixels*, int *nHeightPixels*, int * *pStepBytes*)

8-bit unsigned image memory allocator.

Parameters:

nWidthPixels Image width.

nHeightPixels Image height.

pStepBytes [Line Step](#).

Returns:

Pointer to new image data. NULL pointer indicates allocation failure.

7.4.1.158 Npp8u* nppiMalloc_8u_C2 (int *nWidthPixels*, int *nHeightPixels*, int * *pStepBytes*)

2 channel 8-bit unsigned image memory allocator.

Parameters:

nWidthPixels Image width.

nHeightPixels Image height.

pStepBytes [Line Step](#).

Returns:

Pointer to new image data. NULL pointer indicates allocation failure.

7.4.1.159 Npp8u* nppiMalloc_8u_C3 (int *nWidthPixels*, int *nHeightPixels*, int * *pStepBytes*)

3 channel 8-bit unsigned image memory allocator.

Parameters:

nWidthPixels Image width.

nHeightPixels Image height.

pStepBytes [Line Step](#).

Returns:

Pointer to new image data. NULL pointer indicates allocation failure.

7.4.1.160 Npp8u* nppiMalloc_8u_C4 (int nWidthPixels, int nHeightPixels, int * pStepBytes)

4 channel 8-bit unsigned image memory allocator.

Parameters:

nWidthPixels Image width.

nHeightPixels Image height.

pStepBytes [Line Step](#).

Returns:

Pointer to new image data. NULL pointer indicates allocation failure.

7.4.1.161 NppStatus nppiMean_StdDev_8u_C1R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp64f * pMean, Npp64f * pStdDev)

8-bit unsigned mean standard deviation.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pMean Contains computed mean. This is a host pointer.

pStdDev Contains computed standard deviation. This is a host pointer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.162 NppStatus nppiMinMax_8u_C1R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pMin, Npp8u * pMax, Npp8u * pDeviceBuffer)

8-bit unsigned pixel minimum and maximum.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pMin Device-memory pointer receiving the minimum result.

pMax Device-memory pointer receiving the maximum result.

pDeviceBuffer Buffer to a scratch memory. Use [nppiMinMaxGetBufferSize_8u_C1R](#) to determine the minium number of bytes required.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.163 `NppStatus nppiMinMax_8u_C4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u aMin[4], Npp8u aMax[4], Npp8u * pDeviceBuffer)`

4 channel 8-bit unsigned pixel minimum and maximum.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

aMin Device-pointer (array) receiving the minimum result.

aMax Device-pointer (array) receiving the maximum result.

pDeviceBuffer Buffer to a scratch memory. Use [nppiMinMaxGetBufferSize_8u_C4R](#) to determine the minium number of bytes required.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

Note:

Unlike `nppiMinMax_8u_C1R`, this primitive returns its results as device pointers.

7.4.1.164 `NppStatus nppiMinMaxGetBufferSize_8u_C1R (const NppiSize & oSizeROI, int * hpBufferSize)`

Scratch-buffer size for `nppiMinMax_8u_C1R`.

Parameters:

oSizeROI ROI size.

hpBufferSize Host pointer where required buffer size is returned.

Returns:

Error Code.

7.4.1.165 `NppStatus nppiMinMaxGetBufferSize_8u_C4R (const NppiSize & oSizeROI, int * hpBufferSize)`

Scratch-buffer size for `nppiMinMax_8u_C4R`.

Parameters:

oSizeROI ROI size.

hpBufferSize Host pointer where required buffer size is returned.

Returns:

Error Code.

7.4.1.166 `NppStatus nppiMirror_8u_C1R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oROI, NppiAxis flip)`

8-bit unsigned image mirror.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

- `NPP_MIRROR_FLIP_ERR` if flip has an illegal value.

7.4.1.167 `NppStatus nppiMirror_8u_C4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oROI, NppiAxis flip)`

4 channel 8-bit unsigned image mirror.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Distance in bytes between starts of consecutive lines of the destination image.

oROI Region-of-Interest (ROI).

flip Specifies the axis about which the image is to be mirrored.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

- `NPP_MIRROR_FLIP_ERR` if flip has an illegal value.

7.4.1.168 NppStatus nppiMul_32f_C1R (const Npp32f * *pSrc1*, int *nSrc1Step*, const Npp32f * *pSrc2*, int *nSrc2Step*, Npp32f * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

4 channel 32-bit floating point image multiplication.

Multiply corresponding pixels in ROI.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.169 NppStatus nppiMul_32s_C1R (const Npp32s * *pSrc1*, int *nSrc1Step*, const Npp32s * *pSrc2*, int *nSrc2Step*, Npp32s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

4 channel 32-bit image multiplication.

Multiply corresponding pixels in ROI.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.170 NppStatus nppiMul_8u_AC4RSfs (const Npp8u * *pSrc1*, int *nSrc1Step*, const Npp8u * *pSrc2*, int *nSrc2Step*, Npp8u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

4 channel 8-bit unsigned image multiplication, not affecting Alpha.

Multiply corresponding pixels in ROI.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Result pixel values are scaled by $2^{(-nScaleFactor)}$ and then clamped to [0,255] range.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.171 `NppStatus nppiMul_8u_C1RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

8-bit unsigned image multiplication.

Multiply the pixel values of corresponding pixels in the ROI and write them to the output image.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Result pixel values are scaled by $2^{(-nScaleFactor)}$ and then clamped to [0,255] range.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.172 `NppStatus nppiMul_8u_C4RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

4 channel 8-bit unsigned image multiplication.

Multiply corresponding pixels in ROI.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Result pixel values are scaled by $2^{(-nScaleFactor)}$ and then clamped to [0,255] range.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.173 `NppStatus nppiMulC_32f_C1R (const Npp32f * pSrc, int nSrcStep, Npp32f nValue, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

32-bit floating point image multiply constant.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nValue Constant.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.174 `NppStatus nppiMulC_32fc_C1R (const Npp32fc * pSrc, int nSrcStep, Npp32fc nValue, Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)`

32-bit complex floating point image multiply constant.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nValue Constant.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.175 `NppStatus nppiNormDiff_Inf_8u_C1R (const Npp8u * pSrc1, int nSrcStep1, const Npp8u * pSrc2, int nSrcStep2, NppiSize oSizeROI, Npp64f * pRetVal)`

8-bit unsigned Infinity Norm of pixel differences.

Parameters:

pSrc1 Source-Image Pointer.

nSrcStep1 Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrcStep2 Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

**pRetVal* Contains computed L1-norm of differences. This is a host pointer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.176 `NppStatus nppiNormDiff_L1_8u_C1R (const Npp8u * pSrc1, int nSrcStep1, const Npp8u * pSrc2, int nSrcStep2, NppiSize oSizeROI, Npp64f * pRetVal)`

8-bit unsigned L1 norm of pixel differences.

Parameters:

pSrc1 Source-Image Pointer.

nSrcStep1 Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrcStep2 Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pRetVal Contains computed L1-norm of differences. This is a host pointer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.177 `NppStatus nppiNormDiff_L2_8u_C1R (const Npp8u * pSrc1, int nSrcStep1, const Npp8u * pSrc2, int nSrcStep2, NppiSize oSizeROI, Npp64f * pRetVal)`

8-bit unsigned L2 norm of pixel differences.

Parameters:

pSrc1 Source-Image Pointer.

nSrcStep1 Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrcStep2 Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pRetVal Contains computed L1-norm of differences. This is a host pointer.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.178 NppStatus nppiQuantFwdRawTableInit_JPEG_8u (Npp8u * *pQuantRawTable*, int *nQualityFactor*)

Converts regular quantization tables with the quality factor.

Parameters:

pQuantRawTable Raw quantization table.

nQualityFactor Quality factor for the table. Range is [1:100].

Returns:

[NPP_NULL_POINTER_ERROR](#) *pQuantRawTable* is a null pointer.

7.4.1.179 NppStatus nppiQuantFwdTableInit_JPEG_8u16u (const Npp8u * *pQuantRawTable*, Npp16u * *pQuantFwdRawTable*)

Converts raw quantization table to a forward quantization table.

Parameters:

pQuantRawTable Raw quantization table.

pQuantFwdRawTable Forward quantization table.

Returns:

[NPP_NULL_POINTER_ERROR](#) *pQuantRawTable* is a null pointer.

7.4.1.180 NppStatus nppiQuantInvTableInit_JPEG_8u16u (const Npp8u * *pQuantRawTable*, Npp16u * *pQuantFwdRawTable*)

Converts raw quantization table to an inverse quantization table.

Parameters:

pQuantRawTable Raw quantization table.

pQuantFwdRawTable Inverse quantization table.

Returns:

[NPP_NULL_POINTER_ERROR](#) *pQuantRawTable* or *pQuantFwdRawTable* is a null pointer.

7.4.1.181 NppStatus nppiRectStdDev_32s32f_C1R (const Npp32s * *pSrc*, int *nSrcStep*, const Npp32f * *pSqr*, int *nSqrStep*, Npp32f * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, NppiRect *rect*)

RectStdDev Computes the standard deviation of integral images.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep Source-Image Line Step.
pSqr Destination-Image Pointer.
nSqrStep Destination-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
rect rectangular window

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.182 NppStatus nppiReductionGetBufferHostSize_8u_C1R (const NppiSize & *oSizeROI*, int * *hpBufferSize*)

Scratch-buffer size for nppiSum_8u_C1R.

Parameters:

oSizeROI ROI size.
hpBufferSize Host pointer where required buffer size is returned.

Returns:

Error Code.

7.4.1.183 NppStatus nppiReductionGetBufferHostSize_8u_C4R (const NppiSize & *oSizeROI*, int * *hpBufferSize*)

Scratch-buffer size for nppiSum_8u_C4R.

Parameters:

oSizeROI ROI size.
hpBufferSize Host pointer where required buffer size is returned.

Returns:

Error Code.

7.4.1.184 NppStatus nppiResize_8u_C1R (const Npp8u * *pSrc*, NppiSize *srcSize*, int *nSrcStep*, NppiRect *srcROI*, Npp8u * *pDst*, int *nDstStep*, NppiSize *dstROISize*, double *xFactor*, double *yFactor*, int *interpolation*)

8-bit unsigned image resize.

Parameters:

pSrc Source-Image Pointer.

nSrcStep [Source-Image Line Step](#).

srcSize Size in pixels of the source image

srcROI Region of interest in the source image.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

dstROISize Size in pixels of the destination image

xFactor Factors by which x dimension is changed

yFactor Factors by which y dimension is changed

interpolation The type of interpolation to perform resampling

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_WRONG_INTERSECTION_ROI_ERROR](#) indicates an error condition if *srcROIRect* has no intersection with the source image.
- [NPP_RESIZE_NO_OPERATION_ERROR](#) if either destination ROI width or height is less than 1 pixel.
- [NPP_RESIZE_FACTOR_ERROR](#) Indicates an error condition if either *xFactor* or *yFactor* is less than or equal to zero.
- [NPP_INTERPOLATION_ERROR](#) if interpolation has an illegal value.

7.4.1.185 `NppStatus nppiResize_8u_C4R (const Npp8u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcROI, Npp8u * pDst, int nDstStep, NppiSize dstROISize, double xFactor, double yFactor, int interpolation)`

4 channel 8-bit unsigned image resize.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

srcSize Size in pixels of the source image

srcROI Region of interest in the source image.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

dstROISize Size in pixels of the destination image

xFactor Factors by which x dimension is changed

yFactor Factors by which y dimension is changed

interpolation The type of interpolation to perform resampling

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_WRONG_INTERSECTION_ROI_ERROR](#) indicates an error condition if *srcROIRect* has no intersection with the source image.
- [NPP_RESIZE_NO_OPERATION_ERROR](#) if either destination ROI width or height is less than 1 pixel.
- [NPP_RESIZE_FACTOR_ERROR](#) Indicates an error condition if either *xFactor* or *yFactor* is less than or equal to zero.
- [NPP_INTERPOLATION_ERROR](#) if interpolation has an illegal value.

7.4.1.186 NppStatus nppiRGBToYCbCr420_8u_C3P3R (const Npp8u * pSrc, int nSrcStep, Npp8u ** pDst, int nDstStep[3], NppiSize oSizeROI)

3 channel 8-bit unsigned packed RGB to planar YCbCr420 color conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.187 NppStatus nppiRGBToYCbCr422_8u_C3C2R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

3 channel 8-bit unsigned RGB to 2 channel chroma packed YCbCr422 color conversion.
images.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.188 NppStatus nppiRGBToYCbCr_8u_AC4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

4 channel 8-bit unsigned RGB to YCbCr color conversion, ignoring Alpha.
Alpha channel is the last channel and is not processed.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.189 `NppStatus nppiRGBToYCbCr_8u_C3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

3 channel 8-bit unsigned packed RGB to packed YCbCr color conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.190 `NppStatus nppiRGBToYCbCr_8u_P3R (const Npp8u *const * pSrc, int nSrcStep, Npp8u ** pDst, int nDstStep, NppiSize oSizeROI)`

3 channel planar 8-bit unsigned RGB to YCbCr color conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.191 `NppStatus nppiRotate_8u_C1R (const Npp8u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcROI, Npp8u * pDst, int nDstStep, NppiRect dstROI, double angle, double xShift, double yShift, int interpolation)`

8-bit unsigned image rotate.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
srcSize Size in pixels of the source image
srcROI Region of interest in the source image.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

dstROI Region of interest in the destination image.

angle The angle of rotation in degrees.

xShift Shift along horizontal axis

yShift Shift along vertical axis

interpolation The type of interpolation to perform resampling

Returns:

Image Data Related Error Codes, ROI Related Error Codes

- [NPP_INTERPOLATION_ERROR](#) if interpolation has an illegal value.
- [NPP_RECT_ERROR](#) Indicates an error condition if width or height of the intersection of the srcRoi and source image is less than or equal to 1.
- [NPP_WRONG_INTERSECTION_ROI_ERROR](#) indicates an error condition if srcROIrect has no intersection with the source image.
- [NPP_WRONG_INTERSECTION_QUAD_WARNING](#) indicates a warning that no operation is performed if the transformed source ROI does not intersect the destination ROI.

7.4.1.192 `NppStatus nppiRotate_8u_C4R (const Npp8u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcROI, Npp8u * pDst, int nDstStep, NppiRect dstROI, double angle, double xShift, double yShift, int interpolation)`

4 channel 8-bit unsigned image rotate.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

srcSize Size in pixels of the source image

srcROI Region of interest in the source image.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

dstROI Region of interest in the destination image.

angle The angle of rotation in degrees.

xShift Shift along horizontal axis

yShift Shift along vertical axis

interpolation The type of interpolation to perform resampling

Returns:

Image Data Related Error Codes, ROI Related Error Codes

- [NPP_INTERPOLATION_ERROR](#) if interpolation has an illegal value.
- [NPP_RECT_ERROR](#) Indicates an error condition if width or height of the intersection of the srcRoi and source image is less than or equal to 1.
- [NPP_WRONG_INTERSECTION_ROI_ERROR](#) indicates an error condition if srcROIrect has no intersection with the source image.
- [NPP_WRONG_INTERSECTION_QUAD_WARNING](#) indicates a warning that no operation is performed if the transformed source ROI does not intersect the destination ROI.

7.4.1.193 **NppStatus nppiSet_16s_AC4MR** (const Npp16s *aValues*[3], Npp16s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, const Npp8u * *pMask*, int *nMaskStep*)

Masked 4 channel 16-bit image set method, not affecting Alpha channel.

For RGBA images, this method allows setting of the RGB values without changing the contents of the alpha-channel (fourth channel).

Parameters:

aValues Three-channel array containing the pixel-value to be set.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pMask Pointer to the mask image. This is a single channel 8-bit unsigned int image.

nMaskStep Number of bytes between line starts of successive lines in the mask image.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.194 **NppStatus nppiSet_16s_AC4R** (const Npp16s *aValues*[3], Npp16s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

4 channel 16-bit image set method, not affecting Alpha channel.

For RGBA images, this method allows setting of the RGB values without changing the contents of the alpha-channel (fourth channel).

Parameters:

aValues Three-channel array containing the pixel-value to be set.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.195 **NppStatus nppiSet_16s_C1MR** (Npp16s *nValue*, Npp16s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, const Npp8u * *pMask*, int *nMaskStep*)

Masked 16-bit image set.

Parameters:

nValue New pixel value.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pMask Pointer to the mask image. This is a single channel 8-bit unsigned int image.

nMaskStep Number of bytes between line starts of successive lines in the mask image.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.196 NppStatus nppiSet_16s_C1R (Npp16s nValue, Npp16s * pDst, int nDstStep, NppiSize oSizeROI)

16-bit image set.

Parameters:

nValue New pixel value.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.197 NppStatus nppiSet_16s_C2R (const Npp16s aValues[2], Npp16s * pDst, int nDstStep, NppiSize oSizeROI)

2 channel 16-bit image set.

Parameters:

aValues New pixel value.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.198 NppStatus nppiSet_16s_C4CR (Npp16s nValue, Npp16s * pDst, int nDstStep, NppiSize oSizeROI)

4 channel 16-bit unsigned image set affecting only single channel.

For RGBA images, this method allows setting of a single of the four (RGBA) values without changing the contents of the other three channels. The channel is selected via the pDst pointer. The pointer needs to point to the actual first value to be set, e.g. in order to set the R-channel (first channel), one would pass pDst unmodified, since its value actually points to the r channel. If one wanted to modify the B channel (second channel), one would pass pDst + 2 to the function.

Parameters:

nValue The pixel-value to be set.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.199 `NppStatus nppiSet_16s_C4MR (const Npp16s aValues[4], Npp16s * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, int nMaskStep)`

Masked 4 channel 16-bit image set.

Parameters:

aValues New pixel value.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
pMask Pointer to the mask image. This is a single channel 8-bit unsigned int image.
nMaskStep Number of bytes between line starts of successive lines in the mask image.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.200 `NppStatus nppiSet_16s_C4R (const Npp16s aValues[4], Npp16s * pDst, int nDstStep, NppiSize oSizeROI)`

4 channel 16-bit image set.

Parameters:

aValues New pixel value.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.201 `NppStatus nppiSet_16u_AC4MR (const Npp16u aValues[3], Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, int nMaskStep)`

Masked 4 channel 16-bit unsigned image set method, not affecting Alpha channel.

For RGBA images, this method allows setting of the RGB values without changing the contents of the alpha-channel (fourth channel).

Parameters:

aValues Three-channel array containing the pixel-value to be set.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pMask Pointer to the mask image. This is a single channel 8-bit unsigned int image.

nMaskStep Number of bytes between line starts of successive lines in the mask image.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.202 `NppStatus nppiSet_16u_AC4R (const Npp16u aValues[3], Npp16u * pDst, int nDstStep, NppiSize oSizeROI)`

4 channel 16-bit unsigned image set method, not affecting Alpha channel.

For RGBA images, this method allows setting of the RGB values without changing the contents of the alpha-channel (fourth channel).

Parameters:

aValues Three-channel array containing the pixel-value to be set.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.203 `NppStatus nppiSet_16u_C1MR (Npp16u nValue, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, int nMaskStep)`

Masked 16-bit unsigned image set.

Parameters:

nValue New pixel value.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pMask Pointer to the mask image. This is a single channel 8-bit unsigned int image.

nMaskStep Number of bytes between line starts of successive lines in the mask image.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.204 NppStatus nppiSet_16u_C1R (Npp16u nValue, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

16-bit unsigned image set.

Parameters:

nValue New pixel value.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.205 NppStatus nppiSet_16u_C2R (const Npp16u aValues[2], Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

2 channel 16-bit unsigned image set.

Parameters:

aValues New pixel value.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.206 NppStatus nppiSet_16u_C4CR (Npp16u nValue, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

4 channel 16-bit unsigned image set affecting only single channel.

For RGBA images, this method allows setting of a single of the four (RGBA) values without changing the contents of the other three channels. The channel is selected via the pDst pointer. The pointer needs to point to the actual first value to be set, e.g. in order to set the R-channel (first channel), one would pass pDst unmodified, since its value actually points to the r channel. If one wanted to modify the B channel (second channel), one would pass pDst + 2 to the function.

Parameters:

nValue The pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.207 `NppStatus nppiSet_16u_C4MR (const Npp16u aValues[4], Npp16u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, int nMaskStep)`

Masked 4 channel 16-bit unsigned image set.

Parameters:

aValues New pixel value.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pMask Pointer to the mask image. This is a single channel 8-bit unsigned int image.

nMaskStep Number of bytes between line starts of successive lines in the mask image.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.208 `NppStatus nppiSet_16u_C4R (const Npp16u aValues[4], Npp16u * pDst, int nDstStep, NppiSize oSizeROI)`

4 channel 16-bit unsigned image set.

Parameters:

aValues New pixel value.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.209 **NppStatus nppiSet_32f_AC4MR** (const Npp32f *aValues*[3], Npp32f * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, const Npp8u * *pMask*, int *nMaskStep*)

Masked 4 channel 32-bit floating point image set method, not affecting Alpha channel.

For RGBA images, this method allows setting of the RGB values without changing the contents of the alpha-channel (fourth channel).

Parameters:

aValues Three-channel array containing the pixel-value to be set.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pMask Pointer to the mask image. This is a single channel 8-bit unsigned int image.

nMaskStep Number of bytes between line starts of successive lines in the mask image.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.210 **NppStatus nppiSet_32f_AC4R** (const Npp32f *aValues*[3], Npp32f * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

4 channel 32-bit floating point image set method, not affecting Alpha channel.

For RGBA images, this method allows setting of the RGB values without changing the contents of the alpha-channel (fourth channel).

Parameters:

aValues Three-channel array containing the pixel-value to be set.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.211 **NppStatus nppiSet_32f_C1MR** (Npp32f *nValue*, Npp32f * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, const Npp8u * *pMask*, int *nMaskStep*)

Masked 32-bit floating point image set.

Parameters:

nValue New pixel value.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pMask Pointer to the mask image. This is a single channel 8-bit unsigned int image.

nMaskStep Number of bytes between line starts of successive lines in the mask image.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.212 NppStatus nppiSet_32f_C1R (Npp32f *nValue*, Npp32f * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

32-bit floating point image set.

Parameters:

nValue New pixel value.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.213 NppStatus nppiSet_32f_C4CR (Npp32f *nValue*, Npp32f * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

4 channel 32-bit floating point image set affecting only single channel.

For RGBA images, this method allows setting of a single of the four (RGBA) values without changing the contents of the other three channels. The channel is selected via the *pDst* pointer. The pointer needs to point to the actual first value to be set, e.g. in order to set the R-channel (first channel), one would pass *pDst* unmodified, since its value actually points to the r channel. If one wanted to modify the B channel (second channel), one would pass *pDst* + 2 to the function.

Parameters:

nValue The pixel-value to be set.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.214 NppStatus nppiSet_32f_C4MR (const Npp32f *aValues*[4], Npp32f * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, const Npp8u * *pMask*, int *nMaskStep*)

Masked 4 channel 32-bit floating point image set.

Parameters:

aValues New pixel value.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
pMask Pointer to the mask image. This is a single channel 8-bit unsigned int image.
nMaskStep Number of bytes between line starts of successive lines in the mask image.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.215 NppStatus nppiSet_32f_C4R (const Npp32f aValues[4], Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

4 channel 32-bit floating point image set.

Parameters:

aValues New pixel value.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.216 NppStatus nppiSet_32s_AC4MR (const Npp32s aValues[3], Npp32s * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, int nMaskStep)

Masked 4 channel 16-bit image set method, not affecting Alpha channel.

For RGBA images, this method allows setting of the RGB values without changing the contents of the alpha-channel (fourth channel).

Parameters:

aValues Three-channel array containing the pixel-value to be set.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
pMask Pointer to the mask image. This is a single channel 8-bit unsigned int image.
nMaskStep Number of bytes between line starts of successive lines in the mask image.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.217 `NppStatus nppiSet_32s_AC4R (const Npp32s aValues[3], Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

4 channel 16-bit image set method, not affecting Alpha channel.

For RGBA images, this method allows setting of the RGB values without changing the contents of the alpha-channel (fourth channel).

Parameters:

aValues Three-channel array containing the pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.218 `NppStatus nppiSet_32s_C1MR (Npp32s nValue, Npp32s * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, int nMaskStep)`

Masked 32-bit image set.

Parameters:

nValue New pixel value.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pMask Pointer to the mask image. This is a single channel 8-bit unsigned int image.

nMaskStep Number of bytes between line starts of successive lines in the mask image.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.219 `NppStatus nppiSet_32s_C1R (Npp32s nValue, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

32-bit image set.

Parameters:

nValue New pixel value.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.220 **NppStatus nppiSet_32s_C4CR** (Npp32s *nValue*, Npp32s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

4 channel 32-bit unsigned image set affecting only single channel.

For RGBA images, this method allows setting of a single of the four (RGBA) values without changing the contents of the other three channels. The channel is selected via the *pDst* pointer. The pointer needs to point to the actual first value to be set, e.g. in order to set the R-channel (first channel), one would pass *pDst* unmodified, since its value actually points to the r channel. If one wanted to modify the B channel (second channel), one would pass *pDst* + 2 to the function.

Parameters:

nValue The pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.221 **NppStatus nppiSet_32s_C4MR** (const Npp32s *aValues*[4], Npp32s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, const Npp8u * *pMask*, int *nMaskStep*)

Masked 4 channel 32-bit image set.

Parameters:

aValues New pixel value.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pMask Pointer to the mask image. This is a single channel 8-bit unsigned int image.

nMaskStep Number of bytes between line starts of successive lines in the mask image.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.222 **NppStatus nppiSet_32s_C4R** (const Npp32s *aValues*[4], Npp32s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

4 channel 32-bit image set.

Parameters:

aValues New pixel value.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.223 `NppStatus nppiSet_8u_AC4MR (const Npp8u aValues[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, int nMaskStep)`

Masked 4 channel 8-bit unsigned image set method, not affecting Alpha channel.

For RGBA images, this method allows setting of the RGB values without changing the contents of the alpha-channel (fourth channel).

Parameters:

aValues Three-channel array containing the pixel-value to be set.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pMask Pointer to the mask image. This is a single channel 8-bit unsigned int image.

nMaskStep Number of bytes between line starts of successive lines in the mask image.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.224 `NppStatus nppiSet_8u_AC4R (const Npp8u aValues[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

4 channel 8-bit unsigned image set method, not affecting Alpha channel.

For RGBA images, this method allows setting of the RGB values without changing the contents of the alpha-channel (fourth channel).

Parameters:

aValues Three-channel array containing the pixel-value to be set.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.225 `NppStatus nppiSet_8u_C1MR (Npp8u nValue, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, int nMaskStep)`

Masked 8-bit unsigned image set.

The 8-bit mask image affects setting of the respective pixels in the destination image. If the mask value is zero (0) the pixel is not set, if the mask is non-zero, the corresponding destination pixel is set to specified value.

Parameters:

nValue The pixel value to be set.

pDst Pointer [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

pMask Pointer to the mask image. This is a single channel 8-bit unsigned int image.

nMaskStep Number of bytes between line starts of successive lines in the mask image.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.226 `NppStatus nppiSet_8u_C1R (Npp8u nValue, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

8-bit unsigned image set.

Parameters:

nValue The pixel value to be set.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.227 `NppStatus nppiSet_8u_C4CR (Npp8u nValue, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

4 channel 8-bit unsigned image set affecting only single channel.

For RGBA images, this method allows setting of a single of the four (RGBA) values without changing the contents of the other three channels. The channel is selected via the *pDst* pointer. The pointer needs to point to the actual first value to be set, e.g. in order to set the R-channel (first channel), one would pass *pDst* unmodified, since its value actually points to the r channel. If one wanted to modify the B channel (second channel), one would pass *pDst* + 2 to the function.

Parameters:

nValue The pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.228 `NppStatus nppiSet_8u_C4MR (const Npp8u aValues[4], Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u * pMask, int nMaskStep)`

Masked 4 channel 8-bit unsigned image set.

Parameters:

aValues Four-channel array containing the pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pMask Pointer to the mask image. This is a single channel 8-bit unsigned int image.

nMaskStep Number of bytes between line starts of successive lines in the mask image.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.229 `NppStatus nppiSet_8u_C4R (const Npp8u aValues[4], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

4 channel 8-bit unsigned image set.

Parameters:

aValues Four-channel array containing the pixel-value to be set.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.230 `NppStatus nppiSetDefaultQuantTable (Npp8u * pQuantRawTable, int tableIndex)`

Fills out the quantization table with either luminance and chrominance tables for JPEG.

Parameters:

pQuantRawTable Raw quantization table.

tableIndex Choice for Luminance (tableIndex is 0) or Chrominance component (tableIndex is 1).

Returns:

Error codes:

- [NPP_NULL_POINTER_ERROR](#) pQuantRawTable is a null pointer.
- [NPP_INVALID_INPUT](#) if tableIndex is not 0 or 1.

7.4.1.231 `NppStatus nppiSqrIntegral_8u32s32f_C1R (Npp8u * pSrc, int nSrcStep, Npp32s * pDst, int nDstStep, Npp32f * pSqr, int nSqrStep, NppiSize srcROI, Npp32s val, Npp32f valSqr, Npp32s integralImageNewHeight)`

SqrIntegral Transforms an image to integral and integral of pixel squares representation.

This function assumes that the integral and integral of squares images.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
pSqr Destination-Image Pointer.
nSqrStep Destination-Image Line Step.
srcROI Region-of-Interest (ROI).
val The value to add to pDst image pixels
valSqr The value to add to pSqr image pixels
integralImageNewHeight Extended height of output surfaces (needed by transpose in primitive)

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.232 `NppStatus nppiSub_32f_C1R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

32-bit floating point image subtraction.

Subtract pSrc1's pixels from corresponding pixels in pSrc2.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.233 `NppStatus nppiSub_32s_C1R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

32-bit image subtraction.

Subtract pSrc1's pixels from corresponding pixels in pSrc2.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.234 `NppStatus nppiSub_8u_AC4RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

4 channel 8-bit unsigned image subtraction, not affecting Alpha.

Subtract pSrc1's pixels from corresponding pixels in pSrc2.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Result pixel values are scaled by $2^{(-nScaleFactor)}$ and then clamped to [0,255] range.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.235 `NppStatus nppiSub_8u_C1RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

8-bit unsigned image subtraction.

Subtract the pixel values of corresponding pixels in the ROI and write them to the output image.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Result pixel values are scaled by $2^{(-nScaleFactor)}$ and then clamped to [0,255] range.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.236 `NppStatus nppiSub_8u_C4RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

4 channel 8-bit unsigned image subtraction.

Subtract pSrc1's pixels from corresponding pixels in pSrc2.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Result pixel values are scaled by $2^{(-nScaleFactor)}$ and then clamped to [0,255] range.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.237 `NppStatus nppiSubC_32f_C1R (const Npp32f * pSrc, int nSrcStep, Npp32f nValue, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

32-bit floating point image subtract constant.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nValue Constant.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.238 `NppStatus nppiSubC_32fc_C1R (const Npp32fc * pSrc, int nSrcStep, Npp32fc nValue, Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)`

32-bit complex floating point image subtract constant.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nValue Constant.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.239 `NppStatus nppiSum_8u_C1R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64f * pSum)`

8-bit unsigned image sum.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

oSizeROI Region-of-Interest (ROI).

pDeviceBuffer Pointer to the required device memory allocation.

**pSum* Contains computed sum.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.240 `NppStatus nppiSum_8u_C4R (const Npp8u * pSrc, int nSrcStep, NppiSize oSizeROI, Npp8u * pDeviceBuffer, Npp64f aSum[4])`

4 channel 8-bit unsigned image sum.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.
oSizeROI Region-of-Interest (ROI).
pDeviceBuffer Pointer to the required device memory allocation.
aSum Array contains computed sum for each channel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.241 `NppStatus nppiSumWindowColumn_8u32f_C1R (const Npp8u * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oROI, Npp32s nMaskSize, Npp32s nAnchor)`

8-bit unsigned 1D (column) sum to 32f.

Apply Column Window Summation filter over a 1D mask region around each source pixel for 1-channel 8 bit/pixel input images with 32-bit floating point output. Result 32-bit floating point pixel is equal to the sum of the corresponding and neighboring column pixel values in a mask region of the source image defined by nMaskSize and nAnchor.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oROI Region-of-Interest (ROI).
nMaskSize Length of the linear kernel array.
nAnchor Y offset of the kernel origin frame of reference w.r.t the source pixel.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.242 `NppStatus nppiSumWindowRow_8u32f_C1R (const Npp8u * pSrc, Npp32s nSrcStep, Npp32f * pDst, Npp32s nDstStep, NppiSize oROI, Npp32s nMaskSize, Npp32s nAnchor)`

8-bit unsigned 1D (row) sum to 32f.

Apply Row Window Summation filter over a 1D mask region around each source pixel for 1-channel 8-bit pixel input images with 32-bit floating point output. Result 32-bit floating point pixel is equal to the sum of the corresponding and neighboring row pixel values in a mask region of the source image defined by iKernelDim and iAnchorX.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oROI Region-of-Interest (ROI).

nMaskSize Length of the linear kernel array.

nAnchor X offset of the kernel origin frame of reference w.r.t the source pixel.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.243 NppStatus nppiSwapChannels_8u_C4IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, const int aDstOrder[4])

4 channel 8-bit unsigned swap channels, in-place.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place Line Step.

oSizeROI Region-of-Interest (ROI).

aDstOrder Integer array describing how channel values are permuted. The n-th entry of the array contains the number of the channel that is stored in the n-th channel of the output image. E.g. Given an RGBA image, aDstOrder = [3,2,1,0] converts this to ABGR channel order.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.244 NppStatus nppiThreshold_32f_C1R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, Npp32f nThreshold, NppCmpOp eComparisonOperation)

32-bit floating point threshold.

If for a comparison operations OP the predicate (sourcePixel OP nThreshold) is true, the pixel is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nThreshold The threshold value.

eComparisonOperation The type of comparison operation to be used. The only valid values are: NPP_CMP_LESS and NPP_CMP_GREATER.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or NPP_NOT_SUPPORTED_MODE_ERROR if an invalid comparison operation type is specified.

7.4.1.245 `NppStatus nppiThreshold_8u_AC4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, const Npp8u aThresholds[3], NppCmpOp eComparisonOperation)`

4 channel 8-bit unsigned image threshold, not affecting Alpha.

If for a comparison operations OP the predicate (sourcePixel.channel OP nThreshold) is true, the channel value is set to nThreshold, otherwise it is set to sourcePixel.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

aThresholds The threshold values, one per color channel.

eComparisonOperation The type of comparison operation to be used. The only valid values are: NPP_CMP_LESS and NPP_CMP_GREATER.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#), or NPP_NOT_SUPPORTED_MODE_ERROR if an invalid comparison operation type is specified.

7.4.1.246 `NppStatus nppiTranspose_8u_C1R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oROI)`

8-bit image transpose.

Parameters:

pSrc [Source-Image Pointer](#).

nSrcStep [Source-Image Line Step](#).

pDst Pointer to the destination ROI.

nDstStep [Destination-Image Line Step](#).

oROI [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.247 `NppStatus nppiWarpAffine_16u_AC4R (const Npp16u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp16u * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Affine transform of an image (16bit unsigned integer, four channels RGBA).

See also:

[nppiWarpAffine_16u_C1R](#)

7.4.1.248 NppStatus nppiWarpAffine_16u_C1R (const Npp16u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp16u * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)

Affine transform of an image (16bit unsigned integer, single channel).

This function operates using given transform coefficients that can be obtained by using nppiGetAffineTransform function or set explicitly. The function operates on source and destination regions of interest. The affine warp function transforms the source image pixel coordinates (x, y) according to the following formulas:

$$X_{new} = C_{00} * x + C_{01} * y + C_{02} \quad Y_{new} = C_{10} * x + C_{11} * y + C_{12}$$

The transformed part of the source image is resampled using the specified interpolation method and written to the destination ROI. The functions nppiGetAffineQuad and nppiGetAffineBound can help with destination ROI specification.

NPPI specific recommendation: The function operates using 2 types of kernels: fast and accurate. The fast method is about 4 times faster than its accurate variant, but does not perform memory access checks and requires the destination ROI to be 64 bytes aligned. Hence any destination ROI is chunked into 3 vertical stripes: the first and the third are processed by accurate kernels and the central one is processed by the fast one. In order to get the maximum available speed of execution, the projection of destination ROI onto image addresses must be 64 bytes aligned. This is always true if the values $(\text{int})(\text{void} *) (\text{pDst} + \text{dstRoi.x})$ and $(\text{int})(\text{void} *) (\text{pDst} + \text{dstRoi.x} + \text{dstRoi.width})$ are multiples of 64. Another rule of thumb is to specify destination ROI in such way that left and right sides of the projected image are separated from the ROI by at least 63 bytes from each side. However, this requires the whole ROI to be part of allocated memory. In case when the conditions above are not satisfied, the function may decrease in speed slightly and will return NPP_MISALIGNED_DST_ROI_WARNING warning.

Parameters:

pSrc Source-Image Pointer.

srcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

srcRoi Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

dstRoi Destination ROI

coeffs Affine transform coefficients

interpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_RECT_ERROR](#) Indicates an error condition if width or height of the intersection of the srcRoi and source image is less than or equal to 1
- [NPP_WRONG_INTERSECTION_ROI_ERROR](#) Indicates an error condition if srcRoi has no intersection with the source image
- [NPP_INTERPOLATION_ERROR](#) Indicates an error condition if interpolation has an illegal value
- [NPP_COEFF_ERROR](#) Indicates an error condition if coefficient values are invalid

- [NPP_WRONG_INTERSECTION_QUAD_WARNING](#) Indicates a warning that no operation is performed if the transformed source ROI has no intersection with the destination ROI
- [NPP_MISALIGNED_DST_ROI_WARNING](#) Indicates a warning that the speed of primitive execution was reduced due to destination ROI misalignment

7.4.1.249 `NppStatus nppiWarpAffine_16u_C3R (const Npp16u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp16u * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Affine transform of an image (16bit unsigned integer, three channels).

See also:

[nppiWarpAffine_16u_C1R](#)

7.4.1.250 `NppStatus nppiWarpAffine_16u_C4R (const Npp16u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp16u * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Affine transform of an image (16bit unsigned integer, four channels).

See also:

[nppiWarpAffine_16u_C1R](#)

7.4.1.251 `NppStatus nppiWarpAffine_16u_P3R (const Npp16u * pSrc[3], NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp16u * pDst[3], int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Affine transform of an image (16bit unsigned integer, three planes).

See also:

[nppiWarpAffine_16u_C1R](#)

7.4.1.252 `NppStatus nppiWarpAffine_16u_P4R (const Npp16u * pSrc[4], NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp16u * pDst[4], int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Affine transform of an image (16bit unsigned integer, four planes).

See also:

[nppiWarpAffine_16u_C1R](#)

7.4.1.253 `NppStatus nppiWarpAffine_32f_AC4R (const Npp32f * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp32f * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Affine transform of an image (32bit float, four channels RGBA).

See also:

[nppiWarpAffine_32f_C1R](#)

7.4.1.254 `NppStatus nppiWarpAffine_32f_C1R (const Npp32f * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp32f * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Affine transform of an image (32bit float, single channel).

This function operates using given transform coefficients that can be obtained by using `nppiGetAffineTransform` function or set explicitly. The function operates on source and destination regions of interest. The affine warp function transforms the source image pixel coordinates (x, y) according to the following formulas:

$$X_{new} = C_{00} * x + C_{01} * y + C_{02} \quad Y_{new} = C_{10} * x + C_{11} * y + C_{12}$$

The transformed part of the source image is resampled using the specified interpolation method and written to the destination ROI. The functions `nppiGetAffineQuad` and `nppiGetAffineBound` can help with destination ROI specification.

Parameters:

pSrc [Source-Image Pointer](#).

srcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

srcRoi Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

dstRoi Destination ROI

coeffs Affine transform coefficients

interpolation Interpolation mode: can be `NPPI_INTER_NN`, `NPPI_INTER_LINEAR` or `NPPI_INTER_CUBIC`

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_RECT_ERROR](#) Indicates an error condition if width or height of the intersection of the *srcRoi* and source image is less than or equal to 1
- [NPP_WRONG_INTERSECTION_ROI_ERROR](#) Indicates an error condition if *srcRoi* has no intersection with the source image
- [NPP_INTERPOLATION_ERROR](#) Indicates an error condition if interpolation has an illegal value
- [NPP_COEFF_ERROR](#) Indicates an error condition if coefficient values are invalid

- [NPP_WRONG_INTERSECTION_QUAD_WARNING](#) Indicates a warning that no operation is performed if the transformed source ROI has no intersection with the destination ROI
- [NPP_MISALIGNED_DST_ROI_WARNING](#) Indicates a warning that the speed of primitive execution was reduced due to destination ROI misalignment

7.4.1.255 `NppStatus nppiWarpAffine_32f_C3R (const Npp32f * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp32f * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Affine transform of an image (32bit float, three channels).

See also:

[nppiWarpAffine_32f_C1R](#)

7.4.1.256 `NppStatus nppiWarpAffine_32f_C4R (const Npp32f * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp32f * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Affine transform of an image (32bit float, four channels).

See also:

[nppiWarpAffine_32f_C1R](#)

7.4.1.257 `NppStatus nppiWarpAffine_32f_P3R (const Npp32f * pSrc[3], NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp32f * pDst[3], int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Affine transform of an image (32bit float, three planes).

See also:

[nppiWarpAffine_32f_C1R](#)

7.4.1.258 `NppStatus nppiWarpAffine_32f_P4R (const Npp32f * pSrc[4], NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp32f * pDst[4], int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Affine transform of an image (32bit float, four planes).

See also:

[nppiWarpAffine_32f_C1R](#)

7.4.1.259 `NppStatus nppiWarpAffine_32s_AC4R (const Npp32s * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp32s * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Affine transform of an image (32bit signed integer, four channels RGBA).

See also:

[nppiWarpAffine_32s_C1R](#)

7.4.1.260 `NppStatus nppiWarpAffine_32s_C1R (const Npp32s * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp32s * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Affine transform of an image (32bit signed integer, single channel).

This function operates using given transform coefficients that can be obtained by using `nppiGetAffineTransform` function or set explicitly. The function operates on source and destination regions of interest. The affine warp function transforms the source image pixel coordinates (x, y) according to the following formulas:

$$X_{new} = C_{00} * x + C_{01} * y + C_{02} \quad Y_{new} = C_{10} * x + C_{11} * y + C_{12}$$

The transformed part of the source image is resampled using the specified interpolation method and written to the destination ROI. The functions `nppiGetAffineQuad` and `nppiGetAffineBound` can help with destination ROI specification.

Parameters:

pSrc [Source-Image Pointer](#).

srcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

srcRoi Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

dstRoi Destination ROI

coeffs Affine transform coefficients

interpolation Interpolation mode: can be `NPPI_INTER_NN`, `NPPI_INTER_LINEAR` or `NPPI_INTER_CUBIC`

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_RECT_ERROR](#) Indicates an error condition if width or height of the intersection of the *srcRoi* and source image is less than or equal to 1
- [NPP_WRONG_INTERSECTION_ROI_ERROR](#) Indicates an error condition if *srcRoi* has no intersection with the source image
- [NPP_INTERPOLATION_ERROR](#) Indicates an error condition if interpolation has an illegal value
- [NPP_COEFF_ERROR](#) Indicates an error condition if coefficient values are invalid

- [NPP_WRONG_INTERSECTION_QUAD_WARNING](#) Indicates a warning that no operation is performed if the transformed source ROI has no intersection with the destination ROI
- [NPP_MISALIGNED_DST_ROI_WARNING](#) Indicates a warning that the speed of primitive execution was reduced due to destination ROI misalignment

7.4.1.261 `NppStatus nppiWarpAffine_32s_C3R (const Npp32s * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp32s * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Affine transform of an image (32bit signed integer, three channels).

See also:

[nppiWarpAffine_32s_C1R](#)

7.4.1.262 `NppStatus nppiWarpAffine_32s_C4R (const Npp32s * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp32s * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Affine transform of an image (32bit signed integer, four channels).

See also:

[nppiWarpAffine_32s_C1R](#)

7.4.1.263 `NppStatus nppiWarpAffine_32s_P3R (const Npp32s * pSrc[3], NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp32s * pDst[3], int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Affine transform of an image (32bit signed integer, three planes).

See also:

[nppiWarpAffine_32s_C1R](#)

7.4.1.264 `NppStatus nppiWarpAffine_32s_P4R (const Npp32s * pSrc[4], NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp32s * pDst[4], int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Affine transform of an image (32bit signed integer, four planes).

See also:

[nppiWarpAffine_32s_C1R](#)

7.4.1.265 `NppStatus nppiWarpAffine_8u_AC4R (const Npp8u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp8u * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Affine transform of an image (8bit unsigned integer, four channels RGBA).

See also:

[nppiWarpAffine_8u_C1R](#)

7.4.1.266 `NppStatus nppiWarpAffine_8u_C1R (const Npp8u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp8u * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Affine transform of an image (8bit unsigned integer, single channel).

This function operates using given transform coefficients that can be obtained by using `nppiGetAffineTransform` function or set explicitly. The function operates on source and destination regions of interest. The affine warp function transforms the source image pixel coordinates (x, y) according to the following formulas:

$$X_{new} = C_{00} * x + C_{01} * y + C_{02} \quad Y_{new} = C_{10} * x + C_{11} * y + C_{12}$$

The transformed part of the source image is resampled using the specified interpolation method and written to the destination ROI. The functions `nppiGetAffineQuad` and `nppiGetAffineBound` can help with destination ROI specification.

NPPI specific recommendation: The function operates using 2 types of kernels: fast and accurate. The fast method is about 4 times faster than its accurate variant, but does not perform memory access checks and requires the destination ROI to be 64 bytes aligned. Hence any destination ROI is chunked into 3 vertical stripes: the first and the third are processed by accurate kernels and the central one is processed by the fast one. In order to get the maximum available speed of execution, the projection of destination ROI onto image addresses must be 64 bytes aligned. This is always true if the values `(int)((void *) (pDst + dstRoi.x))` and `(int)((void *) (pDst + dstRoi.x + dstRoi.width))` are multiples of 64. Another rule of thumb is to specify destination ROI in such way that left and right sides of the projected image are separated from the ROI by at least 63 bytes from each side. However, this requires the whole ROI to be part of allocated memory. In case when the conditions above are not satisfied, the function may decrease in speed slightly and will return `NPP_MISALIGNED_DST_ROI_WARNING` warning.

Parameters:

pSrc [Source-Image Pointer](#).

srcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

srcRoi Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

dstRoi Destination ROI

coeffs Affine transform coefficients

interpolation Interpolation mode: can be `NPPI_INTER_NN`, `NPPI_INTER_LINEAR` or `NPPI_INTER_CUBIC`

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_RECT_ERROR](#) Indicates an error condition if width or height of the intersection of the srcRoi and source image is less than or equal to 1
- [NPP_WRONG_INTERSECTION_ROI_ERROR](#) Indicates an error condition if srcRoi has no intersection with the source image
- [NPP_INTERPOLATION_ERROR](#) Indicates an error condition if interpolation has an illegal value
- [NPP_COEFF_ERROR](#) Indicates an error condition if coefficient values are invalid
- [NPP_WRONG_INTERSECTION_QUAD_WARNING](#) Indicates a warning that no operation is performed if the transformed source ROI has no intersection with the destination ROI
- [NPP_MISALIGNED_DST_ROI_WARNING](#) Indicates a warning that the speed of primitive execution was reduced due to destination ROI misalignment

7.4.1.267 `NppStatus nppiWarpAffine_8u_C3R (const Npp8u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp8u * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Affine transform of an image (8bit unsigned integer, three channels).

See also:

[nppiWarpAffine_8u_C1R](#)

7.4.1.268 `NppStatus nppiWarpAffine_8u_C4R (const Npp8u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp8u * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Affine transform of an image (8bit unsigned integer, four channels).

See also:

[nppiWarpAffine_8u_C1R](#)

7.4.1.269 `NppStatus nppiWarpAffine_8u_P3R (const Npp8u * pSrc[3], NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp8u * pDst[3], int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Affine transform of an image (8bit unsigned integer, three planes).

See also:

[nppiWarpAffine_8u_C1R](#)

7.4.1.270 `NppStatus nppiWarpAffine_8u_P4R (const Npp8u * pSrc[4], NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp8u * pDst[4], int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Affine transform of an image (8bit unsigned integer, four planes).

See also:

[nppiWarpAffine_8u_C1R](#)

7.4.1.271 `NppStatus nppiWarpAffineBack_16u_AC4R (const Npp16u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp16u * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Inverse affine transform of an image (16bit unsigned integer, four channels RGBA).

See also:

[nppiWarpAffineBack_16u_C1R](#)

7.4.1.272 `NppStatus nppiWarpAffineBack_16u_C1R (const Npp16u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp16u * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Inverse affine transform of an image (16bit unsigned integer, single channel).

This function operates using given transform coefficients that can be obtained by using `nppiGetAffineTransform` function or set explicitly. Thus there is no need to invert coefficients in your application before calling `WarpAffineBack`. The function operates on source and destination regions of interest. The affine warp function transforms the source image pixel coordinates (x, y) according to the following formulas:

$$C_{00} * X_{new} + C_{01} * Y_{new} + C_{02} = x \quad C_{10} * X_{new} + C_{11} * Y_{new} + C_{12} = y$$

The transformed part of the source image is resampled using the specified interpolation method and written to the destination ROI. The functions `nppiGetAffineQuad` and `nppiGetAffineBound` can help with destination ROI specification.

NPPI specific recommendation: The function operates using 2 types of kernels: fast and accurate. The fast method is about 4 times faster than its accurate variant, but doesn't perform memory access checks and requires the destination ROI to be 64 bytes aligned. Hence any destination ROI is chunked into 3 vertical stripes: the first and the third are processed by accurate kernels and the central one is processed by the fast one. In order to get the maximum available speed of execution, the projection of destination ROI onto image addresses must be 64 bytes aligned. This is always true if the values `(int)((void *) (pDst + dstRoi.x))` and `(int)((void *) (pDst + dstRoi.x + dstRoi.width))` are multiples of 64. Another rule of thumb is to specify destination ROI in such way that left and right sides of the projected image are separated from the ROI by at least 63 bytes from each side. However, this requires the whole ROI to be part of allocated memory. In case when the conditions above are not satisfied, the function may decrease in speed slightly and will return `NPP_MISALIGNED_DST_ROI_WARNING` warning.

Parameters:

pSrc [Source-Image Pointer](#).

srcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

srcRoi Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

dstRoi Destination ROI

coeffs Affine transform coefficients

interpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

Image Data Related Error Codes, ROI Related Error Codes

- [NPP_RECT_ERROR](#) Indicates an error condition if width or height of the intersection of the *srcRoi* and source image is less than or equal to 1
- [NPP_WRONG_INTERSECTION_ROI_ERROR](#) Indicates an error condition if *srcRoi* has no intersection with the source image
- [NPP_INTERPOLATION_ERROR](#) Indicates an error condition if *interpolation* has an illegal value
- [NPP_COEFF_ERROR](#) Indicates an error condition if coefficient values are invalid
- [NPP_WRONG_INTERSECTION_QUAD_WARNING](#) Indicates a warning that no operation is performed if the transformed source ROI has no intersection with the destination ROI
- [NPP_MISALIGNED_DST_ROI_WARNING](#) Indicates a warning that the speed of primitive execution was reduced due to destination ROI misalignment

7.4.1.273 `NppStatus nppiWarpAffineBack_16u_C3R (const Npp16u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp16u * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Inverse affine transform of an image (16bit unsigned integer, three channels).

See also:

[nppiWarpAffineBack_16u_C1R](#)

7.4.1.274 `NppStatus nppiWarpAffineBack_16u_C4R (const Npp16u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp16u * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Inverse affine transform of an image (16bit unsigned integer, four channels).

See also:

[nppiWarpAffineBack_16u_C1R](#)

7.4.1.275 `NppStatus nppiWarpAffineBack_16u_P3R (const Npp16u * pSrc[3], NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp16u * pDst[3], int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Inverse affine transform of an image (16bit unsigned integer, three planes).

See also:

[nppiWarpAffineBack_16u_C1R](#)

7.4.1.276 `NppStatus nppiWarpAffineBack_16u_P4R (const Npp16u * pSrc[4], NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp16u * pDst[4], int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Inverse affine transform of an image (16bit unsigned integer, four planes).

See also:

[nppiWarpAffineBack_16u_C1R](#)

7.4.1.277 `NppStatus nppiWarpAffineBack_32f_AC4R (const Npp32f * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp32f * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Inverse affine transform of an image (32bit float, four channels RGBA).

See also:

[nppiWarpAffineBack_32f_C1R](#)

7.4.1.278 `NppStatus nppiWarpAffineBack_32f_C1R (const Npp32f * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp32f * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Inverse affine transform of an image (32bit float, single channel).

This function operates using given transform coefficients that can be obtained by using `nppiGetAffineTransform` function or set explicitly. Thus there is no need to invert coefficients in your application before calling `WarpAffineBack`. The function operates on source and destination regions of interest. The affine warp function transforms the source image pixel coordinates (x, y) according to the following formulas:

$$C_{00} * X_{new} + C_{01} * Y_{new} + C_{02} = x \quad C_{10} * X_{new} + C_{11} * Y_{new} + C_{12} = y$$

The transformed part of the source image is resampled using the specified interpolation method and written to the destination ROI. The functions `nppiGetAffineQuad` and `nppiGetAffineBound` can help with destination ROI specification.

Parameters:

pSrc [Source-Image Pointer](#).

srcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

srcRoi Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

dstRoi Destination ROI

coeffs Affine transform coefficients

interpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_RECT_ERROR](#) Indicates an error condition if width or height of the intersection of the srcRoi and source image is less than or equal to 1
- [NPP_WRONG_INTERSECTION_ROI_ERROR](#) Indicates an error condition if srcRoi has no intersection with the source image
- [NPP_INTERPOLATION_ERROR](#) Indicates an error condition if interpolation has an illegal value
- [NPP_COEFF_ERROR](#) Indicates an error condition if coefficient values are invalid
- [NPP_WRONG_INTERSECTION_QUAD_WARNING](#) Indicates a warning that no operation is performed if the transformed source ROI has no intersection with the destination ROI
- [NPP_MISALIGNED_DST_ROI_WARNING](#) Indicates a warning that the speed of primitive execution was reduced due to destination ROI misalignment

7.4.1.279 `NppStatus nppiWarpAffineBack_32f_C3R (const Npp32f * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp32f * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Inverse affine transform of an image (32bit float, three channels).

See also:

[npapiWarpAffineBack_32f_C1R](#)

7.4.1.280 `NppStatus nppiWarpAffineBack_32f_C4R (const Npp32f * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp32f * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Inverse affine transform of an image (32bit float, four channels).

See also:

[npapiWarpAffineBack_32f_C1R](#)

7.4.1.281 `NppStatus nppiWarpAffineBack_32f_P3R (const Npp32f * pSrc[3], NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp32f * pDst[3], int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Inverse affine transform of an image (32bit float, three planes).

See also:

[nppiWarpAffineBack_32f_C1R](#)

7.4.1.282 `NppStatus nppiWarpAffineBack_32f_P4R (const Npp32f * pSrc[4], NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp32f * pDst[4], int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Inverse affine transform of an image (32bit float, four planes).

See also:

[nppiWarpAffineBack_32f_C1R](#)

7.4.1.283 `NppStatus nppiWarpAffineBack_32s_AC4R (const Npp32s * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp32s * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Inverse affine transform of an image (32bit signed integer, four channels RGBA).

See also:

[nppiWarpAffineBack_32s_C1R](#)

7.4.1.284 `NppStatus nppiWarpAffineBack_32s_C1R (const Npp32s * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp32s * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Inverse affine transform of an image (32bit signed integer, single channel).

This function operates using given transform coefficients that can be obtained by using `nppiGetAffineTransform` function or set explicitly. Thus there is no need to invert coefficients in your application before calling `WarpAffineBack`. The function operates on source and destination regions of interest. The affine warp function transforms the source image pixel coordinates (x, y) according to the following formulas:

$$C_{00} * X_{new} + C_{01} * Y_{new} + C_{02} = x \quad C_{10} * X_{new} + C_{11} * Y_{new} + C_{12} = y$$

The transformed part of the source image is resampled using the specified interpolation method and written to the destination ROI. The functions `nppiGetAffineQuad` and `nppiGetAffineBound` can help with destination ROI specification.

Parameters:

pSrc [Source-Image Pointer](#).

srcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

srcRoi Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

dstRoi Destination ROI

coeffs Affine transform coefficients

interpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_RECT_ERROR](#) Indicates an error condition if width or height of the intersection of the srcRoi and source image is less than or equal to 1
- [NPP_WRONG_INTERSECTION_ROI_ERROR](#) Indicates an error condition if srcRoi has no intersection with the source image
- [NPP_INTERPOLATION_ERROR](#) Indicates an error condition if interpolation has an illegal value
- [NPP_COEFF_ERROR](#) Indicates an error condition if coefficient values are invalid
- [NPP_WRONG_INTERSECTION_QUAD_WARNING](#) Indicates a warning that no operation is performed if the transformed source ROI has no intersection with the destination ROI
- [NPP_MISALIGNED_DST_ROI_WARNING](#) Indicates a warning that the speed of primitive execution was reduced due to destination ROI misalignment

7.4.1.285 `NppStatus nppiWarpAffineBack_32s_C3R (const Npp32s * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp32s * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Inverse affine transform of an image (32bit signed integer, three channels).

See also:

[nppiWarpAffineBack_32s_C1R](#)

7.4.1.286 `NppStatus nppiWarpAffineBack_32s_C4R (const Npp32s * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp32s * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Inverse affine transform of an image (32bit signed integer, four channels).

See also:

[nppiWarpAffineBack_32s_C1R](#)

7.4.1.287 `NppStatus nppiWarpAffineBack_32s_P3R (const Npp32s * pSrc[3], NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp32s * pDst[3], int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Inverse affine transform of an image (32bit signed integer, three planes).

See also:

[nppiWarpAffineBack_32s_C1R](#)

7.4.1.288 `NppStatus nppiWarpAffineBack_32s_P4R (const Npp32s * pSrc[4], NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp32s * pDst[4], int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Inverse affine transform of an image (32bit signed integer, four planes).

See also:

[nppiWarpAffineBack_32s_C1R](#)

7.4.1.289 `NppStatus nppiWarpAffineBack_8u_AC4R (const Npp8u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp8u * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Inverse affine transform of an image (8bit unsigned integer, four channels RGBA).

See also:

[nppiWarpAffineBack_8u_C1R](#)

7.4.1.290 `NppStatus nppiWarpAffineBack_8u_C1R (const Npp8u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp8u * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Inverse affine transform of an image (8bit unsigned integer, single channel).

This function operates using given transform coefficients that can be obtained by using `nppiGetAffineTransform` function or set explicitly. Thus there is no need to invert coefficients in your application before calling `WarpAffineBack`. The function operates on source and destination regions of interest. The affine warp function transforms the source image pixel coordinates (x, y) according to the following formulas:

$$C_{00} * X_{new} + C_{01} * Y_{new} + C_{02} = x \quad C_{10} * X_{new} + C_{11} * Y_{new} + C_{12} = y$$

The transformed part of the source image is resampled using the specified interpolation method and written to the destination ROI. The functions `nppiGetAffineQuad` and `nppiGetAffineBound` can help with destination ROI specification.

NPPI specific recommendation: The function operates using 2 types of kernels: fast and accurate. The fast method is about 4 times faster than its accurate variant, but doesn't perform memory access checks and requires the destination ROI to be 64 bytes aligned. Hence any destination ROI is chunked into 3 vertical stripes: the first and the third are processed by accurate kernels and the central one is processed by the fast one. In order to get the maximum available speed of execution, the projection of destination ROI onto

image addresses must be 64 bytes aligned. This is always true if the values `(int)((void *) (pDst + dstRoi.x))` and `(int)((void *) (pDst + dstRoi.x + dstRoi.width))` are multiples of 64. Another rule of thumb is to specify destination ROI in such way that left and right sides of the projected image are separated from the ROI by at least 63 bytes from each side. However, this requires the whole ROI to be part of allocated memory. In case when the conditions above are not satisfied, the function may decrease in speed slightly and will return `NPP_MISALIGNED_DST_ROI_WARNING` warning.

Parameters:

pSrc [Source-Image Pointer](#).

srcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

srcRoi Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

dstRoi Destination ROI

coeffs Affine transform coefficients

interpolation Interpolation mode: can be `NPPI_INTER_NN`, `NPPI_INTER_LINEAR` or `NPPI_INTER_CUBIC`

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_RECT_ERROR](#) Indicates an error condition if width or height of the intersection of the *srcRoi* and source image is less than or equal to 1
- [NPP_WRONG_INTERSECTION_ROI_ERROR](#) Indicates an error condition if *srcRoi* has no intersection with the source image
- [NPP_INTERPOLATION_ERROR](#) Indicates an error condition if interpolation has an illegal value
- [NPP_COEFF_ERROR](#) Indicates an error condition if coefficient values are invalid
- [NPP_WRONG_INTERSECTION_QUAD_WARNING](#) Indicates a warning that no operation is performed if the transformed source ROI has no intersection with the destination ROI
- [NPP_MISALIGNED_DST_ROI_WARNING](#) Indicates a warning that the speed of primitive execution was reduced due to destination ROI misalignment

7.4.1.291 `NppStatus nppiWarpAffineBack_8u_C3R (const Npp8u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp8u * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Inverse affine transform of an image (8bit unsigned integer, three channels).

See also:

[nppiWarpAffineBack_8u_C1R](#)

7.4.1.292 `NppStatus nppiWarpAffineBack_8u_C4R (const Npp8u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp8u * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Inverse affine transform of an image (8bit unsigned integer, four channels).

See also:

[nppiWarpAffineBack_8u_C1R](#)

7.4.1.293 `NppStatus nppiWarpAffineBack_8u_P3R (const Npp8u * pSrc[3], NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp8u * pDst[3], int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Inverse affine transform of an image (8bit unsigned integer, three planes).

See also:

[nppiWarpAffineBack_8u_C1R](#)

7.4.1.294 `NppStatus nppiWarpAffineBack_8u_P4R (const Npp8u * pSrc[4], NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp8u * pDst[4], int nDstStep, NppiRect dstRoi, const double coeffs[2][3], int interpolation)`

Inverse affine transform of an image (8bit unsigned integer, four planes).

See also:

[nppiWarpAffineBack_8u_C1R](#)

7.4.1.295 `NppStatus nppiWarpAffineQuad_16u_AC4R (const Npp16u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp16u * pDst, int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Affine transform of an image (16bit unsigned integer, four channels RGBA).

See also:

[nppiWarpAffineQuad_16u_C1R](#)

7.4.1.296 `NppStatus nppiWarpAffineQuad_16u_C1R (const Npp16u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp16u * pDst, int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Affine transform of an image (16bit unsigned integer, single channel).

This function performs affine warping of a the specified quadrangle in the source image to the specified quadrangle in the destination image. The function `nppiWarpAffineQuad` uses the same formulas for pixel mapping as in `nppiWarpAffine` function. The transform coefficients are computed internally. The transformed part of the source image is resampled using the specified interpolation method and written to the destination ROI.

NPPI specific recommendation: The function operates using 2 types of kernels: fast and accurate. The fast method is about 4 times faster than its accurate variant, but doesn't perform memory access checks and requires the destination ROI to be 64 bytes aligned. Hence any destination ROI is chunked into 3 vertical stripes: the first and the third are processed by accurate kernels and the central one is processed by the fast one. In order to get the maximum available speed of execution, the projection of destination ROI onto image addresses must be 64 bytes aligned. This is always true if the values `(int)((void*)(pDst + dstRoi.x))` and `(int)((void*)(pDst + dstRoi.x + dstRoi.width))` are multiples of 64. Another rule of thumb is to specify destination ROI in such way that left and right sides of the projected image are separated from the ROI by at least 63 bytes from each side. However, this requires the whole ROI to be part of allocated memory. In case when the conditions above are not satisfied, the function may decrease in speed slightly and will return `NPP_MISALIGNED_DST_ROI_WARNING` warning.

Parameters:

pSrc [Source-Image Pointer](#).

srcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

srcRoi Source ROI

srcQuad Source quadrangle

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

dstRoi Destination ROI

dstQuad Destination quadrangle

interpolation Interpolation mode: can be `NPPI_INTER_NN`, `NPPI_INTER_LINEAR` or `NPPI_INTER_CUBIC`

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_RECT_ERROR](#) Indicates an error condition if width or height of the intersection of the *srcRoi* and source image is less than or equal to 1
- [NPP_WRONG_INTERSECTION_ROI_ERROR](#) Indicates an error condition if *srcRoi* has no intersection with the source image
- [NPP_INTERPOLATION_ERROR](#) Indicates an error condition if interpolation has an illegal value
- [NPP_COEFF_ERROR](#) Indicates an error condition if coefficient values are invalid
- [NPP_WRONG_INTERSECTION_QUAD_WARNING](#) Indicates a warning that no operation is performed if the transformed source ROI has no intersection with the destination ROI
- [NPP_MISALIGNED_DST_ROI_WARNING](#) Indicates a warning that the speed of primitive execution was reduced due to destination ROI misalignment

7.4.1.297 `NppStatus nppiWarpAffineQuad_16u_C3R (const Npp16u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp16u * pDst, int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Affine transform of an image (16bit unsigned integer, three channels).

See also:

[npapiWarpAffineQuad_16u_C1R](#)

7.4.1.298 `NppStatus nppiWarpAffineQuad_16u_C4R (const Npp16u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp16u * pDst, int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Affine transform of an image (16bit unsigned integer, four channels).

See also:

[nppiWarpAffineQuad_16u_C1R](#)

7.4.1.299 `NppStatus nppiWarpAffineQuad_16u_P3R (const Npp16u * pSrc[3], NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp16u * pDst[3], int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Affine transform of an image (16bit unsigned integer, three planes).

See also:

[nppiWarpAffineQuad_16u_C1R](#)

7.4.1.300 `NppStatus nppiWarpAffineQuad_16u_P4R (const Npp16u * pSrc[4], NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp16u * pDst[4], int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Affine transform of an image (16bit unsigned integer, four planes).

See also:

[nppiWarpAffineQuad_16u_C1R](#)

7.4.1.301 `NppStatus nppiWarpAffineQuad_32f_AC4R (const Npp32f * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp32f * pDst, int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Affine transform of an image (32bit float, four channels RGBA).

See also:

[nppiWarpAffineQuad_32f_C1R](#)

7.4.1.302 `NppStatus nppiWarpAffineQuad_32f_C1R (const Npp32f * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp32f * pDst, int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Affine transform of an image (32bit float, single channel).

This function performs affine warping of a the specified quadrangle in the source image to the specified quadrangle in the destination image. The function `nppiWarpAffineQuad` uses the same formulas for pixel mapping as in `nppiWarpAffine` function. The transform coefficients are computed internally. The transformed part of the source image is resampled using the specified interpolation method and written to the destination ROI.

Parameters:

pSrc [Source-Image Pointer](#).
srcSize Size of source image in pixels
nSrcStep [Source-Image Line Step](#).
srcRoi Source ROI
srcQuad Source quadrangle
pDst [Destination-Image Pointer](#).
nDstStep [Destination-Image Line Step](#).
dstRoi Destination ROI
dstQuad Destination quadrangle
interpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_RECT_ERROR](#) Indicates an error condition if width or height of the intersection of the srcRoi and source image is less than or equal to 1
- [NPP_WRONG_INTERSECTION_ROI_ERROR](#) Indicates an error condition if srcRoi has no intersection with the source image
- [NPP_INTERPOLATION_ERROR](#) Indicates an error condition if interpolation has an illegal value
- [NPP_COEFF_ERROR](#) Indicates an error condition if coefficient values are invalid
- [NPP_WRONG_INTERSECTION_QUAD_WARNING](#) Indicates a warning that no operation is performed if the transformed source ROI has no intersection with the destination ROI
- [NPP_MISALIGNED_DST_ROI_WARNING](#) Indicates a warning that the speed of primitive execution was reduced due to destination ROI misalignment

7.4.1.303 `NppStatus nppiWarpAffineQuad_32f_C3R (const Npp32f * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp32f * pDst, int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Affine transform of an image (32bit float, three channels).

See also:

[npapiWarpAffineQuad_32f_C1R](#)

7.4.1.304 `NppStatus nppiWarpAffineQuad_32f_C4R (const Npp32f * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp32f * pDst, int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Affine transform of an image (32bit float, four channels).

See also:

[npapiWarpAffineQuad_32f_C1R](#)

7.4.1.305 `NppStatus nppiWarpAffineQuad_32f_P3R (const Npp32f * pSrc[3], NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp32f * pDst[3], int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Affine transform of an image (32bit float, three planes).

See also:

[nppiWarpAffineQuad_32f_C1R](#)

7.4.1.306 `NppStatus nppiWarpAffineQuad_32f_P4R (const Npp32f * pSrc[4], NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp32f * pDst[4], int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Affine transform of an image (32bit float, four planes).

See also:

[nppiWarpAffineQuad_32f_C1R](#)

7.4.1.307 `NppStatus nppiWarpAffineQuad_32s_AC4R (const Npp32s * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp32s * pDst, int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Affine transform of an image (32bit signed integer, four channels RGBA).

See also:

[nppiWarpAffineQuad_32s_C1R](#)

7.4.1.308 `NppStatus nppiWarpAffineQuad_32s_C1R (const Npp32s * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp32s * pDst, int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Affine transform of an image (32bit signed integer, single channel).

This function performs affine warping of a the specified quadrangle in the source image to the specified quadrangle in the destination image. The function `nppiWarpAffineQuad` uses the same formulas for pixel mapping as in `nppiWarpAffine` function. The transform coefficients are computed internally. The transformed part of the source image is resampled using the specified interpolation method and written to the destination ROI.

Parameters:

pSrc [Source-Image Pointer](#).

srcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

srcRoi Source ROI

srcQuad Source quadrangle

pDst [Destination-Image Pointer](#).

nDstStep Destination-Image Line Step.

dstRoi Destination ROI

dstQuad Destination quadrangle

interpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

Image Data Related Error Codes, ROI Related Error Codes

- [NPP_RECT_ERROR](#) Indicates an error condition if width or height of the intersection of the srcRoi and source image is less than or equal to 1
- [NPP_WRONG_INTERSECTION_ROI_ERROR](#) Indicates an error condition if srcRoi has no intersection with the source image
- [NPP_INTERPOLATION_ERROR](#) Indicates an error condition if interpolation has an illegal value
- [NPP_COEFF_ERROR](#) Indicates an error condition if coefficient values are invalid
- [NPP_WRONG_INTERSECTION_QUAD_WARNING](#) Indicates a warning that no operation is performed if the transformed source ROI has no intersection with the destination ROI
- [NPP_MISALIGNED_DST_ROI_WARNING](#) Indicates a warning that the speed of primitive execution was reduced due to destination ROI misalignment

7.4.1.309 `NppStatus nppiWarpAffineQuad_32s_C3R (const Npp32s * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp32s * pDst, int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Affine transform of an image (32bit signed integer, three channels).

See also:

[npapiWarpAffineQuad_32s_C1R](#)

7.4.1.310 `NppStatus nppiWarpAffineQuad_32s_C4R (const Npp32s * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp32s * pDst, int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Affine transform of an image (32bit signed integer, four channels).

See also:

[npapiWarpAffineQuad_32s_C1R](#)

7.4.1.311 `NppStatus nppiWarpAffineQuad_32s_P3R (const Npp32s * pSrc[3], NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp32s * pDst[3], int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Affine transform of an image (32bit signed integer, three planes).

See also:

[npapiWarpAffineQuad_32s_C1R](#)

7.4.1.312 `NppStatus nppiWarpAffineQuad_32s_P4R (const Npp32s * pSrc[4], NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp32s * pDst[4], int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Affine transform of an image (32bit signed integer, four planes).

See also:

[nppiWarpAffineQuad_32s_C1R](#)

7.4.1.313 `NppStatus nppiWarpAffineQuad_8u_AC4R (const Npp8u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp8u * pDst, int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Affine transform of an image (8bit unsigned integer, four channels RGBA).

See also:

[nppiWarpAffineQuad_8u_C1R](#)

7.4.1.314 `NppStatus nppiWarpAffineQuad_8u_C1R (const Npp8u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp8u * pDst, int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Affine transform of an image (8bit unsigned integer, single channel).

This function performs affine warping of a the specified quadrangle in the source image to the specified quadrangle in the destination image. The function `nppiWarpAffineQuad` uses the same formulas for pixel mapping as in `nppiWarpAffine` function. The transform coefficients are computed internally. The transformed part of the source image is resampled using the specified interpolation method and written to the destination ROI.

NPPI specific recommendation: The function operates using 2 types of kernels: fast and accurate. The fast method is about 4 times faster than its accurate variant, but does not perform memory access checks and requires the destination ROI to be 64 bytes aligned. Hence any destination ROI is chunked into 3 vertical stripes: the first and the third are processed by accurate kernels and the central one is processed by the fast one. In order to get the maximum available speed of execution, the projection of destination ROI onto image addresses must be 64 bytes aligned. This is always true if the values `(int)((void *) (pDst + dstRoi.x))` and `(int)((void *) (pDst + dstRoi.x + dstRoi.width))` are multiples of 64. Another rule of thumb is to specify destination ROI in such way that left and right sides of the projected image are separated from the ROI by at least 63 bytes from each side. However, this requires the whole ROI to be part of allocated memory. In case when the conditions above are not satisfied, the function may decrease in speed slightly and will return `NPP_MISALIGNED_DST_ROI_WARNING` warning.

Parameters:

pSrc [Source-Image Pointer](#).
srcSize Size of source image in pixels
nSrcStep [Source-Image Line Step](#).
srcRoi Source ROI
srcQuad Source quadrangle
pDst [Destination-Image Pointer](#).

nDstStep Destination-Image Line Step.

dstRoi Destination ROI

dstQuad Destination quadrangle

interpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

Image Data Related Error Codes, ROI Related Error Codes

- [NPP_RECT_ERROR](#) Indicates an error condition if width or height of the intersection of the srcRoi and source image is less than or equal to 1
- [NPP_WRONG_INTERSECTION_ROI_ERROR](#) Indicates an error condition if srcRoi has no intersection with the source image
- [NPP_INTERPOLATION_ERROR](#) Indicates an error condition if interpolation has an illegal value
- [NPP_COEFF_ERROR](#) Indicates an error condition if coefficient values are invalid
- [NPP_WRONG_INTERSECTION_QUAD_WARNING](#) Indicates a warning that no operation is performed if the transformed source ROI has no intersection with the destination ROI
- [NPP_MISALIGNED_DST_ROI_WARNING](#) Indicates a warning that the speed of primitive execution was reduced due to destination ROI misalignment ignored, internally computed coordinates are used instead

7.4.1.315 `NppStatus nppiWarpAffineQuad_8u_C3R (const Npp8u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp8u * pDst, int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Affine transform of an image (8bit unsigned integer, three channels).

See also:

[nppiWarpAffineQuad_8u_C1R](#)

7.4.1.316 `NppStatus nppiWarpAffineQuad_8u_C4R (const Npp8u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp8u * pDst, int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Affine transform of an image (8bit unsigned integer, four channels).

See also:

[nppiWarpAffineQuad_8u_C1R](#)

7.4.1.317 `NppStatus nppiWarpAffineQuad_8u_P3R (const Npp8u * pSrc[3], NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp8u * pDst[3], int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Affine transform of an image (8bit unsigned integer, three planes).

See also:

[nppiWarpAffineQuad_8u_C1R](#)

7.4.1.318 `NppStatus nppiWarpAffineQuad_8u_P4R (const Npp8u * pSrc[4], NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp8u * pDst[4], int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Affine transform of an image (8bit unsigned integer, four planes).

See also:

[nppiWarpAffineQuad_8u_C1R](#)

7.4.1.319 `NppStatus nppiWarpPerspective_16u_AC4R (const Npp16u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp16u * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[3][3], int interpolation)`

Perspective transform of an image (16bit unsigned integer, four channels RGBA).

See also:

[nppiWarpPerspective_16u_C1R](#)

7.4.1.320 `NppStatus nppiWarpPerspective_16u_C1R (const Npp16u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp16u * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[3][3], int interpolation)`

Perspective transform of an image (16bit unsigned integer, single channel).

This function operates using given transform coefficients that can be obtained by using `nppiGetPerspectiveTransform` function or set explicitly. The function operates on source and destination regions of interest. The perspective warp function transforms the source image pixel coordinates (x, y) according to the following formulas:

$$X_{new} = \frac{C_{00} * x + C_{01} * y + C_{02}}{C_{20} * x + C_{21} * y + C_{22}} \quad Y_{new} = \frac{C_{10} * x + C_{11} * y + C_{12}}{C_{20} * x + C_{21} * y + C_{22}}$$

The transformed part of the source image is resampled using the specified interpolation method and written to the destination ROI. The functions `nppiGetPerspectiveQuad` and `nppiGetPerspectiveBound` can help with destination ROI specification.

NPPI specific recommendation: The function operates using 2 types of kernels: fast and accurate. The fast method is about 4 times faster than its accurate variant, but does not perform memory access checks and requires the destination ROI to be 64 bytes aligned. Hence any destination ROI is chunked into 3 vertical stripes: the first and the third are processed by accurate kernels and the central one is processed by the fast one. In order to get the maximum available speed of execution, the projection of destination ROI onto image addresses must be 64 bytes aligned. This is always true if the values `(int)((void *) (pDst + dstRoi.x))` and `(int)((void *) (pDst + dstRoi.x + dstRoi.width))` are multiples of 64. Another rule of thumb is to specify destination ROI in such way that left and right sides of the projected image are separated from the ROI by at least 63 bytes from each side. However, this requires the whole ROI to be part of allocated memory. In case when the conditions above are not satisfied, the function may decrease in speed slightly and will return `NPP_MISALIGNED_DST_ROI_WARNING` warning.

Parameters:

pSrc Source-Image Pointer.

srcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

srcRoi Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

dstRoi Destination ROI

coeffs Perspective transform coefficients

interpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_RECT_ERROR](#) Indicates an error condition if width or height of the intersection of the srcRoi and source image is less than or equal to 1
- [NPP_WRONG_INTERSECTION_ROI_ERROR](#) Indicates an error condition if srcRoi has no intersection with the source image
- [NPP_INTERPOLATION_ERROR](#) Indicates an error condition if interpolation has an illegal value
- [NPP_COEFF_ERROR](#) Indicates an error condition if coefficient values are invalid
- [NPP_WRONG_INTERSECTION_QUAD_WARNING](#) Indicates a warning that no operation is performed if the transformed source ROI has no intersection with the destination ROI
- [NPP_MISALIGNED_DST_ROI_WARNING](#) Indicates a warning that the speed of primitive execution was reduced due to destination ROI

7.4.1.321 `NppStatus nppiWarpPerspective_16u_C3R (const Npp16u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp16u * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[3][3], int interpolation)`

Perspective transform of an image (16bit unsigned integer, three channels).

See also:

[nppiWarpPerspective_16u_C1R](#)

7.4.1.322 `NppStatus nppiWarpPerspective_16u_C4R (const Npp16u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp16u * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[3][3], int interpolation)`

Perspective transform of an image (16bit unsigned integer, four channels).

See also:

[nppiWarpPerspective_16u_C1R](#)

7.4.1.323 `NppStatus nppiWarpPerspective_16u_P3R` (`const Npp16u * pSrc[3]`, `NppiSize srcSize`, `int nSrcStep`, `NppiRect srcRoi`, `Npp16u * pDst[3]`, `int nDstStep`, `NppiRect dstRoi`, `const double coeffs[3][3]`, `int interpolation`)

Perspective transform of an image (16bit unsigned integer, three planes).

See also:

[nppiWarpPerspective_16u_C1R](#)

7.4.1.324 `NppStatus nppiWarpPerspective_16u_P4R` (`const Npp16u * pSrc[4]`, `NppiSize srcSize`, `int nSrcStep`, `NppiRect srcRoi`, `Npp16u * pDst[4]`, `int nDstStep`, `NppiRect dstRoi`, `const double coeffs[3][3]`, `int interpolation`)

Perspective transform of an image (16bit unsigned integer, four planes).

See also:

[nppiWarpPerspective_16u_C1R](#)

7.4.1.325 `NppStatus nppiWarpPerspective_32f_AC4R` (`const Npp32f * pSrc`, `NppiSize srcSize`, `int nSrcStep`, `NppiRect srcRoi`, `Npp32f * pDst`, `int nDstStep`, `NppiRect dstRoi`, `const double coeffs[3][3]`, `int interpolation`)

Perspective transform of an image (32bit float, four channels RGBA).

See also:

[nppiWarpPerspective_32f_C1R](#)

7.4.1.326 `NppStatus nppiWarpPerspective_32f_C1R` (`const Npp32f * pSrc`, `NppiSize srcSize`, `int nSrcStep`, `NppiRect srcRoi`, `Npp32f * pDst`, `int nDstStep`, `NppiRect dstRoi`, `const double coeffs[3][3]`, `int interpolation`)

Perspective transform of an image (32bit float, single channel).

This function operates using given transform coefficients that can be obtained by using `nppiGetPerspectiveTransform` function or set explicitly. The function operates on source and destination regions of interest. The perspective warp function transforms the source image pixel coordinates (x, y) according to the following formulas:

$$X_{new} = \frac{C_{00} * x + C_{01} * y + C_{02}}{C_{20} * x + C_{21} * y + C_{22}} \quad Y_{new} = \frac{C_{10} * x + C_{11} * y + C_{12}}{C_{20} * x + C_{21} * y + C_{22}}$$

The transformed part of the source image is resampled using the specified interpolation method and written to the destination ROI. The functions `nppiGetPerspectiveQuad` and `nppiGetPerspectiveBound` can help with destination ROI specification.

Parameters:

pSrc [Source-Image Pointer](#).

srcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

srcRoi Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

dstRoi Destination ROI

coeffs Perspective transform coefficients

interpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_RECT_ERROR](#) Indicates an error condition if width or height of the intersection of the *srcRoi* and source image is less than or equal to 1
- [NPP_WRONG_INTERSECTION_ROI_ERROR](#) Indicates an error condition if *srcRoi* has no intersection with the source image
- [NPP_INTERPOLATION_ERROR](#) Indicates an error condition if interpolation has an illegal value
- [NPP_COEFF_ERROR](#) Indicates an error condition if coefficient values are invalid
- [NPP_WRONG_INTERSECTION_QUAD_WARNING](#) Indicates a warning that no operation is performed if the transformed source ROI has no intersection with the destination ROI
- [NPP_MISALIGNED_DST_ROI_WARNING](#) Indicates a warning that the speed of primitive execution was reduced due to destination ROI

7.4.1.327 `NppStatus nppiWarpPerspective_32f_C3R (const Npp32f * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp32f * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[3][3], int interpolation)`

Perspective transform of an image (32bit float, three channels).

See also:

[nppiWarpPerspective_32f_C1R](#)

7.4.1.328 `NppStatus nppiWarpPerspective_32f_C4R (const Npp32f * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp32f * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[3][3], int interpolation)`

Perspective transform of an image (32bit float, four channels).

See also:

[nppiWarpPerspective_32f_C1R](#)

7.4.1.329 `NppStatus nppiWarpPerspective_32f_P3R (const Npp32f * pSrc[3], NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp32f * pDst[3], int nDstStep, NppiRect dstRoi, const double coeffs[3][3], int interpolation)`

Perspective transform of an image (32bit float, three planes).

See also:

[nppiWarpPerspective_32f_C1R](#)

7.4.1.330 `NppStatus nppiWarpPerspective_32f_P4R (const Npp32f * pSrc[4], NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp32f * pDst[4], int nDstStep, NppiRect dstRoi, const double coeffs[3][3], int interpolation)`

Perspective transform of an image (32bit float, four planes).

See also:

[nppiWarpPerspective_32f_C1R](#)

7.4.1.331 `NppStatus nppiWarpPerspective_32s_AC4R (const Npp32s * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp32s * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[3][3], int interpolation)`

Perspective transform of an image (32bit signed integer, four channels RGBA).

See also:

[nppiWarpPerspective_32s_C1R](#)

7.4.1.332 `NppStatus nppiWarpPerspective_32s_C1R (const Npp32s * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp32s * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[3][3], int interpolation)`

Perspective transform of an image (32bit signed integer, single channel).

This function operates using given transform coefficients that can be obtained by using `nppiGetPerspectiveTransform` function or set explicitly. The function operates on source and destination regions of interest. The perspective warp function transforms the source image pixel coordinates (x, y) according to the following formulas:

$$X_{new} = \frac{C_{00} * x + C_{01} * y + C_{02}}{C_{20} * x + C_{21} * y + C_{22}} \quad Y_{new} = \frac{C_{10} * x + C_{11} * y + C_{12}}{C_{20} * x + C_{21} * y + C_{22}}$$

The transformed part of the source image is resampled using the specified interpolation method and written to the destination ROI. The functions `nppiGetPerspectiveQuad` and `nppiGetPerspectiveBound` can help with destination ROI specification.

Parameters:

pSrc [Source-Image Pointer](#).

srcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

srcRoi Source ROI

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

dstRoi Destination ROI

coeffs Perspective transform coefficients

interpolation Interpolation mode: can be NPPI_INTER_NN, NPPI_INTER_LINEAR or NPPI_INTER_CUBIC

Returns:

Image Data Related Error Codes, ROI Related Error Codes

- [NPP_RECT_ERROR](#) Indicates an error condition if width or height of the intersection of the *srcRoi* and source image is less than or equal to 1
- [NPP_WRONG_INTERSECTION_ROI_ERROR](#) Indicates an error condition if *srcRoi* has no intersection with the source image
- [NPP_INTERPOLATION_ERROR](#) Indicates an error condition if interpolation has an illegal value
- [NPP_COEFF_ERROR](#) Indicates an error condition if coefficient values are invalid
- [NPP_WRONG_INTERSECTION_QUAD_WARNING](#) Indicates a warning that no operation is performed if the transformed source ROI has no intersection with the destination ROI
- [NPP_MISALIGNED_DST_ROI_WARNING](#) Indicates a warning that the speed of primitive execution was reduced due to destination ROI

7.4.1.333 `NppStatus nppiWarpPerspective_32s_C3R (const Npp32s * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp32s * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[3][3], int interpolation)`

Perspective transform of an image (32bit signed integer, three channels).

See also:

[nppiWarpPerspective_32s_C1R](#)

7.4.1.334 `NppStatus nppiWarpPerspective_32s_C4R (const Npp32s * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp32s * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[3][3], int interpolation)`

Perspective transform of an image (32bit signed integer, four channels).

See also:

[nppiWarpPerspective_32s_C1R](#)

7.4.1.335 `NppStatus nppiWarpPerspective_32s_P3R (const Npp32s * pSrc[3], NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp32s * pDst[3], int nDstStep, NppiRect dstRoi, const double coeffs[3][3], int interpolation)`

Perspective transform of an image (32bit signed integer, three planes).

See also:

[nppiWarpPerspective_32s_C1R](#)

7.4.1.336 `NppStatus nppiWarpPerspective_32s_P4R (const Npp32s * pSrc[4], NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp32s * pDst[4], int nDstStep, NppiRect dstRoi, const double coeffs[3][3], int interpolation)`

Perspective transform of an image (32bit signed integer, four planes).

See also:

[nppiWarpPerspective_32s_C1R](#)

7.4.1.337 `NppStatus nppiWarpPerspective_8u_AC4R (const Npp8u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp8u * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[3][3], int interpolation)`

Perspective transform of an image (8bit unsigned integer, four channels RGBA).

See also:

[nppiWarpPerspective_8u_C1R](#)

7.4.1.338 `NppStatus nppiWarpPerspective_8u_C1R (const Npp8u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp8u * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[3][3], int interpolation)`

Perspective transform of an image (8bit unsigned integer, single channel).

This function operates using given transform coefficients that can be obtained by using `nppiGetPerspectiveTransform` function or set explicitly. The function operates on source and destination regions of interest. The perspective warp function transforms the source image pixel coordinates (x, y) according to the following formulas:

$$X_{new} = \frac{C_{00} * x + C_{01} * y + C_{02}}{C_{20} * x + C_{21} * y + C_{22}} \quad Y_{new} = \frac{C_{10} * x + C_{11} * y + C_{12}}{C_{20} * x + C_{21} * y + C_{22}}$$

The transformed part of the source image is resampled using the specified interpolation method and written to the destination ROI. The functions `nppiGetPerspectiveQuad` and `nppiGetPerspectiveBound` can help with destination ROI specification.

NPPI specific recommendation: The function operates using 2 types of kernels: fast and accurate. The fast method is about 4 times faster than its accurate variant, but does not perform memory access checks and requires the destination ROI to be 64 bytes aligned. Hence any destination ROI is chunked into 3 vertical stripes: the first and the third are processed by accurate kernels and the central one is processed by the

fast one. In order to get the maximum available speed of execution, the projection of destination ROI onto image addresses must be 64 bytes aligned. This is always true if the values `(int)((void*)(pDst + dstRoi.x))` and `(int)((void*)(pDst + dstRoi.x + dstRoi.width))` are multiples of 64. Another rule of thumb is to specify destination ROI in such way that left and right sides of the projected image are separated from the ROI by at least 63 bytes from each side. However, this requires the whole ROI to be part of allocated memory. In case when the conditions above are not satisfied, the function may decrease in speed slightly and will return `NPP_MISALIGNED_DST_ROI_WARNING` warning.

Parameters:

pSrc [Source-Image Pointer](#).

srcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

srcRoi Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

dstRoi Destination ROI

coeffs Perspective transform coefficients

interpolation Interpolation mode: can be `NPPI_INTER_NN`, `NPPI_INTER_LINEAR` or `NPPI_INTER_CUBIC`

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_RECT_ERROR](#) Indicates an error condition if width or height of the intersection of the *srcRoi* and source image is less than or equal to 1
- [NPP_WRONG_INTERSECTION_ROI_ERROR](#) Indicates an error condition if *srcRoi* has no intersection with the source image
- [NPP_INTERPOLATION_ERROR](#) Indicates an error condition if interpolation has an illegal value
- [NPP_COEFF_ERROR](#) Indicates an error condition if coefficient values are invalid
- [NPP_WRONG_INTERSECTION_QUAD_WARNING](#) Indicates a warning that no operation is performed if the transformed source ROI has no intersection with the destination ROI
- [NPP_MISALIGNED_DST_ROI_WARNING](#) Indicates a warning that the speed of primitive execution was reduced due to destination ROI

7.4.1.339 `NppStatus nppiWarpPerspective_8u_C3R (const Npp8u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp8u * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[3][3], int interpolation)`

Perspective transform of an image (8bit unsigned integer, three channels).

See also:

[npplWarpPerspective_8u_C1R](#)

7.4.1.340 `NppStatus nppiWarpPerspective_8u_C4R (const Npp8u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp8u * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[3][3], int interpolation)`

Perspective transform of an image (8bit unsigned integer, four channels).

See also:

[nppiWarpPerspective_8u_C1R](#)

7.4.1.341 `NppStatus nppiWarpPerspective_8u_P3R (const Npp8u * pSrc[3], NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp8u * pDst[3], int nDstStep, NppiRect dstRoi, const double coeffs[3][3], int interpolation)`

Perspective transform of an image (8bit unsigned integer, three planes).

See also:

[nppiWarpPerspective_8u_C1R](#)

7.4.1.342 `NppStatus nppiWarpPerspective_8u_P4R (const Npp8u * pSrc[4], NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp8u * pDst[4], int nDstStep, NppiRect dstRoi, const double coeffs[3][3], int interpolation)`

Perspective transform of an image (8bit unsigned integer, four planes).

See also:

[nppiWarpPerspective_8u_C1R](#)

7.4.1.343 `NppStatus nppiWarpPerspectiveBack_16u_AC4R (const Npp16u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp16u * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[3][3], int interpolation)`

Inverse perspective transform of an image (16bit unsigned integer, four channels RGBA).

See also:

[nppiWarpPerspectiveBack_16u_C1R](#)

7.4.1.344 `NppStatus nppiWarpPerspectiveBack_16u_C1R (const Npp16u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp16u * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[3][3], int interpolation)`

Inverse perspective transform of an image (16bit unsigned integer, single channel).

This function operates using given transform coefficients that can be obtained by using `nppiGetPerspectiveTransform` function or set explicitly. Thus there is no need to invert coefficients in your application before calling `WarpPerspectiveBack`. The function operates on source and destination regions of interest. The

perspective warp function transforms the source image pixel coordinates (x, y) according to the following formulas:

$$\frac{C_{00} * X_{new} + C_{01} * Y_{new} + C_{02}}{C_{20} * X_{new} + C_{21} * Y_{new} + C_{22}} = x \quad \frac{C_{10} * X_{new} + C_{11} * Y_{new} + C_{12}}{C_{20} * X_{new} + C_{21} * Y_{new} + C_{22}} = y$$

The transformed part of the source image is resampled using the specified interpolation method and written to the destination ROI. The functions `npapiGetPerspectiveQuad` and `npapiGetPerspectiveBound` can help with destination ROI specification.

NPPI specific recommendation: The function operates using 2 types of kernels: fast and accurate. The fast method is about 4 times faster than its accurate variant, but does not perform memory access checks and requires the destination ROI to be 64 bytes aligned. Hence any destination ROI is chunked into 3 vertical stripes: the first and the third are processed by accurate kernels and the central one is processed by the fast one. In order to get the maximum available speed of execution, the projection of destination ROI onto image addresses must be 64 bytes aligned. This is always true if the values `(int)((void*)(pDst + dstRoi.x))` and `(int)((void*)(pDst + dstRoi.x + dstRoi.width))` are multiples of 64. Another rule of thumb is to specify destination ROI in such way that left and right sides of the projected image are separated from the ROI by at least 63 bytes from each side. However, this requires the whole ROI to be part of allocated memory. In case when the conditions above are not satisfied, the function may decrease in speed slightly and will return `NPP_MISALIGNED_DST_ROI_WARNING` warning.

Parameters:

pSrc [Source-Image Pointer](#).

srcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

srcRoi Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

dstRoi Destination ROI

coeffs Perspective transform coefficients

interpolation Interpolation mode: can be `NPPI_INTER_NN`, `NPPI_INTER_LINEAR` or `NPPI_INTER_CUBIC`

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_RECT_ERROR](#) Indicates an error condition if width or height of the intersection of the `srcRoi` and source image is less than or equal to 1
- [NPP_WRONG_INTERSECTION_ROI_ERROR](#) Indicates an error condition if `srcRoi` has no intersection with the source image
- [NPP_INTERPOLATION_ERROR](#) Indicates an error condition if interpolation has an illegal value
- [NPP_COEFF_ERROR](#) Indicates an error condition if coefficient values are invalid
- [NPP_WRONG_INTERSECTION_QUAD_WARNING](#) Indicates a warning that no operation is performed if the transformed source ROI has no intersection with the destination ROI
- [NPP_MISALIGNED_DST_ROI_WARNING](#) Indicates a warning that the speed of primitive execution was reduced due to destination ROI

7.4.1.345 `NppStatus nppiWarpPerspectiveBack_16u_C3R (const Npp16u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp16u * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[3][3], int interpolation)`

Inverse perspective transform of an image (16bit unsigned integer, three channels).

See also:

[nppiWarpPerspectiveBack_16u_C1R](#)

7.4.1.346 `NppStatus nppiWarpPerspectiveBack_16u_C4R (const Npp16u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp16u * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[3][3], int interpolation)`

Inverse perspective transform of an image (16bit unsigned integer, four channels).

See also:

[nppiWarpPerspectiveBack_16u_C1R](#)

7.4.1.347 `NppStatus nppiWarpPerspectiveBack_16u_P3R (const Npp16u * pSrc[3], NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp16u * pDst[3], int nDstStep, NppiRect dstRoi, const double coeffs[3][3], int interpolation)`

Inverse perspective transform of an image (16bit unsigned integer, three planes).

See also:

[nppiWarpPerspectiveBack_16u_C1R](#)

7.4.1.348 `NppStatus nppiWarpPerspectiveBack_16u_P4R (const Npp16u * pSrc[4], NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp16u * pDst[4], int nDstStep, NppiRect dstRoi, const double coeffs[3][3], int interpolation)`

Inverse perspective transform of an image (16bit unsigned integer, four planes).

See also:

[nppiWarpPerspectiveBack_16u_C1R](#)

7.4.1.349 `NppStatus nppiWarpPerspectiveBack_32f_AC4R (const Npp32f * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp32f * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[3][3], int interpolation)`

Inverse perspective transform of an image (32bit float, four channels RGBA).

See also:

[nppiWarpPerspectiveBack_32f_C1R](#)

7.4.1.350 **NppStatus nppiWarpPerspectiveBack_32f_C1R** (const Npp32f * *pSrc*, NppiSize *srcSize*, int *nSrcStep*, NppiRect *srcRoi*, Npp32f * *pDst*, int *nDstStep*, NppiRect *dstRoi*, const double *coeffs*[3][3], int *interpolation*)

Inverse perspective transform of an image (32bit float, single channel).

This function operates using given transform coefficients that can be obtained by using `nppiGetPerspectiveTransform` function or set explicitly. Thus there is no need to invert coefficients in your application before calling `WarpPerspectiveBack`. The function operates on source and destination regions of interest. The perspective warp function transforms the source image pixel coordinates (x, y) according to the following formulas:

$$\frac{C_{00} * X_{new} + C_{01} * Y_{new} + C_{02}}{C_{20} * X_{new} + C_{21} * Y_{new} + C_{22}} = x \quad \frac{C_{10} * X_{new} + C_{11} * Y_{new} + C_{12}}{C_{20} * X_{new} + C_{21} * Y_{new} + C_{22}} = y$$

The transformed part of the source image is resampled using the specified interpolation method and written to the destination ROI. The functions `nppiGetPerspectiveQuad` and `nppiGetPerspectiveBound` can help with destination ROI specification.

Parameters:

pSrc [Source-Image Pointer](#).

srcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

srcRoi Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

dstRoi Destination ROI

coeffs Perspective transform coefficients

interpolation Interpolation mode: can be `NPPI_INTER_NN`, `NPPI_INTER_LINEAR` or `NPPI_INTER_CUBIC`

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_RECT_ERROR](#) Indicates an error condition if width or height of the intersection of the *srcRoi* and source image is less than or equal to 1
- [NPP_WRONG_INTERSECTION_ROI_ERROR](#) Indicates an error condition if *srcRoi* has no intersection with the source image
- [NPP_INTERPOLATION_ERROR](#) Indicates an error condition if interpolation has an illegal value
- [NPP_COEFF_ERROR](#) Indicates an error condition if coefficient values are invalid
- [NPP_WRONG_INTERSECTION_QUAD_WARNING](#) Indicates a warning that no operation is performed if the transformed source ROI has no intersection with the destination ROI
- [NPP_MISALIGNED_DST_ROI_WARNING](#) Indicates a warning that the speed of primitive execution was reduced due to destination ROI

7.4.1.351 `NppStatus nppiWarpPerspectiveBack_32f_C3R (const Npp32f * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp32f * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[3][3], int interpolation)`

Inverse perspective transform of an image (32bit float, three channels).

See also:

[nppiWarpPerspectiveBack_32f_C1R](#)

7.4.1.352 `NppStatus nppiWarpPerspectiveBack_32f_C4R (const Npp32f * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp32f * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[3][3], int interpolation)`

Inverse perspective transform of an image (32bit float, four channels).

See also:

[nppiWarpPerspectiveBack_32f_C1R](#)

7.4.1.353 `NppStatus nppiWarpPerspectiveBack_32f_P3R (const Npp32f * pSrc[3], NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp32f * pDst[3], int nDstStep, NppiRect dstRoi, const double coeffs[3][3], int interpolation)`

Inverse perspective transform of an image (32bit float, three planes).

See also:

[nppiWarpPerspectiveBack_32f_C1R](#)

7.4.1.354 `NppStatus nppiWarpPerspectiveBack_32f_P4R (const Npp32f * pSrc[4], NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp32f * pDst[4], int nDstStep, NppiRect dstRoi, const double coeffs[3][3], int interpolation)`

Inverse perspective transform of an image (32bit float, four planes).

See also:

[nppiWarpPerspectiveBack_32f_C1R](#)

7.4.1.355 `NppStatus nppiWarpPerspectiveBack_32s_AC4R (const Npp32s * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp32s * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[3][3], int interpolation)`

Inverse perspective transform of an image (32bit signed integer, four channels RGBA).

See also:

[nppiWarpPerspectiveBack_32s_C1R](#)

7.4.1.356 **NppStatus nppiWarpPerspectiveBack_32s_C1R** (const Npp32s * *pSrc*, NppiSize *srcSize*, int *nSrcStep*, NppiRect *srcRoi*, Npp32s * *pDst*, int *nDstStep*, NppiRect *dstRoi*, const double *coeffs*[3][3], int *interpolation*)

Inverse perspective transform of an image (32bit signed integer, single channel).

This function operates using given transform coefficients that can be obtained by using `nppiGetPerspectiveTransform` function or set explicitly. Thus there is no need to invert coefficients in your application before calling `WarpPerspectiveBack`. The function operates on source and destination regions of interest. The perspective warp function transforms the source image pixel coordinates (x, y) according to the following formulas:

$$\frac{C_{00} * X_{new} + C_{01} * Y_{new} + C_{02}}{C_{20} * X_{new} + C_{21} * Y_{new} + C_{22}} = x \quad \frac{C_{10} * X_{new} + C_{11} * Y_{new} + C_{12}}{C_{20} * X_{new} + C_{21} * Y_{new} + C_{22}} = y$$

The transformed part of the source image is resampled using the specified interpolation method and written to the destination ROI. The functions `nppiGetPerspectiveQuad` and `nppiGetPerspectiveBound` can help with destination ROI specification.

Parameters:

pSrc [Source-Image Pointer](#).

srcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

srcRoi Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

dstRoi Destination ROI

coeffs Perspective transform coefficients

interpolation Interpolation mode: can be `NPPI_INTER_NN`, `NPPI_INTER_LINEAR` or `NPPI_INTER_CUBIC`

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_RECT_ERROR](#) Indicates an error condition if width or height of the intersection of the *srcRoi* and source image is less than or equal to 1
- [NPP_WRONG_INTERSECTION_ROI_ERROR](#) Indicates an error condition if *srcRoi* has no intersection with the source image
- [NPP_INTERPOLATION_ERROR](#) Indicates an error condition if interpolation has an illegal value
- [NPP_COEFF_ERROR](#) Indicates an error condition if coefficient values are invalid
- [NPP_WRONG_INTERSECTION_QUAD_WARNING](#) Indicates a warning that no operation is performed if the transformed source ROI has no intersection with the destination ROI
- [NPP_MISALIGNED_DST_ROI_WARNING](#) Indicates a warning that the speed of primitive execution was reduced due to destination ROI

7.4.1.357 `NppStatus nppiWarpPerspectiveBack_32s_C3R (const Npp32s * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp32s * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[3][3], int interpolation)`

Inverse perspective transform of an image (32bit signed integer, three channels).

See also:

[nppiWarpPerspectiveBack_32s_C1R](#)

7.4.1.358 `NppStatus nppiWarpPerspectiveBack_32s_C4R (const Npp32s * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp32s * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[3][3], int interpolation)`

Inverse perspective transform of an image (32bit signed integer, four channels).

See also:

[nppiWarpPerspectiveBack_32s_C1R](#)

7.4.1.359 `NppStatus nppiWarpPerspectiveBack_32s_P3R (const Npp32s * pSrc[3], NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp32s * pDst[3], int nDstStep, NppiRect dstRoi, const double coeffs[3][3], int interpolation)`

Inverse perspective transform of an image (32bit signed integer, three planes).

See also:

[nppiWarpPerspectiveBack_32s_C1R](#)

7.4.1.360 `NppStatus nppiWarpPerspectiveBack_32s_P4R (const Npp32s * pSrc[4], NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp32s * pDst[4], int nDstStep, NppiRect dstRoi, const double coeffs[3][3], int interpolation)`

Inverse perspective transform of an image (32bit signed integer, four planes).

See also:

[nppiWarpPerspectiveBack_32s_C1R](#)

7.4.1.361 `NppStatus nppiWarpPerspectiveBack_8u_AC4R (const Npp8u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp8u * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[3][3], int interpolation)`

Inverse perspective transform of an image (8bit unsigned integer, four channels RGBA).

See also:

[nppiWarpPerspectiveBack_8u_C1R](#)

7.4.1.362 **NppStatus nppiWarpPerspectiveBack_8u_C1R** (const Npp8u * *pSrc*, NppiSize *srcSize*, int *nSrcStep*, NppiRect *srcRoi*, Npp8u * *pDst*, int *nDstStep*, NppiRect *dstRoi*, const double *coeffs*[3][3], int *interpolation*)

Inverse perspective transform of an image (8bit unsigned integer, single channel).

This function operates using given transform coefficients that can be obtained by using `nppiGetPerspectiveTransform` function or set explicitly. Thus there is no need to invert coefficients in your application before calling `WarpPerspectiveBack`. The function operates on source and destination regions of interest. The perspective warp function transforms the source image pixel coordinates (x, y) according to the following formulas:

$$\frac{C_{00} * X_{new} + C_{01} * Y_{new} + C_{02}}{C_{20} * X_{new} + C_{21} * Y_{new} + C_{22}} = x \quad \frac{C_{10} * X_{new} + C_{11} * Y_{new} + C_{12}}{C_{20} * X_{new} + C_{21} * Y_{new} + C_{22}} = y$$

The transformed part of the source image is resampled using the specified interpolation method and written to the destination ROI. The functions `nppiGetPerspectiveQuad` and `nppiGetPerspectiveBound` can help with destination ROI specification.

NPPI specific recommendation: The function operates using 2 types of kernels: fast and accurate. The fast method is about 4 times faster than its accurate variant, but does not perform memory access checks and requires the destination ROI to be 64 bytes aligned. Hence any destination ROI is chunked into 3 vertical stripes: the first and the third are processed by accurate kernels and the central one is processed by the fast one. In order to get the maximum available speed of execution, the projection of destination ROI onto image addresses must be 64 bytes aligned. This is always true if the values `(int)((void*)(pDst + dstRoi.x))` and `(int)((void*)(pDst + dstRoi.x + dstRoi.width))` are multiples of 64. Another rule of thumb is to specify destination ROI in such way that left and right sides of the projected image are separated from the ROI by at least 63 bytes from each side. However, this requires the whole ROI to be part of allocated memory. In case when the conditions above are not satisfied, the function may decrease in speed slightly and will return `NPP_MISALIGNED_DST_ROI_WARNING` warning.

Parameters:

pSrc [Source-Image Pointer](#).

srcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

srcRoi Source ROI

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

dstRoi Destination ROI

coeffs Perspective transform coefficients

interpolation Interpolation mode: can be `NPPI_INTER_NN`, `NPPI_INTER_LINEAR` or `NPPI_INTER_CUBIC`

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_RECT_ERROR](#) Indicates an error condition if width or height of the intersection of the *srcRoi* and source image is less than or equal to 1
- [NPP_WRONG_INTERSECTION_ROI_ERROR](#) Indicates an error condition if *srcRoi* has no intersection with the source image
- [NPP_INTERPOLATION_ERROR](#) Indicates an error condition if interpolation has an illegal value

- [NPP_COEFF_ERROR](#) Indicates an error condition if coefficient values are invalid
- [NPP_WRONG_INTERSECTION_QUAD_WARNING](#) Indicates a warning that no operation is performed if the transformed source ROI has no intersection with the destination ROI
- [NPP_MISALIGNED_DST_ROI_WARNING](#) Indicates a warning that the speed of primitive execution was reduced due to destination ROI

7.4.1.363 `NppStatus nppiWarpPerspectiveBack_8u_C3R (const Npp8u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp8u * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[3][3], int interpolation)`

Inverse perspective transform of an image (8bit unsigned integer, three channels).

See also:

[nppiWarpPerspectiveBack_8u_C1R](#)

7.4.1.364 `NppStatus nppiWarpPerspectiveBack_8u_C4R (const Npp8u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp8u * pDst, int nDstStep, NppiRect dstRoi, const double coeffs[3][3], int interpolation)`

Inverse perspective transform of an image (8bit unsigned integer, four channels).

See also:

[nppiWarpPerspectiveBack_8u_C1R](#)

7.4.1.365 `NppStatus nppiWarpPerspectiveBack_8u_P3R (const Npp8u * pSrc[3], NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp8u * pDst[3], int nDstStep, NppiRect dstRoi, const double coeffs[3][3], int interpolation)`

Inverse perspective transform of an image (8bit unsigned integer, three planes).

See also:

[nppiWarpPerspectiveBack_8u_C1R](#)

7.4.1.366 `NppStatus nppiWarpPerspectiveBack_8u_P4R (const Npp8u * pSrc[4], NppiSize srcSize, int nSrcStep, NppiRect srcRoi, Npp8u * pDst[4], int nDstStep, NppiRect dstRoi, const double coeffs[3][3], int interpolation)`

Inverse perspective transform of an image (8bit unsigned integer, four planes).

See also:

[nppiWarpPerspectiveBack_8u_C1R](#)

7.4.1.367 `NppStatus nppiWarpPerspectiveQuad_16u_AC4R (const Npp16u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp16u * pDst, int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Perspective transform of an image (16bit unsigned integer, four channels RGBA).

See also:

[nppiWarpPerspectiveQuad_16u_C1R](#)

7.4.1.368 `NppStatus nppiWarpPerspectiveQuad_16u_C1R (const Npp16u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp16u * pDst, int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Perspective transform of an image (16bit unsigned integer, single channel).

This function performs perspective warping of a the specified quadrangle in the source image to the specified quadrangle in the destination image. The function `nppiWarpPerspectiveQuad` uses the same formulas for pixel mapping as in `nppiWarpPerspective` function. The transform coefficients are computed internally. The transformed part of the source image is resampled using the specified interpolation method and written to the destination ROI.

NPPI specific recommendation: The function operates using 2 types of kernels: fast and accurate. The fast method is about 4 times faster than its accurate variant, but does not perform memory access checks and requires the destination ROI to be 64 bytes aligned. Hence any destination ROI is chunked into 3 vertical stripes: the first and the third are processed by accurate kernels and the central one is processed by the fast one. In order to get the maximum available speed of execution, the projection of destination ROI onto image addresses must be 64 bytes aligned. This is always true if the values `(int)((void*)(pDst + dstRoi.x))` and `(int)((void*)(pDst + dstRoi.x + dstRoi.width))` are multiples of 64. Another rule of thumb is to specify destination ROI in such way that left and right sides of the projected image are separated from the ROI by at least 63 bytes from each side. However, this requires the whole ROI to be part of allocated memory. In case when the conditions above are not satisfied, the function may decrease in speed slightly and will return `NPP_MISALIGNED_DST_ROI_WARNING` warning.

Parameters:

pSrc [Source-Image Pointer](#).

srcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

srcRoi Source ROI

srcQuad Source quadrangle

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

dstRoi Destination ROI

dstQuad Destination quadrangle

interpolation Interpolation mode: can be `NPPI_INTER_NN`, `NPPI_INTER_LINEAR` or `NPPI_INTER_CUBIC`

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_RECT_ERROR](#) Indicates an error condition if width or height of the intersection of the srcRoi and source image is less than or equal to 1
- [NPP_WRONG_INTERSECTION_ROI_ERROR](#) Indicates an error condition if srcRoi has no intersection with the source image
- [NPP_INTERPOLATION_ERROR](#) Indicates an error condition if interpolation has an illegal value
- [NPP_COEFF_ERROR](#) Indicates an error condition if coefficient values are invalid
- [NPP_WRONG_INTERSECTION_QUAD_WARNING](#) Indicates a warning that no operation is performed if the transformed source ROI has no intersection with the destination ROI
- [NPP_MISALIGNED_DST_ROI_WARNING](#) Indicates a warning that the speed of primitive execution was reduced due to destination ROI

7.4.1.369 `NppStatus nppiWarpPerspectiveQuad_16u_C3R (const Npp16u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp16u * pDst, int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Perspective transform of an image (16bit unsigned integer, three channels).

See also:

[nppiWarpPerspectiveQuad_16u_C1R](#)

7.4.1.370 `NppStatus nppiWarpPerspectiveQuad_16u_C4R (const Npp16u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp16u * pDst, int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Perspective transform of an image (16bit unsigned integer, four channels).

See also:

[nppiWarpPerspectiveQuad_16u_C1R](#)

7.4.1.371 `NppStatus nppiWarpPerspectiveQuad_16u_P3R (const Npp16u * pSrc[3], NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp16u * pDst[3], int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Perspective transform of an image (16bit unsigned integer, three planes).

See also:

[nppiWarpPerspectiveQuad_16u_C1R](#)

7.4.1.372 `NppStatus nppiWarpPerspectiveQuad_16u_P4R (const Npp16u * pSrc[4], NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp16u * pDst[4], int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Perspective transform of an image (16bit unsigned integer, four planes).

See also:

[nppiWarpPerspectiveQuad_16u_C1R](#)

7.4.1.373 `NppStatus nppiWarpPerspectiveQuad_32f_AC4R (const Npp32f * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp32f * pDst, int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Perspective transform of an image (32bit float, four channels RGBA).

See also:

[nppiWarpPerspectiveQuad_32f_C1R](#)

7.4.1.374 `NppStatus nppiWarpPerspectiveQuad_32f_C1R (const Npp32f * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp32f * pDst, int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Perspective transform of an image (32bit float, single channel).

This function performs perspective warping of a the specified quadrangle in the source image to the specified quadrangle in the destination image. The function `nppiWarpPerspectiveQuad` uses the same formulas for pixel mapping as in `nppiWarpPerspective` function. The transform coefficients are computed internally. The transformed part of the source image is resampled using the specified interpolation method and written to the destination ROI.

Parameters:

pSrc [Source-Image Pointer](#).

srcSize Size of source image in pixels

nSrcStep [Source-Image Line Step](#).

srcRoi Source ROI

srcQuad Source quadrangle

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

dstRoi Destination ROI

dstQuad Destination quadrangle

interpolation Interpolation mode: can be `NPPI_INTER_NN`, `NPPI_INTER_LINEAR` or `NPPI_INTER_CUBIC`

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_RECT_ERROR](#) Indicates an error condition if width or height of the intersection of the *srcRoi* and source image is less than or equal to 1
- [NPP_WRONG_INTERSECTION_ROI_ERROR](#) Indicates an error condition if *srcRoi* has no intersection with the source image
- [NPP_INTERPOLATION_ERROR](#) Indicates an error condition if interpolation has an illegal value
- [NPP_COEFF_ERROR](#) Indicates an error condition if coefficient values are invalid
- [NPP_WRONG_INTERSECTION_QUAD_WARNING](#) Indicates a warning that no operation is performed if the transformed source ROI has no intersection with the destination ROI
- [NPP_MISALIGNED_DST_ROI_WARNING](#) Indicates a warning that the speed of primitive execution was reduced due to destination ROI

7.4.1.375 `NppStatus nppiWarpPerspectiveQuad_32f_C3R (const Npp32f * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp32f * pDst, int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Perspective transform of an image (32bit float, three channels).

See also:

[nppiWarpPerspectiveQuad_32f_C1R](#)

7.4.1.376 `NppStatus nppiWarpPerspectiveQuad_32f_C4R (const Npp32f * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp32f * pDst, int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Perspective transform of an image (32bit float, four channels).

See also:

[nppiWarpPerspectiveQuad_32f_C1R](#)

7.4.1.377 `NppStatus nppiWarpPerspectiveQuad_32f_P3R (const Npp32f * pSrc[3], NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp32f * pDst[3], int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Perspective transform of an image (32bit float, three planes).

See also:

[nppiWarpPerspectiveQuad_32f_C1R](#)

7.4.1.378 `NppStatus nppiWarpPerspectiveQuad_32f_P4R (const Npp32f * pSrc[4], NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp32f * pDst[4], int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Perspective transform of an image (32bit float, four planes).

See also:

[nppiWarpPerspectiveQuad_32f_C1R](#)

7.4.1.379 `NppStatus nppiWarpPerspectiveQuad_32s_AC4R (const Npp32s * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp32s * pDst, int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Perspective transform of an image (32bit signed integer, four channels RGBA).

See also:

[nppiWarpPerspectiveQuad_32s_C1R](#)

7.4.1.380 `NppStatus nppiWarpPerspectiveQuad_32s_C1R (const Npp32s * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp32s * pDst, int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Perspective transform of an image (32bit signed integer, single channel).

This function performs perspective warping of a the specified quadrangle in the source image to the specified quadrangle in the destination image. The function `nppiWarpPerspectiveQuad` uses the same formulas for pixel mapping as in `nppiWarpPerspective` function. The transform coefficients are computed internally. The transformed part of the source image is resampled using the specified interpolation method and written to the destination ROI.

Parameters:

pSrc Source-Image Pointer.

srcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

srcRoi Source ROI

srcQuad Source quadrangle

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

dstRoi Destination ROI

dstQuad Destination quadrangle

interpolation Interpolation mode: can be `NPPI_INTER_NN`, `NPPI_INTER_LINEAR` or `NPPI_INTER_CUBIC`

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_RECT_ERROR](#) Indicates an error condition if width or height of the intersection of the *srcRoi* and source image is less than or equal to 1
- [NPP_WRONG_INTERSECTION_ROI_ERROR](#) Indicates an error condition if *srcRoi* has no intersection with the source image
- [NPP_INTERPOLATION_ERROR](#) Indicates an error condition if interpolation has an illegal value
- [NPP_COEFF_ERROR](#) Indicates an error condition if coefficient values are invalid
- [NPP_WRONG_INTERSECTION_QUAD_WARNING](#) Indicates a warning that no operation is performed if the transformed source ROI has no intersection with the destination ROI
- [NPP_MISALIGNED_DST_ROI_WARNING](#) Indicates a warning that the speed of primitive execution was reduced due to destination ROI

7.4.1.381 `NppStatus nppiWarpPerspectiveQuad_32s_C3R (const Npp32s * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp32s * pDst, int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Perspective transform of an image (32bit signed integer, three channels).

See also:

[nppiWarpPerspectiveQuad_32s_C1R](#)

7.4.1.382 `NppStatus nppiWarpPerspectiveQuad_32s_C4R (const Npp32s * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp32s * pDst, int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Perspective transform of an image (32bit signed integer, four channels).

See also:

[nppiWarpPerspectiveQuad_32s_C1R](#)

7.4.1.383 `NppStatus nppiWarpPerspectiveQuad_32s_P3R (const Npp32s * pSrc[3], NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp32s * pDst[3], int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Perspective transform of an image (32bit signed integer, three planes).

See also:

[nppiWarpPerspectiveQuad_32s_C1R](#)

7.4.1.384 `NppStatus nppiWarpPerspectiveQuad_32s_P4R (const Npp32s * pSrc[4], NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp32s * pDst[4], int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Perspective transform of an image (32bit signed integer, four planes).

See also:

[nppiWarpPerspectiveQuad_32s_C1R](#)

7.4.1.385 `NppStatus nppiWarpPerspectiveQuad_8u_AC4R (const Npp8u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp8u * pDst, int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Perspective transform of an image (8bit unsigned integer, four channels RGBA).

See also:

[nppiWarpPerspectiveQuad_8u_C1R](#)

7.4.1.386 `NppStatus nppiWarpPerspectiveQuad_8u_C1R (const Npp8u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp8u * pDst, int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Perspective transform of an image (8bit unsigned integer, single channel).

This function performs perspective warping of a the specified quadrangle in the source image to the specified quadrangle in the destination image. The function `nppiWarpPerspectiveQuad` uses the same formulas for pixel mapping as in `nppiWarpPerspective` function. The transform coefficients are computed internally.

The transformed part of the source image is resampled using the specified interpolation method and written to the destination ROI.

NPPI specific recommendation: The function operates using 2 types of kernels: fast and accurate. The fast method is about 4 times faster than its accurate variant, but does not perform memory access checks and requires the destination ROI to be 64 bytes aligned. Hence any destination ROI is chunked into 3 vertical stripes: the first and the third are processed by accurate kernels and the central one is processed by the fast one. In order to get the maximum available speed of execution, the projection of destination ROI onto image addresses must be 64 bytes aligned. This is always true if the values `(int)((void *) (pDst + dstRoi.x))` and `(int)((void *) (pDst + dstRoi.x + dstRoi.width))` are multiples of 64. Another rule of thumb is to specify destination ROI in such way that left and right sides of the projected image are separated from the ROI by at least 63 bytes from each side. However, this requires the whole ROI to be part of allocated memory. In case when the conditions above are not satisfied, the function may decrease in speed slightly and will return `NPP_MISALIGNED_DST_ROI_WARNING` warning.

Parameters:

pSrc Source-Image Pointer.

srcSize Size of source image in pixels

nSrcStep Source-Image Line Step.

srcRoi Source ROI

srcQuad Source quadrangle

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

dstRoi Destination ROI

dstQuad Destination quadrangle

interpolation Interpolation mode: can be `NPPI_INTER_NN`, `NPPI_INTER_LINEAR` or `NPPI_INTER_CUBIC`

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

- [NPP_RECT_ERROR](#) Indicates an error condition if width or height of the intersection of the *srcRoi* and source image is less than or equal to 1
- [NPP_WRONG_INTERSECTION_ROI_ERROR](#) Indicates an error condition if *srcRoi* has no intersection with the source image
- [NPP_INTERPOLATION_ERROR](#) Indicates an error condition if interpolation has an illegal value
- [NPP_COEFF_ERROR](#) Indicates an error condition if coefficient values are invalid
- [NPP_WRONG_INTERSECTION_QUAD_WARNING](#) Indicates a warning that no operation is performed if the transformed source ROI has no intersection with the destination ROI
- [NPP_MISALIGNED_DST_ROI_WARNING](#) Indicates a warning that the speed of primitive execution was reduced due to destination ROI

7.4.1.387 `NppStatus nppiWarpPerspectiveQuad_8u_C3R (const Npp8u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp8u * pDst, int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Perspective transform of an image (8bit unsigned integer, three channels).

See also:

[nppiWarpPerspectiveQuad_8u_C1R](#)

7.4.1.388 `NppStatus nppiWarpPerspectiveQuad_8u_C4R (const Npp8u * pSrc, NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp8u * pDst, int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Perspective transform of an image (8bit unsigned integer, four channels).

See also:

[nppiWarpPerspectiveQuad_8u_C1R](#)

7.4.1.389 `NppStatus nppiWarpPerspectiveQuad_8u_P3R (const Npp8u * pSrc[3], NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp8u * pDst[3], int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Perspective transform of an image (8bit unsigned integer, three planes).

See also:

[nppiWarpPerspectiveQuad_8u_C1R](#)

7.4.1.390 `NppStatus nppiWarpPerspectiveQuad_8u_P4R (const Npp8u * pSrc[4], NppiSize srcSize, int nSrcStep, NppiRect srcRoi, const double srcQuad[4][2], Npp8u * pDst[4], int nDstStep, NppiRect dstRoi, const double dstQuad[4][2], int interpolation)`

Perspective transform of an image (8bit unsigned integer, four planes).

See also:

[nppiWarpPerspectiveQuad_8u_C1R](#)

7.4.1.391 `NppStatus nppiYCbCr420ToRGB_8u_P3C3R (const Npp8u * const * pSrc, int nSrcStep[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

3 channel 8-bit unsigned planar YCbCr420 to packed RGB color conversion.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.392 `NppStatus nppiYCbCr420ToYCbCr411_8u_P3P2R (const Npp8u *const *pSrc, int aSrcStep[3], Npp8u *pDstY, int nDstYStep, Npp8u *pDstCbCr, int nDstCbCrStep, NppiSize oSizeROI)`

3 channel 8-bit unsigned planar YCbCr:420 to YCbCr:411 resampling.

Parameters:

pSrc Array of pointers to the source image planes.
aSrcStep Array with distances in bytes between starts of consecutive lines of the source image planes.
pDstY [Destination-Image Pointer](#). Y-channel.
nDstYStep [Destination-Image Line Step](#). Y-channel.
pDstCbCr [Destination-Image Pointer](#). CbCr image.
nDstCbCrStep [Destination-Image Line Step](#). CbCr image.
oSizeROI [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.393 `NppStatus nppiYCbCr420ToYCbCr422_8u_P3R (const Npp8u *const *pSrc, int nSrcStep[3], Npp8u **pDst, int nDstStep[3], NppiSize oSizeROI)`

3 channel 8-bit unsigned planar YCbCr:420 to YCbCr:422 resampling.

Parameters:

pSrc [Source-Image Pointer](#).
nSrcStep [Source-Image Line Step](#).
pDst [Destination-Image Pointer](#).
nDstStep [Destination-Image Line Step](#).
oSizeROI [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.4.1.394 `NppStatus nppiYCbCr422ToRGB_8u_C2C3R (const Npp8u *pSrc, int nSrcStep, Npp8u *pDst, int nDstStep, NppiSize oSizeROI)`

2 channel 8-bit unsigned YCbCr422 to 3 channel packed RGB color conversion.
 images.

Parameters:

pSrc [Source-Image Pointer](#).
nSrcStep [Source-Image Line Step](#).
pDst [Destination-Image Pointer](#).

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.395 `NppStatus nppiYCbCr422ToYCbCr411_8u_P3R (const Npp8u *const * pSrc, int nSrcStep[3], Npp8u ** pDst, int nDstStep[3], NppiSize oSizeROI)`

3 channel 8-bit unsigned planar YCbCr:422 to YCbCr:411 resampling.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.396 `NppStatus nppiYCbCr422ToYCbCr420_8u_P3R (const Npp8u *const * pSrc, int nSrcStep[3], Npp8u ** pDst, int nDstStep[3], NppiSize oSizeROI)`

3 channel 8-bit unsigned planar YCbCr:422 to YCbCr:420 resampling.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.397 `NppStatus nppiYCbCrToRGB_8u_AC4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

4 channel 8-bit unsigned packed YCbCr to RGB color conversion, not affecting Alpha.

Alpha channel is the last channel and is not processed.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.398 `NppStatus nppiYCbCrToRGB_8u_C3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

3 channel 8-bit unsigned packed YCbCr to RGB color conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.4.1.399 `NppStatus nppiYCbCrToRGB_8u_P3R (const Npp8u *const * pSrc, int nSrcStep, Npp8u ** pDst, int nDstStep, NppiSize oSizeROI)`

3 channel 8-bit unsigned planar YCbCr to RGB color conversion.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.5 NPP Signal Processing

Memory Allocation

Signal-allocator methods for allocating 1D arrays of data in device memory.

All allocators have size parameters to specify the size of the signal (1D array) being allocated.

The allocator methods return a pointer to the newly allocated memory of appropriate type. If device-memory allocation is not possible due to resource constraints the allocators return 0 (i.e. NULL pointer).

All signal allocators allocate memory aligned such that it is beneficial to the performance of the majority of the signal-processing primitives. It is no mandatory however to use these allocators. Any valid CUDA device-memory pointers can be passed to NPP primitives.

- `Npp8u * nppsMalloc_8u` (int nSize)
8-bit unsigned signal allocator.
- `Npp16u * nppsMalloc_16u` (int nSize)
16-bit unsigned signal allocator.
- `Npp16s * nppsMalloc_16s` (int nSize)
16-bit signal allocator.
- `Npp16sc * nppsMalloc_16sc` (int nSize)
16-bit complex-value signal allocator.
- `Npp32u * nppsMalloc_32u` (int nSize)
32-bit unsigned signal allocator.
- `Npp32s * nppsMalloc_32s` (int nSize)
32-bit integer signal allocator.
- `Npp32sc * nppsMalloc_32sc` (int nSize)
32-bit complex integer signal allocator.
- `Npp32f * nppsMalloc_32f` (int nSize)
32-bit float signal allocator.
- `Npp32fc * nppsMalloc_32fc` (int nSize)
32-bit complex float signal allocator.
- `Npp64s * nppsMalloc_64s` (int nSize)
64-bit long integer signal allocator.
- `Npp64sc * nppsMalloc_64sc` (int nSize)
64-bit complex long integer signal allocator.
- `Npp64f * nppsMalloc_64f` (int nSize)
64-bit float (double) signal allocator.
- `Npp64fc * nppsMalloc_64fc` (int nSize)

64-bit complex complex signal allocator.

- void [nppsFree](#) (void *pValues)
Free method for any 2D allocated memory.

Set

Set methods for 1D vectors of various types.

The copy methods operate on vector data given as a pointer to the underlying data-type (e.g. 8-bit vectors would be passed as pointers to Npp8u type) and length of the vectors, i.e. the number of items.

- [NppStatus nppsSet_8u](#) ([Npp8u](#) nValue, [Npp8u](#) *pDst, int nLength)
8-bit unsigned char, vector set method.
- [NppStatus nppsSet_16s](#) ([Npp16s](#) nValue, [Npp16s](#) *pDst, int nLength)
16-bit integer, vector set method.
- [NppStatus nppsSet_16sc](#) ([Npp16sc](#) nValue, [Npp16sc](#) *pDst, int nLength)
16-bit integer complex, vector set method.
- [NppStatus nppsSet_32s](#) ([Npp32s](#) nValue, [Npp32s](#) *pDst, int nLength)
32-bit integer, vector set method.
- [NppStatus nppsSet_32sc](#) ([Npp32sc](#) nValue, [Npp32sc](#) *pDst, int nLength)
32-bit integer complex, vector set method.
- [NppStatus nppsSet_32f](#) ([Npp32f](#) nValue, [Npp32f](#) *pDst, int nLength)
32-bit float, vector set method.
- [NppStatus nppsSet_32fc](#) ([Npp32fc](#) nValue, [Npp32fc](#) *pDst, int nLength)
32-bit float complex, vector set method.
- [NppStatus nppsSet_64s](#) ([Npp64s](#) nValue, [Npp64s](#) *pDst, int nLength)
64-bit long long integer, vector set method.
- [NppStatus nppsSet_64sc](#) ([Npp64sc](#) nValue, [Npp64sc](#) *pDst, int nLength)
64-bit long long integer complex, vector set method.
- [NppStatus nppsSet_64f](#) ([Npp64f](#) nValue, [Npp64f](#) *pDst, int nLength)
64-bit double, vector set method.
- [NppStatus nppsSet_64fc](#) ([Npp64fc](#) nValue, [Npp64fc](#) *pDst, int nLength)
64-bit double complex, vector set method.

Zero

Set signals to zero.

- `NppStatus nppsZero_8u (Npp8u *pDst, int nLength)`
8-bit unsigned char, vector zero method.
- `NppStatus nppsZero_16s (Npp16s *pDst, int nLength)`
16-bit integer, vector zero method.
- `NppStatus nppsZero_16sc (Npp16sc *pDst, int nLength)`
16-bit integer complex, vector zero method.
- `NppStatus nppsZero_32s (Npp32s *pDst, int nLength)`
32-bit integer, vector zero method.
- `NppStatus nppsZero_32sc (Npp32sc *pDst, int nLength)`
32-bit integer complex, vector zero method.
- `NppStatus nppsZero_32f (Npp32f *pDst, int nLength)`
32-bit float, vector zero method.
- `NppStatus nppsZero_32fc (Npp32fc *pDst, int nLength)`
32-bit float complex, vector zero method.
- `NppStatus nppsZero_64s (Npp64s *pDst, int nLength)`
64-bit long long integer, vector zero method.
- `NppStatus nppsZero_64sc (Npp64sc *pDst, int nLength)`
64-bit long long integer complex, vector zero method.
- `NppStatus nppsZero_64f (Npp64f *pDst, int nLength)`
64-bit double, vector zero method.
- `NppStatus nppsZero_64fc (Npp64fc *pDst, int nLength)`
64-bit double complex, vector zero method.

Copy

Copy methods for various type signals.

Copy methods operate on signal data given as a pointer to the underlying data-type (e.g. 8-bit vectors would be passed as pointers to `Npp8u` type) and length of the vectors, i.e. the number of items.

- `NppStatus nppsCopy_8u (const Npp8u *pSrc, Npp8u *pDst, int len)`
8-bit unsigned char, vector copy method
- `NppStatus nppsCopy_16s (const Npp16s *pSrc, Npp16s *pDst, int len)`
16-bit signed short, vector copy method.

- `NppStatus nppsCopy_32s` (const `Npp32s` *pSrc, `Npp32s` *pDst, int nLength)
32-bit signed integer, vector copy method.
- `NppStatus nppsCopy_32f` (const `Npp32f` *pSrc, `Npp32f` *pDst, int len)
32-bit float, vector copy method.
- `NppStatus nppsCopy_64s` (const `Npp64s` *pSrc, `Npp64s` *pDst, int len)
64-bit signed integer, vector copy method.
- `NppStatus nppsCopy_16sc` (const `Npp16sc` *pSrc, `Npp16sc` *pDst, int len)
16-bit complex short, vector copy method.
- `NppStatus nppsCopy_32sc` (const `Npp32sc` *pSrc, `Npp32sc` *pDst, int len)
32-bit complex signed integer, vector copy method.
- `NppStatus nppsCopy_32fc` (const `Npp32fc` *pSrc, `Npp32fc` *pDst, int len)
32-bit complex float, vector copy method.
- `NppStatus nppsCopy_64sc` (const `Npp64sc` *pSrc, `Npp64sc` *pDst, int len)
64-bit complex signed integer, vector copy method.
- `NppStatus nppsCopy_64fc` (const `Npp64fc` *pSrc, `Npp64fc` *pDst, int len)
64-bit complex double, vector copy method.

AddC

Adds a constant value to each sample of a signal.

- `NppStatus nppsAddC_8u_ISfs` (`Npp8u` nValue, `Npp8u` *pSrcDst, int nLength, int nScaleFactor)
8-bit unsigned char in place signal add constant, scale, then clamp to saturated value
- `NppStatus nppsAddC_8u_Sfs` (const `Npp8u` *pSrc, `Npp8u` nValue, `Npp8u` *pDst, int nLength, int nScaleFactor)
8-bit unsigned charvector add constant, scale, then clamp to saturated value.
- `NppStatus nppsAddC_16u_ISfs` (`Npp16u` nValue, `Npp16u` *pSrcDst, int nLength, int nScaleFactor)
16-bit unsigned short in place signal add constant, scale, then clamp to saturated value.
- `NppStatus nppsAddC_16u_Sfs` (const `Npp16u` *pSrc, `Npp16u` nValue, `Npp16u` *pDst, int nLength, int nScaleFactor)
16-bit unsigned short vector add constant, scale, then clamp to saturated value.
- `NppStatus nppsAddC_16s_ISfs` (`Npp16s` nValue, `Npp16s` *pSrcDst, int nLength, int nScaleFactor)
16-bit signed short in place signal add constant, scale, then clamp to saturated value.
- `NppStatus nppsAddC_16s_Sfs` (const `Npp16s` *pSrc, `Npp16s` nValue, `Npp16s` *pDst, int nLength, int nScaleFactor)

16-bit signed short signal add constant, scale, then clamp to saturated value.

- **NppStatus nppsAddC_16sc_ISfs** (**Npp16sc** nValue, **Npp16sc** *pSrcDst, int nLength, int nScaleFactor)

16-bit integer complex number (16 bit real, 16 bit imaginary) signal add constant, scale, then clamp to saturated value.

- **NppStatus nppsAddC_16sc_Sfs** (const **Npp16sc** *pSrc, **Npp16sc** nValue, **Npp16sc** *pDst, int nLength, int nScaleFactor)

16-bit integer complex number (16 bit real, 16 bit imaginary) signal add constant, scale, then clamp to saturated value.

- **NppStatus nppsAddC_32s_ISfs** (**Npp32s** nValue, **Npp32s** *pSrcDst, int nLength, int nScaleFactor)

32-bit signed integer in place signal add constant and scale.

- **NppStatus nppsAddC_32s_Sfs** (const **Npp32s** *pSrc, **Npp32s** nValue, **Npp32s** *pDst, int nLength, int nScaleFactor)

32-bit signed integersignal add constant and scale.

- **NppStatus nppsAddC_32sc_ISfs** (**Npp32sc** nValue, **Npp32sc** *pSrcDst, int nLength, int nScaleFactor)

32-bit integer complex number (32 bit real, 32 bit imaginary) in place signal add constant and scale.

- **NppStatus nppsAddC_32sc_Sfs** (const **Npp32sc** *pSrc, **Npp32sc** nValue, **Npp32sc** *pDst, int nLength, int nScaleFactor)

32-bit integer complex number (32 bit real, 32 bit imaginary) signal add constant and scale.

- **NppStatus nppsAddC_32f_I** (**Npp32f** nValue, **Npp32f** *pSrcDst, int nLength)

32-bit floating point in place signal add constant.

- **NppStatus nppsAddC_32f** (const **Npp32f** *pSrc, **Npp32f** nValue, **Npp32f** *pDst, int nLength)

32-bit floating point signal add constant.

- **NppStatus nppsAddC_32fc_I** (**Npp32fc** nValue, **Npp32fc** *pSrcDst, int nLength)

32-bit floating point complex number (32 bit real, 32 bit imaginary) in place signal add constant.

- **NppStatus nppsAddC_32fc** (const **Npp32fc** *pSrc, **Npp32fc** nValue, **Npp32fc** *pDst, int nLength)

32-bit floating point complex number (32 bit real, 32 bit imaginary) signal add constant.

- **NppStatus nppsAddC_64f_I** (**Npp64f** nValue, **Npp64f** *pSrcDst, int nLength)

64-bit floating point, in place signal add constant.

- **NppStatus nppsAddC_64f** (const **Npp64f** *pSrc, **Npp64f** nValue, **Npp64f** *pDst, int nLength)

64-bit floating pointsignal add constant.

- **NppStatus nppsAddC_64fc_I** (**Npp64fc** nValue, **Npp64fc** *pSrcDst, int nLength)

64-bit floating point complex number (64 bit real, 64 bit imaginary) in place signal add constant.

- **NppStatus nppsAddC_64fc** (const **Npp64fc** *pSrc, **Npp64fc** nValue, **Npp64fc** *pDst, int nLength)

64-bit floating point complex number (64 bit real, 64 bit imaginary) signal add constant.

AddProductC

Adds product of a constant and each sample of a source signal to each sample of the destination signal.

- **NppStatus** **nppsAddProductC_8u_ISfs** (**Npp8u** nValue, **Npp8u** *pSrcDst, int nLength, int nScaleFactor)
8-bit unsigned char in place signal add product of signal times constant to destination signal, scale, then clamp to saturated value
- **NppStatus** **nppsAddProductC_8u_Sfs** (const **Npp8u** *pSrc, **Npp8u** nValue, **Npp8u** *pDst, int nLength, int nScaleFactor)
8-bit unsigned char add product of signal times constant to destination signal, scale, then clamp to saturated value.
- **NppStatus** **nppsAddProductC_16u_ISfs** (**Npp16u** nValue, **Npp16u** *pSrcDst, int nLength, int nScaleFactor)
16-bit unsigned short in place signal add product of signal times constant to destination signal, scale, then clamp to saturated value.
- **NppStatus** **nppsAddProductC_16u_Sfs** (const **Npp16u** *pSrc, **Npp16u** nValue, **Npp16u** *pDst, int nLength, int nScaleFactor)
16-bit unsigned short add product of signal times constant to destination signal, scale, then clamp to saturated value.
- **NppStatus** **nppsAddProductC_16s_ISfs** (**Npp16s** nValue, **Npp16s** *pSrcDst, int nLength, int nScaleFactor)
16-bit signed short in place signal add product of signal times constant to destination signal, scale, then clamp to saturated value.
- **NppStatus** **nppsAddProductC_16s_Sfs** (const **Npp16s** *pSrc, **Npp16s** nValue, **Npp16s** *pDst, int nLength, int nScaleFactor)
16-bit signed short signal add product of signal times constant to destination signal, scale, then clamp to saturated value.
- **NppStatus** **nppsAddProductC_16sc_ISfs** (**Npp16sc** nValue, **Npp16sc** *pSrcDst, int nLength, int nScaleFactor)
16-bit integer complex number (16 bit real, 16 bit imaginary)signal add product of signal times constant to destination signal, scale, then clamp to saturated value.
- **NppStatus** **nppsAddProductC_16sc_Sfs** (const **Npp16sc** *pSrc, **Npp16sc** nValue, **Npp16sc** *pDst, int nLength, int nScaleFactor)
16-bit integer complex number (16 bit real, 16 bit imaginary)signal add product of signal times constant to destination signal, scale, then clamp to saturated value.
- **NppStatus** **nppsAddProductC_32s_ISfs** (**Npp32s** nValue, **Npp32s** *pSrcDst, int nLength, int nScaleFactor)
32-bit signed integer in place signal add product of signal times constant to destination signal and scale.
- **NppStatus** **nppsAddProductC_32s_Sfs** (const **Npp32s** *pSrc, **Npp32s** nValue, **Npp32s** *pDst, int nLength, int nScaleFactor)
32-bit signed integer signal add product of signal times constant to destination signal and scale.

- **NppStatus nppsAddProductC_32sc_ISfs** (**Npp32sc** nValue, **Npp32sc** *pSrcDst, int nLength, int nScaleFactor)
32-bit integer complex number (32 bit real, 32 bit imaginary) in place signal add product of signal times constant to destination signal and scale.
- **NppStatus nppsAddProductC_32sc_Sfs** (const **Npp32sc** *pSrc, **Npp32sc** nValue, **Npp32sc** *pDst, int nLength, int nScaleFactor)
32-bit integer complex number (32 bit real, 32 bit imaginary) signal add product of signal times constant to destination signal and scale.
- **NppStatus nppsAddProductC_32f_I** (**Npp32f** nValue, **Npp32f** *pSrcDst, int nLength)
32-bit floating point in place signal add product of signal times constant to destination signal.
- **NppStatus nppsAddProductC_32f** (const **Npp32f** *pSrc, **Npp32f** nValue, **Npp32f** *pDst, int nLength)
32-bit floating point signal add product of signal times constant to destination signal.

MulC

Multiplies each sample of a signal by a constant value.

- **NppStatus nppsMulC_8u_ISfs** (**Npp8u** nValue, **Npp8u** *pSrcDst, int nLength, int nScaleFactor)
8-bit unsigned char in place signal times constant, scale, then clamp to saturated value
- **NppStatus nppsMulC_8u_Sfs** (const **Npp8u** *pSrc, **Npp8u** nValue, **Npp8u** *pDst, int nLength, int nScaleFactor)
8-bit unsigned char signal times constant, scale, then clamp to saturated value.
- **NppStatus nppsMulC_16u_ISfs** (**Npp16u** nValue, **Npp16u** *pSrcDst, int nLength, int nScaleFactor)
16-bit unsigned short in place signal times constant, scale, then clamp to saturated value.
- **NppStatus nppsMulC_16u_Sfs** (const **Npp16u** *pSrc, **Npp16u** nValue, **Npp16u** *pDst, int nLength, int nScaleFactor)
16-bit unsigned short signal times constant, scale, then clamp to saturated value.
- **NppStatus nppsMulC_16s_ISfs** (**Npp16s** nValue, **Npp16s** *pSrcDst, int nLength, int nScaleFactor)
16-bit signed short in place signal times constant, scale, then clamp to saturated value.
- **NppStatus nppsMulC_16s_Sfs** (const **Npp16s** *pSrc, **Npp16s** nValue, **Npp16s** *pDst, int nLength, int nScaleFactor)
16-bit signed short signal times constant, scale, then clamp to saturated value.
- **NppStatus nppsMulC_16sc_ISfs** (**Npp16sc** nValue, **Npp16sc** *pSrcDst, int nLength, int nScaleFactor)
16-bit integer complex number (16 bit real, 16 bit imaginary) signal times constant, scale, then clamp to saturated value.
- **NppStatus nppsMulC_16sc_Sfs** (const **Npp16sc** *pSrc, **Npp16sc** nValue, **Npp16sc** *pDst, int nLength, int nScaleFactor)

16-bit integer complex number (16 bit real, 16 bit imaginary) signal times constant, scale, then clamp to saturated value.

- **NppStatus nppsMulC_32s_ISfs** (**Npp32s** nValue, **Npp32s** *pSrcDst, int nLength, int nScaleFactor)
32-bit signed integer in place signal times constant and scale.
- **NppStatus nppsMulC_32s_Sfs** (const **Npp32s** *pSrc, **Npp32s** nValue, **Npp32s** *pDst, int nLength, int nScaleFactor)
32-bit signed integer signal times constant and scale.
- **NppStatus nppsMulC_32sc_ISfs** (**Npp32sc** nValue, **Npp32sc** *pSrcDst, int nLength, int nScaleFactor)
32-bit integer complex number (32 bit real, 32 bit imaginary) in place signal times constant and scale.
- **NppStatus nppsMulC_32sc_Sfs** (const **Npp32sc** *pSrc, **Npp32sc** nValue, **Npp32sc** *pDst, int nLength, int nScaleFactor)
32-bit integer complex number (32 bit real, 32 bit imaginary) signal times constant and scale.
- **NppStatus nppsMulC_32f_I** (**Npp32f** nValue, **Npp32f** *pSrcDst, int nLength)
32-bit floating point in place signal times constant.
- **NppStatus nppsMulC_32f** (const **Npp32f** *pSrc, **Npp32f** nValue, **Npp32f** *pDst, int nLength)
32-bit floating point signal times constant.
- **NppStatus nppsMulC_Low_32f16s** (const **Npp32f** *pSrc, **Npp32f** nValue, **Npp16s** *pDst, int nLength)
32-bit floating point signal times constant with output converted to 16-bit signed integer.
- **NppStatus nppsMulC_32f16s_Sfs** (const **Npp32f** *pSrc, **Npp32f** nValue, **Npp16s** *pDst, int nLength, int nScaleFactor)
32-bit floating point signal times constant with output converted to 16-bit signed integer with scaling and saturation of output result.
- **NppStatus nppsMulC_32fc_I** (**Npp32fc** nValue, **Npp32fc** *pSrcDst, int nLength)
32-bit floating point complex number (32 bit real, 32 bit imaginary) in place signal times constant.
- **NppStatus nppsMulC_32fc** (const **Npp32fc** *pSrc, **Npp32fc** nValue, **Npp32fc** *pDst, int nLength)
32-bit floating point complex number (32 bit real, 32 bit imaginary) signal times constant.
- **NppStatus nppsMulC_64f_I** (**Npp64f** nValue, **Npp64f** *pSrcDst, int nLength)
64-bit floating point, in place signal times constant.
- **NppStatus nppsMulC_64f** (const **Npp64f** *pSrc, **Npp64f** nValue, **Npp64f** *pDst, int nLength)
64-bit floating point signal times constant.
- **NppStatus nppsMulC_64f64s_ISfs** (**Npp64f** nValue, **Npp64s** *pDst, int nLength, int nScaleFactor)
64-bit floating point signal times constant with in place conversion to 64-bit signed integer and with scaling and saturation of output result.
- **NppStatus nppsMulC_64fc_I** (**Npp64fc** nValue, **Npp64fc** *pSrcDst, int nLength)
64-bit floating point complex number (64 bit real, 64 bit imaginary) in place signal times constant.

- `NppStatus nppsMulC_64fc` (const `Npp64fc` *pSrc, `Npp64fc` nValue, `Npp64fc` *pDst, int nLength)
64-bit floating point complex number (64 bit real, 64 bit imaginary) signal times constant.

SubC

Subtracts a constant from each sample of a signal.

- `NppStatus nppsSubC_8u_ISfs` (`Npp8u` nValue, `Npp8u` *pSrcDst, int nLength, int nScaleFactor)
8-bit unsigned char in place signal subtract constant, scale, then clamp to saturated value
- `NppStatus nppsSubC_8u_Sfs` (const `Npp8u` *pSrc, `Npp8u` nValue, `Npp8u` *pDst, int nLength, int nScaleFactor)
8-bit unsigned char signal subtract constant, scale, then clamp to saturated value.
- `NppStatus nppsSubC_16u_ISfs` (`Npp16u` nValue, `Npp16u` *pSrcDst, int nLength, int nScaleFactor)
16-bit unsigned short in place signal subtract constant, scale, then clamp to saturated value.
- `NppStatus nppsSubC_16u_Sfs` (const `Npp16u` *pSrc, `Npp16u` nValue, `Npp16u` *pDst, int nLength, int nScaleFactor)
16-bit unsigned short signal subtract constant, scale, then clamp to saturated value.
- `NppStatus nppsSubC_16s_ISfs` (`Npp16s` nValue, `Npp16s` *pSrcDst, int nLength, int nScaleFactor)
16-bit signed short in place signal subtract constant, scale, then clamp to saturated value.
- `NppStatus nppsSubC_16s_Sfs` (const `Npp16s` *pSrc, `Npp16s` nValue, `Npp16s` *pDst, int nLength, int nScaleFactor)
16-bit signed short signal subtract constant, scale, then clamp to saturated value.
- `NppStatus nppsSubC_16sc_ISfs` (`Npp16sc` nValue, `Npp16sc` *pSrcDst, int nLength, int nScaleFactor)
16-bit integer complex number (16 bit real, 16 bit imaginary) signal subtract constant, scale, then clamp to saturated value.
- `NppStatus nppsSubC_16sc_Sfs` (const `Npp16sc` *pSrc, `Npp16sc` nValue, `Npp16sc` *pDst, int nLength, int nScaleFactor)
16-bit integer complex number (16 bit real, 16 bit imaginary) signal subtract constant, scale, then clamp to saturated value.
- `NppStatus nppsSubC_32s_ISfs` (`Npp32s` nValue, `Npp32s` *pSrcDst, int nLength, int nScaleFactor)
32-bit signed integer in place signal subtract constant and scale.
- `NppStatus nppsSubC_32s_Sfs` (const `Npp32s` *pSrc, `Npp32s` nValue, `Npp32s` *pDst, int nLength, int nScaleFactor)
32-bit signed integer signal subtract constant and scale.
- `NppStatus nppsSubC_32sc_ISfs` (`Npp32sc` nValue, `Npp32sc` *pSrcDst, int nLength, int nScaleFactor)
32-bit integer complex number (32 bit real, 32 bit imaginary) in place signal subtract constant and scale.

- `NppStatus nppsSubC_32sc_Sfs` (const `Npp32sc` *pSrc, `Npp32sc` nValue, `Npp32sc` *pDst, int nLength, int nScaleFactor)
32-bit integer complex number (32 bit real, 32 bit imaginary) signal subtract constant and scale.
- `NppStatus nppsSubC_32f_I` (`Npp32f` nValue, `Npp32f` *pSrcDst, int nLength)
32-bit floating point in place signal subtract constant.
- `NppStatus nppsSubC_32f` (const `Npp32f` *pSrc, `Npp32f` nValue, `Npp32f` *pDst, int nLength)
32-bit floating point signal subtract constant.
- `NppStatus nppsSubC_32fc_I` (`Npp32fc` nValue, `Npp32fc` *pSrcDst, int nLength)
32-bit floating point complex number (32 bit real, 32 bit imaginary) in place signal subtract constant.
- `NppStatus nppsSubC_32fc` (const `Npp32fc` *pSrc, `Npp32fc` nValue, `Npp32fc` *pDst, int nLength)
32-bit floating point complex number (32 bit real, 32 bit imaginary) signal subtract constant.
- `NppStatus nppsSubC_64f_I` (`Npp64f` nValue, `Npp64f` *pSrcDst, int nLength)
64-bit floating point, in place signal subtract constant.
- `NppStatus nppsSubC_64f` (const `Npp64f` *pSrc, `Npp64f` nValue, `Npp64f` *pDst, int nLength)
64-bit floating point signal subtract constant.
- `NppStatus nppsSubC_64fc_I` (`Npp64fc` nValue, `Npp64fc` *pSrcDst, int nLength)
64-bit floating point complex number (64 bit real, 64 bit imaginary) in place signal subtract constant.
- `NppStatus nppsSubC_64fc` (const `Npp64fc` *pSrc, `Npp64fc` nValue, `Npp64fc` *pDst, int nLength)
64-bit floating point complex number (64 bit real, 64 bit imaginary) signal subtract constant.

SubCRev

Subtracts each sample of a signal from a constant.

- `NppStatus nppsSubCRev_8u_ISfs` (`Npp8u` nValue, `Npp8u` *pSrcDst, int nLength, int nScaleFactor)
8-bit unsigned char in place signal subtract from constant, scale, then clamp to saturated value
- `NppStatus nppsSubCRev_8u_Sfs` (const `Npp8u` *pSrc, `Npp8u` nValue, `Npp8u` *pDst, int nLength, int nScaleFactor)
8-bit unsigned char signal subtract from constant, scale, then clamp to saturated value.
- `NppStatus nppsSubCRev_16u_ISfs` (`Npp16u` nValue, `Npp16u` *pSrcDst, int nLength, int nScaleFactor)
16-bit unsigned short in place signal subtract from constant, scale, then clamp to saturated value.
- `NppStatus nppsSubCRev_16u_Sfs` (const `Npp16u` *pSrc, `Npp16u` nValue, `Npp16u` *pDst, int nLength, int nScaleFactor)
16-bit unsigned short signal subtract from constant, scale, then clamp to saturated value.

- **NppStatus nppsSubCRev_16s_ISfs** (**Npp16s** nValue, **Npp16s** *pSrcDst, int nLength, int nScaleFactor)
16-bit signed short in place signal subtract from constant, scale, then clamp to saturated value.
- **NppStatus nppsSubCRev_16s_Sfs** (const **Npp16s** *pSrc, **Npp16s** nValue, **Npp16s** *pDst, int nLength, int nScaleFactor)
16-bit signed short signal subtract from constant, scale, then clamp to saturated value.
- **NppStatus nppsSubCRev_16sc_ISfs** (**Npp16sc** nValue, **Npp16sc** *pSrcDst, int nLength, int nScaleFactor)
16-bit integer complex number (16 bit real, 16 bit imaginary) signal subtract from constant, scale, then clamp to saturated value.
- **NppStatus nppsSubCRev_16sc_Sfs** (const **Npp16sc** *pSrc, **Npp16sc** nValue, **Npp16sc** *pDst, int nLength, int nScaleFactor)
16-bit integer complex number (16 bit real, 16 bit imaginary) signal subtract from constant, scale, then clamp to saturated value.
- **NppStatus nppsSubCRev_32s_ISfs** (**Npp32s** nValue, **Npp32s** *pSrcDst, int nLength, int nScaleFactor)
32-bit signed integer in place signal subtract from constant and scale.
- **NppStatus nppsSubCRev_32s_Sfs** (const **Npp32s** *pSrc, **Npp32s** nValue, **Npp32s** *pDst, int nLength, int nScaleFactor)
32-bit signed integersignal subtract from constant and scale.
- **NppStatus nppsSubCRev_32sc_ISfs** (**Npp32sc** nValue, **Npp32sc** *pSrcDst, int nLength, int nScaleFactor)
32-bit integer complex number (32 bit real, 32 bit imaginary) in place signal subtract from constant and scale.
- **NppStatus nppsSubCRev_32sc_Sfs** (const **Npp32sc** *pSrc, **Npp32sc** nValue, **Npp32sc** *pDst, int nLength, int nScaleFactor)
32-bit integer complex number (32 bit real, 32 bit imaginary) signal subtract from constant and scale.
- **NppStatus nppsSubCRev_32f_I** (**Npp32f** nValue, **Npp32f** *pSrcDst, int nLength)
32-bit floating point in place signal subtract from constant.
- **NppStatus nppsSubCRev_32f** (const **Npp32f** *pSrc, **Npp32f** nValue, **Npp32f** *pDst, int nLength)
32-bit floating point signal subtract from constant.
- **NppStatus nppsSubCRev_32fc_I** (**Npp32fc** nValue, **Npp32fc** *pSrcDst, int nLength)
32-bit floating point complex number (32 bit real, 32 bit imaginary) in place signal subtract from constant.
- **NppStatus nppsSubCRev_32fc** (const **Npp32fc** *pSrc, **Npp32fc** nValue, **Npp32fc** *pDst, int nLength)
32-bit floating point complex number (32 bit real, 32 bit imaginary) signal subtract from constant.
- **NppStatus nppsSubCRev_64f_I** (**Npp64f** nValue, **Npp64f** *pSrcDst, int nLength)
64-bit floating point, in place signal subtract from constant.

- **NppStatus nppsSubCRev_64f** (const **Npp64f** *pSrc, **Npp64f** nValue, **Npp64f** *pDst, int nLength)
64-bit floating point signal subtract from constant.
- **NppStatus nppsSubCRev_64fc_I** (**Npp64fc** nValue, **Npp64fc** *pSrcDst, int nLength)
64-bit floating point complex number (64 bit real, 64 bit imaginary) in place signal subtract from constant.
- **NppStatus nppsSubCRev_64fc** (const **Npp64fc** *pSrc, **Npp64fc** nValue, **Npp64fc** *pDst, int nLength)
64-bit floating point complex number (64 bit real, 64 bit imaginary) signal subtract from constant.

DivC

Divides each sample of a signal by a constant.

- **NppStatus nppsDivC_8u_ISfs** (**Npp8u** nValue, **Npp8u** *pSrcDst, int nLength, int nScaleFactor)
8-bit unsigned char in place signal divided by constant, scale, then clamp to saturated value
- **NppStatus nppsDivC_8u_Sfs** (const **Npp8u** *pSrc, **Npp8u** nValue, **Npp8u** *pDst, int nLength, int nScaleFactor)
8-bit unsigned char signal divided by constant, scale, then clamp to saturated value.
- **NppStatus nppsDivC_16u_ISfs** (**Npp16u** nValue, **Npp16u** *pSrcDst, int nLength, int nScaleFactor)
16-bit unsigned short in place signal divided by constant, scale, then clamp to saturated value.
- **NppStatus nppsDivC_16u_Sfs** (const **Npp16u** *pSrc, **Npp16u** nValue, **Npp16u** *pDst, int nLength, int nScaleFactor)
16-bit unsigned short signal divided by constant, scale, then clamp to saturated value.
- **NppStatus nppsDivC_16s_ISfs** (**Npp16s** nValue, **Npp16s** *pSrcDst, int nLength, int nScaleFactor)
16-bit signed short in place signal divided by constant, scale, then clamp to saturated value.
- **NppStatus nppsDivC_16s_Sfs** (const **Npp16s** *pSrc, **Npp16s** nValue, **Npp16s** *pDst, int nLength, int nScaleFactor)
16-bit signed short signal divided by constant, scale, then clamp to saturated value.
- **NppStatus nppsDivC_16sc_ISfs** (**Npp16sc** nValue, **Npp16sc** *pSrcDst, int nLength, int nScaleFactor)
16-bit integer complex number (16 bit real, 16 bit imaginary) signal divided by constant, scale, then clamp to saturated value.
- **NppStatus nppsDivC_16sc_Sfs** (const **Npp16sc** *pSrc, **Npp16sc** nValue, **Npp16sc** *pDst, int nLength, int nScaleFactor)
16-bit integer complex number (16 bit real, 16 bit imaginary) signal divided by constant, scale, then clamp to saturated value.
- **NppStatus nppsDivC_32s_ISfs** (**Npp32s** nValue, **Npp32s** *pSrcDst, int nLength, int nScaleFactor)
32-bit signed integer in place signal divided by constant and scale.

- **NppStatus nppsDivC_32s_Sfs** (const **Npp32s** *pSrc, **Npp32s** nValue, **Npp32s** *pDst, int nLength, int nScaleFactor)
32-bit signed integer signal divided by constant and scale.
- **NppStatus nppsDivC_32sc_ISfs** (**Npp32sc** nValue, **Npp32sc** *pSrcDst, int nLength, int nScaleFactor)
32-bit integer complex number (32 bit real, 32 bit imaginary) in place signal divided by constant and scale.
- **NppStatus nppsDivC_32sc_Sfs** (const **Npp32sc** *pSrc, **Npp32sc** nValue, **Npp32sc** *pDst, int nLength, int nScaleFactor)
32-bit integer complex number (32 bit real, 32 bit imaginary) signal divided by constant and scale.
- **NppStatus nppsDivC_32f_I** (**Npp32f** nValue, **Npp32f** *pSrcDst, int nLength)
32-bit floating point in place signal divided by constant.
- **NppStatus nppsDivC_32f** (const **Npp32f** *pSrc, **Npp32f** nValue, **Npp32f** *pDst, int nLength)
32-bit floating point signal divided by constant.
- **NppStatus nppsDivC_32fc_I** (**Npp32fc** nValue, **Npp32fc** *pSrcDst, int nLength)
32-bit floating point complex number (32 bit real, 32 bit imaginary) in place signal divided by constant.
- **NppStatus nppsDivC_32fc** (const **Npp32fc** *pSrc, **Npp32fc** nValue, **Npp32fc** *pDst, int nLength)
32-bit floating point complex number (32 bit real, 32 bit imaginary) signal divided by constant.
- **NppStatus nppsDivC_64f_I** (**Npp64f** nValue, **Npp64f** *pSrcDst, int nLength)
64-bit floating point in place signal divided by constant.
- **NppStatus nppsDivC_64f** (const **Npp64f** *pSrc, **Npp64f** nValue, **Npp64f** *pDst, int nLength)
64-bit floating point signal divided by constant.
- **NppStatus nppsDivC_64fc_I** (**Npp64fc** nValue, **Npp64fc** *pSrcDst, int nLength)
64-bit floating point complex number (64 bit real, 64 bit imaginary) in place signal divided by constant.
- **NppStatus nppsDivC_64fc** (const **Npp64fc** *pSrc, **Npp64fc** nValue, **Npp64fc** *pDst, int nLength)
64-bit floating point complex number (64 bit real, 64 bit imaginary) signal divided by constant.

DivCRev

Divides a constant by each sample of a signal.

- **NppStatus nppsDivCRev_8u_I** (**Npp8u** nValue, **Npp8u** *pSrcDst, int nLength)
8-bit unsigned char signal in place constant divided by signal, scale, then clamp to saturated value
- **NppStatus nppsDivCRev_8u** (const **Npp8u** *pSrc, **Npp8u** nValue, **Npp8u** *pDst, int nLength)
8-bit unsigned char signal divided by constant, then clamp to saturated value.
- **NppStatus nppsDivCRev_16u_I** (**Npp16u** nValue, **Npp16u** *pSrcDst, int nLength)
16-bit unsigned short in place constant divided by signal, then clamp to saturated value.

- `NppStatus nppsDivCRev_16u` (const `Npp16u` *pSrc, `Npp16u` nValue, `Npp16u` *pDst, int nLength)
16-bit unsigned short vector divided by constant, then clamp to saturated value.
- `NppStatus nppsDivCRev_16s_I` (`Npp16s` nValue, `Npp16s` *pSrcDst, int nLength)
16-bit signed short in place constant divided by signal, then clamp to saturated value.
- `NppStatus nppsDivCRev_16s` (const `Npp16s` *pSrc, `Npp16s` nValue, `Npp16s` *pDst, int nLength)
16-bit signed short constant divided by signal, then clamp to saturated value.
- `NppStatus nppsDivCRev_32s_I` (`Npp32s` nValue, `Npp32s` *pSrcDst, int nLength)
32-bit signed integer in place constant divided by signal.
- `NppStatus nppsDivCRev_32s` (const `Npp32s` *pSrc, `Npp32s` nValue, `Npp32s` *pDst, int nLength)
32-bit signed integer constant divided by signal.
- `NppStatus nppsDivCRev_32f_I` (`Npp32f` nValue, `Npp32f` *pSrcDst, int nLength)
32-bit floating point in place constant divided by signal.
- `NppStatus nppsDivCRev_32f` (const `Npp32f` *pSrc, `Npp32f` nValue, `Npp32f` *pDst, int nLength)
32-bit floating point constant divided by signal.
- `NppStatus nppsDivCRev_64f_I` (`Npp64f` nValue, `Npp64f` *pSrcDst, int nLength)
64-bit floating point in place constant divided by signal.
- `NppStatus nppsDivCRev_64f` (const `Npp64f` *pSrc, `Npp64f` nValue, `Npp64f` *pDst, int nLength)
64-bit floating point constant divided by signal.

Add Signal

Sample by sample addition of two signals.

- `NppStatus nppsAdd_16s` (const `Npp16s` *pSrc1, const `Npp16s` *pSrc2, `Npp16s` *pDst, int nLength)
16-bit signed short signal add signal, then clamp to saturated value.
- `NppStatus nppsAdd_16u` (const `Npp16u` *pSrc1, const `Npp16u` *pSrc2, `Npp16u` *pDst, int nLength)
16-bit unsigned short signal add signal, then clamp to saturated value.
- `NppStatus nppsAdd_32u` (const `Npp32u` *pSrc1, const `Npp32u` *pSrc2, `Npp32u` *pDst, int nLength)
32-bit unsigned int signal add signal, then clamp to saturated value.
- `NppStatus nppsAdd_32f` (const `Npp32f` *pSrc1, const `Npp32f` *pSrc2, `Npp32f` *pDst, int nLength)
32-bit floating point signal add signal, then clamp to saturated value.
- `NppStatus nppsAdd_64f` (const `Npp64f` *pSrc1, const `Npp64f` *pSrc2, `Npp64f` *pDst, int nLength)
64-bit floating point signal add signal, then clamp to saturated value.

- **NppStatus nppsAdd_32fc** (const **Npp32fc** *pSrc1, const **Npp32fc** *pSrc2, **Npp32fc** *pDst, int nLength)
32-bit complex floating point signal add signal, then clamp to saturated value.
- **NppStatus nppsAdd_64fc** (const **Npp64fc** *pSrc1, const **Npp64fc** *pSrc2, **Npp64fc** *pDst, int nLength)
64-bit complex floating point signal add signal, then clamp to saturated value.
- **NppStatus nppsAdd_8u16u** (const **Npp8u** *pSrc1, const **Npp8u** *pSrc2, **Npp16u** *pDst, int nLength)
8-bit unsigned char signal add signal with 16-bit unsigned result, then clamp to saturated value.
- **NppStatus nppsAdd_16s32f** (const **Npp16s** *pSrc1, const **Npp16s** *pSrc2, **Npp32f** *pDst, int nLength)
16-bit signed short signal add signal with 32-bit floating point result, then clamp to saturated value.
- **NppStatus nppsAdd_8u_Sfs** (const **Npp8u** *pSrc1, const **Npp8u** *pSrc2, **Npp8u** *pDst, int nLength, int nScaleFactor)
8-bit unsigned char add signal, scale, then clamp to saturated value.
- **NppStatus nppsAdd_16u_Sfs** (const **Npp16u** *pSrc1, const **Npp16u** *pSrc2, **Npp16u** *pDst, int nLength, int nScaleFactor)
16-bit unsigned short add signal, scale, then clamp to saturated value.
- **NppStatus nppsAdd_16s_Sfs** (const **Npp16s** *pSrc1, const **Npp16s** *pSrc2, **Npp16s** *pDst, int nLength, int nScaleFactor)
16-bit signed short add signal, scale, then clamp to saturated value.
- **NppStatus nppsAdd_32s_Sfs** (const **Npp32s** *pSrc1, const **Npp32s** *pSrc2, **Npp32s** *pDst, int nLength, int nScaleFactor)
32-bit signed integer add signal, scale, then clamp to saturated value.
- **NppStatus nppsAdd_64s_Sfs** (const **Npp64s** *pSrc1, const **Npp64s** *pSrc2, **Npp64s** *pDst, int nLength, int nScaleFactor)
64-bit signed integer add signal, scale, then clamp to saturated value.
- **NppStatus nppsAdd_16sc_Sfs** (const **Npp16sc** *pSrc1, const **Npp16sc** *pSrc2, **Npp16sc** *pDst, int nLength, int nScaleFactor)
16-bit signed complex short add signal, scale, then clamp to saturated value.
- **NppStatus nppsAdd_32sc_Sfs** (const **Npp32sc** *pSrc1, const **Npp32sc** *pSrc2, **Npp32sc** *pDst, int nLength, int nScaleFactor)
32-bit signed complex integer add signal, scale, then clamp to saturated value.
- **NppStatus nppsAdd_16s_I** (const **Npp16s** *pSrc, **Npp16s** *pSrcDst, int nLength)
16-bit signed short in place signal add signal, then clamp to saturated value.
- **NppStatus nppsAdd_32f_I** (const **Npp32f** *pSrc, **Npp32f** *pSrcDst, int nLength)
32-bit floating point in place signal add signal, then clamp to saturated value.
- **NppStatus nppsAdd_64f_I** (const **Npp64f** *pSrc, **Npp64f** *pSrcDst, int nLength)

64-bit floating point in place signal add signal, then clamp to saturated value.

- **NppStatus nppsAdd_32fc_I** (const **Npp32fc** *pSrc, **Npp32fc** *pSrcDst, int nLength)
32-bit complex floating point in place signal add signal, then clamp to saturated value.
- **NppStatus nppsAdd_64fc_I** (const **Npp64fc** *pSrc, **Npp64fc** *pSrcDst, int nLength)
64-bit complex floating point in place signal add signal, then clamp to saturated value.
- **NppStatus nppsAdd_16s32s_I** (const **Npp16s** *pSrc, **Npp32s** *pSrcDst, int nLength)
16/32-bit signed short in place signal add signal with 32-bit signed integer results, then clamp to saturated value.
- **NppStatus nppsAdd_8u_ISfs** (const **Npp8u** *pSrc, **Npp8u** *pSrcDst, int nLength, int nScaleFactor)
8-bit unsigned char in place signal add signal, with scaling, then clamp to saturated value.
- **NppStatus nppsAdd_16u_ISfs** (const **Npp16u** *pSrc, **Npp16u** *pSrcDst, int nLength, int nScaleFactor)
16-bit unsigned short in place signal add signal, with scaling, then clamp to saturated value.
- **NppStatus nppsAdd_16s_ISfs** (const **Npp16s** *pSrc, **Npp16s** *pSrcDst, int nLength, int nScaleFactor)
16-bit signed short in place signal add signal, with scaling, then clamp to saturated value.
- **NppStatus nppsAdd_32s_ISfs** (const **Npp32s** *pSrc, **Npp32s** *pSrcDst, int nLength, int nScaleFactor)
32-bit signed integer in place signal add signal, with scaling, then clamp to saturated value.
- **NppStatus nppsAdd_16sc_ISfs** (const **Npp16sc** *pSrc, **Npp16sc** *pSrcDst, int nLength, int nScaleFactor)
16-bit complex signed short in place signal add signal, with scaling, then clamp to saturated value.
- **NppStatus nppsAdd_32sc_ISfs** (const **Npp32sc** *pSrc, **Npp32sc** *pSrcDst, int nLength, int nScaleFactor)
32-bit complex signed integer in place signal add signal, with scaling, then clamp to saturated value.

AddProduct Signal

Adds sample by sample product of two signals to the destination signal.

- **NppStatus nppsAddProduct_32f** (const **Npp32f** *pSrc1, const **Npp32f** *pSrc2, **Npp32f** *pDst, int nLength)
32-bit floating point signal add product of source signal times destination signal to destination signal, then clamp to saturated value.
- **NppStatus nppsAddProduct_64f** (const **Npp64f** *pSrc1, const **Npp64f** *pSrc2, **Npp64f** *pDst, int nLength)
64-bit floating point signal add product of source signal times destination signal to destination signal, then clamp to saturated value.

- **NppStatus nppsAddProduct_32fc** (const **Npp32fc** *pSrc1, const **Npp32fc** *pSrc2, **Npp32fc** *pDst, int nLength)
32-bit complex floating point signal add product of source signal times destination signal to destination signal, then clamp to saturated value.
- **NppStatus nppsAddProduct_64fc** (const **Npp64fc** *pSrc1, const **Npp64fc** *pSrc2, **Npp64fc** *pDst, int nLength)
64-bit complex floating point signal add product of source signal times destination signal to destination signal, then clamp to saturated value.
- **NppStatus nppsAddProduct_16s_Sfs** (const **Npp16s** *pSrc1, const **Npp16s** *pSrc2, **Npp16s** *pDst, int nLength, int nScaleFactor)
16-bit signed short signal add product of source signal1 times source signal2 to destination signal, with scaling, then clamp to saturated value.
- **NppStatus nppsAddProduct_32s_Sfs** (const **Npp32s** *pSrc1, const **Npp32s** *pSrc2, **Npp32s** *pDst, int nLength, int nScaleFactor)
32-bit signed short signal add product of source signal1 times source signal2 to destination signal, with scaling, then clamp to saturated value.
- **NppStatus nppsAddProduct_16s32s_Sfs** (const **Npp16s** *pSrc1, const **Npp16s** *pSrc2, **Npp32s** *pDst, int nLength, int nScaleFactor)
16-bit signed short signal add product of source signal1 times source signal2 to 32-bit signed integer destination signal, with scaling, then clamp to saturated value.

Mul Signal

Sample by sample multiplication the samples of two signals.

- **NppStatus nppsMul_16s** (const **Npp16s** *pSrc1, const **Npp16s** *pSrc2, **Npp16s** *pDst, int nLength)
16-bit signed short signal times signal, then clamp to saturated value.
- **NppStatus nppsMul_32f** (const **Npp32f** *pSrc1, const **Npp32f** *pSrc2, **Npp32f** *pDst, int nLength)
32-bit floating point signal times signal, then clamp to saturated value.
- **NppStatus nppsMul_64f** (const **Npp64f** *pSrc1, const **Npp64f** *pSrc2, **Npp64f** *pDst, int nLength)
64-bit floating point signal times signal, then clamp to saturated value.
- **NppStatus nppsMul_32fc** (const **Npp32fc** *pSrc1, const **Npp32fc** *pSrc2, **Npp32fc** *pDst, int nLength)
32-bit complex floating point signal times signal, then clamp to saturated value.
- **NppStatus nppsMul_64fc** (const **Npp64fc** *pSrc1, const **Npp64fc** *pSrc2, **Npp64fc** *pDst, int nLength)
64-bit complex floating point signal times signal, then clamp to saturated value.
- **NppStatus nppsMul_8u16u** (const **Npp8u** *pSrc1, const **Npp8u** *pSrc2, **Npp16u** *pDst, int nLength)
8-bit unsigned char signal times signal with 16-bit unsigned result, then clamp to saturated value.

- **NppStatus nppsMul_16s32f** (const **Npp16s** *pSrc1, const **Npp16s** *pSrc2, **Npp32f** *pDst, int nLength)
16-bit signed short signal times signal with 32-bit floating point result, then clamp to saturated value.
- **NppStatus nppsMul_32f32fc** (const **Npp32f** *pSrc1, const **Npp32fc** *pSrc2, **Npp32fc** *pDst, int nLength)
32-bit floating point signal times 32-bit complex floating point signal with complex 32-bit floating point result, then clamp to saturated value.
- **NppStatus nppsMul_8u_Sfs** (const **Npp8u** *pSrc1, const **Npp8u** *pSrc2, **Npp8u** *pDst, int nLength, int nScaleFactor)
8-bit unsigned char signal times signal, scale, then clamp to saturated value.
- **NppStatus nppsMul_16u_Sfs** (const **Npp16u** *pSrc1, const **Npp16u** *pSrc2, **Npp16u** *pDst, int nLength, int nScaleFactor)
16-bit unsigned short signal time signal, scale, then clamp to saturated value.
- **NppStatus nppsMul_16s_Sfs** (const **Npp16s** *pSrc1, const **Npp16s** *pSrc2, **Npp16s** *pDst, int nLength, int nScaleFactor)
16-bit signed short signal times signal, scale, then clamp to saturated value.
- **NppStatus nppsMul_32s_Sfs** (const **Npp32s** *pSrc1, const **Npp32s** *pSrc2, **Npp32s** *pDst, int nLength, int nScaleFactor)
32-bit signed integer signal times signal, scale, then clamp to saturated value.
- **NppStatus nppsMul_16sc_Sfs** (const **Npp16sc** *pSrc1, const **Npp16sc** *pSrc2, **Npp16sc** *pDst, int nLength, int nScaleFactor)
16-bit signed complex short signal times signal, scale, then clamp to saturated value.
- **NppStatus nppsMul_32sc_Sfs** (const **Npp32sc** *pSrc1, const **Npp32sc** *pSrc2, **Npp32sc** *pDst, int nLength, int nScaleFactor)
32-bit signed complex integer signal times signal, scale, then clamp to saturated value.
- **NppStatus nppsMul_16u16s_Sfs** (const **Npp16u** *pSrc1, const **Npp16s** *pSrc2, **Npp16s** *pDst, int nLength, int nScaleFactor)
16-bit unsigned short signal times 16-bit signed short signal, scale, then clamp to 16-bit signed saturated value.
- **NppStatus nppsMul_16s32s_Sfs** (const **Npp16s** *pSrc1, const **Npp16s** *pSrc2, **Npp32s** *pDst, int nLength, int nScaleFactor)
16-bit signed short signal times signal, scale, then clamp to 32-bit signed saturated value.
- **NppStatus nppsMul_32s32sc_Sfs** (const **Npp32s** *pSrc1, const **Npp32sc** *pSrc2, **Npp32sc** *pDst, int nLength, int nScaleFactor)
32-bit signed integer signal times 32-bit complex signed integer signal, scale, then clamp to 32-bit complex integer saturated value.
- **NppStatus nppsMul_Low_32s_Sfs** (const **Npp32s** *pSrc1, const **Npp32s** *pSrc2, **Npp32s** *pDst, int nLength, int nScaleFactor)
32-bit signed integer signal times signal, scale, then clamp to saturated value.

- **NppStatus nppsMul_16s_I** (const **Npp16s** *pSrc, **Npp16s** *pSrcDst, int nLength)
16-bit signed short in place signal times signal, then clamp to saturated value.
- **NppStatus nppsMul_32f_I** (const **Npp32f** *pSrc, **Npp32f** *pSrcDst, int nLength)
32-bit floating point in place signal times signal, then clamp to saturated value.
- **NppStatus nppsMul_64f_I** (const **Npp64f** *pSrc, **Npp64f** *pSrcDst, int nLength)
64-bit floating point in place signal times signal, then clamp to saturated value.
- **NppStatus nppsMul_32fc_I** (const **Npp32fc** *pSrc, **Npp32fc** *pSrcDst, int nLength)
32-bit complex floating point in place signal times signal, then clamp to saturated value.
- **NppStatus nppsMul_64fc_I** (const **Npp64fc** *pSrc, **Npp64fc** *pSrcDst, int nLength)
64-bit complex floating point in place signal times signal, then clamp to saturated value.
- **NppStatus nppsMul_32f32fc_I** (const **Npp32f** *pSrc, **Npp32fc** *pSrcDst, int nLength)
32-bit complex floating point in place signal times 32-bit floating point signal, then clamp to 32-bit complex floating point saturated value.
- **NppStatus nppsMul_8u_ISfs** (const **Npp8u** *pSrc, **Npp8u** *pSrcDst, int nLength, int nScaleFactor)
8-bit unsigned char in place signal times signal, with scaling, then clamp to saturated value.
- **NppStatus nppsMul_16u_ISfs** (const **Npp16u** *pSrc, **Npp16u** *pSrcDst, int nLength, int nScaleFactor)
16-bit unsigned short in place signal times signal, with scaling, then clamp to saturated value.
- **NppStatus nppsMul_16s_ISfs** (const **Npp16s** *pSrc, **Npp16s** *pSrcDst, int nLength, int nScaleFactor)
16-bit signed short in place signal times signal, with scaling, then clamp to saturated value.
- **NppStatus nppsMul_32s_ISfs** (const **Npp32s** *pSrc, **Npp32s** *pSrcDst, int nLength, int nScaleFactor)
32-bit signed integer in place signal times signal, with scaling, then clamp to saturated value.
- **NppStatus nppsMul_16sc_ISfs** (const **Npp16sc** *pSrc, **Npp16sc** *pSrcDst, int nLength, int nScaleFactor)
16-bit complex signed short in place signal times signal, with scaling, then clamp to saturated value.
- **NppStatus nppsMul_32sc_ISfs** (const **Npp32sc** *pSrc, **Npp32sc** *pSrcDst, int nLength, int nScaleFactor)
32-bit complex signed integer in place signal times signal, with scaling, then clamp to saturated value.
- **NppStatus nppsMul_32s32sc_ISfs** (const **Npp32s** *pSrc, **Npp32sc** *pSrcDst, int nLength, int nScaleFactor)
32-bit complex signed integer in place signal times 32-bit signed integer signal, with scaling, then clamp to saturated value.

Sub Signal

Sample by sample subtraction of the samples of two signals.

- **NppStatus nppsSub_16s** (const **Npp16s** *pSrc1, const **Npp16s** *pSrc2, **Npp16s** *pDst, int nLength)
16-bit signed short signal subtract signal, then clamp to saturated value.
- **NppStatus nppsSub_32f** (const **Npp32f** *pSrc1, const **Npp32f** *pSrc2, **Npp32f** *pDst, int nLength)
32-bit floating point signal subtract signal, then clamp to saturated value.
- **NppStatus nppsSub_64f** (const **Npp64f** *pSrc1, const **Npp64f** *pSrc2, **Npp64f** *pDst, int nLength)
64-bit floating point signal subtract signal, then clamp to saturated value.
- **NppStatus nppsSub_32fc** (const **Npp32fc** *pSrc1, const **Npp32fc** *pSrc2, **Npp32fc** *pDst, int nLength)
32-bit complex floating point signal subtract signal, then clamp to saturated value.
- **NppStatus nppsSub_64fc** (const **Npp64fc** *pSrc1, const **Npp64fc** *pSrc2, **Npp64fc** *pDst, int nLength)
64-bit complex floating point signal subtract signal, then clamp to saturated value.
- **NppStatus nppsSub_16s32f** (const **Npp16s** *pSrc1, const **Npp16s** *pSrc2, **Npp32f** *pDst, int nLength)
16-bit signed short signal subtract 16-bit signed short signal, then clamp and convert to 32-bit floating point saturated value.
- **NppStatus nppsSub_8u_Sfs** (const **Npp8u** *pSrc1, const **Npp8u** *pSrc2, **Npp8u** *pDst, int nLength, int nScaleFactor)
8-bit unsigned char signal subtract signal, scale, then clamp to saturated value.
- **NppStatus nppsSub_16u_Sfs** (const **Npp16u** *pSrc1, const **Npp16u** *pSrc2, **Npp16u** *pDst, int nLength, int nScaleFactor)
16-bit unsigned short signal subtract signal, scale, then clamp to saturated value.
- **NppStatus nppsSub_16s_Sfs** (const **Npp16s** *pSrc1, const **Npp16s** *pSrc2, **Npp16s** *pDst, int nLength, int nScaleFactor)
16-bit signed short signal subtract signal, scale, then clamp to saturated value.
- **NppStatus nppsSub_32s_Sfs** (const **Npp32s** *pSrc1, const **Npp32s** *pSrc2, **Npp32s** *pDst, int nLength, int nScaleFactor)
32-bit signed integer signal subtract signal, scale, then clamp to saturated value.
- **NppStatus nppsSub_16sc_Sfs** (const **Npp16sc** *pSrc1, const **Npp16sc** *pSrc2, **Npp16sc** *pDst, int nLength, int nScaleFactor)
16-bit signed complex short signal subtract signal, scale, then clamp to saturated value.
- **NppStatus nppsSub_32sc_Sfs** (const **Npp32sc** *pSrc1, const **Npp32sc** *pSrc2, **Npp32sc** *pDst, int nLength, int nScaleFactor)
32-bit signed complex integer signal subtract signal, scale, then clamp to saturated value.
- **NppStatus nppsSub_16s_I** (const **Npp16s** *pSrc, **Npp16s** *pSrcDst, int nLength)

16-bit signed short in place signal subtract signal, then clamp to saturated value.

- **NppStatus nppsSub_32f_I** (const **Npp32f** *pSrc, **Npp32f** *pSrcDst, int nLength)
32-bit floating point in place signal subtract signal, then clamp to saturated value.
- **NppStatus nppsSub_64f_I** (const **Npp64f** *pSrc, **Npp64f** *pSrcDst, int nLength)
64-bit floating point in place signal subtract signal, then clamp to saturated value.
- **NppStatus nppsSub_32fc_I** (const **Npp32fc** *pSrc, **Npp32fc** *pSrcDst, int nLength)
32-bit complex floating point in place signal subtract signal, then clamp to saturated value.
- **NppStatus nppsSub_64fc_I** (const **Npp64fc** *pSrc, **Npp64fc** *pSrcDst, int nLength)
64-bit complex floating point in place signal subtract signal, then clamp to saturated value.
- **NppStatus nppsSub_8u_ISfs** (const **Npp8u** *pSrc, **Npp8u** *pSrcDst, int nLength, int nScaleFactor)
8-bit unsigned char in place signal subtract signal, with scaling, then clamp to saturated value.
- **NppStatus nppsSub_16u_ISfs** (const **Npp16u** *pSrc, **Npp16u** *pSrcDst, int nLength, int nScaleFactor)
16-bit unsigned short in place signal subtract signal, with scaling, then clamp to saturated value.
- **NppStatus nppsSub_16s_ISfs** (const **Npp16s** *pSrc, **Npp16s** *pSrcDst, int nLength, int nScaleFactor)
16-bit signed short in place signal subtract signal, with scaling, then clamp to saturated value.
- **NppStatus nppsSub_32s_ISfs** (const **Npp32s** *pSrc, **Npp32s** *pSrcDst, int nLength, int nScaleFactor)
32-bit signed integer in place signal subtract signal, with scaling, then clamp to saturated value.
- **NppStatus nppsSub_16sc_ISfs** (const **Npp16sc** *pSrc, **Npp16sc** *pSrcDst, int nLength, int nScaleFactor)
16-bit complex signed short in place signal subtract signal, with scaling, then clamp to saturated value.
- **NppStatus nppsSub_32sc_ISfs** (const **Npp32sc** *pSrc, **Npp32sc** *pSrcDst, int nLength, int nScaleFactor)
32-bit complex signed integer in place signal subtract signal, with scaling, then clamp to saturated value.

Div Signal

Sample by sample division of the samples of two signals.

- **NppStatus nppsDiv_8u_Sfs** (const **Npp8u** *pSrc1, const **Npp8u** *pSrc2, **Npp8u** *pDst, int nLength, int nScaleFactor)
8-bit unsigned char signal divide signal, scale, then clamp to saturated value.
- **NppStatus nppsDiv_16u_Sfs** (const **Npp16u** *pSrc1, const **Npp16u** *pSrc2, **Npp16u** *pDst, int nLength, int nScaleFactor)
16-bit unsigned short signal divide signal, scale, then clamp to saturated value.

- `NppStatus nppsDiv_16s_Sfs` (const `Npp16s` *pSrc1, const `Npp16s` *pSrc2, `Npp16s` *pDst, int nLength, int nScaleFactor)
16-bit signed short signal divide signal, scale, then clamp to saturated value.
- `NppStatus nppsDiv_32s_Sfs` (const `Npp32s` *pSrc1, const `Npp32s` *pSrc2, `Npp32s` *pDst, int nLength, int nScaleFactor)
32-bit signed integer signal divide signal, scale, then clamp to saturated value.
- `NppStatus nppsDiv_16sc_Sfs` (const `Npp16sc` *pSrc1, const `Npp16sc` *pSrc2, `Npp16sc` *pDst, int nLength, int nScaleFactor)
16-bit signed complex short signal divide signal, scale, then clamp to saturated value.
- `NppStatus nppsDiv_32s16s_Sfs` (const `Npp16s` *pSrc1, const `Npp32s` *pSrc2, `Npp16s` *pDst, int nLength, int nScaleFactor)
32-bit signed integer signal divided by 16-bit signed short signal, scale, then clamp to 16-bit signed short saturated value.
- `NppStatus nppsDiv_32f` (const `Npp32f` *pSrc1, const `Npp32f` *pSrc2, `Npp32f` *pDst, int nLength)
32-bit floating point signal divide signal, then clamp to saturated value.
- `NppStatus nppsDiv_64f` (const `Npp64f` *pSrc1, const `Npp64f` *pSrc2, `Npp64f` *pDst, int nLength)
64-bit floating point signal divide signal, then clamp to saturated value.
- `NppStatus nppsDiv_32fc` (const `Npp32fc` *pSrc1, const `Npp32fc` *pSrc2, `Npp32fc` *pDst, int nLength)
32-bit complex floating point signal divide signal, then clamp to saturated value.
- `NppStatus nppsDiv_64fc` (const `Npp64fc` *pSrc1, const `Npp64fc` *pSrc2, `Npp64fc` *pDst, int nLength)
64-bit complex floating point signal divide signal, then clamp to saturated value.
- `NppStatus nppsDiv_8u_ISfs` (const `Npp8u` *pSrc, `Npp8u` *pSrcDst, int nLength, int nScaleFactor)
8-bit unsigned char in place signal divide signal, with scaling, then clamp to saturated value.
- `NppStatus nppsDiv_16u_ISfs` (const `Npp16u` *pSrc, `Npp16u` *pSrcDst, int nLength, int nScaleFactor)
16-bit unsigned short in place signal divide signal, with scaling, then clamp to saturated value.
- `NppStatus nppsDiv_16s_ISfs` (const `Npp16s` *pSrc, `Npp16s` *pSrcDst, int nLength, int nScaleFactor)
16-bit signed short in place signal divide signal, with scaling, then clamp to saturated value.
- `NppStatus nppsDiv_16sc_ISfs` (const `Npp16sc` *pSrc, `Npp16sc` *pSrcDst, int nLength, int nScaleFactor)
16-bit complex signed short in place signal divide signal, with scaling, then clamp to saturated value.
- `NppStatus nppsDiv_32s_ISfs` (const `Npp32s` *pSrc, `Npp32s` *pSrcDst, int nLength, int nScaleFactor)
32-bit signed integer in place signal divide signal, with scaling, then clamp to saturated value.
- `NppStatus nppsDiv_32f_I` (const `Npp32f` *pSrc, `Npp32f` *pSrcDst, int nLength)

32-bit floating point in place signal divide signal, then clamp to saturated value.

- **NppStatus nppsDiv_64f_I** (const **Npp64f** *pSrc, **Npp64f** *pSrcDst, int nLength)
64-bit floating point in place signal divide signal, then clamp to saturated value.
- **NppStatus nppsDiv_32fc_I** (const **Npp32fc** *pSrc, **Npp32fc** *pSrcDst, int nLength)
32-bit complex floating point in place signal divide signal, then clamp to saturated value.
- **NppStatus nppsDiv_64fc_I** (const **Npp64fc** *pSrc, **Npp64fc** *pSrcDst, int nLength)
64-bit complex floating point in place signal divide signal, then clamp to saturated value.

Div_Round Signal

Sample by sample division of the samples of two signals with rounding.

- **NppStatus nppsDiv_Round_8u_Sfs** (const **Npp8u** *pSrc1, const **Npp8u** *pSrc2, **Npp8u** *pDst, int nLength, **NppRoundMode** nRndMode, int nScaleFactor)
8-bit unsigned char signal divide signal, scale, then clamp to saturated value.
- **NppStatus nppsDiv_Round_16u_Sfs** (const **Npp16u** *pSrc1, const **Npp16u** *pSrc2, **Npp16u** *pDst, int nLength, **NppRoundMode** nRndMode, int nScaleFactor)
16-bit unsigned short signal divide signal, scale, round, then clamp to saturated value.
- **NppStatus nppsDiv_Round_16s_Sfs** (const **Npp16s** *pSrc1, const **Npp16s** *pSrc2, **Npp16s** *pDst, int nLength, **NppRoundMode** nRndMode, int nScaleFactor)
16-bit signed short signal divide signal, scale, round, then clamp to saturated value.
- **NppStatus nppsDiv_Round_8u_ISfs** (const **Npp8u** *pSrc, **Npp8u** *pSrcDst, int nLength, **NppRoundMode** nRndMode, int nScaleFactor)
8-bit unsigned char in place signal divide signal, with scaling, rounding then clamp to saturated value.
- **NppStatus nppsDiv_Round_16u_ISfs** (const **Npp16u** *pSrc, **Npp16u** *pSrcDst, int nLength, **NppRoundMode** nRndMode, int nScaleFactor)
16-bit unsigned short in place signal divide signal, with scaling, rounding then clamp to saturated value.
- **NppStatus nppsDiv_Round_16s_ISfs** (const **Npp16s** *pSrc, **Npp16s** *pSrcDst, int nLength, **NppRoundMode** nRndMode, int nScaleFactor)
16-bit signed short in place signal divide signal, with scaling, rounding then clamp to saturated value.

Absolute Value Signal

Absolute value of each sample of a signal.

- **NppStatus nppsAbs_16s** (const **Npp16s** *pSrc, **Npp16s** *pDst, int nLength)
16-bit signed short signal absolute value.
- **NppStatus nppsAbs_32s** (const **Npp32s** *pSrc, **Npp32s** *pDst, int nLength)

32-bit signed integer signal absolute value.

- `NppStatus nppsAbs_32f` (const `Npp32f` *pSrc, `Npp32f` *pDst, int nLength)
32-bit floating point signal absolute value.
- `NppStatus nppsAbs_64f` (const `Npp64f` *pSrc, `Npp64f` *pDst, int nLength)
64-bit floating point signal absolute value.
- `NppStatus nppsAbs_16s_I` (`Npp16s` *pSrcDst, int nLength)
16-bit signed short signal absolute value.
- `NppStatus nppsAbs_32s_I` (`Npp32s` *pSrcDst, int nLength)
32-bit signed integer signal absolute value.
- `NppStatus nppsAbs_32f_I` (`Npp32f` *pSrcDst, int nLength)
32-bit floating point signal absolute value.
- `NppStatus nppsAbs_64f_I` (`Npp64f` *pSrcDst, int nLength)
64-bit floating point signal absolute value.

Square Signal

Squares each sample of a signal.

- `NppStatus nppsSqr_32f` (const `Npp32f` *pSrc, `Npp32f` *pDst, int nLength)
32-bit floating point signal squared.
- `NppStatus nppsSqr_64f` (const `Npp64f` *pSrc, `Npp64f` *pDst, int nLength)
64-bit floating point signal squared.
- `NppStatus nppsSqr_32fc` (const `Npp32fc` *pSrc, `Npp32fc` *pDst, int nLength)
32-bit complex floating point signal squared.
- `NppStatus nppsSqr_64fc` (const `Npp64fc` *pSrc, `Npp64fc` *pDst, int nLength)
64-bit complex floating point signal squared.
- `NppStatus nppsSqr_32f_I` (`Npp32f` *pSrcDst, int nLength)
32-bit floating point signal squared.
- `NppStatus nppsSqr_64f_I` (`Npp64f` *pSrcDst, int nLength)
64-bit floating point signal squared.
- `NppStatus nppsSqr_32fc_I` (`Npp32fc` *pSrcDst, int nLength)
32-bit complex floating point signal squared.
- `NppStatus nppsSqr_64fc_I` (`Npp64fc` *pSrcDst, int nLength)
64-bit complex floating point signal squared.
- `NppStatus nppsSqr_8u_Sfs` (const `Npp8u` *pSrc, `Npp8u` *pDst, int nLength, int nScaleFactor)

8-bit unsigned char signal squared, scale, then clamp to saturated value.

- **NppStatus nppsSqr_16u_Sfs** (const **Npp16u** *pSrc, **Npp16u** *pDst, int nLength, int nScaleFactor)
16-bit unsigned short signal squared, scale, then clamp to saturated value.
- **NppStatus nppsSqr_16s_Sfs** (const **Npp16s** *pSrc, **Npp16s** *pDst, int nLength, int nScaleFactor)
16-bit signed short signal squared, scale, then clamp to saturated value.
- **NppStatus nppsSqr_16sc_Sfs** (const **Npp16sc** *pSrc, **Npp16sc** *pDst, int nLength, int nScaleFactor)
16-bit complex signed short signal squared, scale, then clamp to saturated value.
- **NppStatus nppsSqr_8u_ISfs** (**Npp8u** *pSrcDst, int nLength, int nScaleFactor)
8-bit unsigned char signal squared, scale, then clamp to saturated value.
- **NppStatus nppsSqr_16u_ISfs** (**Npp16u** *pSrcDst, int nLength, int nScaleFactor)
16-bit unsigned short signal squared, scale, then clamp to saturated value.
- **NppStatus nppsSqr_16s_ISfs** (**Npp16s** *pSrcDst, int nLength, int nScaleFactor)
16-bit signed short signal squared, scale, then clamp to saturated value.
- **NppStatus nppsSqr_16sc_ISfs** (**Npp16sc** *pSrcDst, int nLength, int nScaleFactor)
16-bit complex signed short signal squared, scale, then clamp to saturated value.

Square Root Signal

Square root of each sample of a signal.

- **NppStatus nppsSqrt_32f** (const **Npp32f** *pSrc, **Npp32f** *pDst, int nLength)
32-bit floating point signal square root.
- **NppStatus nppsSqrt_64f** (const **Npp64f** *pSrc, **Npp64f** *pDst, int nLength)
64-bit floating point signal square root.
- **NppStatus nppsSqrt_32fc** (const **Npp32fc** *pSrc, **Npp32fc** *pDst, int nLength)
32-bit complex floating point signal square root.
- **NppStatus nppsSqrt_64fc** (const **Npp64fc** *pSrc, **Npp64fc** *pDst, int nLength)
64-bit complex floating point signal square root.
- **NppStatus nppsSqrt_32f_I** (**Npp32f** *pSrcDst, int nLength)
32-bit floating point signal square root.
- **NppStatus nppsSqrt_64f_I** (**Npp64f** *pSrcDst, int nLength)
64-bit floating point signal square root.
- **NppStatus nppsSqrt_32fc_I** (**Npp32fc** *pSrcDst, int nLength)
32-bit complex floating point signal square root.

- **NppStatus nppsSqrt_64fc_I** (**Npp64fc** *pSrcDst, int nLength)
64-bit complex floating point signal square root.
- **NppStatus nppsSqrt_8u_Sfs** (const **Npp8u** *pSrc, **Npp8u** *pDst, int nLength, int nScaleFactor)
8-bit unsigned char signal square root, scale, then clamp to saturated value.
- **NppStatus nppsSqrt_16u_Sfs** (const **Npp16u** *pSrc, **Npp16u** *pDst, int nLength, int nScaleFactor)
16-bit unsigned short signal square root, scale, then clamp to saturated value.
- **NppStatus nppsSqrt_16s_Sfs** (const **Npp16s** *pSrc, **Npp16s** *pDst, int nLength, int nScaleFactor)
16-bit signed short signal square root, scale, then clamp to saturated value.
- **NppStatus nppsSqrt_16sc_Sfs** (const **Npp16sc** *pSrc, **Npp16sc** *pDst, int nLength, int nScaleFactor)
16-bit complex signed short signal square root, scale, then clamp to saturated value.
- **NppStatus nppsSqrt_64s_Sfs** (const **Npp64s** *pSrc, **Npp64s** *pDst, int nLength, int nScaleFactor)
64-bit signed integer signal square root, scale, then clamp to saturated value.
- **NppStatus nppsSqrt_32s16s_Sfs** (const **Npp32s** *pSrc, **Npp16s** *pDst, int nLength, int nScaleFactor)
32-bit signed integer signal square root, scale, then clamp to 16-bit signed integer saturated value.
- **NppStatus nppsSqrt_64s16s_Sfs** (const **Npp64s** *pSrc, **Npp16s** *pDst, int nLength, int nScaleFactor)
64-bit signed integer signal square root, scale, then clamp to 16-bit signed integer saturated value.
- **NppStatus nppsSqrt_8u_ISfs** (**Npp8u** *pSrcDst, int nLength, int nScaleFactor)
8-bit unsigned char signal square root, scale, then clamp to saturated value.
- **NppStatus nppsSqrt_16u_ISfs** (**Npp16u** *pSrcDst, int nLength, int nScaleFactor)
16-bit unsigned short signal square root, scale, then clamp to saturated value.
- **NppStatus nppsSqrt_16s_ISfs** (**Npp16s** *pSrcDst, int nLength, int nScaleFactor)
16-bit signed short signal square root, scale, then clamp to saturated value.
- **NppStatus nppsSqrt_16sc_ISfs** (**Npp16sc** *pSrcDst, int nLength, int nScaleFactor)
16-bit complex signed short signal square root, scale, then clamp to saturated value.
- **NppStatus nppsSqrt_64s_ISfs** (**Npp64s** *pSrcDst, int nLength, int nScaleFactor)
64-bit signed integer signal square root, scale, then clamp to saturated value.

Cube Root Signal

Cube root of each sample of a signal.

- **NppStatus nppsCubrt_32f** (const **Npp32f** *pSrc, **Npp32f** *pDst, int nLength)
32-bit floating point signal cube root.

- `NppStatus nppsCubrt_32s16s_Sfs` (const `Npp32s` *pSrc, `Npp16s` *pDst, int nLength, int nScaleFactor)

32-bit signed integer signal cube root, scale, then clamp to 16-bit signed integer saturated value.

Exponent Signal

E raised to the power of each sample of a signal.

- `NppStatus nppsExp_32f` (const `Npp32f` *pSrc, `Npp32f` *pDst, int nLength)
32-bit floating point signal exponent.
- `NppStatus nppsExp_64f` (const `Npp64f` *pSrc, `Npp64f` *pDst, int nLength)
64-bit floating point signal exponent.
- `NppStatus nppsExp_32f64f` (const `Npp32f` *pSrc, `Npp64f` *pDst, int nLength)
32-bit floating point signal exponent with 64-bit floating point result.
- `NppStatus nppsExp_32f_I` (`Npp32f` *pSrcDst, int nLength)
32-bit floating point signal exponent.
- `NppStatus nppsExp_64f_I` (`Npp64f` *pSrcDst, int nLength)
64-bit floating point signal exponent.
- `NppStatus nppsExp_16s_Sfs` (const `Npp16s` *pSrc, `Npp16s` *pDst, int nLength, int nScaleFactor)
16-bit signed short signal exponent, scale, then clamp to saturated value.
- `NppStatus nppsExp_32s_Sfs` (const `Npp32s` *pSrc, `Npp32s` *pDst, int nLength, int nScaleFactor)
32-bit signed integer signal exponent, scale, then clamp to saturated value.
- `NppStatus nppsExp_64s_Sfs` (const `Npp64s` *pSrc, `Npp64s` *pDst, int nLength, int nScaleFactor)
64-bit signed integer signal exponent, scale, then clamp to saturated value.
- `NppStatus nppsExp_16s_ISfs` (`Npp16s` *pSrcDst, int nLength, int nScaleFactor)
16-bit signed short signal exponent, scale, then clamp to saturated value.
- `NppStatus nppsExp_32s_ISfs` (`Npp32s` *pSrcDst, int nLength, int nScaleFactor)
32-bit signed integer signal exponent, scale, then clamp to saturated value.
- `NppStatus nppsExp_64s_ISfs` (`Npp64s` *pSrcDst, int nLength, int nScaleFactor)
64-bit signed integer signal exponent, scale, then clamp to saturated value.

Natural Logarithm Signal

Natural logarithm of each sample of a signal.

- `NppStatus nppsLn_32f` (const `Npp32f` *pSrc, `Npp32f` *pDst, int nLength)
32-bit floating point signal natural logarithm.

- **NppStatus nppsLn_64f** (const **Npp64f** *pSrc, **Npp64f** *pDst, int nLength)
64-bit floating point signal natural logarithm.
- **NppStatus nppsLn_64f32f** (const **Npp64f** *pSrc, **Npp32f** *pDst, int nLength)
64-bit floating point signal natural logarithm with 32-bit floating point result.
- **NppStatus nppsLn_32f_I** (**Npp32f** *pSrcDst, int nLength)
32-bit floating point signal natural logarithm.
- **NppStatus nppsLn_64f_I** (**Npp64f** *pSrcDst, int nLength)
64-bit floating point signal natural logarithm.
- **NppStatus nppsLn_16s_Sfs** (const **Npp16s** *pSrc, **Npp16s** *pDst, int nLength, int nScaleFactor)
16-bit signed short signal natural logarithm, scale, then clamp to saturated value.
- **NppStatus nppsLn_32s_Sfs** (const **Npp32s** *pSrc, **Npp32s** *pDst, int nLength, int nScaleFactor)
32-bit signed integer signal natural logarithm, scale, then clamp to saturated value.
- **NppStatus nppsLn_32s16s_Sfs** (const **Npp32s** *pSrc, **Npp16s** *pDst, int nLength, int nScaleFactor)
32-bit signed integer signal natural logarithm, scale, then clamp to 16-bit signed short saturated value.
- **NppStatus nppsLn_16s_ISfs** (**Npp16s** *pSrcDst, int nLength, int nScaleFactor)
16-bit signed short signal natural logarithm, scale, then clamp to saturated value.
- **NppStatus nppsLn_32s_ISfs** (**Npp32s** *pSrcDst, int nLength, int nScaleFactor)
32-bit signed integer signal natural logarithm, scale, then clamp to saturated value.

Ten Times Base Ten Logarithm Signal

Ten times the decimal logarithm of each sample of a signal.

- **NppStatus npps10Log10_32s_Sfs** (const **Npp32s** *pSrc, **Npp32s** *pDst, int nLength, int nScaleFactor)
32-bit signed integer signal 10 times base 10 logarithm, scale, then clamp to saturated value.
- **NppStatus npps10Log10_32s_ISfs** (**Npp32s** *pSrcDst, int nLength, int nScaleFactor)
32-bit signed integer signal 10 times base 10 logarithm, scale, then clamp to saturated value.

Inverse Tangent Signal

Inverse tangent of each sample of a signal.

- **NppStatus nppsArctan_32f** (const **Npp32f** *pSrc, **Npp32f** *pDst, int nLength)
32-bit floating point signal inverse tangent.

- `NppStatus nppsArctan_64f` (const `Npp64f` *pSrc, `Npp64f` *pDst, int nLength)
64-bit floating point signal inverse tangent.
- `NppStatus nppsArctan_32f_I` (`Npp32f` *pSrcDst, int nLength)
32-bit floating point signal inverse tangent.
- `NppStatus nppsArctan_64f_I` (`Npp64f` *pSrcDst, int nLength)
64-bit floating point signal inverse tangent.

Normalize Signal

Normalize each sample of a real or complex signal using offset and division operations.

- `NppStatus nppsNormalize_32f` (const `Npp32f` *pSrc, `Npp32f` *pDst, int nLength, `Npp32f` vSub, `Npp32f` vDiv)
32-bit floating point signal normalize.
- `NppStatus nppsNormalize_32fc` (const `Npp32fc` *pSrc, `Npp32fc` *pDst, int nLength, `Npp32fc` vSub, `Npp32fc` vDiv)
32-bit complex floating point signal normalize.
- `NppStatus nppsNormalize_64f` (const `Npp64f` *pSrc, `Npp64f` *pDst, int nLength, `Npp64f` vSub, `Npp64f` vDiv)
64-bit floating point signal normalize.
- `NppStatus nppsNormalize_64fc` (const `Npp64fc` *pSrc, `Npp64fc` *pDst, int nLength, `Npp64fc` vSub, `Npp64fc` vDiv)
64-bit complex floating point signal normalize.
- `NppStatus nppsNormalize_16s_Sfs` (const `Npp16s` *pSrc, `Npp16s` *pDst, int nLength, `Npp16s` vSub, int vDiv, int nScaleFactor)
16-bit signed short signal normalize, scale, then clamp to saturated value.
- `NppStatus nppsNormalize_16sc_Sfs` (const `Npp16sc` *pSrc, `Npp16sc` *pDst, int nLength, `Npp16sc` vSub, int vDiv, int nScaleFactor)
16-bit complex signed short signal normalize, scale, then clamp to saturated value.

Cauchy, CauchyD, and CauchyDD2 Signal

Determine Cauchy robust error function and its first and second derivatives for each sample of a signal.

- `NppStatus nppsCauchy_32f_I` (`Npp32f` *pSrcDst, int nLength, `Npp32f` nParam)
32-bit floating point signal Cauchy error calculation.
- `NppStatus nppsCauchyD_32f_I` (`Npp32f` *pSrcDst, int nLength, `Npp32f` nParam)
32-bit floating point signal Cauchy first derivative.

- `NppStatus nppsCauchyDD2_32f_I` (`Npp32f *pSrcDst`, `Npp32f *pD2FVal`, `int nLength`, `Npp32f nParam`)

32-bit floating point signal Cauchy first and second derivatives.

AndC

Bitwise AND of a constant and each sample of a signal.

- `NppStatus nppsAndC_8u` (`const Npp8u *pSrc`, `Npp8u nValue`, `Npp8u *pDst`, `int nLength`)
8-bit unsigned char signal and with constant.
- `NppStatus nppsAndC_16u` (`const Npp16u *pSrc`, `Npp16u nValue`, `Npp16u *pDst`, `int nLength`)
16-bit unsigned short signal and with constant.
- `NppStatus nppsAndC_32u` (`const Npp32u *pSrc`, `Npp32u nValue`, `Npp32u *pDst`, `int nLength`)
32-bit unsigned integer signal and with constant.
- `NppStatus nppsAndC_8u_I` (`Npp8u nValue`, `Npp8u *pSrcDst`, `int nLength`)
8-bit unsigned char in place signal and with constant.
- `NppStatus nppsAndC_16u_I` (`Npp16u nValue`, `Npp16u *pSrcDst`, `int nLength`)
16-bit unsigned short in place signal and with constant.
- `NppStatus nppsAndC_32u_I` (`Npp32u nValue`, `Npp32u *pSrcDst`, `int nLength`)
32-bit unsigned signed integer in place signal and with constant.

And

Sample by sample bitwise AND of samples from two signals.

- `NppStatus nppsAnd_8u` (`const Npp8u *pSrc1`, `const Npp8u *pSrc2`, `Npp8u *pDst`, `int nLength`)
8-bit unsigned char signal and with signal.
- `NppStatus nppsAnd_16u` (`const Npp16u *pSrc1`, `const Npp16u *pSrc2`, `Npp16u *pDst`, `int nLength`)
16-bit unsigned short signal and with signal.
- `NppStatus nppsAnd_32u` (`const Npp32u *pSrc1`, `const Npp32u *pSrc2`, `Npp32u *pDst`, `int nLength`)
32-bit unsigned integer signal and with signal.
- `NppStatus nppsAnd_8u_I` (`const Npp8u *pSrc`, `Npp8u *pSrcDst`, `int nLength`)
8-bit unsigned char in place signal and with signal.
- `NppStatus nppsAnd_16u_I` (`const Npp16u *pSrc`, `Npp16u *pSrcDst`, `int nLength`)
16-bit unsigned short in place signal and with signal.

- `NppStatus nppsAnd_32u_I` (const `Npp32u` *pSrc, `Npp32u` *pSrcDst, int nLength)
32-bit unsigned integer in place signal and with signal.

OrC

Bitwise OR of a constant and each sample of a signal.

- `NppStatus nppsOrC_8u` (const `Npp8u` *pSrc, `Npp8u` nValue, `Npp8u` *pDst, int nLength)
8-bit unsigned char signal or with constant.
- `NppStatus nppsOrC_16u` (const `Npp16u` *pSrc, `Npp16u` nValue, `Npp16u` *pDst, int nLength)
16-bit unsigned short signal or with constant.
- `NppStatus nppsOrC_32u` (const `Npp32u` *pSrc, `Npp32u` nValue, `Npp32u` *pDst, int nLength)
32-bit unsigned integer signal or with constant.
- `NppStatus nppsOrC_8u_I` (`Npp8u` nValue, `Npp8u` *pSrcDst, int nLength)
8-bit unsigned char in place signal or with constant.
- `NppStatus nppsOrC_16u_I` (`Npp16u` nValue, `Npp16u` *pSrcDst, int nLength)
16-bit unsigned short in place signal or with constant.
- `NppStatus nppsOrC_32u_I` (`Npp32u` nValue, `Npp32u` *pSrcDst, int nLength)
32-bit unsigned signed integer in place signal or with constant.

Or

Sample by sample bitwise OR of the samples from two signals.

- `NppStatus nppsOr_8u` (const `Npp8u` *pSrc1, const `Npp8u` *pSrc2, `Npp8u` *pDst, int nLength)
8-bit unsigned char signal or with signal.
- `NppStatus nppsOr_16u` (const `Npp16u` *pSrc1, const `Npp16u` *pSrc2, `Npp16u` *pDst, int nLength)
16-bit unsigned short signal or with signal.
- `NppStatus nppsOr_32u` (const `Npp32u` *pSrc1, const `Npp32u` *pSrc2, `Npp32u` *pDst, int nLength)
32-bit unsigned integer signal or with signal.
- `NppStatus nppsOr_8u_I` (const `Npp8u` *pSrc, `Npp8u` *pSrcDst, int nLength)
8-bit unsigned char in place signal or with signal.
- `NppStatus nppsOr_16u_I` (const `Npp16u` *pSrc, `Npp16u` *pSrcDst, int nLength)
16-bit unsigned short in place signal or with signal.
- `NppStatus nppsOr_32u_I` (const `Npp32u` *pSrc, `Npp32u` *pSrcDst, int nLength)
32-bit unsigned integer in place signal or with signal.

XorC

Bitwise XOR of a constant and each sample of a signal.

- `NppStatus nppsXorC_8u` (const `Npp8u` *pSrc, `Npp8u` nValue, `Npp8u` *pDst, int nLength)
8-bit unsigned char signal exclusive or with constant.
- `NppStatus nppsXorC_16u` (const `Npp16u` *pSrc, `Npp16u` nValue, `Npp16u` *pDst, int nLength)
16-bit unsigned short signal exclusive or with constant.
- `NppStatus nppsXorC_32u` (const `Npp32u` *pSrc, `Npp32u` nValue, `Npp32u` *pDst, int nLength)
32-bit unsigned integer signal exclusive or with constant.
- `NppStatus nppsXorC_8u_I` (`Npp8u` nValue, `Npp8u` *pSrcDst, int nLength)
8-bit unsigned char in place signal exclusive or with constant.
- `NppStatus nppsXorC_16u_I` (`Npp16u` nValue, `Npp16u` *pSrcDst, int nLength)
16-bit unsigned short in place signal exclusive or with constant.
- `NppStatus nppsXorC_32u_I` (`Npp32u` nValue, `Npp32u` *pSrcDst, int nLength)
32-bit unsigned signed integer in place signal exclusive or with constant.

Xor

Sample by sample bitwise XOR of the samples from two signals.

- `NppStatus nppsXor_8u` (const `Npp8u` *pSrc1, const `Npp8u` *pSrc2, `Npp8u` *pDst, int nLength)
8-bit unsigned char signal exclusive or with signal.
- `NppStatus nppsXor_16u` (const `Npp16u` *pSrc1, const `Npp16u` *pSrc2, `Npp16u` *pDst, int nLength)
16-bit unsigned short signal exclusive or with signal.
- `NppStatus nppsXor_32u` (const `Npp32u` *pSrc1, const `Npp32u` *pSrc2, `Npp32u` *pDst, int nLength)
32-bit unsigned integer signal exclusive or with signal.
- `NppStatus nppsXor_8u_I` (const `Npp8u` *pSrc, `Npp8u` *pSrcDst, int nLength)
8-bit unsigned char in place signal exclusive or with signal.
- `NppStatus nppsXor_16u_I` (const `Npp16u` *pSrc, `Npp16u` *pSrcDst, int nLength)
16-bit unsigned short in place signal exclusive or with signal.
- `NppStatus nppsXor_32u_I` (const `Npp32u` *pSrc, `Npp32u` *pSrcDst, int nLength)
32-bit unsigned integer in place signal exclusive or with signal.

Not

Bitwise NOT of each sample of a signal.

- `NppStatus nppsNot_8u` (const `Npp8u` *pSrc, `Npp8u` *pDst, int nLength)
8-bit unsigned char not signal.
- `NppStatus nppsNot_16u` (const `Npp16u` *pSrc, `Npp16u` *pDst, int nLength)
16-bit unsigned short not signal.
- `NppStatus nppsNot_32u` (const `Npp32u` *pSrc, `Npp32u` *pDst, int nLength)
32-bit unsigned integer not signal.
- `NppStatus nppsNot_8u_I` (`Npp8u` *pSrcDst, int nLength)
8-bit unsigned char in place not signal.
- `NppStatus nppsNot_16u_I` (`Npp16u` *pSrcDst, int nLength)
16-bit unsigned short in place not signal.
- `NppStatus nppsNot_32u_I` (`Npp32u` *pSrcDst, int nLength)
32-bit unsigned signed integer in place not signal.

LShiftC

Left shifts the bits of each sample of a signal by a constant amount.

- `NppStatus nppsLShiftC_8u` (const `Npp8u` *pSrc, int nValue, `Npp8u` *pDst, int nLength)
8-bit unsigned char signal left shift with constant.
- `NppStatus nppsLShiftC_16u` (const `Npp16u` *pSrc, int nValue, `Npp16u` *pDst, int nLength)
16-bit unsigned short signal left shift with constant.
- `NppStatus nppsLShiftC_16s` (const `Npp16s` *pSrc, int nValue, `Npp16s` *pDst, int nLength)
16-bit signed short signal left shift with constant.
- `NppStatus nppsLShiftC_32u` (const `Npp32u` *pSrc, int nValue, `Npp32u` *pDst, int nLength)
32-bit unsigned integer signal left shift with constant.
- `NppStatus nppsLShiftC_32s` (const `Npp32s` *pSrc, int nValue, `Npp32s` *pDst, int nLength)
32-bit signed integer signal left shift with constant.
- `NppStatus nppsLShiftC_8u_I` (int nValue, `Npp8u` *pSrcDst, int nLength)
8-bit unsigned char in place signal left shift with constant.
- `NppStatus nppsLShiftC_16u_I` (int nValue, `Npp16u` *pSrcDst, int nLength)
16-bit unsigned short in place signal left shift with constant.
- `NppStatus nppsLShiftC_16s_I` (int nValue, `Npp16s` *pSrcDst, int nLength)

16-bit signed short in place signal left shift with constant.

- `NppStatus nppsLShiftC_32u_I` (int nValue, `Npp32u` *pSrcDst, int nLength)
32-bit unsigned signed integer in place signal left shift with constant.
- `NppStatus nppsLShiftC_32s_I` (int nValue, `Npp32s` *pSrcDst, int nLength)
32-bit signed signed integer in place signal left shift with constant.

RShiftC

Right shifts the bits of each sample of a signal by a constant amount.

- `NppStatus nppsRShiftC_8u` (const `Npp8u` *pSrc, int nValue, `Npp8u` *pDst, int nLength)
8-bit unsigned char signal right shift with constant.
- `NppStatus nppsRShiftC_16u` (const `Npp16u` *pSrc, int nValue, `Npp16u` *pDst, int nLength)
16-bit unsigned short signal right shift with constant.
- `NppStatus nppsRShiftC_16s` (const `Npp16s` *pSrc, int nValue, `Npp16s` *pDst, int nLength)
16-bit signed short signal right shift with constant.
- `NppStatus nppsRShiftC_32u` (const `Npp32u` *pSrc, int nValue, `Npp32u` *pDst, int nLength)
32-bit unsigned integer signal right shift with constant.
- `NppStatus nppsRShiftC_32s` (const `Npp32s` *pSrc, int nValue, `Npp32s` *pDst, int nLength)
32-bit signed integer signal right shift with constant.
- `NppStatus nppsRShiftC_8u_I` (int nValue, `Npp8u` *pSrcDst, int nLength)
8-bit unsigned char in place signal right shift with constant.
- `NppStatus nppsRShiftC_16u_I` (int nValue, `Npp16u` *pSrcDst, int nLength)
16-bit unsigned short in place signal right shift with constant.
- `NppStatus nppsRShiftC_16s_I` (int nValue, `Npp16s` *pSrcDst, int nLength)
16-bit signed short in place signal right shift with constant.
- `NppStatus nppsRShiftC_32u_I` (int nValue, `Npp32u` *pSrcDst, int nLength)
32-bit unsigned signed integer in place signal right shift with constant.
- `NppStatus nppsRShiftC_32s_I` (int nValue, `Npp32s` *pSrcDst, int nLength)
32-bit signed signed integer in place signal right shift with constant.

Statistical Functions

Functions that provide global signal statistics like: average, standard deviation, minimum, etc.

- `NppStatus nppsReductionGetBufferSize_8u` (int nLength, int *hpBufferSize)

Device-buffer size (in bytes) for 8u reductions.

- [NppStatus nppsReductionGetBufferSize_16s](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for 16s reductions.
- [NppStatus nppsReductionGetBufferSize_16u](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for 16u reductions.
- [NppStatus nppsReductionGetBufferSize_16s_Sfs](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for 16s reductions with integer-results scaling.
- [NppStatus nppsReductionGetBufferSize_16sc](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for 16sc reductions.
- [NppStatus nppsReductionGetBufferSize_16sc_Sfs](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for 16sc reductions with integer-results scaling.
- [NppStatus nppsReductionGetBufferSize_32s](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for 32s reductions.
- [NppStatus nppsReductionGetBufferSize_32u](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for 32u reductions.
- [NppStatus nppsReductionGetBufferSize_32s_Sfs](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for 32s reductions with integer-results scaling.
- [NppStatus nppsReductionGetBufferSize_32sc](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for 32sc reductions.
- [NppStatus nppsReductionGetBufferSize_32f](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for 32f reductions.
- [NppStatus nppsReductionGetBufferSize_32fc](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for 32fc reductions.
- [NppStatus nppsReductionGetBufferSize_64s](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for 64s reductions.
- [NppStatus nppsReductionGetBufferSize_64f](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for 64f reductions.
- [NppStatus nppsReductionGetBufferSize_64fc](#) (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for 64fc reductions.
- [NppStatus nppsSum_32f](#) (const [Npp32f](#) *pSrc, int nLength, [Npp32f](#) *pSum, [NppHintAlgorithm](#) eHint, [Npp8u](#) *pDeviceBuffer)
32-bit float vector sum method
- [NppStatus nppsSum_32fc](#) (const [Npp32fc](#) *pSrc, int nLength, [Npp32fc](#) *pSum, [NppHintAlgorithm](#) eHint, [Npp8u](#) *pDeviceBuffer)

32-bit float complex vector sum method

- `NppStatus nppsSum_64f` (const `Npp64f` *pSrc, int nLength, `Npp64f` *pSum, `Npp8u` *pDeviceBuffer)

64-bit double vector sum method

- `NppStatus nppsSum_64fc` (const `Npp64fc` *pSrc, int nLength, `Npp64fc` *pSum, `Npp8u` *pDeviceBuffer)

64-bit double complex vector sum method

- `NppStatus nppsSum_16s_Sfs` (const `Npp16s` *pSrc, int nLength, `Npp16s` *pSum, int nScaleFactor, `Npp8u` *pDeviceBuffer)

16-bit short vector sum with integer scaling method

- `NppStatus nppsSum_32s_Sfs` (const `Npp32s` *pSrc, int nLength, `Npp32s` *pSum, int nScaleFactor, `Npp8u` *pDeviceBuffer)

32-bit integer vector sum with integer scaling method

- `NppStatus nppsSum_16sc_Sfs` (const `Npp16sc` *pSrc, int nLength, `Npp16sc` *pSum, int nScaleFactor, `Npp8u` *pDeviceBuffer)

16-bit short complex vector sum with integer scaling method

- `NppStatus nppsSum_16sc32sc_Sfs` (const `Npp16sc` *pSrc, int nLength, `Npp32sc` *pSum, int nScaleFactor, `Npp8u` *pDeviceBuffer)

16-bit short complex vector sum (32bit int complex) with integer scaling method

- `NppStatus nppsSum_16s32s_Sfs` (const `Npp16s` *pSrc, int nLength, `Npp32s` *pSum, int nScaleFactor, `Npp8u` *pDeviceBuffer)

16-bit integer vector sum (32bit) with integer scaling method

- `NppStatus nppsMax_16s` (const `Npp16s` *pSrc, int nLength, `Npp16s` *pMax, `Npp8u` *pDeviceBuffer)

16-bit integer vector max method

- `NppStatus nppsMax_32s` (const `Npp32s` *pSrc, int nLength, `Npp32s` *pMax, `Npp8u` *pDeviceBuffer)

32-bit integer vector max method

- `NppStatus nppsMax_32f` (const `Npp32f` *pSrc, int nLength, `Npp32f` *pMax, `Npp8u` *pDeviceBuffer)

32-bit float vector max method

- `NppStatus nppsMax_64f` (const `Npp64f` *pSrc, int nLength, `Npp64f` *pMax, `Npp8u` *pDeviceBuffer)

64-bit float vector max method

- `NppStatus nppsMin_16s` (const `Npp16s` *pSrc, int nLength, `Npp16s` *pMin, `Npp8u` *pDeviceBuffer)

16-bit integer vector min method

- **NppStatus nppsMin_32s** (const **Npp32s** *pSrc, int nLength, **Npp32s** *pMin, **Npp8u** *pDeviceBuffer)
32-bit integer vector min method
- **NppStatus nppsMin_32f** (const **Npp32f** *pSrc, int nLength, **Npp32f** *pMin, **Npp8u** *pDeviceBuffer)
32-bit integer vector min method
- **NppStatus nppsMin_64f** (const **Npp64f** *pSrc, int nLength, **Npp64f** *pMin, **Npp8u** *pDeviceBuffer)
64-bit integer vector min method
- **NppStatus nppsMinMaxGetBufferSize_8u** (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsMinMax_8u.
- **NppStatus nppsMinMaxGetBufferSize_16s** (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsMinMax_16s.
- **NppStatus nppsMinMaxGetBufferSize_16u** (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsMinMax_16u.
- **NppStatus nppsMinMaxGetBufferSize_32s** (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsMinMax_32s.
- **NppStatus nppsMinMaxGetBufferSize_32u** (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsMinMax_32u.
- **NppStatus nppsMinMaxGetBufferSize_32f** (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsMinMax_32f.
- **NppStatus nppsMinMaxGetBufferSize_64f** (int nLength, int *hpBufferSize)
Device-buffer size (in bytes) for nppsMinMax_64f.
- **NppStatus nppsMinMax_8u** (const **Npp8u** *pSrc, int nLength, **Npp8u** *pMin, **Npp8u** *pMax, **Npp8u** *pDeviceBuffer)
8-bit char vector min and max method
- **NppStatus nppsMinMax_16s** (const **Npp16s** *pSrc, int nLength, **Npp16s** *pMin, **Npp16s** *pMax, **Npp8u** *pDeviceBuffer)
16-bit signed short vector min and max method
- **NppStatus nppsMinMax_16u** (const **Npp16u** *pSrc, int nLength, **Npp16u** *pMin, **Npp16u** *pMax, **Npp8u** *pDeviceBuffer)
16-bit unsigned short vector min and max method
- **NppStatus nppsMinMax_32u** (const **Npp32u** *pSrc, int nLength, **Npp32u** *pMin, **Npp32u** *pMax, **Npp8u** *pDeviceBuffer)
32-bit unsigned int vector min and max method
- **NppStatus nppsMinMax_32s** (const **Npp32s** *pSrc, int nLength, **Npp32s** *pMin, **Npp32s** *pMax, **Npp8u** *pDeviceBuffer)

32-bit signed int vector min and max method

- `NppStatus nppsMinMax_32f` (const `Npp32f` *pSrc, int nLength, `Npp32f` *pMin, `Npp32f` *pMax, `Npp8u` *pDeviceBuffer)

32-bit float vector min and max method

- `NppStatus nppsMinMax_64f` (const `Npp64f` *pSrc, int nLength, `Npp64f` *pMin, `Npp64f` *pMax, `Npp8u` *pDeviceBuffer)

64-bit double vector min and max method

Filtering Functions

Functions that provide functionality of generating output signal based on the input signal like signal integral, etc.

- `NppStatus nppsIntegralGetBufferSize_32s` (int nLength, int *hpBufferSize)
- `NppStatus nppsIntegral_32s` (const `Npp32s` *pSrc, `Npp32s` *pDst, int nLength, `Npp8u` *pDeviceBuffer)

7.5.1 Function Documentation

7.5.1.1 `NppStatus npps10Log10_32s_ISfs` (`Npp32s` *pSrcDst, int nLength, int nScaleFactor)

32-bit signed integer signal 10 times base 10 logarithm, scale, then clamp to saturated value.

Parameters:

pSrcDst In-Place Signal Pointer.
nLength Signal Length.
nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.2 `NppStatus npps10Log10_32s_Sfs` (const `Npp32s` *pSrc, `Npp32s` *pDst, int nLength, int nScaleFactor)

32-bit signed integer signal 10 times base 10 logarithm, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.
pDst Destination Signal Pointer.
nLength Signal Length.
nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.3 NppStatus nppsAbs_16s (const Npp16s * *pSrc*, Npp16s * *pDst*, int *nLength*)

16-bit signed short signal absolute value.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.4 NppStatus nppsAbs_16s_I (Npp16s * *pSrcDst*, int *nLength*)

16-bit signed short signal absolute value.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.5 NppStatus nppsAbs_32f (const Npp32f * *pSrc*, Npp32f * *pDst*, int *nLength*)

32-bit floating point signal absolute value.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.6 NppStatus nppsAbs_32f_I (Npp32f * *pSrcDst*, int *nLength*)

32-bit floating point signal absolute value.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.7 NppStatus nppsAbs_32s (const Npp32s * *pSrc*, Npp32s * *pDst*, int *nLength*)

32-bit signed integer signal absolute value.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.8 NppStatus nppsAbs_32s_I (Npp32s * *pSrcDst*, int *nLength*)

32-bit signed integer signal absolute value.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.9 NppStatus nppsAbs_64f (const Npp64f * *pSrc*, Npp64f * *pDst*, int *nLength*)

64-bit floating point signal absolute value.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.10 NppStatus nppsAbs_64f_I (Npp64f * *pSrcDst*, int *nLength*)

64-bit floating point signal absolute value.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.11 NppStatus nppsAdd_16s (const Npp16s * *pSrc1*, const Npp16s * *pSrc2*, Npp16s * *pDst*, int *nLength*)

16-bit signed short signal add signal, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal2 elements to be added to signal1 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.12 NppStatus nppsAdd_16s32f (const Npp16s * *pSrc1*, const Npp16s * *pSrc2*, Npp32f * *pDst*, int *nLength*)

16-bit signed short signal add signal with 32-bit floating point result, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal2 elements to be added to signal1 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.13 NppStatus nppsAdd_16s32s_I (const Npp16s * *pSrc*, Npp32s * *pSrcDst*, int *nLength*)

16/32-bit signed short in place signal add signal with 32-bit signed integer results, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal2 elements to be added to signal1 elements

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.14 NppStatus nppsAdd_16s_I (const Npp16s * *pSrc*, Npp16s * *pSrcDst*, int *nLength*)

16-bit signed short in place signal add signal, then clamp to saturated value.

Parameters:

pSrc [Source Signal Pointer](#).

pSrcDst [In-Place Signal Pointer](#). signal2 elements to be added to signal1 elements

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.15 NppStatus nppsAdd_16s_ISfs (const Npp16s * *pSrc*, Npp16s * *pSrcDst*, int *nLength*, int *nScaleFactor*)

16-bit signed short in place signal add signal, with scaling, then clamp to saturated value.

Parameters:

pSrc [Source Signal Pointer](#).

pSrcDst [In-Place Signal Pointer](#). signal2 elements to be added to signal1 elements

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.16 NppStatus nppsAdd_16s_Sfs (const Npp16s * *pSrc1*, const Npp16s * *pSrc2*, Npp16s * *pDst*, int *nLength*, int *nScaleFactor*)

16-bit signed short add signal, scale, then clamp to saturated value.

Parameters:

pSrc1 [Source Signal Pointer](#).

pSrc2 [Source Signal Pointer](#), signal2 elements to be added to signal1 elements.

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.17 NppStatus nppsAdd_16sc_ISfs (const Npp16sc * *pSrc*, Npp16sc * *pSrcDst*, int *nLength*, int *nScaleFactor*)

16-bit complex signed short in place signal add signal, with scaling, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal2 elements to be added to signal1 elements

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.18 NppStatus nppsAdd_16sc_Sfs (const Npp16sc * *pSrc1*, const Npp16sc * *pSrc2*, Npp16sc * *pDst*, int *nLength*, int *nScaleFactor*)

16-bit signed complex short add signal, scale, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal2 elements to be added to signal1 elements.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.19 NppStatus nppsAdd_16u (const Npp16u * *pSrc1*, const Npp16u * *pSrc2*, Npp16u * *pDst*, int *nLength*)

16-bit unsigned short signal add signal, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal2 elements to be added to signal1 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.20 NppStatus nppsAdd_16u_ISfs (const Npp16u * *pSrc*, Npp16u * *pSrcDst*, int *nLength*, int *nScaleFactor*)

16-bit unsigned short in place signal add signal, with scaling, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal2 elements to be added to signal1 elements

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.21 NppStatus nppsAdd_16u_Sfs (const Npp16u * *pSrc1*, const Npp16u * *pSrc2*, Npp16u * *pDst*, int *nLength*, int *nScaleFactor*)

16-bit unsigned short add signal, scale, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal2 elements to be added to signal1 elements.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.22 NppStatus nppsAdd_32f (const Npp32f * *pSrc1*, const Npp32f * *pSrc2*, Npp32f * *pDst*, int *nLength*)

32-bit floating point signal add signal, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal2 elements to be added to signal1 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.23 NppStatus nppsAdd_32f_I (const Npp32f * *pSrc*, Npp32f * *pSrcDst*, int *nLength*)

32-bit floating point in place signal add signal, then clamp to saturated value.

Parameters:

pSrc [Source Signal Pointer](#).

pSrcDst [In-Place Signal Pointer](#). signal2 elements to be added to signal1 elements

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.24 NppStatus nppsAdd_32fc (const Npp32fc * *pSrc1*, const Npp32fc * *pSrc2*, Npp32fc * *pDst*, int *nLength*)

32-bit complex floating point signal add signal, then clamp to saturated value.

Parameters:

pSrc1 [Source Signal Pointer](#).

pSrc2 [Source Signal Pointer](#). signal2 elements to be added to signal1 elements

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.25 NppStatus nppsAdd_32fc_I (const Npp32fc * *pSrc*, Npp32fc * *pSrcDst*, int *nLength*)

32-bit complex floating point in place signal add signal, then clamp to saturated value.

Parameters:

pSrc [Source Signal Pointer](#).

pSrcDst [In-Place Signal Pointer](#). signal2 elements to be added to signal1 elements

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.26 NppStatus nppsAdd_32s_ISfs (const Npp32s * *pSrc*, Npp32s * *pSrcDst*, int *nLength*, int *nScaleFactor*)

32-bit signed integer in place signal add signal, with scaling, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal2 elements to be added to signal1 elements

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.27 NppStatus nppsAdd_32s_Sfs (const Npp32s * *pSrc1*, const Npp32s * *pSrc2*, Npp32s * *pDst*, int *nLength*, int *nScaleFactor*)

32-bit signed integer add signal, scale, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal2 elements to be added to signal1 elements.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.28 NppStatus nppsAdd_32sc_ISfs (const Npp32sc * *pSrc*, Npp32sc * *pSrcDst*, int *nLength*, int *nScaleFactor*)

32-bit complex signed integer in place signal add signal, with scaling, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal2 elements to be added to signal1 elements

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.29 NppStatus nppsAdd_32sc_Sfs (const Npp32sc * *pSrc1*, const Npp32sc * *pSrc2*, Npp32sc * *pDst*, int *nLength*, int *nScaleFactor*)

32-bit signed complex integer add signal, scale, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal2 elements to be added to signal1 elements.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.30 NppStatus nppsAdd_32u (const Npp32u * *pSrc1*, const Npp32u * *pSrc2*, Npp32u * *pDst*, int *nLength*)

32-bit unsigned int signal add signal, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal2 elements to be added to signal1 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.31 NppStatus nppsAdd_64f (const Npp64f * *pSrc1*, const Npp64f * *pSrc2*, Npp64f * *pDst*, int *nLength*)

64-bit floating point signal add signal, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal2 elements to be added to signal1 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.32 NppStatus nppsAdd_64f_I (const Npp64f * *pSrc*, Npp64f * *pSrcDst*, int *nLength*)

64-bit floating point in place signal add signal, then clamp to saturated value.

Parameters:

pSrc [Source Signal Pointer](#).

pSrcDst [In-Place Signal Pointer](#). signal2 elements to be added to signal1 elements

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.33 NppStatus nppsAdd_64fc (const Npp64fc * *pSrc1*, const Npp64fc * *pSrc2*, Npp64fc * *pDst*, int *nLength*)

64-bit complex floating point signal add signal, then clamp to saturated value.

Parameters:

pSrc1 [Source Signal Pointer](#).

pSrc2 [Source Signal Pointer](#). signal2 elements to be added to signal1 elements

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.34 NppStatus nppsAdd_64fc_I (const Npp64fc * *pSrc*, Npp64fc * *pSrcDst*, int *nLength*)

64-bit complex floating point in place signal add signal, then clamp to saturated value.

Parameters:

pSrc [Source Signal Pointer](#).

pSrcDst [In-Place Signal Pointer](#). signal2 elements to be added to signal1 elements

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.35 NppStatus nppsAdd_64s_Sfs (const Npp64s * *pSrc1*, const Npp64s * *pSrc2*, Npp64s * *pDst*, int *nLength*, int *nScaleFactor*)

64-bit signed integer add signal, scale, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal2 elements to be added to signal1 elements.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.36 NppStatus nppsAdd_8u16u (const Npp8u * *pSrc1*, const Npp8u * *pSrc2*, Npp16u * *pDst*, int *nLength*)

8-bit unsigned char signal add signal with 16-bit unsigned result, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal2 elements to be added to signal1 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.37 NppStatus nppsAdd_8u_ISfs (const Npp8u * *pSrc*, Npp8u * *pSrcDst*, int *nLength*, int *nScaleFactor*)

8-bit unsigned char in place signal add signal, with scaling, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal2 elements to be added to signal1 elements

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.38 NppStatus nppsAdd_8u_Sfs (const Npp8u * *pSrc1*, const Npp8u * *pSrc2*, Npp8u * *pDst*, int *nLength*, int *nScaleFactor*)

8-bit unsigned char add signal, scale, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal2 elements to be added to signal1 elements.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.39 NppStatus nppsAddC_16s_ISfs (Npp16s *nValue*, Npp16s * *pSrcDst*, int *nLength*, int *nScaleFactor*)

16-bit signed short in place signal add constant, scale, then clamp to saturated value.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be added to each vector element

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.40 NppStatus nppsAddC_16s_Sfs (const Npp16s * *pSrc*, Npp16s *nValue*, Npp16s * *pDst*, int *nLength*, int *nScaleFactor*)

16-bit signed short signal add constant, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be added to each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.41 NppStatus nppsAddC_16sc_ISfs (Npp16sc *nValue*, Npp16sc * *pSrcDst*, int *nLength*, int *nScaleFactor*)

16-bit integer complex number (16 bit real, 16 bit imaginary) signal add constant, scale, then clamp to saturated value.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value to be added to each vector element

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.42 NppStatus nppsAddC_16sc_Sfs (const Npp16sc * *pSrc*, Npp16sc *nValue*, Npp16sc * *pDst*, int *nLength*, int *nScaleFactor*)

16-bit integer complex number (16 bit real, 16 bit imaginary) signal add constant, scale, then clamp to saturated value.

Parameters:

pSrc [Source Signal Pointer](#).

nValue Constant value to be added to each vector element

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.43 NppStatus nppsAddC_16u_ISfs (Npp16u *nValue*, Npp16u * *pSrcDst*, int *nLength*, int *nScaleFactor*)

16-bit unsigned short in place signal add constant, scale, then clamp to saturated value.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value to be added to each vector element

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.44 NppStatus nppsAddC_16u_Sfs (const Npp16u * *pSrc*, Npp16u *nValue*, Npp16u * *pDst*, int *nLength*, int *nScaleFactor*)

16-bit unsigned short vector add constant, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be added to each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.45 NppStatus nppsAddC_32f (const Npp32f * *pSrc*, Npp32f *nValue*, Npp32f * *pDst*, int *nLength*)

32-bit floating point signal add constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be added to each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.46 NppStatus nppsAddC_32f_I (Npp32f *nValue*, Npp32f * *pSrcDst*, int *nLength*)

32-bit floating point in place signal add constant.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be added to each vector element

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.47 NppStatus nppsAddC_32fc (const Npp32fc * *pSrc*, Npp32fc *nValue*, Npp32fc * *pDst*, int *nLength*)

32-bit floating point complex number (32 bit real, 32 bit imaginary) signal add constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be added to each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.48 NppStatus nppsAddC_32fc_I (Npp32fc *nValue*, Npp32fc * *pSrcDst*, int *nLength*)

32-bit floating point complex number (32 bit real, 32 bit imaginary) in place signal add constant.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be added to each vector element

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.49 NppStatus nppsAddC_32s_ISfs (Npp32s *nValue*, Npp32s * *pSrcDst*, int *nLength*, int *nScaleFactor*)

32-bit signed integer in place signal add constant and scale.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be added to each vector element

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.50 NppStatus nppsAddC_32s_Sfs (const Npp32s * *pSrc*, Npp32s *nValue*, Npp32s * *pDst*, int *nLength*, int *nScaleFactor*)

32-bit signed integersignal add constant and scale.

Parameters:

pSrc [Source Signal Pointer](#).

nValue Constant value to be added to each vector element

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.51 NppStatus nppsAddC_32sc_ISfs (Npp32sc *nValue*, Npp32sc * *pSrcDst*, int *nLength*, int *nScaleFactor*)

32-bit integer complex number (32 bit real, 32 bit imaginary) in place signal add constant and scale.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value to be added to each vector element

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.52 NppStatus nppsAddC_32sc_Sfs (const Npp32sc * *pSrc*, Npp32sc *nValue*, Npp32sc * *pDst*, int *nLength*, int *nScaleFactor*)

32-bit integer complex number (32 bit real, 32 bit imaginary) signal add constant and scale.

Parameters:

pSrc [Source Signal Pointer](#).

nValue Constant value to be added to each vector element

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.53 NppStatus nppsAddC_64f (const Npp64f * *pSrc*, Npp64f *nValue*, Npp64f * *pDst*, int *nLength*)

64-bit floating point signal add constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be added to each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.54 NppStatus nppsAddC_64f_I (Npp64f *nValue*, Npp64f * *pSrcDst*, int *nLength*)

64-bit floating point, in place signal add constant.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be added to each vector element

nLength Length of the vectors, number of items.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.55 NppStatus nppsAddC_64fc (const Npp64fc * *pSrc*, Npp64fc *nValue*, Npp64fc * *pDst*, int *nLength*)

64-bit floating point complex number (64 bit real, 64 bit imaginary) signal add constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be added to each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.56 NppStatus nppsAddC_64fc_I (Npp64fc *nValue*, Npp64fc * *pSrcDst*, int *nLength*)

64-bit floating point complex number (64 bit real, 64 bit imaginary) in place signal add constant.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value to be added to each vector element

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.57 NppStatus nppsAddC_8u_ISfs (Npp8u *nValue*, Npp8u * *pSrcDst*, int *nLength*, int *nScaleFactor*)

8-bit unsigned char in place signal add constant, scale, then clamp to saturated value

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value to be added to each vector element

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.58 NppStatus nppsAddC_8u_Sfs (const Npp8u * *pSrc*, Npp8u *nValue*, Npp8u * *pDst*, int *nLength*, int *nScaleFactor*)

8-bit unsigned charvector add constant, scale, then clamp to saturated value.

Parameters:

pSrc [Source Signal Pointer](#).

nValue Constant value to be added to each vector element

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.59 NppStatus nppsAddProduct_16s32s_Sfs (const Npp16s * pSrc1, const Npp16s * pSrc2, Npp32s * pDst, int nLength, int nScaleFactor)

16-bit signed short signal add product of source signal1 times source signal2 to 32-bit signed integer destination signal, with scaling, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

pDst Destination Signal Pointer. product of source1 and source2 signal elements to be added to destination elements

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.60 NppStatus nppsAddProduct_16s_Sfs (const Npp16s * pSrc1, const Npp16s * pSrc2, Npp16s * pDst, int nLength, int nScaleFactor)

16-bit signed short signal add product of source signal1 times source signal2 to destination signal, with scaling, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

pDst Destination Signal Pointer. product of source1 and source2 signal elements to be added to destination elements

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.61 NppStatus nppsAddProduct_32f (const Npp32f * pSrc1, const Npp32f * pSrc2, Npp32f * pDst, int nLength)

32-bit floating point signal add product of source signal times destination signal to destination signal, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

pDst Destination Signal Pointer. product of source1 and source2 signal elements to be added to destination elements

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.62 NppStatus nppsAddProduct_32fc (const Npp32fc * *pSrc1*, const Npp32fc * *pSrc2*, Npp32fc * *pDst*, int *nLength*)

32-bit complex floating point signal add product of source signal times destination signal to destination signal, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

pDst Destination Signal Pointer. product of source1 and source2 signal elements to be added to destination elements

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.63 NppStatus nppsAddProduct_32s_Sfs (const Npp32s * *pSrc1*, const Npp32s * *pSrc2*, Npp32s * *pDst*, int *nLength*, int *nScaleFactor*)

32-bit signed short signal add product of source signal1 times source signal2 to destination signal, with scaling, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer.

pDst Destination Signal Pointer. product of source1 and source2 signal elements to be added to destination elements

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.64 NppStatus nppsAddProduct_64f (const Npp64f * *pSrc1*, const Npp64f * *pSrc2*, Npp64f * *pDst*, int *nLength*)

64-bit floating point signal add product of source signal times destination signal to destination signal, then clamp to saturated value.

Parameters:*pSrc1* Source Signal Pointer.*pSrc2* Source Signal Pointer.*pDst* Destination Signal Pointer. product of source1 and source2 signal elements to be added to destination elements*nLength* Signal Length.**Returns:**

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.65 NppStatus nppsAddProduct_64fc (const Npp64fc * *pSrc1*, const Npp64fc * *pSrc2*, Npp64fc * *pDst*, int *nLength*)

64-bit complex floating point signal add product of source signal times destination signal to destination signal, then clamp to saturated value.

Parameters:*pSrc1* Source Signal Pointer.*pSrc2* Source Signal Pointer.*pDst* Destination Signal Pointer. product of source1 and source2 signal elements to be added to destination elements*nLength* Signal Length.**Returns:**

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.66 NppStatus nppsAddProductC_16s_ISfs (Npp16s *nValue*, Npp16s * *pSrcDst*, int *nLength*, int *nScaleFactor*)

16-bit signed short in place signal add product of signal times constant to destination signal, scale, then clamp to saturated value.

Parameters:*pSrcDst* In-Place Signal Pointer.*nValue* Constant value to be multiplied by each vector element*nLength* Signal Length.*nScaleFactor* Integer Result Scaling.**Returns:**

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.67 NppStatus nppsAddProductC_16s_Sfs (const Npp16s * *pSrc*, Npp16s *nValue*, Npp16s * *pDst*, int *nLength*, int *nScaleFactor*)

16-bit signed short signal add product of signal times constant to destination signal, scale, then clamp to saturated value.

Parameters:

pSrc [Source Signal Pointer](#).

nValue Constant value to be multiplied by each vector element

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.68 NppStatus nppsAddProductC_16sc_ISfs (Npp16sc *nValue*, Npp16sc * *pSrcDst*, int *nLength*, int *nScaleFactor*)

16-bit integer complex number (16 bit real, 16 bit imaginary)signal add product of signal times constant to destination signal, scale, then clamp to saturated value.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value to be multiplied by each vector element

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.69 NppStatus nppsAddProductC_16sc_Sfs (const Npp16sc * *pSrc*, Npp16sc *nValue*, Npp16sc * *pDst*, int *nLength*, int *nScaleFactor*)

16-bit integer complex number (16 bit real, 16 bit imaginary)signal add product of signal times constant to destination signal, scale, then clamp to saturated value.

Parameters:

pSrc [Source Signal Pointer](#).

nValue Constant value to be multiplied by each vector element

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.70 **NppStatus nppsAddProductC_16u_ISfs (Npp16u *nValue*, Npp16u * *pSrcDst*, int *nLength*, int *nScaleFactor*)**

16-bit unsigned short in place signal add product of signal times constant to destination signal, scale, then clamp to saturated value.

Parameters:

pSrcDst [In-Place Signal Pointer](#).
nValue Constant value to be multiplied by each vector element
nLength [Signal Length](#).
nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.71 **NppStatus nppsAddProductC_16u_Sfs (const Npp16u * *pSrc*, Npp16u *nValue*, Npp16u * *pDst*, int *nLength*, int *nScaleFactor*)**

16-bit unsigned short add product of signal times constant to destination signal, scale, then clamp to saturated value.

Parameters:

pSrc [Source Signal Pointer](#).
nValue Constant value to be multiplied by each vector element
pDst [Destination Signal Pointer](#).
nLength [Signal Length](#).
nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.72 **NppStatus nppsAddProductC_32f (const Npp32f * *pSrc*, Npp32f *nValue*, Npp32f * *pDst*, int *nLength*)**

32-bit floating point signal add product of signal times constant to destination signal.

Parameters:

pSrc [Source Signal Pointer](#).
nValue Constant value to be multiplied by each vector element
pDst [Destination Signal Pointer](#).
nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.73 NppStatus nppsAddProductC_32f_I (Npp32f *nValue*, Npp32f * *pSrcDst*, int *nLength*)

32-bit floating point in place signal add product of signal times constant to destination signal.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value to be multiplied by each vector element

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.74 NppStatus nppsAddProductC_32s_ISfs (Npp32s *nValue*, Npp32s * *pSrcDst*, int *nLength*, int *nScaleFactor*)

32-bit signed integer in place signal add product of signal times constant to destination signal and scale.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value to be multiplied by each vector element

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.75 NppStatus nppsAddProductC_32s_Sfs (const Npp32s * *pSrc*, Npp32s *nValue*, Npp32s * *pDst*, int *nLength*, int *nScaleFactor*)

32-bit signed integer signal add product of signal times constant to destination signal and scale.

Parameters:

pSrc [Source Signal Pointer](#).

nValue Constant value to be multiplied by each vector element

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.76 NppStatus nppsAddProductC_32sc_ISfs (Npp32sc *nValue*, Npp32sc * *pSrcDst*, int *nLength*, int *nScaleFactor*)

32-bit integer complex number (32 bit real, 32 bit imaginary) in place signal add product of signal times constant to destination signal and scale.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be multiplied by each vector element

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.77 NppStatus nppsAddProductC_32sc_Sfs (const Npp32sc * *pSrc*, Npp32sc *nValue*, Npp32sc * *pDst*, int *nLength*, int *nScaleFactor*)

32-bit integer complex number (32 bit real, 32 bit imaginary) signal add product of signal times constant to destination signal and scale.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be multiplied by each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.78 NppStatus nppsAddProductC_8u_ISfs (Npp8u *nValue*, Npp8u * *pSrcDst*, int *nLength*, int *nScaleFactor*)

8-bit unsigned char in place signal add product of signal times constant to destination signal, scale, then clamp to saturated value

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be multiplied by each vector element

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.79 NppStatus nppsAddProductC_8u_Sfs (const Npp8u * *pSrc*, Npp8u *nValue*, Npp8u * *pDst*, int *nLength*, int *nScaleFactor*)

8-bit unsigned char add product of signal times constant to destination signal, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be multiplied by each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.80 NppStatus nppsAnd_16u (const Npp16u * *pSrc1*, const Npp16u * *pSrc2*, Npp16u * *pDst*, int *nLength*)

16-bit unsigned short signal and with signal.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal2 elements to be anded with signal1 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.81 NppStatus nppsAnd_16u_I (const Npp16u * *pSrc*, Npp16u * *pSrcDst*, int *nLength*)

16-bit unsigned short in place signal and with signal.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal2 elements to be anded with signal1 elements

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.82 NppStatus nppsAnd_32u (const Npp32u * *pSrc1*, const Npp32u * *pSrc2*, Npp32u * *pDst*, int *nLength*)

32-bit unsigned integer signal and with signal.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal2 elements to be anded with signal1 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.83 NppStatus nppsAnd_32u_I (const Npp32u * *pSrc*, Npp32u * *pSrcDst*, int *nLength*)

32-bit unsigned integer in place signal and with signal.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal2 elements to be anded with signal1 elements

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.84 NppStatus nppsAnd_8u (const Npp8u * *pSrc1*, const Npp8u * *pSrc2*, Npp8u * *pDst*, int *nLength*)

8-bit unsigned char signal and with signal.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal2 elements to be anded with signal1 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.85 NppStatus nppsAnd_8u_I (const Npp8u * *pSrc*, Npp8u * *pSrcDst*, int *nLength*)

8-bit unsigned char in place signal and with signal.

Parameters:

pSrc [Source Signal Pointer](#).

pSrcDst [In-Place Signal Pointer](#). signal2 elements to be anded with signal1 elements

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.86 NppStatus nppsAndC_16u (const Npp16u * *pSrc*, Npp16u *nValue*, Npp16u * *pDst*, int *nLength*)

16-bit unsigned short signal and with constant.

Parameters:

pSrc [Source Signal Pointer](#).

nValue Constant value to be anded with each vector element

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.87 NppStatus nppsAndC_16u_I (Npp16u *nValue*, Npp16u * *pSrcDst*, int *nLength*)

16-bit unsigned short in place signal and with constant.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value to be anded with each vector element

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.88 NppStatus nppsAndC_32u (const Npp32u * *pSrc*, Npp32u *nValue*, Npp32u * *pDst*, int *nLength*)

32-bit unsigned integer signal and with constant.

Parameters:

pSrc Source Signal Pointer.
nValue Constant value to be added with each vector element
pDst Destination Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.89 NppStatus nppsAndC_32u_I (Npp32u nValue, Npp32u * pSrcDst, int nLength)

32-bit unsigned integer in place signal and with constant.

Parameters:

pSrcDst In-Place Signal Pointer.
nValue Constant value to be added with each vector element
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.90 NppStatus nppsAndC_8u (const Npp8u * pSrc, Npp8u nValue, Npp8u * pDst, int nLength)

8-bit unsigned char signal and with constant.

Parameters:

pSrc Source Signal Pointer.
nValue Constant value to be added with each vector element
pDst Destination Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.91 NppStatus nppsAndC_8u_I (Npp8u nValue, Npp8u * pSrcDst, int nLength)

8-bit unsigned char in place signal and with constant.

Parameters:

pSrcDst In-Place Signal Pointer.
nValue Constant value to be added with each vector element
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.92 NppStatus nppsArctan_32f (const Npp32f * *pSrc*, Npp32f * *pDst*, int *nLength*)

32-bit floating point signal inverse tangent.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.93 NppStatus nppsArctan_32f_I (Npp32f * *pSrcDst*, int *nLength*)

32-bit floating point signal inverse tangent.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.94 NppStatus nppsArctan_64f (const Npp64f * *pSrc*, Npp64f * *pDst*, int *nLength*)

64-bit floating point signal inverse tangent.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.95 NppStatus nppsArctan_64f_I (Npp64f * *pSrcDst*, int *nLength*)

64-bit floating point signal inverse tangent.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.96 NppStatus nppsCauchy_32f_I (Npp32f * pSrcDst, int nLength, Npp32f nParam)

32-bit floating point signal Cauchy error calculation.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nLength [Signal Length](#).

nParam constant used in Cauchy formula

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.97 NppStatus nppsCauchyD_32f_I (Npp32f * pSrcDst, int nLength, Npp32f nParam)

32-bit floating point signal Cauchy first derivative.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nLength [Signal Length](#).

nParam constant used in Cauchy formula

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.98 NppStatus nppsCauchyDD2_32f_I (Npp32f * pSrcDst, Npp32f * pD2FVal, int nLength, Npp32f nParam)

32-bit floating point signal Cauchy first and second derivatives.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

pD2FVal [Source Signal Pointer](#). This signal contains the second derivative of the source signal.

nLength [Signal Length](#).

nParam constant used in Cauchy formula

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.99 NppStatus nppsCopy_16s (const Npp16s * pSrc, Npp16s * pDst, int len)

16-bit signed short, vector copy method.

Parameters:

pSrc [Source Signal Pointer](#).

pDst Destination Signal Pointer.

len Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.100 NppStatus nppsCopy_16sc (const Npp16sc * pSrc, Npp16sc * pDst, int len)

16-bit complex short, vector copy method.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

len Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.101 NppStatus nppsCopy_32f (const Npp32f * pSrc, Npp32f * pDst, int len)

32-bit float, vector copy method.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

len Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.102 NppStatus nppsCopy_32fc (const Npp32fc * pSrc, Npp32fc * pDst, int len)

32-bit complex float, vector copy method.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

len Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.103 NppStatus nppsCopy_32s (const Npp32s * *pSrc*, Npp32s * *pDst*, int *nLength*)

32-bit signed integer, vector copy method.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.104 NppStatus nppsCopy_32sc (const Npp32sc * *pSrc*, Npp32sc * *pDst*, int *len*)

32-bit complex signed integer, vector copy method.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

len Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.105 NppStatus nppsCopy_64fc (const Npp64fc * *pSrc*, Npp64fc * *pDst*, int *len*)

64-bit complex double, vector copy method.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

len Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.106 NppStatus nppsCopy_64s (const Npp64s * *pSrc*, Npp64s * *pDst*, int *len*)

64-bit signed integer, vector copy method.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

len Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.107 NppStatus nppsCopy_64sc (const Npp64sc * *pSrc*, Npp64sc * *pDst*, int *len*)

64-bit complex signed integer, vector copy method.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

len Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.108 NppStatus nppsCopy_8u (const Npp8u * *pSrc*, Npp8u * *pDst*, int *len*)

8-bit unsigned char, vector copy method

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

len Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.109 NppStatus nppsCubrt_32f (const Npp32f * *pSrc*, Npp32f * *pDst*, int *nLength*)

32-bit floating point signal cube root.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.110 NppStatus nppsCubrt_32s16s_Sfs (const Npp32s * *pSrc*, Npp16s * *pDst*, int *nLength*, int *nScaleFactor*)

32-bit signed integer signal cube root, scale, then clamp to 16-bit signed integer saturated value.

Parameters:

pSrc Source Signal Pointer.
pDst Destination Signal Pointer.
nLength Signal Length.
nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.111 NppStatus nppsDiv_16s_ISfs (const Npp16s * *pSrc*, Npp16s * *pSrcDst*, int *nLength*, int *nScaleFactor*)

16-bit signed short in place signal divide signal, with scaling, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.
pSrcDst In-Place Signal Pointer. signal1 divisor elements to be divided into signal2 dividend elements
nLength Signal Length.
nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.112 NppStatus nppsDiv_16s_Sfs (const Npp16s * *pSrc1*, const Npp16s * *pSrc2*, Npp16s * *pDst*, int *nLength*, int *nScaleFactor*)

16-bit signed short signal divide signal, scale, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.
pSrc2 Source Signal Pointer, signal1 divisor elements to be divided into signal2 dividend elements.
pDst Destination Signal Pointer.
nLength Signal Length.
nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.113 **NppStatus nppsDiv_16sc_ISfs** (const Npp16sc * *pSrc*, Npp16sc * *pSrcDst*, int *nLength*, int *nScaleFactor*)

16-bit complex signed short in place signal divide signal, with scaling, then clamp to saturated value.

Parameters:

pSrc [Source Signal Pointer](#).

pSrcDst [In-Place Signal Pointer](#). signal1 divisor elements to be divided into signal2 dividend elements

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.114 **NppStatus nppsDiv_16sc_Sfs** (const Npp16sc * *pSrc1*, const Npp16sc * *pSrc2*, Npp16sc * *pDst*, int *nLength*, int *nScaleFactor*)

16-bit signed complex short signal divide signal, scale, then clamp to saturated value.

Parameters:

pSrc1 [Source Signal Pointer](#).

pSrc2 [Source Signal Pointer](#), signal1 divisor elements to be divided into signal2 dividend elements.

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.115 **NppStatus nppsDiv_16u_ISfs** (const Npp16u * *pSrc*, Npp16u * *pSrcDst*, int *nLength*, int *nScaleFactor*)

16-bit unsigned short in place signal divide signal, with scaling, then clamp to saturated value.

Parameters:

pSrc [Source Signal Pointer](#).

pSrcDst [In-Place Signal Pointer](#). signal1 divisor elements to be divided into signal2 dividend elements

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.116 NppStatus nppsDiv_16u_Sfs (const Npp16u * *pSrc1*, const Npp16u * *pSrc2*, Npp16u * *pDst*, int *nLength*, int *nScaleFactor*)

16-bit unsigned short signal divide signal, scale, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal1 divisor elements to be divided into signal2 dividend elements.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.117 NppStatus nppsDiv_32f (const Npp32f * *pSrc1*, const Npp32f * *pSrc2*, Npp32f * *pDst*, int *nLength*)

32-bit floating point signal divide signal, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal1 divisor elements to be divided into signal2 dividend elements.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.118 NppStatus nppsDiv_32f_I (const Npp32f * *pSrc*, Npp32f * *pSrcDst*, int *nLength*)

32-bit floating point in place signal divide signal, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal1 divisor elements to be divided into signal2 dividend elements

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.119 `NppStatus nppsDiv_32fc (const Npp32fc * pSrc1, const Npp32fc * pSrc2, Npp32fc * pDst, int nLength)`

32-bit complex floating point signal divide signal, then clamp to saturated value.

Parameters:

pSrc1 [Source Signal Pointer](#).

pSrc2 [Source Signal Pointer](#), signal1 divisor elements to be divided into signal2 dividend elements.

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.120 `NppStatus nppsDiv_32fc_I (const Npp32fc * pSrc, Npp32fc * pSrcDst, int nLength)`

32-bit complex floating point in place signal divide signal, then clamp to saturated value.

Parameters:

pSrc [Source Signal Pointer](#).

pSrcDst [In-Place Signal Pointer](#). signal1 divisor elements to be divided into signal2 dividend elements

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.121 `NppStatus nppsDiv_32s16s_Sfs (const Npp16s * pSrc1, const Npp32s * pSrc2, Npp16s * pDst, int nLength, int nScaleFactor)`

32-bit signed integer signal divided by 16-bit signed short signal, scale, then clamp to 16-bit signed short saturated value.

Parameters:

pSrc1 [Source Signal Pointer](#).

pSrc2 [Source Signal Pointer](#), signal1 divisor elements to be divided into signal2 dividend elements.

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.122 NppStatus nppsDiv_32s_ISfs (const Npp32s * *pSrc*, Npp32s * *pSrcDst*, int *nLength*, int *nScaleFactor*)

32-bit signed integer in place signal divide signal, with scaling, then clamp to saturated value.

Parameters:

pSrc [Source Signal Pointer](#).

pSrcDst [In-Place Signal Pointer](#), signal1 divisor elements to be divided into signal2 dividend elements

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.123 NppStatus nppsDiv_32s_Sfs (const Npp32s * *pSrc1*, const Npp32s * *pSrc2*, Npp32s * *pDst*, int *nLength*, int *nScaleFactor*)

32-bit signed integer signal divide signal, scale, then clamp to saturated value.

Parameters:

pSrc1 [Source Signal Pointer](#).

pSrc2 [Source Signal Pointer](#), signal1 divisor elements to be divided into signal2 dividend elements.

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.124 NppStatus nppsDiv_64f (const Npp64f * *pSrc1*, const Npp64f * *pSrc2*, Npp64f * *pDst*, int *nLength*)

64-bit floating point signal divide signal, then clamp to saturated value.

Parameters:

pSrc1 [Source Signal Pointer](#).

pSrc2 [Source Signal Pointer](#), signal1 divisor elements to be divided into signal2 dividend elements.

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.125 NppStatus nppsDiv_64f_I (const Npp64f * pSrc, Npp64f * pSrcDst, int nLength)

64-bit floating point in place signal divide signal, then clamp to saturated value.

Parameters:

pSrc [Source Signal Pointer](#).

pSrcDst [In-Place Signal Pointer](#). signal1 divisor elements to be divided into signal2 dividend elements

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.126 NppStatus nppsDiv_64fc (const Npp64fc * pSrc1, const Npp64fc * pSrc2, Npp64fc * pDst, int nLength)

64-bit complex floating point signal divide signal, then clamp to saturated value.

Parameters:

pSrc1 [Source Signal Pointer](#).

pSrc2 [Source Signal Pointer](#), signal1 divisor elements to be divided into signal2 dividend elements.

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.127 NppStatus nppsDiv_64fc_I (const Npp64fc * pSrc, Npp64fc * pSrcDst, int nLength)

64-bit complex floating point in place signal divide signal, then clamp to saturated value.

Parameters:

pSrc [Source Signal Pointer](#).

pSrcDst [In-Place Signal Pointer](#). signal1 divisor elements to be divided into signal2 dividend elements

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.128 NppStatus nppsDiv_8u_ISfs (const Npp8u * pSrc, Npp8u * pSrcDst, int nLength, int nScaleFactor)

8-bit unsigned char in place signal divide signal, with scaling, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal1 divisor elements to be divided into signal2 dividend elements

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.129 `NppStatus nppsDiv_8u_Sfs (const Npp8u * pSrc1, const Npp8u * pSrc2, Npp8u * pDst, int nLength, int nScaleFactor)`

8-bit unsigned char signal divide signal, scale, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal1 divisor elements to be divided into signal2 dividend elements.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.130 `NppStatus nppsDiv_Round_16s_ISfs (const Npp16s * pSrc, Npp16s * pSrcDst, int nLength, NppRoundMode nRndMode, int nScaleFactor)`

16-bit signed short in place signal divide signal, with scaling, rounding then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal1 divisor elements to be divided into signal2 dividend elements

nLength Signal Length.

nRndMode various rounding modes.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.131 `NppStatus nppsDiv_Round_16s_Sfs (const Npp16s * pSrc1, const Npp16s * pSrc2, Npp16s * pDst, int nLength, NppRoundMode nRndMode, int nScaleFactor)`

16-bit signed short signal divide signal, scale, round, then clamp to saturated value.

Parameters:

pSrc1 [Source Signal Pointer](#).

pSrc2 [Source Signal Pointer](#), signal1 divisor elements to be divided into signal2 dividend elements.

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

nRndMode various rounding modes.

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.132 `NppStatus nppsDiv_Round_16u_ISfs (const Npp16u * pSrc, Npp16u * pSrcDst, int nLength, NppRoundMode nRndMode, int nScaleFactor)`

16-bit unsigned short in place signal divide signal, with scaling, rounding then clamp to saturated value.

Parameters:

pSrc [Source Signal Pointer](#).

pSrcDst [In-Place Signal Pointer](#), signal1 divisor elements to be divided into signal2 dividend elements

nLength [Signal Length](#).

nRndMode various rounding modes.

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.133 `NppStatus nppsDiv_Round_16u_Sfs (const Npp16u * pSrc1, const Npp16u * pSrc2, Npp16u * pDst, int nLength, NppRoundMode nRndMode, int nScaleFactor)`

16-bit unsigned short signal divide signal, scale, round, then clamp to saturated value.

Parameters:

pSrc1 [Source Signal Pointer](#).

pSrc2 [Source Signal Pointer](#), signal1 divisor elements to be divided into signal2 dividend elements.

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

nRndMode various rounding modes.

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.134 `NppStatus nppsDiv_Round_8u_ISfs (const Npp8u * pSrc, Npp8u * pSrcDst, int nLength, NppRoundMode nRndMode, int nScaleFactor)`

8-bit unsigned char in place signal divide signal, with scaling, rounding then clamp to saturated value.

Parameters:

pSrc [Source Signal Pointer](#).

pSrcDst [In-Place Signal Pointer](#). signal1 divisor elements to be divided into signal2 dividend elements

nLength [Signal Length](#).

nRndMode various rounding modes.

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.135 `NppStatus nppsDiv_Round_8u_Sfs (const Npp8u * pSrc1, const Npp8u * pSrc2, Npp8u * pDst, int nLength, NppRoundMode nRndMode, int nScaleFactor)`

8-bit unsigned char signal divide signal, scale, then clamp to saturated value.

Parameters:

pSrc1 [Source Signal Pointer](#).

pSrc2 [Source Signal Pointer](#), signal1 divisor elements to be divided into signal2 dividend elements.

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

nRndMode various rounding modes.

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.136 `NppStatus nppsDivC_16s_ISfs (Npp16s nValue, Npp16s * pSrcDst, int nLength, int nScaleFactor)`

16-bit signed short in place signal divided by constant, scale, then clamp to saturated value.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value to be divided into each vector element

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.137 NppStatus nppsDivC_16s_Sfs (const Npp16s * *pSrc*, Npp16s *nValue*, Npp16s * *pDst*, int *nLength*, int *nScaleFactor*)

16-bit signed short signal divided by constant, scale, then clamp to saturated value.

Parameters:

pSrc [Source Signal Pointer](#).

nValue Constant value to be divided into each vector element

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.138 NppStatus nppsDivC_16sc_ISfs (Npp16sc *nValue*, Npp16sc * *pSrcDst*, int *nLength*, int *nScaleFactor*)

16-bit integer complex number (16 bit real, 16 bit imaginary) signal divided by constant, scale, then clamp to saturated value.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value to be divided into each vector element

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.139 NppStatus nppsDivC_16sc_Sfs (const Npp16sc * *pSrc*, Npp16sc *nValue*, Npp16sc * *pDst*, int *nLength*, int *nScaleFactor*)

16-bit integer complex number (16 bit real, 16 bit imaginary) signal divided by constant, scale, then clamp to saturated value.

Parameters:

pSrc [Source Signal Pointer](#).

nValue Constant value to be divided into each vector element

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.140 NppStatus nppsDivC_16u_ISfs (Npp16u *nValue*, Npp16u * *pSrcDst*, int *nLength*, int *nScaleFactor*)

16-bit unsigned short in place signal divided by constant, scale, then clamp to saturated value.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be divided into each vector element

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.141 NppStatus nppsDivC_16u_Sfs (const Npp16u * *pSrc*, Npp16u *nValue*, Npp16u * *pDst*, int *nLength*, int *nScaleFactor*)

16-bit unsigned short signal divided by constant, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be divided into each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.142 NppStatus nppsDivC_32f (const Npp32f * *pSrc*, Npp32f *nValue*, Npp32f * *pDst*, int *nLength*)

32-bit floating point signal divided by constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be divided into each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.143 NppStatus nppsDivC_32f_I (Npp32f *nValue*, Npp32f * *pSrcDst*, int *nLength*)

32-bit floating point in place signal divided by constant.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value to be divided into each vector element

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.144 NppStatus nppsDivC_32fc (const Npp32fc * *pSrc*, Npp32fc *nValue*, Npp32fc * *pDst*, int *nLength*)

32-bit floating point complex number (32 bit real, 32 bit imaginary) signal divided by constant.

Parameters:

pSrc [Source Signal Pointer](#).

nValue Constant value to be divided into each vector element

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.145 NppStatus nppsDivC_32fc_I (Npp32fc *nValue*, Npp32fc * *pSrcDst*, int *nLength*)

32-bit floating point complex number (32 bit real, 32 bit imaginary) in place signal divided by constant.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value to be divided into each vector element

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.146 NppStatus nppsDivC_32s_ISfs (Npp32s *nValue*, Npp32s * *pSrcDst*, int *nLength*, int *nScaleFactor*)

32-bit signed integer in place signal divided by constant and scale.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be divided into each vector element

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.147 `NppStatus nppsDivC_32s_Sfs (const Npp32s *pSrc, Npp32s nValue, Npp32s *pDst, int nLength, int nScaleFactor)`

32-bit signed integer signal divided by constant and scale.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be divided into each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.148 `NppStatus nppsDivC_32sc_ISfs (Npp32sc nValue, Npp32sc *pSrcDst, int nLength, int nScaleFactor)`

32-bit integer complex number (32 bit real, 32 bit imaginary) in place signal divided by constant and scale.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be divided into each vector element

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.149 **NppStatus nppsDivC_32sc_Sfs** (const Npp32sc * *pSrc*, Npp32sc *nValue*, Npp32sc * *pDst*, int *nLength*, int *nScaleFactor*)

32-bit integer complex number (32 bit real, 32 bit imaginary) signal divided by constant and scale.

Parameters:

pSrc [Source Signal Pointer](#).

nValue Constant value to be divided into each vector element

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.150 **NppStatus nppsDivC_64f** (const Npp64f * *pSrc*, Npp64f *nValue*, Npp64f * *pDst*, int *nLength*)

64-bit floating point signal divided by constant.

Parameters:

pSrc [Source Signal Pointer](#).

nValue Constant value to be divided into each vector element

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.151 **NppStatus nppsDivC_64f_I** (Npp64f *nValue*, Npp64f * *pSrcDst*, int *nLength*)

64-bit floating point in place signal divided by constant.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value to be divided into each vector element

nLength Length of the vectors, number of items.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.152 NppStatus nppsDivC_64fc (const Npp64fc * *pSrc*, Npp64fc *nValue*, Npp64fc * *pDst*, int *nLength*)

64-bit floating point complex number (64 bit real, 64 bit imaginary) signal divided by constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be divided into each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.153 NppStatus nppsDivC_64fc_I (Npp64fc *nValue*, Npp64fc * *pSrcDst*, int *nLength*)

64-bit floating point complex number (64 bit real, 64 bit imaginary) in place signal divided by constant.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be divided into each vector element

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.154 NppStatus nppsDivC_8u_ISfs (Npp8u *nValue*, Npp8u * *pSrcDst*, int *nLength*, int *nScaleFactor*)

8-bit unsigned char in place signal divided by constant, scale, then clamp to saturated value

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be divided into each vector element

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.155 `NppStatus nppsDivC_8u_Sfs (const Npp8u * pSrc, Npp8u nValue, Npp8u * pDst, int nLength, int nScaleFactor)`

8-bit unsigned char signal divided by constant, scale, then clamp to saturated value.

Parameters:

pSrc [Source Signal Pointer](#).

nValue Constant value to be divided into each vector element

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.156 `NppStatus nppsDivCRev_16s (const Npp16s * pSrc, Npp16s nValue, Npp16s * pDst, int nLength)`

16-bit signed short constant divided by signal, then clamp to saturated value.

Parameters:

pSrc [Source Signal Pointer](#).

nValue Constant value to be divided by each vector element

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.157 `NppStatus nppsDivCRev_16s_I (Npp16s nValue, Npp16s * pSrcDst, int nLength)`

16-bit signed short in place constant divided by signal, then clamp to saturated value.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value to be divided by each vector element

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.158 NppStatus nppsDivCRev_16u (const Npp16u * *pSrc*, Npp16u *nValue*, Npp16u * *pDst*, int *nLength*)

16-bit unsigned short vector divided by constant, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be divided by each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.159 NppStatus nppsDivCRev_16u_I (Npp16u *nValue*, Npp16u * *pSrcDst*, int *nLength*)

16-bit unsigned short in place constant divided by signal, then clamp to saturated value.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be divided by each vector element

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.160 NppStatus nppsDivCRev_32f (const Npp32f * *pSrc*, Npp32f *nValue*, Npp32f * *pDst*, int *nLength*)

32-bit floating point constant divided by signal.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be divided by each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.161 NppStatus nppsDivCRev_32f_I (Npp32f *nValue*, Npp32f * *pSrcDst*, int *nLength*)

32-bit floating point in place constant divided by signal.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value to be divided by each vector element

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.162 NppStatus nppsDivCRev_32s (const Npp32s * *pSrc*, Npp32s *nValue*, Npp32s * *pDst*, int *nLength*)

32-bit signed integer constant divided by signal.

Parameters:

pSrc [Source Signal Pointer](#).

nValue Constant value to be divided by each vector element

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.163 NppStatus nppsDivCRev_32s_I (Npp32s *nValue*, Npp32s * *pSrcDst*, int *nLength*)

32-bit signed integer in place constant divided by signal.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value to be divided by each vector element

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.164 NppStatus nppsDivCRev_64f (const Npp64f * *pSrc*, Npp64f *nValue*, Npp64f * *pDst*, int *nLength*)

64-bit floating point constant divided by signal.

Parameters:

pSrc Source Signal Pointer.
nValue Constant value to be divided by each vector element
pDst Destination Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.165 NppStatus nppsDivCRev_64f_I (Npp64f nValue, Npp64f * pSrcDst, int nLength)

64-bit floating point in place constant divided by signal.

Parameters:

pSrcDst In-Place Signal Pointer.
nValue Constant value to be divided by each vector element
nLength Length of the vectors, number of items.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.166 NppStatus nppsDivCRev_8u (const Npp8u * pSrc, Npp8u nValue, Npp8u * pDst, int nLength)

8-bit unsigned char signal divided by constant, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.
nValue Constant value to be divided by each vector element
pDst Destination Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.167 NppStatus nppsDivCRev_8u_I (Npp8u nValue, Npp8u * pSrcDst, int nLength)

8-bit unsigned char signal in place constant divided by signal, scale, then clamp to saturated value

Parameters:

pSrcDst In-Place Signal Pointer.
nValue Constant value to be divided by each vector element
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.168 NppStatus nppsExp_16s_ISfs (Npp16s * *pSrcDst*, int *nLength*, int *nScaleFactor*)

16-bit signed short signal exponent, scale, then clamp to saturated value.

Parameters:

pSrcDst In-Place Signal Pointer.
nLength Signal Length.
nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.169 NppStatus nppsExp_16s_Sfs (const Npp16s * *pSrc*, Npp16s * *pDst*, int *nLength*, int *nScaleFactor*)

16-bit signed short signal exponent, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.
pDst Destination Signal Pointer.
nLength Signal Length.
nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.170 NppStatus nppsExp_32f (const Npp32f * *pSrc*, Npp32f * *pDst*, int *nLength*)

32-bit floating point signal exponent.

Parameters:

pSrc Source Signal Pointer.
pDst Destination Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.171 NppStatus nppsExp_32f64f (const Npp32f * *pSrc*, Npp64f * *pDst*, int *nLength*)

32-bit floating point signal exponent with 64-bit floating point result.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.172 NppStatus nppsExp_32f_I (Npp32f * *pSrcDst*, int *nLength*)

32-bit floating point signal exponent.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.173 NppStatus nppsExp_32s_ISfs (Npp32s * *pSrcDst*, int *nLength*, int *nScaleFactor*)

32-bit signed integer signal exponent, scale, then clamp to saturated value.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.174 NppStatus nppsExp_32s_Sfs (const Npp32s * *pSrc*, Npp32s * *pDst*, int *nLength*, int *nScaleFactor*)

32-bit signed integer signal exponent, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.175 NppStatus nppsExp_64f (const Npp64f * *pSrc*, Npp64f * *pDst*, int *nLength*)

64-bit floating point signal exponent.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.176 NppStatus nppsExp_64f_I (Npp64f * *pSrcDst*, int *nLength*)

64-bit floating point signal exponent.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.177 NppStatus nppsExp_64s_ISfs (Npp64s * *pSrcDst*, int *nLength*, int *nScaleFactor*)

64-bit signed integer signal exponent, scale, then clamp to saturated value.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.178 NppStatus nppsExp_64s_Sfs (const Npp64s * *pSrc*, Npp64s * *pDst*, int *nLength*, int *nScaleFactor*)

64-bit signed integer signal exponent, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.179 void nppsFree (void * *pValues*)

Free method for any 2D allocated memory.

This method should be used to free memory allocated with any of the nppiMalloc_<modifier> methods.

Parameters:

pValues A pointer to memory allocated using nppiMalloc_<modifier>.

7.5.1.180 NppStatus nppsIntegral_32s (const Npp32s * *pSrc*, Npp32s * *pDst*, int *nLength*, Npp8u * *pDeviceBuffer*)

7.5.1.181 NppStatus nppsIntegralGetBufferSize_32s (int *nLength*, int * *hpBufferSize*)

7.5.1.182 NppStatus nppsLn_16s_ISfs (Npp16s * *pSrcDst*, int *nLength*, int *nScaleFactor*)

16-bit signed short signal natural logarithm, scale, then clamp to saturated value.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.183 NppStatus nppsLn_16s_Sfs (const Npp16s * *pSrc*, Npp16s * *pDst*, int *nLength*, int *nScaleFactor*)

16-bit signed short signal natural logarithm, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.184 NppStatus nppsLn_32f (const Npp32f * *pSrc*, Npp32f * *pDst*, int *nLength*)

32-bit floating point signal natural logarithm.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.185 NppStatus nppsLn_32f_I (Npp32f * *pSrcDst*, int *nLength*)

32-bit floating point signal natural logarithm.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.186 NppStatus nppsLn_32s16s_Sfs (const Npp32s * *pSrc*, Npp16s * *pDst*, int *nLength*, int *nScaleFactor*)

32-bit signed integer signal natural logarithm, scale, then clamp to 16-bit signed short saturated value.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.187 NppStatus nppsLn_32s_ISfs (Npp32s * *pSrcDst*, int *nLength*, int *nScaleFactor*)

32-bit signed integer signal natural logarithm, scale, then clamp to saturated value.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.188 NppStatus nppsLn_32s_Sfs (const Npp32s * *pSrc*, Npp32s * *pDst*, int *nLength*, int *nScaleFactor*)

32-bit signed integer signal natural logarithm, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.189 NppStatus nppsLn_64f (const Npp64f * *pSrc*, Npp64f * *pDst*, int *nLength*)

64-bit floating point signal natural logarithm.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.190 NppStatus nppsLn_64f32f (const Npp64f * *pSrc*, Npp32f * *pDst*, int *nLength*)

64-bit floating point signal natural logarithm with 32-bit floating point result.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.191 NppStatus nppsLn_64f_I (Npp64f * *pSrcDst*, int *nLength*)

64-bit floating point signal natural logarithm.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.192 NppStatus nppsLShiftC_16s (const Npp16s * *pSrc*, int *nValue*, Npp16s * *pDst*, int *nLength*)

16-bit signed short signal left shift with constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be used to left shift each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.193 NppStatus nppsLShiftC_16s_I (int *nValue*, Npp16s * *pSrcDst*, int *nLength*)

16-bit signed short in place signal left shift with constant.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be used to left shift each vector element

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.194 NppStatus nppsLShiftC_16u (const Npp16u * *pSrc*, int *nValue*, Npp16u * *pDst*, int *nLength*)

16-bit unsigned short signal left shift with constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be used to left shift each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.195 NppStatus nppsLShiftC_16u_I (int *nValue*, Npp16u **pSrcDst*, int *nLength*)

16-bit unsigned short in place signal left shift with constant.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be used to left shift each vector element

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.196 NppStatus nppsLShiftC_32s (const Npp32s **pSrc*, int *nValue*, Npp32s **pDst*, int *nLength*)

32-bit signed integer signal left shift with constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be used to left shift each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.197 NppStatus nppsLShiftC_32s_I (int *nValue*, Npp32s **pSrcDst*, int *nLength*)

32-bit signed signed integer in place signal left shift with constant.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be used to left shift each vector element

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.198 NppStatus nppsLShiftC_32u (const Npp32u * *pSrc*, int *nValue*, Npp32u * *pDst*, int *nLength*)

32-bit unsigned integer signal left shift with constant.

Parameters:

pSrc [Source Signal Pointer](#).

nValue Constant value to be used to left shift each vector element

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.199 NppStatus nppsLShiftC_32u_I (int *nValue*, Npp32u * *pSrcDst*, int *nLength*)

32-bit unsigned signed integer in place signal left shift with constant.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value to be used to left shift each vector element

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.200 NppStatus nppsLShiftC_8u (const Npp8u * *pSrc*, int *nValue*, Npp8u * *pDst*, int *nLength*)

8-bit unsigned char signal left shift with constant.

Parameters:

pSrc [Source Signal Pointer](#).

nValue Constant value to be used to left shift each vector element

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.201 NppStatus nppsLShiftC_8u_I (int *nValue*, Npp8u * *pSrcDst*, int *nLength*)

8-bit unsigned char in place signal left shift with constant.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value to be used to left shift each vector element

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.202 Npp16s* nppsMalloc_16s (int *nSize*)

16-bit signal allocator.

Parameters:

nSize Number of shorts in the new signal.

Returns:

A pointer to the new signal. 0 (NULL-pointer) indicates that an error occurred during allocation.

7.5.1.203 Npp16sc* nppsMalloc_16sc (int *nSize*)

16-bit complex-value signal allocator.

Parameters:

nSize Number of 16-bit complex numbers in the new signal.

Returns:

A pointer to the new signal. 0 (NULL-pointer) indicates that an error occurred during allocation.

7.5.1.204 Npp16u* nppsMalloc_16u (int *nSize*)

16-bit unsigned signal allocator.

Parameters:

nSize Number of unsigned shorts in the new signal.

Returns:

A pointer to the new signal. 0 (NULL-pointer) indicates that an error occurred during allocation.

7.5.1.205 Npp32f* nppsMalloc_32f (int *nSize*)

32-bit float signal allocator.

Parameters:

nSize Number of floats in the new signal.

Returns:

A pointer to the new signal. 0 (NULL-pointer) indicates that an error occurred during allocation.

7.5.1.206 Npp32fc* nppsMalloc_32fc (int *nSize*)

32-bit complex float signal allocator.

Parameters:

nSize Number of complex float values in the new signal.

Returns:

A pointer to the new signal. 0 (NULL-pointer) indicates that an error occurred during allocation.

7.5.1.207 Npp32s* nppsMalloc_32s (int *nSize*)

32-bit integer signal allocator.

Parameters:

nSize Number of ints in the new signal.

Returns:

A pointer to the new signal. 0 (NULL-pointer) indicates that an error occurred during allocation.

7.5.1.208 Npp32sc* nppsMalloc_32sc (int *nSize*)

32-bit complex integer signal allocator.

Parameters:

nSize Number of complex integner values in the new signal.

Returns:

A pointer to the new signal. 0 (NULL-pointer) indicates that an error occurred during allocation.

7.5.1.209 Npp32u* nppsMalloc_32u (int nSize)

32-bit unsigned signal allocator.

Parameters:

nSize Number of unsigned ints in the new signal.

Returns:

A pointer to the new signal. 0 (NULL-pointer) indicates that an error occurred during allocation.

7.5.1.210 Npp64f* nppsMalloc_64f (int nSize)

64-bit float (double) signal allocator.

Parameters:

nSize Number of doubles in the new signal.

Returns:

A pointer to the new signal. 0 (NULL-pointer) indicates that an error occurred during allocation.

7.5.1.211 Npp64fc* nppsMalloc_64fc (int nSize)

64-bit complex complex signal allocator.

Parameters:

nSize Number of complex double values in the new signal.

Returns:

A pointer to the new signal. 0 (NULL-pointer) indicates that an error occurred during allocation.

7.5.1.212 Npp64s* nppsMalloc_64s (int nSize)

64-bit long integer signal allocator.

Parameters:

nSize Number of long ints in the new signal.

Returns:

A pointer to the new signal. 0 (NULL-pointer) indicates that an error occurred during allocation.

7.5.1.213 Npp64sc* nppsMalloc_64sc (int nSize)

64-bit complex long integer signal allocator.

Parameters:

nSize Number of complex long int values in the new signal.

Returns:

A pointer to the new signal. 0 (NULL-pointer) indicates that an error occurred during allocation.

7.5.1.214 Npp8u* nppsMalloc_8u (int nSize)

8-bit unsigned signal allocator.

Parameters:

nSize Number of unsigned chars in the new signal.

Returns:

A pointer to the new signal. 0 (NULL-pointer) indicates that an error occurred during allocation.

7.5.1.215 NppStatus nppsMax_16s (const Npp16s * pSrc, int nLength, Npp16s * pMax, Npp8u * pDeviceBuffer)

16-bit integer vector max method

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pMax Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.216 NppStatus nppsMax_32f (const Npp32f * pSrc, int nLength, Npp32f * pMax, Npp8u * pDeviceBuffer)

32-bit float vector max method

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pMax Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.217 NppStatus nppsMax_32s (const Npp32s * *pSrc*, int *nLength*, Npp32s * *pMax*, Npp8u * *pDeviceBuffer*)

32-bit integer vector max method

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pMax Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.218 NppStatus nppsMax_64f (const Npp64f * *pSrc*, int *nLength*, Npp64f * *pMax*, Npp8u * *pDeviceBuffer*)

64-bit float vector max method

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pMax Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.219 NppStatus nppsMin_16s (const Npp16s * *pSrc*, int *nLength*, Npp16s * *pMin*, Npp8u * *pDeviceBuffer*)

16-bit integer vector min method

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pMin Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.220 **NppStatus nppsMin_32f** (const Npp32f * *pSrc*, int *nLength*, Npp32f * *pMin*, Npp8u * *pDeviceBuffer*)

32-bit integer vector min method

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pMin Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.221 **NppStatus nppsMin_32s** (const Npp32s * *pSrc*, int *nLength*, Npp32s * *pMin*, Npp8u * *pDeviceBuffer*)

32-bit integer vector min method

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pMin Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.222 **NppStatus nppsMin_64f** (const Npp64f * *pSrc*, int *nLength*, Npp64f * *pMin*, Npp8u * *pDeviceBuffer*)

64-bit integer vector min method

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pMin Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.223 NppStatus nppsMinMax_16s (const Npp16s * *pSrc*, int *nLength*, Npp16s * *pMin*, Npp16s * *pMax*, Npp8u * *pDeviceBuffer*)

16-bit signed short vector min and max method

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pMin Pointer to the min output result.

pMax Pointer to the max output result.

pDeviceBuffer Pointer to the required device memory allocation.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.224 NppStatus nppsMinMax_16u (const Npp16u * *pSrc*, int *nLength*, Npp16u * *pMin*, Npp16u * *pMax*, Npp8u * *pDeviceBuffer*)

16-bit unsigned short vector min and max method

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pMin Pointer to the min output result.

pMax Pointer to the max output result.

pDeviceBuffer Pointer to the required device memory allocation.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.225 NppStatus nppsMinMax_32f (const Npp32f * *pSrc*, int *nLength*, Npp32f * *pMin*, Npp32f * *pMax*, Npp8u * *pDeviceBuffer*)

32-bit float vector min and max method

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pMin Pointer to the min output result.

pMax Pointer to the max output result.

pDeviceBuffer Pointer to the required device memory allocation.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.226 `NppStatus nppsMinMax_32s (const Npp32s * pSrc, int nLength, Npp32s * pMin, Npp32s * pMax, Npp8u * pDeviceBuffer)`

32-bit signed int vector min and max method

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pMin Pointer to the min output result.

pMax Pointer to the max output result.

pDeviceBuffer Pointer to the required device memory allocation.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.227 `NppStatus nppsMinMax_32u (const Npp32u * pSrc, int nLength, Npp32u * pMin, Npp32u * pMax, Npp8u * pDeviceBuffer)`

32-bit unsigned int vector min and max method

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pMin Pointer to the min output result.

pMax Pointer to the max output result.

pDeviceBuffer Pointer to the required device memory allocation.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.228 `NppStatus nppsMinMax_64f (const Npp64f * pSrc, int nLength, Npp64f * pMin, Npp64f * pMax, Npp8u * pDeviceBuffer)`

64-bit double vector min and max method

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pMin Pointer to the min output result.

pMax Pointer to the max output result.

pDeviceBuffer Pointer to the required device memory allocation.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.229 NppStatus nppsMinMax_8u (const Npp8u * pSrc, int nLength, Npp8u * pMin, Npp8u * pMax, Npp8u * pDeviceBuffer)

8-bit char vector min and max method

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pMin Pointer to the min output result.

pMax Pointer to the max output result.

pDeviceBuffer Pointer to the required device memory allocation.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.230 NppStatus nppsMinMaxGetBufferSize_16s (int nLength, int * hpBufferSize)

Device-buffer size (in bytes) for nppsMinMax_16s.

Parameters:

nLength Signal Length.

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*.

Returns:

NPP_SUCCESS

7.5.1.231 NppStatus nppsMinMaxGetBufferSize_16u (int nLength, int * hpBufferSize)

Device-buffer size (in bytes) for nppsMinMax_16u.

Parameters:

nLength Signal Length.

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*.

Returns:

NPP_SUCCESS

7.5.1.232 NppStatus nppsMinMaxGetBufferSize_32f (int nLength, int * hpBufferSize)

Device-buffer size (in bytes) for nppsMinMax_32f.

Parameters:

nLength Signal Length.

hpBufferSize Required buffer size. Important: hpBufferSize is a *host pointer*.

Returns:

NPP_SUCCESS

7.5.1.233 NppStatus nppsMinMaxGetBufferSize_32s (int *nLength*, int * *hpBufferSize*)

Device-buffer size (in bytes) for nppsMinMax_32s.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.5.1.234 NppStatus nppsMinMaxGetBufferSize_32u (int *nLength*, int * *hpBufferSize*)

Device-buffer size (in bytes) for nppsMinMax_32u.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.5.1.235 NppStatus nppsMinMaxGetBufferSize_64f (int *nLength*, int * *hpBufferSize*)

Device-buffer size (in bytes) for nppsMinMax_64f.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.5.1.236 NppStatus nppsMinMaxGetBufferSize_8u (int *nLength*, int * *hpBufferSize*)

Device-buffer size (in bytes) for nppsMinMax_8u.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.5.1.237 NppStatus nppsMul_16s (const Npp16s * *pSrc1*, const Npp16s * *pSrc2*, Npp16s * *pDst*, int *nLength*)

16-bit signed short signal times signal, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal2 elements to be multiplied by signal1 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.238 NppStatus nppsMul_16s32f (const Npp16s * *pSrc1*, const Npp16s * *pSrc2*, Npp32f * *pDst*, int *nLength*)

16-bit signed short signal times signal with 32-bit floating point result, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal2 elements to be multiplied by signal1 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.239 NppStatus nppsMul_16s32s_Sfs (const Npp16s * *pSrc1*, const Npp16s * *pSrc2*, Npp32s * *pDst*, int *nLength*, int *nScaleFactor*)

16-bit signed short signal times signal, scale, then clamp to 32-bit signed saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal2 elements to be multiplied by signal1 elements.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.240 NppStatus nppsMul_16s_I (const Npp16s * *pSrc*, Npp16s * *pSrcDst*, int *nLength*)

16-bit signed short in place signal times signal, then clamp to saturated value.

Parameters:

pSrc [Source Signal Pointer](#).

pSrcDst [In-Place Signal Pointer](#). signal2 elements to be multiplied by signal1 elements

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.241 NppStatus nppsMul_16s_ISfs (const Npp16s * *pSrc*, Npp16s * *pSrcDst*, int *nLength*, int *nScaleFactor*)

16-bit signed short in place signal times signal, with scaling, then clamp to saturated value.

Parameters:

pSrc [Source Signal Pointer](#).

pSrcDst [In-Place Signal Pointer](#). signal2 elements to be multiplied by signal1 elements

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.242 NppStatus nppsMul_16s_Sfs (const Npp16s * *pSrc1*, const Npp16s * *pSrc2*, Npp16s * *pDst*, int *nLength*, int *nScaleFactor*)

16-bit signed short signal times signal, scale, then clamp to saturated value.

Parameters:

pSrc1 [Source Signal Pointer](#).

pSrc2 [Source Signal Pointer](#), signal2 elements to be multiplied by signal1 elements.

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.243 **NppStatus nppsMul_16sc_ISfs** (const Npp16sc * *pSrc*, Npp16sc * *pSrcDst*, int *nLength*, int *nScaleFactor*)

16-bit complex signed short in place signal times signal, with scaling, then clamp to saturated value.

Parameters:

pSrc [Source Signal Pointer](#).

pSrcDst [In-Place Signal Pointer](#). signal2 elements to be multiplied by signal1 elements

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.244 **NppStatus nppsMul_16sc_Sfs** (const Npp16sc * *pSrc1*, const Npp16sc * *pSrc2*, Npp16sc * *pDst*, int *nLength*, int *nScaleFactor*)

16-bit signed complex short signal times signal, scale, then clamp to saturated value.

Parameters:

pSrc1 [Source Signal Pointer](#).

pSrc2 [Source Signal Pointer](#), signal2 elements to be multiplied by signal1 elements.

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.245 **NppStatus nppsMul_16u16s_Sfs** (const Npp16u * *pSrc1*, const Npp16s * *pSrc2*, Npp16s * *pDst*, int *nLength*, int *nScaleFactor*)

16-bit unsigned short signal times 16-bit signed short signal, scale, then clamp to 16-bit signed saturated value.

Parameters:

pSrc1 [Source Signal Pointer](#).

pSrc2 [Source Signal Pointer](#), signal2 elements to be multiplied by signal1 elements.

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.246 **NppStatus nppsMul_16u_ISfs** (const Npp16u * *pSrc*, Npp16u * *pSrcDst*, int *nLength*, int *nScaleFactor*)

16-bit unsigned short in place signal times signal, with scaling, then clamp to saturated value.

Parameters:

pSrc [Source Signal Pointer](#).

pSrcDst [In-Place Signal Pointer](#). signal2 elements to be multiplied by signal1 elements

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.247 **NppStatus nppsMul_16u_Sfs** (const Npp16u * *pSrc1*, const Npp16u * *pSrc2*, Npp16u * *pDst*, int *nLength*, int *nScaleFactor*)

16-bit unsigned short signal time signal, scale, then clamp to saturated value.

Parameters:

pSrc1 [Source Signal Pointer](#).

pSrc2 [Source Signal Pointer](#). signal2 elements to be multiplied by signal1 elements.

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.248 **NppStatus nppsMul_32f** (const Npp32f * *pSrc1*, const Npp32f * *pSrc2*, Npp32f * *pDst*, int *nLength*)

32-bit floating point signal times signal, then clamp to saturated value.

Parameters:

pSrc1 [Source Signal Pointer](#).

pSrc2 [Source Signal Pointer](#). signal2 elements to be multiplied by signal1 elements

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.249 **NppStatus nppsMul_32f32fc** (const Npp32f * *pSrc1*, const Npp32fc * *pSrc2*, Npp32fc * *pDst*, int *nLength*)

32-bit floating point signal times 32-bit complex floating point signal with complex 32-bit floating point result, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal2 elements to be multiplied by signal1 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.250 **NppStatus nppsMul_32f32fc_I** (const Npp32f * *pSrc*, Npp32fc * *pSrcDst*, int *nLength*)

32-bit complex floating point in place signal times 32-bit floating point signal, then clamp to 32-bit complex floating point saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal2 elements to be multiplied by signal1 elements

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.251 **NppStatus nppsMul_32f_I** (const Npp32f * *pSrc*, Npp32f * *pSrcDst*, int *nLength*)

32-bit floating point in place signal times signal, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal2 elements to be multiplied by signal1 elements

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.252 **NppStatus nppsMul_32fc** (const Npp32fc * *pSrc1*, const Npp32fc * *pSrc2*, Npp32fc * *pDst*, int *nLength*)

32-bit complex floating point signal times signal, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal2 elements to be multiplied by signal1 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.253 **NppStatus nppsMul_32fc_I** (const Npp32fc * *pSrc*, Npp32fc * *pSrcDst*, int *nLength*)

32-bit complex floating point in place signal times signal, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal2 elements to be multiplied by signal1 elements

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.254 **NppStatus nppsMul_32s32sc_ISfs** (const Npp32s * *pSrc*, Npp32sc * *pSrcDst*, int *nLength*, int *nScaleFactor*)

32-bit complex signed integer in place signal times 32-bit signed integer signal, with scaling, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal2 elements to be multiplied by signal1 elements

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.255 **NppStatus nppsMul_32s32sc_Sfs** (const Npp32s * *pSrc1*, const Npp32sc * *pSrc2*, Npp32sc * *pDst*, int *nLength*, int *nScaleFactor*)

32-bit signed integer signal times 32-bit complex signed integer signal, scale, then clamp to 32-bit complex integer saturated value.

Parameters:

pSrc1 [Source Signal Pointer](#).

pSrc2 [Source Signal Pointer](#), signal2 elements to be multiplied by signal1 elements.

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.256 **NppStatus nppsMul_32s_ISfs** (const Npp32s * *pSrc*, Npp32s * *pSrcDst*, int *nLength*, int *nScaleFactor*)

32-bit signed integer in place signal times signal, with scaling, then clamp to saturated value.

Parameters:

pSrc [Source Signal Pointer](#).

pSrcDst [In-Place Signal Pointer](#). signal2 elements to be multiplied by signal1 elements

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.257 **NppStatus nppsMul_32s_Sfs** (const Npp32s * *pSrc1*, const Npp32s * *pSrc2*, Npp32s * *pDst*, int *nLength*, int *nScaleFactor*)

32-bit signed integer signal times signal, scale, then clamp to saturated value.

Parameters:

pSrc1 [Source Signal Pointer](#).

pSrc2 [Source Signal Pointer](#), signal2 elements to be multiplied by signal1 elements.

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.258 NppStatus nppsMul_32sc_ISfs (const Npp32sc * *pSrc*, Npp32sc * *pSrcDst*, int *nLength*, int *nScaleFactor*)

32-bit complex signed integer in place signal times signal, with scaling, then clamp to saturated value.

Parameters:

pSrc [Source Signal Pointer](#).

pSrcDst [In-Place Signal Pointer](#). signal2 elements to be multiplied by signal1 elements

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.259 NppStatus nppsMul_32sc_Sfs (const Npp32sc * *pSrc1*, const Npp32sc * *pSrc2*, Npp32sc * *pDst*, int *nLength*, int *nScaleFactor*)

32-bit signed complex integer signal times signal, scale, then clamp to saturated value.

Parameters:

pSrc1 [Source Signal Pointer](#).

pSrc2 [Source Signal Pointer](#). signal2 elements to be multiplied by signal1 elements.

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.260 NppStatus nppsMul_64f (const Npp64f * *pSrc1*, const Npp64f * *pSrc2*, Npp64f * *pDst*, int *nLength*)

64-bit floating point signal times signal, then clamp to saturated value.

Parameters:

pSrc1 [Source Signal Pointer](#).

pSrc2 [Source Signal Pointer](#). signal2 elements to be multiplied by signal1 elements

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.261 NppStatus nppsMul_64f_I (const Npp64f * *pSrc*, Npp64f * *pSrcDst*, int *nLength*)

64-bit floating point in place signal times signal, then clamp to saturated value.

Parameters:

pSrc [Source Signal Pointer](#).

pSrcDst [In-Place Signal Pointer](#). signal2 elements to be multiplied by signal1 elements

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.262 NppStatus nppsMul_64fc (const Npp64fc * *pSrc1*, const Npp64fc * *pSrc2*, Npp64fc * *pDst*, int *nLength*)

64-bit complex floating point signal times signal, then clamp to saturated value.

Parameters:

pSrc1 [Source Signal Pointer](#).

pSrc2 [Source Signal Pointer](#). signal2 elements to be multiplied by signal1 elements

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.263 NppStatus nppsMul_64fc_I (const Npp64fc * *pSrc*, Npp64fc * *pSrcDst*, int *nLength*)

64-bit complex floating point in place signal times signal, then clamp to saturated value.

Parameters:

pSrc [Source Signal Pointer](#).

pSrcDst [In-Place Signal Pointer](#). signal2 elements to be multiplied by signal1 elements

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.264 NppStatus nppsMul_8u16u (const Npp8u * *pSrc1*, const Npp8u * *pSrc2*, Npp16u * *pDst*, int *nLength*)

8-bit unsigned char signal times signal with 16-bit unsigned result, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.
pSrc2 Source Signal Pointer. signal2 elements to be multiplied by signal1 elements
pDst Destination Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.265 `NppStatus nppsMul_8u_ISfs (const Npp8u * pSrc, Npp8u * pSrcDst, int nLength, int nScaleFactor)`

8-bit unsigned char in place signal times signal, with scaling, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.
pSrcDst In-Place Signal Pointer. signal2 elements to be multiplied by signal1 elements
nLength Signal Length.
nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.266 `NppStatus nppsMul_8u_Sfs (const Npp8u * pSrc1, const Npp8u * pSrc2, Npp8u * pDst, int nLength, int nScaleFactor)`

8-bit unsigned char signal times signal, scale, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.
pSrc2 Source Signal Pointer, signal2 elements to be multiplied by signal1 elements.
pDst Destination Signal Pointer.
nLength Signal Length.
nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.267 NppStatus nppsMul_Low_32s_Sfs (const Npp32s * *pSrc1*, const Npp32s * *pSrc2*, Npp32s * *pDst*, int *nLength*, int *nScaleFactor*)

32-bit signed integer signal times signal, scale, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal2 elements to be multiplied by signal1 elements.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.268 NppStatus nppsMulC_16s_ISfs (Npp16s *nValue*, Npp16s * *pSrcDst*, int *nLength*, int *nScaleFactor*)

16-bit signed short in place signal times constant, scale, then clamp to saturated value.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be multiplied by each vector element

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.269 NppStatus nppsMulC_16s_Sfs (const Npp16s * *pSrc*, Npp16s *nValue*, Npp16s * *pDst*, int *nLength*, int *nScaleFactor*)

16-bit signed short signal times constant, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be multiplied by each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.270 NppStatus nppsMulC_16sc_ISfs (Npp16sc *nValue*, Npp16sc * *pSrcDst*, int *nLength*, int *nScaleFactor*)

16-bit integer complex number (16 bit real, 16 bit imaginary) signal times constant, scale, then clamp to saturated value.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value to be multiplied by each vector element

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.271 NppStatus nppsMulC_16sc_Sfs (const Npp16sc * *pSrc*, Npp16sc *nValue*, Npp16sc * *pDst*, int *nLength*, int *nScaleFactor*)

16-bit integer complex number (16 bit real, 16 bit imaginary) signal times constant, scale, then clamp to saturated value.

Parameters:

pSrc [Source Signal Pointer](#).

nValue Constant value to be multiplied by each vector element

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.272 NppStatus nppsMulC_16u_ISfs (Npp16u *nValue*, Npp16u * *pSrcDst*, int *nLength*, int *nScaleFactor*)

16-bit unsigned short in place signal times constant, scale, then clamp to saturated value.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value to be multiplied by each vector element

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.273 NppStatus nppsMulC_16u_Sfs (const Npp16u * *pSrc*, Npp16u *nValue*, Npp16u * *pDst*, int *nLength*, int *nScaleFactor*)

16-bit unsigned short signal times constant, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be multiplied by each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.274 NppStatus nppsMulC_32f (const Npp32f * *pSrc*, Npp32f *nValue*, Npp32f * *pDst*, int *nLength*)

32-bit floating point signal times constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be multiplied by each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.275 NppStatus nppsMulC_32f16s_Sfs (const Npp32f * *pSrc*, Npp32f *nValue*, Npp16s * *pDst*, int *nLength*, int *nScaleFactor*)

32-bit floating point signal times constant with output converted to 16-bit signed integer with scaling and saturation of output result.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be multiplied by each vector element

pDst Destination Signal Pointer.

nScaleFactor Integer Result Scaling.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.276 NppStatus nppsMulC_32f_I (Npp32f *nValue*, Npp32f * *pSrcDst*, int *nLength*)

32-bit floating point in place signal times constant.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value to be multiplied by each vector element

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.277 NppStatus nppsMulC_32fc (const Npp32fc * *pSrc*, Npp32fc *nValue*, Npp32fc * *pDst*, int *nLength*)

32-bit floating point complex number (32 bit real, 32 bit imaginary) signal times constant.

Parameters:

pSrc [Source Signal Pointer](#).

nValue Constant value to be multiplied by each vector element

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.278 NppStatus nppsMulC_32fc_I (Npp32fc *nValue*, Npp32fc * *pSrcDst*, int *nLength*)

32-bit floating point complex number (32 bit real, 32 bit imaginary) in place signal times constant.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value to be multiplied by each vector element

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.279 NppStatus nppsMulC_32s_ISfs (Npp32s *nValue*, Npp32s * *pSrcDst*, int *nLength*, int *nScaleFactor*)

32-bit signed integer in place signal times constant and scale.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be multiplied by each vector element

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.280 `NppStatus nppsMulC_32s_Sfs (const Npp32s * pSrc, Npp32s nValue, Npp32s * pDst, int nLength, int nScaleFactor)`

32-bit signed integer signal times constant and scale.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be multiplied by each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.281 `NppStatus nppsMulC_32sc_ISfs (Npp32sc nValue, Npp32sc * pSrcDst, int nLength, int nScaleFactor)`

32-bit integer complex number (32 bit real, 32 bit imaginary) in place signal times constant and scale.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be multiplied by each vector element

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.282 `NppStatus nppsMulC_32sc_Sfs (const Npp32sc * pSrc, Npp32sc nValue, Npp32sc * pDst, int nLength, int nScaleFactor)`

32-bit integer complex number (32 bit real, 32 bit imaginary) signal times constant and scale.

Parameters:

pSrc [Source Signal Pointer](#).

nValue Constant value to be multiplied by each vector element

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.283 `NppStatus nppsMulC_64f (const Npp64f * pSrc, Npp64f nValue, Npp64f * pDst, int nLength)`

64-bit floating point signal times constant.

Parameters:

pSrc [Source Signal Pointer](#).

nValue Constant value to be multiplied by each vector element

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.284 `NppStatus nppsMulC_64f64s_ISfs (Npp64f nValue, Npp64s * pDst, int nLength, int nScaleFactor)`

64-bit floating point signal times constant with in place conversion to 64-bit signed integer and with scaling and saturation of output result.

Parameters:

nValue Constant value to be multiplied by each vector element

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.285 NppStatus nppsMulC_64f_I (Npp64f *nValue*, Npp64f * *pSrcDst*, int *nLength*)

64-bit floating point, in place signal times constant.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value to be multiplied by each vector element

nLength Length of the vectors, number of items.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.286 NppStatus nppsMulC_64fc (const Npp64fc * *pSrc*, Npp64fc *nValue*, Npp64fc * *pDst*, int *nLength*)

64-bit floating point complex number (64 bit real, 64 bit imaginary) signal times constant.

Parameters:

pSrc [Source Signal Pointer](#).

nValue Constant value to be multiplied by each vector element

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.287 NppStatus nppsMulC_64fc_I (Npp64fc *nValue*, Npp64fc * *pSrcDst*, int *nLength*)

64-bit floating point complex number (64 bit real, 64 bit imaginary) in place signal times constant.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value to be multiplied by each vector element

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.288 NppStatus nppsMulC_8u_ISfs (Npp8u *nValue*, Npp8u * *pSrcDst*, int *nLength*, int *nScaleFactor*)

8-bit unsigned char in place signal times constant, scale, then clamp to saturated value

Parameters:

pSrcDst In-Place Signal Pointer.
nValue Constant value to be multiplied by each vector element
nLength Signal Length.
nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.289 `NppStatus nppsMulC_8u_Sfs (const Npp8u *pSrc, Npp8u nValue, Npp8u *pDst, int nLength, int nScaleFactor)`

8-bit unsigned char signal times constant, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.
nValue Constant value to be multiplied by each vector element
pDst Destination Signal Pointer.
nLength Signal Length.
nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.290 `NppStatus nppsMulC_Low_32f16s (const Npp32f *pSrc, Npp32f nValue, Npp16s *pDst, int nLength)`

32-bit floating point signal times constant with output converted to 16-bit signed integer.

Parameters:

pSrc Source Signal Pointer.
nValue Constant value to be multiplied by each vector element
pDst Destination Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.291 NppStatus nppsNormalize_16s_Sfs (const Npp16s * *pSrc*, Npp16s * *pDst*, int *nLength*, Npp16s *vSub*, int *vDiv*, int *nScaleFactor*)

16-bit signed short signal normalize, scale, then clamp to saturated value.

Parameters:

pSrc [Source Signal Pointer](#).

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

vSub value subtracted from each signal element before division

vDiv divisor of post-subtracted signal element dividend

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.292 NppStatus nppsNormalize_16sc_Sfs (const Npp16sc * *pSrc*, Npp16sc * *pDst*, int *nLength*, Npp16sc *vSub*, int *vDiv*, int *nScaleFactor*)

16-bit complex signed short signal normalize, scale, then clamp to saturated value.

Parameters:

pSrc [Source Signal Pointer](#).

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

vSub value subtracted from each signal element before division

vDiv divisor of post-subtracted signal element dividend

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.293 NppStatus nppsNormalize_32f (const Npp32f * *pSrc*, Npp32f * *pDst*, int *nLength*, Npp32f *vSub*, Npp32f *vDiv*)

32-bit floating point signal normalize.

Parameters:

pSrc [Source Signal Pointer](#).

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

vSub value subtracted from each signal element before division

vDiv divisor of post-subtracted signal element dividend

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.294 `NppStatus nppsNormalize_32fc (const Npp32fc * pSrc, Npp32fc * pDst, int nLength, Npp32fc vSub, Npp32f vDiv)`

32-bit complex floating point signal normalize.

Parameters:

pSrc [Source Signal Pointer](#).

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

vSub value subtracted from each signal element before division

vDiv divisor of post-subtracted signal element dividend

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.295 `NppStatus nppsNormalize_64f (const Npp64f * pSrc, Npp64f * pDst, int nLength, Npp64f vSub, Npp64f vDiv)`

64-bit floating point signal normalize.

Parameters:

pSrc [Source Signal Pointer](#).

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

vSub value subtracted from each signal element before division

vDiv divisor of post-subtracted signal element dividend

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.296 `NppStatus nppsNormalize_64fc (const Npp64fc * pSrc, Npp64fc * pDst, int nLength, Npp64fc vSub, Npp64f vDiv)`

64-bit complex floating point signal normalize.

Parameters:

pSrc [Source Signal Pointer](#).

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

vSub value subtracted from each signal element before division

vDiv divisor of post-subtracted signal element dividend

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.297 NppStatus nppsNot_16u (const Npp16u * *pSrc*, Npp16u * *pDst*, int *nLength*)

16-bit unsigned short not signal.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.298 NppStatus nppsNot_16u_I (Npp16u * *pSrcDst*, int *nLength*)

16-bit unsigned short in place not signal.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.299 NppStatus nppsNot_32u (const Npp32u * *pSrc*, Npp32u * *pDst*, int *nLength*)

32-bit unsigned integer not signal.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.300 NppStatus nppsNot_32u_I (Npp32u * *pSrcDst*, int *nLength*)

32-bit unsigned signed integer in place not signal.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.301 NppStatus nppsNot_8u (const Npp8u * *pSrc*, Npp8u * *pDst*, int *nLength*)

8-bit unsigned char not signal.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.302 NppStatus nppsNot_8u_I (Npp8u * *pSrcDst*, int *nLength*)

8-bit unsigned char in place not signal.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.303 NppStatus nppsOr_16u (const Npp16u * *pSrc1*, const Npp16u * *pSrc2*, Npp16u * *pDst*, int *nLength*)

16-bit unsigned short signal or with signal.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal2 elements to be ored with signal1 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.304 NppStatus nppsOr_16u_I (const Npp16u * *pSrc*, Npp16u * *pSrcDst*, int *nLength*)

16-bit unsigned short in place signal or with signal.

Parameters:

pSrc Source Signal Pointer.

pSrcDst [In-Place Signal Pointer](#). signal2 elements to be ored with signal1 elements
nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.305 `NppStatus nppsOr_32u (const Npp32u *pSrc1, const Npp32u *pSrc2, Npp32u *pDst, int nLength)`

32-bit unsigned integer signal or with signal.

Parameters:

pSrc1 [Source Signal Pointer](#).
pSrc2 [Source Signal Pointer](#). signal2 elements to be ored with signal1 elements
pDst [Destination Signal Pointer](#).
nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.306 `NppStatus nppsOr_32u_I (const Npp32u *pSrc, Npp32u *pSrcDst, int nLength)`

32-bit unsigned integer in place signal or with signal.

Parameters:

pSrc [Source Signal Pointer](#).
pSrcDst [In-Place Signal Pointer](#). signal2 elements to be ored with signal1 elements
nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.307 `NppStatus nppsOr_8u (const Npp8u *pSrc1, const Npp8u *pSrc2, Npp8u *pDst, int nLength)`

8-bit unsigned char signal or with signal.

Parameters:

pSrc1 [Source Signal Pointer](#).
pSrc2 [Source Signal Pointer](#). signal2 elements to be ored with signal1 elements
pDst [Destination Signal Pointer](#).
nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.308 NppStatus nppsOr_8u_I (const Npp8u * *pSrc*, Npp8u * *pSrcDst*, int *nLength*)

8-bit unsigned char in place signal or with signal.

Parameters:

pSrc [Source Signal Pointer](#).

pSrcDst [In-Place Signal Pointer](#). signal2 elements to be ored with signal1 elements

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.309 NppStatus nppsOrC_16u (const Npp16u * *pSrc*, Npp16u *nValue*, Npp16u * *pDst*, int *nLength*)

16-bit unsigned short signal or with constant.

Parameters:

pSrc [Source Signal Pointer](#).

nValue Constant value to be ored with each vector element

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.310 NppStatus nppsOrC_16u_I (Npp16u *nValue*, Npp16u * *pSrcDst*, int *nLength*)

16-bit unsigned short in place signal or with constant.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value to be ored with each vector element

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.311 NppStatus nppsOrC_32u (const Npp32u * *pSrc*, Npp32u *nValue*, Npp32u * *pDst*, int *nLength*)

32-bit unsigned integer signal or with constant.

Parameters:

pSrc Source Signal Pointer.
nValue Constant value to be ored with each vector element
pDst Destination Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.312 NppStatus nppsOrC_32u_I (Npp32u nValue, Npp32u * pSrcDst, int nLength)

32-bit unsigned signed integer in place signal or with constant.

Parameters:

pSrcDst In-Place Signal Pointer.
nValue Constant value to be ored with each vector element
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.313 NppStatus nppsOrC_8u (const Npp8u * pSrc, Npp8u nValue, Npp8u * pDst, int nLength)

8-bit unsigned char signal or with constant.

Parameters:

pSrc Source Signal Pointer.
nValue Constant value to be ored with each vector element
pDst Destination Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.314 NppStatus nppsOrC_8u_I (Npp8u nValue, Npp8u * pSrcDst, int nLength)

8-bit unsigned char in place signal or with constant.

Parameters:

pSrcDst In-Place Signal Pointer.
nValue Constant value to be ored with each vector element
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.315 NppStatus nppsReductionGetBufferSize_16s (int *nLength*, int * *hpBufferSize*)

Device-buffer size (in bytes) for 16s reductions.

This primitive provides the correct buffer size for nppsSum_16s, nppsMin_16s, nppsMax_16s.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.5.1.316 NppStatus nppsReductionGetBufferSize_16s_Sfs (int *nLength*, int * *hpBufferSize*)

Device-buffer size (in bytes) for 16s reductions with integer-results scaling.

This primitive provides the correct buffer size for nppsSum_16s_Sfs.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.5.1.317 NppStatus nppsReductionGetBufferSize_16sc (int *nLength*, int * *hpBufferSize*)

Device-buffer size (in bytes) for 16sc reductions.

This primitive provides the correct buffer size for nppsSum_16sc, nppsMin_16sc, nppsMax_16sc.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.5.1.318 NppStatus nppsReductionGetBufferSize_16sc_Sfs (int *nLength*, int * *hpBufferSize*)

Device-buffer size (in bytes) for 16sc reductions with integer-results scaling.

This primitive provides the correct buffer size for nppsSum_16sc_Sfs.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.5.1.319 NppStatus nppsReductionGetBufferSize_16u (int *nLength*, int * *hpBufferSize*)
[inline]

Device-buffer size (in bytes) for 16u reductions.

This primitive provides the correct buffer size for *nppsSum_16u*, *nppsMin_16u*, *nppsMax_16u*.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.5.1.320 NppStatus nppsReductionGetBufferSize_32f (int *nLength*, int * *hpBufferSize*)

Device-buffer size (in bytes) for 32f reductions.

This primitive provides the correct buffer size for *nppsSum_32f*, *nppsMin_32f*, *nppsMax_32f*.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.5.1.321 NppStatus nppsReductionGetBufferSize_32fc (int *nLength*, int * *hpBufferSize*)

Device-buffer size (in bytes) for 32fc reductions.

This primitive provides the correct buffer size for *nppsSum_32fc*, *nppsMin_32fc*, *nppsMax_32fc*.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.5.1.322 NppStatus nppsReductionGetBufferSize_32s (int *nLength*, int * *hpBufferSize*)

Device-buffer size (in bytes) for 32s reductions.

This primitive provides the correct buffer size for nppsSum_32sc, nppsMin_32sc, nppsMax_32sc.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.5.1.323 NppStatus nppsReductionGetBufferSize_32s_Sfs (int *nLength*, int * *hpBufferSize*)

Device-buffer size (in bytes) for 32s reductions with integer-results scaling.

This primitive provides the correct buffer size for nppsSum_32s_Sfs.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.5.1.324 NppStatus nppsReductionGetBufferSize_32sc (int *nLength*, int * *hpBufferSize*)

Device-buffer size (in bytes) for 32sc reductions.

This primitive provides the correct buffer size for nppsSum_32sc, nppsMin_32sc, nppsMax_32sc.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

**7.5.1.325 NppStatus nppsReductionGetBufferSize_32u (int *nLength*, int * *hpBufferSize*)
[inline]**

Device-buffer size (in bytes) for 32u reductions.

This primitive provides the correct buffer size for nppsSum_32u, nppsMin_32u, nppsMax_32u.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.5.1.326 NppStatus nppsReductionGetBufferSize_64f (int *nLength*, int * *hpBufferSize*)

Device-buffer size (in bytes) for 64f reductions.

This primitive provides the correct buffer size for *nppsSum_64f*, *nppsMin_64f*, *nppsMax_64f*.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.5.1.327 NppStatus nppsReductionGetBufferSize_64fc (int *nLength*, int * *hpBufferSize*)

Device-buffer size (in bytes) for 64fc reductions.

This primitive provides the correct buffer size for *nppsSum_64fc*, *nppsMin_64fc*, *nppsMax_64fc*.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.5.1.328 NppStatus nppsReductionGetBufferSize_64s (int *nLength*, int * *hpBufferSize*)

Device-buffer size (in bytes) for 64s reductions.

This primitive provides the correct buffer size for *nppsSum_64s*, *nppsMin_64s*, *nppsMax_64s*.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.5.1.329 NppStatus nppsReductionGetBufferSize_8u (int *nLength*, int * *hpBufferSize*)

Device-buffer size (in bytes) for 8u reductions.

This primitive provides the correct buffer size for nppsSum_8u, nppsMin_8u, nppsMax_8u.

Parameters:

nLength [Signal Length](#).

hpBufferSize Required buffer size. Important: *hpBufferSize* is a *host pointer*.

Returns:

NPP_SUCCESS

7.5.1.330 NppStatus nppsRShiftC_16s (const Npp16s * *pSrc*, int *nValue*, Npp16s * *pDst*, int *nLength*)

16-bit signed short signal right shift with constant.

Parameters:

pSrc [Source Signal Pointer](#).

nValue Constant value to be used to right shift each vector element

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.331 NppStatus nppsRShiftC_16s_I (int *nValue*, Npp16s * *pSrcDst*, int *nLength*)

16-bit signed short in place signal right shift with constant.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value to be used to right shift each vector element

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.332 NppStatus nppsRShiftC_16u (const Npp16u * *pSrc*, int *nValue*, Npp16u * *pDst*, int *nLength*)

16-bit unsigned short signal right shift with constant.

Parameters:

pSrc Source Signal Pointer.
nValue Constant value to be used to right shift each vector element
pDst Destination Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.333 NppStatus nppsRShiftC_16u_I (int *nValue*, Npp16u * *pSrcDst*, int *nLength*)

16-bit unsigned short in place signal right shift with constant.

Parameters:

pSrcDst In-Place Signal Pointer.
nValue Constant value to be used to right shift each vector element
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.334 NppStatus nppsRShiftC_32s (const Npp32s * *pSrc*, int *nValue*, Npp32s * *pDst*, int *nLength*)

32-bit signed integer signal right shift with constant.

Parameters:

pSrc Source Signal Pointer.
nValue Constant value to be used to right shift each vector element
pDst Destination Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.335 NppStatus nppsRShiftC_32s_I (int *nValue*, Npp32s * *pSrcDst*, int *nLength*)

32-bit signed integer in place signal right shift with constant.

Parameters:

pSrcDst In-Place Signal Pointer.
nValue Constant value to be used to right shift each vector element
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.336 NppStatus nppsRShiftC_32u (const Npp32u * *pSrc*, int *nValue*, Npp32u * *pDst*, int *nLength*)

32-bit unsigned integer signal right shift with constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be used to right shift each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.337 NppStatus nppsRShiftC_32u_I (int *nValue*, Npp32u * *pSrcDst*, int *nLength*)

32-bit unsigned signed integer in place signal right shift with constant.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be used to right shift each vector element

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.338 NppStatus nppsRShiftC_8u (const Npp8u * *pSrc*, int *nValue*, Npp8u * *pDst*, int *nLength*)

8-bit unsigned char signal right shift with constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be used to right shift each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.339 NppStatus nppsRShiftC_8u_I (int *nValue*, Npp8u * *pSrcDst*, int *nLength*)

8-bit unsigned char in place signal right shift with constant.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value to be used to right shift each vector element

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.340 NppStatus nppsSet_16s (Npp16s *nValue*, Npp16s * *pDst*, int *nLength*)

16-bit integer, vector set method.

Parameters:

nValue Value used to initialize the vector *pDst*.

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.341 NppStatus nppsSet_16sc (Npp16sc *nValue*, Npp16sc * *pDst*, int *nLength*)

16-bit integer complex, vector set method.

Parameters:

nValue Value used to initialize the vector *pDst*.

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.342 NppStatus nppsSet_32f (Npp32f *nValue*, Npp32f * *pDst*, int *nLength*)

32-bit float, vector set method.

Parameters:

nValue Value used to initialize the vector *pDst*.

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.343 NppStatus nppsSet_32fc (Npp32fc *nValue*, Npp32fc * *pDst*, int *nLength*)

32-bit float complex, vector set method.

Parameters:

nValue Value used to initialize the vector pDst.

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.344 NppStatus nppsSet_32s (Npp32s *nValue*, Npp32s * *pDst*, int *nLength*)

32-bit integer, vector set method.

Parameters:

nValue Value used to initialize the vector pDst.

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.345 NppStatus nppsSet_32sc (Npp32sc *nValue*, Npp32sc * *pDst*, int *nLength*)

32-bit integer complex, vector set method.

Parameters:

nValue Value used to initialize the vector pDst.

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.346 NppStatus nppsSet_64f (Npp64f *nValue*, Npp64f * *pDst*, int *nLength*)

64-bit double, vector set method.

Parameters:

nValue Value used to initialize the vector pDst.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.347 NppStatus nppsSet_64fc (Npp64fc *nValue*, Npp64fc * *pDst*, int *nLength*)

64-bit double complex, vector set method.

Parameters:

nValue Value used to initialize the vector pDst.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.348 NppStatus nppsSet_64s (Npp64s *nValue*, Npp64s * *pDst*, int *nLength*)

64-bit long long integer, vector set method.

Parameters:

nValue Value used to initialize the vector pDst.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.349 NppStatus nppsSet_64sc (Npp64sc *nValue*, Npp64sc * *pDst*, int *nLength*)

64-bit long long integer complex, vector set method.

Parameters:

nValue Value used to initialize the vector pDst.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.350 NppStatus nppsSet_8u (Npp8u *nValue*, Npp8u * *pDst*, int *nLength*)

8-bit unsigned char, vector set method.

Parameters:

nValue Value used to initialize the vector pDst.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.351 NppStatus nppsSqr_16s_ISfs (Npp16s * *pSrcDst*, int *nLength*, int *nScaleFactor*)

16-bit signed short signal squared, scale, then clamp to saturated value.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.352 NppStatus nppsSqr_16s_Sfs (const Npp16s * *pSrc*, Npp16s * *pDst*, int *nLength*, int *nScaleFactor*)

16-bit signed short signal squared, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.353 NppStatus nppsSqr_16sc_ISfs (Npp16sc * *pSrcDst*, int *nLength*, int *nScaleFactor*)

16-bit complex signed short signal squared, scale, then clamp to saturated value.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.354 NppStatus nppsSqr_16sc_Sfs (const Npp16sc * *pSrc*, Npp16sc * *pDst*, int *nLength*, int *nScaleFactor*)

16-bit complex signed short signal squared, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.355 NppStatus nppsSqr_16u_ISfs (Npp16u * *pSrcDst*, int *nLength*, int *nScaleFactor*)

16-bit unsigned short signal squared, scale, then clamp to saturated value.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.356 NppStatus nppsSqr_16u_Sfs (const Npp16u * *pSrc*, Npp16u * *pDst*, int *nLength*, int *nScaleFactor*)

16-bit unsigned short signal squared, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.
pDst Destination Signal Pointer.
nLength Signal Length.
nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.357 NppStatus nppsSqr_32f (const Npp32f * *pSrc*, Npp32f * *pDst*, int *nLength*)

32-bit floating point signal squared.

Parameters:

pSrc Source Signal Pointer.
pDst Destination Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.358 NppStatus nppsSqr_32f_I (Npp32f * *pSrcDst*, int *nLength*)

32-bit floating point signal squared.

Parameters:

pSrcDst In-Place Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.359 NppStatus nppsSqr_32fc (const Npp32fc * *pSrc*, Npp32fc * *pDst*, int *nLength*)

32-bit complex floating point signal squared.

Parameters:

pSrc Source Signal Pointer.
pDst Destination Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.360 `NppStatus nppsSqr_32fc_I (Npp32fc * pSrcDst, int nLength)`

32-bit complex floating point signal squared.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.361 `NppStatus nppsSqr_64f (const Npp64f * pSrc, Npp64f * pDst, int nLength)`

64-bit floating point signal squared.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.362 `NppStatus nppsSqr_64f_I (Npp64f * pSrcDst, int nLength)`

64-bit floating point signal squared.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.363 `NppStatus nppsSqr_64fc (const Npp64fc * pSrc, Npp64fc * pDst, int nLength)`

64-bit complex floating point signal squared.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.364 NppStatus nppsSqr_64fc_I (Npp64fc * *pSrcDst*, int *nLength*)

64-bit complex floating point signal squared.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.365 NppStatus nppsSqr_8u_ISfs (Npp8u * *pSrcDst*, int *nLength*, int *nScaleFactor*)

8-bit unsigned char signal squared, scale, then clamp to saturated value.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.366 NppStatus nppsSqr_8u_Sfs (const Npp8u * *pSrc*, Npp8u * *pDst*, int *nLength*, int *nScaleFactor*)

8-bit unsigned char signal squared, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.367 NppStatus nppsSqrt_16s_ISfs (Npp16s * *pSrcDst*, int *nLength*, int *nScaleFactor*)

16-bit signed short signal square root, scale, then clamp to saturated value.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.368 NppStatus nppsSqrt_16s_Sfs (const Npp16s * *pSrc*, Npp16s * *pDst*, int *nLength*, int *nScaleFactor*)

16-bit signed short signal square root, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.369 NppStatus nppsSqrt_16sc_ISfs (Npp16sc * *pSrcDst*, int *nLength*, int *nScaleFactor*)

16-bit complex signed short signal square root, scale, then clamp to saturated value.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.370 NppStatus nppsSqrt_16sc_Sfs (const Npp16sc * *pSrc*, Npp16sc * *pDst*, int *nLength*, int *nScaleFactor*)

16-bit complex signed short signal square root, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.371 NppStatus nppsSqrt_16u_ISfs (Npp16u * *pSrcDst*, int *nLength*, int *nScaleFactor*)

16-bit unsigned short signal square root, scale, then clamp to saturated value.

Parameters:

pSrcDst In-Place Signal Pointer.
nLength Signal Length.
nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.372 NppStatus nppsSqrt_16u_Sfs (const Npp16u * *pSrc*, Npp16u * *pDst*, int *nLength*, int *nScaleFactor*)

16-bit unsigned short signal square root, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.
pDst Destination Signal Pointer.
nLength Signal Length.
nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.373 NppStatus nppsSqrt_32f (const Npp32f * *pSrc*, Npp32f * *pDst*, int *nLength*)

32-bit floating point signal square root.

Parameters:

pSrc Source Signal Pointer.
pDst Destination Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.374 NppStatus nppsSqrt_32f_I (Npp32f * *pSrcDst*, int *nLength*)

32-bit floating point signal square root.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.375 NppStatus nppsSqrt_32fc (const Npp32fc * pSrc, Npp32fc * pDst, int nLength)

32-bit complex floating point signal square root.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.376 NppStatus nppsSqrt_32fc_I (Npp32fc * pSrcDst, int nLength)

32-bit complex floating point signal square root.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.377 NppStatus nppsSqrt_32s16s_Sfs (const Npp32s * pSrc, Npp16s * pDst, int nLength, int nScaleFactor)

32-bit signed integer signal square root, scale, then clamp to 16-bit signed integer saturated value.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.378 NppStatus nppsSqrt_64f (const Npp64f * *pSrc*, Npp64f * *pDst*, int *nLength*)

64-bit floating point signal square root.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.379 NppStatus nppsSqrt_64f_I (Npp64f * *pSrcDst*, int *nLength*)

64-bit floating point signal square root.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.380 NppStatus nppsSqrt_64fc (const Npp64fc * *pSrc*, Npp64fc * *pDst*, int *nLength*)

64-bit complex floating point signal square root.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.381 NppStatus nppsSqrt_64fc_I (Npp64fc * *pSrcDst*, int *nLength*)

64-bit complex floating point signal square root.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.382 NppStatus nppsSqrt_64s16s_Sfs (const Npp64s * *pSrc*, Npp16s * *pDst*, int *nLength*, int *nScaleFactor*)

64-bit signed integer signal square root, scale, then clamp to 16-bit signed integer saturated value.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.383 NppStatus nppsSqrt_64s_ISfs (Npp64s * *pSrcDst*, int *nLength*, int *nScaleFactor*)

64-bit signed integer signal square root, scale, then clamp to saturated value.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.384 NppStatus nppsSqrt_64s_Sfs (const Npp64s * *pSrc*, Npp64s * *pDst*, int *nLength*, int *nScaleFactor*)

64-bit signed integer signal square root, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.385 NppStatus nppsSqrt_8u_ISfs (Npp8u * *pSrcDst*, int *nLength*, int *nScaleFactor*)

8-bit unsigned char signal square root, scale, then clamp to saturated value.

Parameters:

pSrcDst In-Place Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.386 NppStatus nppsSqrt_8u_Sfs (const Npp8u * *pSrc*, Npp8u * *pDst*, int *nLength*, int *nScaleFactor*)

8-bit unsigned char signal square root, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.387 NppStatus nppsSub_16s (const Npp16s * *pSrc1*, const Npp16s * *pSrc2*, Npp16s * *pDst*, int *nLength*)

16-bit signed short signal subtract signal, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal1 elements to be subtracted from signal2 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.388 NppStatus nppsSub_16s32f (const Npp16s * *pSrc1*, const Npp16s * *pSrc2*, Npp32f * *pDst*, int *nLength*)

16-bit signed short signal subtract 16-bit signed short signal, then clamp and convert to 32-bit floating point saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal1 elements to be subtracted from signal2 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.389 NppStatus nppsSub_16s_I (const Npp16s * *pSrc*, Npp16s * *pSrcDst*, int *nLength*)

16-bit signed short in place signal subtract signal, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal1 elements to be subtracted from signal2 elements

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.390 NppStatus nppsSub_16s_ISfs (const Npp16s * *pSrc*, Npp16s * *pSrcDst*, int *nLength*, int *nScaleFactor*)

16-bit signed short in place signal subtract signal, with scaling, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal1 elements to be subtracted from signal2 elements

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.391 **NppStatus nppsSub_16s_Sfs** (const Npp16s * *pSrc1*, const Npp16s * *pSrc2*, Npp16s * *pDst*, int *nLength*, int *nScaleFactor*)

16-bit signed short signal subtract signal, scale, then clamp to saturated value.

Parameters:

pSrc1 [Source Signal Pointer](#).
pSrc2 [Source Signal Pointer](#), signal1 elements to be subtracted from signal2 elements.
pDst [Destination Signal Pointer](#).
nLength [Signal Length](#).
nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.392 **NppStatus nppsSub_16sc_ISfs** (const Npp16sc * *pSrc*, Npp16sc * *pSrcDst*, int *nLength*, int *nScaleFactor*)

16-bit complex signed short in place signal subtract signal, with scaling, then clamp to saturated value.

Parameters:

pSrc [Source Signal Pointer](#).
pSrcDst [In-Place Signal Pointer](#). signal1 elements to be subtracted from signal2 elements
nLength [Signal Length](#).
nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.393 **NppStatus nppsSub_16sc_Sfs** (const Npp16sc * *pSrc1*, const Npp16sc * *pSrc2*, Npp16sc * *pDst*, int *nLength*, int *nScaleFactor*)

16-bit signed complex short signal subtract signal, scale, then clamp to saturated value.

Parameters:

pSrc1 [Source Signal Pointer](#).
pSrc2 [Source Signal Pointer](#), signal1 elements to be subtracted from signal2 elements.
pDst [Destination Signal Pointer](#).
nLength [Signal Length](#).
nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.394 NppStatus nppsSub_16u_ISfs (const Npp16u * *pSrc*, Npp16u * *pSrcDst*, int *nLength*, int *nScaleFactor*)

16-bit unsigned short in place signal subtract signal, with scaling, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal1 elements to be subtracted from signal2 elements

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.395 NppStatus nppsSub_16u_Sfs (const Npp16u * *pSrc1*, const Npp16u * *pSrc2*, Npp16u * *pDst*, int *nLength*, int *nScaleFactor*)

16-bit unsigned short signal subtract signal, scale, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal1 elements to be subtracted from signal2 elements.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.396 NppStatus nppsSub_32f (const Npp32f * *pSrc1*, const Npp32f * *pSrc2*, Npp32f * *pDst*, int *nLength*)

32-bit floating point signal subtract signal, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal1 elements to be subtracted from signal2 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.397 NppStatus nppsSub_32f_I (const Npp32f * pSrc, Npp32f * pSrcDst, int nLength)

32-bit floating point in place signal subtract signal, then clamp to saturated value.

Parameters:

pSrc [Source Signal Pointer](#).

pSrcDst [In-Place Signal Pointer](#). signal1 elements to be subtracted from signal2 elements

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.398 NppStatus nppsSub_32fc (const Npp32fc * pSrc1, const Npp32fc * pSrc2, Npp32fc * pDst, int nLength)

32-bit complex floating point signal subtract signal, then clamp to saturated value.

Parameters:

pSrc1 [Source Signal Pointer](#).

pSrc2 [Source Signal Pointer](#). signal1 elements to be subtracted from signal2 elements

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.399 NppStatus nppsSub_32fc_I (const Npp32fc * pSrc, Npp32fc * pSrcDst, int nLength)

32-bit complex floating point in place signal subtract signal, then clamp to saturated value.

Parameters:

pSrc [Source Signal Pointer](#).

pSrcDst [In-Place Signal Pointer](#). signal1 elements to be subtracted from signal2 elements

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.400 NppStatus nppsSub_32s_ISfs (const Npp32s * pSrc, Npp32s * pSrcDst, int nLength, int nScaleFactor)

32-bit signed integer in place signal subtract signal, with scaling, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal1 elements to be subtracted from signal2 elements

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.401 `NppStatus nppsSub_32s_Sfs (const Npp32s * pSrc1, const Npp32s * pSrc2, Npp32s * pDst, int nLength, int nScaleFactor)`

32-bit signed integer signal subtract signal, scale, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal1 elements to be subtracted from signal2 elements.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.402 `NppStatus nppsSub_32sc_ISfs (const Npp32sc * pSrc, Npp32sc * pSrcDst, int nLength, int nScaleFactor)`

32-bit complex signed integer in place signal subtract signal, with scaling, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal1 elements to be subtracted from signal2 elements

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.403 **NppStatus nppsSub_32sc_Sfs** (const Npp32sc * *pSrc1*, const Npp32sc * *pSrc2*, Npp32sc * *pDst*, int *nLength*, int *nScaleFactor*)

32-bit signed complex integer signal subtract signal, scale, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal1 elements to be subtracted from signal2 elements.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.404 **NppStatus nppsSub_64f** (const Npp64f * *pSrc1*, const Npp64f * *pSrc2*, Npp64f * *pDst*, int *nLength*)

64-bit floating point signal subtract signal, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal1 elements to be subtracted from signal2 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.405 **NppStatus nppsSub_64f_I** (const Npp64f * *pSrc*, Npp64f * *pSrcDst*, int *nLength*)

64-bit floating point in place signal subtract signal, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer, signal1 elements to be subtracted from signal2 elements

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.406 NppStatus nppsSub_64fc (const Npp64fc * *pSrc1*, const Npp64fc * *pSrc2*, Npp64fc * *pDst*, int *nLength*)

64-bit complex floating point signal subtract signal, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal1 elements to be subtracted from signal2 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.407 NppStatus nppsSub_64fc_I (const Npp64fc * *pSrc*, Npp64fc * *pSrcDst*, int *nLength*)

64-bit complex floating point in place signal subtract signal, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal1 elements to be subtracted from signal2 elements

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.408 NppStatus nppsSub_8u_ISfs (const Npp8u * *pSrc*, Npp8u * *pSrcDst*, int *nLength*, int *nScaleFactor*)

8-bit unsigned char in place signal subtract signal, with scaling, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

pSrcDst In-Place Signal Pointer. signal1 elements to be subtracted from signal2 elements

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.409 NppStatus nppsSub_8u_Sfs (const Npp8u * *pSrc1*, const Npp8u * *pSrc2*, Npp8u * *pDst*, int *nLength*, int *nScaleFactor*)

8-bit unsigned char signal subtract signal, scale, then clamp to saturated value.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer, signal1 elements to be subtracted from signal2 elements.

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.410 NppStatus nppsSubC_16s_ISfs (Npp16s *nValue*, Npp16s * *pSrcDst*, int *nLength*, int *nScaleFactor*)

16-bit signed short in place signal subtract constant, scale, then clamp to saturated value.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be subtracted from each vector element

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.411 NppStatus nppsSubC_16s_Sfs (const Npp16s * *pSrc*, Npp16s *nValue*, Npp16s * *pDst*, int *nLength*, int *nScaleFactor*)

16-bit signed short signal subtract constant, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be subtracted from each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.412 NppStatus nppsSubC_16sc_ISfs (Npp16sc *nValue*, Npp16sc * *pSrcDst*, int *nLength*, int *nScaleFactor*)

16-bit integer complex number (16 bit real, 16 bit imaginary) signal subtract constant, scale, then clamp to saturated value.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value to be subtracted from each vector element

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.413 NppStatus nppsSubC_16sc_Sfs (const Npp16sc * *pSrc*, Npp16sc *nValue*, Npp16sc * *pDst*, int *nLength*, int *nScaleFactor*)

16-bit integer complex number (16 bit real, 16 bit imaginary) signal subtract constant, scale, then clamp to saturated value.

Parameters:

pSrc [Source Signal Pointer](#).

nValue Constant value to be subtracted from each vector element

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.414 NppStatus nppsSubC_16u_ISfs (Npp16u *nValue*, Npp16u * *pSrcDst*, int *nLength*, int *nScaleFactor*)

16-bit unsigned short in place signal subtract constant, scale, then clamp to saturated value.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value to be subtracted from each vector element

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.415 `NppStatus nppsSubC_16u_Sfs (const Npp16u * pSrc, Npp16u nValue, Npp16u * pDst, int nLength, int nScaleFactor)`

16-bit unsigned short signal subtract constant, scale, then clamp to saturated value.

Parameters:

pSrc [Source Signal Pointer](#).

nValue Constant value to be subtracted from each vector element

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.416 `NppStatus nppsSubC_32f (const Npp32f * pSrc, Npp32f nValue, Npp32f * pDst, int nLength)`

32-bit floating point signal subtract constant.

Parameters:

pSrc [Source Signal Pointer](#).

nValue Constant value to be subtracted from each vector element

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.417 `NppStatus nppsSubC_32f_I (Npp32f nValue, Npp32f * pSrcDst, int nLength)`

32-bit floating point in place signal subtract constant.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value to be subtracted from each vector element

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.418 NppStatus nppsSubC_32fc (const Npp32fc * *pSrc*, Npp32fc *nValue*, Npp32fc * *pDst*, int *nLength*)

32-bit floating point complex number (32 bit real, 32 bit imaginary) signal subtract constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be subtracted from each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.419 NppStatus nppsSubC_32fc_I (Npp32fc *nValue*, Npp32fc * *pSrcDst*, int *nLength*)

32-bit floating point complex number (32 bit real, 32 bit imaginary) in place signal subtract constant.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be subtracted from each vector element

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.420 NppStatus nppsSubC_32s_ISfs (Npp32s *nValue*, Npp32s * *pSrcDst*, int *nLength*, int *nScaleFactor*)

32-bit signed integer in place signal subtract constant and scale.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be subtracted from each vector element

nLength Signal Length.

nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.421 **NppStatus nppsSubC_32s_Sfs** (const Npp32s * *pSrc*, Npp32s *nValue*, Npp32s * *pDst*, int *nLength*, int *nScaleFactor*)

32-bit signed integer signal subtract constant and scale.

Parameters:

pSrc [Source Signal Pointer](#).

nValue Constant value to be subtracted from each vector element

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.422 **NppStatus nppsSubC_32sc_ISfs** (Npp32sc *nValue*, Npp32sc * *pSrcDst*, int *nLength*, int *nScaleFactor*)

32-bit integer complex number (32 bit real, 32 bit imaginary) in place signal subtract constant and scale.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value to be subtracted from each vector element

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.423 **NppStatus nppsSubC_32sc_Sfs** (const Npp32sc * *pSrc*, Npp32sc *nValue*, Npp32sc * *pDst*, int *nLength*, int *nScaleFactor*)

32-bit integer complex number (32 bit real, 32 bit imaginary) signal subtract constant and scale.

Parameters:

pSrc [Source Signal Pointer](#).

nValue Constant value to be subtracted from each vector element

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.424 NppStatus nppsSubC_64f (const Npp64f * *pSrc*, Npp64f *nValue*, Npp64f * *pDst*, int *nLength*)

64-bit floating point signal subtract constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be subtracted from each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.425 NppStatus nppsSubC_64f_I (Npp64f *nValue*, Npp64f * *pSrcDst*, int *nLength*)

64-bit floating point, in place signal subtract constant.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be subtracted from each vector element

nLength Length of the vectors, number of items.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.426 NppStatus nppsSubC_64fc (const Npp64fc * *pSrc*, Npp64fc *nValue*, Npp64fc * *pDst*, int *nLength*)

64-bit floating point complex number (64 bit real, 64 bit imaginary) signal subtract constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be subtracted from each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.427 NppStatus nppsSubC_64fc_I (Npp64fc *nValue*, Npp64fc * *pSrcDst*, int *nLength*)

64-bit floating point complex number (64 bit real, 64 bit imaginary) in place signal subtract constant.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value to be subtracted from each vector element

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.428 NppStatus nppsSubC_8u_ISfs (Npp8u *nValue*, Npp8u * *pSrcDst*, int *nLength*, int *nScaleFactor*)

8-bit unsigned char in place signal subtract constant, scale, then clamp to saturated value

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value to be subtracted from each vector element

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.429 NppStatus nppsSubC_8u_Sfs (const Npp8u * *pSrc*, Npp8u *nValue*, Npp8u * *pDst*, int *nLength*, int *nScaleFactor*)

8-bit unsigned char signal subtract constant, scale, then clamp to saturated value.

Parameters:

pSrc [Source Signal Pointer](#).

nValue Constant value to be subtracted from each vector element

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.430 NppStatus nppsSubCRev_16s_ISfs (Npp16s *nValue*, Npp16s * *pSrcDst*, int *nLength*, int *nScaleFactor*)

16-bit signed short in place signal subtract from constant, scale, then clamp to saturated value.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value each vector element is to be subtracted from

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.431 NppStatus nppsSubCRev_16s_Sfs (const Npp16s * *pSrc*, Npp16s *nValue*, Npp16s * *pDst*, int *nLength*, int *nScaleFactor*)

16-bit signed short signal subtract from constant, scale, then clamp to saturated value.

Parameters:

pSrc [Source Signal Pointer](#).

nValue Constant value each vector element is to be subtracted from

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.432 NppStatus nppsSubCRev_16sc_ISfs (Npp16sc *nValue*, Npp16sc * *pSrcDst*, int *nLength*, int *nScaleFactor*)

16-bit integer complex number (16 bit real, 16 bit imaginary) signal subtract from constant, scale, then clamp to saturated value.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value each vector element is to be subtracted from

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.433 `NppStatus nppsSubCRev_16sc_Sfs (const Npp16sc * pSrc, Npp16sc nValue, Npp16sc * pDst, int nLength, int nScaleFactor)`

16-bit integer complex number (16 bit real, 16 bit imaginary) signal subtract from constant, scale, then clamp to saturated value.

Parameters:

pSrc [Source Signal Pointer](#).

nValue Constant value each vector element is to be subtracted from

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.434 `NppStatus nppsSubCRev_16u_ISfs (Npp16u nValue, Npp16u * pSrcDst, int nLength, int nScaleFactor)`

16-bit unsigned short in place signal subtract from constant, scale, then clamp to saturated value.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value each vector element is to be subtracted from

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.435 `NppStatus nppsSubCRev_16u_Sfs (const Npp16u * pSrc, Npp16u nValue, Npp16u * pDst, int nLength, int nScaleFactor)`

16-bit unsigned short signal subtract from constant, scale, then clamp to saturated value.

Parameters:

pSrc [Source Signal Pointer](#).

nValue Constant value each vector element is to be subtracted from

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.436 NppStatus nppsSubCRev_32f (const Npp32f * *pSrc*, Npp32f *nValue*, Npp32f * *pDst*, int *nLength*)

32-bit floating point signal subtract from constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value each vector element is to be subtracted from

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.437 NppStatus nppsSubCRev_32f_I (Npp32f *nValue*, Npp32f * *pSrcDst*, int *nLength*)

32-bit floating point in place signal subtract from constant.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value each vector element is to be subtracted from

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.438 NppStatus nppsSubCRev_32fc (const Npp32fc * *pSrc*, Npp32fc *nValue*, Npp32fc * *pDst*, int *nLength*)

32-bit floating point complex number (32 bit real, 32 bit imaginary) signal subtract from constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value each vector element is to be subtracted from

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.439 NppStatus nppsSubCRev_32fc_I (Npp32fc *nValue*, Npp32fc * *pSrcDst*, int *nLength*)

32-bit floating point complex number (32 bit real, 32 bit imaginary) in place signal subtract from constant.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value each vector element is to be subtracted from

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.440 NppStatus nppsSubCRev_32s_ISfs (Npp32s *nValue*, Npp32s * *pSrcDst*, int *nLength*, int *nScaleFactor*)

32-bit signed integer in place signal subtract from constant and scale.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value each vector element is to be subtracted from

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.441 NppStatus nppsSubCRev_32s_Sfs (const Npp32s * *pSrc*, Npp32s *nValue*, Npp32s * *pDst*, int *nLength*, int *nScaleFactor*)

32-bit signed integersignal subtract from constant and scale.

Parameters:

pSrc [Source Signal Pointer](#).

nValue Constant value each vector element is to be subtracted from

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.442 NppStatus nppsSubCRev_32sc_ISfs (Npp32sc *nValue*, Npp32sc * *pSrcDst*, int *nLength*, int *nScaleFactor*)

32-bit integer complex number (32 bit real, 32 bit imaginary) in place signal subtract from constant and scale.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value each vector element is to be subtracted from

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.443 NppStatus nppsSubCRev_32sc_Sfs (const Npp32sc * *pSrc*, Npp32sc *nValue*, Npp32sc * *pDst*, int *nLength*, int *nScaleFactor*)

32-bit integer complex number (32 bit real, 32 bit imaginary) signal subtract from constant and scale.

Parameters:

pSrc [Source Signal Pointer](#).

nValue Constant value each vector element is to be subtracted from

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.444 NppStatus nppsSubCRev_64f (const Npp64f * *pSrc*, Npp64f *nValue*, Npp64f * *pDst*, int *nLength*)

64-bit floating point signal subtract from constant.

Parameters:

pSrc [Source Signal Pointer](#).

nValue Constant value each vector element is to be subtracted from

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.445 NppStatus nppsSubCRev_64f_I (Npp64f *nValue*, Npp64f * *pSrcDst*, int *nLength*)

64-bit floating point, in place signal subtract from constant.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value each vector element is to be subtracted from

nLength Length of the vectors, number of items.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.446 NppStatus nppsSubCRev_64fc (const Npp64fc * *pSrc*, Npp64fc *nValue*, Npp64fc * *pDst*, int *nLength*)

64-bit floating point complex number (64 bit real, 64 bit imaginary) signal subtract from constant.

Parameters:

pSrc [Source Signal Pointer](#).

nValue Constant value each vector element is to be subtracted from

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.447 NppStatus nppsSubCRev_64fc_I (Npp64fc *nValue*, Npp64fc * *pSrcDst*, int *nLength*)

64-bit floating point complex number (64 bit real, 64 bit imaginary) in place signal subtract from constant.

Parameters:

pSrcDst [In-Place Signal Pointer](#).

nValue Constant value each vector element is to be subtracted from

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.448 NppStatus nppsSubCRev_8u_ISfs (Npp8u *nValue*, Npp8u * *pSrcDst*, int *nLength*, int *nScaleFactor*)

8-bit unsigned char in place signal subtract from constant, scale, then clamp to saturated value

Parameters:

pSrcDst In-Place Signal Pointer.
nValue Constant value each vector element is to be subtracted from
nLength Signal Length.
nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.449 `NppStatus nppsSubCRev_8u_Sfs (const Npp8u * pSrc, Npp8u nValue, Npp8u * pDst, int nLength, int nScaleFactor)`

8-bit unsigned char signal subtract from constant, scale, then clamp to saturated value.

Parameters:

pSrc Source Signal Pointer.
nValue Constant value each vector element is to be subtracted from
pDst Destination Signal Pointer.
nLength Signal Length.
nScaleFactor Integer Result Scaling.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.450 `NppStatus nppsSum_16s32s_Sfs (const Npp16s * pSrc, int nLength, Npp32s * pSum, int nScaleFactor, Npp8u * pDeviceBuffer)`

16-bit integer vector sum (32bit) with integer scaling method

Parameters:

pSrc Source Signal Pointer.
nLength Signal Length.
pSum Pointer to the output result.
pDeviceBuffer Pointer to the required device memory allocation.
nScaleFactor Integer-result scale factor.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.451 `NppStatus nppsSum_16s_Sfs (const Npp16s * pSrc, int nLength, Npp16s * pSum, int nScaleFactor, Npp8u * pDeviceBuffer)`

16-bit short vector sum with integer scaling method

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pSum Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation.

nScaleFactor Integer-result scale factor.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.452 `NppStatus nppsSum_16sc32sc_Sfs (const Npp16sc * pSrc, int nLength, Npp32sc * pSum, int nScaleFactor, Npp8u * pDeviceBuffer)`

16-bit short complex vector sum (32bit int complex) with integer scaling method

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pSum Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation.

nScaleFactor Integer-result scale factor.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.453 `NppStatus nppsSum_16sc_Sfs (const Npp16sc * pSrc, int nLength, Npp16sc * pSum, int nScaleFactor, Npp8u * pDeviceBuffer)`

16-bit short complex vector sum with integer scaling method

Parameters:

pSrc [Source Signal Pointer](#).

nLength [Signal Length](#).

pSum Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation.

nScaleFactor Integer-result scale factor.

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.454 `NppStatus nppsSum_32f (const Npp32f * pSrc, int nLength, Npp32f * pSum, NppHintAlgorithm eHint, Npp8u * pDeviceBuffer)`

32-bit float vector sum method

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pSum Pointer to the output result.

eHint Suggests using specific code.

pDeviceBuffer Pointer to the required device memory allocation.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.455 `NppStatus nppsSum_32fc (const Npp32fc * pSrc, int nLength, Npp32fc * pSum, NppHintAlgorithm eHint, Npp8u * pDeviceBuffer)`

32-bit float complex vector sum method

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pSum Pointer to the output result.

eHint Suggests using specific code.

pDeviceBuffer Pointer to the required device memory allocation.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.456 `NppStatus nppsSum_32s_Sfs (const Npp32s * pSrc, int nLength, Npp32s * pSum, int nScaleFactor, Npp8u * pDeviceBuffer)`

32-bit integer vector sum with integer scaling method

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pSum Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation.

nScaleFactor Integer-result scale factor.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.457 NppStatus nppsSum_64f (const Npp64f * *pSrc*, int *nLength*, Npp64f * *pSum*, Npp8u * *pDeviceBuffer*)

64-bit double vector sum method

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pSum Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.458 NppStatus nppsSum_64fc (const Npp64fc * *pSrc*, int *nLength*, Npp64fc * *pSum*, Npp8u * *pDeviceBuffer*)

64-bit double complex vector sum method

Parameters:

pSrc Source Signal Pointer.

nLength Signal Length.

pSum Pointer to the output result.

pDeviceBuffer Pointer to the required device memory allocation.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.459 NppStatus nppsXor_16u (const Npp16u * *pSrc1*, const Npp16u * *pSrc2*, Npp16u * *pDst*, int *nLength*)

16-bit unsigned short signal exclusive or with signal.

Parameters:

pSrc1 Source Signal Pointer.

pSrc2 Source Signal Pointer. signal2 elements to be exclusive ored with signal1 elements

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.460 NppStatus nppsXor_16u_I (const Npp16u * *pSrc*, Npp16u * *pSrcDst*, int *nLength*)

16-bit unsigned short in place signal exclusive or with signal.

Parameters:

pSrc [Source Signal Pointer](#).

pSrcDst [In-Place Signal Pointer](#). signal2 elements to be exclusive ored with signal1 elements

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.461 NppStatus nppsXor_32u (const Npp32u * *pSrc1*, const Npp32u * *pSrc2*, Npp32u * *pDst*, int *nLength*)

32-bit unsigned integer signal exclusive or with signal.

Parameters:

pSrc1 [Source Signal Pointer](#).

pSrc2 [Source Signal Pointer](#). signal2 elements to be exclusive ored with signal1 elements

pDst [Destination Signal Pointer](#).

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.462 NppStatus nppsXor_32u_I (const Npp32u * *pSrc*, Npp32u * *pSrcDst*, int *nLength*)

32-bit unsigned integer in place signal exclusive or with signal.

Parameters:

pSrc [Source Signal Pointer](#).

pSrcDst [In-Place Signal Pointer](#). signal2 elements to be exclusive ored with signal1 elements

nLength [Signal Length](#).

Returns:

[Signal Data Related Error Codes](#), [Length Related Error Codes](#).

7.5.1.463 NppStatus nppsXor_8u (const Npp8u * *pSrc1*, const Npp8u * *pSrc2*, Npp8u * *pDst*, int *nLength*)

8-bit unsigned char signal exclusive or with signal.

Parameters:

pSrc1 Source Signal Pointer.
pSrc2 Source Signal Pointer. signal2 elements to be exclusive ored with signal1 elements
pDst Destination Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.464 NppStatus nppsXor_8u_I (const Npp8u * pSrc, Npp8u * pSrcDst, int nLength)

8-bit unsigned char in place signal exclusive or with signal.

Parameters:

pSrc Source Signal Pointer.
pSrcDst In-Place Signal Pointer. signal2 elements to be exclusive ored with signal1 elements
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.465 NppStatus nppsXorC_16u (const Npp16u * pSrc, Npp16u nValue, Npp16u * pDst, int nLength)

16-bit unsigned short signal exclusive or with constant.

Parameters:

pSrc Source Signal Pointer.
nValue Constant value to be exclusive ored with each vector element
pDst Destination Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.466 NppStatus nppsXorC_16u_I (Npp16u nValue, Npp16u * pSrcDst, int nLength)

16-bit unsigned short in place signal exclusive or with constant.

Parameters:

pSrcDst In-Place Signal Pointer.
nValue Constant value to be exclusive ored with each vector element
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.467 NppStatus nppsXorC_32u (const Npp32u * *pSrc*, Npp32u *nValue*, Npp32u * *pDst*, int *nLength*)

32-bit unsigned integer signal exclusive or with constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be exclusive ored with each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.468 NppStatus nppsXorC_32u_I (Npp32u *nValue*, Npp32u * *pSrcDst*, int *nLength*)

32-bit unsigned signed integer in place signal exclusive or with constant.

Parameters:

pSrcDst In-Place Signal Pointer.

nValue Constant value to be exclusive ored with each vector element

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.469 NppStatus nppsXorC_8u (const Npp8u * *pSrc*, Npp8u *nValue*, Npp8u * *pDst*, int *nLength*)

8-bit unsigned char signal exclusive or with constant.

Parameters:

pSrc Source Signal Pointer.

nValue Constant value to be exclusive ored with each vector element

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.470 NppStatus nppsXorC_8u_I (Npp8u *nValue*, Npp8u * *pSrcDst*, int *nLength*)

8-bit unsigned char in place signal exclusive or with constant.

Parameters:

pSrcDst In-Place Signal Pointer.
nValue Constant value to be exclusive ored with each vector element
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.471 NppStatus nppsZero_16s (Npp16s * *pDst*, int *nLength*)

16-bit integer, vector zero method.

Parameters:

pDst Destination Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.472 NppStatus nppsZero_16sc (Npp16sc * *pDst*, int *nLength*)

16-bit integer complex, vector zero method.

Parameters:

pDst Destination Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.473 NppStatus nppsZero_32f (Npp32f * *pDst*, int *nLength*)

32-bit float, vector zero method.

Parameters:

pDst Destination Signal Pointer.
nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.474 NppStatus nppsZero_32fc (Npp32fc * *pDst*, int *nLength*)

32-bit float complex, vector zero method.

Parameters:

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.475 NppStatus nppsZero_32s (Npp32s * *pDst*, int *nLength*)

32-bit integer, vector zero method.

Parameters:

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.476 NppStatus nppsZero_32sc (Npp32sc * *pDst*, int *nLength*)

32-bit integer complex, vector zero method.

Parameters:

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.477 NppStatus nppsZero_64f (Npp64f * *pDst*, int *nLength*)

64-bit double, vector zero method.

Parameters:

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.478 NppStatus nppsZero_64fc (Npp64fc * *pDst*, int *nLength*)

64-bit double complex, vector zero method.

Parameters:

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.479 NppStatus nppsZero_64s (Npp64s * *pDst*, int *nLength*)

64-bit long long integer, vector zero method.

Parameters:

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.480 NppStatus nppsZero_64sc (Npp64sc * *pDst*, int *nLength*)

64-bit long long integer complex, vector zero method.

Parameters:

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

7.5.1.481 NppStatus nppsZero_8u (Npp8u * *pDst*, int *nLength*)

8-bit unsigned char, vector zero method.

Parameters:

pDst Destination Signal Pointer.

nLength Signal Length.

Returns:

Signal Data Related Error Codes, Length Related Error Codes.

Chapter 8

Data Structure Documentation

8.1 Npp16sc Struct Reference

Complex Number This struct represents a short complex number.

```
#include <nppdefs.h>
```

Data Fields

- [Npp16s re](#)
Real part.
- [Npp16s im](#)
Imaginary part.

8.1.1 Detailed Description

Complex Number This struct represents a short complex number.

8.1.2 Field Documentation

8.1.2.1 Npp16s Npp16sc::im

Imaginary part.

8.1.2.2 Npp16s Npp16sc::re

Real part.

The documentation for this struct was generated from the following file:

- C:/Perforce/sw/rel/gpgpu/toolkit/r4.0/NPP/npp/include/nppdefs.h

8.2 Npp32fc Struct Reference

Complex Number This struct represents a single floating-point complex number.

```
#include <nppdefs.h>
```

Data Fields

- [Npp32f re](#)
Real part.
- [Npp32f im](#)
Imaginary part.

8.2.1 Detailed Description

Complex Number This struct represents a single floating-point complex number.

8.2.2 Field Documentation

8.2.2.1 Npp32f Npp32fc::im

Imaginary part.

8.2.2.2 Npp32f Npp32fc::re

Real part.

The documentation for this struct was generated from the following file:

- C:/Perforce/sw/rel/gpgpu/toolkit/r4.0/NPP/npp/include/nppdefs.h

8.3 Npp32sc Struct Reference

Complex Number This struct represents a signed int complex number.

```
#include <nppdefs.h>
```

Data Fields

- [Npp32s re](#)
Real part.
- [Npp32s im](#)
Imaginary part.

8.3.1 Detailed Description

Complex Number This struct represents a signed int complex number.

8.3.2 Field Documentation

8.3.2.1 Npp32s Npp32sc::im

Imaginary part.

8.3.2.2 Npp32s Npp32sc::re

Real part.

The documentation for this struct was generated from the following file:

- C:/Perforce/sw/rel/gpgpu/toolkit/r4.0/NPP/npp/include/nppdefs.h

8.4 Npp64fc Struct Reference

Complex Number This struct represents a double floating-point complex number.

```
#include <nppdefs.h>
```

Data Fields

- [Npp64f re](#)
Real part.
- [Npp64f im](#)
Imaginary part.

8.4.1 Detailed Description

Complex Number This struct represents a double floating-point complex number.

8.4.2 Field Documentation

8.4.2.1 Npp64f Npp64fc::im

Imaginary part.

8.4.2.2 Npp64f Npp64fc::re

Real part.

The documentation for this struct was generated from the following file:

- C:/Perforce/sw/rel/gpgpu/toolkit/r4.0/NPP/npp/include/nppdefs.h

8.5 Npp64sc Struct Reference

Complex Number This struct represents a long long complex number.

```
#include <nppdefs.h>
```

Data Fields

- [Npp64s re](#)
Real part.
- [Npp64s im](#)
Imaginary part.

8.5.1 Detailed Description

Complex Number This struct represents a long long complex number.

8.5.2 Field Documentation

8.5.2.1 Npp64s Npp64sc::im

Imaginary part.

8.5.2.2 Npp64s Npp64sc::re

Real part.

The documentation for this struct was generated from the following file:

- C:/Perforce/sw/rel/gpgpu/toolkit/r4.0/NPP/npp/include/nppdefs.h

8.6 NppiHaarBuffer Struct Reference

```
#include <nppdefs.h>
```

Data Fields

- `int haarBufferSize`
size of the buffer
- `Npp32s * haarBuffer`
buffer

8.6.1 Field Documentation

8.6.1.1 `Npp32s* NppiHaarBuffer::haarBuffer`

buffer

8.6.1.2 `int NppiHaarBuffer::haarBufferSize`

size of the buffer

The documentation for this struct was generated from the following file:

- `C:/Perforce/sw/rel/gpgpu/toolkit/r4.0/NPP/npp/include/nppdefs.h`

8.7 NppiHaarClassifier_32f Struct Reference

```
#include <nppdefs.h>
```

Data Fields

- int [numClassifiers](#)
number of classifiers
- [Npp32s](#) * [classifiers](#)
packed classifier data 40 bytes each
- [size_t](#) [classifierStep](#)
- [NppiSize](#) [classifierSize](#)
- [Npp32s](#) * [counterDevice](#)

8.7.1 Field Documentation

8.7.1.1 [Npp32s](#)* [NppiHaarClassifier_32f::classifiers](#)

packed classifier data 40 bytes each

8.7.1.2 [NppiSize](#) [NppiHaarClassifier_32f::classifierSize](#)

8.7.1.3 [size_t](#) [NppiHaarClassifier_32f::classifierStep](#)

8.7.1.4 [Npp32s](#)* [NppiHaarClassifier_32f::counterDevice](#)

8.7.1.5 [int](#) [NppiHaarClassifier_32f::numClassifiers](#)

number of classifiers

The documentation for this struct was generated from the following file:

- C:/Perforce/sw/rel/gpgpu/toolkit/r4.0/NPP/npp/include/nppdefs.h

8.8 NppiPoint Struct Reference

2D Point

```
#include <nppdefs.h>
```

Data Fields

- `int x`
x-coordinate.
- `int y`
y-coordinate.

8.8.1 Detailed Description

2D Point

8.8.2 Field Documentation

8.8.2.1 `int NppiPoint::x`

x-coordinate.

8.8.2.2 `int NppiPoint::y`

y-coordinate.

The documentation for this struct was generated from the following file:

- `C:/Perforce/sw/rel/gpgpu/toolkit/r4.0/NPP/npp/include/nppdefs.h`

8.9 NppiRect Struct Reference

2D Rectangle This struct contains position and size information of a rectangle in two space.

```
#include <nppdefs.h>
```

Data Fields

- `int x`
x-coordinate of upper left corner.
- `int y`
y-coordinate of upper left corner.
- `int width`
Rectangle width.
- `int height`
Rectangle height.

8.9.1 Detailed Description

2D Rectangle This struct contains position and size information of a rectangle in two space.

The rectangle's position is usually signified by the coordinate of its upper-left corner.

8.9.2 Field Documentation

8.9.2.1 `int NppiRect::height`

Rectangle height.

8.9.2.2 `int NppiRect::width`

Rectangle width.

8.9.2.3 `int NppiRect::x`

x-coordinate of upper left corner.

8.9.2.4 `int NppiRect::y`

y-coordinate of upper left corner.

The documentation for this struct was generated from the following file:

- `C:/Perforce/sw/rel/gpgpu/toolkit/r4.0/NPP/npp/include/nppdefs.h`

8.10 NppiSize Struct Reference

2D Size This struct typically represents the size of a rectangular region in two space.

```
#include <nppdefs.h>
```

Data Fields

- int [width](#)
Rectangle width.
- int [height](#)
Rectangle height.

8.10.1 Detailed Description

2D Size This struct typically represents the size of a rectangular region in two space.

8.10.2 Field Documentation

8.10.2.1 int NppiSize::height

Rectangle height.

8.10.2.2 int NppiSize::width

Rectangle width.

The documentation for this struct was generated from the following file:

- C:/Perforce/sw/rel/gpgpu/toolkit/r4.0/NPP/npp/include/nppdefs.h

8.11 NppLibraryVersion Struct Reference

```
#include <nppdefs.h>
```

Data Fields

- int [major](#)
Major version number.
- int [minor](#)
Minor version number.
- int [build](#)
Build number. This reflects the nightly build this release was made from.

8.11.1 Field Documentation

8.11.1.1 int NppLibraryVersion::build

Build number. This reflects the nightly build this release was made from.

8.11.1.2 int NppLibraryVersion::major

Major version number.

8.11.1.3 int NppLibraryVersion::minor

Minor version number.

The documentation for this struct was generated from the following file:

- C:/Perforce/sw/rel/gpgpu/toolkit/r4.0/NPP/npp/include/nppdefs.h