

GGBase: infrastructure for genetics of gene expression

VJ Carey

April 23, 2010

1 Introduction

Data representations for genetics of gene expression in humans must be as efficient as possible. Up to Bioconductor 2.1, integrative genomics experiments could be represented by `racExSet` instances as defined in package `GGtools`. Genotypes were represented as integers.

For Bioconductor 2.2, we have access to the `snpMatrix` package of D. Clayton, and we have introduced the `smlSet` class to represent genetics of gene expression studies with lists of `snp.matrix` instances, along with ordinary representations of expression data.

2 Primary class structure, and associated methods

```
> library(GGBase)
> getClass("smlSet")
```

```
Class "smlSet" [package "GGBase"]
```

```
Slots:
```

Name:	smlEnv	annotation	organism
Class:	environment	character	character

Name:	assayData	phenoData	featureData
Class:	AssayData	AnnotatedDataFrame	AnnotatedDataFrame

Name:	experimentData	protocolData	.___classVersion__
Class:	MIAME	AnnotatedDataFrame	Versions

```
Extends:
```

```
Class "eSet", directly
```

Class "VersionedBiobase", by class "eSet", distance 2

Class "Versioned", by class "eSet", distance 3

```
> showMethods(class = "smlSet", where = "package:GGBase")
```

Function: [(package base)

x="smlSet", i="ANY", j="ANY", drop="ANY"

Function: coerce (package methods)

from="smlSet", to="ExpressionSet"

Function: combine (package Biobase)

x="smlSet", y="smlSet"

Function: exprs (package Biobase)

object="smlSet"

Function: getAlleles (package GGBase)

x="smlSet", rs="rsid"

Function: getSnpsLocs (package GGBase)

x="smlSet", c="chrnum"

x="smlSet", c="missing"

Function: plot_EvG (package GGBase)

gsym="genesym", rsid="rsid", sms="smlSet"

gsym="probeId", rsid="rsid", sms="smlSet"

Function: plot_EvG2 (package GGBase)

gsym="genesym", rsid1="rsid", rsid2="rsid", sms="smlSet"

gsym="probeId", rsid1="rsid", rsid2="rsid", sms="smlSet"

Function: show (package methods)

object="smlSet"

Function: smlEnv (package GGBase)

x="smlSet"

Function: smList (package GGBase)

x="smlSet"

Function: snpNames (package GGBase)

x="smlSet", c="chrnum"

```
x="smlSet", c="missing"
```

```
Function: snps (package GGBase)  
x="smlSet", chr="chrnum"
```

```
Function: updateObject (package Biobase)  
object="smlSet"
```

3 Example data structure

```
> data(smlSet.example)  
> smlSet.example
```

```
snp.matrix-based genotype set:  
number of samples: 10  
number of chromosomes present: 1  
annotation: illuminaHumanv1.db  
Expression data dims: 100 x 10  
Phenodata: An object of class "AnnotatedDataFrame"  
  sampleNames: NA06985, NA06991, ..., NA07048 (10 total)  
  varLabels and varMetadata description:  
    famid: hapmap family id  
    persid: hapmap person id  
    ...: ...  
    male: logical TRUE if male  
    (7 total)
```

4 SNP location infrastructure

see the newSNPloc vignette

5 Conclusion

The concepts discussed above define the bulk of the tools supporting the `gwSnpTests` method of GGtools. Consult the vignette of GGtools for more information.