

Gforth

for version 0.7.9 20230330, March 30, 2023

Neal Crook
Anton Ertl
David Kuehling
Bernd Paysan
Jens Wilke

This manual is for Gforth (version 0.7.9'20230330, March 30, 2023), a fast and portable implementation of the Standard Forth language. It serves as reference manual, but it also contains an introduction to Forth and a Forth tutorial.

Authors: Bernd Paysan, Anton Ertl, Gerald Wodni Copyright © 1995, 1996, 1997, 1998, 2000, 2003, 2004, 2005, 2006, 2007, 2008, 2009, 2010, 2011, 2012, 2013, 2014,2015,2016,2017,2018,2019,2020,2021,2022 Free Software Foundation, Inc.

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.1 or any later version published by the Free Software Foundation; with no Invariant Sections, with the Front-Cover texts being “A GNU Manual,” and with the Back-Cover Texts as in (a) below. A copy of the license is included in the section entitled “GNU Free Documentation License.”

(a) The FSF’s Back-Cover Text is: “You have freedom to copy and modify this GNU Manual, like GNU software. Copies published by the Free Software Foundation raise funds for GNU development.”

Table of Contents

Preface	1
1 Goals of Gforth	2
1.1 Stability Goals	2
2 Gforth Environment	3
2.1 Invoking Gforth	3
2.2 Leaving Gforth	6
2.3 Help on Gforth	6
2.4 Command-line editing	7
2.5 Environment variables	7
2.6 Gforth files	8
2.7 Gforth in pipes	8
2.8 Startup speed	9
3 Forth Tutorial	11
3.1 Starting Gforth	11
3.2 Syntax	11
3.3 Crash Course	11
3.4 Stack	12
3.5 Arithmetics	12
3.6 Stack Manipulation	13
3.7 Using files for Forth code	13
3.8 Comments	14
3.9 Colon Definitions	14
3.10 Decompilation	15
3.11 Stack-Effect Comments	15
3.12 Types	16
3.13 Factoring	17
3.14 Designing the stack effect	17
3.15 Local Variables	18
3.16 Conditional execution	19
3.17 Flags and Comparisons	19
3.18 General Loops	21
3.19 Counted loops	22
3.20 Recursion	23
3.21 Leaving definitions or loops	23
3.22 Return Stack	24
3.23 Memory	25
3.24 Characters and Strings	26
3.25 Alignment	27
3.26 Floating Point	27

3.27	Files	28
3.27.1	Open file for input	29
3.27.2	Create file for output	29
3.27.3	Scan file for a particular line	29
3.27.4	Copy input to output	30
3.27.5	Close files	30
3.28	Interpretation and Compilation Semantics and Immediacy	30
3.29	Execution Tokens	31
3.30	Exceptions	33
3.31	Defining Words	34
3.32	Arrays and Records	35
3.33	POSTPONE	35
3.34	Literal	36
3.35	Advanced macros	37
3.36	Compilation Tokens	38
3.37	Wordlists and Search Order	38
4	An Introduction to Standard Forth	40
4.1	Introducing the Text Interpreter	40
4.2	Stacks, postfix notation and parameter passing	42
4.3	Your first Forth definition	45
4.4	How does that work?	46
4.5	Forth is written in Forth	48
4.6	Review - elements of a Forth system	49
4.7	Where To Go Next	49
4.8	Exercises	50
5	Literals in source code	51
6	Forth Words	54
6.1	Notation	54
6.2	Case insensitivity	56
6.3	Comments	56
6.4	Boolean Flags	56
6.5	Arithmetic	57
6.5.1	Single precision	57
6.5.2	Double precision	57
6.5.3	Mixed precision	58
6.5.4	Integer division	58
6.5.5	Two-stage integer division	60
6.5.6	Bitwise operations	62
6.5.7	Numeric comparison	64
6.5.8	Floating Point	65
6.6	Stack Manipulation	68
6.6.1	Data stack	68

6.6.2	Floating point stack	68
6.6.3	Return stack	69
6.6.4	Locals stack	69
6.6.5	Stack pointer manipulation	69
6.7	Memory	70
6.7.1	Memory model	70
6.7.2	Dictionary allocation	70
6.7.3	Heap allocation	72
6.7.4	Memory Access	72
6.7.5	Special Memory Accesses	73
6.7.6	Address arithmetic	75
6.7.7	Memory Blocks	77
6.8	Strings and Characters	78
6.8.1	Characters	78
6.8.2	String representations	78
6.8.3	String and Character literals	79
6.8.4	String words	80
6.8.5	\$string words	81
6.8.6	Counted string words	84
6.9	Control Structures	84
6.9.1	Selection	84
6.9.2	Simple Loops	85
6.9.3	Counted Loops	86
6.9.4	Begin loops with multiple exits	88
6.9.5	General control structures with case	89
6.9.6	Arbitrary control structures	90
6.9.6.1	Programming Style	93
6.9.7	Calls and returns	93
6.9.8	Exception Handling	94
6.10	Defining Words	98
6.10.1	CREATE	98
6.10.2	Variables	99
6.10.3	Constants	99
6.10.4	Values	100
6.10.5	Colon Definitions	101
6.10.6	Anonymous Definitions	101
6.10.7	Quotations	102
6.10.8	Supplying the name of a defined word	102
6.10.9	User-defined Defining Words	102
6.10.9.1	User-defined defining words with colon definitions ..	102
6.10.9.2	User-defined defining words using create	103
6.10.9.3	Applications of CREATE . DOES >	105
6.10.9.4	The gory details of CREATE . DOES >	106
6.10.9.5	Advanced does> usage example	107
6.10.9.6	User-defined TO and DEFER @	109
6.10.9.7	User-defined compile ,	110
6.10.9.8	Creating from a prototype	111

6.10.9.9	Const-does>	112
6.10.10	Deferred Words	112
6.10.11	Forward	114
6.10.12	Aliases	114
6.11	Interpretation and Compilation Semantics	115
6.11.1	Combined Words	116
6.12	Tokens for Words	117
6.12.1	Execution token	117
6.12.2	Name token	118
6.12.3	Compilation token	120
6.13	Compiling words	120
6.13.1	Literals	120
6.13.2	Macros	122
6.14	The Text Interpreter	125
6.14.1	Input Sources	127
6.14.2	Number Conversion	128
6.14.3	Interpret/Compile states	128
6.14.4	Interpreter Directives	129
6.14.5	Recognizers	130
6.15	The Input Stream	132
6.16	Word Lists	133
6.16.1	Vocabularies	135
6.16.2	Why use word lists?	136
6.16.3	Word list example	137
6.17	Environmental Queries	137
6.18	Files	138
6.18.1	Forth source files	139
6.18.2	General files	140
6.18.3	Redirection	141
6.18.4	Directories	142
6.18.5	Search Paths	143
6.18.5.1	Source Search Paths	143
6.18.5.2	General Search Paths	143
6.19	Blocks	144
6.20	Other I/O	147
6.20.1	Simple numeric output	148
6.20.2	Formatted numeric output	148
6.20.3	Floating-point output	151
6.20.4	Miscellaneous output	153
6.20.5	Displaying characters and strings	154
6.20.6	Terminal output	154
6.20.6.1	Color output	154
6.20.6.2	Color themes	155
6.20.7	Single-key input	155
6.20.8	Line input and conversion	157
6.20.9	Pipes	159
6.20.10	Xchars and Unicode	159

6.20.11	Internationalization and Localization	161
6.20.12	Substitute.....	162
6.20.13	CSV Reader.....	162
6.21	OS command line arguments	163
6.22	Locals	164
6.22.1	Gforth locals	164
6.22.1.1	Where are locals visible by name?.....	165
6.22.1.2	How long do locals live?	167
6.22.1.3	Locals programming style.....	168
6.22.1.4	Locals implementation.....	169
6.22.1.5	Closures.....	171
6.22.2	Standard Forth locals.....	172
6.23	Structures.....	173
6.23.1	Why explicit structure support?	173
6.23.2	Structure Usage	174
6.23.3	Structure Naming Convention	175
6.23.4	Structure Implementation	176
6.23.5	Structure Glossary	176
6.23.6	Forth200x Structures	177
6.24	Object-oriented Forth	178
6.24.1	Why object-oriented programming?.....	178
6.24.2	Object-Oriented Terminology	178
6.24.3	The <code>objects.fs</code> model.....	179
6.24.3.1	Properties of the <code>objects.fs</code> model	179
6.24.3.2	Basic <code>objects.fs</code> Usage.....	180
6.24.3.3	The <code>object.fs</code> base class	181
6.24.3.4	Creating objects.....	181
6.24.3.5	Object-Oriented Programming Style	181
6.24.3.6	Class Binding	181
6.24.3.7	Method conveniences	182
6.24.3.8	Classes and Scoping	183
6.24.3.9	Dividing classes	183
6.24.3.10	Object Interfaces	184
6.24.3.11	<code>objects.fs</code> Implementation.....	185
6.24.3.12	<code>objects.fs</code> Glossary.....	186
6.24.4	The <code>oof.fs</code> model	189
6.24.4.1	Properties of the <code>oof.fs</code> model	189
6.24.4.2	Basic <code>oof.fs</code> Usage	190
6.24.4.3	The <code>oof.fs</code> base class	191
6.24.4.4	Class Declaration.....	192
6.24.4.5	Class Implementation.....	192
6.24.5	The <code>mini-oof.fs</code> model.....	192
6.24.5.1	Basic <code>mini-oof.fs</code> Usage	193
6.24.5.2	Mini-OOF Example	193
6.24.5.3	<code>mini-oof.fs</code> Implementation.....	194
6.24.6	Mini-OOF2	196
6.24.7	Comparison with other object models.....	196

6.25	Programming Tools	197
6.25.1	Locating source code definitions	197
6.25.2	Locating documentation	198
6.25.3	Locating uses of a word	198
6.25.4	Locating exception source	199
6.25.5	Examining compiled code	199
6.25.6	Examining data and code	201
6.25.7	Forgetting words	202
6.25.8	Debugging	202
6.25.9	Assertions	204
6.25.10	Singlestep Debugger	205
6.25.11	Code Coverage and Execution Frequency	206
6.26	Multitasker	207
6.26.1	Pthreads	207
6.26.1.1	Special User Variables	208
6.26.1.2	Semaphores	208
6.26.1.3	Atomic operations	209
6.26.1.4	Message Queues	209
6.26.1.5	Conditions	210
6.27	C Interface	210
6.27.1	Calling C functions	210
6.27.2	Declaring C Functions	211
6.27.3	Calling C function pointers from Forth	213
6.27.4	Defining library interfaces	213
6.27.5	Declaring OS-level libraries	214
6.27.6	Callbacks	215
6.27.7	How the C interface works	215
6.27.8	Low-Level C Interface Words	215
6.27.9	Automated interface generation using SWIG	216
6.27.9.1	Basic operation	216
6.27.9.2	Detailed operation:	216
6.27.9.3	Examples	216
6.27.10	Migrating from Gforth 0.7	216
6.28	Assembler and Code Words	217
6.28.1	Definitions in assembly language	217
6.28.2	Common Assembler	219
6.28.3	Common Disassembler	220
6.28.4	386 Assembler	220
6.28.5	AMD64 (x86_64) Assembler	222
6.28.6	Alpha Assembler	225
6.28.7	MIPS assembler	225
6.28.8	PowerPC assembler	226
6.28.9	ARM Assembler	227
6.28.10	Other assemblers	228
6.29	Carnal words	229
6.29.1	Header fields	229
6.29.2	Header methods	230

6.29.3	Threading Words	233
6.30	Passing Commands to the Operating System	235
6.31	Keeping track of Time	235
6.32	Miscellaneous Words	236
7	Error messages	237
8	Tools	238
8.1	<code>ans-report.fs</code> : Report the words used, sorted by wordset	238
8.1.1	Caveats	238
8.2	Stack depth changes during interpretation	238
9	Standard conformance	240
9.1	The Core Words	241
9.1.1	Implementation Defined Options	241
9.1.2	Ambiguous conditions	244
9.1.3	Other system documentation	247
9.2	The optional Block word set	247
9.2.1	Implementation Defined Options	247
9.2.2	Ambiguous conditions	248
9.2.3	Other system documentation	248
9.3	The optional Double Number word set	248
9.3.1	Ambiguous conditions	248
9.4	The optional Exception word set	248
9.4.1	Implementation Defined Options	248
9.5	The optional Facility word set	248
9.5.1	Implementation Defined Options	249
9.5.2	Ambiguous conditions	249
9.6	The optional File-Access word set	249
9.6.1	Implementation Defined Options	249
9.6.2	Ambiguous conditions	250
9.7	The optional Floating-Point word set	250
9.7.1	Implementation Defined Options	251
9.7.2	Ambiguous conditions	251
9.8	The optional Locals word set	252
9.8.1	Implementation Defined Options	252
9.8.2	Ambiguous conditions	252
9.9	The optional Memory-Allocation word set	253
9.9.1	Implementation Defined Options	253
9.10	The optional Programming-Tools word set	253
9.10.1	Implementation Defined Options	253
9.10.2	Ambiguous conditions	253
9.11	The optional Search-Order word set	254
9.11.1	Implementation Defined Options	254
9.11.2	Ambiguous conditions	254

10	Should I use Gforth extensions?.....	255
11	Model	256
12	Integrating Gforth into C programs	257
12.1	Types.....	257
12.2	Variables.....	258
12.3	Functions.....	258
12.4	Signals.....	258
13	Emacs and Gforth	259
13.1	Installing gforth.el.....	259
13.2	Emacs Tags.....	259
13.3	Hilighting.....	260
13.4	Auto-Indentation.....	260
13.5	Blocks Files.....	261
14	Image Files.....	262
14.1	Image Licensing Issues	262
14.2	Image File Background.....	262
14.3	Non-Relocatable Image Files	263
14.4	Data-Relocatable Image Files.....	264
14.5	Fully Relocatable Image Files	264
14.5.1	<code>gforthmi</code>	264
14.5.2	<code>cross.fs</code>	265
14.6	Stack and Dictionary Sizes	265
14.7	Running Image Files	265
14.8	Modifying the Startup Sequence.....	266
15	Engine.....	268
15.1	Portability	268
15.2	Threading.....	268
15.2.1	Scheduling	269
15.2.2	Direct or Indirect Threaded?	270
15.2.3	Dynamic Superinstructions	270
15.2.4	DOES>	272
15.3	Primitives.....	272
15.3.1	Automatic Generation.....	272
15.3.2	TOS Optimization	273
15.3.3	Produced code	274
15.4	Performance	274

16	Cross Compiler	277
16.1	Using the Cross Compiler	277
16.2	How the Cross Compiler Works.....	279
17	MINOS2, a GUI library.....	280
17.1	MINOS2 object framework.....	280
17.1.1	<code>actor</code> methods:.....	280
17.1.2	<code>widget</code> methods:.....	280
17.2	MINOS2 tutorial.....	280
Appendix A	Bugs	282
Appendix B	Authors and Ancestors of Gforth ..	283
B.1	Authors and Contributors.....	283
B.2	Pedigree.....	283
Appendix C	Other Forth-related information ..	284
Appendix D	Licenses	285
D.1	GNU Free Documentation License	285
D.1.1	ADDENDUM: How to use this License for your documents ..	291
D.2	GNU GENERAL PUBLIC LICENSE	291
Word Index	303
Concept and Word Index	318

Preface

This manual documents Gforth. Some introductory material is provided for readers who are unfamiliar with Forth or who are migrating to Gforth from other Forth compilers. However, this manual is primarily a reference manual.

1 Goals of Gforth

The goal of the Gforth Project is to develop a standard model for Standard Forth. This can be split into several subgoals:

- Gforth should conform to the Forth Standard.
- It should be a model, i.e. it should define all the implementation-dependent things.
- It should become standard, i.e. widely accepted and used. This goal is the most difficult one.

To achieve these goals Gforth should be

- Similar to previous models (fig-Forth, F83)
- Powerful. It should provide for all the things that are considered necessary today and even some that are not yet considered necessary.
- Efficient. It should not get the reputation of being exceptionally slow.
- Free.
- Available on many machines/easy to port.

Have we achieved these goals? Gforth conforms to the Forth-94 (ANS Forth) and Forth-2012 standards. We have changed some of the internal data structures (in particular, the headers) over time, so Gforth cannot be considered a stable model. It certainly has not yet become a de facto standard, but it appears to be quite popular. It has some similarities to and some differences from previous models. It has some powerful features, but not yet everything that we envisioned. We certainly have achieved our execution speed goals (see Section 15.4 [Performance], page 274)¹. It is free and available on many machines.

1.1 Stability Goals

Programs that work on earlier versions of Gforth should also work on newer versions. However, there are some caveats:

Internal data structures (including the representation of code) of Gforth may change between versions, unless they are documented.

Moreover, we only feel obliged to keep standard words (i.e., with standard wordset names) and words documented as permanent Gforth extensions (with wordset name `gforth` or `gforth-<version>`, see Section 6.1 [Notation], page 54). Other words may be removed in newer releases.

In particular, you may find a word by using `locate` or otherwise inspecting Gforth's source code. You can see the wordset in a comment right after the stack-effect comment. If there is no wordset for a word, it is an internal factor and may be removed in a future version. If the wordset is `gforth-experimental`, `gforth-internal`, or `gforth-obsolete`, the word may also be removed in a future version.

If you want to use a particular word that is not marked as permanent, please let us know, and we will consider to add the word as permanent word (or we may suggest an alternative to using this word).

¹ However, in 1998 the bar was raised when the major commercial Forth vendors switched to native code compilers.

2 Gforth Environment

Note: ultimately, the Gforth man page will be auto-generated from the material in this chapter.

For related information about the creation of images see Chapter 14 [Image Files], page 262.

2.1 Invoking Gforth

Gforth is made up of two parts; an executable “engine” (named **gforth** or **gforth-fast**) and an image file. To start it, you will usually just say **gforth** – this automatically loads the default image file **gforth.fi**. In many other cases the default Gforth image will be invoked like this:

```
gforth [file | -e forth-code] ...
```

This interprets the contents of the files and the Forth code in the order they are given.

In addition to the **gforth** engine, there is also an engine called **gforth-fast**, which is faster, but gives less informative error messages (see Chapter 7 [Error messages], page 237) and may catch some errors (in particular, stack underflows and integer division errors) later or not at all. You should use it for debugged, performance-critical programs.

Moreover, there is an engine called **gforth-its**, which is useful in some backwards-compatibility situations (see Section 15.2.2 [Direct or Indirect Threaded?], page 270).

In general, the command line looks like this:

```
gforth[-fast] [engine options] [image options]
```

The engine options must come before the rest of the command line. They are:

--image-file file

-i file Loads the Forth image *file* instead of the default **gforth.fi** (see Chapter 14 [Image Files], page 262).

--appl-image file

Loads the image *file* and leaves all further command-line arguments to the image (instead of processing them as engine options). This is useful for building executable application images on Unix, built with **gforthmi --application**

--path path

-p path Uses *path* for searching the image file and Forth source code files instead of the default in the environment variable **GFORTHPATH** or the path specified at installation time and the working directory **.** (e.g., **/usr/local/share/gforth/0.2.0:.**). A path is given as a list of directories, separated by **‘:’** (previous versions had **‘;’** for other OSes, but since Cygwin now only accepts **/cygdrive/<letter>**, and we dropped support for OS/2 and MS-DOS, it is **‘:’** everywhere).

--dictionary-size size

-m size Allocate *size* space for the Forth dictionary space instead of using the default specified in the image (typically 256K). The *size* specification for this and subsequent options consists of an integer and a unit (e.g., **4M**). The unit can be

one of **b** (bytes), **e** (element size, in this case Cells), **k** (kilobytes), **M** (Megabytes), **G** (Gigabytes), and **T** (Terabytes). If no unit is specified, **e** is used.

--data-stack-size size

-d size Allocate *size* space for the data stack instead of using the default specified in the image (typically 16K).

--return-stack-size size

-r size Allocate *size* space for the return stack instead of using the default specified in the image (typically 15K).

--fp-stack-size size

-f size Allocate *size* space for the floating point stack instead of using the default specified in the image (typically 15.5K). In this case the unit specifier **e** refers to floating point numbers.

--locals-stack-size size

-l size Allocate *size* space for the locals stack instead of using the default specified in the image (typically 14.5K).

--vm-commit

Normally, Gforth tries to start up even if there is not enough virtual memory for the dictionary and the stacks (using **MAP_NORESERVE** on OSs that support it); so you can ask for a really big dictionary and/or stacks, and as long as you don't use more virtual memory than is available, everything will be fine (but if you use more, processes get killed). With this option you just use the default allocation policy of the OS; for OSs that don't overcommit (e.g., Solaris), this means that you cannot and should not ask for as big dictionary and stacks, but once Gforth successfully starts up, out-of-memory won't kill it.

--help

-h Print a message about the command-line options

--version

-v Print version and exit

--debug Print some information useful for debugging on startup.

--offset-image

Start the dictionary at a slightly different position than would be used otherwise (useful for creating data-relocatable images, see Section 14.4 [Data-Relocatable Image Files], page 264).

--no-offset-im

Start the dictionary at the normal position.

--clear-dictionary

Initialize all bytes in the dictionary to 0 before loading the image (see Section 14.4 [Data-Relocatable Image Files], page 264).

--die-on-signal

Normally Gforth handles most signals (e.g., the user interrupt **SIGINT**, or the segmentation violation **SIGSEGV**) by translating it into a Forth **THROW**. With this option, Gforth exits if it receives such a signal. This option is useful when

the engine and/or the image might be severely broken (such that it causes another signal before recovering from the first); this option avoids endless loops in such cases.

`--no-dynamic`

`--dynamic`

Disable or enable dynamic superinstructions with replication (see Section 15.2.3 [Dynamic Superinstructions], page 270).

`--no-super`

Disable dynamic superinstructions, use just dynamic replication; this is useful if you want to patch threaded code (see Section 15.2.3 [Dynamic Superinstructions], page 270).

`--ss-number=N`

Use only the first *N* static superinstructions compiled into the engine (default: use them all; note that only **gforth-fast** has any). This option is useful for measuring the performance impact of static superinstructions.

`--ss-min-codesize`

`--ss-min-ls`

`--ss-min-lsu`

`--ss-min-nexts`

Use specified metric for determining the cost of a primitive or static superinstruction for static superinstruction selection. **Codesize** is the native code size of the primitive or static superinstruction, **ls** is the number of loads and stores, **lsu** is the number of loads, stores, and updates, and **nexts** is the number of dispatches (not taking dynamic superinstructions into account), i.e. every primitive or static superinstruction has cost 1. Default: **codesize** if you use dynamic code generation, otherwise **nexts**.

`--ss-greedy`

This option is useful for measuring the performance impact of static superinstructions. By default, an optimal shortest-path algorithm is used for selecting static superinstructions. With `--ss-greedy` this algorithm is modified to assume that anything after the static superinstruction currently under consideration is not combined into static superinstructions. With `--ss-min-nexts` this produces the same result as a greedy algorithm that always selects the longest superinstruction available at the moment. E.g., if there are superinstructions AB and BCD, then for the sequence A B C D the optimal algorithm will select A BCD and the greedy algorithm will select AB C D.

`--print-metrics`

Prints some metrics used during static superinstruction selection: **code size** is the actual size of the dynamically generated code. **Metric codesize** is the sum of the codesize metrics as seen by static superinstruction selection; there is a difference from **code size**, because not all primitives and static superinstructions are compiled into dynamically generated code, and because of markers. The other metrics correspond to the `ss-min-...` options. This option is useful for evaluating the effects of the `--ss-...` options.

As explained above, the image-specific command-line arguments for the default image `gforth.fi` consist of a sequence of filenames and `-e forth-code` options that are interpreted in the sequence in which they are given. The `-e forth-code` or `--evaluate forth-code` option evaluates the Forth code. This option takes only one argument; if you want to evaluate more Forth words, you have to quote them or use `-e` several times. To exit after processing the command line (instead of entering interactive mode) append `-e bye` to the command line. You can also process the command-line arguments with a Forth program (see Section 6.21 [OS command line arguments], page 163).

If you have several versions of Gforth installed, `gforth` will invoke the version that was installed last. `gforth-<version>` invokes a specific version. If your environment contains the variable `GFORTHPATH`, you may want to override it by using the `--path` option.

On startup, before processing any of the image option, the user initialization file either specified in the environment variable `GFORTH_ENV` or, if not set, `~/.config/gforthrc0` is included, if it exists. If `GFORTH_ENV` is “off,” nothing is included. After processing all the image options and just before printing the boot message, the user initialization file `~/.config/gforthrc` from your home directory is included, unless the option `--no-rc` is given.

Warning levels can be set with

```
-W           Turn off warnings
-Won        Turn on warnings (level 1)
-Wall       Turn on beginner warnings (level 2)
-Wpedantic  Turn on pedantic warnings (level 3)
-Werror     Turn warnings into errors (level 4)
```

2.2 Leaving Gforth

You can leave Gforth by typing `bye` or `Ctrl-d` (at the start of a line) or (if you invoked Gforth with the `--die-on-signal` option) `Ctrl-c`. When you leave Gforth, all of your definitions and data are discarded. For ways of saving the state of the system before leaving Gforth see Chapter 14 [Image Files], page 262.

`bye (-) tools-ext “bye”`

2.3 Help on Gforth

Gforth has a simple, text-based online help system.

`help ("rest-of-line" -) gforth-1.0 “help”`

If no name is given, show basic help. If a documentation node name is given followed by `::`, show the start of the node. If the name of a word is given, show the documentation of the word if it exists, or its source code if not. Use `g` to enter the editor at the point shown by `help`. open command addr u, and read in the result

`authors (-) gforth-1.0 “authors”`

show the list of authors

`license (-) gforth-0.2 “license”`

print the license statement

2.4 Command-line editing

Gforth maintains a history file that records every line that you type to the text interpreter. This file is preserved between sessions, and is used to provide a command-line recall facility; if you type *Ctrl-P* repeatedly you can recall successively older commands from this (or previous) session(s). The full list of command-line editing facilities is:

- *Ctrl-p* (“previous”) (or up-arrow) to recall successively older commands from the history buffer.
- *Ctrl-n* (“next”) (or down-arrow) to recall successively newer commands from the history buffer.
- *Ctrl-f* (or right-arrow) to move the cursor right, non-destructively.
- *Ctrl-b* (or left-arrow) to move the cursor left, non-destructively.
- *Ctrl-h* (backspace) to delete the character to the left of the cursor, closing up the line.
- *Ctrl-k* to delete (“kill”) from the cursor to the end of the line.
- *Ctrl-a* to move the cursor to the start of the line.
- *Ctrl-e* to move the cursor to the end of the line.
- RET (*Ctrl-m*) or LFD (*Ctrl-j*) to submit the current line.
- TAB to step through all possible full-word completions of the word currently being typed.
- *Ctrl-d* on an empty line to terminate Gforth (gracefully, using *bye*).
- *Ctrl-x* (or *Ctrl-d* on a non-empty line) to delete the character under the cursor.

When editing, displayable characters are inserted to the left of the cursor position; the line is always in “insert” (as opposed to “overstrike”) mode.

On Unix systems, the history file is `~/.local/share/gforth/history` by default¹. You can find out the name and location of your history file using:

```
history-file type \ Unix-class systems
```

```
history-file type \ Other systems
history-dir type
```

If you enter long definitions by hand, you can use a text editor to paste them out of the history file into a Forth source file for reuse at a later time.

Gforth never trims the size of the history file, so you should do this periodically, if necessary.

2.5 Environment variables

Gforth uses these environment variables:

- **GFORTH HIST** – (Unix systems only) specifies the path for the history file `.gforth-history`. Default: `$HOME/.gforth-history`.

¹ i.e. it is stored in the user’s home directory.

- **GFORTHPATH** – specifies the path used when searching for the gforth image file and for Forth source-code files (usually ‘.’, the current working directory). Path separator is ‘:’, a typical path would be `/usr/local/share/gforth/0.8.0:..`.
- **LANG** – see **LC_CTYPE**
- **LC_ALL** – see **LC_CTYPE**
- **LC_CTYPE** – If this variable contains “UTF-8” on Gforth startup, Gforth uses the UTF-8 encoding for strings internally and expects its input and produces its output in UTF-8 encoding, otherwise the encoding is 8bit (see Section 6.20.10 [Xchars and Unicode], page 159). If this environment variable is unset, Gforth looks in **LC_ALL**, and if that is unset, in **LANG**.
- **GFORTHSYSTEMPREFIX** – specifies what to prepend to the argument of **system** before passing it to C’s **system()**. Default: `"/$COMSPEC /c "` on Windows, `"` on other OSs. The prefix and the command are directly concatenated, so if a space between them is necessary, append it to the prefix.
- **GFORTH** – used by **gforthmi**, See Section 14.5.1 [gforthmi], page 264.
- **GFORTHHD** – used by **gforthmi**, See Section 14.5.1 [gforthmi], page 264.
- **TMP, TEMP** - (non-Unix systems only) used as a potential location for the history file.

All the Gforth environment variables default to sensible values if they are not set.

2.6 Gforth files

When you install Gforth on a Unix system, it installs files in these locations by default:

- `/usr/local/bin/gforth`
- `/usr/local/bin/gforthmi`
- `/usr/local/man/man1/gforth.1` - man page.
- `/usr/local/info` - the Info version of this manual.
- `/usr/local/lib/gforth/<version>/...` - Gforth **.fi** files.
- `/usr/local/share/gforth/<version>/TAGS` - Emacs TAGS file.
- `/usr/local/share/gforth/<version>/...` - Gforth source files.
- `.../emacs/site-lisp/gforth.el` - Emacs gforth mode.

You can select different places for installation by using **configure** options (listed with **configure --help**).

2.7 Gforth in pipes

Gforth can be used in pipes created elsewhere (described in the following). It can also create pipes on its own (see Section 6.20.9 [Pipes], page 159).

If you pipe into Gforth, your program should read with **read-file** or **read-line** from **stdin** (see Section 6.18.2 [General files], page 140). **Key** does not recognize the end of input. Words like **accept** echo the input and are therefore usually not useful for reading from a pipe. You have to invoke the Forth program with an OS command-line option, as you have

no chance to use the Forth command line (the text interpreter would try to interpret the pipe input).

You can output to a pipe with `type`, `emit`, `cr` etc.

When you write to a pipe that has been closed at the other end, Gforth receives a `SIGPIPE` signal (“pipe broken”). Gforth translates this into the exception `broken-pipe-error`. If your application does not catch that exception, the system catches it and exits, usually silently (unless you were working on the Forth command line; then it prints an error message and exits). This is usually the desired behaviour.

If you do not like this behaviour, you have to catch the exception yourself, and react to it.

Here’s an example of an invocation of Gforth that is usable in a pipe:

```
gforth -e ": foo begin pad dup 10 stdin read-file throw dup while \
type repeat ; foo bye"
```

This example just copies the input verbatim to the output. A very simple pipe containing this example looks like this:

```
cat startup.fs |
gforth -e ": foo begin pad dup 80 stdin read-file throw dup while \
type repeat ; foo bye"|
head
```

Pipes involving Gforth’s `stderr` output do not work.

2.8 Startup speed

If Gforth is used for CGI scripts or in shell scripts, its startup speed may become a problem. On a 3GHz Core 2 Duo E8400 under 64-bit Linux 2.6.27.8 with `libc-2.7`, `gforth-fast -e bye` takes 13.1ms user and 1.2ms system time (`gforth -e bye` is faster on startup with about 3.4ms user time and 1.2ms system time, because it subsumes some of the options discussed below).

If startup speed is a problem, you may consider the following ways to improve it; or you may consider ways to reduce the number of startups (for example, by using Fast-CGI). Note that the first steps below improve the startup time at the cost of run-time (including compile-time), so whether they are profitable depends on the balance of these times in your application.

An easy step that influences Gforth startup speed is the use of a number of options that increase run-time, but decrease image-loading time.

The first of these that you should try is `--ss-number=0 --ss-states=1` because this option buys relatively little run-time speedup and costs quite a bit of time at startup. `gforth-fast --ss-number=0 --ss-states=1 -e bye` takes about 2.8ms user and 1.5ms system time.

The next option is `--no-dynamic` which has a substantial impact on run-time (about a factor of 2 on several platforms), but still makes startup speed a little faster: `gforth-fast --ss-number=0 --ss-states=1 --no-dynamic -e bye` consumes about 2.6ms user and 1.2ms system time.

The next step to improve startup speed is to use a data-relocatable image (see Section 14.4 [Data-Relocatable Image Files], page 264). This avoids the relocation cost for the code in the

image (but not for the data). Note that the image is then specific to the particular binary you are using (i.e., whether it is `gforth`, `gforth-fast`, and even the particular build). You create the data-relocatable image that works with `./gforth-fast` with `GFORTHHD="./gforth-fast --no-dynamic" gforthmi gforthdr.fi` (the `--no-dynamic` is required here or the image will not work). And you run it with `gforth-fast -i gforthdr.fi ... -e bye` (the flags discussed above don't matter here, because they only come into play on relocatable code). `gforth-fast -i gforthdr.fi -e bye` takes about 1.1ms user and 1.2ms system time.

One step further is to avoid all relocation cost and part of the copy-on-write cost through using a non-relocatable image (see Section 14.3 [Non-Relocatable Image Files], page 263). However, this has the disadvantage that it does not work on operating systems with address space randomization (the default in, e.g., Linux nowadays), or if the dictionary moves for any other reason (e.g., because of a change of the OS kernel or an updated library), so we cannot really recommend it. You create a non-relocatable image with `gforth-fast --no-dynamic -e "savesystem gforthnr.fi bye"` (the `--no-dynamic` is required here, too). And you run it with `gforth-fast -i gforthnr.fi ... -e bye` (again the flags discussed above don't matter). `gforth-fast -i gforthdr.fi -e bye` takes about 0.9ms user and 0.9ms system time.

If the script you want to execute contains a significant amount of code, it may be profitable to compile it into the image to avoid the cost of compiling it at startup time.

3 Forth Tutorial

The difference of this chapter from the Introduction (see Chapter 4 [Introduction], page 40) is that this tutorial is more fast-paced, should be used while sitting in front of a computer, and covers much more material, but does not explain how the Forth system works.

This tutorial can be used with any Standard-compliant Forth; any Gforth-specific features are marked as such and you can skip them if you work with another Forth. This tutorial does not explain all features of Forth, just enough to get you started and give you some ideas about the facilities available in Forth. Read the rest of the manual when you are through this.

The intended way to use this tutorial is that you work through it while sitting in front of the console, take a look at the examples and predict what they will do, then try them out; if the outcome is not as expected, find out why (e.g., by trying out variations of the example), so you understand what's going on. There are also some assignments that you should solve.

This tutorial assumes that you have programmed before and know what, e.g., a loop is.

3.1 Starting Gforth

You can start Gforth by typing its name:

```
gforth
```

That puts you into interactive mode; you can leave Gforth by typing `bye`. While in Gforth, you can edit the command line and access the command line history with cursor keys, similar to `bash`.

3.2 Syntax

A *word* is a sequence of arbitrary characters (except white space). Words are separated by white space. E.g., each of the following lines contains exactly one word:

```
word
!@#$$%^&*()
1234567890
5!a
```

A frequent beginner's error is to leave out necessary white space, resulting in an error like 'Undefined word'; so if you see such an error, check if you have put spaces wherever necessary.

```
." hello, world" \ correct
."hello, world" \ gives an "Undefined word" error
```

Gforth and most other Forth systems ignore differences in case (they are case-insensitive), i.e., 'word' is the same as 'Word'. If your system is case-sensitive, you may have to type all the examples given here in upper case.

3.3 Crash Course

Forth does not prevent you from shooting yourself in the foot. Let's try a few ways to crash Gforth:

```
0 0 !
```

```
here execute
' catch >body 20 erase abort
' (quit1) >body 20 erase
```

The last two examples are guaranteed to destroy important parts of Gforth (and most other systems), so you better leave Gforth afterwards (if it has not finished by itself). On some systems you may have to kill gforth from outside (e.g., in Unix with `kill`).

You will find out later what these lines do and then you will get an idea why they produce crashes.

Now that you know how to produce crashes (and that there's not much to them), let's learn how to produce meaningful programs.

3.4 Stack

The most obvious feature of Forth is the stack. When you type in a number, it is pushed on the stack. You can display the contents of the stack with `.s`.

```
1 2 .s
3 .s
```

`.s` displays the top-of-stack to the right, i.e., the numbers appear in `.s` output as they appeared in the input.

You can print the top element of the stack with `..`

```
1 2 3 . . .
```

In general, words consume their stack arguments (`.s` is an exception).

Assignment: What does the stack contain after `5 6 7 .?`

3.5 Arithmetics

The words `+`, `-`, `*`, `/`, and `mod` always operate on the top two stack items:

```
2 2 .s
+ .s
.
2 1 - .
7 3 mod .
```

The operands of `-`, `/`, and `mod` are in the same order as in the corresponding infix expression (this is generally the case in Forth).

Parentheses are superfluous (and not available), because the order of the words unambiguously determines the order of evaluation and the operands:

```
3 4 + 5 * .
3 4 5 * + .
```

Assignment: What are the infix expressions corresponding to the Forth code above? Write `6-7*8+9` in Forth notation¹.

To change the sign, use `negate`:

```
2 negate .
```

¹ This notation is also known as Postfix or RPN (Reverse Polish Notation).

Assignment: Convert $-(-3)*4-5$ to Forth.

/mod performs both / and mod.

```
7 3 /mod . .
```

Reference: Section 6.5 [Arithmetic], page 57.

3.6 Stack Manipulation

Stack manipulation words rearrange the data on the stack.

```
1 .s drop .s
1 .s dup .s drop drop .s
1 2 .s over .s drop drop drop
1 2 .s swap .s drop drop
1 2 3 .s rot .s drop drop drop
```

These are the most important stack manipulation words. There are also variants that manipulate twice as many stack items:

```
1 2 3 4 .s 2swap .s 2drop 2drop
```

Two more stack manipulation words are:

```
1 2 .s nip .s drop
1 2 .s tuck .s 2drop drop
```

Assignment: Replace nip and tuck with combinations of other stack manipulation words.

Given:	How do you get:
1 2 3	3 2 1
1 2 3	1 2 3 2
1 2 3	1 2 3 3
1 2 3	1 3 3
1 2 3	2 1 3
1 2 3 4	4 3 2 1
1 2 3	1 2 3 1 2 3
1 2 3 4	1 2 3 4 1 2
1 2 3	
1 2 3	1 2 3 4
1 2 3	1 3

```
5 dup * .
```

Assignment: Write 17^3 and 17^4 in Forth, without writing 17 more than once. Write a piece of Forth code that expects two numbers on the stack (a and b , with b on top) and computes $(a-b)(a+1)$.

Reference: Section 6.6 [Stack Manipulation], page 68.

3.7 Using files for Forth code

While working at the Forth command line is convenient for one-line examples and short one-off code, you probably want to store your source code in files for convenient editing

and persistence. You can use your favourite editor (Gforth includes Emacs support, see Chapter 13 [Emacs and Gforth], page 259) to create *file.fs* and use

```
s" file.fs" included
```

to load it into your Forth system. The file name extension I use for Forth files is *‘.fs’*.

You can easily start Gforth with some files loaded like this:

```
gforth file1.fs file2.fs
```

If an error occurs during loading these files, Gforth terminates, whereas an error during **INCLUDED** within Gforth usually gives you a Gforth command line. Starting the Forth system every time gives you a clean start every time, without interference from the results of earlier tries.

I often put all the tests in a file, then load the code and run the tests with

```
gforth code.fs tests.fs -e bye
```

(often by performing this command with *C-x C-e* in Emacs). The *-e bye* ensures that Gforth terminates afterwards so that I can restart this command without ado.

The advantage of this approach is that the tests can be repeated easily every time the program is changed, making it easy to catch bugs introduced by the change.

Reference: Section 6.18.1 [Forth source files], page 139.

3.8 Comments

```
\ That's a comment; it ends at the end of the line
( Another comment; it ends here: ) .s
```

** and *(* are ordinary Forth words and therefore have to be separated with white space from the following text.

```
\This gives an "Undefined word" error
```

The first *)* ends a comment started with *(*, so you cannot nest *(*-comments; and you cannot comment out text containing a *)* with *(...)²*.

I use **-comments for descriptive text and for commenting out code of one or more line; I use *(*-comments for describing the stack effect, the stack contents, or for commenting out sub-line pieces of code.

The Emacs mode *gforth.el* (see Chapter 13 [Emacs and Gforth], page 259) supports these uses by commenting out a region with *C-x *, uncommenting a region with *C-u C-x *, and filling a **-commented region with *M-q*.

Reference: Section 6.3 [Comments], page 56.

3.9 Colon Definitions

are similar to procedures and functions in other programming languages.

```
: squared ( n -- n^2 )
  dup * ;
5 squared .
7 squared .
```

² therefore it's a good idea to avoid *)* in word names.

: starts the colon definition; its name is **squared**. The following comment describes its stack effect. The words **dup** ***** are not executed, but compiled into the definition. **;** ends the colon definition.

The newly-defined word can be used like any other word, including using it in other definitions:

```
: cubed ( n -- n^3 )
    dup squared * ;
-5 cubed .
: fourth-power ( n -- n^4 )
    squared squared ;
3 fourth-power .
```

Assignment: Write colon definitions for **nip**, **tuck**, **negate**, and **/mod** in terms of other Forth words, and check if they work (hint: test your tests on the originals first). Don't let the 'redefined'-Messages spook you, they are just warnings.

Reference: Section 6.10.5 [Colon Definitions], page 101.

3.10 Decompilation

You can decompile colon definitions with **see**:

```
see squared
see cubed
```

In Gforth **see** shows you a reconstruction of the source code from the executable code. Informations that were present in the source, but not in the executable code, are lost (e.g., comments).

You can also decompile the predefined words:

```
see .
see +
```

3.11 Stack-Effect Comments

By convention the comment after the name of a definition describes the stack effect: The part in front of the '--' describes the state of the stack before the execution of the definition, i.e., the parameters that are passed into the colon definition; the part behind the '--' is the state of the stack after the execution of the definition, i.e., the results of the definition. The stack comment only shows the top stack items that the definition accesses and/or changes.

You should put a correct stack effect on every definition, even if it is just (--). You should also add some descriptive comment to more complicated words (I usually do this in the lines following :). If you don't do this, your code becomes unreadable (because you have to work through every definition before you can understand any).

Assignment: The stack effect of **swap** can be written like this: **x1 x2 -- x2 x1**. Describe the stack effect of **-**, **drop**, **dup**, **over**, **rot**, **nip**, and **tuck**. Hint: When you are done, you can compare your stack effects to those in this manual (see [Word Index], page 303).

Sometimes programmers put comments at various places in colon definitions that describe the contents of the stack at that place (stack comments); i.e., they are like the first part of a stack-effect comment. E.g.,

```

: cubed ( n -- n^3 )
  dup squared ( n n^2 ) * ;

```

In this case the stack comment is pretty superfluous, because the word is simple enough. If you think it would be a good idea to add such a comment to increase readability, you should also consider factoring the word into several simpler words (see Section 3.13 [Factoring], page 17), which typically eliminates the need for the stack comment; however, if you decide not to refactor it, then having such a comment is better than not having it.

The names of the stack items in stack-effect and stack comments in the standard, in this manual, and in many programs specify the type through a type prefix, similar to Fortran and Hungarian notation. The most frequent prefixes are:

<code>n</code>	signed integer
<code>u</code>	unsigned integer
<code>c</code>	character
<code>f</code>	Boolean flags, i.e. <code>false</code> or <code>true</code> .
<code>a-addr, a-</code>	Cell-aligned address
<code>c-addr, c-</code>	Char-aligned address (note that a Char may have two bytes in Windows NT)
<code>xt</code>	Execution token, same size as Cell
<code>w, x</code>	Cell, can contain an integer or an address. It usually takes 32, 64 or 16 bits (depending on your platform and Forth system). A cell is more commonly known as machine word, but the term <i>word</i> already means something different in Forth.
<code>d</code>	signed double-cell integer
<code>ud</code>	unsigned double-cell integer
<code>r</code>	Float (on the FP stack)

You can find a more complete list in Section 6.1 [Notation], page 54.

Assignment: Write stack-effect comments for all definitions you have written up to now.

3.12 Types

In Forth the names of the operations are not overloaded; so similar operations on different types need different names; e.g., `+` adds integers, and you have to use `f+` to add floating-point numbers. The following prefixes are often used for related operations on different types:

<code>(none)</code>	signed integer
<code>u</code>	unsigned integer
<code>c</code>	character
<code>d</code>	signed double-cell integer

<code>ud, du</code>	unsigned double-cell integer
<code>2</code>	two cells (not-necessarily double-cell numbers)
<code>m, um</code>	mixed single-cell and double-cell operations
<code>f</code>	floating-point (note that in stack comments ‘ <code>f</code> ’ represents flags, and ‘ <code>r</code> ’ represents FP numbers; also, you need to include the exponent part in literal FP numbers, see Section 3.26 [Floating Point Tutorial], page 27).

If there are no differences between the signed and the unsigned variant (e.g., for `+`), there is only the prefix-less variant.

Forth does not perform type checking, neither at compile time, nor at run time. If you use the wrong operation, the data are interpreted incorrectly:

```
-1 u.
```

If you have only experience with type-checked languages until now, and have heard how important type-checking is, don’t panic! In my experience (and that of other Forthers), type errors in Forth code are usually easy to find (once you get used to it), the increased vigilance of the programmer tends to catch some harder errors in addition to most type errors, and you never have to work around the type system, so in most situations the lack of type-checking seems to be a win (projects to add type checking to Forth have not caught on).

3.13 Factoring

If you try to write longer definitions, you will soon find it hard to keep track of the stack contents. Therefore, good Forth programmers tend to write only short definitions (e.g., three lines). The art of finding meaningful short definitions is known as factoring (as in factoring polynomials).

Well-factored programs offer additional advantages: smaller, more general words, are easier to test and debug and can be reused more and better than larger, specialized words.

So, if you run into difficulties with stack management, when writing code, try to define meaningful factors for the word, and define the word in terms of those. Even if a factor contains only two words, it is often helpful.

Good factoring is not easy, and it takes some practice to get the knack for it; but even experienced Forth programmers often don’t find the right solution right away, but only when rewriting the program. So, if you don’t come up with a good solution immediately, keep trying, don’t despair.

3.14 Designing the stack effect

In other languages you can use an arbitrary order of parameters for a function; and since there is only one result, you don’t have to deal with the order of results, either.

In Forth (and other stack-based languages, e.g., PostScript) the parameter and result order of a definition is important and should be designed well. The general guideline is to design the stack effect such that the word is simple to use in most cases, even if that complicates the implementation of the word. Some concrete rules are:

- Words consume all of their parameters (e.g., `.`).

- If there is a convention on the order of parameters (e.g., from mathematics or another programming language), stick with it (e.g., -).
- If one parameter usually requires only a short computation (e.g., it is a constant), pass it on the top of the stack. Conversely, parameters that usually require a long sequence of code to compute should be passed as the bottom (i.e., first) parameter. This makes the code easier to read, because the reader does not need to keep track of the bottom item through a long sequence of code (or, alternatively, through stack manipulations). E.g., `!` (store, see Section 6.7 [Memory], page 70) expects the address on top of the stack because it is usually simpler to compute than the stored value (often the address is just a variable).
- Similarly, results that are usually consumed quickly should be returned on the top of stack, whereas a result that is often used in long computations should be passed as bottom result. E.g., the file words like `open-file` return the error code on the top of stack, because it is usually consumed quickly by `throw`; moreover, the error code has to be checked before doing anything with the other results.

These rules are just general guidelines, don't lose sight of the overall goal to make the words easy to use. E.g., if the convention rule conflicts with the computation-length rule, you might decide in favour of the convention if the word will be used rarely, and in favour of the computation-length rule if the word will be used frequently (because with frequent use the cost of breaking the computation-length rule would be quite high, and frequent use makes it easier to remember an unconventional order).

3.15 Local Variables

You can define local variables (*locals*) in a colon definition:

```
: swap { a b -- b a }
  b a ;
1 2 swap .s 2drop
```

(If your Forth system does not support this syntax, include `compat/anslocal.fs` first).

In this example `{ a b -- b a }` is the locals definition; it takes two cells from the stack, puts the top of stack in `b` and the next stack element in `a`. `--` starts a comment ending with `}`. After the locals definition, using the name of the local will push its value on the stack. You can omit the comment part (`-- b a`):

```
: swap ( x1 x2 -- x2 x1 )
  { a b } b a ;
```

In Gforth you can have several locals definitions, anywhere in a colon definition; in contrast, in a standard program you can have only one locals definition per colon definition, and that locals definition must be outside any control structure.

With locals you can write slightly longer definitions without running into stack trouble. However, I recommend trying to write colon definitions without locals for exercise purposes to help you gain the essential factoring skills.

Assignment: Rewrite your definitions until now with locals

Reference: Section 6.22 [Locals], page 164.

3.16 Conditional execution

In Forth you can use control structures only inside colon definitions. An `if`-structure looks like this:

```
: abs ( n1 -- +n2 )
  dup 0 < if
    negate
  endif ;
5 abs .
-5 abs .
```

`if` takes a flag from the stack. If the flag is non-zero (true), the following code is performed, otherwise execution continues after the `endif` (or `else`). `<` compares the top two stack elements and produces a flag:

```
1 2 < .
2 1 < .
1 1 < .
```

Actually the standard name for `endif` is `then`. This tutorial presents the examples using `endif`, because this is often less confusing for people familiar with other programming languages where `then` has a different meaning. If your system does not have `endif`, define it with

```
: endif postpone then ; immediate
```

You can optionally use an `else`-part:

```
: min ( n1 n2 -- n )
  2dup < if
    drop
  else
    nip
  endif ;
2 3 min .
3 2 min .
```

Assignment: Write `min` without `else`-part (hint: what's the definition of `nip`?).

Reference: Section 6.9.1 [Selection], page 84.

3.17 Flags and Comparisons

In a false-flag all bits are clear (0 when interpreted as integer). In a canonical true-flag all bits are set (-1 as a twos-complement signed integer); in many contexts (e.g., `if`) any non-zero value is treated as true flag.

```
false .
true .
true hex u. decimal
```

Comparison words produce canonical flags:

```
1 1 = .
1 0= .
0 1 < .
```

```
0 0 < .
-1 1 u< . \ type error, u< interprets -1 as large unsigned number
-1 1 < .
```

Gforth supports all combinations of the prefixes `0 u d d0 du f f0` (or none) and the comparisons `= <> < > <= >=`. Only a part of these combinations are standard (for details see the standard, Section 6.5.7 [Numeric comparison], page 64, Section 6.5.8 [Floating Point], page 65, or [Word Index], page 303).

You can use `and` or `xor` `invert` as operations on canonical flags. Actually they are bitwise operations:

```
1 2 and .
1 2 or .
1 3 xor .
1 invert .
```

You can convert a zero/non-zero flag into a canonical flag with `0<>` (and complement it on the way with `0=`; indeed, it is more common to use `0=` instead of `invert` for canonical flags).

```
1 0= .
1 0<> .
```

While you can use `if` without `0<>` to test for zero/non-zero, you sometimes need to use `0<>` when combining zero/non-zero values with `and` or `xor` because of their bitwise nature. The simplest, least error-prone, and probably clearest way is to use `0<>` in all these cases, but in some cases you can use fewer `0<>`s. Here are some stack effects, where *fc* represents a canonical flag, and *fz* represents zero/non-zero (every *fc* also works as *fz*):

```
or ( fz1 fz2 -- fz3 )
and ( fz1 fc -- fz2 )
and ( fc fz1 -- fz2 )
```

So, if you see code like this:

```
( n1 n2 ) 0<> and if
```

This tests whether *n1* and *n2* are non-zero and if yes, performs the code after `if`; it treats *n1* as zero/non-zero and uses `0<>` to convert *n2* into a canonical flag; the `and` then produces an *fz*, which is consumed by the `if`.

You can use the all-bits-set feature of canonical flags and the bitwise operation of the Boolean operations to avoid `ifs`:

```
: foo ( n1 -- n2 )
  0= if
    14
  else
    0
  endif ;
0 foo .
1 foo .

: foo ( n1 -- n2 )
  0= 14 and ;
```

```
0 foo .
1 foo .
```

Assignment: Write `min` without `if`.

For reference, see Section 6.4 [Boolean Flags], page 56, Section 6.5.7 [Numeric comparison], page 64, and Section 6.5.6 [Bitwise operations], page 62.

3.18 General Loops

The endless loop is the most simple one:

```
: endless ( -- )
  0 begin
    dup . 1+
    again ;
endless
```

Terminate this loop by pressing *Ctrl-C* (in Gforth). `begin` does nothing at run-time, `again` jumps back to `begin`.

A loop with one exit at any place looks like this:

```
: log2 ( +n1 -- n2 )
\ logarithmus dualis of n1>0, rounded down to the next integer
assert( dup 0> )
2/ 0 begin
  over 0> while
    1+ swap 2/ swap
  repeat
  nip ;
7 log2 .
8 log2 .
```

At run-time `while` consumes a flag; if it is 0, execution continues behind the `repeat`; if the flag is non-zero, execution continues behind the `while`. `Repeat` jumps back to `begin`, just like `again`.

In Forth there are a number of combinations/abbreviations, like `1+`. However, `2/` is not one of them; it shifts its argument right by one bit (arithmetic shift right), and viewed as division that always rounds towards negative infinity (floored division), like Gforth's `/` (since Gforth 0.7), but unlike `/` in many other Forth systems.

```
-5 2 / . \ -2 or -3
-5 2/ . \ -3
```

`assert(` is no standard word, but you can get it on systems other than Gforth by including `compat/assert.fs`. You can see what it does by trying

```
0 log2 .
```

Here's a loop with an exit at the end:

```
: log2 ( +n1 -- n2 )
\ logarithmus dualis of n1>0, rounded down to the next integer
assert( dup 0 > )
-1 begin
```



```

    1+ swap 2/ swap
    over 0 <=
until
nip ;

```

Until consumes a flag; if it is zero, execution continues at the **begin**, otherwise after the **until**.

Assignment: Write a definition for computing the greatest common divisor.

Reference: Section 6.9.2 [Simple Loops], page 85.

3.19 Counted loops

```

: ^ ( n1 u -- n )
\ n = the uth power of n1
  1 swap 0 u+do
    over *
  loop
  nip ;
3 2 ^ .
4 3 ^ .

```

U+do (from `compat/loops.fs`, if your Forth system doesn't have it) takes two numbers of the stack (`u3 u4 --`), and then performs the code between **u+do** and **loop** for `u3-u4` times (or not at all, if `u3-u4<0`).

You can see the stack effect design rules at work in the stack effect of the loop start words: Since the start value of the loop is more frequently constant than the end value, the start value is passed on the top-of-stack.

You can access the counter of a counted loop with **i**:

```

: fac ( u -- u! )
  1 swap 1+ 1 u+do
    i *
  loop ;
5 fac .
7 fac .

```

There is also **+do**, which expects signed numbers (important for deciding whether to enter the loop).

Assignment: Write a definition for computing the *n*th Fibonacci number.

You can also use increments other than 1:

```

: up2 ( n1 n2 -- )
  +do
    i .
  2 +loop ;
10 0 up2

: down2 ( n1 n2 -- )
  -do
    i .

```

```

    2 -loop ;
0 10 down2

```

Reference: Section 6.9.3 [Counted Loops], page 86.

3.20 Recursion

Usually the name of a definition is not visible in the definition; but earlier definitions are usually visible:

```

1 0 / . \ "Floating-point unidentified fault" in Gforth on some platforms
: / ( n1 n2 -- n )
  dup 0= if
    -10 throw \ report division by zero
  endif
  /          \ old version
;
1 0 /

```

For recursive definitions you can use `recursive` (non-standard) or `recurse`:

```

: fac1 ( n -- n! ) recursive
  dup 0> if
    dup 1- fac1 *
  else
    drop 1
  endif ;
7 fac1 .

```

```

: fac2 ( n -- n! )
  dup 0> if
    dup 1- recurse *
  else
    drop 1
  endif ;
8 fac2 .

```

Assignment: Write a recursive definition for computing the *n*th Fibonacci number.

Reference (including indirect recursion): See Section 6.9.7 [Calls and returns], page 93.

3.21 Leaving definitions or loops

`EXIT` exits the current definition right away. For every counted loop that is left in this way, an `UNLOOP` has to be performed before the `EXIT`:

```

: ...
... u+do
... if
... unloop exit
endif
...

```

```

loop
... ;

```

LEAVE leaves the innermost counted loop right away:

```

: ...
... u+do
... if
... leave
endif
...
loop
... ;

```

Reference: Section 6.9.7 [Calls and returns], page 93, Section 6.9.3 [Counted Loops], page 86.

3.22 Return Stack

In addition to the data stack Forth also has a second stack, the return stack; most Forth systems store the return addresses of procedure calls there (thus its name). Programmers can also use this stack:

```

: foo ( n1 n2 -- )
.s
>r .s
r@ .
>r .s
r@ .
r> .
r@ .
r> . ;
1 2 foo

```

`>r` takes an element from the data stack and pushes it onto the return stack; conversely, `r>` moves an element from the return to the data stack; `r@` pushes a copy of the top of the return stack on the data stack.

Forth programmers usually use the return stack for storing data temporarily, if using the data stack alone would be too complex, and factoring and locals are not an option:

```

: 2swap ( x1 x2 x3 x4 -- x3 x4 x1 x2 )
rot >r rot r> ;

```

The return address of the definition and the loop control parameters of counted loops usually reside on the return stack, so you have to take all items, that you have pushed on the return stack in a colon definition or counted loop, from the return stack before the definition or loop ends. You cannot access items that you pushed on the return stack outside some definition or loop within the definition of loop.

If you miscount the return stack items, this usually ends in a crash:

```

: crash ( n -- )
>r ;
5 crash

```

You cannot mix using locals and using the return stack (according to the standard; Gforth has no problem). However, they solve the same problems, so this shouldn't be an issue.

Assignment: Can you rewrite any of the definitions you wrote until now in a better way using the return stack?

Reference: Section 6.6.3 [Return stack], page 69.

3.23 Memory

You can create a global variable `v` with

```
variable v ( -- addr )
```

`v` pushes the address of a cell in memory on the stack. This cell was reserved by `variable`. You can use `!` (store) to store values from the stack into this cell and `@` (fetch) to load the value from memory onto the stack:

```
v .
5 v ! .s
v @ .
```

You can see a raw dump of memory with `dump`:

```
v 1 cells .s dump
```

`Cells (n1 -- n2)` gives you the number of bytes (or, more generally, address units (aus)) that `n1 cells` occupy. You can also reserve more memory:

```
create v2 20 cells allot
v2 20 cells dump
```

creates a variable-like word `v2` and reserves 20 uninitialized cells; the address pushed by `v2` points to the start of these 20 cells (see Section 6.10.1 [CREATE], page 98). You can use address arithmetic to access these cells:

```
3 v2 5 cells + !
v2 20 cells dump
```

You can reserve and initialize memory with `,:`

```
create v3
  5 , 4 , 3 , 2 , 1 ,
v3 @ .
v3 cell+ @ .
v3 2 cells + @ .
v3 5 cells dump
```

Assignment: Write a definition `vsum (addr u -- n)` that computes the sum of `u` cells, with the first of these cells at `addr`, the next one at `addr cell+` etc.

The difference between `variable` and `create` is that `variable` allots a cell, and that you cannot allot additional memory to a variable in standard Forth.

You can also reserve memory without creating a new word:

```
here 10 cells allot .
here .
```

The first **here** pushes the start address of the memory area, the second **here** the address after the dictionary area. You should store the start address somewhere, or you will have a hard time finding the memory area again.

Allot manages dictionary memory. The dictionary memory contains the system's data structures for words etc. on Gforth and most other Forth systems. It is managed like a stack: You can free the memory that you have just **alloted** with

```
-10 cells allot
here .
```

Note that you cannot do this if you have created a new word in the meantime (because then your **alloted** memory is no longer on the top of the dictionary "stack").

Alternatively, you can use **allocate** and **free** which allow freeing memory in any order:

```
10 cells allocate throw .s
20 cells allocate throw .s
swap
free throw
free throw
```

The **throws** deal with errors (e.g., out of memory).

And there is also a garbage collector (<https://www.complang.tuwien.ac.at/forth/garbage-collection.zip>), which eliminates the need to **free** memory explicitly.

Reference: Section 6.7 [Memory], page 70.

3.24 Characters and Strings

On the stack characters take up a cell, like numbers. In memory they have their own size (one 8-bit byte on most systems), and therefore require their own words for memory access:

```
create v4
  104 c, 97 c, 108 c, 108 c, 111 c,
v4 4 chars + c@ .
v4 5 chars dump
```

The preferred representation of strings on the stack is **addr u-count**, where **addr** is the address of the first character and **u-count** is the number of characters in the string.

```
v4 5 type
```

You get a string constant with

```
s" hello, world" .s
type
```

Make sure you have a space between **s"** and the string; **s"** is a normal Forth word and must be delimited with white space (try what happens when you remove the space).

However, this interpretive use of **s"** is quite restricted: the string exists only until the next call of **s"** (some Forth systems keep more than one of these strings, but usually they still have a limited lifetime).

```
s" hello," s" world" .s
type
type
```

You can also use `s"` in a definition, and the resulting strings then live forever (well, for as long as the definition):

```
: foo s" hello," s" world" ;
foo .s
type
type
```

Assignment: `Emit (c --)` types `c` as character (not a number). Implement `type (addr u --)`.

Reference: Section 6.7.7 [Memory Blocks], page 77.

3.25 Alignment

On many processors cells have to be aligned in memory, if you want to access them with `@` and `!` (and even if the processor does not require alignment, access to aligned cells is faster).

`Create` aligns `here` (i.e., the place where the next allocation will occur, and that the `created` word points to). Likewise, the memory produced by `allocate` starts at an aligned address. Adding a number of `cells` to an aligned address produces another aligned address.

However, address arithmetic involving `char+` and `chars` can create an address that is not cell-aligned. `Aligned (addr -- a-addr)` produces the next aligned address:

```
v3 char+ aligned .s @ .
v3 char+ .s @ .
```

Similarly, `align` advances `here` to the next aligned address:

```
create v5 97 c,
here .
align here .
1000 ,
```

Note that you should use aligned addresses even if your processor does not require them, if you want your program to be portable.

Reference: Section 6.7.6 [Address arithmetic], page 75.

3.26 Floating Point

Floating-point (FP) numbers and arithmetic in Forth works mostly as one might expect, but there are a few things worth noting:

The first point is not specific to Forth, but so important and yet not universally known that I mention it here: FP numbers are not reals. Many properties (e.g., arithmetic laws) that reals have and that one expects of all kinds of numbers do not hold for FP numbers. If you want to use FP computations, you should learn about their problems and how to avoid them; a good starting point is *David Goldberg, What Every Computer Scientist Should Know About Floating-Point Arithmetic* (https://docs.oracle.com/cd/E19957-01/806-3568/ncg_goldberg.html), *ACM Computing Surveys* 23(1):5–48, March 1991.

In Forth source code literal FP numbers need an exponent, e.g., `1e0`; this can also be written shorter as `1e`, longer as `+1.0e+0`, and many variations in between. The reason

for this is that, for historical reasons, Forth interprets a decimal point alone (e.g., 1.) as indicating a double-cell integer. Examples:

```
2e 2e f+ f.
```

Another requirement for literal FP numbers is that the current base is decimal; with a hex base 1e is interpreted as an integer.

Forth has a separate stack for FP numbers in conformance with Forth-2012. One advantage of this model is that cells are not in the way when accessing FP values, and vice versa. Forth has a set of words for manipulating the FP stack: `fdup fswap fdrop fover frot` and (non-standard) `fnip ftuck fpick`.

FP arithmetic words are prefixed with `F`. There is the usual set `f+ f- f* f/ f** fnegate` as well as a number of words for other functions, e.g., `fsqrt fsin fln fmin`. One word that you might expect is `f=`; but `f=` is non-standard, because FP computation results are usually inaccurate, so exact comparison is usually a mistake, and one should use approximate comparison. Unfortunately, `f~`, the standard word for that purpose, is not well designed, so Gforth provides `f~abs` and `f~rel` as well.

And of course there are words for accessing FP numbers in memory (`f@ f!`), and for address arithmetic (`floats float+ faligned`). There are also variants of these words with an `sf` and `df` prefix for accessing IEEE format single-precision and double-precision numbers in memory; their main purpose is for accessing external FP data (e.g., that has been read from or will be written to a file).

Here is an example of a dot-product word and its use:

```
: v* ( f_addr1 nstride1 f_addr2 nstride2 ucount -- r )
  >r swap 2swap swap 0e r> 0 ?DO
    dup f@ over + 2swap dup f@ f* f+ over + 2swap
  LOOP
  2drop 2drop ;
```

```
create v 1.23e f, 4.56e f, 7.89e f,
```

```
v 1 floats v 1 floats 3 v* f.
```

Assignment: Write a program to solve a quadratic equation. Then read *Henry G. Baker, You Could Learn a Lot from a Quadratic* (<https://citeseerx.ist.psu.edu/viewdoc/download?doi=10.1.1.111.4448&rep=rep1&type=pdf>), *ACM SIGPLAN Notices*, 33(1):30–39, January 1998, and see if you can improve your program. Finally, find a test case where the original and the improved version produce different results.

Reference: Section 6.5.8 [Floating Point], page 65; Section 6.6.2 [Floating point stack], page 68; Section 6.14.2 [Number Conversion], page 128; Section 6.7.4 [Memory Access], page 72; Section 6.7.6 [Address arithmetic], page 75.

3.27 Files

This section gives a short introduction into how to use files inside Forth. It's broken up into five easy steps:

1. Open an ASCII text file for input

2. Open a file for output
3. Read input file until string matches (or some other condition is met)
4. Write some lines from input (modified or not) to output
5. Close the files.

Reference: Section 6.18.2 [General files], page 140.

3.27.1 Open file for input

```
s" foo.in"  r/o open-file throw Value fd-in
```

3.27.2 Create file for output

```
s" foo.out" w/o create-file throw Value fd-out
```

The available file modes are `r/o` for read-only access, `r/w` for read-write access, and `w/o` for write-only access. You could open both files with `r/w`, too, if you like. All file words return error codes; for most applications, it's best to pass there error codes with `throw` to the outer error handler.

If you want words for opening and assigning, define them as follows:

```
0 Value fd-in
0 Value fd-out
: open-input ( addr u -- )  r/o open-file throw to fd-in ;
: open-output ( addr u -- ) w/o create-file throw to fd-out ;
```

Usage example:

```
s" foo.in" open-input
s" foo.out" open-output
```

3.27.3 Scan file for a particular line

```
256 Constant max-line
Create line-buffer  max-line 2 + allot
```

```
: scan-file ( addr u -- )
  begin
    line-buffer max-line fd-in read-line throw
  while
    >r 2dup line-buffer r> compare 0=
  until
  else
    drop
  then
  2drop ;
```

`read-line (addr u1 fd -- u2 flag ior)` reads up to `u1` bytes into the buffer at `addr`, and returns the number of bytes read, a flag that is false when the end of file is reached, and an error code.

`compare (addr1 u1 addr2 u2 -- n)` compares two strings and returns zero if both strings are equal. It returns a positive number if the first string is lexically greater, a negative if the second string is lexically greater.

We haven't seen this loop here; it has two exits. Since the **while** exits with the number of bytes read on the stack, we have to clean up that separately; that's after the **else**.

Usage example:

```
s" The text I search is here" scan-file
```

3.27.4 Copy input to output

```
: copy-file ( -- )
  begin
    line-buffer max-line fd-in read-line throw
  while
    line-buffer swap fd-out write-line throw
  repeat
  drop ;
```

3.27.5 Close files

```
fd-in close-file throw
fd-out close-file throw
```

Likewise, you can put that into definitions, too:

```
: close-input ( -- ) fd-in close-file throw ;
: close-output ( -- ) fd-out close-file throw ;
```

Assignment: How could you modify **copy-file** so that it copies until a second line is matched? Can you write a program that extracts a section of a text file, given the line that starts and the line that terminates that section?

3.28 Interpretation and Compilation Semantics and Immediacy

When a word is compiled, it behaves differently from being interpreted. E.g., consider **+**:

```
1 2 + .
: foo + ;
```

These two behaviours are known as compilation and interpretation semantics. For normal words (e.g., **+**), the compilation semantics is to append the interpretation semantics to the currently defined word (**foo** in the example above). I.e., when **foo** is executed later, the interpretation semantics of **+** (i.e., adding two numbers) will be performed.

However, there are words with non-default compilation semantics, e.g., the control-flow words like **if**. You can use **immediate** to change the compilation semantics of the last defined word to be equal to the interpretation semantics:

```
: [F00] ( -- )
  5 . ; immediate

[F00]
: bar ( -- )
  [F00] ;
bar
see bar
```

Two conventions to mark words with non-default compilation semantics are names with brackets (more frequently used) and to write them all in upper case (less frequently used).

For some words, such as `if`, using their interpretation semantics is usually a mistake, so we mark them as `compile-only`, and you get a warning when you interpret them.

```
: flip ( -- )
  6 . ; compile-only \ but not immediate
flip

: flop ( -- )
  flip ;
flop
```

In this example, first the interpretation semantics of `flip` is used (and you get a warning); the second use of `flip` uses the compilation semantics (and you get no warning). You can also see in this example that `compile-only` is a property that is evaluated at text interpretation time, not at run-time.

The text interpreter has two states: in interpret state, it performs the interpretation semantics of words it encounters; in compile state, it performs the compilation semantics of these words.

Among other things, `:` switches into compile state, and `;` switches back to interpret state. They contain the factors `]` (switch to compile state) and `[` (switch to interpret state), that do nothing but switch the state.

```
: xxx ( -- )
  [ 5 . ]
;

xxx
see xxx
```

These brackets are also the source of the naming convention mentioned above.

Reference: Section 6.11 [Interpretation and Compilation Semantics], page 115.

3.29 Execution Tokens

`' word` gives you the execution token (XT) of a word. The XT is a cell representing the interpretation semantics of a word. You can execute this semantics with `execute`:

```
' + .s
1 2 rot execute .
```

The XT is similar to a function pointer in C. However, parameter passing through the stack makes it a little more flexible:

```
: map-array ( ... addr u xt -- ... )
\ executes xt ( ... x -- ... ) for every element of the array starting
\ at addr and containing u elements
{ xt }
cells over + swap ?do
  i @ xt execute
1 cells +loop ;
```

```

create a 3 , 4 , 2 , -1 , 4 ,
a 5 ' . map-array .s
0 a 5 ' + map-array .
s" max-n" environment? drop .s
a 5 ' min map-array .

```

You can use `map-array` with the XTs of words that consume one element more than they produce. In theory you can also use it with other XTs, but the stack effect then depends on the size of the array, which is hard to understand.

Since XTs are cell-sized, you can store them in memory and manipulate them on the stack like other cells. You can also compile the XT into a word with `compile,:`

```

: foo1 ( n1 n2 -- n )
  [ ' + compile, ] ;
see foo1

```

This is non-standard, because `compile,` has no compilation semantics in the standard, but it works in good Forth systems. For the broken ones, use

```

: [compile,] compile, ; immediate

: foo1 ( n1 n2 -- n )
  [ ' + ] [compile,] ;
see foo1

```

`'` is a word with default compilation semantics; it parses the next word when its interpretation semantics are executed, not during compilation:

```

: foo ( -- xt )
  ' ;
see foo
: bar ( ... "word" -- ... )
  ' execute ;
see bar
1 2 bar + .

```

You often want to parse a word during compilation and compile its XT so it will be pushed on the stack at run-time. `[']` does this:

```

: xt-+ ( -- xt )
  ['] + ;
see xt-+
1 2 xt-+ execute .

```

Many programmers tend to see `'` and the word it parses as one unit, and expect it to behave like `[']` when compiled, and are confused by the actual behaviour. If you are, just remember that the Forth system just takes `'` as one unit and has no idea that it is a parsing word (attempts to convenience programmers in this issue have usually resulted in even worse pitfalls, see *State-smartness—Why it is evil and How to Exorcise it* (<https://www.complang.tuwien.ac.at/papers/ert198.ps.gz>)).

Note that the state of the interpreter does not come into play when creating and executing XTs. I.e., even when you execute `'` in compile state, it still gives you the interpretation

semantics. And whatever that state is, **execute** performs the semantics represented by the XT (i.e., for XTs produced with ' the interpretation semantics).

Reference: Section 6.12 [Tokens for Words], page 117.

3.30 Exceptions

throw (*n* --) causes an exception unless *n* is zero.

```
100 throw .s
0 throw .s
```

catch (... *xt* -- ... *n*) behaves similar to **execute**, but it catches exceptions and pushes the number of the exception on the stack (or 0, if the *xt* executed without exception). If there was an exception, the stacks have the same depth as when entering **catch**:

```
.s
3 0 ' / catch .s
3 2 ' / catch .s
```

Assignment: Try the same with **execute** instead of **catch**.

Throw always jumps to the dynamically next enclosing **catch**, even if it has to leave several call levels to achieve this:

```
: foo 100 throw ;
: foo1 foo ." after foo" ;
: bar ['] foo1 catch ;
bar .
```

It is often important to restore a value upon leaving a definition, even if the definition is left through an exception. You can ensure this like this:

```
: ...
  save-x
  ['] word-changing-x catch ( ... n )
  restore-x
  ( ... n ) throw ;
```

However, this is still not safe against, e.g., the user pressing **Ctrl-C** when execution is between the **catch** and **restore-x**.

Gforth provides an alternative exception handling syntax that is safe against such cases: **try** ... **restore** ... **endtry**. If the code between **try** and **endtry** has an exception, the stack depths are restored, the exception number is pushed on the stack, and the execution continues right after **restore**.

The safer equivalent to the restoration code above is

```
: ...
  save-x
  try
    word-changing-x 0
  restore
  restore-x
endtry
throw ;
```

Reference: Section 6.9.8 [Exception Handling], page 94.

3.31 Defining Words

`:`, `create`, and `variable` are definition words: They define other words. `constant` is another definition word:

```
5 constant foo
foo .
```

You can also use the prefixes `2` (double-cell) and `f` (floating point) with `variable` and `constant`.

You can also define your own defining words. E.g.:

```
: variable ( "name" -- )
  create 0 , ;
```

You can also define defining words that create words that do something other than just producing their address:

```
: constant ( n "name" -- )
  create ,
does> ( -- n )
  ( addr ) @ ;
```

```
5 constant foo
foo .
```

The definition of `constant` above ends at the `does>`; i.e., `does>` replaces `;`, but it also does something else: It changes the last defined word such that it pushes the address of the body of the word and then performs the code after the `does>` whenever it is called.

In the example above, `constant` uses `,` to store 5 into the body of `foo`. When `foo` executes, it pushes the address of the body onto the stack, then (in the code after the `does>`) fetches the 5 from there.

The stack comment near the `does>` reflects the stack effect of the defined word, not the stack effect of the code after the `does>` (the difference is that the code expects the address of the body that the stack comment does not show).

You can use these definition words to do factoring in cases that involve (other) definition words. E.g., a field offset is always added to an address. Instead of defining

```
2 cells constant offset-field1
```

and using this like

```
( addr ) offset-field1 +
```

you can define a definition word

```
: simple-field ( n "name" -- )
  create ,
does> ( n1 -- n1+n )
  ( addr ) @ + ;
```

Definition and use of field offsets now look like this:

```
2 cells simple-field field1
create mystruct 4 cells allot
mystruct .s field1 .s drop
```

If you want to do something with the word without performing the code after the `does>`, you can access the body of a created word with `>body (xt -- addr)`:

```
: value ( n "name" -- )
  create ,
does> ( -- n1 )
  @ ;
: to ( n "name" -- )
  ' >body ! ;
```

```
5 value foo
foo .
7 to foo
foo .
```

Assignment: Define `defer ("name" --)`, which creates a word that stores an XT (at the start the XT of `abort`), and upon execution **executes** the XT. Define `is (xt "name" --)` that stores `xt` into `name`, a word defined with `defer`. Indirect recursion is one application of `defer`.

Reference: Section 6.10.9 [User-defined Defining Words], page 102.

3.32 Arrays and Records

Forth has no standard words for defining arrays, but you can build them yourself based on address arithmetic. You can also define words for defining arrays and records (see Section 3.31 [Defining Words], page 34).

One of the first projects a Forth newcomer sets out upon when learning about defining words is an array defining word (possibly for n-dimensional arrays). Go ahead and do it, I did it, too; you will learn something from it. However, don't be disappointed when you later learn that you have little use for these words (inappropriate use would be even worse). I have not found a set of useful array words yet; the needs are just too diverse, and named, global arrays (the result of naive use of defining words) are often not flexible enough (e.g., consider how to pass them as parameters). Another such project is a set of words to help dealing with strings.

On the other hand, there is a useful set of record words, and it has been defined in `compat/struct.fs`; these words are predefined in Gforth. They are explained in depth elsewhere in this manual (see see Section 6.23 [Structures], page 173). The `simple-field` example above is simplified variant of fields in this package.

3.33 POSTPONE

You can compile the compilation semantics (instead of compiling the interpretation semantics) of a word with `POSTPONE`:

```
: MY-+ ( Compilation: -- ; Run-time of compiled code: n1 n2 -- n )
  POSTPONE + ; immediate
: foo ( n1 n2 -- n )
  MY-+ ;
1 2 foo .
```

```
see foo
```

During the definition of `foo` the text interpreter performs the compilation semantics of `MY++`, which performs the compilation semantics of `+`, i.e., it compiles `+` into `foo`.

This example also displays separate stack comments for the compilation semantics and for the stack effect of the compiled code. For words with default compilation semantics these stack effects are usually not displayed; the stack effect of the compilation semantics is always `(--)` for these words, the stack effect for the compiled code is the stack effect of the interpretation semantics.

Note that the state of the interpreter does not come into play when performing the compilation semantics in this way. You can also perform it interpretively, e.g.:

```
: foo2 ( n1 n2 -- n )
  [ MY++ ] ;
1 2 foo .
see foo
```

However, there are some broken Forth systems where this does not always work, and therefore this practice was been declared non-standard in 1999.

Here is another example for using `POSTPONE`:

```
: MY-- ( Compilation: -- ; Run-time of compiled code: n1 n2 -- n )
  POSTPONE negate POSTPONE + ; immediate compile-only
: bar ( n1 n2 -- n )
  MY-- ;
2 1 bar .
see bar
```

You can define `ENDIF` in this way:

```
: ENDIF ( Compilation: orig -- )
  POSTPONE then ; immediate
```

Assignment: Write `MY-2DUP` that has compilation semantics equivalent to `2dup`, but compiles `over over`.

3.34 Literal

You cannot `POSTPONE` numbers:

```
: [FOO] POSTPONE 500 ; immediate
```

Instead, you can use `LITERAL` (compilation: `n --`; run-time: `-- n`):

```
: [FOO] ( compilation: --; run-time: -- n )
  500 POSTPONE literal ; immediate
```

```
: flip [FOO] ;
flip .
see flip
```

`LITERAL` consumes a number at compile-time (when it's compilation semantics are executed) and pushes it at run-time (when the code it compiled is executed). A frequent use of `LITERAL` is to compile a number computed at compile time into the current word:

```
: bar ( -- n )
```

```

    [ 2 2 + ] literal ;
see bar

```

Assignment: Write]L which allows writing the example above as : bar (-- n) [2 2 +]L ;

3.35 Advanced macros

Reconsider map-array from Section 3.29 [Execution Tokens], page 31. It frequently performs `execute`, a relatively expensive operation in some Forth implementations. You can use `compile`, and `POSTPONE` to eliminate these `executes` and produce a word that contains the word to be performed directly:

```

: compile-map-array ( compilation: xt -- ; run-time: ... addr u -- ... )
\ at run-time, execute xt ( ... x -- ... ) for each element of the
\ array beginning at addr and containing u elements
{ xt }
POSTPONE cells POSTPONE over POSTPONE + POSTPONE swap POSTPONE ?do
  POSTPONE i POSTPONE @ xt compile,
  1 cells POSTPONE literal POSTPONE +loop ;

: sum-array ( addr u -- n )
  0 rot rot [ ' + compile-map-array ] ;
see sum-array
a 5 sum-array .

```

You can use the full power of Forth for generating the code; here's an example where the code is generated in a loop:

```

: compile-vmul-step ( compilation: n --; run-time: n1 addr1 -- n2 addr2 )
\ n2=n1+(addr1)*n, addr2=addr1+cell
  POSTPONE tuck POSTPONE @
  POSTPONE literal POSTPONE * POSTPONE +
  POSTPONE swap POSTPONE cell+ ;

: compile-vmul ( compilation: addr1 u -- ; run-time: addr2 -- n )
\ n=v1*v2 (inner product), where the v_i are represented as addr_i u
  0 postpone literal postpone swap
  [ ' compile-vmul-step compile-map-array ]
  postpone drop ;
see compile-vmul

: a-vmul ( addr -- n )
\ n=a*v, where v is a vector that's as long as a and starts at addr
  [ a 5 compile-vmul ] ;
see a-vmul
a a-vmul .

```

This example uses `compile-map-array` to show off, but you could also use `map-array` instead (try it now!).

You can use this technique for efficient multiplication of large matrices. In matrix multiplication, you multiply every row of one matrix with every column of the other matrix. You can generate the code for one row once, and use it for every column. The only downside of this technique is that it is cumbersome to recover the memory consumed by the generated code when you are done (and in more complicated cases it is not possible portably).

3.36 Compilation Tokens

This section is Gforth-specific. You can skip it.

' **word compile**, compiles the interpretation semantics. For words with default compilation semantics this is the same as performing the compilation semantics. To represent the compilation semantics of other words (e.g., words like **if** that have no interpretation semantics), Gforth has the concept of a compilation token (CT, consisting of two cells), and words **comp'** and **[comp']**. You can perform the compilation semantics represented by a CT with **execute**:

```
: foo2 ( n1 n2 -- n )
  [ comp' + execute ] ;
see foo
```

You can compile the compilation semantics represented by a CT with **postpone,:**

```
: foo3 ( -- )
  [ comp' + postpone, ] ;
see foo3
```

[comp' word postpone,] is equivalent to **POSTPONE word**. **comp'** is particularly useful for words that have no interpretation semantics:

```
' if
comp' if .s 2drop
```

Reference: Section 6.12 [Tokens for Words], page 117.

3.37 Wordlists and Search Order

The dictionary is not just a memory area that allows you to allocate memory with **allot**, it also contains the Forth words, arranged in several wordlists. When searching for a word in a wordlist, conceptually you start searching at the youngest and proceed towards older words (in reality most systems nowadays use hash-tables); i.e., if you define a word with the same name as an older word, the new word shadows the older word.

Which wordlists are searched in which order is determined by the search order. You can display the search order with **order**. It displays first the search order, starting with the wordlist searched first, then it displays the wordlist that will contain newly defined words.

You can create a new, empty wordlist with **wordlist (-- wid)**:

```
wordlist constant mywords
```

Set-current (wid --) sets the wordlist that will contain newly defined words (the *current* wordlist):

```
mywords set-current
order
```

Gforth does not display a name for the wordlist in `mywords` because this wordlist was created anonymously with `wordlist`.

You can get the current wordlist with `get-current (-- wid)`. If you want to put something into a specific wordlist without overall effect on the current wordlist, this typically looks like this:

```
get-current mywords set-current ( wid )
create someword
( wid ) set-current
```

You can write the search order with `set-order (wid1 .. widn n --)` and read it with `get-order (-- wid1 .. widn n)`. The first searched wordlist is topmost.

```
get-order mywords swap 1+ set-order
order
```

Yes, the order of wordlists in the output of `order` is reversed from stack comments and the output of `.s` and thus unintuitive.

Assignment: Define `>order (wid --)` which adds `wid` as first searched wordlist to the search order. Define `previous (--)`, which removes the first searched wordlist from the search order. Experiment with boundary conditions (you will see some crashes or situations that are hard or impossible to leave).

The search order is a powerful foundation for providing features similar to Modula-2 modules and C++ namespaces. However, trying to modularize programs in this way has disadvantages for debugging and reuse/factoring that overcome the advantages in my experience (I don't do huge projects, though). These disadvantages are not so clear in other languages/programming environments, because these languages are not so strong in debugging and reuse.

Reference: Section 6.16 [Word Lists], page 133.

4 An Introduction to Standard Forth

The difference of this chapter from the Tutorial (see Chapter 3 [Tutorial], page 11) is that it is slower-paced in its examples, but uses them to dive deep into explaining Forth internals (not covered by the Tutorial). Apart from that, this chapter covers far less material. It is suitable for reading without using a computer.

The primary purpose of this manual is to document Gforth. However, since Forth is not a widely-known language and there is a lack of up-to-date teaching material, it seems worthwhile to provide some introductory material. For other sources of Forth-related information, see Appendix C [Forth-related information], page 284.

The examples in this section should work on any Standard Forth; the output shown was produced using Gforth. Each example attempts to reproduce the exact output that Gforth produces. If you try out the examples (and you should), what you should type is shown *like this* and Gforth's response is shown *like this*. The single exception is that, where the example shows RET it means that you should press the “carriage return” key. Unfortunately, some output formats for this manual cannot show the difference between *this* and *this* which will make trying out the examples harder (but not impossible).

Forth is an unusual language. It provides an interactive development environment which includes both an interpreter and compiler. Forth programming style encourages you to break a problem down into many small fragments (*factoring*), and then to develop and test each fragment interactively. Forth advocates assert that breaking the edit-compile-test cycle used by conventional programming languages can lead to great productivity improvements.

4.1 Introducing the Text Interpreter

When you invoke the Forth image, you will see a startup banner printed and nothing else (if you have Gforth installed on your system, try invoking it now, by typing *gforth*RET). Forth is now running its command line interpreter, which is called the *Text Interpreter* (also known as the *Outer Interpreter*). (You will learn a lot about the text interpreter as you read through this chapter, for more detail see Section 6.14 [The Text Interpreter], page 125).

Although it's not obvious, Forth is actually waiting for your input. Type a number and press the RET key:

```
45RET  ok
```

Rather than give you a prompt to invite you to input something, the text interpreter prints a status message *after* it has processed a line of input. The status message in this case (“ok” followed by carriage-return) indicates that the text interpreter was able to process all of your input successfully. Now type something illegal:

```
qwer341RET
*the terminal*:2: Undefined word
>>>qwer341<<<
Backtrace:
$2A95B42A20 throw
$2A95B57FB8 no.extensions
```

The exact text, other than the “Undefined word” may differ slightly on your system, but the effect is the same; when the text interpreter detects an error, it discards any remaining

text on a line, resets certain internal state and prints an error message. For a detailed description of error messages see Chapter 7 [Error messages], page 237.

The text interpreter waits for you to press carriage-return, and then processes your input line. Starting at the beginning of the line, it breaks the line into groups of characters separated by spaces. For each group of characters in turn, it makes two attempts to do something:

- It tries to treat it as a command. It does this by searching a *name dictionary*. If the group of characters matches an entry in the name dictionary, the name dictionary provides the text interpreter with information that allows the text interpreter to perform some actions. In Forth jargon, we say that the group of characters names a *word*, that the dictionary search returns an *execution token* (*xt*) corresponding to the *definition* of the word, and that the text interpreter executes the *xt*. Often, the terms *word* and *definition* are used interchangeably.
- If the text interpreter fails to find a match in the name dictionary, it tries to treat the group of characters as a number in the current number base (when you start up Forth, the current number base is base 10). If the group of characters legitimately represents a number, the text interpreter pushes the number onto a stack (we'll learn more about that in the next section).

If the text interpreter is unable to do either of these things with any group of characters, it discards the group of characters and the rest of the line, then prints an error message. If the text interpreter reaches the end of the line without error, it prints the status message “ok” followed by carriage-return.

This is the simplest command we can give to the text interpreter:

```
RET ok
```

The text interpreter did everything we asked it to do (nothing) without an error, so it said that everything is “ok”. Try a slightly longer command:

```
12 dup fred dupRET
*the terminal*:3: Undefined word
12 dup >>>fred<<< dup
Backtrace:
$2A95B42A20 throw
$2A95B57FB8 no.extensions
```

When you press the carriage-return key, the text interpreter starts to work its way along the line:

- When it gets to the space after the 2, it takes the group of characters 12 and looks them up in the name dictionary¹. There is no match for this group of characters in the name dictionary, so it tries to treat them as a number. It is able to do this successfully, so it puts the number, 12, “on the stack” (whatever that means).
- The text interpreter resumes scanning the line and gets the next group of characters, *dup*. It looks it up in the name dictionary and (you'll have to take my word for this) finds it, and executes the word *dup* (whatever that means).

¹ We can't tell if it found them or not, but assume for now that it did not

- Once again, the text interpreter resumes scanning the line and gets the group of characters `fred`. It looks them up in the name dictionary, but can't find them. It tries to treat them as a number, but they don't represent any legal number.

At this point, the text interpreter gives up and prints an error message. The error message shows exactly how far the text interpreter got in processing the line. In particular, it shows that the text interpreter made no attempt to do anything with the final character group, `dup`, even though we have good reason to believe that the text interpreter would have no problem looking that word up and executing it a second time.

4.2 Stacks, postfix notation and parameter passing

In procedural programming languages (like C and Pascal), the building-block of programs is the *function* or *procedure*. These functions or procedures are called with *explicit parameters*. For example, in C we might write:

```
total = total + new_volume(length,height,depth);
```

where `new_volume` is a function-call to another piece of code, and `total`, `length`, `height` and `depth` are all variables. `length`, `height` and `depth` are parameters to the function-call.

In Forth, the equivalent of the function or procedure is the *definition* and parameters are implicitly passed between definitions using a shared stack that is visible to the programmer. Although Forth does support variables, the existence of the stack means that they are used far less often than in most other programming languages. When the text interpreter encounters a number, it will place (*push*) it on the stack. There are several stacks (the actual number is implementation-dependent ...) and the particular stack used for any operation is implied unambiguously by the operation being performed. The stack used for all integer operations is called the *data stack* and, since this is the stack used most commonly, references to “the data stack” are often abbreviated to “the stack”.

The stacks have a last-in, first-out (LIFO) organisation. If you type:

```
1 2 3RET ok
```

Then this instructs the text interpreter to place three numbers on the (data) stack. An analogy for the behaviour of the stack is to take a pack of playing cards and deal out the ace (1), 2 and 3 into a pile on the table. The 3 was the last card onto the pile (“last-in”) and if you take a card off the pile then, unless you're prepared to fiddle a bit, the card that you take off will be the 3 (“first-out”). The number that will be first-out of the stack is called the *top of stack*, which is often abbreviated to *TOS*.

To understand how parameters are passed in Forth, consider the behaviour of the definition `+` (pronounced “plus”). You will not be surprised to learn that this definition performs addition. More precisely, it adds two numbers together and produces a result. Where does it get the two numbers from? It takes the top two numbers off the stack. Where does it place the result? On the stack. You can act out the behaviour of `+` with your playing cards like this:

- Pick up two cards from the stack on the table
- Stare at them intently and ask yourself “what *is* the sum of these two numbers”
- Decide that the answer is 5
- Shuffle the two cards back into the pack and find a 5

- Put a 5 on the remaining ace that's on the table.

If you don't have a pack of cards handy but you do have Forth running, you can use the definition `.s` to show the current state of the stack, without affecting the stack. Type:

```
clearstacks 1 2 3RET ok
.sRET <3> 1 2 3 ok
```

The text interpreter looks up the word `clearstacks` and executes it; it tidies up the stacks (data and floating point stack) and removes any entries that may have been left on them by earlier examples. The text interpreter pushes each of the three numbers in turn onto the stack. Finally, the text interpreter looks up the word `.s` and executes it. The effect of executing `.s` is to print the “<3>” (the total number of items on the stack) followed by a list of all the items on the stack; the item on the far right-hand side is the TOS.

You can now type:

```
+ .sRET <2> 1 5 ok
```

which is correct; there are now 2 items on the stack and the result of the addition is 5.

If you're playing with cards, try doing a second addition: pick up the two cards, work out that their sum is 6, shuffle them into the pack, look for a 6 and place that on the table. You now have just one item on the stack. What happens if you try to do a third addition? Pick up the first card, pick up the second card – ah! There is no second card. This is called a *stack underflow* and constitutes an error. If you try to do the same thing with Forth it often reports an error (probably a Stack Underflow or an Invalid Memory Address error).

The opposite situation to a stack underflow is a *stack overflow*, which simply accepts that there is a finite amount of storage space reserved for the stack. To stretch the playing card analogy, if you had enough packs of cards and you piled the cards up on the table, you would eventually be unable to add another card; you'd hit the ceiling. Gforth allows you to set the maximum size of the stacks. In general, the only time that you will get a stack overflow is because a definition has a bug in it and is generating data on the stack uncontrollably.

There's one final use for the playing card analogy. If you model your stack using a pack of playing cards, the maximum number of items on your stack will be 52 (I assume you didn't use the Joker). The maximum *value* of any item on the stack is 13 (the King). In fact, the only possible numbers are positive integer numbers 1 through 13; you can't have (for example) 0 or 27 or 3.52 or -2. If you change the way you think about some of the cards, you can accommodate different numbers. For example, you could think of the Jack as representing 0, the Queen as representing -1 and the King as representing -2. Your *range* remains unchanged (you can still only represent a total of 13 numbers) but the numbers that you can represent are -2 through 10.

In that analogy, the limit was the amount of information that a single stack entry could hold, and Forth has a similar limit. In Forth, the size of a stack entry is called a *cell*. The actual size of a cell is implementation dependent and affects the maximum value that a stack entry can hold. A Standard Forth provides a cell size of at least 16-bits, and most desktop systems use a cell size of 32-bits.

Forth does not do any type checking for you, so you are free to manipulate and combine stack items in any way you wish. A convenient way of treating stack items is as 2's complement signed integers, and that is what Standard words like `+` do. Therefore you can type:

```
-5 12 + .sRET <1> 7 ok
```

If you use numbers and definitions like `+` in order to turn Forth into a great big pocket calculator, you will realise that it's rather different from a normal calculator. Rather than typing `2 + 3 =` you had to type `2 3 +` (ignore the fact that you had to use `.s` to see the result). The terminology used to describe this difference is to say that your calculator uses *Infix Notation* (parameters and operators are mixed) whilst Forth uses *Postfix Notation* (parameters and operators are separate), also called *Reverse Polish Notation*.

Whilst postfix notation might look confusing to begin with, it has several important advantages:

- it is unambiguous
- it is more concise
- it fits naturally with a stack-based system

To examine these claims in more detail, consider these sums:

```
6 + 5 * 4 =
4 * 5 + 6 =
```

If you're just learning maths or your maths is very rusty, you will probably come up with the answer 44 for the first and 26 for the second. If you are a bit of a whizz at maths you will remember the *convention* that multiplication takes precedence over addition, and you'd come up with the answer 26 both times. To explain the answer 26 to someone who got the answer 44, you'd probably rewrite the first sum like this:

```
6 + (5 * 4) =
```

If what you really wanted was to perform the addition before the multiplication, you would have to use parentheses to force it.

If you did the first two sums on a pocket calculator you would probably get the right answers, unless you were very cautious and entered them using these keystroke sequences:

```
6 + 5 = * 4 = 4 * 5 = + 6 =
```

Postfix notation is unambiguous because the order that the operators are applied is always explicit; that also means that parentheses are never required. The operators are *active* (the act of quoting the operator makes the operation occur) which removes the need for “=”.

The sum `6 + 5 * 4` can be written (in postfix notation) in two equivalent ways:

```
6 5 4 * +      or:
5 4 * 6 +
```

An important thing that you should notice about this notation is that the *order* of the numbers does not change; if you want to subtract 2 from 10 you type `10 2 -`.

The reason that Forth uses postfix notation is very simple to explain: it makes the implementation extremely simple, and it follows naturally from using the stack as a mechanism for passing parameters. Another way of thinking about this is to realise that all Forth definitions are *active*; they execute as they are encountered by the text interpreter. The result of this is that the syntax of Forth is trivially simple.

4.3 Your first Forth definition

Until now, the examples we've seen have been trivial; we've just been using Forth as a bigger-than-pocket calculator. Also, each calculation we've shown has been a "one-off" – to repeat it we'd need to type it in again² In this section we'll see how to add new words to Forth's vocabulary.

The easiest way to create a new word is to use a *colon definition*. We'll define a few and try them out before worrying too much about how they work. Try typing in these examples; be careful to copy the spaces accurately:

```
: add-two 2 + . ;
: greet ." Hello and welcome" ;
: demo 5 add-two ;
```

Now try them out:

```
greetRET Hello and welcome ok
greet greetRET Hello and welcomeHello and welcome ok
4 add-twoRET 6 ok
demoRET 7 ok
9 greet demo add-twoRET Hello and welcome7 11 ok
```

The first new thing that we've introduced here is the pair of words `:` and `;`. These are used to start and terminate a new definition, respectively. The first word after the `:` is the name for the new definition.

As you can see from the examples, a definition is built up of words that have already been defined; Forth makes no distinction between definitions that existed when you started the system up, and those that you define yourself.

The examples also introduce the words `.` (dot), `."` (dot-quote) and `dup` (dewp). Dot takes the value from the top of the stack and displays it. It's like `.s` except that it only displays the top item of the stack and it is destructive; after it has executed, the number is no longer on the stack. There is always one space printed after the number, and no spaces before it. Dot-quote defines a string (a sequence of characters) that will be printed when the word is executed. The string can contain any printable characters except `"`. A `"` has a special function; it is not a Forth word but it acts as a delimiter (the way that delimiters work is described in the next section). Finally, `dup` duplicates the value at the top of the stack. Try typing `5 dup .s` to see what it does.

We already know that the text interpreter searches through the dictionary to locate names. If you've followed the examples earlier, you will already have a definition called `add-two`. Lets try modifying it by typing in a new definition:

```
: add-two dup . ." + 2 = " 2 + . ;RET redefined add-two ok
```

Forth recognised that we were defining a word that already exists, and printed a message to warn us of that fact. Let's try out the new definition:

```
9 add-twoRET 9 + 2 = 11 ok
```

All that we've actually done here, though, is to create a new definition, with a particular name. The fact that there was already a definition with the same name did not make

² That's not quite true. If you press the up-arrow key on your keyboard you should be able to scroll back to any earlier command, edit it and re-enter it.

any difference to the way that the new definition was created (except that Forth printed a warning message). The old definition of `add-two` still exists (try `demo` again to see that this is true). Any new definition will use the new definition of `add-two`, but old definitions continue to use the version that already existed at the time that they were `compiled`.

Before you go on to the next section, try defining and redefining some words of your own.

4.4 How does that work?

Now we're going to take another look at the definition of `add-two` from the previous section. From our knowledge of the way that the text interpreter works, we would have expected this result when we tried to define `add-two`:

```
: add-two 2 + . ;RET
*the terminal*:4: Undefined word
: >>>add-two<<< 2 + . ;
```

The reason that this didn't happen is bound up in the way that `:` works. The word `:` does two special things. The first special thing that it does is to prevent the text interpreter from ever seeing the characters `add-two`. The text interpreter uses a variable called `>IN` (pronounced "to-in") to keep track of where it is in the input line. When it encounters the word `:` it behaves in exactly the same way as it does for any other word; it looks it up in the name dictionary, finds its `xt` and executes it. When `:` executes, it looks at the input buffer, finds the word `add-two` and advances the value of `>IN` to point past it. It then does some other stuff associated with creating the new definition (including creating an entry for `add-two` in the name dictionary). When the execution of `:` completes, control returns to the text interpreter, which is oblivious to the fact that it has been tricked into ignoring part of the input line.

Words like `:` – words that advance the value of `>IN` and so prevent the text interpreter from acting on the whole of the input line – are called *parsing words*.

The second special thing that `:` does is change the value of a variable called `state`, which affects the way that the text interpreter behaves. When Gforth starts up, `state` has the value 0, and the text interpreter is said to be *interpreting*. During a colon definition (started with `:`), `state` is set to -1 and the text interpreter is said to be *compiling*.

In this example, the text interpreter is compiling when it processes the string `"2 + . ;"`. It still breaks the string down into character sequences in the same way. However, instead of pushing the number 2 onto the stack, it lays down (*compiles*) some magic into the definition of `add-two` that will make the number 2 get pushed onto the stack when `add-two` is *executed*. Similarly, the behaviours of `+` and `.` are also compiled into the definition.

Certain kinds of words do not get compiled. These so-called *immediate words* get executed (performed *now*) regardless of whether the text interpreter is interpreting or compiling. The word `;` is an immediate word. Rather than being compiled into the definition, it executes. Its effect is to terminate the current definition, which includes changing the value of `state` back to 0.

When you execute `add-two`, it has a *run-time effect* that is exactly the same as if you had typed `2 + . RET` outside of a definition.

In Forth, every word or number can be described in terms of two properties:

- Its *interpretation semantics* describe how it will behave when the text interpreter encounters it in *interpret* state. The interpretation semantics of a word are represented by its *execution token* (see Section 6.12.1 [Execution token], page 117).
- Its *compilation semantics* describe how it will behave when the text interpreter encounters it in *compile* state. The compilation semantics of a word are represented by its *compilation token* (see Section 6.12.3 [Compilation token], page 120).

Numbers are always treated in a fixed way:

- When the number is *interpreted*, its behaviour is to push the number onto the stack.
- When the number is *compiled*, a piece of code is appended to the current definition that pushes the number when it runs. (In other words, the compilation semantics of a number are to postpone its interpretation semantics until the run-time of the definition that it is being compiled into.)

Words don't always behave in such a regular way, but most have *default semantics* which means that they behave like this:

- The *interpretation semantics* of the word are to do something useful.
- The *compilation semantics* of the word are to append its *interpretation semantics* to the current definition (so that its run-time behaviour is to do something useful).

The actual behaviour of any particular word can be controlled by using the words **immediate** and **compile-only** when the word is defined. These words set flags in the name dictionary entry of the most recently defined word, and these flags are retrieved by the text interpreter when it finds the word in the name dictionary.

A word that is marked as *immediate* has compilation semantics that are identical to its interpretation semantics. In other words, it behaves like this:

- The *interpretation semantics* of the word are to do something useful.
- The *compilation semantics* of the word are to do something useful (and actually the same thing); i.e., it is executed during compilation.

Marking a word as *compile-only* means that the text interpreter produces a warning when encountering this word in interpretation state; ticking the word (with ' or ['] also produces a warning.

It is never necessary to use **compile-only** (and it is not even part of Standard Forth, though it is provided by many implementations) but it is good etiquette to apply it to a word that will not behave correctly (and might have unexpected side-effects) in interpret state. For example, it is only legal to use the conditional word **IF** within a definition. If you forget this and try to use it elsewhere, the fact that (in Gforth) it is marked as **compile-only** allows the text interpreter to generate a helpful warning.

This example shows the difference between an immediate and a non-immediate word:

```
: show-state state @ . ;
: show-state-now show-state ; immediate
: word1 show-state ;
: word2 show-state-now ;
```

The word **immediate** after the definition of **show-state-now** makes that word an immediate word. These definitions introduce a new word: **@** (pronounced “fetch”). This word

fetches the value of a variable, and leaves it on the stack. Therefore, the behaviour of **show-state** is to print a number that represents the current value of **state**.

When you execute **word1**, it prints the number 0, indicating that the system is interpreting. When the text interpreter compiled the definition of **word1**, it encountered **show-state** whose compilation semantics are to append its interpretation semantics to the current definition. When you execute **word1**, it performs the interpretation semantics of **show-state**. At the time that **word1** (and therefore **show-state**) is executed, the system is interpreting.

When you pressed RET after entering the definition of **word2**, you should have seen the number -1 printed, followed by “ok”. When the text interpreter compiled the definition of **word2**, it encountered **show-state-now**, an immediate word, whose compilation semantics are therefore to perform its interpretation semantics. It is executed straight away (even before the text interpreter has moved on to process another group of characters; the ; in this example). The effect of executing it is to display the value of **state** *at the time that the definition of word2 is being defined*. Printing -1 demonstrates that the system is compiling at this time. If you execute **word2** it does nothing at all.

Before leaving the subject of immediate words, consider the behaviour of **.** in the definition of **greet**, in the previous section. This word is both a parsing word and an immediate word. Notice that there is a space between **.** and the start of the text **Hello and welcome**, but that there is no space between the last letter of **welcome** and the **"** character. The reason for this is that **.** is a Forth word; it must have a space after it so that the text interpreter can identify it. The **"** is not a Forth word; it is a *delimiter*. The examples earlier show that, when the string is displayed, there is neither a space before the H nor after the e. Since **.** is an immediate word, it executes at the time that **greet** is defined. When it executes, its behaviour is to search forward in the input line looking for the delimiter. When it finds the delimiter, it updates >IN to point past the delimiter. It also compiles some magic code into the definition of **greet**; the xt of a run-time routine that prints a text string. It compiles the string **Hello and welcome** into memory so that it is available to be printed later. When the text interpreter gains control, the next word it finds in the input stream is ; and so it terminates the definition of **greet**.

4.5 Forth is written in Forth

When you start up a Forth compiler, a large number of definitions already exist. In Forth, you develop a new application using bottom-up programming techniques to create new definitions that are defined in terms of existing definitions. As you create each definition you can test and debug it interactively.

If you have tried out the examples in this section, you will probably have typed them in by hand; when you leave Gforth, your definitions will be lost. You can avoid this by using a text editor to enter Forth source code into a file, and then loading code from the file using **include** (see Section 6.18.1 [Forth source files], page 139). A Forth source file is processed by the text interpreter, just as though you had typed it in by hand³.

Gforth also supports the traditional Forth alternative to using text files for program entry (see Section 6.19 [Blocks], page 144).

³ Actually, there are some subtle differences – see Section 6.14 [The Text Interpreter], page 125.

In common with many, if not most, Forth compilers, most of Gforth is actually written in Forth. All of the `.fs` files in the installation directory⁴ are Forth source files, which you can study to see examples of Forth programming.

Gforth maintains a history file that records every line that you type to the text interpreter. This file is preserved between sessions, and is used to provide a command-line recall facility. If you enter long definitions by hand, you can use a text editor to paste them out of the history file into a Forth source file for reuse at a later time (for more information see Section 2.4 [Command-line editing], page 7).

4.6 Review - elements of a Forth system

To summarise this chapter:

- Forth programs use *factoring* to break a problem down into small fragments called *words* or *definitions*.
- Forth program development is an interactive process.
- The main command loop that accepts input, and controls both interpretation and compilation, is called the *text interpreter* (also known as the *outer interpreter*).
- Forth has a very simple syntax, consisting of words and numbers separated by spaces or carriage-return characters. Any additional syntax is imposed by *parsing words*.
- Forth uses a stack to pass parameters between words. As a result, it uses postfix notation.
- To use a word that has previously been defined, the text interpreter searches for the word in the *name dictionary*.
- Words have *interpretation semantics* and *compilation semantics*.
- The text interpreter uses the value of `state` to select between the use of the *interpretation semantics* and the *compilation semantics* of a word that it encounters.
- The relationship between the *interpretation semantics* and *compilation semantics* for a word depends upon the way in which the word was defined (for example, whether it is an *immediate* word).
- Forth definitions can be implemented in Forth (called *high-level definitions*) or in some other way (usually a lower-level language and as a result often called *low-level definitions*, *code definitions* or *primitives*).
- Many Forth systems are implemented mainly in Forth.

4.7 Where To Go Next

Amazing as it may seem, if you have read (and understood) this far, you know almost all the fundamentals about the inner workings of a Forth system. You certainly know enough to be able to read and understand the rest of this manual and the Standard Forth document, to learn more about the facilities that Forth in general and Gforth in particular provide. Even scarier, you know almost enough to implement your own Forth system. However, that's not a good idea just yet... better to try writing some programs in Gforth.

⁴ For example, `/usr/local/share/gforth...`

Forth has such a rich vocabulary that it can be hard to know where to start in learning it. This section suggests a few sets of words that are enough to write small but useful programs. Use the word index in this document to learn more about each word, then try it out and try to write small definitions using it. Start by experimenting with these words:

- Arithmetic: `+` `-` `*` `/` `/MOD` `*/` `ABS` `INVERT`
- Comparison: `MIN` `MAX` `=`
- Logic: `AND` `OR` `XOR` `NOT`
- Stack manipulation: `DUP` `DROP` `SWAP` `OVER`
- Loops and decisions: `IF` `ELSE` `ENDIF` `?DO` `I` `LOOP`
- Input/Output: `.` `."` `EMIT` `CR` `KEY`
- Defining words: `:` `;` `CREATE`
- Memory allocation words: `ALLOT` `,`
- Tools: `SEE WORDS` `.S` `MARKER`

When you have mastered those, go on to:

- More defining words: `VARIABLE` `CONSTANT` `VALUE` `TO` `CREATE` `DOES>`
- Memory access: `@` `!`

When you have mastered these, there's nothing for it but to read through the whole of this manual and find out what you've missed.

4.8 Exercises

TODO: provide a set of programming excercises linked into the stuff done already and into other sections of the manual. Provide solutions to all the exercises in a `.fs` file in the distribution.

5 Literals in source code

To push an integer number on the data stack, you write the number in source code, e.g., 123. You can prefix the digits with `-` to indicate a negative number, e.g. `-123`. This works both inside colon definitions and outside. The number is interpreted according to the value of `base` (see Section 6.14.2 [Number Conversion], page 128). The digits are 0 to 9 and `a` (decimal 10) to `z` (decimal 35), but only digits smaller than the base are recognized. The conversion is case-insensitive, so `A` and `a` are the same digit.

You can make the base explicit for the number by using a prefix:

- `#` – decimal
- `%` – binary
- `$` – hexadecimal
- `&` – decimal (non-standard)
- `0x` – hexadecimal, if `base<33` (non-standard).

For combinations including base-prefix and sign, the standard order is to have the base-prefix first (e.g., `#-123`); Gforth supports both orders.

You can put a decimal point `.` at the end of a number (or, non-standardly, anywhere else except before a prefix) to get a double-cell integer (e.g., `#-123.` or `#-.123` (the same number)). If users experienced in another programming language see or write such a number without base prefix (e.g., `-123.`), they may expect that the number represents a floating-point value. To clear up the confusion early, Gforth warns of such usage; to avoid the warnings, the best approach is to always write double numbers with a base prefix (e.g., `#-123.`)

Here are some examples, with the equivalent decimal number shown after in braces:

`$-41` (-65), `%1001101` (205), `%1001.0001` (145 - a double-precision number), `#905` (905), `$abc` (2478), `$ABC` (2478).

You can get the numeric value of a (character) code point by surrounding the character with `'` (e.g., `'a'`). The trailing `'` is required by the standard, but you can leave it away in Gforth. Note that this also works for non-ASCII characters. For many uses, it is more useful to have the character as a string rather than as a cell; see below for the string syntax.

For floating-point numbers in Forth, you recognize them due to their exponent. I.e. `1.` is a double-cell integer, and `1e0` is a floating-point number; the latter can be (and usually is) shortened to `1e`. Both the significand (the part before the `e` or `E`) and the exponent may have signs (including `+`); the significand must contain at least one digit and may contain a decimal point, the exponent can be empty. Floating-point numbers always use decimal base for both significand and exponent, and are only recognized when the base is decimal. Examples are: `1e 1e0 1.e 1.e0 +1e+0` (which all represent the same number) `+12.E-4`.

A Gforth extension (since 1.0) is to write a floating-point number in scaled notation: It can optionally have a sign, then one or more digits, then use one of the mostly SI-defined scaling symbols (aka metric prefixes) or `%`, and then optionally more digits. Here's the full list of scaling symbols that Gforth accepts:

- `Q e30` quetta
- `R e27` ronna
- `Y e24` yotta

- `Z e21` zetta
- `X e18` exa (not `E`)
- `P e15` peta
- `T e12` tera
- `G e9` giga
- `M e6` mega
- `k e3` kilo
- `h e2` hecto
- `d e-1` deci
- `% e-2` percent (not `c`)
- `m e-3` milli
- `u e-6` micro (not μ)
- `n e-9` nano
- `p e-12` pico
- `f e-15` femto
- `a e-18` atto
- `z e-21` zepto
- `y e-24` yocto
- `r e-27` ronto
- `q e-30` quecto

Unlike most of the rest of Gforth, scaling symbols are treated case-sensitively. Using the scaled notation is equivalent to using a decimal point instead of the scaling symbol and appending the exponential notation at the end. Examples of scaled notation: `6k5` (6500e) `23%` (0.23e).

You can input a string by surrounding it with `"` (e.g. `"abc"`, `"a b"`). The result is the starting address and byte (=char) count of the string on the data stack.

You have to escape any `"` inside the string with `\` (e.g., `"double-quote->\<-"`). In addition, this string syntax supports all the ways to write control characters that are supported by `s\` (see Section 6.8.3 [String and character literals], page 79). A disadvantage of this string syntax is that it is non-standard; for standard programs, use `s\` instead.

You can input an environment variable by first loading `rec-env.fs` and then prefixing the environment variable with `$`, e.g., `$HOME`; the result is a string descriptor on the data stack in the format described above. This is equivalent to `"HOME" getenv`, i.e., the environment variable is resolved at run-time.

You can input an execution token (xt) of a word by prefixing the name of the word with `'` (e.g., `'dup`). An advantage over using `'` or `[]` is you do not need to switch between them when copying and pasting code from inside to outside a colon definition or vice versa. A disadvantage is that this syntax is non-standard.

You can input a name token (nt) of a word by prefixing the name of the word with `‘` (e.g., `‘dup`). This syntax is also non-standard.

You can input a body address of a word by surrounding it with `<` and `>` (e.g., `<spaces>`). You can also input an address that is at a positive offset from the body address (typically an address in that body), by putting `+` and a number (see syntax above) between the word name and the closing `>` (e.g., `<spaces+$15>`, `spaces+-3`). You will get the body address plus the number. This non-standard feature exists to allow copying and pasting the output of ... (see Section 6.25.6 [Examining data], page 201).

6 Forth Words

6.1 Notation

The Forth words are described in this section in the glossary notation that has become a de-facto standard for Forth texts:

word Stack effect wordset pronunciation

Description

word The name of the word.

Stack effect

The stack effect is written in the notation *before* -- *after*, where *before* and *after* describe the top of stack entries before and after the execution of the word. The rest of the stack is not touched by the word. The top of stack is rightmost, i.e., a stack sequence is written as it is typed in. Note that Gforth uses a separate floating point stack, but a unified stack notation. Also, return stack effects are not shown in *stack effect*, but in *Description*. The name of a stack item describes the type and/or the function of the item. See below for a discussion of the types.

All words have two stack effects: A compile-time stack effect and a run-time stack effect. The compile-time stack-effect of most words is `-`. If the compile-time stack-effect of a word deviates from this standard behaviour, or the word does other unusual things at compile time, both stack effects are shown; otherwise only the run-time stack effect is shown.

Also note that in code templates or examples there can be comments in parentheses that display the stack picture at this point; there is no -- in these places, because there is no before-after situation.

pronunciation

How the word is pronounced.

wordset The wordset specifies whether a word has been standardized, it is an environmental query string, or if it is a Gforth-specific word. In the latter case the wordset contains the string `gforth`, other wordset names are either `environment` of refer to standard word sets.

The Forth standard is divided into several word sets. In theory, a standard system need not support all of them, but in practice, serious systems on non-tiny machines support almost all standardized words (some systems require explicit loading of some word sets, however), so it does not increase portability in practice to be parsimonious in using word sets.

For the Gforth-specific words, we have the following categories:

`gforth`

`gforth-<version>`

We intend to permanently support this word in Gforth and it has been available since Gforth `<version>` (possibly not as supported word at that time).

gforth-experimental

This word is available in the present version and may turn into a permanent word or may be removed in a future release of Gforth. Feedback welcome.

gforth-internal

This word is an internal factor, not a supported word, and it may be removed in a future release of Gforth.

gforth-obsolete

This word will be removed in a future release of Gforth.

Description

A description of the behaviour of the word.

The type of a stack item is specified by the character(s) the name starts with:

f	Boolean flags, i.e. false or true .
c	Char
w	Cell, can contain an integer or an address
n	signed integer
u	unsigned integer
d	double sized signed integer
ud	double sized unsigned integer
r	Float (on the FP stack)
a-	Cell-aligned address
c-	Char-aligned address (note that a Char may have two bytes in Windows NT)
f-	Float-aligned address
df-	Address aligned for IEEE double precision float
sf-	Address aligned for IEEE single precision float
xt	Execution token, same size as Cell
wid	Word list ID, same size as Cell
ior, wior	I/O result code, cell-sized. In Gforth, you can throw iors.
f83name	Pointer to a name structure
"	string in the input stream (not on the stack). The terminating character is a blank by default. If it is not a blank, it is shown in <> quotes.

6.2 Case insensitivity

Gforth is case-insensitive; you can enter definitions and invoke Standard words using upper, lower or mixed case (however, see Section 9.1.1 [Implementation-defined options], page 241).

Standard Forth only *requires* implementations to recognise Standard words when they are typed entirely in upper case. Therefore, a Standard program must use upper case for all Standard words. You can use whatever case you like for words that you define, but in a Standard program you have to use the words in the same case that you defined them.

Gforth supports case sensitivity through **cs-wordlists** (case-sensitive wordlists, see Section 6.16 [Word Lists], page 133).

Two people have asked how to convert Gforth to be case-sensitive; while we think this is a bad idea, you can change all wordlists into tables like this:

```
' table-find forth-wordlist wordlist-map !
```

Note that you now have to type the predefined words in the same case that we defined them, which are varying. You may want to convert them to your favourite case before doing this operation (I won't explain how, because if you are even contemplating doing this, you'd better have enough knowledge of Forth systems to know this already).

6.3 Comments

Forth supports two styles of comment; the traditional *in-line* comment, (and its modern cousin, the *comment to end of line*; \.

```
( ( compilation 'ccc<close-paren>' - ; run-time - ) core,file "paren"
```

Comment, usually till the next): parse and discard all subsequent characters in the parse area until ")" is encountered. During interactive input, an end-of-line also acts as a comment terminator. For file input, it does not; if the end-of-file is encountered whilst parsing for the ")" delimiter, Gforth will generate a warning.

```
\ ( compilation 'ccc<newline>' - ; run-time - ) core-ext,block-ext "backslash"
```

Comment until the end of line: parse and discard all remaining characters in the parse area, except while **loading** from a block: while **loading** from a block, parse and discard all remaining characters in the 64-byte line.

```
\G ( compilation 'ccc<newline>' - ; run-time - ) gforth-0.2 "backslash-gee"
```

Equivalent to \ but used as a tag to annotate definition comments into documentation.

6.4 Boolean Flags

A Boolean flag is cell-sized. A cell with all bits clear represents the flag **false** and a flag with all bits set represents the flag **true**. Words that check a flag (for example, **IF**) will treat a cell that has *any* bit set as **true**.

```
true ( - f ) core-ext "true"
```

Constant - f is a cell with all bits set.

```
false ( - f ) core-ext "false"
```

Constant - f is a cell with all bits clear.

```
on ( a-addr - ) gforth-0.2 "on"
```

Set the (value of the) variable at *a-addr* to **true**.

off (*a-addr* -) gforth-0.2 “off”

Set the (value of the) variable at *a-addr* to **false**.

select (*u1 u2 f - u*) gforth-1.0 “select”

If *f* is false, *u* is *u2*, otherwise *u1*.

6.5 Arithmetic

Forth arithmetic is not checked, i.e., you will not hear about integer overflow on addition or multiplication, you may hear about division by zero if you are lucky. The operator is written after the operands, but the operands are still in the original order. I.e., the infix *2-1* corresponds to *2 1 -*. Forth offers a variety of division operators. If you perform division with potentially negative operands, you do not want to use */* or */mod* with its implementation-defined behaviour, but, e.g., */f*, */modf* or *fm/mod* (see Section 6.5.4 [Integer division], page 58).

6.5.1 Single precision

By default, numbers in Forth are single-precision integers that are one cell in size. They can be signed or unsigned, depending upon how you treat them. For the rules used by the text interpreter for recognising single-precision integers see Section 6.14.2 [Number Conversion], page 128.

These words are all defined for signed operands, but some of them also work for unsigned numbers: **+**, **1+**, **-**, **1-**, *****.

+ (*n1 n2 - n*) core “plus”

1+ (*n1 - n2*) core “one-plus”

under+ (*n1 n2 n3 - n n2*) gforth-0.3 “under-plus”

add *n3* to *n1* (giving *n*)

- (*n1 n2 - n*) core “minus”

1- (*n1 - n2*) core “one-minus”

***** (*n1 n2 - n*) core “star”

negate (*n1 - n2*) core “negate”

abs (*n - u*) core “abs”

min (*n1 n2 - n*) core “min”

max (*n1 n2 - n*) core “max”

umin (*u1 u2 - u*) gforth-0.5 “umin”

umax (*u1 u2 - u*) gforth-1.0 “umax”

6.5.2 Double precision

For the rules used by the text interpreter for recognising double-precision integers, see Section 6.14.2 [Number Conversion], page 128.

A double precision number is represented by a cell pair, with the most significant cell at the TOS. It is trivial to convert an unsigned single to a double: simply push a 0 onto the TOS. Since numbers are represented by Gforth using 2’s complement arithmetic, converting

a signed single to a (signed) double requires sign-extension across the most significant cell. This can be achieved using `s>d`. The moral of the story is that you cannot convert a number without knowing whether it represents an unsigned or a signed number.

These words are all defined for signed operands, but some of them also work for unsigned numbers: `d+`, `d-`.

```
s>d ( n - d ) core “s-to-d”
d>s ( d - n ) double “d-to-s”
d+ ( ud1 ud2 - ud ) double “d-plus”
d- ( d1 d2 - d ) double “d-minus”
dnegate ( d1 - d2 ) double “d-negate”
dabs ( d - ud ) double “d-abs”
dmin ( d1 d2 - d ) double “d-min”
dmax ( d1 d2 - d ) double “d-max”
```

6.5.3 Mixed precision

```
m+ ( d1 n - d2 ) double “m-plus”
m* ( n1 n2 - d ) core “m-star”
um* ( u1 u2 - ud ) core “u-m-star”
```

6.5.4 Integer division

Below you find a considerable number of words for dealing with divisions. A major difference between them is in dealing with signed division: Do the words support signed division (those with the `U` prefix do not)?

If they do, do they round towards negative infinity (floored division, suffix `F`), or towards 0 (symmetric division, suffix `S`). The standard leaves the issue implementation-defined for most standard words (`/ mod /mod */ */mod m*/`), and different systems have made different choices. Gforth implements these words as floored (since Gforth 0.7). There is only a difference between floored and symmetric division if the dividend and the divisor have different signs, and the dividend is not a multiple of the divisor. The following table illustrates the results:

dividend	divisor	floored		symmetric	
		remainder	quotient	remainder	quotient
10	7	3	1	3	1
-10	7	4	-2	-3	-1
10	-7	-4	-2	3	-1
-10	-7	-3	1	-3	1

The common case where floored vs. symmetric makes a difference is when dividends `n1` with varying sign are divided by the same positive divisor `n2`; in that case you usually want floored division, because then the remainder is always positive and does not change sign depending on the dividend; also, with floored division, the quotient always increases by 1 when `n1` increases by `n2`, while with symmetric division there is no increase in the quotient for `-n2 < n1 < n2` (the quotient is 0 in this range).

In any case, if you divide numbers where floored vs. symmetric makes a difference, you should think about which variant is the right one for you, and then use either the appropriately suffixed Gforth words, or the standard words **fm/mod** or **sm/rem**.

Single-by-single-cell division:

```

/ ( n1 n2 - n ) core "slash"
  n=n1/n2
/s ( n1 n2 - n ) gforth-1.0 "slash-s"
/f ( n1 n2 - n ) gforth-1.0 "slash-f"
u/ ( u1 u2 - u ) gforth-1.0 "u-slash"
mod ( n1 n2 - n ) core "mod"
  n is the modulus of n1/n2
mods ( n1 n2 - n ) gforth-1.0 "mod-s"
modf ( n1 n2 - n ) gforth-1.0 "modf"
umod ( u1 u2 - u ) gforth-1.0 "umod"
/mod ( n1 n2 - n3 n4 ) core "slash-mod"
  n1=n2*n4+n3; n3 is the modulus, n4 the quotient.
/mods ( n1 n2 - n3 n4 ) gforth-1.0 "slash-mod-s"
  n3 is the remainder, n4 the quotient
/modf ( n1 n2 - n3 n4 ) gforth-1.0 "slash-mod-f"
  n3 is the modulus, n4 the quotient
u/mod ( u1 u2 - u3 u4 ) gforth-1.0 "u-slash-mod"
  u3 is the modulus, u4 the quotient

```

Double-by-single-cell division with single-cell results; these words are roughly as fast as the words above on some architectures (e.g., AMD64), but much slower on others (e.g., an order of magnitude on various Aarch64 CPUs).

```
fm/mod ( d1 n1 - n2 n3 ) core "f-m-slash-mod"
```

Floored division: $d1 = n3*n1+n2$, $n1>n2>=0$ or $0>=n2>n1$.

```
sm/rem ( d1 n1 - n2 n3 ) core "s-m-slash-rem"
```

Symmetric division: $d1 = n3*n1+n2$, $\text{sign}(n2)=\text{sign}(d1)$ or 0.

```
um/mod ( ud u1 - u2 u3 ) core "u-m-slash-mod"
```

$ud=u3*u1+u2$, $0<=u2<u1$

```
du/mod ( d u - n u1 ) gforth-1.0 "du-slash-mod"
```

$d=n*u+u1$, $0<=u1<u$; PolyForth style mixed division

```
*/ ( ( n1 n2 n3 - n4 ) core "star-slash"
```

$n4=(n1*n2)/n3$, with the intermediate result being double

```
*/s ( n1 n2 n3 - n4 ) gforth-1.0 "star-slash-s"
```

$n4=(n1*n2)/n3$, with the intermediate result being double

```
*/f ( n1 n2 n3 - n4 ) gforth-1.0 "star-slash-f"
```

$n4=(n1*n2)/n3$, with the intermediate result being double
u*/ (*u1 u2 u3 - u4*) gforth-1.0 “u-star-slash”
 $u4=(u1*u2)/u3$, with the intermediate result being double.
***/mod** (*n1 n2 n3 - n4 n5*) core “star-slash-mod”
 $n1*n2=n3*n5+n4$, with the intermediate result ($n1*n2$) being double; $n4$ is the modulus, $n5$ the quotient.
***/mods** (*n1 n2 n3 - n4 n5*) gforth-1.0 “star-slash-mod-s”
 $n1*n2=n3*n5+n4$, with the intermediate result ($n1*n2$) being double; $n4$ is the remainder, $n5$ the quotient
***/modf** (*n1 n2 n3 - n4 n5*) gforth-1.0 “star-slash-mod-f”
 $n1*n2=n3*n5+n4$, with the intermediate result ($n1*n2$) being double; $n4$ is the modulus, $n5$ the quotient
u*/mod (*u1 u2 u3 - u4 u5*) gforth-1.0 “u-star-slash-mod”
 $u1*u2=u3*u5+u4$, with the intermediate result ($u1*u2$) being double.
 Division with double-cell results; these words are much slower than the words above.
ud/mod (*ud1 u2 - urem udquot*) gforth-0.2 “ud/mod”
 divide unsigned double *ud1* by *u2*, resulting in a unsigned double quotient *udquot* and a single remainder *urem*.
m*/ (*d1 n2 u3 - dquot*) double “m-star-slash”
 $dquot=(d1*n2)/u3$, with the intermediate result being triple-precision. In ANS Forth *u3* can only be a positive signed number.

You can use the following environmental query to learn whether **/ mod /mod */ */mod m*/** use floored or symmetric division.

FLOORED (*- f*) environment “FLOORED”

True if **/** etc. perform floored division

One other aspect of the integer division words is that most of them can overflow, and division by zero is mathematically undefined. What happens if you hit one of these conditions depends on the engine, the hardware, and the operating system: The engine **gforth** tries hard to throw the appropriate error -10 (Division by zero) or -11 (Result out of range), but on some platforms throws -55 (Floating-point unidentified fault). The engine **gforth-fast** may produce an inappropriate throw code (and error message), or may produce no error, just produce a bogus value. I.e., you should not bet on such conditions being thrown, but for quicker debugging **gforth** catches more and produces more accurate errors than **gforth-fast**.

6.5.5 Two-stage integer division

On most hardware, multiplication is significantly faster than division. So if you have to divide many numbers by the same divisor, it is usually faster to determine the reciprocal of the divisor once and multiply the numbers with the reciprocal. For integers, this is tricky, so Gforth packages this work into the words described in this section.

Let’s start with an example: You want to divide all elements of an array of cells by the same number *n*. A straightforward way to implement this is:

```
: array/ ( addr u n -- )
```

```

-rot cells bounds u+do
  i @ over / i !
1 cells +loop
drop ;

```

A more efficient version looks like this:

```

: array/ ( addr u n -- )
  {: | reci[ staged/-size ] :}
  reci[ /f-stage1m
  cells bounds u+do
    i @ reci[ /f-stage2m i !
  1 cells +loop ;

```

This example first creates a local buffer `reci[` with size `staged/-size` for storing the reciprocal data. Then `/f-stage1m` computes the reciprocal of n and stores it in `reci[`. Finally, inside the loop `/f-stage2m` uses the data in `reci[` to compute the quotient.

There are some limitations: Only positive divisors are supported for `/f-stage1m`; for `u/-stage1m` you can use a divisor of 2 or higher. You get an error if you try to use an unsupported divisor. You must initialize the reciprocal buffer for the floored second-stage words with `/f-stage1m` and for the unsigned second-stage words with `u/-stage1m`. You must not modify the reciprocal buffer between the first stage and the second stage; basically, don't treat it as a memory buffer, but as something that is only mutable by the first stage; the point of this rule is that future versions of Gforth will not consider aliasing of this buffer.

The words are:

`staged/-size (- u) gforth-1.0 "staged-slash-size"`

Size of buffer for `u/-stage1m` or `/f-stage1m`.

`/f-stage1m (n addr-reci -) gforth-1.0 "slash-f-stage1m"`

Compute the reciprocal of n and store it in the buffer `addr-reci` of size `staged/-size`. Throws an error if $n < 1$.

`/f-stage2m (n1 a-reci - nquotient) gforth-1.0 "slash-f-stage2m"`

$N_{quotient}$ is the result of dividing $n1$ by the divisor represented by `a-reci`, which was computed by `/f-stage1m`.

`modf-stage2m (n1 a-reci - umodulus) gforth-1.0 "mod-f-stage2m"`

$U_{modulus}$ is the remainder of dividing $n1$ by the divisor represented by `a-reci`, which was computed by `/f-stage1m`.

`/modf-stage2m (n1 a-reci - umodulus nquotient) gforth-1.0 "slash-mod-f-stage2m"`

$N_{quotient}$ is the quotient and $umodulus$ is the remainder of dividing $n1$ by the divisor represented by `a-reci`, which was computed by `/f-stage1m`.

`u/-stage1m (u addr-reci -) gforth-1.0 "u-slash-stage1m"`

Compute the reciprocal of u and store it in the buffer `addr-reci` of size `staged/-size`. Throws an error if $u < 2$.

`u/-stage2m (u1 a-reci - uquotient) gforth-1.0 "u-slash-stage2m"`

$U_{quotient}$ is the result of dividing $u1$ by the divisor represented by `a-reci`, which was computed by `u/-stage1m`.

`umod-stage2m (u1 a-reci - umodulus) gforth-1.0 "u-mod-stage2m"`

Umodulus is the remainder of dividing *u1* by the divisor represented by *a-reci*, which was computed by **u/-stage1m**.

u/mod-stage2m (*u1 a-reci - umodulus uquotient*) gforth-1.0 “u-slash-mod-stage2m”

Uquotient is the quotient and *umodulus* is the remainder of dividing *u1* by the divisor represented by *a-reci*, which was computed by **u/-stage1m**.

Gforth currently does not support staged symmetrical division.

You can recover the divisor from (the address of) a reciprocal with **staged/-divisor @: staged/-divisor** (*addr1 - addr2*) gforth-1.0 “staged-slash-divisor”

Addr1 is the address of a reciprocal, *addr2* is the address containing the divisor from which the reciprocal was computed.

This can be useful when looking at the decompiler output of Gforth: a division by a constant is often compiled to a literal containing the address of a reciprocal followed by a second-stage word.

The performance impact of using these words strongly depends on the architecture (does it have hardware division?) and the specific implementation (how fast is hardware division?), but just to give you an idea about the relative performance of these words, here are the cycles per iteration of a microbenchmark (which performs the mentioned word once per iteration) on two AMD64 implementations; the *norm* column shows the normal division word (e.g., **u/**), while the *stg2* column shows the corresponding stage2 word (e.g., **u/-stage2m**):

Skylake			Zen2		
norm	stg2		norm	stg2	
41.3	15.8	u/	35.2	21.4	u/
39.8	19.7	umod	36.9	25.8	umod
44.0	25.3	u/mod	43.0	33.9	u/mod
48.7	16.9	/f	36.2	22.5	/f
47.9	20.5	modf	37.9	27.1	modf
53.0	24.6	/modf	45.8	35.4	/modf
227.2		u/stage1	101.9		u/stage1
159.8		/fstage1	97.7		/fstage1

6.5.6 Bitwise operations

and (*w1 w2 - w*) core “and”

or (*w1 w2 - w*) core “or”

xor (*w1 w2 - w*) core “x-or”

invert (*w1 - w2*) core “invert”

mux (*u1 u2 u3 - u*) gforth-1.0 “mux”

Multiplex: For every bit in *u3*: for a 1 bit, select the corresponding bit from *u1*, otherwise the corresponding bit from *u2*. E.g., **%0011 %1100 %1010 mux** gives **%0110**

lshift (*u1 u - u2*) core “l-shift”

Shift *u1* left by *u* bits.

rshift (*u1 u - u2*) core “r-shift”

Shift *u1* (cell) right by *u* bits, filling the shifted-in bits with zero (logical/unsigned shift).

arshift (*n1 u - n2*) gforth-1.0 “ar-shift”

Shift $n1$ (cell) right by u bits, filling the shifted-in bits from the sign bit of $n1$ (arithmetic shift).

dlshift ($u1\ u - u2$) gforth-1.0 “dlshift”

Shift $u1$ (double-cell) left by u bits.

drshift ($u1\ u - u2$) gforth-1.0 “drshift”

Shift $u1$ (double-cell) right by u bits, filling the shifted-in bits with zero (logical/unsigned shift).

darshift ($d1\ u - d2$) gforth-1.0 “darshift”

Shift $d1$ (double-cell) right by u bits, filling the shifted-in bits from the sign bit of $d1$ (arithmetic shift).

2* ($n1 - n2$) core “two-star”

Shift left by 1; also works on unsigned numbers

2/ ($n1 - n2$) core “two-slash”

Arithmetic shift right by 1. For signed numbers this is a floored division by 2 (note that / not necessarily floors).

d2* ($d1 - d2$) double “d-two-star”

Shift double-cell left by 1; also works on unsigned numbers

d2/ ($d1 - d2$) double “d-two-slash”

Arithmetic shift right by 1. For signed numbers this is a floored division by 2.

>pow2 ($u1 - u2$) gforth-1.0 “to-pow2”

$u2$ is the lowest power-of-2 number with $u2 \geq u1$.

log2 ($u - n$) gforth-1.0 “log2”

N is the rounded-down binary logarithm of u , i.e., the index of the first set bit; if $u=0$, $n=-1$.

pow2? ($u - f$) gforth-1.0 “pow-two-query”

f is true iff u is a power of two, i.e., there is exactly one bit set in u .

ctz ($x - u$) gforth-1.0 “c-t-z”

count trailing zeros in binary representation of x

Unlike most other operations, rotation of narrower units cannot easily be synthesized from rotation of wider units, so using cell-wide and double-wide rotation operations means that the results depend on the cell width. For published algorithms or cell-width-independent results, you usually need to use a fixed-width rotation operation.

wrol ($u1\ u - u2$) gforth-1.0 “wrol”

Rotate the least significant 16 bits of $u1$ left by u bits, set the other bits to 0.

wror ($u1\ u - u2$) gforth-1.0 “wror”

Rotate the least significant 16 bits of $u1$ right by u bits, set the other bits to 0.

lrol ($u1\ u - u2$) gforth-1.0 “lrol”

Rotate the least significant 32 bits of $u1$ left by u bits, set the other bits to 0.

lror ($u1\ u - u2$) gforth-1.0 “lror”

Rotate the least significant 32 bits of *u1* right by *u* bits, set the other bits to 0.

rol (*u1 u - u2*) gforth-1.0 “rol”

Rotate all bits of *u1* left by *u* bits.

ror (*u1 u - u2*) gforth-1.0 “ror”

Rotate all bits of *u1* right by *u* bits.

drol (*ud1 u - ud2*) gforth-1.0 “drol”

Rotate all bits of *ud1* (double-cell) left by *u* bits.

dror (*ud1 u - ud2*) gforth-1.0 “dror”

Rotate all bits of *ud1* (double-cell) right by *u* bits.

6.5.7 Numeric comparison

Note that the words that compare for equality (= <> 0= 0<> d= d<> d0= d0<>) work for both signed and unsigned numbers.

< (*n1 n2 - f*) core “less-than”

<= (*n1 n2 - f*) gforth-0.2 “less-or-equal”

<> (*n1 n2 - f*) core-ext “not-equals”

= (*n1 n2 - f*) core “equals”

> (*n1 n2 - f*) core “greater-than”

>= (*n1 n2 - f*) gforth-0.2 “greater-or-equal”

0< (*n - f*) core “zero-less-than”

0<= (*n - f*) gforth-0.2 “zero-less-or-equal”

0<> (*n - f*) core-ext “zero-not-equals”

0= (*n - f*) core “zero-equals”

0> (*n - f*) core-ext “zero-greater-than”

0>= (*n - f*) gforth-0.2 “zero-greater-or-equal”

u< (*u1 u2 - f*) core “u-less-than”

u<= (*u1 u2 - f*) gforth-0.2 “u-less-or-equal”

u> (*u1 u2 - f*) core-ext “u-greater-than”

u>= (*u1 u2 - f*) gforth-0.2 “u-greater-or-equal”

within (*u1 u2 u3 - f*) core-ext “within”

u2<*u3* and *u1* in [*u2*,*u3*) or: *u2*>=*u3* and *u1* not in [*u3*,*u2*). This works for unsigned and signed numbers (but not a mixture). Another way to think about this word is to consider the numbers as a circle (wrapping around from **max-u** to 0 for unsigned, and from **max-n** to **min-n** for signed numbers); now consider the range from *u2* towards increasing numbers up to and excluding *u3* (giving an empty range if *u2*=*u3*); if *u1* is in this range, **within** returns true.

d< (*d1 d2 - f*) double “d-less-than”

d<= (*d1 d2 - f*) gforth-0.2 “d-less-or-equal”

d<> (*d1 d2 - f*) gforth-0.2 “d-not-equals”

d= (*d1 d2 - f*) double “d-equals”

```

d> ( d1 d2 - f ) gforth-0.2 "d-greater-than"
d>= ( d1 d2 - f ) gforth-0.2 "d-greater-or-equal"
d0< ( d - f ) double "d-zero-less-than"
d0<= ( d - f ) gforth-0.2 "d-zero-less-or-equal"
d0<> ( d - f ) gforth-0.2 "d-zero-not-equals"
d0= ( d - f ) double "d-zero-equals"
d0> ( d - f ) gforth-0.2 "d-zero-greater-than"
d0>= ( d - f ) gforth-0.2 "d-zero-greater-or-equal"
du< ( ud1 ud2 - f ) double-ext "d-u-less-than"
du<= ( ud1 ud2 - f ) gforth-0.2 "d-u-less-or-equal"
du> ( ud1 ud2 - f ) gforth-0.2 "d-u-greater-than"
du>= ( ud1 ud2 - f ) gforth-0.2 "d-u-greater-or-equal"

```

6.5.8 Floating Point

For the rules used by the text interpreter for recognising floating-point numbers see Section 6.14.2 [Number Conversion], page 128.

Gforth has a separate floating point stack, but the documentation uses the unified notation.¹

Floating point numbers have a number of unpleasant surprises for the unwary (e.g., floating point addition is not associative) and even a few for the wary. You should not use them unless you know what you are doing or you don't care that the results you get are totally bogus. If you want to learn about the problems of floating point numbers (and how to avoid them), you might start with *David Goldberg, What Every Computer Scientist Should Know About Floating-Point Arithmetic* (https://docs.oracle.com/cd/E19957-01/806-3568/ncg_goldberg.html), *ACM Computing Surveys* 23(1):5–48, March 1991.

Conversion between integers and floating-point:

```

s>f ( n - r ) floating-ext "s-to-f"
d>f ( d - r ) floating "d-to-f"
f>s ( r - n ) floating-ext "f-to-s"
f>d ( r - d ) floating "f-to-d"

```

Arithmetics:

```

f+ ( r1 r2 - r3 ) floating "f-plus"
f- ( r1 r2 - r3 ) floating "f-minus"
f* ( r1 r2 - r3 ) floating "f-star"
f/ ( r1 r2 - r3 ) floating "f-slash"
fnegate ( r1 - r2 ) floating "f-negate"
fabs ( r1 - r2 ) floating-ext "f-abs"

```

¹ It's easy to generate the separate notation from that by just separating the floating-point numbers out: e.g. (n r1 u r2 -- r3) becomes (n u --) (F: r1 r2 -- r3).

fmax (*r1 r2 - r3*) floating “f-max”

fmin (*r1 r2 - r3*) floating “f-min”

floor (*r1 - r2*) floating “floor”

Round towards the next smaller integral value, i.e., round toward negative infinity.

fround (*r1 - r2*) floating “f-round”

Round to the nearest integral value.

f** (*r1 r2 - r3*) floating-ext “f-star-star”

r3 is *r1* raised to the *r2*th power.

fsqrt (*r1 - r2*) floating-ext “f-square-root”

fexp (*r1 - r2*) floating-ext “f-e-x-p”

fexpm1 (*r1 - r2*) floating-ext “f-e-x-p-m-one”

$r2 = e^{r1} - 1$

fln (*r1 - r2*) floating-ext “f-l-n”

flnp1 (*r1 - r2*) floating-ext “f-l-n-p-one”

$r2 = \ln(r1 + 1)$

flog (*r1 - r2*) floating-ext “f-log”

The decimal logarithm.

falog (*r1 - r2*) floating-ext “f-a-log”

$r2 = 10^{r1}$

f2* (*r1 - r2*) gforth-0.2 “f2*”

Multiply *r1* by 2.0e0

f2/ (*r1 - r2*) gforth-0.2 “f2/”

Multiply *r1* by 0.5e0

1/f (*r1 - r2*) gforth-0.2 “1/f”

Divide 1.0e0 by *r1*.

Vector arithmetics:

v* (*f-addr1 nstride1 f-addr2 nstride2 ucount - r*) gforth-0.5 “v-star”

dot-product: $r = v1 * v2$. The first element of *v1* is at *f-addr1*, the next at *f-addr1*+*nstride1* and so on (similar for *v2*). Both vectors have *ucount* elements.

faxpy (*ra f-x nstridex f-y nstridey ucount -*) gforth-0.5 “faxpy”

$vy = ra * vx + vy$

Angles in floating point operations are given in radians (a full circle has 2 pi radians).

fsin (*r1 - r2*) floating-ext “f-sine”

fcos (*r1 - r2*) floating-ext “f-cos”

fsincos (*r1 - r2 r3*) floating-ext “f-sine-cos”

$r2 = \sin(r1)$, $r3 = \cos(r1)$
ftan ($r1 - r2$) floating-ext “f-tan”
fasin ($r1 - r2$) floating-ext “f-a-sine”
facos ($r1 - r2$) floating-ext “f-a-cos”
fatan ($r1 - r2$) floating-ext “f-a-tan”
fatan2 ($r1\ r2 - r3$) floating-ext “f-a-tan-two”

$r1/r2 = \tan(r3)$. ANS Forth does not require, but probably intends this to be the inverse of **fsincos**. In gforth it is.

fsinh ($r1 - r2$) floating-ext “f-cinch”
fcosh ($r1 - r2$) floating-ext “f-cosh”
ftanh ($r1 - r2$) floating-ext “f-tan-h”
fasinh ($r1 - r2$) floating-ext “f-a-cinch”
facosh ($r1 - r2$) floating-ext “f-a-cosh”
fatanh ($r1 - r2$) floating-ext “f-a-tan-h”
pi ($- r$) gforth-0.2 “pi”

Fconstant – r is the value pi; the ratio of a circle’s area to its diameter.

One particular problem with floating-point arithmetic is that comparison for equality often fails when you would expect it to succeed. For this reason approximate equality is often preferred (but you still have to know what you are doing). Also note that IEEE NaNs may compare differently from what you might expect. The comparison words are:

f~rel ($r1\ r2\ r3 - flag$) gforth-0.5 “f~rel”

Approximate equality with relative error: $|r1-r2| < r3 * |r1+r2|$.

f~abs ($r1\ r2\ r3 - flag$) gforth-0.5 “f~abs”

Approximate equality with absolute error: $|r1-r2| < r3$.

f~ ($r1\ r2\ r3 - flag$) floating-ext “f-proximate”

ANS Forth medley for comparing $r1$ and $r2$ for equality: $r3 > 0$: **f~abs**; $r3 = 0$: bitwise comparison; $r3 < 0$: **fnegate f~rel**.

f= ($r1\ r2 - f$) gforth-0.2 “f-equals”
f<> ($r1\ r2 - f$) gforth-0.2 “f-not-equals”
f< ($r1\ r2 - f$) floating “f-less-than”
f<= ($r1\ r2 - f$) gforth-0.2 “f-less-or-equal”
f> ($r1\ r2 - f$) gforth-0.2 “f-greater-than”
f>= ($r1\ r2 - f$) gforth-0.2 “f-greater-or-equal”
f0< ($r - f$) floating “f-zero-less-than”
f0<= ($r - f$) gforth-0.2 “f-zero-less-or-equal”
f0<> ($r - f$) gforth-0.2 “f-zero-not-equals”
f0= ($r - f$) floating “f-zero-equals”
f0> ($r - f$) gforth-0.2 “f-zero-greater-than”
f0>= ($r - f$) gforth-0.2 “f-zero-greater-or-equal”

6.6 Stack Manipulation

Gforth maintains a number of separate stacks:

- A data stack (also known as the *parameter stack*) – for characters, cells, addresses, and double cells.
- A floating point stack – for holding floating point (FP) numbers.
- A return stack – for holding the return addresses of colon definitions and other (non-FP) data.
- A locals stack – for holding local variables.

6.6.1 Data stack

```
drop ( w - ) core “drop”
nip ( w1 w2 - w2 ) core-ext “nip”
dup ( w - w w ) core “dupe”
over ( w1 w2 - w1 w2 w1 ) core “over”
third ( w1 w2 w3 - w1 w2 w3 w1 ) gforth-1.0 “third”
fourth ( w1 w2 w3 w4 - w1 w2 w3 w4 w1 ) gforth-1.0 “fourth”
tuck ( w1 w2 - w2 w1 w2 ) core-ext “tuck”
swap ( w1 w2 - w2 w1 ) core “swap”
pick ( S:... u - S:... w ) core-ext “pick”
```

Actually the stack effect is `x0 ... xu u -- x0 ... xu x0 .`

```
rot ( w1 w2 w3 - w2 w3 w1 ) core “rote”
-rot ( w1 w2 w3 - w3 w1 w2 ) gforth-0.2 “not-rote”
?dup ( w - S:... w ) core “question-dupe”
```

Actually the stack effect is: `(w -- 0 | w w)`. It performs a `dup` if `w` is nonzero.

```
roll ( x0 x1 .. xn n - x1 .. xn x0 ) core-ext “roll”
2drop ( w1 w2 - ) core “two-drop”
2nip ( w1 w2 w3 w4 - w3 w4 ) gforth-0.2 “two-nip”
2dup ( w1 w2 - w1 w2 w1 w2 ) core “two-dupe”
2over ( w1 w2 w3 w4 - w1 w2 w3 w4 w1 w2 ) core “two-over”
2tuck ( w1 w2 w3 w4 - w3 w4 w1 w2 w3 w4 ) gforth-0.2 “two-tuck”
2swap ( w1 w2 w3 w4 - w3 w4 w1 w2 ) core “two-swap”
2rot ( w1 w2 w3 w4 w5 w6 - w3 w4 w5 w6 w1 w2 ) double-ext “two-rote”
```

6.6.2 Floating point stack

```
floating-stack ( - n ) environment “floating-stack”
```

`n` is non-zero, showing that Gforth maintains a separate floating-point stack of depth `n`.

```
fdrop ( r - ) floating “f-drop”
fnip ( r1 r2 - r2 ) gforth-0.2 “f-nip”
fdup ( r - r r ) floating “f-dupe”
```

```

fover ( r1 r2 - r1 r2 r1 ) floating "f-over"
fthird ( r1 r2 r3 - r1 r2 r3 r1 ) gforth-1.0 "fthird"
ffourth ( r1 r2 r3 r4 - r1 r2 r3 r4 r1 ) gforth-1.0 "ffourth"
ftuck ( r1 r2 - r2 r1 r2 ) gforth-0.2 "f-tuck"
fswap ( r1 r2 - r2 r1 ) floating "f-swap"
fpick ( f:... u - f:... r ) gforth-0.4 "fpick"

```

Actually the stack effect is `r0 ... ru u -- r0 ... ru r0 .`

```

frot ( r1 r2 r3 - r2 r3 r1 ) floating "f-rote"
f-rot ( r1 r2 r3 - r3 r1 r2 ) floating "f-not-rote"

```

6.6.3 Return stack

A Forth system is allowed to keep local variables on the return stack. This is reasonable, as local variables usually eliminate the need to use the return stack explicitly. So, if you want to produce a standard compliant program and you are using local variables in a word, forget about return stack manipulations in that word (refer to the standard document for the exact rules).

```

>r ( w - R:w ) core "to-r"
r> ( R:w - w ) core "r-from"
r@ ( - w ; R: w - w ) core "r-fetch"
rdrop ( R:w - ) gforth-0.2 "rdrop"
2>r ( w1 w2 - R:w1 R:w2 ) core-ext "two-to-r"
2r> ( R:w1 R:w2 - w1 w2 ) core-ext "two-r-from"
2r@ ( R:w1 R:w2 - R:w1 R:w2 w1 w2 ) core-ext "two-r-fetch"
2rdrop ( R:w1 R:w2 - ) gforth-0.2 "two-r-drop"

```

6.6.4 Locals stack

Gforth uses an extra locals stack. It is described, along with the reasons for its existence, in Section 6.22.1.4 [Locals implementation], page 169.

6.6.5 Stack pointer manipulation

```
sp0 ( - a-addr ) gforth-0.4 "sp0"
```

User variable – initial value of the data stack pointer.

```

sp@ ( S:... - a-addr ) gforth-0.2 "sp-fetch"
sp! ( a-addr - S:... ) gforth-0.2 "sp-store"
fp0 ( - a-addr ) gforth-0.4 "fp0"

```

User variable – initial value of the floating-point stack pointer.

```

fp@ ( f:... - f-addr ) gforth-0.2 "fp-fetch"
fp! ( f-addr - f:... ) gforth-0.2 "fp-store"
rp0 ( - a-addr ) gforth-0.4 "rp0"

```


User variable – initial value of the return stack pointer.

`rp@ (- a-addr) gforth-0.2 “rp-fetch”`

`rp! (a-addr -) gforth-0.2 “rp-store”`

`lp0 (- a-addr) gforth-0.4 “lp0”`

User variable – initial value of the locals stack pointer.

`lp@ (- addr) gforth-0.2 “lp-fetch”`

`lp! (c-addr -) gforth-internal “lp-store”`

6.7 Memory

In addition to the standard Forth memory allocation words, there is also a garbage collector (<https://www.complang.tuwien.ac.at/forth/garbage-collection.zip>).

6.7.1 Memory model

Standard Forth considers a Forth system as consisting of several address spaces, of which only *data space* is managed and accessible with the memory words. Memory not necessarily in data space includes the stacks, the code (called code space) and the headers (called name space). In Gforth everything is in data space, but the code for the primitives is usually read-only.

Data space is divided into a number of areas: The (data space portion of the) dictionary², the heap, and a number of system-allocated buffers.

Gforth provides one big address space, and address arithmetic can be performed between any addresses. However, in the dictionary headers or code are interleaved with data, so almost the only contiguous data space regions there are those described by Standard Forth as contiguous; but you can be sure that the dictionary is allocated towards increasing addresses even between contiguous regions. The memory order of allocations in the heap is platform-dependent (and possibly different from one run to the next).

6.7.2 Dictionary allocation

Dictionary allocation is a stack-oriented allocation scheme, i.e., if you want to deallocate X, you also deallocate everything allocated after X.

The allocations using the words below are contiguous and grow the region towards increasing addresses. Other words that allocate dictionary memory of any kind (i.e., defining words including `:noname`) end the contiguous region and start a new one.

In Standard Forth only `created` words are guaranteed to produce an address that is the start of the following contiguous region. In particular, the cell allocated by `variable` is not guaranteed to be contiguous with following `alloted` memory.

You can deallocate memory by using `allot` with a negative argument (with some restrictions, see `allot`). For larger deallocations use `marker`.

`here (- addr) core “here”`

Return the address of the next free location in data space.

`unused (- u) core-ext “unused”`

² Sometimes, the term *dictionary* is used to refer to the search data structure embodied in word lists and headers, because it is used for looking up names, just as you would in a conventional dictionary.

Return the amount of free space remaining (in address units) in the region addressed by **here**.

allot (*n* -) core “allot”

Reserve *n* address units of data space without initialization. *n* is a signed number, passing a negative *n* releases memory. In ANS Forth you can only deallocate memory from the current contiguous region in this way. In Gforth you can deallocate anything in this way but named words. The system does not check this restriction.

->here (*addr* -) gforth-1.0 “to-here”

Change the value of **here** to *addr*.

c, (*c* -) core “c-comma”

Reserve data space for one char and store *c* in the space.

f, (*f* -) gforth-0.2 “f,”

Reserve data space for one floating-point number and store *f* in the space.

, (*w* -) core “comma”

Reserve data space for one cell and store *w* in the space.

2, (*w1 w2* -) gforth-0.2 “2,”

Reserve data space for two cells and store the double *w1 w2* there, *w2* first (lower address).

w, (*w* -) gforth-1.0 “w-comma”

l, (*l* -) gforth-1.0 “l-comma”

x, (*x* -) gforth-1.0 “x-comma”

xd, (*xd* -) gforth-1.0 “x-d-comma”

Memory accesses have to be aligned (see Section 6.7.6 [Address arithmetic], page 75). So of course you should allocate memory in an aligned way, too. I.e., before allocating allocating a cell, **here** must be cell-aligned, etc. The words below align **here** if it is not already. Basically it is only already aligned for a type, if the last allocation was a multiple of the size of this type and if **here** was aligned for this type before.

After freshly **create**ing a word, **here** is aligned in Standard Forth (**maxaligned** in Gforth).

align (-) core “align”

If the data-space pointer is not aligned, reserve enough space to align it.

falign (-) floating “f-align”

If the data-space pointer is not float-aligned, reserve enough space to align it.

salign (-) floating-ext “s-f-align”

If the data-space pointer is not single-float-aligned, reserve enough space to align it.

dalign (-) floating-ext “d-f-align”

If the data-space pointer is not double-float-aligned, reserve enough space to align it.

maxalign (-) gforth-0.2 “maxalign”

Align data-space pointer for all alignment requirements.

cfalign (-) gforth-0.2 “cfalign”

Align data-space pointer for code field requirements (i.e., such that the corresponding body is maxaligned).

6.7.3 Heap allocation

Heap allocation supports deallocation of allocated memory in any order. Dictionary allocation is not affected by it (i.e., it does not end a contiguous region). In Gforth, these words are implemented using the standard C library calls `malloc()`, `free()` and `realloc()`.

The memory region produced by one invocation of **allocate** or **resize** is internally contiguous. There is no contiguity between such a region and any other region (including others allocated from the heap).

allocate (*u* – *a-addr* *wior*) memory “allocate”

Allocate *u* address units of contiguous data space. The initial contents of the data space is undefined. If the allocation is successful, *a-addr* is the start address of the allocated region and *wior* is 0. If the allocation fails, *a-addr* is undefined and *wior* is a non-zero I/O result code.

free (*a-addr* – *wior*) memory “free”

Return the region of data space starting at *a-addr* to the system. The region must originally have been obtained using **allocate** or **resize**. If the operation is successful, *wior* is 0. If the operation fails, *wior* is a non-zero I/O result code.

resize (*a-addr1* *u* – *a-addr2* *wior*) memory “resize”

Change the size of the allocated area at *a-addr1* to *u* address units, possibly moving the contents to a different area. *a-addr2* is the address of the resulting area. If the operation is successful, *wior* is 0. If the operation fails, *wior* is a non-zero I/O result code. If *a-addr1* is 0, Gforth’s (but not the Standard) **resize** allocates *u* address units.

6.7.4 Memory Access

@ (*a-addr* – *w*) core “fetch”

w is the cell stored at *a-addr*.

! (*w* *a-addr* –) core “store”

Store *w* into the cell at *a-addr*.

+! (*n* *a-addr* –) core “plus-store”

Add *n* to the cell at *a-addr*.

c@ (*c-addr* – *c*) core “c-fetch”

c is the char stored at *c-addr*.

c! (*c* *c-addr* –) core “c-store”

Store *c* into the char at *c-addr*.

2@ (*a-addr* – *w1* *w2*) core “two-fetch”

w2 is the content of the cell stored at *a-addr*, *w1* is the content of the next cell.

2! (*w1* *w2* *a-addr* –) core “two-store”

Store *w2* into the cell at *c-addr* and *w1* into the next cell.

f@ (*f-addr* – *r*) floating “f-fetch”

r is the float at address *f-addr*.

f! (*r* *f-addr* –) floating “f-store”

Store r into the float at address f_addr .

sf@ ($sf_addr - r$) floating-ext “s-f-fetch”

Fetch the single-precision IEEE floating-point value r from the address sf_addr .

sf! ($r sf_addr -$) floating-ext “s-f-store”

Store r as single-precision IEEE floating-point value to the address sf_addr .

df@ ($df_addr - r$) floating-ext “d-f-fetch”

Fetch the double-precision IEEE floating-point value r from the address df_addr .

df! ($r df_addr -$) floating-ext “d-f-store”

Store r as double-precision IEEE floating-point value to the address df_addr .

6.7.5 Special Memory Accesses

This section is about memory accesses useful for communicating with other software or other computers. This means that the accesses are of a certain bit width (independent of Gforth’s cell width), are possibly not naturally aligned and typically have a certain byte order that may be different from the native byte order of the system that Gforth runs on.

We use the following prefixes:

c	8 bits (character)
w	16 bits
l	32 bits
x	64 bits represented as one cell
xd	64 bits represented as two cells

The **x**-prefix words do not work properly on 32-bit systems, so for code that is intended to be portable to 32-bit systems you should use **xd**-prefix words. Note that **xd**-prefix words work on 64-bit systems: there the upper cell is just 0 (for unsigned values) or a sign extension of the lower cell.

The memory-access words below all work with arbitrarily (un)aligned addresses (unlike **@**, **!**, **f@**, **f!**, which require alignment on some hardware).

w@ ($c_addr - u$) gforth-0.5 “w-fetch”

u is the zero-extended 16-bit value stored at c_addr .

w! ($w c_addr -$) gforth-0.7 “w-store”

Store the bottom 16 bits of w at c_addr .

l@ ($c_addr - u$) gforth-0.7 “l-fetch”

u is the zero-extended 32-bit value stored at c_addr .

l! ($w c_addr -$) gforth-0.7 “l-store”

Store the bottom 32 bits of w at c_addr .

x@ ($c_addr - u$) gforth-1.0 “x-fetch”

u is the zero-extended 64-bit value stored at 64-bit-aligned c_addr .

x! ($w c_addr -$) gforth-1.0 “x-store”

Store the bottom 64 bits of w at 64-bit-aligned c_addr .

xd@ ($c_addr - ud$) gforth-1.0 “x-d-fetch”

ud is the zero-extended 64-bit value stored at 64-bit-aligned c_addr .

xd! ($ud c_addr -$) gforth-1.0 “x-d-store”

Store the bottom 64 bits of ud at 64-bit-aligned c_addr .

For accesses with a specific byte order, you have to perform byte-order adjustment immediately after a fetch (before the sign-extension), or immediately before the store. The results of these byte-order adjustment words are always zero-extended.

wbe ($u1 - u2$) gforth-1.0 “wbe”

Convert 16-bit value in $u1$ from native byte order to big-endian or from big-endian to native byte order (the same operation)

wle ($u1 - u2$) gforth-1.0 “wle”

Convert 16-bit value in $u1$ from native byte order to little-endian or from little-endian to native byte order (the same operation)

lbe ($u1 - u2$) gforth-1.0 “lbe”

Convert 32-bit value in $u1$ from native byte order to big-endian or from big-endian to native byte order (the same operation)

lle ($u1 - u2$) gforth-1.0 “lle”

Convert 32-bit value in $u1$ from native byte order to little-endian or from little-endian to native byte order (the same operation)

xbe ($u1 - u2$) gforth-1.0 “xbe”

Convert 64-bit value in $u1$ from native byte order to big-endian or from big-endian to native byte order (the same operation)

xle ($u1 - u2$) gforth-1.0 “xle”

Convert 64-bit value in $u1$ from native byte order to little-endian or from little-endian to native byte order (the same operation)

xdbe ($ud1 - ud2$) gforth-1.0 “xdbe”

Convert 64-bit value in $ud1$ from native byte order to big-endian or from big-endian to native byte order (the same operation)

xdle ($ud1 - ud2$) gforth-1.0 “xdle”

Convert 64-bit value in $ud1$ from native byte order to little-endian or from little-endian to native byte order (the same operation)

For signed fetches with a specific byte order, you have to perform a sign-extension word after an unsigned fetch and a byte-order correction:

c>s ($x - n$) gforth-1.0 “c-to-s”

Sign-extend the 8-bit value in x to cell n .

w>s ($x - n$) gforth-1.0 “w-to-s”

Sign-extend the 16-bit value in x to cell n .

l>s ($x - n$) gforth-1.0 “l-to-s”

Sign-extend the 32-bit value in x to cell n .

x>s ($x - n$) gforth-1.0 “x>s”

Sign-extend the 64-bit value in x to cell n .

`xd>s ($xd - d$) gforth-1.0 “xd>s”`

Sign-extend the 64-bit value in xd to double-cell d .

Overall, this leads to sequences like

```
w@ wbe w>s    \ 16-bit unaligned signed big-endian fetch
>r lle r> 1! \ 32-bit unaligned little-endian store
```

6.7.6 Address arithmetic

Address arithmetic is the foundation on which you can build data structures like arrays, records (see Section 6.23 [Structures], page 173) and objects (see Section 6.24 [Object-oriented Forth], page 178).

Standard Forth does not specify the sizes of the data types. Instead, it offers a number of words for computing sizes and doing address arithmetic. Address arithmetic is performed in terms of address units (aus); on most systems the address unit is one byte. Note that a character may have more than one au, so `chars` is no noop (on platforms where it is a noop, it compiles to nothing).

The basic address arithmetic words are `+` and `-`. E.g., if you have the address of a cell, perform `1 cells +`, and you will have the address of the next cell.

Standard Forth also defines words for aligning addresses for specific types. Many computers require that accesses to specific data types must only occur at specific addresses; e.g., that cells may only be accessed at addresses divisible by 4. Even if a machine allows unaligned accesses, it can usually perform aligned accesses faster.

For the performance-conscious: alignment operations are usually only necessary during the definition of a data structure, not during the (more frequent) accesses to it.

Standard Forth defines no words for character-aligning addresses; in Forth-2012 all addresses are character-aligned.

Standard Forth guarantees that addresses returned by `CREATED` words are cell-aligned; in addition, Gforth guarantees that these addresses are aligned for all purposes.

Note that the Standard Forth word `char` has nothing to do with address arithmetic.

`chars ($n1 - n2$) core “chars”`

$n2$ is the number of address units of $n1$ chars.”

`char+ ($c\text{-}addr1 - c\text{-}addr2$) core “char-plus”`

`1 chars +.`

`cells ($n1 - n2$) core “cells”`

$n2$ is the number of address units of $n1$ cells.

`cell+ ($a\text{-}addr1 - a\text{-}addr2$) core “cell-plus”`

`1 cells +`

`cell- ($a\text{-}addr1 - a\text{-}addr2$) core “cell-minus”`

`1 cells -`

`cell/ ($n1 - n2$) gforth-1.0 “cell-divide”`

$n2$ is the number of cells that fit into $n1$

`cell ($- u$) gforth-0.2 “cell”`

Constant – 1 cells

`aligned (c-addr – a-addr)` core “aligned”

a-addr is the first aligned address greater than or equal to *c-addr*.

`floats (n1 – n2)` floating “floats”

n2 is the number of address units of *n1* floats.

`float+ (f-addr1 – f-addr2)` floating “float-plus”

1 floats +.

`float (– u)` gforth-0.3 “float”

Constant – the number of address units corresponding to a floating-point number.

`float/ (n1 – n2)` gforth-1.0 “float-divide”

`faligned (c-addr – f-addr)` floating “f-aligned”

f-addr is the first float-aligned address greater than or equal to *c-addr*.

`sfloats (n1 – n2)` floating-ext “s-floats”

n2 is the number of address units of *n1* single-precision IEEE floating-point numbers.

`sfloat+ (sf-addr1 – sf-addr2)` floating-ext “s-float-plus”

1 sfloats +.

`sfloat/ (n1 – n2)` gforth-1.0 “dfloat-divide”

`sfaligned (c-addr – sf-addr)` floating-ext “s-f-aligned”

sf-addr is the first single-float-aligned address greater than or equal to *c-addr*.

`dfloats (n1 – n2)` floating-ext “d-floats”

n2 is the number of address units of *n1* double-precision IEEE floating-point numbers.

`dfloat+ (df-addr1 – df-addr2)` floating-ext “d-float-plus”

1 dfloats +.

`dfloat/ (n1 – n2)` gforth-1.0 “sfloat-divide”

`dfaligned (c-addr – df-addr)` floating-ext “d-f-aligned”

df-addr is the first double-float-aligned address greater than or equal to *c-addr*.

`maxaligned (addr1 – addr2)` gforth-0.2 “maxaligned”

addr2 is the first address after *addr1* that satisfies all alignment restrictions. maxaligned”

`cfaligned (addr1 – addr2)` gforth-0.2 “cfaligned”

addr2 is the first address after *addr1* that is aligned for a code field (i.e., such that the corresponding body is maxaligned).

`naligned (addr1 n – addr2)` gforth-0.5 “naligned”

addr2 is the aligned version of *addr1* with respect to the alignment *n*.

`waligned (addr – addr')` gforth-1.0 “waligned”

`laligned (addr – addr')` gforth-1.0 “laligned”

`xaligned (addr – addr')` gforth-1.0 “xaligned”

The following environmental queries may be useful to those who want to write software portable to non-byte-addressed machines.

`ADDRESS-UNIT-BITS (– n)` environment “ADDRESS-UNIT-BITS”

Size of one address unit, in bits.

`/w (- u) gforth-0.7 “slash-w”`

address units for a 16-bit value

`/l (- u) gforth-0.7 “slash-l”`

address units for a 32-bit value

`/x (- u) gforth-1.0 “slash-x”`

address units for a 64-bit value

6.7.7 Memory Blocks

Memory blocks often represent character strings; For ways of storing character strings in memory see Section 6.8.2 [String representations], page 78. For other string-processing words see Section 6.20.5 [Displaying characters and strings], page 154.

A few of these words work on address unit blocks. In that case, you usually have to insert **CHARS** before the word when working on character strings. Most words work on character blocks, and expect a char-aligned address.

When copying characters between overlapping memory regions, use **chars move** or choose carefully between **cmove** and **cmove>**.

move (*c-from c-to ucount* -) core “move”

Copy the contents of *ucount* aus at *c-from* to *c-to*. **move** works correctly even if the two areas overlap.

erase (*addr u* -) core-ext “erase”

Clear all bits in *u* aus starting at *addr*.

cmove (*c-from c-to u* -) string “c-move”

Copy the contents of *ucount* characters from data space at *c-from* to *c-to*. The copy proceeds **char-by-char** from low address to high address; i.e., for overlapping areas it is safe if *c-to* ≤ *c-from*.

cmove> (*c-from c-to u* -) string “c-move-up”

Copy the contents of *ucount* characters from data space at *c-from* to *c-to*. The copy proceeds **char-by-char** from high address to low address; i.e., for overlapping areas it is safe if *c-to* ≥ *c-from*.

fill (*c-addr u c* -) core “fill”

Store *c* in *u* chars starting at *c-addr*.

blank (*c-addr u* -) string “blank”

Store the space character into *u* chars starting at *c-addr*.

compare (*c-addr1 u1 c-addr2 u2* - *n*) string “compare”

Compare two strings lexicographically, based on the values of the bytes in the strings (i.e., case-sensitive and without locale-specific collation order orderings). If they are equal, *n* is 0; if the first string is smaller, *n* is -1; if the first string is larger, *n* is 1.

bounds (*addr u* - *addr+u addr*) gforth-0.2 “bounds”

Given a memory block represented by starting address *addr* and length *u* in aus, produce the end address *addr+u* and the start address in the right order for **u+do** or **?do**.

pad (- *c-addr*) core-ext “pad”

c-addr is the address of a transient region that can be used as temporary data storage. At least 84 characters of space is available.

6.8 Strings and Characters

6.8.1 Characters

Forth supports chars (aka bytes), used by words such as `c@`; these can be used to represent an ASCII character.

Forth also supports extended characters, which may be represented by a sequence of several bytes (i.e., several chars). A common character encoding is the UTF-8 representation of Unicode.

In general, most code does not have to worry about extended characters: In the string representation it does not matter whether a byte is a part of an extended character, or it is a character by itself, and words that consume chars (like `emit`) also work when the extended character is transferred as a sequence of chars. Forth still provides words for dealing with extended characters (see Section 6.20.10 [Xchars and Unicode], page 159).

In Unicode terms, chars are *code units*, whereas extended characters are *code points*. Note that an Unicode *abstract character* can consist of a sequence of code points, but Forth (like other programming languages) has no data type for individual abstract characters; of course, they can be represented as strings.

You can use the usual integer words on chars and Xchars on the stack, but Gforth also has some words for dealing with chars on the stack:

toupper (*c1* – *c2*) gforth-0.2 “toupper”

If *c1* is a lower-case ASCII character, *c2* is the equivalent upper-case character, otherwise *c2* is *c1*.

6.8.2 String representations

Forth commonly represents strings as cell pair *c-addr u* on the stack; *u* is the length of the string in bytes (aka chars), and *c-addr* is the address of the first byte of the string. Note that a code point may be represented by a sequence of several chars in the string (and a Unicode “abstract character” may consist of several code points). See Section 6.8.4 [String words], page 80.

Another string representation is used with the string library of words containing `$`. It represents the string on the stack through the address of a cell-sized string handle, which can be located in, e.g., a variable. See Section 6.8.5 [\$string words], page 81.

A legacy string representation are *counted strings*, represented on the stack by *c-addr*. The char addressed by *c-addr* contains a character-count, *n*, of the string and the string occupies the subsequent *n* char addresses in memory. Counted strings are limited to 255 bytes in length. While counted strings may look attractive due to needing only one stack item, due to their limitations we recommend avoiding them, especially as input parameters of words. See Section 6.8.6 [Counted string words], page 84.

6.8.3 String and Character literals

The nicest way to write a string literal is to write it as `"STRING"`. You can use the same \-escapes inside as for `s\`. However, this way is non-standard, so you may want to use one of the following words for improved portability:

`s\` (*compilation* '*ccc*' - ; *run-time* - *c-addr u*) core-ext,file-ext "s-backslash-quote"

Like `S`, but translates C-like \-escape-sequences, as follows: `\a` BEL (alert), `\b` BS, `\e` ESC (not in C99), `\f` FF, `\n` newline, `\r` CR, `\t` HT, `\v` VT, `\"` ", `\\` \, `\[0-7]{1,3}` octal numerical character value (non-standard), `\x[0-9a-f]{0,2}` hex numerical character value (standard only with two digits), `\u[0-9a-f]{4}` for unicode codepoints (auto-merges surrogate pairs), `\U[0-9a-f]{8}` for extended unicode code points; a `\` before any other character is reserved.

Note that `\xXX` produces raw bytes, while `\uXXXX` and `\UXXXXXXXX` produce code points for the current encoding. E.g., if we use UTF-8 encoding and want to encode ä (code point U+00E4), you can write the letter ä itself, or write `\xc3\xa4` (the UTF-8 bytes for this code point), `\u00e4`, or `\U000000e4`.

Note that, unlike in C, `\n` produces the preferred newline sequence for the host OS, which may consist of several chars. I.e., `"\n"` is equivalent to `newline`.

`S` (*compilation* '*ccc*' - ; *run-time* - *c-addr u*) core,file "s-quote"

Compilation: Parse a string *ccc* delimited by a `"` (double quote). At run-time, return the length, *u*, and the start address, *c-addr* of the string. Interpretation: parse the string as before, and return *c-addr*, *u*. Gforth **allocates** the string. The resulting memory leak is usually not a problem; the exception is if you create strings containing `S` and **evaluate** them; then the leak is not bounded by the size of the interpreted files and you may want to **free** the strings. Forth-2012 only guarantees two buffers of 80 characters each, so in standard programs you should assume that the string lives only until the next-but-one `s`.

Likewise, You can get the code *xc* of a character *C* with `'C'`. This way has been standardized since Forth-2012. An older way to get it is to use one of the following words:

`char` ('*<spaces>ccc*' - *c*) core,xchar-ext "char"

Skip leading spaces. Parse the string *ccc* and return *c*, the display code representing the first character of *ccc*.

`[char]` ('*<spaces>ccc*' - ; *run-time* - *c*) core,xchar-ext "bracket-char"

Compilation: skip leading spaces. Parse the string *ccc*. Run-time: return *c*, the display code representing the first character of *ccc*. Interpretation semantics for this word are undefined. Parse *ccc*, delimited by the string *c-addr1 u1*, in the parse area. *c-addr2 u2* specifies the parsed string within the parse area. If the parse area was empty, *u2* is 0. Parse *ccc*, delimited by *xchar*, in the parse area. *c-addr u* specifies the parsed string within the parse area. If the parse area was empty, *u* is 0.

You usually use `char` outside and `[char]` inside colon definitions, or you just use `'C'`.

Note that, e.g.,

`"C" type`

is (slightly) more efficient than

`'C' xemit`

because the latter converts the code point into a sequence of bytes and individually **emits** them. Similarly, dealing with general characters is usually more efficient when representing them as strings rather than code points.

There are the following words for producing commonly-used characters and strings that cannot be produced with `S"` or `'C'`:

newline (*- c-addr u*) gforth-0.5 “newline”

String containing the newline sequence of the host OS

bl (*- c-char*) core “b-l”

c-char is the character value for a space.

#tab (*- c*) gforth-0.2 “number-tab”

#lf (*- c*) gforth-0.2 “number-l-f”

#cr (*- c*) gforth-0.2 “number-c-r”

#ff (*- c*) gforth-0.2 “number-f-f”

#bs (*- c*) gforth-0.2 “number-b-s”

#del (*- c*) gforth-0.2 “number-del”

#bell (*- c*) gforth-0.2 “number-bell”

#esc (*- c*) gforth-0.5 “number-esc”

#eof (*- c*) gforth-0.7 “number-e-o-f”

actually EOT (ASCII code 4 aka `^D`)

6.8.4 String words

Words that are used for memory blocks are also useful for strings, so for words that move, copy, compare and search strings, see Section 6.7.7 [Memory Blocks], page 77. For words that display characters and strings, see Section 6.20.5 [Displaying characters and strings], page 154.

capscompare (*c-addr1 u1 c-addr2 u2 - n*) gforth-0.7 “capscompare”

Compare two strings lexicographically, based on the values of the bytes in the strings, but comparing ASCII characters case-insensitively, and non-ASCII characters case-sensitively and without locale-specific collation order. If they are equal, *n* is 0; if the first string is smaller, *n* is -1; if the first string is larger, *n* is 1.

str= (*c-addr1 u1 c-addr2 u2 - f*) gforth-0.6 “str-equals”

str< (*c-addr1 u1 c-addr2 u2 - f*) gforth-0.6 “str-less-than”

string-prefix? (*c-addr1 u1 c-addr2 u2 - f*) gforth-0.6 “string-prefix-question”

Is *c-addr2 u2* a prefix of *c-addr1 u1*?

string-suffix? (*c-addr1 u1 c-addr2 u2 - f*) gforth-1.0 “string-suffix-question”

Is *c-addr2 u2* a suffix of *c-addr1 u1*?

search (*c-addr1 u1 c-addr2 u2 - c-addr3 u3 flag*) string “search”

Search the string specified by *c-addr1, u1* for the string specified by *c-addr2, u2*. If *flag* is true: match was found at *c-addr3* with *u3* characters remaining. If *flag* is false: no match was found; *c-addr3, u3* are equal to *c-addr1, u1*.

scan (*c-addr1 u1 c - c-addr2 u2*) gforth-0.2 “scan”

Skip all characters not equal to *c*. The result starts with *c* or is empty. **Scan** is limited to single-byte (ASCII) characters. Use **search** to search for multi-byte characters.

skip (*c-addr1 u1 c - c-addr2 u2*) gforth-0.2 “skip”

Skip all characters equal to *c*. The result starts with the first non-*c* character, or it is empty. **Scan** is limited to single-byte (ASCII) characters.

-trailing (*c-addr u1 - c-addr u2*) string “dash-trailing”

Adjust the string specified by *c-addr, u1* to remove all trailing spaces. *u2* is the length of the modified string.

/string (*c-addr1 u1 n - c-addr2 u2*) string “slash-string”

Adjust the string specified by *c-addr1, u1* to remove *n* characters from the start of the string.

safe/string (*c-addr1 u1 n - c-addr2 u2*) gforth-1.0 “safe-slash-string”

Adjust the string specified by *c-addr1, u1* to remove *n* characters from the start of the string. Unlike **/string**, **safe/string** removes at least 0 and at most *u1* characters.

delete (*buffer size u -*) gforth-0.7 “delete”

deletes the first *u* bytes from a buffer and fills the rest at the end with blanks.

insert (*string length buffer size -*) gforth-0.7 “insert”

inserts a string at the front of a buffer. The remaining bytes are moved on.

6.8.5 \$string words

The following string library stores strings in ordinary cell-size variables (string handles). These handles contain a pointer to a cell-counted string allocated from the heap. The string library originates from bigFORTH.

Because there is only one permanent reference to the contents (the one in the handle), the string can be relocated or deleted without worrying about dangling references; this requires that the programmer uses references produced by, e.g., **\$@** only for temporary purposes, i.e., these references are not passed out, e.g., as return values or stored in global memory, and words that may change the handle are not called while these references exist.

This library is complemented by the cell-pair representation: You use the \$string words for variable strings which are cumbersome with the *c-addr u* representation. You use the cell-pair representation for processing (e.g., inspecting) strings while they do not change.

\$! (*addr1 u \$addr -*) gforth-0.7 “string-store”

stores a newly allocated string buffer at an address, frees the previous buffer if necessary.

\$@ (*\$addr - addr2 u*) gforth-0.7 “string-fetch”

returns the stored string.

\$@len (*\$addr - u*) gforth-0.7 “string-fetch-len”

returns the length of the stored string.

\$!len (*u \$addr -*) gforth-0.7 “string-store-len”

changes the length of the stored string. Therefore we must change the memory area and adjust address and count cell as well.

\$+!len (*u \$addr - addr*) gforth-1.0 “string-plus-store-len”

make room for *u* bytes at the end of the memory area referenced by *\$addr*; *addr* is the address of the first of these bytes.

\$del (*addr off u* –) gforth-0.7 “string-del”

deletes *u* bytes from a string with offset *off*.

\$ins (*addr1 u \$addr off* –) gforth-0.7 “string-ins”

inserts a string at offset *off*.

\$+! (*addr1 u \$addr* –) gforth-0.7 “string-plus-store”

appends a string to another.

c\$+! (*char \$addr* –) gforth-1.0 “c-string-plus-store”

append a character to a string.

\$free (*\$addr* –) gforth-1.0 “string-free”

free the string pointed to by *addr*, and set *addr* to 0

\$init (*\$addr* –) gforth-1.0 “string-init”

store an empty string there, regardless of what was in before

\$split (*addr u char – addr1 u1 addr2 u2*) gforth-0.7 “string-split”

divides a string into two, with one *char* as separator (e.g. ‘?’ for arguments in an HTML query)

\$iter (*.. \$addr char xt – ..*) gforth-0.7 “string-iter”

takes a string apart piece for piece, also with a character as separator. For each part a passed token will be called. With this you can take apart arguments – separated with ‘&’ – at ease.

\$over (*addr u \$addr off* –) gforth-1.0 “string-over”

overwrite string at offset *off* with *addr u*

\$exec (*xt addr* –) gforth-1.0 “string-exec”

execute *xt* while the standard output (TYPE, EMIT, and everything that uses them) is appended to the string variable *addr*.

\$tmp (*xt – addr u*) gforth-1.0 “string-t-m-p”

generate a temporary string from the output of a word slurp a file *fid* into a string *addr2*, append mode

\$. (*addr* –) gforth-1.0 “string-dot”

print a string, shortcut

\$slurp (*fid addr* –) gforth-1.0 “string-slurp”

slurp a file *fid* into a string *addr2*

\$slurp-file (*addr1 u1 addr2* –) gforth-1.0 “string-slurp-file”

slurp a named file *addr1 u1* into a string *addr2*

\$[] (*u \$[]addr – addr*) gforth-1.0 “string-array”

index into the string array and return the address at index *u* The array will be resized as needed

\$[]! (*addr u n \$[]addr* –) gforth-1.0 “string-array-store”

store a string into an array at index n

`$[]+!` ($addr$ u n `$[]` $addr$ -) gforth-1.0 “string-array-plus-store”

add a string to the string at index n

`$[]@` (n `$[]` $addr$ - $addr$ u) gforth-1.0 “string-array-fetch”

fetch a string from array index n — return the zero string if empty, and don’t accidentally grow the array.

`$[]#` ($addr$ - len) gforth-1.0 “string-array-num”

return the number of elements in an array

`$[]map` ($addr$ xt -) gforth-1.0 “string-array-map”

execute xt for all elements of the string array $addr$. xt is ($addr$ u -), getting one string at a time

`$[]slurp` (fid $addr$ -) gforth-1.0 “string-array-slurp”

slurp a file fid line by line into a string array $addr$

`$[]slurp-file` ($addr$ u `$[]` $addr$ -) gforth-1.0 “string-array-slurp-file”

slurp a named file $addr$ u line by line into a string array `$[]` $addr$

`$[].` ($addr$ -) gforth-1.0 “string-array-dot”

print all array entries

`$[]free` ($addr$ -) gforth-1.0 “string-array-free”

$addr$ contains the address of a cell-counted string that contains the addresses of a number of cell-counted strings; `$[]free` frees these strings, frees the array, and sets $addr$ to 0

`$save` (`$[]` $addr$ -) gforth-1.0 “string-save”

push string to dictionary for savesys

`$[]save` ($addr$ -) gforth-1.0 “string-array-save”

push string array to dictionary for savesys

`$boot` (`$[]` $addr$ -) gforth-1.0 “string-boot”

take string from dictionary to allocated memory. clean dictionary afterwards.

`$[]boot` ($addr$ -) gforth-1.0 “string-array-boot”

take string array from dictionary to allocated memory

`$saved` ($addr$ -) gforth-1.0 “string-saved”

mark an address as booted/saved

`$[]saved` ($addr$ -) gforth-1.0 “string-array-saved”

mark an address as booted/saved

`$Variable` (-) gforth-1.0 “string-variable”

A string variable which is preserved across savesystem

`$[]Variable` (-) gforth-1.0 “string-array-variable”

A string variable which is preserved across savesystem

6.8.6 Counted string words

count (*c-addr1* – *c-addr2* *u*) core “count”

c-addr2 is the first character and *u* the length of the counted string at *c-addr1*.

The following word has no useful interpretation semantics (unlike **s**) and no interpretive counterpart (unlike **[char]**), so you should use it only inside colon definitions (if at all):

C (*compilation* “*ccc*<quote>” – ; *run-time* – *c-addr*) core-ext “c-quote”

Compilation: parse a string *ccc* delimited by a " (double quote). At run-time, return *c-addr* which specifies the counted string *ccc*. Interpretation semantics are undefined.

6.9 Control Structures

Control structures in Forth cannot be used interpretively, only in a colon definition³. We do not like this limitation, but have not seen a satisfying way around it yet, although many schemes have been proposed.

6.9.1 Selection

```
flag
IF
  code
ENDIF
```

If *flag* is non-zero (as far as IF etc. are concerned, a cell with any bit set represents truth) *code* is executed.

```
flag
IF
  code1
ELSE
  code2
ENDIF
```

If *flag* is true, *code1* is executed, otherwise *code2* is executed.

You can use **THEN** instead of **ENDIF**. Indeed, **THEN** is standard, and **ENDIF** is not, although it is quite popular. We recommend using **ENDIF**, because it is less confusing for people who also know other languages (and is not prone to reinforcing negative prejudices against Forth in these people). Adding **ENDIF** to a system that only supplies **THEN** is simple:

```
: ENDIF  POSTPONE then ; immediate
```

[According to *Webster’s New Encyclopedic Dictionary*, *then* (*adv.*) has the following meanings:

... 2b: following next after in order ... 3d: as a necessary consequence (if you were there, then you saw them).

Forth’s **THEN** has the meaning 2b, whereas **THEN** in Pascal and many other programming languages has the meaning 3d.]

³ To be precise, they have no interpretation semantics (see Section 6.11 [Interpretation and Compilation Semantics], page 115).

Gforth also provides the words `?DUP-IF` and `?DUP-0=-IF`, so you can avoid using `?dup`. Using these alternatives is also more efficient than using `?dup`. Definitions in Standard Forth for `ENDIF`, `?DUP-IF` and `?DUP-0=-IF` are provided in `compat/control.fs`.

```
x
CASE
  x1 OF code1 ENDOF
  x2 OF code2 ENDOF
  ...
  ( x ) default-code ( x )
ENDCASE ( )
```

Executes the first *codei*, where the *xi* is equal to *x*. If no *xi* matches, the optional *default-code* is executed. The optional default case can be added by simply writing the code after the last `ENDOF`. It may use *x*, which is on top of the stack, but must not consume it. The value *x* is consumed by this construction (either by an `OF` that matches, or by the `ENDCASE`, if no `OF` matches). Example:

```
: num-name ( n -- c-addr u )
  case
    0 of s" zero " endof
    1 of s" one " endof
    2 of s" two " endof
    \ default case:
    s" other number"
    rot \ get n on top so ENDCASE can drop it
  endcase ;
```

You can also use (the non-standard) `?of` to use `case` as a general selection structure for more than two alternatives. `?Of` takes a flag. Example:

```
: sgn ( n1 -- n2 )
  \ sign function
  case
dup 0< ?of drop -1 endof
dup 0> ?of drop 1 endof
dup \ n1=0 -> n2=0; dup an item, to be consumed by ENDCASE
  endcase ;
```

Programming style note: To keep the code understandable, you should ensure that you change the stack in the same way (wrt. number and types of stack items consumed and pushed) on all paths through a selection structure.

6.9.2 Simple Loops

```
BEGIN
  code1
  flag
WHILE
  code2
REPEAT
```


code1 is executed and *flag* is computed. If it is true, *code2* is executed and the loop is restarted; If *flag* is false, execution continues after the **REPEAT**.

```
BEGIN
  code
  flag
UNTIL
```

code is executed. The loop is restarted if **flag** is false.

Programming style note: To keep the code understandable, a complete iteration of the loop should not change the number and types of the items on the stacks.

```
BEGIN
  code
AGAIN
```

This is an endless loop.

6.9.3 Counted Loops

The basic counted loop is:

```
limit start
?DO
  body
LOOP
```

This performs one iteration for every integer, starting from *start* and up to, but excluding *limit*. The counter, or *index*, can be accessed with **i**. For example, the loop:

```
10 0 ?DO
  i .
LOOP
```

prints 0 1 2 3 4 5 6 7 8 9

The index of the innermost loop can be accessed with **i**, the index of the next loop with **j**, and the index of the third loop with **k**.

i (*R:n* – *R:n* *n*) core “i”

n is the index of the innermost counted loop.

j (*R:n* *R:w1* *R:w2* – *n* *R:n* *R:w1* *R:w2*) core “j”

n is the index of the next-to-innermost counted loop.

k (*R:n* *R:w1* *R:w2* *R:w3* *R:w4* – *n* *R:n* *R:w1* *R:w2* *R:w3* *R:w4*) gforth-0.3 “k”

n is the index of the third-innermost counted loop.

i’ (*R:w* *R:w2* – *R:w* *R:w2* *w*) gforth-0.2 “i-tick”

The limit of the innermost counted loop; can also be used to access the second item on the return stack

The loop control data are kept on the return stack, so there are some restrictions on mixing return stack accesses and counted loop words. In particular, if you put values on the return stack outside the loop, you cannot read them inside the loop⁴. If you put values

⁴ well, not in a way that is portable.

on the return stack within a loop, you have to remove them before the end of the loop and before accessing the index of the loop.

There are several variations on the counted loop:

- **LEAVE** leaves the innermost counted loop immediately; execution continues after the associated **LOOP** or **NEXT**. For example:

```
10 0 ?DO i DUP . 3 = IF LEAVE THEN LOOP
```

prints 0 1 2 3

- **UNLOOP** prepares for an abnormal loop exit, e.g., via **EXIT**. **UNLOOP** removes the loop control parameters from the return stack so **EXIT** can get to its return address. For example:

```
: demo 10 0 ?DO i DUP . 3 = IF UNLOOP EXIT THEN LOOP ." Done" ;
```

prints 0 1 2 3

- If *start* is greater than *limit*, a **?DO** loop is entered (and **LOOP** iterates until they become equal by wrap-around arithmetic). This behaviour is usually not what you want. Therefore, Gforth offers **+DO** and **U+DO** (as replacements for **?DO**), which do not enter the loop if *start* is greater than *limit*; **+DO** is for signed loop parameters, **U+DO** for unsigned loop parameters.
- **?DO** can be replaced by **DO**. **DO** always enters the loop, independent of the loop parameters. Do not use **DO**, even if you know that the loop is entered in any case. Such knowledge tends to become invalid during maintenance of a program, and then the **DO** will make trouble.
- **LOOP** can be replaced with **n+LOOP**; this updates the index by *n* instead of by 1. The loop is terminated when the border between *limit-1* and *limit* is crossed. E.g.:

```
4 0 +DO i . 2 +LOOP
```

prints 0 2

```
4 1 +DO i . 2 +LOOP
```

prints 1 3

- The behaviour of **n+LOOP** is peculiar when *n* is negative:

```
-1 0 ?DO i . -1 +LOOP
```

prints 0 -1

```
0 0 ?DO i . -1 +LOOP
```

prints nothing.

Therefore we recommend avoiding **n+LOOP** with negative *n*. One alternative is **u-LOOP**, which reduces the index by *u* each iteration. The loop is terminated when the border between *limit+1* and *limit* is crossed. Gforth also provides **-DO** and **U-DO** for down-counting loops. E.g.:

```
-2 0 -DO i . 1 -LOOP
```

prints 0 -1

```
-1 0 -DO i . 1 -LOOP
```

prints 0

```
0 0 -DO i . 1 -LOOP
```

prints nothing.

Unfortunately, `+DO`, `U+DO`, `-DO`, `U-DO` and `-LOOP` are not defined in Standard Forth. However, an implementation for these words that uses only standard words is provided in `compat/loops.fs`.

Another counted loop is:

```

  n
  FOR
    body
  NEXT

```

This is the preferred loop of native code compiler writers who are too lazy to optimize `?DO` loops properly. This loop structure is not defined in Standard Forth. In Gforth, this loop iterates $n+1$ times; it produces values starting with n and ending with 0. Other Forth systems may behave differently, even if they support `FOR` loops. To avoid problems, don't use `FOR` loops.

6.9.4 Begin loops with multiple exits

For counted loops, you can use `leave` in several places. For `begin` loops, you have the following options:

Use `exit` (possibly several times) in the loop to leave not just the loop, but the whole colon definition. E.g.,:

```

: foo
  begin
    condition1 while
      condition2 if
        exit-code2 exit then
      condition3 if
        exit-code3 exit then
    ...
  repeat
  exit-code1 ;

```

The disadvantage of this approach is that, if you want to have some common code afterwards, you either have to wrap `foo` in another word that contains the common code, or you have to call the common code several times, from each exit-code.

Another approach is to use several `whiles` in a `begin` loop. You have to append a `then` behind the loop for every additional `while`. E.g.,;

```

begin
  condition1 while
    condition2 while
      condition3 while
        again then then then

```

Here I used `again` at the end of the loop so that I would have a `then` for each `while`; `repeat` would result in one less `then`, but otherwise the same behaviour. For an explanation of why this works, See Section 6.9.6 [Arbitrary control structures], page 90.

We can have common code afterwards, but, as presented above, we cannot have different exit-codes for the different exits. You can have these different exit-codes, as follows:

```

begin

```

```

    condition1 while
      condition2 while
        condition3 while
      again then exit-code3
    else exit-code2 then
    else exit-code1 then

```

This is relatively hard to comprehend, because the exit-codes are relatively far from the exit conditions (it does not help that we are not used to such control structures, either).

6.9.5 General control structures with case

Gforth provides an extended **case** that solves the problems of the multi-exit loops discussed above, and offers additional options. You can find a portable implementation of this extended **case** in `compat/caseext.fs`.

There are three additional words in the extension. The first is **?of** which allows general tests (rather than just testing for equality) in a **case**; e.g.,

```

: sgn ( n -- -1|0|1 )
  ( n ) case
    dup 0 < ?of drop -1 endof
    dup 0 > ?of drop 1 endof
    \ otherwise leave the 0 on the stack
  0 endcase ;

```

Note that **endcase** drops a value, which works fine much of the time with **of**, but usually not with **?of**, so we leave a 0 on the stack for **endcase** to drop. The **n** that is passed into **sgn** is also 0 if neither **?of** triggers, and that is then passed out.

The second additional word is **next-case**, which allows turning **case** into a loop. Our triple-exit loop becomes:

```

case
  condition1 ?of exit-code1 endof
  condition2 ?of exit-code2 endof
  condition3 ?of exit-code3 endof
  ...
next-case
common code afterwards

```

As you can see, this solves both problems of the variants discussed above (see Section 6.9.4 [BEGIN loops with multiple exits], page 88). Note that **next-case** does not drop a value, unlike **endcase**.⁵

The last additional word is **contof**, which is used instead of **endof** and starts the next iteration instead of leaving the loop. This can be used in ways similar to Dijkstra's guarded command *do*, e.g.:

```

: gcd ( n1 n2 -- n )
  case
    2dup > ?of tuck - contof

```

⁵ **Next-case** has a **-**, unlike the other **case** words, because VFX Forth contains a **nextcase** that drops a value.

```

    2dup < ?of over - contof
  endcase ;

```

Here the two `?ofs` have different ways of continuing the loop; when neither `?of` triggers, the two numbers are equal and are the gcd. `Endcase` drops one of them, leaving the other as `n`.

You can also combine these words. Here's an example that uses each of the `case` words once, except `endcase`:

```

: collatz ( u -- )
  \ print the 3n+1 sequence starting at u until we reach 1
  case
    dup .
    1 of endof
      dup 1 and ?of 3 * 1+ contof
      2/
    next-case ;

```

This example keeps the current value of the sequence on the stack. If it is 1, the `of` triggers, drops the value, and leaves the `case` structure. For odd numbers, the `?of` triggers, computes $3n+1$, and starts the next iteration with `contof`. Otherwise, if the number is even, it is divided by 2, and the loop is restarted with `next-case`.

6.9.6 Arbitrary control structures

Standard Forth permits and supports using control structures in a non-nested way. Information about incomplete control structures is stored on the control-flow stack. This stack may be implemented on the Forth data stack, and this is what we have done in Gforth.

An *orig* entry represents an unresolved forward branch, a *dest* entry represents a backward branch target. A few words are the basis for building any control structure possible (except control structures that need storage, like calls, coroutines, and backtracking).

IF (*compilation* – *orig* ; *run-time* *f* –) core “IF”

At run-time, if $f=0$, execution continues after the **THEN** (or **ELSE**) that consumes the *orig*, otherwise right after the **IF** (see Section 6.9.1 [Selection], page 84).

AHEAD (*compilation* – *orig* ; *run-time* –) tools-ext “AHEAD”

At run-time, execution continues after the **THEN** that consumes the *orig*.

THEN (*compilation* *orig* – ; *run-time* –) core “THEN”

The **IF**, **AHEAD**, **ELSE** or **WHILE** that pushed *orig* jumps right after the **THEN** (see Section 6.9.1 [Selection], page 84).

BEGIN (*compilation* – *dest* ; *run-time* –) core “BEGIN”

The **UNTIL**, **AGAIN** or **REPEAT** that consumes the *dest* jumps right behind the **BEGIN** (see Section 6.9.2 [Simple Loops], page 85).

UNTIL (*compilation* *dest* – ; *run-time* *f* –) core “UNTIL”

At run-time, if $f=0$, execution continues after the **BEGIN** that produced *dest*, otherwise right after the **UNTIL** (see Section 6.9.2 [Simple Loops], page 85).

AGAIN (*compilation* *dest* – ; *run-time* –) core-ext “AGAIN”

At run-time, execution continues after the **BEGIN** that produced the *dest* (see Section 6.9.2 [Simple Loops], page 85).

CS-PICK (*orig0/dest0 orig1/dest1 ... origu/destu u - ... orig0/dest0*) tools-ext “c-s-pick”

CS-ROLL (*destu/origu .. dest0/orig0 u - .. dest0/orig0 destu/origu*) tools-ext “c-s-roll”

CS-DROP (*dest -*) gforth-1.0 “CS-DROP”

The Standard words **CS-PICK** and **CS-ROLL** allow you to manipulate the control-flow stack in a portable way. Without them, you would need to know how many stack items are occupied by a control-flow entry (many systems use one cell. In Gforth they currently take three, but this may change in the future).

CS-PICK can only pick a *dest* and **CS-DROP** can only drop a *dest*, because an *orig* must be resolved exactly once.

Some standard control structure words are built from these words:

ELSE (*compilation orig1 - orig2 ; run-time -*) core “ELSE”

At run-time, execution continues after the **THEN** that consumes the *orig*; the **IF**, **AHEAD**, **ELSE** or **WHILE** that pushed *orig1* jumps right after the **ELSE**. (see Section 6.9.1 [Selection], page 84).

WHILE (*compilation dest - orig dest ; run-time f -*) core “WHILE”

At run-time, if *f*=0, execution continues after the **REPEAT** (or **THEN** or **ELSE**) that consumes the *orig*, otherwise right after the **WHILE** (see Section 6.9.2 [Simple Loops], page 85).

REPEAT (*compilation orig dest - ; run-time -*) core “REPEAT”

At run-time, execution continues after the **BEGIN** that produced the *dest*; the **WHILE**, **IF**, **AHEAD** or **ELSE** that pushed *orig* jumps right after the **REPEAT**. (see Section 6.9.2 [Simple Loops], page 85).

Gforth adds some more control-structure words:

ENDIF (*compilation orig - ; run-time -*) gforth-0.2 “ENDIF”

Same as **THEN**.

?dup-IF (*compilation - orig ; run-time n - n|*) gforth-0.2 “question-dupe-if”

This is the preferred alternative to the idiom “**?DUP IF**”, since it can be better handled by tools like stack checkers. Besides, it’s faster.

?DUP-0==IF (*compilation - orig ; run-time n - n|*) gforth-0.2 “question-dupe-zero-equals-if”

Counted loop words constitute a separate group of words:

?DO (*compilation - do-sys ; run-time w1 w2 - | loop-sys*) core-ext “question-do”

See Section 6.9.3 [Counted Loops], page 86.

+DO (*compilation - do-sys ; run-time n1 n2 - | loop-sys*) gforth-0.2 “plus-do”

See Section 6.9.3 [Counted Loops], page 86.

U+DO (*compilation - do-sys ; run-time u1 u2 - | loop-sys*) gforth-0.2 “u-plus-do”

See Section 6.9.3 [Counted Loops], page 86.

-DO (*compilation - do-sys ; run-time n1 n2 - | loop-sys*) gforth-0.2 “minus-do”

See Section 6.9.3 [Counted Loops], page 86.

U-DO (*compilation - do-sys ; run-time u1 u2 - | loop-sys*) gforth-0.2 “u-minus-do”

See Section 6.9.3 [Counted Loops], page 86.

DO (*compilation* – *do-sys* ; *run-time* *w1 w2* – *loop-sys*) core “DO”

See Section 6.9.3 [Counted Loops], page 86.

FOR (*compilation* – *do-sys* ; *run-time* *u* – *loop-sys*) gforth-0.2 “FOR”

See Section 6.9.3 [Counted Loops], page 86.

LOOP (*compilation* *do-sys* – ; *run-time* *loop-sys1* – | *loop-sys2*) core “LOOP”

See Section 6.9.3 [Counted Loops], page 86.

+LOOP (*compilation* *do-sys* – ; *run-time* *loop-sys1 n* – | *loop-sys2*) core “plus-loop”

See Section 6.9.3 [Counted Loops], page 86.

-LOOP (*compilation* *do-sys* – ; *run-time* *loop-sys1 u* – | *loop-sys2*) gforth-0.2 “minus-loop”

See Section 6.9.3 [Counted Loops], page 86.

NEXT (*compilation* *do-sys* – ; *run-time* *loop-sys1* – | *loop-sys2*) gforth-0.2 “NEXT”

See Section 6.9.3 [Counted Loops], page 86.

LEAVE (*compilation* – ; *run-time* *loop-sys* –) core “LEAVE”

See Section 6.9.3 [Counted Loops], page 86.

?LEAVE (*compilation* – ; *run-time* *f* | *f loop-sys* –) gforth-0.2 “question-leave”

See Section 6.9.3 [Counted Loops], page 86.

unloop (*R:w1 R:w2* –) core “unloop”

DONE (*compilation* *orig* – ; *run-time* –) gforth-0.2 “DONE”

resolves all LEAVES up to the compilation orig (from a BEGIN)

The standard does not allow using CS-PICK and CS-ROLL on *do-sys*. Gforth allows it, but it’s your job to ensure that for every ?DO etc. there is exactly one UNLOOP on any path through the definition (LOOP etc. compile an UNLOOP on the fall-through path). Also, you have to ensure that all LEAVES are resolved (by using one of the loop-ending words or DONE).

Another group of control structure words are:

case (*compilation* – *case-sys* ; *run-time* –) core-ext “case”

Start a **case** structure.

endcase (*compilation* *case-sys* – ; *run-time* *x* –) core-ext “end-case”

Finish the **case** structure; drop *x*, and continue behind the **endcase**. Dropping *x* is useful in the original **case** construct (with only **ofs**), but you may have to supply an *x* in other cases (especially when using **?of**).

next-case (*compilation* *case-sys* – ; *run-time* –) gforth-1.0 “next-case”

Restart the **case** loop by jumping to the matching **case**. Note that **next-case** does not drop a cell, unlike **endcase**.

of (*compilation* – *of-sys* ; *run-time* *x1 x2* – | *x1*) core-ext “of”

If *x1*=*x2*, continue (dropping both); otherwise, leave *x1* on the stack and jump behind **endof** or **contof**.

?of (*compilation* – *of-sys* ; *run-time* *f* –) gforth-1.0 “question-of”

If *f* is true, continue; otherwise, jump behind **endof** or **contof**.

endof (*compilation* *case-sys1 of-sys* – *case-sys2* ; *run-time* –) core-ext “end-of”

Exit the enclosing **case** structure by jumping behind **endcase/next-case**.

contof (*compilation case-sys1 of-sys – case-sys2 ; run-time –*) gforth-1.0 “cont-of”

Restart the **case** loop by jumping to the enclosing **case**.

Internally, *of-sys* is an **orig**; and *case-sys* is a cell and some stack-depth information, 0 or more **origs**, and a **dest**.

6.9.6.1 Programming Style

In order to ensure readability we recommend that you do not create arbitrary control structures directly, but define new control structure words for the control structure you want and use these words in your program. For example, instead of writing:

```
BEGIN
...
IF [ 1 CS-ROLL ]
...
AGAIN THEN
```

we recommend defining control structure words, e.g.,

```
: WHILE ( DEST -- ORIG DEST )
  POSTPONE IF
  1 CS-ROLL ; immediate

: REPEAT ( orig dest -- )
  POSTPONE AGAIN
  POSTPONE THEN ; immediate
```

and then using these to create the control structure:

```
BEGIN
...
WHILE
...
REPEAT
```

That’s much easier to read, isn’t it? Of course, **REPEAT** and **WHILE** are predefined, so in this example it would not be necessary to define them.

6.9.7 Calls and returns

A definition can be called simply by writing the name of the definition to be called. Normally a definition is invisible during its own definition. If you want to write a directly recursive definition, you can use **recursive** to make the current definition visible, or **recurse** to call the current definition directly.

recursive (*compilation – ; run-time –*) gforth-0.2 “recursive”

Make the current definition visible, enabling it to call itself recursively.

recurse (... – ...) core “recurse”

Alias to the current definition.

For examples of using these words, See Section 3.20 [Recursion Tutorial], page 23.

Programming style note: I prefer using **recursive** to **recurse**, because calling the definition by name is more descriptive (if the name is well-chosen) than the somewhat cryptic

recurse. E.g., in a quicksort implementation, it is much better to read (and think) “now sort the partitions” than to read “now do a recursive call”.

For mutual recursion, use **Deferred** words, like this:

```
Defer foo

: bar ( ... -- ... )
... foo ... ;

:noname ( ... -- ... )
... bar ... ;
IS foo
```

Deferred words are discussed in more detail in Section 6.10.10 [Deferred Words], page 112.

The current definition returns control to the calling definition when the end of the definition is reached or **EXIT** is encountered.

EXIT (*compilation - ; run-time nest-sys -*) core “EXIT”

Return to the calling definition; usually used as a way of forcing an early return from a definition. Before **EXIT**ing you must clean up the return stack and **UNLOOP** any outstanding **?DO...LOOP**s. Use **;s** for a tickable word that behaves like **exit** in the absence of locals.

;s (*R:w -*) gforth-0.2 “semis”

The primitive compiled by **EXIT**.

6.9.8 Exception Handling

If a word detects an error condition that it cannot handle, it can **throw** an exception. In the simplest case, this will terminate your program, and report an appropriate error.

throw (*y1 .. ym nerror - y1 .. ym / z1 .. zn error*) exception “throw”

If *nerror* is 0, drop it and continue. Otherwise, transfer control to the next dynamically enclosing exception handler, reset the stacks accordingly, and push *nerror*.

fast-throw (*... wball - ... wball*) gforth-experimental “fast-throw”

Lightweight **throw** variant: only for non-zero balls, and does not store a backtrace or deal with missing **catch**.

Throw consumes a cell-sized error number on the stack. There are some predefined error numbers in Standard Forth (see **errors.fs**). In Gforth (and most other systems) you can use the iors produced by various words as error numbers (e.g., a typical use of **allocate** is **allocate throw**). Gforth also provides the word **exception** to define your own error numbers (with decent error reporting); a Standard Forth version of this word (but without the error messages) is available in **compat/except.fs**. And finally, you can use your own error numbers (anything outside the range -4095..0), but won’t get nice error messages, only numbers. For example, try:

```
-10 throw          \ Standard defined
-267 throw         \ system defined
s" my error" exception throw \ user defined
7 throw           \ arbitrary number
```

exception (*addr u - n*) gforth-0.2 “exception”

n is a previously unused **throw** value in the range (-4095...-256). Consecutive calls to **exception** return consecutive decreasing numbers. Gforth uses the string *addr u* as an error message.

A common idiom to **THROW** a specific error if a flag is true is this:

```
( flag ) 0<> errno and throw
```

Your program can provide exception handlers to catch exceptions. An exception handler can be used to correct the problem, or to clean up some data structures and just throw the exception to the next exception handler. Note that **throw** jumps to the dynamically innermost exception handler. The system's exception handler is outermost, and just prints an error and restarts command-line interpretation (or, in batch mode (i.e., while processing the shell command line), leaves Gforth).

The Standard Forth way to catch exceptions is **catch**:

```
catch ( x1 .. xn xt - y1 .. ym 0 / z1 .. zn error ) exception "catch"
```

Executes *xt*. If execution returns normally, **catch** pushes 0 on the stack. If execution returns through **throw**, all the stacks are reset to the depth on entry to **catch**, and the TOS (the *xt* position) is replaced with the throw code.

```
nothrow ( - ) gforth-0.7 "nothrow"
```

Use this (or the standard sequence `['] false catch 2drop`) after a **catch** or **endtry** that does not rethrow; this ensures that the next **throw** will record a backtrace.

The most common use of exception handlers is to clean up the state when an error happens. E.g.,

```
base @ >r hex \ actually the HEX should be inside foo to protect
                \ against exceptions between HEX and CATCH
['] foo catch ( nerror|0 )
r> base !
( nerror|0 ) throw \ pass it on
```

A use of **catch** for handling the error **myerror** might look like this:

```
['] foo catch
CASE
  myerror OF ... ( do something about it ) nothrow ENDOF
  dup throw \ default: pass other errors on, do nothing on non-errors
ENDCASE
```

Having to wrap the code into a separate word is often cumbersome, therefore Gforth provides an alternative syntax:

```
TRY
  code1
IFERROR
  code2
THEN
  code3
ENDTRY
```

This performs *code1*. If *code1* completes normally, execution continues with *code3*. If there is an exception in *code1* or before **endtry**, the stacks are reset to the depth during

try, the throw value is pushed on the data stack, and execution continues at *code2*, and finally falls through to *code3*.

```
try ( compilation - orig ; run-time - R:sys1 ) gforth-0.5 "try"
```

Start an exception-catching region.

```
endtry ( compilation - ; run-time R:sys1 - ) gforth-0.5 "endtry"
```

End an exception-catching region.

```
iferror ( compilation orig1 - orig2 ; run-time - ) gforth-0.7 "iferror"
```

Starts the exception handling code (executed if there is an exception between **try** and **endtry**). This part has to be finished with **then**.

If you don't need *code2*, you can write **restore** instead of **iferror then**:

```
TRY
  code1
RESTORE
  code3
ENDTRY
```

The cleanup example from above in this syntax:

```
base @ { oldbase }
TRY
  hex foo \ now the hex is placed correctly
  0       \ value for throw
RESTORE
  oldbase base !
ENDTRY
throw
```

An additional advantage of this variant is that an exception between **restore** and **endtry** (e.g., from the user pressing **Ctrl-C**) restarts the execution of the code after **restore**, so the base will be restored under all circumstances.

However, you have to ensure that this code does not cause an exception itself, otherwise the **iferror/restore** code will loop. Moreover, you should also make sure that the stack contents needed by the **iferror/restore** code exist everywhere between **try** and **endtry**; in our example this is achieved by putting the data in a local before the **try** (you cannot use the return stack because the exception frame (*sys1*) is in the way there).

This kind of usage corresponds to Lisp's **unwind-protect**.

If you do not want this exception-restarting behaviour, you achieve this as follows:

```
TRY
  code1
ENDTRY-IFERROR
  code2
THEN
```

If there is an exception in *code1*, then *code2* is executed, otherwise execution continues behind the **then** (or in a possible **else** branch). This corresponds to the construct

```
TRY
  code1
```

```

RECOVER
  code2
ENDTRY

```

in Gforth before version 0.7. So you can directly replace **recover**-using code; however, we recommend that you check if it would not be better to use one of the other **try** variants while you are at it.

To ease the transition, Gforth provides two compatibility files: **endtry-iferror.fs** provides the **try ... endtry-iferror ... then** syntax (but not **iferror** or **restore**) for old systems; **recover-endtry.fs** provides the **try ... recover ... endtry** syntax on new systems, so you can use that file as a stopgap to run old programs. Both files work on any system (they just do nothing if the system already has the syntax it implements), so you can unconditionally **require** one of these files, even if you use a mix old and new systems.

restore (*compilation orig1 - ; run-time -*) gforth-0.7 “restore”

Starts restoring code, that is executed if there is an exception, and if there is no exception.

endtry-iferror (*compilation orig1 - orig2 ; run-time R:sys1 -*) gforth-0.7 “endtry-iferror”

End an exception-catching region while starting exception-handling code outside that region (executed if there is an exception between **try** and **endtry-iferror**). This part has to be finished with **then** (or **else...then**).

Here’s the error handling example:

```

TRY
  foo
ENDTRY-IFERROR
CASE
  myerror OF ... ( do something about it ) nothrow ENDOF
  throw \ pass other errors on
ENDCASE
THEN

```

Programming style note: As usual, you should ensure that the stack depth is statically known at the end: either after the **throw** for passing on errors, or after the **ENDTRY** (or, if you use **catch**, after the end of the selection construct for handling the error).

There are two alternatives to **throw**: **Abort** is conditional and you can provide an error message. **Abort** just produces an “Aborted” error.

The problem with these words is that exception handlers cannot differentiate between different **abort**’s; they just look like **-2 throw** to them (the error message cannot be accessed by standard programs). Similar **abort** looks like **-1 throw** to exception handlers.

ABORT (*compilation 'ccc' - ; run-time f -*) core,exception-ext “abort-quote”

If any bit of *f* is non-zero, perform the function of **-2 throw**, displaying the string *ccc* if there is no exception frame on the exception stack.

abort (*?? - ??*) core,exception-ext “abort”

-1 throw.

For problems that are not that awful that you need to abort execution, you can just display a warning. The variable **warnings** allows to tune how many warnings you see.

WARNING (*compilation 'ccc' - ; run-time f -*) gforth-1.0 “WARNING”

if *f* is non-zero, display the string *ccc* as warning message.

```
warnings ( - addr ) gforth-0.2 "warnings"
  set warnings level to
0          turns warnings off
-1         turns normal warnings on
-2         turns beginner warnings on
-3         pedantic warnings on
-4         turns warnings into errors (including beginner warnings)
```

6.10 Defining Words

Defining words are used to extend Forth by creating new entries in the dictionary.

6.10.1 CREATE

Defining words are used to create new entries in the dictionary. The simplest defining word is **CREATE**. **CREATE** is used like this:

```
CREATE new-word1
```

CREATE is a parsing word, i.e., it takes an argument from the input stream (**new-word1** in our example). It generates a dictionary entry for **new-word1**. When **new-word1** is executed, all that it does is leave an address on the stack. The address represents the value of the data space pointer (**HERE**) at the time that **new-word1** was defined. Therefore, **CREATE** is a way of associating a name with the address of a region of memory.

```
Create ( "name" - ) core "Create"
```

Note that Standard Forth guarantees only for **create** that its body is in dictionary data space (i.e., where **here**, **allot** etc. work, see Section 6.7.2 [Dictionary allocation], page 70). Also, in Standard Forth only **created** words can be modified with **does>** (see Section 6.10.9 [User-defined Defining Words], page 102). And in Standard Forth **>body** can only be applied to **created** words.

By extending this example to reserve some memory in data space, we end up with something like a *variable*. Here are two different ways to do it:

```
CREATE new-word2 1 cells allot \ reserve 1 cell - initial value undefined
CREATE new-word3 4 ,           \ reserve 1 cell and initialise it (to 4)
```

The variable can be examined and modified using **@** ("fetch") and **!** ("store") like this:

```
new-word2 @ . \ get address, fetch from it and display
1234 new-word2 ! \ new value, get address, store to it
```

A similar mechanism can be used to create arrays. For example, an 80-character text input buffer:

```
CREATE text-buf 80 chars allot
```

```
text-buf 0 chars + c@ \ the 1st character (offset 0)
text-buf 3 chars + c@ \ the 4th character (offset 3)
```

You can build arbitrarily complex data structures by allocating appropriate areas of memory. For further discussions of this, and to learn about some Gforth tools that make it easier, See Section 6.23 [Structures], page 173.

6.10.2 Variables

The previous section showed how a sequence of commands could be used to generate a variable. As a final refinement, the whole code sequence can be wrapped up in a defining word (pre-empting the subject of the next section), making it easier to create new variables:

```
: myvariableX ( "name" -- a-addr ) CREATE 1 cells allot ;
: myvariable0 ( "name" -- a-addr ) CREATE 0 , ;

myvariableX foo \ variable foo starts off with an unknown value
myvariable0 joe \ whilst joe is initialised to 0

45 3 * foo !    \ set foo to 135
1234 joe !      \ set joe to 1234
3 joe +!        \ increment joe by 3.. to 1237
```

Not surprisingly, there is no need to define `myvariable`, since Forth already has a definition `Variable`. Standard Forth does not guarantee that a `Variable` is initialised when it is created (i.e., it may behave like `myvariableX`). In contrast, Gforth's `Variable` initialises the variable to 0 (i.e., it behaves exactly like `myvariable0`). Forth also provides `2Variable` and `fvariable` for double and floating-point variables, respectively – they are initialised to 0. and 0e in Gforth. If you use a `Variable` to store a boolean, you can use `on` and `off` to toggle its state.

```
Variable ( "name" – ) core “Variable”
2Variable ( "name" – ) double “two-variable”
fvariable ( "name" – ) floating “f-variable”
```

The defining word `User` behaves in the same way as `Variable`. The difference is that it reserves space in *user (data) space* rather than normal data space. In a Forth system that has a multi-tasker, each task has its own set of user variables.

```
User ( "name" – ) gforth-0.2 “User”
```

6.10.3 Constants

`Constant` allows you to declare a fixed value and refer to it by name. For example:

```
12 Constant INCHES-PER-FOOT
3E+08 fconstant SPEED-O-LIGHT
```

A `Variable` can be both read and written, so its run-time behaviour is to supply an address through which its current value can be manipulated. In contrast, the value of a `Constant` cannot be changed once it has been declared⁶ so it's not necessary to supply the address – it is more efficient to return the value of the constant directly. That's exactly what happens; the run-time effect of a constant is to put its value on the top of the stack (You can find one way of implementing `Constant` in Section 6.10.9 [User-defined Defining Words], page 102).

Forth also provides `2Constant` and `fconstant` for defining double and floating-point constants, respectively.

```
Constant ( w "name" – ) core “Constant”
```

⁶ Well, often it can be – but not in a Standard, portable way. It's safer to use a `Value` (read on).

Define a constant *name* with value *w*.

name execution: – *w*

2Constant (*w1 w2 "name" –*) double “two-constant”

fconstant (*r "name" –*) floating “f-constant”

Constants in Forth behave differently from their equivalents in other programming languages. In other languages, a constant (such as an EQU in assembler or a #define in C) only exists at compile-time; in the executable program the constant has been translated into an absolute number and, unless you are using a symbolic debugger, it’s impossible to know what abstract thing that number represents. In Forth a constant has an entry in the header space and remains there after the code that uses it has been defined. In fact, it must remain in the dictionary since it has run-time duties to perform. For example:

```
12 Constant INCHES-PER-FOOT
: FEET-TO-INCHES ( n1 -- n2 ) INCHES-PER-FOOT * ;
```

When FEET-TO-INCHES is executed, it will in turn execute the xt associated with the constant INCHES-PER-FOOT. If you use **see** to decompile the definition of FEET-TO-INCHES, you can see that it makes a call to INCHES-PER-FOOT. Some Forth compilers attempt to optimise constants by in-lining them where they are used. You can force Gforth to in-line a constant like this:

```
: FEET-TO-INCHES ( n1 -- n2 ) [ INCHES-PER-FOOT ] LITERAL * ;
```

If you use **see** to decompile *this* version of FEET-TO-INCHES, you can see that INCHES-PER-FOOT is no longer present. To understand how this works, read Section 6.14.3 [Interpret/Compile states], page 128, and Section 6.13.1 [Literals], page 120.

In-lining constants in this way might improve execution time fractionally, and can ensure that a constant is now only referenced at compile-time. However, the definition of the constant still remains in the dictionary. Some Forth compilers provide a mechanism for controlling a second dictionary for holding transient words such that this second dictionary can be deleted later in order to recover memory space. However, there is no standard way of doing this.

6.10.4 Values

A **Value** behaves like a **Constant**, but it can be changed. **TO** is a parsing word that changes a **Values**. In Gforth (not in Standard Forth) you can access (and change) a **value** also with **>body**.

Here are some examples:

```
12 Value APPLES      \ Define APPLES with an initial value of 12
34 TO APPLES          \ Change the value of APPLES. TO is a parsing word
1 ' APPLES >body +!   \ Increment APPLES. Non-standard usage.
APPLES                \ puts 35 on the top of the stack.
```

Value (*w "name" –*) core-ext “Value”

TO (*value "name" –*) core-ext “TO”

changes the value of *name* to *value*

+TO (*value "name" –*) gforth-1.0 “+TO”

increments the value of *name* by *value*
`addr ("name" - addr) gforth-1.0 "addr"`
 provides the address *addr* of the value stored in *name*

6.10.5 Colon Definitions

```
: name ( ... -- ... )
  word1 word2 word3 ;
```

Creates a word called **name** that, upon execution, executes **word1 word2 word3**. **name** is a (*colon*) definition.

The explanation above is somewhat superficial. For simple examples of colon definitions see Section 4.3 [Your first definition], page 45. For an in-depth discussion of some of the issues involved, See Section 6.11 [Interpretation and Compilation Semantics], page 115.

```
: ( "name" - colon-sys ) core "colon"
; ( compilation colon-sys - ; run-time nest-sys ) core "semicolon"
```

6.10.6 Anonymous Definitions

Sometimes you want to define an *anonymous word*; a word without a name. You can do this with:

```
:noname ( - xt colon-sys ) core-ext "colon-no-name"
```

This leaves the execution token for the word on the stack after the closing `;`. Here's an example in which a deferred word is initialised with an `xt` from an anonymous colon definition:

```
Defer deferred
:noname ( ... -- ... )
  ... ;
IS deferred
```

Gforth provides an alternative way of doing this, using two separate words:

```
noname ( - ) gforth-0.2 "noname"
```

The next defined word will be anonymous. The defining word will leave the input stream alone. The `xt` of the defined word will be given by `latestxt`.

```
latestxt ( - xt ) gforth-0.6 "latestxt"
```

xt is the execution token of the last word defined.

The previous example can be rewritten using **noname** and **latestxt**:

```
Defer deferred
noname : ( ... -- ... )
  ... ;
latestxt IS deferred
```

noname works with any defining word, not just `:`.

latestxt also works when the last word was not defined as **noname**. It does not work for combined words, though. It also has the useful property that it is valid as soon as the header for a definition has been built. Thus:

```
latestxt . : foo [ latestxt . ] ; ' foo .
```

prints 3 numbers; the last two are the same.

6.10.7 Quotations

A quotation is an anonymous colon definition inside another colon definition. Quotations are useful when dealing with words that consume an execution token, like `catch` or `outfile-execute`. E.g. consider the following example of using `outfile-execute` (see Section 6.18.3 [Redirection], page 141):

```
: some-warning ( n -- )
  cr ." warning# " . ;

: print-some-warning ( n -- )
  ['] some-warning stderr outfile-execute ;
```

Here we defined `some-warning` as a helper word whose xt we could pass to `outfile-execute`. Instead, we can use a quotation to define such a word anonymously inside `print-some-warning`:

```
: print-some-warning ( n -- )
  [: cr ." warning# " . ;] stderr outfile-execute ;
```

The quotation is bounded by `[:` and `];`. It produces an execution token at run-time.

`[: (compile-time: - quotation-sys flag colon-sys) gforth-1.0 "bracket-colon"`

Starts a quotation

`]; (compile-time: quotation-sys - ; run-time: - xt) gforth-1.0 "semi-bracket"`

ends a quotation

6.10.8 Supplying the name of a defined word

By default, a defining word takes the name for the defined word from the input stream. Sometimes you want to supply the name from a string. You can do this with:

`nextname (c-addr u -) gforth-0.2 "nextname"`

The next defined word will have the name `c-addr u`; the defining word will leave the input stream alone.

For example:

```
s" foo" nextname create
```

is equivalent to:

```
create foo
```

`nextname` works with any defining word.

6.10.9 User-defined Defining Words

You can define new defining words in terms of any existing defining word, but `:` and `create...does>/set-does>` are particularly flexible, whereas the children of, e.g., `constant` are all just constants.

6.10.9.1 User-defined defining words with colon definitions

You can create a new defining word by wrapping defining-time code around an existing defining word and putting the sequence in a colon definition.

For example, suppose that you have a word **stats** that gathers statistics about colon definitions given the *xt* of the definition, and you want every colon definition in your application to make a call to **stats**. You can define and use a new version of **:** like this:

```
: stats
  ( xt -- ) DUP ." (Gathering statistics for " . ." )"
  ... ; \ other code

: my: : latestxt postpone literal ['] stats compile, ;

my: foo + - ;
```

When **foo** is defined using **my:** these steps occur:

- **my:** is executed.
- The **:** within the definition (the one between **my:** and **latestxt**) is executed, and does just what it always does; it parses the input stream for a name, builds a dictionary header for the name **foo** and switches **state** from **interpret** to **compile**.
- The word **latestxt** is executed. It puts the *xt* for the word that is being defined – **foo** – onto the stack.
- The code that was produced by **postpone literal** is executed; this causes the value on the stack to be compiled as a literal in the code area of **foo**.
- The code **['] stats** compiles a literal into the definition of **my:**. When **compile,** is executed, that literal – the execution token for **stats** – is layed down in the code area of **foo**, following the literal⁷.
- At this point, the execution of **my:** is complete, and control returns to the text interpreter. The text interpreter is in **compile** state, so subsequent text **+ -** is compiled into the definition of **foo** and the **;** terminates the definition as always.

You can use **see** to decompile a word that was defined using **my:** and see how it is different from a normal **:** definition. For example:

```
: bar + - ; \ like foo but using : rather than my:
see bar
: bar
  + - ;
see foo
: foo
  'foo stats + - ;
'foo is another way of writing ['] foo.
```

6.10.9.2 User-defined defining words using **create**

If you want the words defined with your defining words to behave differently from words defined with standard defining words, you can write your defining word like this:

```
: def-word ( "name" -- )
```

⁷ Strictly speaking, the mechanism that **compile,** uses to convert an *xt* into something in the code area is implementation-dependent. A threaded implementation might spit out the execution token directly whilst another implementation might spit out a native code sequence.

```

      CREATE code1
DOES> ( ... -- ... )
      code2 ;

```

`def-word name`

This fragment defines a *defining word* `def-word` and then executes it. When `def-word` executes, it `CREATEs` a new word `name`, and executes the code `code1`. The code `code2` is not executed at this time. The word `name` is sometimes called a *child* of `def-word`.

When you execute `name`, the address of the body of `name` is put on the data stack and `code2` is executed (the address of the body of `name` is the address `HERE` returns immediately after the `CREATE`, i.e., the address a `created` word returns by default).

You can use `def-word` to define a set of child words that behave similarly; they all have a common run-time behaviour determined by `code2`. Typically, the `code1` sequence builds a data area in the body of the child word. The structure of the data is common to all children of `def-word`, but the data values are specific – and private – to each child word. When a child word is executed, the address of its private data area is passed as a parameter on TOS to be used and manipulated⁸ by `code2`.

The two fragments of code that make up the defining words act (are executed) at two completely separate times:

- At *define time*, the defining word executes `code1` to generate a child word
- At *child execution time*, when a child word is invoked, `code2` is executed, using parameters (data) that are private and specific to the child word.

Another way of understanding the behaviour of `def-word` and `name` is to say that, if you make the following definitions:

```

: def-word1 ( "name" -- )
  CREATE code1 ;

: action1 ( ... -- ... )
  code2 ;

```

`def-word1 name1`

Then using `name1 action1` is equivalent to using `name`.

Another way of writing `def-word` is (see Section 6.10.7 [Quotations], page 102):

```

: def-word ( "name" -- ; name execution: ... -- ... )
  create code1
  [: code2 ;] set-does> ;

```

Gforth actually compiles the code using `does>` into code equivalent to the latter code. An advantage of the `set-does>` approach is that you can put other code behind it and you can use it inside control structures without needing workarounds. A disadvantage is that it is Gforth-specific.

A classic example is that you can define `CONSTANT` in this way:

```

: CONSTANT ( w "name" -- )

```

⁸ It is legitimate both to read and write to this data area.

```

      CREATE ,
DOES> ( -- w )
      @ ;

```

or equivalently

```

      : CONSTANT ( w "name" -- ; name execution: -- w )
      create ,
      ['] @ set-does> ;

```

When you create a constant with 5 `CONSTANT five`, a set of define-time actions take place; first a new word `five` is created, then the value 5 is laid down in the body of `five` with `,`. When `five` is executed, the address of the body is put on the stack, and `@` retrieves the value 5. The word `five` has no code of its own; it simply contains a data field and the xt of the quotation or of `@`.

The final example in this section is intended to remind you that space reserved in `CREATED` words is *data* space and therefore can be both read and written by a Standard program⁹:

```

      : foo ( "name" -- )
      CREATE -1 ,
DOES> ( -- )
      @ . ;

```

```

foo first-word
foo second-word

```

```

123 ' first-word >BODY !

```

If `first-word` had been a `CREATED` word, we could simply have executed it to get the address of its data field. However, since it was defined to have `DOES>` actions, its execution semantics are to perform those `DOES>` actions. To get the address of its data field it's necessary to use `'` to get its xt, then `>BODY` to translate the xt into the address of the data field. When you execute `first-word`, it will display 123. When you execute `second-word` it will display -1.

In the examples above the stack comment after the `DOES>` specifies the stack effect of the defined words, not the stack effect of the following code (the following code expects the address of the body on the top of stack, which is not reflected in the stack comment). This is the convention that I use and recommend (it clashes a bit with using locals declarations for stack effect specification, though).

6.10.9.3 Applications of `CREATE..DOES>`

You may wonder how to use this feature. Here are some usage patterns:

When you see a sequence of code occurring several times, and you can identify a meaning, you will factor it out as a colon definition. When you see similar colon definitions, you can factor them using `CREATE..DOES>`. E.g., an assembler usually defines several words that look very similar:

```

      : ori, ( reg-target reg-source n -- )

```

⁹ Exercise: use this example as a starting point for your own implementation of `Value` and `T0` – if you get stuck, investigate the behaviour of `'` and `[']`.

```

    0 asm-reg-reg-imm ;
: andi, ( reg-target reg-source n -- )
    1 asm-reg-reg-imm ;

```

This could be factored with:

```

: reg-reg-imm ( op-code -- )
    CREATE ,
DOES> ( reg-target reg-source n -- )
    @ asm-reg-reg-imm ;

```

```

0 reg-reg-imm ori,
1 reg-reg-imm andi,

```

Another view of `CREATE..DOES>` is to consider it as a crude way to supply a part of the parameters for a word (known as *currying* in the functional language community). E.g., `+` needs two parameters. Creating versions of `+` with one parameter fixed can be done like this:

```

: curry+ ( n1 "name" -- )
    CREATE ,
DOES> ( n2 -- n1+n2 )
    @ + ;

```

```

3 curry+ 3+
-2 curry+ 2-

```

6.10.9.4 The gory details of `CREATE..DOES>`

```
DOES> ( compilation colon-sys1 - colon-sys2 ) core "does"
```

This means that you need not use `CREATE` and `DOES>` in the same definition; you can put the `DOES>`-part in a separate definition. This allows us to, e.g., select among different `DOES>`-parts:

```

: does1
DOES> ( ... -- ... )
    code1 ;

: does2
DOES> ( ... -- ... )
    code2 ;

: def-word ( ... -- ... )
    create ...
    IF
        does1
    ELSE
        does2
    ENDIF ;

```

In this example, the selection of whether to use `does1` or `does2` is made at definition-time; at the time that the child word is `CREATED`.

Note that the property of `does>` to end the definition makes it necessary to introduce extra definitions `does1` and `does2`. You can avoid that with `set-does>`:

```
: def-word ( ... -- ... )
  create ...
  IF
    [: code1 ;] set-does>
  ELSE
    [: code2 ;] set-does>
  ENDIF ;
```

In a standard program you can apply a `DOES>`-part only if the last word was defined with `CREATE`. In Gforth, the `DOES>`-part will override the behaviour of the last word defined in any case. In a standard program, you can use `DOES>` only in a colon definition. In Gforth, you can also use it in interpretation state, in a kind of one-shot mode; for example:

```
CREATE name ( ... -- ... )
  initialization
DOES>
  code ;
```

is equivalent to the standard:

```
:noname
DOES>
  code ;
CREATE name EXECUTE ( ... -- ... )
  initialization
```

Gforth also supports quotations in interpreted code, and quotations save and restore the current definition, so you can also write the example above also as:

```
CREATE name ( ... -- ... )
  initialization
  [: code ;] set-does>
```

`set-does>` (*xt* -) gforth-1.0 “Changes”

pushes its body address and then executes *xt*. Also changes the `compile`, implementation accordingly. Call `set-optimizer` afterwards if you want a more efficient implementation.

`>body` (*xt* - *a_addr*) core “to-body”

Get the address of the body of the word represented by *xt* (the address of the word’s data field).

6.10.9.5 Advanced `does>` usage example

The MIPS disassembler (`arch/mips/disasm.fs`) contains many words for disassembling instructions, that follow a very repetitive scheme:

```
:noname disasm-operands s" inst-name" type ;
entry-num cells table + !
```

Of course, this inspires the idea to factor out the commonalities to allow a definition like

```
disasm-operands entry-num table define-inst inst-name
```

The parameters *disasm-operands* and *table* are usually correlated. Moreover, before I wrote the disassembler, there already existed code that defines instructions like this:

```
entry-num inst-format inst-name
```

This code comes from the assembler and resides in `arch/mips/insts.fs`.

So I had to define the *inst-format* words that performed the scheme above when executed. At first I chose to use run-time code-generation:

```
: inst-format ( entry-num "name" -- ; compiled code: addr w -- )
  :noname Postpone disasm-operands
  name Postpone sliteral Postpone type Postpone ;
  swap cells table + ! ;
```

Note that this supplies the other two parameters of the scheme above.

An alternative would have been to write this using `create/does>`:

```
: inst-format ( entry-num "name" -- )
  here name string, ( entry-num c-addr ) \ parse and save "name"
  noname create , ( entry-num )
  latestxt swap cells table + !
does> ( addr w -- )
  \ disassemble instruction w at addr
  @ >r
  disasm-operands
  r> count type ;
```

Somehow the first solution is simpler, mainly because it's simpler to shift a string from definition-time to use-time with `sliteral` than with `string`, and friends.

I wrote a lot of words following this scheme and soon thought about factoring out the commonalities among them. Note that this uses a two-level defining word, i.e., a word that defines ordinary defining words.

This time a solution involving `postpone` and friends seemed more difficult (try it as an exercise), so I decided to use a `create/does>` word; since I was already at it, I also used `create/does>` for the lower level (try using `postpone` etc. as an exercise), resulting in the following definition:

```
: define-format ( disasm-xt table-xt -- )
  \ define an instruction format that uses disasm-xt for
  \ disassembling and enters the defined instructions into table
  \ table-xt
  create 2,
does> ( u "inst" -- )
  \ defines an anonymous word for disassembling instruction inst,
  \ and enters it as u-th entry into table-xt
  2@ swap here name string, ( u table-xt disasm-xt c-addr ) \ remember string
  noname create 2, \ define anonymous word
  execute latestxt swap ! \ enter xt of defined word into table-xt
does> ( addr w -- )
  \ disassemble instruction w at addr
  2@ >r ( addr w disasm-xt R: c-addr )
```

```
execute ( R: c-addr ) \ disassemble operands
r> count type ; \ print name
```

Note that the tables here (in contrast to above) do the `cells +` by themselves (that's why you have to pass an `xt`). This word is used in the following way:

```
' disasm-operands ' table define-format inst-format
```

As shown above, the defined instruction format is then used like this:

```
entry-num inst-format inst-name
```

In terms of currying, this kind of two-level defining word provides the parameters in three stages: first *disasm-operands* and *table*, then *entry-num* and *inst-name*, finally *addr w*, i.e., the instruction to be disassembled.

Of course this did not quite fit all the instruction format names used in `insts.fs`, so I had to define a few wrappers that conditioned the parameters into the right form.

If you have trouble following this section, don't worry. First, this is involved and takes time (and probably some playing around) to understand; second, this is the first two-level `create/does>` word I have written in seventeen years of Forth; and if I did not have `insts.fs` to start with, I may well have elected to use just a one-level defining word (with some repeating of parameters when using the defining word). So it is not necessary to understand this, but it may improve your understanding of Forth.

6.10.9.6 User-defined TO and DEFER@

Gforth allows you to change the `(to)` action of a word.

`(to) (val xt -)` gforth-1.0 “paren-to”

xt is of a value like word *name*. Stores *val* to *name*.

doc-set-to

`(to)` is a word used inside `to:` it stores the value at run-time. The general stack effect of `(to)` method is `(val xt --)`, where *xt* identifies the word stored into, and *val* is the value (of appropriate type) stored there.

E.g., one can implement `fvalue` as follows:

```
: fvalue-to ( r xt -- )
  >body f! ;

: fvalue ( r "name" -- ; name: -- r )
  create f,
  ['] f@ set-does>
  ['] fvalue-to set-to ;

5e fvalue foo
: bar foo 1e f+ to foo ;
see bar
```

`(To)` is also known as `defer!` (called by `is`, see Section 6.10.10 [Deferred Words], page 112), so you can use it to implement variations of deferred words. You also need to change `defer@` then, and you can do that, too:

doc-set-defer

6.10.9.7 User-defined compile,

You can also change the implementation of `compile`, for a word, with

`set-optimizer (xt -) gforth-1.0 "set-optimizer"`

Changes the current word such that `compile`,ing it executes *xt* (with the same stack contents as passed to `compile`,. Note that `compile`, must be consistent with `execute`, so you must use `set-optimizer` only to install a more efficient implementation of the same behaviour.

Note that the resulting `compile`, must still be equivalent to `postpone literal postpone execute`, so `set-optimizer` is useful for efficiency, not for changing the behaviour. There is nothing that prevents you from shooting yourself in the foot, however. You can check whether your uses of `set-optimizer` are correct by comparing the results when you use it with the results you get when you disable your uses by first defining

```
: set-optimizer drop ;
```

As an example of the use of `set-optimizer`, we can enhance one of the definitions of `CONSTANT` above as follows.

```
: CONSTANT ( n "name" -- ; name: -- n )
  create ,
  ['] @ set-does>
  [: >body @ postpone literal ;] set-optimizer
;
```

The only change is the addition of the `set-optimizer` line. When you define a constant and compile it:

```
5 constant five
: foo five ;
```

the compiled `five` in `foo` is now compiled to the literal 5 instead of a generic invocation of `five`. The quotation has the same stack effect as `compile,: (xt --)`. The passed *xt* belongs to the `compile,d` word, i.e., `five` in the example. In the example the *xt* is first converted to the body address, then the value 5 at that place is fetched, and that value is compiled with the `postpone literal` (see Section 6.13.1 [Literals], page 120).

This use of `set-optimizer` assumes that the user does not change the value of a constant with, e.g., `6 ' five >body !`. While `five` has been defined with `create`, that is an implementation detail of `CONSTANT`, and if you don't document it, the user must not rely on it. And if you use `set-optimizer` in a way that assumes that the body does not change (like is done here), you must not document that `create` is used; and conversely, if you document it, you have to write the `compile`, implementation such that it can deal with changing bodies.

Another example is a better-optimized variant of the `fvalue` example above:

```
: compile-fvalue-to ( xt-value-to -- )
  drop ]] >body f! [[ ;

: fvalue-to ( r xt -- )
  >body f! ;
' compile-fvalue-to set-optimizer
```

```

: fvalue ( r "name" -- ; name: -- r )
  create f,
  ['] f@ set-does>
  [: >body ]] literal f@ [[ ;] set-optimizer
  ['] fvalue-to set-to ;

5e fvalue foo
: bar foo 1e f+ to foo ;
see bar

```

Compare the code for `bar` with the one for the earlier definition. Here we see the optimization of both the code for reading the `fvalue` (coming from the `set-optimizer` in `fvalue`) and for writing the `fvalue` (coming from the `set-optimizer` applied to `fvalue-to`). Because an `fvalue` can change (unlike a constant), the reading part (inside `fvalue`) compiles the address and a `f@` that is performed at run-time.

For `fvalue-to`, the `compile`, implementation basically just compiles the code executed by `fvalue` inline. The compilation semantics of `to` compiles the address as literal and then the `(to)` implementation (i.e., `fvalue-to`). In this process the `>body` is optimized away.

In practice Gforth's `fvalue` includes a few additional twists, e.g., to support `+T0`.

Note that the call to `set-optimizer` has to be performed after the call to `set-does>` (or `does>`, because `set-does>` overwrites the `compile`, implementation itself).

As we can see in the `fvalue-to` example, we can also apply `set-optimizer` to individual words rather than inside a defining word like `constant` or `fvalue`. In this case, the `xt` of the word passed to optimizer is usually unnecessary and is dropped, as in `compile-fvalue-to`.

The engine `gforth-itc` uses `,` for `compile`, and `set-optimizer` has no effect there.

6.10.9.8 Creating from a prototype

In the above we show how to define a word by first using `create`, and then modifying it with `set-does>`, `set-to`, `set-optimizer` etc.

An alternative way is to create a prototype using these words, and then create a new word from that prototype. This kind of copying does not cover the body, so that has to be allocated and initialized explicitly. Taking `fvalue` above, we could instead define it as:

```

create fvalue-prototype ( -- r )
  ['] f@ set-does>
  [: >body ]] literal f@ [[ ;] set-optimizer
  ['] fvalue-to set-to

: fvalue ( r "name" -- ; name: -- r )
  ``fvalue-prototype create-from f, ;

```

An advantage of this approach is that creating `fvalue` words is now faster, because it does not need to first duplicate the header methods of `create`, modify them, and eventually deduplicate them. But this advantage is only relevant if the number of words created with this defining word is huge.

`create-from` (*nt* "name" -) gforth-1.0 "create-from"

Create a word *name* that behaves like *nt*, but with an empty body. *nt* must be the *nt* of a named word. The resulting header is not yet revealed. Creating a word with

`create-from` without using any `set-` words is faster than if you create a word using `set-` words, `immediate`, or `does>`. You can use `noname` with `create-from`.

The performance advantage does not extend to using `noname` with the defining word. Therefore we also have

`noname-from` (*xt* –) gforth-1.0 “noname-from”

Create a nameless word that behaves like *xt*, but with an empty body. *xt* must be the nt of a nameless word.

Here’s a usage example:

```
‘‘fvalue-prototype noname create-from
latestnt constant noname-fvalue-prototype

: noname-fvalue ( r -- xt ; xt execution: -- r )
  noname-fvalue-prototype noname-from f,
  latestxt ;
```

6.10.9.9 Const-does>

A frequent use of `create...does>` is for transferring some values from definition-time to run-time. Gforth supports this use with

`const-does>` (*run-time: w*uw r*ur uw ur "name" –*) gforth-0.6 “const-does>”

Defines *name* and returns.

name execution: pushes *w*uw r*ur*, then performs the code following the `const-does>`.

A typical use of this word is:

```
: curry+ ( n1 "name" -- )
1 0 CONST-DOES> ( n2 -- n1+n2 )
  + ;
```

```
3 curry+ 3+
```

Here the 1 0 means that 1 cell and 0 floats are transferred from definition to run-time.

The advantages of using `const-does>` are:

- You don’t have to deal with storing and retrieving the values, i.e., your program becomes more writable and readable.
- When using `does>`, you have to introduce a `@` that cannot be optimized away (because you could change the data using `>body...!`); `const-does>` avoids this problem.

A Standard Forth implementation of `const-does>` is available in `compat/const-does.fs`.

6.10.10 Deferred Words

The defining word `Defer` allows you to define a word by name without defining its behaviour; the definition of its behaviour is deferred. Here are two situation where this can be useful:

- Where you want to allow the behaviour of a word to be altered later, and for all precompiled references to the word to change when its behaviour is changed.
- For mutual recursion; See Section 6.9.7 [Calls and returns], page 93.

In the following example, `foo` always invokes the version of `greet` that prints “Good morning” whilst `bar` always invokes the version that prints “Hello”. There is no way of getting `foo` to use the later version without re-ordering the source code and recompiling it.

```
: greet ." Good morning" ;
: foo ... greet ... ;
: greet ." Hello" ;
: bar ... greet ... ;
```

This problem can be solved by defining `greet` as a `Deferred` word. The behaviour of a `Deferred` word can be defined and redefined at any time by using `IS` to associate the xt of a previously-defined word with it. The previous example becomes:

```
Defer greet ( -- )
: foo ... greet ... ;
: bar ... greet ... ;
: greet1 ( -- ) ." Good morning" ;
: greet2 ( -- ) ." Hello" ;
' greet2 IS greet \ make greet behave like greet2
```

Programming style note: You should write a stack comment for every deferred word, and put only XTs into deferred words that conform to this stack effect. Otherwise it’s too difficult to use the deferred word.

A deferred word can be used to improve the statistics-gathering example from Section 6.10.9 [User-defined Defining Words], page 102; rather than edit the application’s source code to change every `:` to a `my:`, do this:

```
: real: : ; \ retain access to the original
defer : \ redefine as a deferred word
' my: IS : \ use special version of :
\
\ load application here
\
' real: IS : \ go back to the original
```

One thing to note is that `IS` has special compilation semantics, such that it parses the name at compile time (like `T0`):

```
: set-greet ( xt -- )
  IS greet ;

' greet1 set-greet
```

In situations where `IS` does not fit, use `defer!` instead.

A deferred word can only inherit execution semantics from the xt (because that is all that an xt can represent – for more discussion of this see Section 6.12 [Tokens for Words], page 117); by default it will have default interpretation and compilation semantics deriving from this execution semantics. However, you can change the interpretation and compilation semantics of the deferred word in the usual ways:

```
: bar .... ; immediate
Defer fred immediate
Defer jim
```

```

    ' bar IS jim \ jim has default semantics
    ' bar IS fred \ fred is immediate
Defer ( "name" - ) core-ext "Defer"

```

Define a deferred word *name*; its execution semantics can be set with **defer!** or **is** (and they have to, before first executing *name*).

```
defer! ( xt xt-deferred - ) core-ext "defer-store"
```

```
IS ( value "name" - ) core-ext "IS"
```

changes the deferred word *name* to execute *value*

```
defer@ ( xt-deferred - xt ) core-ext "defer-fetch"
```

xt represents the word currently associated with the deferred word *xt-deferred*.

```
action-of ( interpretation "name" - xt; compilation "name" - ; run-time - xt ) core-ext "action-of"
```

Xt is the XT that is currently assigned to *name*.

```
defers ( compilation "name" - ; run-time ... - ... ) gforth-0.2 "defers"
```

Compiles the present contents of the deferred word *name* into the current definition. I.e., this produces static binding as if *name* was not deferred.

Definitions of these words (except **defers**) in Standard Forth are provided in `compat/defer.fs`.

6.10.11 Forward

The defining word **Forward** in `forward.fs` allows you to create forward references, which are resolved automatically, and do not incur additional costs like the indirection of **Defer**. However, these forward definitions only work for colon definitions.

```
forward ( "name" - ) gforth-1.0 "forward"
```

Defines a forward reference to a colon definition. Defining a colon definition with the same name in the same wordlist resolves the forward references. Use **.unresolved** to check whether any forwards are unresolved. auto-resolve the forward reference in check-shadow

```
.unresolved ( - ) gforth-1.0 ".unresolved"
```

print all unresolved forward references

6.10.12 Aliases

The defining word **synonym** allows you to define a word by name that has the same behaviour as some other word. Here are two situation where this can be useful:

- When you want access to a word's definition from a different word list (for an example of this, see the definition of the **Root** word list in the Gforth source).
- When you want to create a synonym; a definition that can be known by either of two names (for example, **THEN** and **ENDIF** are synonyms).

```
Synonym ( "name" "oldname" - ) tools-ext "Synonym"
```

Define *name* to behave the same way as *oldname*: Same interpretation semantics, same compilation semantics, same **to/defer!** and **defer@** semantics.

Gforth also offers the non-standard **alias**, that does not inherit the compilation semantics, **to/defer!** or **defer@** semantics from its parent. You can then change, e.g., the compilation semantics with, e.g., **immediate**.

Alias (*xt* "*name*" –) gforth-0.2 “Alias”

Define *name* as a word that performs *xt*. Unlike for deferred words, aliases don’t have an indirection overhead when compiled.

Example:

```
: foo ... ; immediate

' foo Alias bar1          \ bar1 is not an immediate word
' foo Alias bar2 immediate \ bar2 is an immediate word
synonym bar3 foo          \ bar3 is an immediate word
```

Both synonyms and aliases have a different *nt* than the original, but ticking it (or using **name>interpret**) produces the same *xt* as the original (see Section 6.12 [Tokens for Words], page 117).

6.11 Interpretation and Compilation Semantics

The *interpretation semantics* of a (named) word are what the text interpreter does when it encounters the word in interpret state. It also appears in some other contexts, e.g., the execution token returned by **' word** identifies the interpretation semantics of *word* (in other words, **' word execute** is equivalent to interpret-state text interpretation of *word*).

The *compilation semantics* of a (named) word are what the text interpreter does when it encounters the word in compile state. It also appears in other contexts, e.g., **POSTPONE word** compiles¹⁰ the compilation semantics of *word*.

Most words have default compilation semantics: compile the execution semantics (stack effect (--)). But a number of words have other compilation semantics, documented for the individual word (including its stack effect).

The standard also talks about *execution semantics*. In the standard it never differs from the interpretation semantics if both are defined, but one or both of them may not be defined. Gforth makes no difference between interpretation and execution semantics, so these terms are used interchangeably.

In Gforth (since 1.0) all words have defined interpretation/execution semantics. For many words that have no defined interpretation nor execution semantics in the standard (e.g., **if**), the interpretation/execution semantics in Gforth are to perform the compilation semantics.

In the standard, execution semantics are used to define interpretation and compilation semantics by default: By default, the interpretation semantics of a word are to **execute** its execution semantics, and the compilation semantics of a word are to **compile**, its execution semantics.¹¹

Unnamed words (see Section 6.10.6 [Anonymous Definitions], page 101) cannot be encountered by the text interpreter, ticked, or **postponed**. Such a word is represented by

¹⁰ In standard terminology, “appends to the current definition”.

¹¹ In standard terminology: The default interpretation semantics are its execution semantics; the default compilation semantics are to append its execution semantics to the execution semantics of the current definition.

its `xt` (see Section 6.12 [Tokens for Words], page 117), and the behaviour when this `xt` is **executed** is called its execution semantics.

You can change the semantics of the most-recently defined word:

```
immediate ( - ) core “immediate”
```

Make the compilation semantics of a word be to **execute** the execution semantics.

```
compile-only ( - ) gforth-0.2 “compile-only”
```

Mark the last definition as compile-only; as a result, the text interpreter and `'` will warn when they encounter such a word.

```
restrict ( - ) gforth-0.2 “restrict”
```

A synonym for **compile-only**

By convention, words with non-default compilation semantics (e.g., immediate words) often have names surrounded with brackets (e.g., `[']`, see Section 6.12.1 [Execution token], page 117).

Note that ticking (`'`) a compile-only word gives a warning (“<word> is compile-only”).

6.11.1 Combined Words

Gforth allows you to define *combined words* – words that have an arbitrary combination of interpretation and compilation semantics.

```
interpret/compile: ( interp-xt comp-xt "name" - ) gforth-0.2 “interpret/compile:”
```

This feature was introduced for implementing **T0** and **S**. I recommend that you do not define such words, as cute as they may be: they make it hard to get at both parts of the word in some contexts. E.g., assume you want to get an execution token for the compilation part. Instead, define two words, one that embodies the interpretation part, and one that embodies the compilation part. Once you have done that, you can define a combined word with **interpret/compile:** for the convenience of your users.

You might try to use this feature to provide an optimizing implementation of the default compilation semantics of a word. For example, by defining:

```
:noname
  foo bar ;
:noname
  POSTPONE foo POSTPONE bar ;
interpret/compile: opti-foobar
```

as an optimizing version of:

```
: foobar
  foo bar ;
```

Unfortunately, this does not work correctly with **[compile]**, because **[compile]** assumes that the compilation semantics of all **interpret/compile:** words are non-default. I.e., **[compile] opti-foobar** would compile compilation semantics, whereas **[compile] foobar** would compile interpretation semantics.

Some people try to use *state-smart* words to emulate the feature provided by **interpret/compile:** (words are state-smart if they check **STATE** during execution). E.g., they would try to code **foobar** like this:

```
: foobar
```

```

STATE @
IF ( compilation state )
  POSTPONE foo POSTPONE bar
ELSE
  foo bar
ENDIF ; immediate

```

Although this works if `foobar` is only processed by the text interpreter, it does not work in other contexts (like `'` or `POSTPONE`). E.g., `' foobar` will produce an execution token for a state-smart word, not for the interpretation semantics of the original `foobar`; when you execute this execution token (directly with `EXECUTE` or indirectly through `COMPILE`), in compile state, the result will not be what you expected (i.e., it will not perform `foo bar`). State-smart words are a bad idea. Simply don't write them¹²!

6.12 Tokens for Words

This section describes the creation and use of tokens that represent words.

6.12.1 Execution token

An *execution token* (*xt*) represents some behaviour of a word. You can use `execute` to invoke the behaviour represented by the *xt* and `compile`, (see Section 6.13.2 [Macros], page 122) to compile it into the current definition. Other uses include deferred words (see Section 6.10.10 [Deferred Words], page 112).

In particular, there is *the* execution token of a word that represents its interpretation semantics aka execution semantics.¹³

For a named word *x*, you can use `'x` to get its execution token:

```

5 ' . ( n xt )
execute ( )      \ execute the xt (i.e., ".")
: foo ' . execute ;
5 foo

```

However, the `'` prefix is a Gforth extension, so you may prefer to use the standard Forth words:

`' ("name" - xt)` core “tick”

xt represents *name*'s interpretation semantics. Perform `-14 throw` if the word has no interpretation semantics.

`['] (compilation. "name" - ; run-time. - xt)` core “bracket-tick”

xt represents *name*'s interpretation semantics. Perform `-14 throw` if the word has no interpretation semantics.

These are parsing words (whereas `'x` is treated as a literal by a recognizer), and you may find the behaviour in interpreted and compiled code unintuitive:

```

5 ' . ( n xt )

```

¹² For a more detailed discussion of this topic, see M. Anton Ertl, *State-smartness—Why it is Evil and How to Exorcise it* (<https://www.complang.tuwien.ac.at/papers/ertl98.ps.gz>), EuroForth '98.

¹³ The Forth standard has words with undefined interpretation semantics (e.g., `r@`) and words without defined execution semantics (e.g., `s"`) and words with neither (e.g., `if`), but in cases where both interpretation and execution semantics are defined, they are the same; so we treat them as being the same.


```

execute ( )      \ execute the xt of .
\ does not work as intended:
\ : foo ' . ;
\ 5 foo execute
\ instead:
: foo ['] . ;
5 foo execute    \ execute the xt of .
\ Usage of ' in colon definition:
: bar ' execute ;
5 bar .          \ execute the xt of .

```

' parses at run-time, so if you put it in a colon definition, as in `bar`, it does not consume the next word in the colon definition, but the next word at run-time (i.e., the `.` in the invocation of `bar`). If you want to put a literal xt in a colon definition without writing `'x`, write `['] x`.

Gforth's `'x`, `'` and `[']` warn when you use them on compile-only words, because such usage may be non-portable between different Forth systems.

You can avoid that warning as well as the portability problems by defining an immediate variant of the word, e.g.:

```

: if postpone if ; immediate
: test [ ' if execute ] ." test" then ;

```

The resulting execution token performs the compilation semantics of `if` when **executed**.

Another way to get an xt is `:noname` or `latestxt` (see Section 6.10.6 [Anonymous Definitions], page 101). For anonymous words this gives an xt for the only behaviour the word has (the execution semantics), but you can also use it after defining a named word to get its xt.

```

:noname ." hello" ;
execute

```

An xt occupies one cell and can be manipulated like any other cell.

In Standard Forth the xt is just an abstract data type (i.e., defined by the operations that produce or consume it). The concrete implementation (since Gforth 1.0) is the body address (for old hands: PFA) of the word; in Gforth 0.7 and earlier, the xt was implemented as code field address (CFA, 2 cells before the PFA).

execute (*xt* -) core “execute”

Perform the semantics represented by the execution token, *xt*.

perform (*a-addr* -) gforth-0.2 “perform”

@ **execute**.

Noop is sometimes used to have a placeholder execution token:

noop (-) gforth-0.2 “noop”

6.12.2 Name token

Gforth represents named words by the *name token*, (*nt*). The name token is a cell-sized abstract data type that occurs as argument or result of the words below.

Since Gforth 1.0, for most words the concrete implementation of their *nt* is the same address as its *xt* (this is the primary *nt* for the *xt*). However, synonyms, aliases, and

words defined with **interpret/compile**: get their *xt* from another word, but still have an *nt* of their own (that is different from the *xt*). Therefore, you cannot use *xts* and *nts* interchangeably, even if you are prepared to write code specific to Gforth 1.0. You do not get these alternate *nts* for the *xt* with **>name**.

You get the *nt* of a word *x* with ‘**x** (since Gforth 1.0) or with
find-name (*c-addr u* – *nt* | 0) gforth-0.2 “find-name”

Find the name *c-addr u* in the current search order. Return its *nt*, if found, otherwise 0.
find-name-in (*c-addr u* *wid* – *nt* | 0) gforth-1.0 “find-name-in”

search the word list identified by *wid* for the definition named by the string at *c-addr u*. Return its *nt*, if found, otherwise 0.

latest (– *nt*) gforth-0.6 “latest”

nt is the name token of the last word defined; it is 0 if the last word has no name.

latestnt (– *nt*) gforth-1.0 “latestnt”

nt is the name token of the last word defined.

>name (*xt* – *nt* | 0) gforth-0.2 “to-name”

The primary name token *nt* of the word represented by *xt*. Returns 0 if *xt* is not an *xt* (using a heuristic check that has a small chance of misidentifying a non-*xt* as *xt*), or if the primary *nt* is of an unnamed word. As of Gforth 1.0, every *xt* has a primary *nt*, but other named words may have the same interpretation semantics *xt*. another name of **>name**

You can use the *nt* to access the interpretation and compilation semantics of a word, its name, and the next word in the wordlist:

name>interpret (*nt* – *xt* | 0) tools-ext “name-to-interpret”

xt represents the interpretation semantics *nt*; returns 0 if *nt* has no interpretation semantics

name>compile (*nt* – *w xt*) tools-ext “name-to-compile”

w xt is the compilation token for the word *nt*.

name>string (*nt* – *addr u*) tools-ext “name-to-string”

addr count is the name of the word represented by *nt*.

id. (*nt* –) gforth-0.6 “i-d-dot”

Print the name of the word represented by *nt*.

name>link (*nt1* – *nt2* / 0) gforth-1.0 “name-to-link”

For a word *nt1*, returns the previous word *nt2* in the same wordlist, or 0 if there is no previous word.

A nameless word usually has no interpretation nor compilation semantics, no name, and it’s not in a wordlist. But in Gforth (since 1.0) all words are equal, so even nameless words have an *nt*, you can get it with **latestnt**, and the words above that consume *nts* do something reasonable for these *nts*.

The closest thing to the *nt* in older Forth systems is the name field address (NFA), but there are significant differences: in older Forth systems each word had a unique NFA, LFA, CFA and PFA (in this order, or LFA, NFA, CFA, PFA) and there were words for getting from one to the next. In contrast, in Gforth several *nts* can get the same *xt* from

`name>interpret xt`; there is a link field in the structure identified by the name token, but searching usually uses a hash table external to these structures; the name in Gforth has a cell-wide count-and-flags field, and the `nt` is not implemented as the address of that count field.

6.12.3 Compilation token

The compilation semantics of a named word is represented by a *compilation token* consisting of two cells: *w xt*. The top cell *xt* is an execution token. The compilation semantics represented by the compilation token can be performed with `execute`, which consumes the whole compilation token, with an additional stack effect determined by the represented compilation semantics.

At present, the *w* part of a compilation token is an execution token, and the *xt* part represents either `execute` or `compile`,¹⁴. However, don't rely on that knowledge, unless necessary; future versions of Gforth may introduce unusual compilation tokens (e.g., a compilation token that represents the compilation semantics of a literal).

You get the compilation token of, e.g., `if` in a standard way with `name>compile`, e.g., `'if name>compile`, but there are also parsing words to get the compilation token of a word: `[COMP'] (compilation "name" - ; run-time - w xt)` gforth-0.2 “bracket-comp-tick”

Compilation token *w xt* represents *name*'s compilation semantics.

`COMP' ("name" - w xt)` gforth-0.2 “comp-tick”

Compilation token *w xt* represents *name*'s compilation semantics.

You can perform the compilation semantics represented by the compilation token with `execute`. You can compile the compilation semantics with `postpone`,. I.e., `'x name>compile postpone`, is equivalent to `postpone x`.

`postpone, (w xt -)` gforth-0.2 “postpone-comma”

Compile the compilation semantics represented by the compilation token *w xt*.

6.13 Compiling words

In contrast to most other languages, Forth has no strict boundary between compilation and run-time. E.g., you can run arbitrary code between defining words (or for computing data used by defining words like `constant`). Moreover, `Immediate` (see Section 6.11 [Interpretation and Compilation Semantics], page 115, and [...]) (see below) allow running arbitrary code while compiling a colon definition (exception: you must not allot dictionary space).

6.13.1 Literals

The simplest and most frequent example is to compute a literal during compilation. E.g., the following definition prints an array of strings, one string per line:

```
: .strings ( addr u -- ) \ gforth
  2* cells bounds U+D0
  cr i 20 type
  2 cells +LOOP ;
```

¹⁴ Depending upon the compilation semantics of the word. If the word has default compilation semantics, the *xt* will represent `compile`,. Otherwise (e.g., for immediate words), the *xt* will represent `execute`.

With a simple-minded compiler like Gforth's, this computes `2 cells` on every loop iteration. You can compute this value once and for all at compile time and compile it into the definition like this:

```
: .strings ( addr u -- ) \ gforth
  2* cells bounds U+D0
cr i 2@ type
  [ 2 cells ] literal +LOOP ;
```

[switches the text interpreter to interpret state (you will get an `ok` prompt if you type this example interactively and insert a newline between [and]), so it performs the interpretation semantics of `2 cells`; this computes a number.] switches the text interpreter back into compile state. It then performs `Literal`'s compilation semantics, which are to compile this number into the current word. You can decompile the word with `see .strings` to see the effect on the compiled code.

You can also optimize the `2* cells` into `[2 cells] literal *` in this way.

[(-) core “left-bracket”

Enter interpretation state. Immediate word.

] (-) core “right-bracket”

Enter compilation state.

Literal (*compilation n - ; run-time - n*) core “Literal”

Compilation semantics: compile the run-time semantics.

Run-time Semantics: push *n*.

Interpretation semantics: undefined.

]L (*compilation: n - ; run-time: - n*) gforth-0.5 “]L”

equivalent to] **literal**

There are also words for compiling other data types than single cells as literals:

2Literal (*compilation w1 w2 - ; run-time - w1 w2*) double “two-literal”

Compile appropriate code such that, at run-time, *w1 w2* are placed on the stack. Interpretation semantics are undefined.

FLiteral (*compilation r - ; run-time - r*) floating “f-literal”

Compile appropriate code such that, at run-time, *r* is placed on the (floating-point) stack. Interpretation semantics are undefined.

SLiteral (*Compilation c-addr1 u ; run-time - c-addr2 u*) string “SLiteral”

Compilation: compile the string specified by *c-addr1*, *u* into the current definition. Run-time: return *c-addr2 u* describing the address and length of the string.

You might be tempted to pass data from outside a colon definition to the inside on the data stack. This does not work, because `:` pushes a colon-sys, making stuff below inaccessible. E.g., this does not work:

```
5 : foo literal ; \ error: "unstructured"
```

Instead, you have to pass the value in some other way, e.g., through a variable:

```
variable temp
5 temp !
: foo [ temp @ ] literal ;
```

6.13.2 Macros

Literal and friends compile data values into the current definition. You can also write words that compile other words into the current definition. E.g.,

```
: compile-+ ( -- ) \ compiled code: ( n1 n2 -- n )
  POSTPONE + ;

: foo ( n1 n2 -- n )
  [ compile-+ ] ;
1 2 foo .
```

This is equivalent to `: foo + ;` (see `foo` to check this). What happens in this example? **Postpone** compiles the compilation semantics of `+` into `compile-+`; later the text interpreter executes `compile-+` and thus the compilation semantics of `+`, which compile (the execution semantics of) `+` into `foo`.¹⁵

postpone ("*name*" -) core "postpone"

Compiles the compilation semantics of *name*.

Compiling words like `compile-+` are usually immediate (or similar) so you do not have to switch to interpret state to execute them; modifying the last example accordingly produces:

```
: [compile-+] ( compilation: --; interpretation: -- )
  \ compiled code: ( n1 n2 -- n )
  POSTPONE + ; immediate

: foo ( n1 n2 -- n )
  [compile-+] ;
1 2 foo .
```

You will occasionally find the need to **POSTPONE** several words; putting **POSTPONE** before each such word is cumbersome, so Gforth provides a more convenient syntax: `]] ... [[`. This allows us to write `[compile-+]` as:

```
: [compile-+] ( compilation: --; interpretation: -- )
  ]] + [[ ; immediate
```

`]] (-)` gforth-0.6 "right-bracket-bracket"

switch into postpone state

The unusual direction of the brackets indicates their function: `]]` switches from compilation to postponing (i.e., compilation of compilation), just like `]` switches from immediate execution (interpretation) to compilation. Conversely, `[[` switches from postponing to compilation, analogous to `[` which switches from compilation to immediate execution.

The real advantage of `]] ... [[` becomes apparent when there are many words to **POSTPONE**. E.g., the word `compile-map-array` (see Section 3.35 [Advanced macros Tutorial], page 37) can be written much shorter as follows:

```
: compile-map-array ( compilation: xt -- ; run-time: ... addr u -- ... )
  \ at run-time, execute xt ( ... x -- ... ) for each element of the
  \ array beginning at addr and containing u elements
```

¹⁵ A recent RFI answer requires that compiling words should only be executed in compile state, so this example is not guaranteed to work on all standard systems, but on any decent system it will work.

```
{: xt: xt :}
]] cells over + swap ?do
  i @ xt 1 cells +loop [[ ;
```

```
: sum-array ( addr u -- n )
  0 [ ' + compile-map-array ] ;
```

If you then say `see sum-array`, it shows the following code:

```
: sum-array
  #0 over + swap ?do
    i + #8 +LOOP
;
```

In addition to `]]...[[`, this example shows off some other features:

- It uses a defer-flavoured (defined with `xt: local xt`; mentioning the local inside `]]...[[` results in `compile`,ing the `xt` in the local.
- It uses the literal `1` inside `]]...[[`. This results in `postpone`ing the `1`, i.e. compiling it when `compile-map-array` is run.
- When `compile-map-array` is run, `1 cells` is compiled and optimized into `#8` by Gforth's constant folding.

Note that parsing words such as `s\"` don't parse at postpone time and therefore not inside `]]...[[`. Instead of `s\" mystring\n\"` you can use the string recognizer and write `"mystring\n"`, which works inside `]]...[[`. Likewise for the parsing word `[']` and the recognizer notation starting with `'`.

But if you prefer to use `s\"` (or have a parsing word that has no recognizer replacement), you can do it by switching back to compilation:

```
]] ... [[ s\" mystring\n\" ]] 2literal ... [[
```

Definitions of `]]` and friends in Standard Forth are provided in `compat/macros.fs`.

Immediate compiling words are similar to macros in other languages (in particular, Lisp). The important differences to macros in, e.g., C are:

- You use the same language for defining and processing macros, not a separate preprocessor language and processor.
- Consequently, the full power of Forth is available in macro definitions. E.g., you can perform arbitrarily complex computations, or generate different code conditionally or in a loop (e.g., see Section 3.35 [Advanced macros Tutorial], page 37). This power is very useful when writing a parser generators or other code-generating software.
- Macros defined using `postpone` etc. deal with the language at a higher level than strings; name binding happens at macro definition time, so you can avoid the pitfalls of name collisions that can happen in C macros. Of course, Forth is a liberal language and also allows to shoot yourself in the foot with text-interpreted macros like

```
: [compile-+] s\" +\" evaluate ; immediate
```

Apart from binding the name at macro use time, using `evaluate` also makes your definition `state-smart` (see [state-smartness], page 116).

You may want the macro to compile a number into a word. The word to do it is `literal`, but you have to `postpone` it, so its compilation semantics take effect when the macro is executed, not when it is compiled:

```
: [compile-5] ( -- ) \ compiled code: ( -- n )
  5 POSTPONE literal ; immediate

: foo [compile-5] ;
foo .
```

You may want to pass parameters to a macro, that the macro should compile into the current definition. If the parameter is a number, then you can use `postpone literal` (similar for other values).

If you want to pass a word that is to be compiled, the usual way is to pass an execution token and `compile`, it:

```
: twice1 ( xt -- ) \ compiled code: ... -- ...
  dup compile, compile, ;

: 2+ ( n1 -- n2 )
  [ ' 1+ twice1 ] ;
```

`compile, (xt -)` core-ext “compile-comma”

Append the semantics represented by `xt` to the current definition. When the resulting code fragment is run, it behaves the same as if `xt` is `executed`.

An alternative available in Gforth, that allows you to pass the compilation semantics as parameters is to use the compilation token (see Section 6.12.3 [Compilation token], page 120). The same example in this technique:

```
: twice ( ... ct -- ... ) \ compiled code: ... -- ...
  2dup 2>r execute 2r> execute ;

: 2+ ( n1 -- n2 )
  [ comp' 1+ twice ] ;
```

In the example above `2>r` and `2r>` ensure that `twice` works even if the executed compilation semantics has an effect on the data stack.

You can also define complete definitions with these words; this provides an alternative to using `does>` (see Section 6.10.9 [User-defined Defining Words], page 102). E.g., instead of

```
: curry+ ( n1 "name" -- )
  CREATE ,
DOES> ( n2 -- n1+n2 )
  @ + ;
```

you could define

```
: curry+ ( n1 "name" -- )
  \ name execution: ( n2 -- n1+n2 )
  >r : r> POSTPONE literal POSTPONE + POSTPONE ; ;
```

```
-3 curry+ 3-
see 3-
```

The sequence `>r : r>` is necessary, because `:` puts a colon-sys on the data stack that makes everything below it inaccessible.

This way of writing defining words is sometimes more, sometimes less convenient than using `does>` (see Section 6.10.9.5 [Advanced `does>` usage example], page 107). One advantage of this method is that it can be optimized better, because the compiler knows that the value compiled with `literal` is fixed, whereas the data associated with a `created` word can be changed.

6.14 The Text Interpreter

The text interpreter¹⁶ is an endless loop that processes input from the current input device. It is also called the outer interpreter, in contrast to the inner interpreter (see Chapter 15 [Engine], page 268) which executes the compiled Forth code on interpretive implementations.

The text interpreter operates in one of two states: *interpret state* and *compile state*. The current state is defined by the aptly-named variable `state`.

This section starts by describing how the text interpreter behaves when it is in interpret state, processing input from the user input device – the keyboard. This is the mode that a Forth system is in after it starts up.

The text interpreter works from an area of memory called the *input buffer*¹⁷, which stores your keyboard input when you press the RET key. Starting at the beginning of the input buffer, it skips leading spaces (called *delimiters*) then parses a string (a sequence of non-space characters) until it reaches either a space character or the end of the buffer. Having parsed a string, it makes two attempts to process it:

- It looks for the string in a *dictionary* of definitions. If the string is found, the string names a *definition* (also known as a *word*) and the dictionary search returns information that allows the text interpreter to perform the word's *interpretation semantics*. In most cases, this simply means that the word will be executed.
- If the string is not found in the dictionary, the text interpreter attempts to treat it as a number, using the rules described in Section 6.14.2 [Number Conversion], page 128. If the string represents a legal number in the current radix, the number is pushed onto a parameter stack (the data stack for integers, the floating-point stack for floating-point numbers).

If both attempts fail, the text interpreter discards the remainder of the input buffer, issues an error message and waits for more input. If one of the attempts succeeds, the text interpreter repeats the parsing process until the whole of the input buffer has been processed, at which point it prints the status message “ok” and waits for more input.

The text interpreter keeps track of its position in the input buffer by updating a variable called `>IN` (pronounced “to-in”). The value of `>IN` starts out as 0, indicating an offset of 0 from the start of the input buffer. The region from offset `>IN @` to the end of the input buffer is called the *parse area*¹⁸. This example shows how `>IN` changes as the text interpreter parses the input buffer:

¹⁶ This is an expanded version of the material in Section 4.1 [Introducing the Text Interpreter], page 40.

¹⁷ When the text interpreter is processing input from the keyboard, this area of memory is called the *terminal input buffer* (TIB) and is addressed by the (obsolescent) words `TIB` and `#TIB`.

¹⁸ In other words, the text interpreter processes the contents of the input buffer by parsing strings from the parse area until the parse area is empty.


```

: remaining source >in @ /string
  cr ." ->" type ." <-" ; immediate

1 2 3 remaining + remaining .

: foo 1 2 3 remaining swap remaining ;

```

The result is:

```

->+ remaining .<-
->.<-5 ok

->SWAP remaining ;-<
->;<- ok

```

The value of >IN can also be modified by a word in the input buffer that is executed by the text interpreter. This means that a word can “trick” the text interpreter into either skipping a section of the input buffer¹⁹ or into parsing a section twice. For example:

```

: lat ." <<foo>>" ;
: flat ." <<bar>>" >IN DUP @ 3 - SWAP ! ;

```

When `flat` is executed, this output is produced²⁰:

```
<<bar>><<foo>>
```

This technique can be used to work around some of the interoperability problems of parsing words. Of course, it’s better to avoid parsing words where possible.

Two important notes about the behaviour of the text interpreter:

- It processes each input string to completion before parsing additional characters from the input buffer.
- It treats the input buffer as a read-only region (and so must your code).

When the text interpreter is in compile state, its behaviour changes in these ways:

- If a parsed string is found in the dictionary, the text interpreter will perform the word’s *compilation semantics*. In most cases, this simply means that the execution semantics of the word will be appended to the current definition.
- When a number is encountered, it is compiled into the current definition (as a literal) rather than being pushed onto a parameter stack.
- If an error occurs, `state` is modified to put the text interpreter back into interpret state.
- Each time a line is entered from the keyboard, Gforth prints “`compiled`” rather than “`ok`”.

When the text interpreter is using an input device other than the keyboard, its behaviour changes in these ways:

- When the parse area is empty, the text interpreter attempts to refill the input buffer from the input source. When the input source is exhausted, the input source is set back to the previous input source.

¹⁹ This is how parsing words work.

²⁰ Exercise for the reader: what would happen if the 3 were replaced with 4?

- It doesn't print out "ok" or "compiled" messages each time the parse area is emptied.
- If an error occurs, the input source is set back to the user input device.

You can read about this in more detail in Section 6.14.1 [Input Sources], page 127.

>in (*- addr*) core "to-in"

uvar variable – *a-addr* is the address of a cell containing the char offset from the start of the input buffer to the start of the parse area.

source (*- addr u*) core "source"

Return address *addr* and length *u* of the current input buffer

tib (*- addr*) core-ext-obsolete "t-i-b"

#tib (*- addr*) core-ext-obsolete "number-t-i-b"

uvar variable – *a-addr* is the address of a cell containing the number of characters in the terminal input buffer. OBSOLETE: **source** supercedes the function of this word.

6.14.1 Input Sources

By default, the text interpreter processes input from the user input device (the keyboard) when Forth starts up. The text interpreter can process input from any of these sources:

- The user input device – the keyboard.
- A file, using the words described in Section 6.18.1 [Forth source files], page 139.
- A block, using the words described in Section 6.19 [Blocks], page 144.
- A text string, using **evaluate**.

A program can identify the current input device from the values of **source-id** and **blk**.
source-id (*- 0 | -1 | fileid*) core-ext,file "source-i-d"

Return 0 (the input source is the user input device), -1 (the input source is a string being processed by **evaluate**) or a *fileid* (the input source is the file specified by *fileid*).

blk (*- addr*) block "b-l-k"

uvar variable – This cell contains the current block number (or 0 if the current input source is not a block).

save-input (*- x1 .. xn n*) core-ext "save-input"

The *n* entries *xn - x1* describe the current state of the input source specification, in some platform-dependent way that can be used by **restore-input**.

restore-input (*x1 .. xn n - flag*) core-ext "restore-input"

Attempt to restore the input source specification to the state described by the *n* entries *xn - x1*. *flag* is true if the restore fails. In Gforth with the new input code, it fails only with a flag that can be used to throw again; it is also possible to save and restore between different active input streams. Note that closing the input streams must happen in the reverse order as they have been opened, but in between everything is allowed.

evaluate (*... addr u - ...*) core,block "evaluate"

Save the current input source specification. Store -1 in **source-id** and 0 in **blk**. Set **>IN** to 0 and make the string *c-addr u* the input source and input buffer. Interpret. When the parse area is empty, restore the input source specification.

query (*-*) core-ext-obsolete "query"

Make the user input device the input source. Receive input into the Terminal Input Buffer. Set `>IN` to zero. OBSOLESCENT: superceeded by `accept`.

6.14.2 Number Conversion

You get an overview of how the text interpreter converts its numeric input in Chapter 5 [Literals in source code], page 51. This section describes some related words.

By default, the number base used for integer number conversion is given by the contents of the variable `base`. Note that a lot of confusion can result from unexpected values of `base`. If you change `base` anywhere, make sure to save the old value and restore it afterwards; better yet, use `base-execute`, which does this for you. In general I recommend keeping `base` decimal, and using the prefixes described in Chapter 5 [Literals in source code], page 51, for the popular non-decimal bases.

`base-execute` (*i*x xt u - j*x*) gforth-0.7 “base-execute”

execute *xt* with the content of `BASE` being *u*, and restoring the original `BASE` afterwards.

`base` (- *a-addr*) core “base”

User variable - *a-addr* is the address of a cell that stores the number base used by default for number conversion during input and output. Don't store to `base`, use `base-execute` instead.

`hex` (-) core-ext “hex”

Set `base` to &16 (hexadecimal). Don't use `hex`, use `base-execute` instead.

`decimal` (-) core “decimal”

Set `base` to &10 (decimal). Don't use `decimal`, use `base-execute` instead.

`dpl` (- *a-addr*) gforth-0.2 “Decimal-PLace”

User variable - *a-addr* is the address of a cell that stores the position of the decimal point in the most recent numeric conversion. Initialised to -1. After the conversion of a number containing no decimal point, `dpl` is -1. After the conversion of 2. it holds 0. After the conversion of 234123.9 it contains 1, and so forth.

Number conversion has a number of traps for the unwary:

- You cannot determine the current number base using the code sequence `base @ .` - the number base is always 10 in the current number base. Instead, use something like `base @ dec .`
- There is a word `bin` but it does *not* set the number base! (see Section 6.18.2 [General files], page 140).
- Standard Forth requires the `.` of a double-precision number to be the final character in the string. Gforth allows the `.` to be anywhere.
- The number conversion process does not check for overflow.

You can read numbers into your programs with the words described in Section 6.20.8 [Line input and conversion], page 157.

6.14.3 Interpret/Compile states

A standard program is not permitted to change `state` explicitly. However, it can change `state` implicitly, using the words `[` and `]`. When `[` is executed it switches `state` to interpret state, and therefore the text interpreter starts interpreting. When `]` is executed it switches

state to compile state and therefore the text interpreter starts compiling. The most common usage for these words is for switching into interpret state and back from within a colon definition; this technique can be used to compile a literal (for an example, see Section 6.13.1 [Literals], page 120) or for conditional compilation (for an example, see Section 6.14.4 [Interpreter Directives], page 129).

6.14.4 Interpreter Directives

These words are usually used in interpret state; typically to control which parts of a source file are processed by the text interpreter. There are only a few Standard Forth Standard words, but Gforth supplements these with a rich set of immediate control structure words to compensate for the fact that the non-immediate versions can only be used in compile state (see Section 6.9 [Control Structures], page 84). Typical usages:

```

FALSE Constant HAVE-ASSEMBLER
.
.
HAVE-ASSEMBLER [IF]
: ASSEMBLER-FEATURE
...
;
[ENDIF]
.
.
: SEE
... \ general-purpose SEE code
[ HAVE-ASSEMBLER [IF] ]
... \ assembler-specific SEE code
[ [ENDIF] ]
;
[IF] ( flag - ) tools-ext "bracket-if"
```

If flag is TRUE do nothing (and therefore execute subsequent words as normal). If flag is FALSE, parse and discard words from the parse area (refilling it if necessary using REFILL) including nested instances of [IF].. [ELSE].. [THEN] and [IF].. [THEN] until the balancing [ELSE] or [THEN] has been parsed and discarded. Immediate word.

[ELSE] (-) tools-ext "bracket-else"

Parse and discard words from the parse area (refilling it if necessary using REFILL) including nested instances of [IF].. [ELSE].. [THEN] and [IF].. [THEN] until the balancing [THEN] has been parsed and discarded. [ELSE] only gets executed if the balancing [IF] was TRUE; if it was FALSE, [IF] would have parsed and discarded the [ELSE], leaving the subsequent words to be executed as normal. Immediate word.

[THEN] (-) tools-ext "bracket-then"

Do nothing; used as a marker for other words to parse and discard up to. Immediate word.

[ENDIF] (-) gforth-0.2 "bracket-end-if"

Do nothing; synonym for [THEN]

[IFDEF] ("<spaces>name" -) gforth-0.2 "bracket-if-def"

If name is found in the current search-order, behave like [IF] with a TRUE flag, otherwise behave like [IF] with a FALSE flag. Immediate word.

[IFUNDEF] ("<spaces>name" -) gforth-0.2 "bracket-if-un-def"

If name is not found in the current search-order, behave like [IF] with a TRUE flag, otherwise behave like [IF] with a FALSE flag. Immediate word.

[?DO] (*n-limit n-index* -) gforth-0.2 "bracket-question-do"

[DO] (*n-limit n-index* -) gforth-0.2 "bracket-do"

[FOR] (*n* -) gforth-0.2 "bracket-for"

[LOOP] (-) gforth-0.2 "bracket-loop"

[+LOOP] (*n* -) gforth-0.2 "bracket-question-plus-loop"

[NEXT] (*n* -) gforth-0.2 "bracket-next"

[BEGIN] (-) gforth-0.2 "bracket-begin"

[UNTIL] (*flag* -) gforth-0.2 "bracket-until"

[AGAIN] (-) gforth-0.2 "bracket-again"

[WHILE] (*flag* -) gforth-0.2 "bracket-while"

[REPEAT] (-) gforth-0.2 "bracket-repeat"

6.14.5 Recognizers

The standard Forth text interpreter recognizes the following types of tokens: words in the dictionary, integer numbers, and floating point numbers. Defining new types of tokens isn't yet standardized. Gforth provides recognizers to make the text interpreter extensible as well.

Recognizers take a string and return some data and a translator for interpreting that data. Gforth implements that translator as xt (executing it will perform the appropriate action to handle the token in the current state), but other Forth systems may implement it as actual table, with three xts inside. The first xt is the interpretation/run-time xt, it performs the interpretation semantics on the data (usually, this means it just leaves the data on the stack). The second xt performs the compilation semantics, it gets the data and the run-time semantics xt. The third xt performs the postpone semantics, it also gets the data and the run-time semantics xt. You can use `>postpone` to postpone the run-time xt.

Recognizers are organized as stack, so you can arrange the sequence of recognizers in the same way as the vocabulary stack. Recognizer stacks are themselves recognizers, i.e. they are executable, take a string and return a translator.

notfound (*state* -) gforth-experimental "notfound"

If a recognizer fails, it returns **notfound**

rec-nt (*addr u - nt translate-nt | notfound*) gforth-experimental "rec-nt"

recognize a name token

rec-num (*addr u - n/d table | notfound*) gforth-experimental "rec-num"

converts a number to a single/double integer

rec-float (*addr u - r translate-float | notfound*) gforth-experimental "rec-float"

recognize floating point numbers

rec-string (*addr u - addr u' r:string | rectype-null*) gforth-experimental "rec-string"

Convert strings enclosed in double quotes into string literals, escapes are treated as in S\".

rec-to (*addr u* - *xt r:to* | *rectype-null*) gforth-experimental “rec-to”

words prefixed with -> are treated as if preceeded by T0 or IS, with +> as +T0 and with '>' as ADDR.

rec-tick (*addr u* - *xt rectype-num* | *rectype-null*) gforth-experimental “rec-tick”

words prefixed with ‘ return their xt. Example: ‘dup gives the xt of dup

rec-dtick (*addr u* - *nt rectype-num* | *rectype-null*) gforth-experimental “rec-dtick”

words prefixed with ‘‘ return their nt. Example: ‘‘S” gives the nt of S”

rec-body (*addr u* - *xt translate-tick* | *translate-null*) gforth-experimental “rec-body”

words bracketed with '<' '>' return their body. Example: <dup> gives the body of dup

get-recognizers (- *xt1 .. xtn n*) gforth-experimental “get-recognizers”

push the content on the recognizer stack

set-recognizers (*xt1 .. xtn n* -) gforth-experimental “set-recognizers”

set the recognizer stack from content on the stack

recognize (*addr u rec-addr* - ... *rectype*) gforth-experimental “recognize”

apply a recognizer stack to a string, delivering a token

doc-recognize-sequence:

forth-recognize (*c-addr u* - ... *translate-xt*) recognizer “forth-recognize”

The system recognizer

forth-recognizer (- *xt*) gforth-experimental “forth-recognizer”

backward compatible to Matthias Trute recognizer API

set-forth-recognize (*xt* -) recognizer “set-forth-recognize”

Change the system recognizer

translate: (*int-xt comp-xt post-xt "name"* -) gforth-experimental “translate:”

create a new recognizer table. Items are in order of *STATE* value, which are 0 or negative. Up to 7 slots are available for extensions.

translate-nt (*i*x nt* - *j*x*) gforth-experimental “translate-nt”

translate a name token

translate-num (*x* - | *x*) gforth-experimental “translate-num”

translate a number

doc-translate-float

The following extension is only avaiable if you load **recognizer-ext.fs**:

doc-interpret-translator doc-compile-translator doc-postpone-translator doc-translator:

6.15 The Input Stream

The text interpreter reads from the input stream, which can come from several sources (see Section 6.14.1 [Input Sources], page 127). Some words, in particular defining words, but also words like `'`, read parameters from the input stream instead of from the stack.

Such words are called parsing words, because they parse the input stream. Parsing words are hard to use in other words, because it is hard to pass program-generated parameters through the input stream. They also usually have an unintuitive combination of interpretation and compilation semantics when implemented naively, leading to various approaches that try to produce a more intuitive behaviour (see Section 6.11.1 [Combined words], page 116).

It should be obvious by now that parsing words are a bad idea. If you want to implement a parsing word for convenience, also provide a factor of the word that does not parse, but takes the parameters on the stack. To implement the parsing word on top of it, you can use the following words:

parse (*xchar* "ccc<xchar>" – *c-addr u*) core-ext,xchar-ext "parse"

Parse *ccc*, delimited by *xchar*, in the parse area. *c-addr u* specifies the parsed string within the parse area. If the parse area was empty, *u* is 0.

parse-name ("name" – *c-addr u*) core-ext "parse-name"

Get the next word from the input buffer

parse-word (– *c-addr u*) gforth-obsolete "parse-word"

old name for **parse-name**; this word has a conflicting behaviour in some other systems.

name (– *c-addr u*) gforth-obsolete "name"

old name for **parse-name**

word (*char* "<chars>ccc<char>" – *c-addr*) core "word"

Skip leading delimiters. Parse *ccc*, delimited by *char*, in the parse area. *c-addr* is the address of a transient region containing the parsed string in counted-string format. If the parse area was empty or contained no characters other than delimiters, the resulting string has zero length. A program may replace characters within the counted string. OBSOLESCENT: the counted string has a trailing space that is not included in its length.

refill (– *flag*) core-ext,block-ext,file-ext "refill"

Attempt to fill the input buffer from the input source. When the input source is the user input device, attempt to receive input into the terminal input device. If successful, make the result the input buffer, set `>IN` to 0 and return true; otherwise return false. When the input source is a block, add 1 to the value of `BLK` to make the next block the input source and current input buffer, and set `>IN` to 0; return true if the new value of `BLK` is a valid block number, false otherwise. When the input source is a text file, attempt to read the next line from the file. If successful, make the result the current input buffer, set `>IN` to 0 and return true; otherwise, return false. A successful result includes receipt of a line containing 0 characters.

If you have to deal with a parsing word that does not have a non-parsing factor, you can use **execute-parsing** to pass a string to it:

execute-parsing (... *addr u xt* – ...) gforth-0.6 "execute-parsing"

Make *addr u* the current input source, execute *xt* (... -- ...), then restore the previous input source.

Example:

```
5 s" foo" ' constant execute-parsing
\ equivalent to
5 constant foo
```

A definition of this word in Standard Forth is provided in `compat/execute-parsing.fs`.

If you want to run a parsing word on a file, the following word should help:

`execute-parsing-file` (*i*x fileid xt - j*x*) gforth-0.6 “execute-parsing-file”

Make *fileid* the current input source, execute *xt* (*i*x -- j*x*), then restore the previous input source.

6.16 Word Lists

A wordlist is a list of named words; you can add new words and look up words by name (and you can remove words in a restricted way with markers). Every named (and **revealed**) word is in one wordlist.

The text interpreter searches the wordlists present in the search order (a stack of wordlists), from the top to the bottom. Within each wordlist, the search starts conceptually at the newest word; i.e., if two words in a wordlist have the same name, the newer word is found.

New words are added to the *compilation wordlist* (aka current wordlist).

A word list is identified by a cell-sized word list identifier (*wid*) in much the same way as a file is identified by a file handle. The numerical value of the *wid* has no (portable) meaning, and might change from session to session.

The Standard Forth “Search order” word set is intended to provide a set of low-level tools that allow various different schemes to be implemented. Gforth also provides `vocabulary`, a traditional Forth word. `compat/vocabulary.fs` provides an implementation in Standard Forth.

`forth-wordlist` (- *wid*) search “forth-wordlist”

`definitions` (-) search “definitions”

Set the compilation word list to be the same as the word list that is currently at the top of the search order.

`get-current` (- *wid*) search “get-current”

wid is the identifier of the current compilation word list.

`set-current` (*wid* -) search “set-current”

Set the compilation word list to the word list identified by *wid*.

`get-order` (- *widn* .. *wid1 n*) search “get-order”

Copy the search order to the data stack. The current search order has *n* entries, of which *wid1* represents the wordlist that is searched first (the word list at the top of the search order) and *widn* represents the wordlist that is searched last.

`set-order` (*widn* .. *wid1 n* -) search “set-order”

If *n*=0, empty the search order. If *n*=-1, set the search order to the implementation-defined minimum search order (for Gforth, this is the word list `Root`). Otherwise, replace

the existing search order with the *n* *wid* entries such that *wid1* represents the word list that will be searched first and *widn* represents the word list that will be searched last.

wordlist (- *wid*) search “wordlist”

Create a new, empty word list represented by *wid*.

table (- *wid*) gforth-0.2 “table”

Create a lookup table (case-sensitive, no warnings).

cs-wordlist (- *wid*) gforth-1.0 “cs-wordlist”

Create a case-sensitive wordlist.

cs-vocabulary ("*name*" -) gforth-1.0 “cs-vocabulary”

Create a case-sensitive vocabulary

>order (*wid* -) gforth-0.5 “to-order”

Push *wid* on the search order.

previous (-) search-ext “previous”

Drop the wordlist at the top of the search order.

also (-) search-ext “also”

Like DUP for the search order. Usually used before a vocabulary (e.g., **also Forth**); the combined effect is to push the wordlist represented by the vocabulary on the search order.

Forth (-) search-ext “Forth”

Replace the *wid* at the top of the search order with the *wid* associated with the word list **forth-wordlist**.

Only (-) search-ext “Only”

Set the search order to the implementation-defined minimum search order (for Gforth, this is the word list **Root**).

order (-) search-ext “order”

Print the search order and the compilation word list. The word lists are printed in the order in which they are searched (which is reversed with respect to the conventional way of displaying stacks). The compilation word list is displayed last.

find (*c-addr* - *xt* +-1 | *c-addr* 0) core,search “find”

Search all word lists in the current search order for the definition named by the counted string at *c-addr*. If the definition is not found, return 0. If the definition is found return 1 (if the definition has non-default compilation semantics) or -1 (if the definition has default compilation semantics). The *xt* returned in interpret state represents the interpretation semantics. The *xt* returned in compile state represented either the compilation semantics (for non-default compilation semantics) or the run-time semantics that the compilation semantics would **compile**, (for default compilation semantics). The ANS Forth standard does not specify clearly what the returned *xt* represents (and also talks about immediacy instead of non-default compilation semantics), so this word is questionable in portable programs. If non-portability is ok, **find-name** and friends are better (see Section 6.12.2 [Name token], page 118). list all words matching the optional parameter *pattern*; if none, all words match. Words are listed old to new. Pattern match like **search** (default), possible to switch to

filename-match. status line prints a stack of status words filename of view (obtained by `name>view`)

search-wordlist (*c-addr count wid* – 0 | *xt* +1) search “search-wordlist”

Search the word list identified by *wid* for the definition named by the string at *c-addr count*. If the definition is not found, return 0. If the definition is found return 1 (if the definition is immediate) or -1 (if the definition is not immediate) together with the *xt*. In Gforth, the *xt* returned represents the interpretation semantics. ANS Forth does not specify clearly what *xt* represents.

words (–) tools “words”

** this will not get annotated. See other defn in search.fs .. ** It does not work to use "wordset-" prefix since this file is glossed by cross.fs which doesn't have the same functionality as makedoc.fs

vlist (–) gforth-0.2 “vlist”

Old (pre-Forth-83) name for **WORDS**.

Root (–) gforth-0.2 “Root”

Add the root wordlist to the search order stack. This vocabulary makes up the minimum search order and contains only a search-order words.

Vocabulary (“name” –) gforth-0.2 “Vocabulary”

Create a definition “name” and associate a new word list with it. The run-time effect of “name” is to replace the *wid* at the top of the search order with the *wid* associated with the new word list.

seal (–) gforth-0.2 “seal”

Remove all word lists from the search order stack other than the word list that is currently on the top of the search order stack.

vocs (–) gforth-0.2 “vocs”

List vocabularies and wordlists defined in the system.

current (– *addr*) gforth-0.2 “current”

Variable – holds the *wid* of the compilation word list.

context (– *addr*) gforth-0.2 “context”

context @ is the *wid* of the word list at the top of the search order.

6.16.1 Vocabularies

Here is an example of creating and using a new wordlist using Standard Forth words:

```
wordlist constant my-new-words-wordlist
: my-new-words get-order nip my-new-words-wordlist swap set-order ;

\ add it to the search order
also my-new-words

\ alternatively, add it to the search order and make it
\ the compilation word list
also my-new-words definitions
```

```
\ type "order" to see the problem
```

The problem with this example is that `order` has no way to associate the name `my-new-words` with the wid of the word list (in Gforth, `order` and `vocs` will display `???` for a wid that has no associated name). There is no Standard way of associating a name with a wid.

In Gforth, this example can be re-coded using `vocabulary`, which associates a name with a wid:

```
vocabulary my-new-words
```

```
\ add it to the search order
also my-new-words
```

```
\ alternatively, add it to the search order and make it
\ the compilation word list
my-new-words definitions
\ type "order" to see that the problem is solved
```

6.16.2 Why use word lists?

Here are some reasons why people use wordlists:

- To prevent a set of words from being used outside the context in which they are valid. Two classic examples of this are an integrated editor (all of the edit commands are defined in a separate word list; the search order is set to the editor word list when the editor is invoked; the old search order is restored when the editor is terminated) and an integrated assembler (the op-codes for the machine are defined in a separate word list which is used when a `CODE` word is defined).
- To organize the words of an application or library into a user-visible set (in `forth-wordlist` or some other common wordlist) and a set of helper words used just for the implementation (hidden in a separate wordlist). This keeps `words`' output smaller, separates implementation and interface, and reduces the chance of name conflicts within the common wordlist.
- To prevent a name-space clash between multiple definitions with the same name. For example, when building a cross-compiler you might have a word `IF` that generates conditional code for your target system. By placing this definition in a different word list you can control whether the host system's `IF` or the target system's `IF` get used in any particular context by controlling the order of the word lists on the search order stack.

The downsides of using wordlists are:

- Debugging becomes more cumbersome.
- Name conflicts worked around with wordlists are still there, and you have to arrange the search order carefully to get the desired results; if you forget to do that, you get hard-to-find errors (as in any case where you read the code differently from the compiler; `see` can help seeing which of several possible words the name resolves to in such cases). `See` displays just the name of the words, not what wordlist they belong to, so it might be misleading. Using unique names is a better approach to avoid name conflicts.

- You have to explicitly undo any changes to the search order. In many cases it would be more convenient if this happened implicitly. Gforth currently does not provide such a feature, but it may do so in the future.

6.16.3 Word list example

The following example is from the garbage collector (<https://www.complang.tuwien.ac.at/forth/garbage-collection.zip>) and uses wordlists to separate public words from helper words:

```
get-current ( wid )
vocabulary garbage-collector also garbage-collector definitions
... \ define helper words
( wid ) set-current \ restore original (i.e., public) compilation wordlist
... \ define the public (i.e., API) words
    \ they can refer to the helper words
previous \ restore original search order (helper words become invisible)
```

6.17 Environmental Queries

Forth-94 introduced the idea of “environmental queries” as a way for a program running on a system to determine certain characteristics of the system. The Standard specifies a number of strings that might be recognised by a system.

The Standard requires that the header space used for environmental queries be distinct from the header space used for definitions.

Typically, environmental queries are supported by creating a set of definitions in a word list that is *only* used during environmental queries; that is what Gforth does. There is no Standard way of adding definitions to the set of recognised environmental queries, but any implementation that supports the loading of optional word sets must have some mechanism for doing this (after loading the word set, the associated environmental query string must return **true**). In Gforth, the word list used to honour environmental queries can be manipulated just like any other word list.

environment? (*c-addr u* – *false* / ... *true*) core “environment-query”

c-addr, u specify a counted string. If the string is not recognised, return a **false** flag. Otherwise return a **true** flag and some (string-specific) information about the queried string.

environment-wordlist (– *wid*) gforth-0.2 “environment-wordlist”

wid identifies the word list that is searched by environmental queries.

gforth (– *c-addr u*) gforth-environment “gforth”

Counted string representing a version string for this version of Gforth (for versions > 0.3.0). The version strings of the various versions are guaranteed to be ordered lexicographically.

os-class (– *c-addr u*) gforth-environment “os-class”

Counted string representing a description of the host operating system.

Note that, whilst the documentation for (e.g.) **gforth** shows it returning two items on the stack, querying it using **environment?** will return an additional item; the **true** flag that shows that the string was recognised.

Here are some examples of using environmental queries:

```
s" address-unit-bits" environment? 0=
[IF]
    cr .( environmental attribute address-units-bits unknown... ) cr
[ELSE]
    drop \ ensure balanced stack effect
[THEN]

\ this might occur in the prelude of a standard program that uses THROW
s" exception" environment? [IF]
    0= [IF]
        : throw abort" exception thrown" ;
    [THEN]
[ELSE] \ we don't know, so make sure
    : throw abort" exception thrown" ;
[THEN]

s" gforth" environment? [IF] .( Gforth version ) TYPE
[ELSE] .( Not Gforth..) [THEN]

\ a program using v*
s" gforth" environment? [IF]
    s" 0.5.0" compare 0< [IF] \ v* is a primitive since 0.5.0
        : v* ( f_addr1 nstride1 f_addr2 nstride2 ucount -- r )
            >r swap 2swap swap 0e r> 0 ?DO
                dup f@ over + 2swap dup f@ f* f+ over + 2swap
            LOOP
            2drop 2drop ;
        [THEN]
[ELSE] \
    : v* ( f_addr1 nstride1 f_addr2 nstride2 ucount -- r )
        ...
[THEN]
```

Here is an example of adding a definition to the environment word list:

```
get-current environment-wordlist set-current
true constant block
true constant block-ext
set-current
```

You can see what definitions are in the environment word list like this:

```
environment-wordlist >order words previous
```

6.18 Files

Gforth provides facilities for accessing files that are stored in the host operating system's file-system. Files that are processed by Gforth can be divided into two categories:

- Files that are processed by the Text Interpreter (*Forth source files*).

- Files that are processed by some other program (*general files*).

6.18.1 Forth source files

The simplest way to interpret the contents of a file is to use one of these two formats:

```
include mysource.fs
s" mysource.fs" included
```

You usually want to include a file only if it is not included already (by, say, another source file). In that case, you can use one of these three formats:

```
require mysource.fs
needs mysource.fs
s" mysource.fs" required
```

It is good practice to write your source files such that interpreting them does not change the stack. Source files designed in this way can be used with **required** and friends without complications. For example:

```
1024 require foo.fs drop
```

Here you want to pass the argument 1024 (e.g., a buffer size) to **foo.fs**. Interpreting **foo.fs** has the stack effect ($n - n$), which allows its use with **require**. Of course with such parameters to required files, you have to ensure that the first **require** fits for all uses (i.e., **require** it early in the master load file).

```
include-file ( i*x wfileid - j*x ) file "include-file"
```

Interpret (process using the text interpreter) the contents of the file *wfileid*.

```
included ( i*x c-addr u - j*x ) file "included"
```

include-file the file whose name is given by the string *c-addr u*.

```
included? ( c-addr u - f ) gforth-0.2 "included?"
```

True only if the file *c-addr u* is in the list of earlier included files. If the file has been loaded, it may have been specified as, say, **foo.fs** and found somewhere on the Forth search path. To return **true** from **included?**, you must specify the exact path to the file, even if that is **./foo.fs**

```
include ( ... "file" - ... ) file-ext "include"
```

include-file the file *file*.

```
required ( i*x addr u - i*x ) file-ext "required"
```

include-file the file with the name given by *addr u*, if it is not **included** (or **required**) already. Currently this works by comparing the name of the file (with path) against the names of earlier included files.

```
require ( ... "file" - ... ) file-ext "require"
```

include-file *file* only if it is not included already.

```
needs ( ... "name" - ... ) gforth-0.2 "needs"
```

An alias for **require**; exists on other systems (e.g., Win32Forth).

```
sourcefilename ( - c-addr u ) gforth-0.2 "sourcefilename"
```

The name of the source file which is currently the input source. The result is valid only while the file is being loaded. If the current input source is no (stream) file, the result is

undefined. In Gforth, the result is valid during the whole session (but not across `savesystem` etc.).

sourceline# (*- u*) gforth-0.2 “sourceline-number”

The line number of the line that is currently being interpreted from a (stream) file. The first line has the number 1. If the current input source is not a (stream) file, the result is undefined.

A definition in Standard Forth for `required` is provided in `compat/required.fs`.

6.18.2 General files

Files are opened/created by name and type. The following file access methods (FAMs) are recognised:

r/o (*- fam*) file “r-o”

r/w (*- fam*) file “r-w”

w/o (*- fam*) file “w-o”

bin (*fam1 - fam2*) file “bin”

+fmode (*fam1 rwxrwxrwx - fam2*) gforth-1.0 “plus-f-mode”

add file access mode to fam - for create-file only

When a file is opened/created, it returns a file identifier, *wfileid* that is used for all other file commands. All file commands also return a status value, *wior*, that is 0 for a successful operation and an implementation-defined non-zero value in the case of an error.

open-file (*c-addr u wfam - wfileid wior*) file “open-file”

create-file (*c-addr u wfam - wfileid wior*) file “create-file”

close-file (*wfileid - wior*) file “close-file”

delete-file (*c-addr u - wior*) file “delete-file”

rename-file (*c-addr1 u1 c-addr2 u2 - wior*) file-ext “rename-file”

Rename file *c-addr1 u1* to new name *c-addr2 u2*

read-file (*c-addr u1 wfileid - u2 wior*) file “read-file”

Read *u1* characters from file *wfileid* into the buffer at *c-addr*. A non-zero *wior* indicates an error. *U2* indicates the length of the read data. End-of-file is not an error and is indicated by *u2* < *u1* and *wior*=0.

read-line (*c-addr u1 wfileid - u2 flag wior*) file “read-line”

Reads a line from *wfileid* into the buffer at *c-addr u1*. Gforth supports all three common line terminators: LF, CR and CRLF. A non-zero *wior* indicates an error. A false *flag* indicates that **read-line** has been invoked at the end of the file. *u2* indicates the line length (without terminator): *u2* < *u1* indicates that the line is *u2* chars long; *u2*=*u1* indicates that the line is at least *u1* chars long, the *u1* chars of the buffer have been filled with chars from the line, and the next slice of the line will be read with the next **read-line**. If the line is *u1* chars long, the first **read-line** returns *u2*=*u1* and the next read-line returns *u2*=0.

key-file (*fd - key*) gforth-0.4 “key-file”

Read one character *n* from *wfileid*. This word disables buffering for *wfileid*. If you want to read characters from a terminal in non-canonical (raw) mode, you have to put the terminal

in non-canonical mode yourself (using the C interface); the exception is `stdin`: Gforth automatically puts it into non-canonical mode.

`key?-file (wfileid - f) gforth-0.4 “key-q-file”`

f is true if at least one character can be read from *wfileid* without blocking. If you also want to use `read-file` or `read-line` on the file, you have to call `key?-file` or `key-file` first (these two words disable buffering).

`file-eof? (wfileid - flag) gforth-0.6 “file-eof-query”`

Flag is true if the end-of-file indicator for *wfileid* is set.

`write-file (c-addr u1 wfileid - wior) file “write-file”`

`write-line (c-addr u wfileid - ior) file “write-line”`

`emit-file (c wfileid - wior) gforth-0.2 “emit-file”`

`flush-file (wfileid - wior) file-ext “flush-file”`

`file-status (c-addr u - wfam wior) file-ext “file-status”`

`file-position (wfileid - ud wior) file “file-position”`

`reposition-file (ud wfileid - wior) file “reposition-file”`

`file-size (wfileid - ud wior) file “file-size”`

`resize-file (ud wfileid - wior) file “resize-file”`

`slurp-file (c-addr1 u1 - c-addr2 u2) gforth-0.6 “slurp-file”`

c-addr1 u1 is the filename, *c-addr2 u2* is the file’s contents

`slurp-fid (fid - addr u) gforth-0.6 “slurp-fid”`

addr u is the content of the file *fid*

`stdin (- wfileid) gforth-0.4 “stdin”`

The standard input file of the Gforth process.

`stdout (- wfileid) gforth-0.2 “stdout”`

The standard output file of the Gforth process.

`stderr (- wfileid) gforth-0.2 “stderr”`

The standard error output file of the Gforth process.

6.18.3 Redirection

You can redirect the output of `type` and `emit` and all the words that use them (all output words that don’t have an explicit target file) to an arbitrary file with the `outfile-execute`, used like this:

```
: some-warning ( n -- )
  cr ." warning# " . ;

: print-some-warning ( n -- )
  ['] some-warning stderr outfile-execute ;
```

After `some-warning` is executed, the original output direction is restored; this construct is safe against exceptions. Similarly, there is `infile-execute` for redirecting the input of `key` and its users (any input word that does not take a file explicitly).

`outfile-execute (... xt file-id - ...) gforth-0.7 “outfile-execute”`

execute *xt* with the output of **type** etc. redirected to *file-id*.

outfile-id (*- file-id*) gforth-0.2 “outfile-id”

File-id is used by **emit**, **type**, and any output word that does not take a file-id as input. By default **outfile-id** produces the process’s **stdout**, unless changed with **outfile-execute**.

infile-execute (... *xt file-id* - ...) gforth-0.7 “infile-execute”

execute *xt* with the input of **key** etc. redirected to *file-id*. execute a theme-color changing *xt* and return to the previous theme color

infile-id (*- file-id*) gforth-0.4 “infile-id”

File-id is used by **key**, **?key**, and anything that refers to the “user input device”. By default **infile-id** produces the process’s **stdin**, unless changed with **infile-execute**.

If you do not want to redirect the input or output to a file, you can also make use of the fact that **key**, **emit** and **type** are deferred words (see Section 6.10.10 [Deferred Words], page 112). However, in that case you have to worry about the restoration and the protection against exceptions yourself; also, note that for redirecting the output in this way, you have to redirect both **emit** and **type**.

6.18.4 Directories

You can open and read directories similar to files. Reading gives you one directory entry at a time; you can match that to a filename (with wildcards).

open-dir (*c-addr u - wdirid wior*) gforth-0.5 “open-dir”

Open the directory specified by *c-addr*, *u* and return *dir-id* for further access to it.

read-dir (*c-addr u1 wdirid - u2 flag wior*) gforth-0.5 “read-dir”

Attempt to read the next entry from the directory specified by *dir-id* to the buffer of length *u1* at address *c-addr*. If the attempt fails because there is no more entries, *ior*=0, *flag*=0, *u2*=0, and the buffer is unmodified. If the attempt to read the next entry fails because of any other reason, return *ior*<>0. If the attempt succeeds, store file name to the buffer at *c-addr* and return *ior*=0, *flag*=true and *u2* equal to the size of the file name. If the length of the file name is greater than *u1*, store first *u1* characters from file name into the buffer and indicate “name too long” with *ior*, *flag*=true, and *u2*=*u1*.

close-dir (*wdirid - wior*) gforth-0.5 “close-dir”

Close the directory specified by *dir-id*.

filename-match (*c-addr1 u1 c-addr2 u2 - flag*) gforth-0.5 “match-file”

match the file name *c-addr1 u1* with the pattern *c-addr2 u2*. Patterns match char by char except for the special characters ‘*’ and ‘?’, which are wildcards for several (‘*’) or one (‘?’) character.

get-dir (*c-addr1 u1 - c-addr2 u2*) gforth-0.7 “get-dir”

Store the current directory in the buffer specified by *c-addr1*, *u1*. If the buffer size is not sufficient, return 0 0

set-dir (*c-addr u - wior*) gforth-0.7 “set-dir”

Change the current directory to *c-addr*, *u*. Return an error if this is not possible

=mkdir (*c-addr u wmode - wior*) gforth-0.7 “equals-mkdir”

Create directory *c-addr u* with mode *wmode*.

mkdir-parents (*c-addr u mode - ior*) gforth-0.7 “mkdir-parents”

create the directory *c-addr u* and all its parents with mode *mode* (modified by *umask*)
get rest of the string word to update the editor display

6.18.5 Search Paths

If you specify an absolute filename (i.e., a filename starting with */* or *~*, or with *:* in the second position (as in ‘*C:...*’)) for **included** and friends, that file is included just as you would expect.

If the filename starts with *./*, this refers to the directory that the present file was **included** from. This allows files to include other files relative to their own position (irrespective of the current working directory or the absolute position). This feature is essential for libraries consisting of several files, where a file may include other files from the library. It corresponds to **#include "..."** in C. If the current input source is not a file, *.* refers to the directory of the innermost file being included, or, if there is no file being included, to the current working directory.

For relative filenames (not starting with *./*), Gforth uses a search path similar to Forth’s search order (see Section 6.16 [Word Lists], page 133). It tries to find the given filename in the directories present in the path, and includes the first one it finds. There are separate search paths for Forth source files and general files. If the search path contains the directory *.*, this refers to the directory of the current file, or the working directory, as if the file had been specified with *./*.

Use *~+* to refer to the current working directory (as in the **bash**).

6.18.5.1 Source Search Paths

The search path is initialized when you start Gforth (see Section 2.1 [Invoking Gforth], page 3). You can display it and change it using **fpath** in combination with the general path handling words.

fpath (*- path-addr*) gforth-0.4 “fpath”

Here is an example of using **fpath** and **require**:

```
fpath path= /usr/lib/forth/|./
require timer.fs
```

6.18.5.2 General Search Paths

Your application may need to search files in several directories, like **included** does. To facilitate this, Gforth allows you to define and use your own search paths, by providing generic equivalents of the Forth search path words:

open-path-file (*addr1 u1 path-addr - wfileid addr2 u2 0 | ior*) gforth-0.2 “open-path-file”

Look in path *path-addr* for the file specified by *addr1 u1*. If found, the resulting path and an (read-only) open file descriptor are returned. If the file is not found, *ior* is what came back from the last attempt at opening the file (in the current implementation).

clear-path (*path-addr -*) gforth-0.5 “clear-path”

Set the path *path-addr* to empty.

```
also-path ( c-addr len path-addr - ) gforth-0.4 "also-path"
```

add the directory *c-addr len* to *path-addr*.

```
.path ( path-addr - ) gforth-0.4 ".path"
```

Display the contents of the search path *path-addr*.

```
path+ ( path-addr "dir" - ) gforth-0.4 "path+"
```

Add the directory *dir* to the search path *path-addr*.

```
path= ( path-addr "dir1|dir2|dir3" - ) gforth-0.4 "path-equals"
```

Make a complete new search path; the path separator is |.

Here's an example of creating a custom search path:

```
variable mypath \ no special allocation required, just a variable
mypath path= /lib|usr/lib \ assign initial directories
mypath path+ /usr/local/lib \ append directory
mypath .path \ output: "/lib /usr/lib /usr/local/lib"
```

Search file and show resulting path:

```
s" libm.so" mypath open-path-file throw type close-file \ output: "/lib/libm.so"■
```

6.19 Blocks

When you run Gforth on a modern desk-top computer, it runs under the control of an operating system which provides certain services. One of these services is *file services*, which allows Forth source code and data to be stored in files and read into Gforth (see Section 6.18 [Files], page 138).

Traditionally, Forth has been an important programming language on systems where it has interfaced directly to the underlying hardware with no intervening operating system. Forth provides a mechanism, called *blocks*, for accessing mass storage on such systems.

A block is a 1024-byte data area, which can be used to hold data or Forth source code. No structure is imposed on the contents of the block. A block is identified by its number; blocks are numbered contiguously from 1 to an implementation-defined maximum.

A typical system that used blocks but no operating system might use a single floppy-disk drive for mass storage, with the disks formatted to provide 256-byte sectors. Blocks would be implemented by assigning the first four sectors of the disk to block 1, the second four sectors to block 2 and so on, up to the limit of the capacity of the disk. The disk would not contain any file system information, just the set of blocks.

On systems that do provide file services, blocks are typically implemented by storing a sequence of blocks within a single *blocks file*. The size of the blocks file will be an exact multiple of 1024 bytes, corresponding to the number of blocks it contains. This is the mechanism that Gforth uses.

Only one blocks file can be open at a time. If you use block words without having specified a blocks file, Gforth defaults to the blocks file `blocks.fb`. Gforth uses the Forth search path when attempting to locate a blocks file (see Section 6.18.5.1 [Source Search Paths], page 143).

When you read and write blocks under program control, Gforth uses a number of *block buffers* as intermediate storage. These buffers are not used when you use `load` to interpret the contents of a block.

The behaviour of the block buffers is analogous to that of a cache. Each block buffer has three states:

- Unassigned
- Assigned-clean
- Assigned-dirty

Initially, all block buffers are *unassigned*. In order to access a block, the block (specified by its block number) must be assigned to a block buffer.

The assignment of a block to a block buffer is performed by `block` or `buffer`. Use `block` when you wish to modify the existing contents of a block. Use `buffer` when you don't care about the existing contents of the block²¹.

Once a block has been assigned to a block buffer using `block` or `buffer`, that block buffer becomes the *current block buffer*. Data may only be manipulated (read or written) within the current block buffer.

When the contents of the current block buffer has been modified it is necessary, *before calling `block` or `buffer` again*, to either abandon the changes (by doing nothing) or mark the block as changed (assigned-dirty), using `update`. Using `update` does not change the blocks file; it simply changes a block buffer's state to *assigned-dirty*. The block will be written implicitly when it's buffer is needed for another block, or explicitly by `flush` or `save-buffers`.

word `Flush` writes all *assigned-dirty* blocks back to the blocks file on disk. Leaving Gforth with `bye` also performs a `flush`.

In Gforth, `block` and `buffer` use a *direct-mapped* algorithm to assign a block buffer to a block. That means that any particular block can only be assigned to one specific block buffer, called (for the particular operation) the *victim buffer*. If the victim buffer is *unassigned* or *assigned-clean* it is allocated to the new block immediately. If it is *assigned-dirty* its current contents are written back to the blocks file on disk before it is allocated to the new block.

Although no structure is imposed on the contents of a block, it is traditional to display the contents as 16 lines each of 64 characters. A block provides a single, continuous stream of input (for example, it acts as a single parse area) – there are no end-of-line characters within a block, and no end-of-file character at the end of a block. There are two consequences of this:

- The last character of one line wraps straight into the first character of the following line
- The word `\` – comment to end of line – requires special treatment; in the context of a block it causes all characters until the end of the current 64-character “line” to be ignored.

²¹ The Standard Forth definition of `buffer` is intended not to cause disk I/O; if the data associated with the particular block is already stored in a block buffer due to an earlier `block` command, `buffer` will return that block buffer and the existing contents of the block will be available. Otherwise, `buffer` will simply assign a new, empty block buffer for the block.

In Gforth, when you use **block** with a non-existent block number, the current blocks file will be extended to the appropriate size and the block buffer will be initialised with spaces.

Gforth includes a simple block editor (type `use blocked.fb 0 list` for details) but doesn't encourage the use of blocks; the mechanism is only provided for backward compatibility.

Common techniques that are used when working with blocks include:

- A screen editor that allows you to edit blocks without leaving the Forth environment.
- Shadow screens; where every code block has an associated block containing comments (for example: code in odd block numbers, comments in even block numbers). Typically, the block editor provides a convenient mechanism to toggle between code and comments.
- Load blocks; a single block (typically block 1) contains a number of **thru** commands which **load** the whole of the application.

See Frank Sergeant's Pygmy Forth to see just how well blocks can be integrated into a Forth programming environment.

open-blocks (*c-addr u* -) gforth-0.2 "open-blocks"

Use the file, whose name is given by *c-addr u*, as the blocks file.

use ("*file*" -) gforth-0.2 "use"

Use *file* as the blocks file.

block-offset (- *addr*) gforth-0.5 "block-offset"

User variable containing the number of the first block (default since 0.5.0: 0). Block files created with Gforth versions before 0.5.0 have the offset 1. If you use these files you can: **1 offset !**; or add 1 to every block number used; or prepend 1024 characters to the file.

get-block-fid (- *wfileid*) gforth-0.2 "get-block-fid"

Return the file-id of the current blocks file. If no blocks file has been opened, use **blocks.fb** as the default blocks file.

block-position (*u* -) block "block-position"

Position the block file to the start of block *u*.

list (*u* -) block-ext "list"

Display block *u*. In Gforth, the block is displayed as 16 numbered lines, each of 64 characters.

scr (- *a-addr*) block-ext "s-c-r"

User variable containing the block number of the block most recently processed by **list**.

block (*u* - *a-addr*) block "block"

If a block buffer is assigned for block *u*, return its start address, *a-addr*. Otherwise, assign a block buffer for block *u* (if the assigned block buffer has been **updated**, transfer the contents to mass storage), read the block into the block buffer and return its start address, *a-addr*.

buffer (*u* - *a-addr*) block "buffer"

If a block buffer is assigned for block *u*, return its start address, *a-addr*. Otherwise, assign a block buffer for block *u* (if the assigned block buffer has been **updated**, transfer the contents to mass storage) and return its start address, *a-addr*. The subtle difference

between **buffer** and **block** mean that you should only use **buffer** if you don't care about the previous contents of block *u*. In Gforth, this simply calls **block**.

empty-buffers (-) block-ext “empty-buffers”

Mark all block buffers as unassigned; if any had been marked as assigned-dirty (by **update**), the changes to those blocks will be lost.

empty-buffer (*buffer* -) gforth-0.2 “empty-buffer”

update (-) block “update”

Mark the state of the current block buffer as assigned-dirty.

updated? (*n* - *f*) gforth-0.2 “updated?”

Return true if **updated** has been used to mark block *n* as assigned-dirty.

save-buffers (-) block “save-buffers”

Transfer the contents of each **updated** block buffer to mass storage, then mark all block buffers as assigned-clean.

save-buffer (*buffer* -) gforth-0.2 “save-buffer”

flush (-) block “flush”

Perform the functions of **save-buffers** then **empty-buffers**.

load (*i***x* *u* - *j***x*) block “load”

Text-interpret block *u*. Block 0 cannot be loaded.

thru (*i***x* *n1* *n2* - *j***x*) block-ext “thru”

load the blocks *n1* through *n2* in sequence.

+load (*i***x* *n* - *j***x*) gforth-0.2 “+load”

Used within a block to load the block specified as the current block + *n*.

+thru (*i***x* *n1* *n2* - *j***x*) gforth-0.2 “+thru”

Used within a block to load the range of blocks specified as the current block + *n1* thru the current block + *n2*.

--> (-) gforth-0.2 “chain”

If this symbol is encountered whilst loading block *n*, discard the remainder of the block and load block *n+1*. Used for chaining multiple blocks together as a single loadable unit. Not recommended, because it destroys the independence of loading. Use **thru** (which is standard) or **+thru** instead.

block-included (*a-addr* *u* -) gforth-0.2 “block-included”

Use within a block that is to be processed by **load**. Save the current blocks file specification, open the blocks file specified by *a-addr* *u* and **load** block 1 from that file (which may in turn chain or load other blocks). Finally, close the blocks file and restore the original blocks file.

6.20 Other I/O

6.20.1 Simple numeric output

The simplest output functions are those that display numbers from the data stack. Numbers are displayed in the base (aka radix) stored in `base` (see Section 6.14.2 [Number Conversion], page 128).

`. (n -)` core “dot”

Display (the signed single number) *n* in free-format, followed by a space.

`dec. (n -)` gforth-0.2 “dec.”

Display *n* as a signed decimal number, followed by a space.

`hex. (u -)` gforth-0.2 “hex.”

Display *u* as an unsigned hex number, prefixed with a “\$” and followed by a space.

`u. (u -)` core “u-dot”

Display (the unsigned single number) *u* in free-format, followed by a space.

`.r (n1 n2 -)` core-ext “dot-r”

Display *n1* right-aligned in a field *n2* characters wide. If more than *n2* characters are needed to display the number, all digits are displayed. If appropriate, *n2* must include a character for a leading “-”.

`u.r (u n -)` core-ext “u-dot-r”

Display *u* right-aligned in a field *n* characters wide. If more than *n* characters are needed to display the number, all digits are displayed.

`d. (d -)` double “d-dot”

Display (the signed double number) *d* in free-format. followed by a space.

`ud. (ud -)` gforth-0.2 “u-d-dot”

Display (the signed double number) *ud* in free-format, followed by a space.

`d.r (d n -)` double “d-dot-r”

Display *d* right-aligned in a field *n* characters wide. If more than *n* characters are needed to display the number, all digits are displayed. If appropriate, *n* must include a character for a leading “-”.

`ud.r (ud n -)` gforth-0.2 “u-d-dot-r”

Display *ud* right-aligned in a field *n* characters wide. If more than *n* characters are needed to display the number, all digits are displayed.

6.20.2 Formatted numeric output

Forth traditionally uses a technique called *pictured numeric output* for formatted printing of integers. In this technique, digits are extracted from the number (using the current output radix defined by `base`, see Section 6.14.2 [Number Conversion], page 128), converted to ASCII codes and prepended to a string that is built in a scratch-pad area of memory (see Section 9.1.1 [Implementation-defined options], page 241). Arbitrary characters can be prepended to the string during the extraction process. The completed string is specified by an address and length and can be manipulated (TYPEd, copied, modified) under program control.

All of the integer output words described in the previous section (see Section 6.20.1 [Simple numeric output], page 148) are implemented in Gforth using pictured numeric output.

Three important things to remember about pictured numeric output:

- It always operates on double-precision numbers; to display a single-precision number, convert it first (for ways of doing this see Section 6.5.2 [Double precision], page 57).
- It always treats the double-precision number as though it were unsigned. The examples below show ways of printing signed numbers.
- The string is built up from right to left; least significant digit first.

Standard Forth supports a single output buffer (aka hold area) that you empty and initialize with `<#` and for which you get the result string with `#>`.

Gforth additionally supports nested usage of this buffer, allowing, e.g., to nest output from the debugging tracer `~~` inside code dealing with the hold area: `<<#` starts a new nest, `#>` produces the result string, and `#>>` unnests: the hold area for the nest is reclaimed, and `#>` now produces the string for the next-outer nest. All of Gforth's higher-level numeric output words use `<<# ... #> ... #>>` and can be nested inside other users of the hold area.

`<# (-)` core “less-number-sign”

Initialise/clear the pictured numeric output string.

`<<# (-)` gforth-0.5 “less-less-number-sign”

Start a hold area that ends with `#>>`. Can be nested in each other and in `<#`. Note: if you do not match up the `<<#`s with `#>>`s, you will eventually run out of hold area; you can reset the hold area to empty with `<#`.

`# (ud1 - ud2)` core “number-sign”

Used between `<<#` and `#>`. Prepend the least-significant digit (according to `base`) of `ud1` to the pictured numeric output string. `ud2` is `ud1/base`, i.e., the number representing the remaining digits.

`#s (ud - 0 0)` core “number-sign-s”

Used between `<<#` and `#>`. Prepend all digits of `ud` to the pictured numeric output string. `#s` will convert at least one digit. Therefore, if `ud` is 0, `#s` will prepend a “0” to the pictured numeric output string.

`hold (char -)` core “hold”

Used between `<<#` and `#>`. Prepend the character `char` to the pictured numeric output string.

`holds (addr u -)` core-ext “holds”

Used between `<<#` and `#>`. Prepend the string `addr u` to the pictured numeric output string.

`sign (n -)` core “sign”

Used between `<<#` and `#>`. If `n` (a *single* number) is negative, prepend “-” to the pictured numeric output string.

`#> (xd - addr u)` core “number-sign-greater”

Complete the pictured numeric output string by discarding `xd` and returning `addr u`; the address and length of the formatted string. A Standard program may modify characters

within the string. Does not release the hold area; use `#>>` to release a hold area started with `<<#`, or `<#` to release all hold areas.

`#>>` (-) gforth-0.5 “number-sign-greater-greater”

Release the hold area started with `<<#`.

Here are some examples of using pictured numeric output:

```
: my-u. ( u -- )
  \ Simplest use of pns.. behaves like Standard u.
  0          \ convert to unsigned double
  <<#        \ start conversion
  #s         \ convert all digits
  #>         \ complete conversion
  TYPE SPACE \ display, with trailing space
  #>> ;     \ release hold area

: cents-only ( u -- )
  0          \ convert to unsigned double
  <<#        \ start conversion
  # #        \ convert two least-significant digits
  #>         \ complete conversion, discard other digits
  TYPE SPACE \ display, with trailing space
  #>> ;     \ release hold area

: dollars-and-cents ( u -- )
  0          \ convert to unsigned double
  <<#        \ start conversion
  # #        \ convert two least-significant digits
  '.' hold   \ insert decimal point
  #s         \ convert remaining digits
  '$' hold   \ append currency symbol
  #>         \ complete conversion
  TYPE SPACE \ display, with trailing space
  #>> ;     \ release hold area

: my-. ( n -- )
  \ handling negatives.. behaves like Standard .
  s>d        \ convert to signed double
  swap over dabs \ leave sign byte followed by unsigned double
  <<#        \ start conversion
  #s         \ convert all digits
  rot sign    \ get at sign byte, append "-" if needed
  #>         \ complete conversion
  TYPE SPACE \ display, with trailing space
  #>> ;     \ release hold area

: account. ( n -- )
  \ accountants don't like minus signs, they use parentheses
```

```

\ for negative numbers
s>d          \ convert to signed double
swap over dabs \ leave sign byte followed by unsigned double
<<#         \ start conversion
2 pick      \ get copy of sign byte
0< IF ' )' hold THEN \ right-most character of output
#s          \ convert all digits
rot         \ get at sign byte
0< IF '( ' hold THEN
#>         \ complete conversion
TYPE SPACE \ display, with trailing space
#>> ;     \ release hold area

```

Here are some examples of using these words:

```

1 my-u. 1
hex -1 my-u. decimal FFFFFFFF
1 cents-only 01
1234 cents-only 34
2 dollars-and-cents $0.02
1234 dollars-and-cents $12.34
123 my-. 123
-123 my. -123
123 account. 123
-456 account. (456)

```

6.20.3 Floating-point output

Floating-point output is always displayed using base 10.

f. (*r* –) floating-ext “f-dot”

Display (the floating-point number) *r* without exponent, followed by a space.

fe. (*r* –) floating-ext “f-e-dot”

Display *r* using engineering notation (with exponent dividable by 3), followed by a space.

fs. (*r* –) floating-ext “f-s-dot”

Display *r* using scientific notation (with exponent), followed by a space.

fp. (*r* –) floating-ext “f-e-dot”

Display *r* using SI prefix notation (with exponent dividable by 3, converted into SI prefixes if available), followed by a space. translate floating point numbers

Examples of printing the number 1234.5678E23 in the different floating-point output formats are shown below.

```

f. 12345678000000000000000000000000.
fe. 123.45678000000000E24
fs. 1.2345678000000000E26
fp. 123.4567800000000Y

```

The length of the output is influenced by:

precision (– *u*) floating-ext “precision”

u is the number of significant digits currently used by F. FE. and FS.

set-precision (u -) floating-ext “set-precision”

Set the number of significant digits currently used by F. FE. and FS. to u . scratchpad for floating point - use space at the end of the user area

You can control the output in more detail with:

f.rdp ($rf + nr + nd + np$ -) gforth-0.6 “f.rdp”

Print float rf formatted. The total width of the output is nr . For fixed-point notation, the number of digits after the decimal point is $+nd$ and the minimum number of significant digits is np . **Set-precision** has no effect on **f.rdp**. Fixed-point notation is used if the number of significant digits would be at least np and if the number of digits before the decimal point would fit. If fixed-point notation is not used, exponential notation is used, and if that does not fit, asterisks are printed. We recommend using $nr \geq 7$ to avoid the risk of numbers not fitting at all. We recommend $nr \geq np + 5$ to avoid cases where **f.rdp** switches to exponential notation because fixed-point notation would have too few significant digits, yet exponential notation offers fewer significant digits. We recommend $nr \geq nd + 2$, if you want to have fixed-point notation for some numbers; the smaller the value of np , the more cases are shown in fixed-point notation (cases where few or no significant digits remain in fixed-point notation). We recommend $np > nr$, if you want to have exponential notation for all numbers. the field width for f.s output. Other precision details are derived from that value.

To give you a better intuition of how they influence the output, here are some examples of parameter combinations; in each line the same number is printed, in each column the same parameter combination is used for printing:

12 13 0	7 3 4	7 3 0	7 3 1	7 5 1	7 7 1	7 0 2	4 2 1
-1.234568E-6	-1.2E-6	-0.000	-1.2E-6	-1.2E-6	-1.2E-6	-1.2E-6	****
-1.234568E-5	-1.2E-5	-0.000	-1.2E-5	-.00001	-1.2E-5	-1.2E-5	****
-1.234568E-4	-1.2E-4	-0.000	-1.2E-4	-.00012	-1.2E-4	-1.2E-4	****
-1.234568E-3	-1.2E-3	-0.001	-0.001	-.00123	-1.2E-3	-1.2E-3	****
-1.234568E-2	-1.2E-2	-0.012	-0.012	-.01235	-1.2E-2	-1.2E-2	-.01
-1.234568E-1	-1.2E-1	-0.123	-0.123	-.12346	-1.2E-1	-1.2E-1	-.12
-1.2345679E0	-1.235	-1.235	-1.235	-1.23E0	-1.23E0	-1.23E0	-1E0
-1.2345679E1	-12.346	-12.346	-12.346	-1.23E1	-1.23E1	-12.	-1E1
-1.2345679E2	-1.23E2	-1.23E2	-1.23E2	-1.23E2	-1.23E2	-123.	-1E2
-1.2345679E3	-1.23E3	-1.23E3	-1.23E3	-1.23E3	-1.23E3	-1235.	-1E3
-1.2345679E4	-1.23E4	-1.23E4	-1.23E4	-1.23E4	-1.23E4	-12346.	-1E4
-1.2345679E5	-1.23E5	-1.23E5	-1.23E5	-1.23E5	-1.23E5	-1.23E5	-1E5

You can generate a string instead of displaying the number with:

f>str-rdp ($rf + nr + nd + np$ - c -addr nr) gforth-0.6 “f>str-rdp”

Convert rf into a string at c -addr nr . The conversion rules and the meanings of $nr + nd + np$ are the same as for **f.rdp**. The result is in the pictured numeric output buffer and will be destroyed by anything destroying that buffer.

f>buf-rdp (rf c -addr $+nr + nd + np$ -) gforth-0.6 “f>buf-rdp”

Convert rf into a string at c -addr nr . The conversion rules and the meanings of $nr + nd + np$ are the same as for **f.rdp**.

There is also a primitive used for implementing higher-level FP-to-string words:

represent (*r c-addr u - n f1 f2*) floating “represent”

Convert the decimal significand (aka mantissa) of *r* into a string in buffer *c-addr u*; *n* is the exponent, *f1* is true if *r* is negative, and *f2* is true if *r* is valid (a finite number in Gforth).

6.20.4 Miscellaneous output

cr (-) core “c-r”

Output a newline (of the favourite kind of the host OS). Note that due to the way the Forth command line interpreter inserts newlines, the preferred way to use **cr** is at the start of a piece of text; e.g., **cr . " hello, world"**.

space (-) core “space”

Display one space.

spaces (*u* -) core “spaces”

Display *u* spaces.

out (- *addr*) gforth-1.0 “out”

Addr contains a number that tries to give the position of the cursor within the current line on the user output device: It resets to 0 on **cr**, increases by the number of characters by **type** and **emit**, and decreases on **backspaces**. Unfortunately, it does not take into account tabs, multi-byte characters, or the existence of Unicode characters with width 0 and 2, so it only works for simple cases.

. (*compilation 'ccc' - ; run-time* -) gforth-0.6 “dot-backslash-quote”

Like **.**, but translates C-like \-escape-sequences (see **S**).

." (*compilation 'ccc' - ; run-time* -) core “dot-quote”

Compilation: Parse a string *ccc* delimited by a " (double quote). At run-time, display the string. Interpretation semantics for this word are undefined in standard Forth. Gforth’s interpretation semantics are to display the string.

.((*compilation&interpretation "ccc<paren>" -*) core-ext “dot-paren”

Compilation and interpretation semantics: Parse a string *ccc* delimited by a) (right parenthesis). Display the string. This is often used to display progress information during compilation; see examples below.

If you don’t want to worry about whether to use **.(hello)** or **." hello"**, you can write **"hello" type**, which gives you what you usually want (but is less portable to other Forth systems).

As an example, consider the following text, stored in a file **test.fs**:

```
.( text-1)
: my-word
  ." text-2" cr
  .( text-3)
  "text-4" type
;

." text-5"
```

"text-6" type

When you load this code into Gforth, the following output is generated:

```
include test.fs RET text-1text-3text-5text-6 ok
```

- Messages **text-1** and **text-3** are displayed because **.(** is an immediate word; it behaves in the same way whether it is used inside or outside a colon definition.
- Message **text-5** is displayed because of Gforth's added interpretation semantics for **."**.
- Message **text-6** is displayed because **"text-6" type** is interpreted.
- Message **text-2** is *not* displayed, because the text interpreter performs the compilation semantics for **."** within the definition of **my-word**.
- Message **text-4** is *not* displayed, because **"text-4" type** is compiled into **my-word**.

6.20.5 Displaying characters and strings

type (*c-addr u* -) core "type"

If *u*>0, display *u* characters from a string starting with the character stored at *c-addr*.

xemit (*xc* -) xchar "x-emit"

Prints an xchar on the terminal.

emit (*c* -) core "emit"

Send the byte *c* to the current output; for ASCII characters, **emit** is equivalent to **xemit**.

typewhite (*addr n* -) gforth-0.2 "typewhite"

Like **type**, but white space is printed instead of the characters.

6.20.6 Terminal output

If you are outputting to a terminal, you may want to control the positioning of the cursor:

at-xy (*x y* -) facility "at-x-y"

Put the cursor at position *x y*

at-deltaxy (*dx dy* -) gforth-0.7 "at-deltaxy"

With the current position at *x y*, put the cursor at *x+dx y+dy*.

In order to know where to position the cursor, it is often helpful to know the size of the screen:

form (- *nlines ncols*) gforth-0.2 "form"

And sometimes you want to use:

page (-) facility "page"

Clear the screen

Note that on non-terminals you should use **12 emit**, not **page**, to get a form feed.

6.20.6.1 Color output

The following words are used to create (semantic) colorful output; further output is produced in the color and style given by the word; the actual color and style depends on the theme (see below).

default-color (-) gforth-1.0 "default-color"

```

    use system-default color
error-color ( - ) gforth-1.0 "error-color"
    error color: red
error-hl-inv ( - ) gforth-1.0 "error-hl-inv"
    color mod for error highlight inverse
error-hl-ul ( - ) gforth-1.0 "error-hl-ul"
    color mod for error highlight underline
warning-color ( - ) gforth-1.0 "warning-color"
    color for warnings: blue/yellow on black terminals
info-color ( - ) gforth-1.0 "info-color"
    color for info: green/cyan on black terminals
success-color ( - ) gforth-1.0 "success-color"
    color for success: green
input-color ( - ) gforth-1.0 "input-color"
    color for user-input: black/white (both bold)
status-color ( - ) gforth-1.0 "status-color"
    color mod for error highlight inverse

```

6.20.6.2 Color themes

Depending on whether you prefer bright or dark background the foreground colors-theme can be changed by:

```

light-mode ( - ) gforth-1.0 "light-mode"
    color theme for white background
dark-mode ( - ) gforth-1.0 "dark-mode"
    color theme for black background

```

6.20.7 Single-key input

If you want to get a single printable character, you can use **key**; to check whether a character is available for **key**, you can use **key?**.

```
key ( - char ) core "key"
```

Receive (but do not display) one character, *char*.

```
key-ior ( - char|ior ) gforth-1.0 "key-ior"
```

Receive (but do not display) one character, *char*, in case of an error or interrupt, return the negative *ior* instead.

```
key? ( - flag ) facility "key-question"
```

Determine whether a character is available. If a character is available, *flag* is true; the next call to **key** will yield the character. Once **key?** returns true, subsequent calls to **key?** before calling **key** or **ekey** will also return true.

If you want to process a mix of printable and non-printable characters, you can do that with **ekey** and friends. **Ekey** produces a keyboard event that you have to convert into a character with **ekey>char** or into a key identifier with **ekey>fkey**.

Typical code for using EKEY looks like this:

```
ekey ekey>char if ( c )
  ... \ do something with the character
else ekey>fkey if ( key-id )
  case
    k-up                                of ... endof
    k-f1                                of ... endof
    k-left k-shift-mask or k-ctrl-mask or of ... endof
    ...
  endcase
else ( keyboard-event )
  drop \ just ignore an unknown keyboard event type
then then
```

ekey (*- u*) facility-ext “e-key”

Receive a keyboard event *u* (encoding implementation-defined).

ekey>char (*u - u false | c true*) facility-ext “e-key-to-char”

Convert keyboard event *u* into character *c* if possible.

ekey>fkey (*u1 - u2 f*) facility-ext “e-key-to-f-key”

If *u1* is a keyboard event in the special key set, convert keyboard event *u1* into key id *u2* and return true; otherwise return *u1* and false.

ekey? (*- flag*) facility-ext “e-key-question”

True if a keyboard event is available.

The key identifiers for cursor keys are:

k-left (*- u*) facility-ext “k-left”

k-right (*- u*) facility-ext “k-right”

k-up (*- u*) facility-ext “k-up”

k-down (*- u*) facility-ext “k-down”

k-home (*- u*) facility-ext “k-home”

aka Pos1

k-end (*- u*) facility-ext “k-end”

k-prior (*- u*) facility-ext “k-prior”

aka PgUp

k-next (*- u*) facility-ext “k-next”

aka PgDn

k-insert (*- u*) facility-ext “k-insert”

k-delete (*- u*) facility-ext “k-delete”

The key identifiers for function keys (aka keypad keys) are:

k-f1 (*- u*) facility-ext “k-f-1”

k-f2 (*- u*) facility-ext “k-f-2”

k-f3 (*- u*) facility-ext “k-f-3”

k-f4 (*- u*) facility-ext “k-f-4”

```

k-f5 ( - u ) facility-ext “k-f-5”
k-f6 ( - u ) facility-ext “k-f-6”
k-f7 ( - u ) facility-ext “k-f-7”
k-f8 ( - u ) facility-ext “k-f-8”
k-f9 ( - u ) facility-ext “k-f-9”
k-f10 ( - u ) facility-ext “k-f-10”
k-f11 ( - u ) facility-ext “k-f-11”
k-f12 ( - u ) facility-ext “k-f-12”

```

Note that **k-f11** and **k-f12** are not as widely available.

You can combine these key identifiers with masks for various shift keys:

```

k-shift-mask ( - u ) facility-ext “k-shift-mask”
k-ctrl-mask ( - u ) facility-ext “k-ctrl-mask”
k-alt-mask ( - u ) facility-ext “k-alt-mask”

```

Note that, even if a Forth system has **ekey>fkey** and the key identifier words, the keys are not necessarily available or it may not necessarily be able to report all the keys and all the possible combinations with shift masks. Therefore, write your programs in such a way that they are still useful even if the keys and key combinations cannot be pressed or are not recognized.

Examples: Older keyboards often do not have an F11 and F12 key. If you run Gforth in an xterm, the xterm catches a number of combinations (e.g., **Shift-Up**), and never passes it to Gforth. Finally, Gforth currently does not recognize and report combinations with multiple shift keys (so the **shift-ctrl-left** case in the example above would never be entered).

Gforth recognizes various keys available on ANSI terminals (in MS-DOS you need the ANSISYS driver to get that behaviour); it works by recognizing the escape sequences that ANSI terminals send when such a key is pressed. If you have a terminal that sends other escape sequences, you will not get useful results on Gforth. Other Forth systems may work in a different way.

Gforth also provides a few words for outputting names of function keys:

```

fkey. ( u - ) gforth-1.0 “fkey-dot”

```

Print a string representation for the function key *u*. *U* must be a function key (possibly with modifier masks), otherwise there may be an exception.

```

simple-fkey-string ( u1 - c-addr u ) gforth-1.0 “simple-fkey-string”

```

c-addr u is the string name of the function key *u1*. Only works for simple function keys without modifier masks. Any *u1* that does not correspond to a simple function key currently produces an exception.

6.20.8 Line input and conversion

For ways of storing character strings in memory see Section 6.8.2 [String representations], page 78.

Words for inputting one line from the keyboard:

```

accept ( c-addr +n1 - +n2 ) core “accept”

```


Get a string of up to *n1* characters from the user input device and store it at *c-addr*. *n2* is the length of the received string. The user indicates the end by pressing RET. Gforth supports all the editing functions available on the Forth command line (including history and word completion) in **accept**.

edit-line (*c-addr n1 n2 - n3*) gforth-0.6 “edit-line”

edit the string with length *n2* in the buffer *c-addr n1*, like **accept**.

Conversion words:

s>number? (*addr u - d f*) gforth-0.5 “s>number?”

converts string *addr u* into *d*, *flag* indicates success

s>unnumber? (*c-addr u - ud flag*) gforth-0.5 “s>unnumber?”

converts string *c-addr u* into *ud*, *flag* indicates success

>number (*ud1 c-addr1 u1 - ud2 c-addr2 u2*) core “to-number”

Attempt to convert the character string *c-addr1 u1* to an unsigned number in the current number base. The double *ud1* accumulates the result of the conversion to form *ud2*. Conversion continues, left-to-right, until the whole string is converted or a character that is not convertible in the current number base is encountered (including + or -). For each convertible character, *ud1* is first multiplied by the value in **BASE** and then incremented by the value represented by the character. *c-addr2* is the location of the first unconverted character (past the end of the string if the whole string was converted). *u2* is the number of unconverted characters in the string. Overflow is not detected.

>float (*c-addr u - f:... flag*) floating “to-float”

Actual stack effect: (*c-addr u - r t | f*). Attempt to convert the character string *c-addr u* to internal floating-point representation. If the string represents a valid floating-point number, *r* is placed on the floating-point stack and *flag* is true. Otherwise, *flag* is false. A string of blanks is a special case and represents the floating-point number 0.

>float1 (*c-addr u c - f:... flag*) gforth-1.0 “to-float1”

Actual stack effect: (*c-addr u c - r t | f*). Attempt to convert the character string *c-addr u* to internal floating-point representation, with *c* being the decimal separator. If the string represents a valid floating-point number, *r* is placed on the floating-point stack and *flag* is true. Otherwise, *flag* is false. A string of blanks is a special case and represents the floating-point number 0.

Obsolescent input and conversion words:

convert (*ud1 c-addr1 - ud2 c-addr2*) core-ext-obsolescent “convert”

Obsolescent: superseded by **>number**.

expect (*c-addr +n -*) core-ext-obsolescent “expect”

Receive a string of at most *+n* characters, and store it in memory starting at *c-addr*. The string is displayed. Input terminates when the <return> key is pressed or *+n* characters have been received. The normal Gforth line editing capabilities are available. The length of the string is stored in **span**; it does not include the <return> character. OBSOLESCENT: superseded by **accept**.

span (*- c-addr*) core-ext-obsolescent “span”

Variable – *c-addr* is the address of a cell that stores the length of the last string received by **expect**. OBSOLESCENT.

6.20.9 Pipes

In addition to using Gforth in pipes created by other processes (see Section 2.7 [Gforth in pipes], page 8), you can create your own pipe with **open-pipe**, and read from or write to it.

open-pipe (*c-addr u wfam – wfileid wior*) gforth-0.2 “open-pipe”

close-pipe (*wfileid – wretval wior*) gforth-0.2 “close-pipe”

If you write to a pipe, Gforth can throw a **broken-pipe-error**; if you don’t catch this exception, Gforth will catch it and exit, usually silently (see Section 2.7 [Gforth in pipes], page 8). Since you probably do not want this, you should wrap a **catch** or **try** block around the code from **open-pipe** to **close-pipe**, so you can deal with the problem yourself, and then return to regular processing.

broken-pipe-error (*– n*) gforth-0.6 “broken-pipe-error”

the error number for a broken pipe

6.20.10 Xchars and Unicode

ASCII is only appropriate for the English language. Most western languages however fit somewhat into the Forth frame, since a byte is sufficient to encode the few special characters in each (though not always the same encoding can be used; latin-1 is most widely used, though). For other languages, different char-sets have to be used, several of them variable-width. To deal with this problem, characters are often represented as Unicode codepoints on the stack, and as UTF-8 byte strings in memory. An Unicode codepoint often represents one application-level character, but Unicode also supports decomposed characters that consist of several code points, e.g., a base letter and a combining diacritical mark.

An Unicode codepoint can consume more than one byte in memory, so we adjust our terminology: A char is a raw byte in memory or a value in the range 0-255 on the stack. An xchar (for extended char) stands for one codepoint; it is represented by one or more bytes in memory and may have larger values on the stack. ASCII characters are the same as chars and as xchars: values in the range 0-127, and a single byte with that value in memory.

When using UTF-8 encoding, all other codepoints take more than one byte/char. In most cases, you can just treat such characters as strings in memory and don’t need to use the following words, but if you want to deal with individual codepoints, the following words are useful. We currently have no words for dealing with decomposed characters.

The xchar words add a few data types:

- **xc** is an extended char (xchar) on the stack. It occupies one cell, and is a subset of unsigned cell. On 16 bit systems, only the BMP subset of the Unicode character set (i.e., codepoints <65536) can be represented on the stack. If you represent your application characters as strings at all times, you can avoid this limitation.
- **xc-addr** is the address of an xchar in memory. Alignment requirements are the same as **c-addr**. The memory representation of an xchar differs from the stack representation, and depends on the encoding used. An xchar may use a variable number of chars in memory.
- **xc-addr u** is a buffer of xchars in memory, starting at **xc-addr**, **u** chars (i.e., bytes, not xchars) long.

xc-size (*xc – u*) xchar “x-c-size”

Computes the memory size of the xchar *xc* in chars.

x-size (*xc-addr u1 - u2*) xchar “x-size”

Computes the memory size of the first xchar stored at *xc-addr* in chars.

xc@+ (*xc-addr1 - xc-addr2 xc*) xchar “x-c-fetch-plus”

Fetches the xchar *xc* at *xc-addr1*. *xc-addr2* points to the first memory location after *xc*.

xc!+? (*xc xc-addr1 u1 - xc-addr2 u2 f*) xchar “x-c-store-plus-query”

Stores the xchar *xc* into the buffer starting at address *xc-addr1*, *u1* chars large. *xc-addr2* points to the first memory location after *xc*, *u2* is the remaining size of the buffer. If the xchar *xc* did fit into the buffer, *f* is true, otherwise *f* is false, and *xc-addr2 u2* equal *xc-addr1 u1*. **XC!+?** is safe for buffer overflows, and therefore preferred over **XC!+**.

xchar+ (*xc-addr1 - xc-addr2*) xchar “x-char-plus”

Adds the size of the xchar stored at *xc-addr1* to this address, giving *xc-addr2*.

xchar- (*xc-addr1 - xc-addr2*) xchar-ext “x-char-minus”

Goes backward from *xc-addr1* until it finds an xchar so that the size of this xchar added to *xc-addr2* gives *xc-addr1*.

+x/string (*xc-addr1 u1 - xc-addr2 u2*) xchar-ext “plus-x-slash-string”

Step forward by one xchar in the buffer defined by address *xc-addr1*, size *u1* chars. *xc-addr2* is the address and *u2* the size in chars of the remaining buffer after stepping over the first xchar in the buffer.

x\string- (*xc-addr u1 - xc-addr u2*) xchar-ext “x-backslash-string-minus”

Step backward by one xchar in the buffer defined by address *xc-addr* and size *u1* in chars, starting at the end of the buffer. *xc-addr* is the address and *u2* the size in chars of the remaining buffer after stepping backward over the last xchar in the buffer.

-trailing-garbage (*xc-addr u1 - xc-addr u2*) xchar-ext “minus-trailing-garbage”

Examine the last XCHAR in the buffer *xc-addr u1*—if the encoding is correct and it represents a full char, *u2* equals *u1*, otherwise, *u2* represents the string without the last (garbled) xchar.

x-width (*xc-addr u - n*) xchar-ext “x-width”

n is the number of monospace ASCII chars that take the same space to display as the the xchar string starting at *xc-addr*, using *u* chars; assuming a monospaced display font, i.e. char width is always an integer multiple of the width of an ASCII char.

xkey (- *xc*) xchar “x-key”

Reads an xchar from the terminal. This will discard all input events up to the completion of the xchar.

xc-width (*xc - n*) xchar-ext “x-c-width”

xc has a width of *n* times the width of a normal fixed-width glyph.

There’s a new environment query

xchar-encoding (- *addr u*) xchar-ext “xchar-encoding”

Returns a printable ASCII string that represents the encoding, and use the preferred MIME name (if any) or the name in <http://www.iana.org/assignments/character-sets> like “ISO-LATIN-1” or “UTF-8”, with the exception of “ASCII”, where we prefer the alias

“ASCII”. uses the file as is (default) uses a short file format (default) uses a fully expanded file format (to pass to e.g. editors) prepends the file to a list of locations in that file (like SwiftForth) Set the line number to *u* and (if present) the file name to *file*. Consumes the rest of the line.

6.20.11 Internationalization and Localization

Programs for end users require to address those in their native language. There is a decades old proposal for such a facility that has been split from other proposals for international character sets like Xchars (see Section 6.20.10 [Xchars and Unicode], page 159) and Substitute (see Section 6.20.12 [Substitute], page 162). Messages displayed on the screen need to be translated from the native language of the developers to the local languages of the user.

Strings subject to translation are declared with `L" string"`. This returns a locale string identifier (LSID). LSIDs are opaque types, taking a cell on the stack. LSIDs can be translated into a locale; locales are languages and country-specific variants of that language.

`L" ("lsid<">" - lsid)` gforth-experimental “l-quote”

Parse a string and define a new *lsid*, if the string is uniquely new. Identical strings result in identical *lsids*, which allows to refer to the same *lsid* from multiple locations using the same string.

`LU" ("lsid<">" - lsid)` gforth-experimental “l-unique-quote”

Parse a string and always define a new *lsid*, even if the string is not unique.

`native@ (lsid - addr u)` gforth-experimental “native-fetch”

fetch native string from an *lsid*

`locale@ (lsid - addr u)` gforth-experimental “locale-fetch”

fetch the localized string in the current language and country

`locale! (addr u lsid -)` gforth-experimental “locale-store”

Store localized string *addr u* for the current locale and country in *lsid*.

`Language ("name" -)` gforth-experimental “Language”

define a locale. Executing that locale makes it the current locale.

`Country (<lang> "name" -)` gforth-experimental “Country”

define a variant (typical: country) for the current locale. Executing that locale makes it the current locale. You can create variants of variants (a country may have variants within, e.g. think of how many words for rolls/buns there are in many languages).

`locale-file (fid -)` gforth-experimental “locale-file”

read lines from *fid* into the current locale.

`included-locale (addr u -)` gforth-experimental “included-locale”

read lines from the file *addr u* into the current locale.

`include-locale ("name" -)` gforth-experimental “include-locale”

read lines from the file "*name*" into the current locale.

`locale-csv ("name" -)` gforth-experimental “locale-csv”

import comma-separated value table into locales. first line contains locale names, “program” and “default” are special entries; generic languages must precede translations for

specific countries. Entries under “program” (must be leftmost) are used to search for the `lsid`; if empty, the line number-1 is the `lsid` index.

.locale-csv (*-*) gforth-experimental “dot-locale-csv”

write the locale database in CSV format to the terminal output.

locale-csv-out (*"name"* *-*) gforth-experimental “locale-csv”

Create file *"name"* and write the locale database out to the file *"name"* in CSV format.

6.20.12 Substitute

This is a simple text macro replacement facility. Texts in the form *"text %macro% text"* are processed, and the macro variables enclosed in *'%'* are replaced with their associated strings. Two consecutive *%* are replaced by one *%*. Macros are defined in a specific wordlist, and return a string upon execution; the standard defines only one way to declare macros, **replaces**, which creates a macro that just returns a string.

macros-wordlist (*- wid*) gforth-experimental “macros-wordlist”

wordlist for string replacement macros

replaces (*addr1 len1 addr2 len2* *-*) string-ext “replaces”

create a macro with name *addr2 len2* and content *addr1 len1*. If the macro already exists, just change the content.

.substitute (*addr1 len1* *- n / ior*) gforth-experimental “dot-substitute”

substitute all macros in text *addr1 len1* and print the result. *n* is the number of substitutions or, if negative, a throwable *ior*.

\$substitute (*addr1 len1* *- addr2 len2 n/ior*) gforth-experimental “string-substitute”

substitute all macros in text *addr1 len1*. *n* is the number of substitutions, if negative, it’s a throwable *ior*, *addr2 len2* the result.

substitute (*addr1 len1 addr2 len2* *- addr2 len3 n/ior*) string-ext “substitute”

substitute all macros in text *addr1 len1*, and copy the result to *addr2 len2*. *n* is the number of substitutions or, if negative, a throwable *ior*, *addr2 len3* the result.

unescape (*addr1 u1 dest* *- dest u2*) string-ext “unescape”

double all delimiters in *addr1 u1*, so that substitute will result in the original text. Note that the buffer *dest* does not have a size, as in worst case, it will need just twice as many characters as *u1*. *dest u2* is the resulting string.

\$unescape (*addr1 u1* *- addr2 u2*) gforth-experimental “string-unescape”

same as **unescape**, but creates a temporary destination string with **\$tmp**.

6.20.13 CSV Reader

Comma-separated values (CSV) are a popular text format to interchange data. Gforth provides an reader in **csv.fs**.

read-csv (*addr u xt* *-*) gforth-experimental “read-csv”

read CVS file *addr u* and execute *xt* for every item found. *xt* takes (**addr u col line** *--*), i.e. the string, the current column (starting with 0), and the current line (starting with 1).

6.21 OS command line arguments

The usual way to pass arguments to Gforth programs on the command line is via the `-e` option, e.g.

```
gforth -e "123 456" foo.fs -e bye
```

However, you may want to interpret the command-line arguments directly. In that case, you can access the (image-specific) command-line arguments through `next-arg`:

`next-arg (- addr u)` gforth-0.7 “next-arg”

get the next argument from the OS command line, consuming it; if there is no argument left, return 0 0.

Here’s an example program `echo.fs` for `next-arg`:

```
: echo ( -- )
  begin
  next-arg 2dup 0 0 d<> while
    type space
  repeat
  2drop ;

echo cr bye
```

This can be invoked with

```
gforth echo.fs hello world
```

and it will print

```
hello world
```

The next lower level of dealing with the OS command line are the following words:

`arg (u - addr count)` gforth-0.2 “arg”

Return the string for the *uth* command-line argument; returns 0 0 if the access is beyond the last argument. 0 `arg` is the program name with which you started Gforth. The next unprocessed argument is always 1 `arg`, the one after that is 2 `arg` etc. All arguments already processed by the system are deleted. After you have processed an argument, you can delete it with `shift-args`.

`shift-args (-)` gforth-0.7 “shift-args”

1 `arg` is deleted, shifting all following OS command line parameters to the left by 1, and reducing `argc` @. This word can change `argv` @.

Finally, at the lowest level Gforth provides the following words:

`argc (- addr)` gforth-0.2 “argc”

Variable – the number of command-line arguments (including the command name). Changed by `next-arg` and `shift-args`.

`argv (- addr)` gforth-0.2 “argv”

Variable – a pointer to a vector of pointers to the command-line arguments (including the command-name). Each argument is represented as a C-style zero-terminated string. Changed by `next-arg` and `shift-args`.

6.22 Locals

Local variables can make Forth programming more enjoyable and Forth programs easier to read. Unfortunately, the locals of Standard Forth are laden with restrictions. Therefore, we provide not only the Standard Forth locals wordset, but also our own, more powerful locals wordset (we implemented the Standard Forth locals wordset through our locals wordset).

The ideas in this section have also been published in M. Anton Ertl, *Automatic Scoping of Local Variables* (<https://www.complang.tuwien.ac.at/papers/ertl94l.ps.gz>), EuroForth '94.

6.22.1 Gforth locals

Locals can be defined with

```
{ local1 local2 ... -- comment }
or
{ local1 local2 ... }
```

E.g.,

```
: max { n1 n2 -- n3 }
  n1 n2 > if
    n1
  else
    n2
  endif ;
```

The similarity of locals definitions with stack comments is intended. A locals definition often replaces the stack comment of a word. The order of the locals corresponds to the order in a stack comment and everything after the `--` is really a comment.

This similarity has one disadvantage: It is too easy to confuse locals declarations with stack comments, causing bugs and making them hard to find. However, this problem can be avoided by appropriate coding conventions: Do not use both notations in the same program. If you do, they should be distinguished using additional means, e.g. by position.

The name of the local may be preceded by a type specifier, e.g., `F:` for a floating point value:

```
: CX* { F: Ar F: Ai F: Br F: Bi -- Cr Ci }
\ complex multiplication
Ar Br f* Ai Bi f* f-
Ar Bi f* Ai Br f* f+ ;
```

Gforth currently supports cells (`W:`, `W^`), doubles (`D:`, `D^`), floats (`F:`, `F^`) and characters (`C:`, `C^`) in two flavours: a value-flavoured local (defined with `W:`, `D:` etc.) produces its value and can be changed with `T0`. A variable-flavoured local (defined with `W^` etc.) produces its address (which becomes invalid when the variable's scope is left). E.g., the standard word `emit` can be defined in terms of `type` like this:

```
: emit { C^ char* -- }
  char* 1 type ;
```

A local without type specifier is a `W:` local. Both flavours of locals are initialized with values from the data or FP stack.

Gforth supports the square bracket notation of local data structures. These locals are similar to variable-flavored locals, the size is specified as a constant expression. A declaration looks `name[size]`. The Forth expression `size` is evaluated during declaration, it must have the stack effect (-- +n), giving the size in bytes. The square bracket `[` is part of the defined name.

Local data structures are initialized by copying `size` bytes from an address passed on the stack; uninitialized local data structures (after `|` in the declaration) are not erased, they just contain whatever data there was on the locals stack before.

Example:

```
begin-structure test-struct
  field: a1
  field: a2
end-structure

: test-local { : foo[ test-struct ] : }
  foo[ a1 !  foo[ a2 !
  foo[ test-struct dump ;
```

Gforth allows defining locals everywhere in a colon definition. This poses the following questions:

6.22.1.1 Where are locals visible by name?

Basically, the answer is that locals are visible where you would expect it in block-structured languages, and sometimes a little longer. If you want to restrict the scope of a local, enclose its definition in `SCOPE...ENDSCOPE`.

`scope` (*compilation* - *scope* ; *run-time* -) gforth-0.2 “scope”

`endscope` (*compilation* *scope* - ; *run-time* -) gforth-0.2 “endscope”

These words behave like control structure words, so you can use them with `CS-PICK` and `CS-ROLL` to restrict the scope in arbitrary ways.

If you want a more exact answer to the visibility question, here’s the basic principle: A local is visible in all places that can only be reached through the definition of the local²². In other words, it is not visible in places that can be reached without going through the definition of the local. E.g., locals defined in `IF...ENDIF` are visible until the `ENDIF`, locals defined in `BEGIN...UNTIL` are visible after the `UNTIL` (until, e.g., a subsequent `ENDSCOPE`).

The reasoning behind this solution is: We want to have the locals visible as long as it is meaningful. The user can always make the visibility shorter by using explicit scoping. In a place that can only be reached through the definition of a local, the meaning of a local name is clear. In other places it is not: How is the local initialized at the control flow path that does not contain the definition? Which local is meant, if the same name is defined twice in two independent control flow paths?

This should be enough detail for nearly all users, so you can skip the rest of this section. If you really must know all the gory details and options, read on.

In order to implement this rule, the compiler has to know which places are unreachable. It knows this automatically after `AHEAD`, `AGAIN`, `EXIT` and `LEAVE`; in other cases (e.g., after

²² In compiler construction terminology, all places dominated by the definition of the local.

most **THROWS**), you can use the word **UNREACHABLE** to tell the compiler that the control flow never reaches that place. If **UNREACHABLE** is not used where it could, the only consequence is that the visibility of some locals is more limited than the rule above says. If **UNREACHABLE** is used where it should not (i.e., if you lie to the compiler), buggy code will be produced.

UNREACHABLE (-) gforth-0.2 “UNREACHABLE”

Another problem with this rule is that at **BEGIN**, the compiler does not know which locals will be visible on the incoming back-edge. All problems discussed in the following are due to this ignorance of the compiler (we discuss the problems using **BEGIN** loops as examples; the discussion also applies to **?DO** and other loops). Perhaps the most insidious example is:

```
AHEAD
BEGIN
  x
  [ 1 CS-ROLL ] THEN
  { x }
  ...
UNTIL
```

This should be legal according to the visibility rule. The use of **x** can only be reached through the definition; but that appears textually below the use.

From this example it is clear that the visibility rules cannot be fully implemented without major headaches. Our implementation treats common cases as advertised and the exceptions are treated in a safe way: The compiler makes a reasonable guess about the locals visible after a **BEGIN**; if it is too pessimistic, the user will get a spurious error about the local not being defined; if the compiler is too optimistic, it will notice this later and issue a warning. In the case above the compiler would complain about **x** being undefined at its use. You can see from the obscure examples in this section that it takes quite unusual control structures to get the compiler into trouble, and even then it will often do fine.

If the **BEGIN** is reachable from above, the most optimistic guess is that all locals visible before the **BEGIN** will also be visible after the **BEGIN**. This guess is valid for all loops that are entered only through the **BEGIN**, in particular, for normal **BEGIN...WHILE...REPEAT** and **BEGIN...UNTIL** loops and it is implemented in our compiler. When the branch to the **BEGIN** is finally generated by **AGAIN** or **UNTIL**, the compiler checks the guess and warns the user if it was too optimistic:

```
IF
  { x }
BEGIN
  \ x ?
  [ 1 cs-roll ] THEN
  ...
UNTIL
```

Here, **x** lives only until the **BEGIN**, but the compiler optimistically assumes that it lives until the **THEN**. It notices this difference when it compiles the **UNTIL** and issues a warning. The user can avoid the warning, and make sure that **x** is not used in the wrong area by using explicit scoping:

```
IF
  SCOPE
```

```

    { x }
  ENDScope
BEGIN
[ 1 cs-roll ] THEN
...
UNTIL

```

Since the guess is optimistic, there will be no spurious error messages about undefined locals.

If the **BEGIN** is not reachable from above (e.g., after **AHEAD** or **EXIT**), the compiler cannot even make an optimistic guess, as the locals visible after the **BEGIN** may be defined later. Therefore, the compiler assumes that no locals are visible after the **BEGIN**. However, the user can use **ASSUME-LIVE** to make the compiler assume that the same locals are visible at the **BEGIN** as at the point where the top control-flow stack item was created.

ASSUME-LIVE (*orig* – *orig*) gforth-0.2 “ASSUME-LIVE”

E.g.,

```

    { x }
  AHEAD
  ASSUME-LIVE
  BEGIN
    x
  [ 1 CS-ROLL ] THEN
    ...
  UNTIL

```

Other cases where the locals are defined before the **BEGIN** can be handled by inserting an appropriate **CS-ROLL** before the **ASSUME-LIVE** (and changing the control-flow stack manipulation behind the **ASSUME-LIVE**).

Cases where locals are defined after the **BEGIN** (but should be visible immediately after the **BEGIN**) can only be handled by rearranging the loop. E.g., the “most insidious” example above can be arranged into:

```

  BEGIN
    { x }
    ... 0=
  WHILE
    x
  REPEAT

```

6.22.1.2 How long do locals live?

The right answer for the lifetime question would be: A local lives at least as long as it can be accessed. For a value-flavoured local this means: until the end of its visibility. However, a variable-flavoured local could be accessed through its address far beyond its visibility scope. Ultimately, this would mean that such locals would have to be garbage collected. Since this entails un-Forth-like implementation complexities, I adopted the same cowardly solution as some other languages (e.g., C): The local lives only as long as it is visible; afterwards its address is invalid (and programs that access it afterwards are erroneous).

6.22.1.3 Locals programming style

The freedom to define locals anywhere has the potential to change programming styles dramatically. In particular, the need to use the return stack for intermediate storage vanishes. Moreover, all stack manipulations (except PICKs and ROLLs with run-time determined arguments) can be eliminated: If the stack items are in the wrong order, just write a locals definition for all of them; then write the items in the order you want.

This seems a little far-fetched and eliminating stack manipulations is unlikely to become a conscious programming objective. Still, the number of stack manipulations will be reduced dramatically if local variables are used liberally (e.g., compare `max` (see Section 6.22.1 [Gforth locals], page 164) with a traditional implementation of `max`).

This shows one potential benefit of locals: making Forth programs more readable. Of course, this benefit will only be realized if the programmers continue to honour the principle of factoring instead of using the added latitude to make the words longer.

Using `T0` can and should be avoided. Without `T0`, every value-flavoured local has only a single assignment and many advantages of functional languages apply to Forth. I.e., programs are easier to analyse, to optimize and to read: It is clear from the definition what the local stands for, it does not turn into something different later.

E.g., a definition using `T0` might look like this:

```
: strcmp { addr1 u1 addr2 u2 -- n }
  u1 u2 min 0
  ?do
    addr1 c@ addr2 c@ -
    ?dup-if
    unloop exit
  then
    addr1 char+ T0 addr1
    addr2 char+ T0 addr2
  loop
  u1 u2 - ;
```

Here, `T0` is used to update `addr1` and `addr2` at every loop iteration. `strcmp` is a typical example of the readability problems of using `T0`. When you start reading `strcmp`, you think that `addr1` refers to the start of the string. Only near the end of the loop you realize that it is something else.

This can be avoided by defining two locals at the start of the loop that are initialized with the right value for the current iteration.

```
: strcmp { addr1 u1 addr2 u2 -- n }
  addr1 addr2
  u1 u2 min 0
  ?do { s1 s2 }
    s1 c@ s2 c@ -
    ?dup-if
    unloop exit
  then
    s1 char+ s2 char+
  loop
```

```
2drop
u1 u2 - ;
```

Here it is clear from the start that `s1` has a different value in every loop iteration.

6.22.1.4 Locals implementation

Gforth uses an extra locals stack. The most compelling reason for this is that the return stack is not float-aligned; using an extra stack also eliminates the problems and restrictions of using the return stack as locals stack. Like the other stacks, the locals stack grows toward lower addresses. A few primitives allow an efficient implementation:

```
@local# ( #noffset - w ) gforth-0.2 "fetch-local-number"
f@local# ( #noffset - r ) gforth-0.2 "f-fetch-local-number"
laddr# ( #noffset - c-addr ) gforth-0.2 "laddr-number"
lp+!# ( #noffset - ) gforth-0.2 "lp-plus-store-number"
```

used with negative immediate values it allocates memory on the local stack, a positive immediate argument drops memory from the local stack

```
lp! ( c-addr - ) gforth-internal "lp-store"
>l ( w - ) gforth-0.2 "to-l"
f>l ( r - ) gforth-0.2 "f-to-l"
```

In addition to these primitives, some specializations of these primitives for commonly occurring inline arguments are provided for efficiency reasons, e.g., `@local0` as specialization of `@local#` for the inline argument 0. The following compiling words compile the right specialized version, or the general version, as appropriate:

```
compile-lp+! ( n - ) gforth-0.2 "compile-l-p-plus-store"
```

Combinations of conditional branches and `lp+!#` like `?branch-lp+!#` (the locals pointer is only changed if the branch is taken) are provided for efficiency and correctness in loops.

A special area in the dictionary space is reserved for keeping the local variable names. `{` switches the dictionary pointer to this area and `}` switches it back and generates the locals initializing code. `W:` etc. are normal defining words. This special area is cleared at the start of every colon definition.

A special feature of Gforth's dictionary is used to implement the definition of locals without type specifiers: every word list (aka vocabulary) has its own methods for searching etc. (see Section 6.16 [Word Lists], page 133). For the present purpose we defined a word list with a special search method: When it is searched for a word, it actually creates that word using `W:`. `{` changes the search order to first search the word list containing `}`, `W:` etc., and then the word list for defining locals without type specifiers.

The lifetime rules support a stack discipline within a colon definition: The lifetime of a local is either nested with other locals lifetimes or it does not overlap them.

At `BEGIN`, `IF`, and `AHEAD` no code for locals stack pointer manipulation is generated. Between control structure words locals definitions can push locals onto the locals stack. `AGAIN` is the simplest of the other three control flow words. It has to restore the locals stack depth of the corresponding `BEGIN` before branching. The code looks like this:

```
lp+!# current-locals-size - dest-locals-size
branch <begin>
```

UNTIL is a little more complicated: If it branches back, it must adjust the stack just like AGAIN. But if it falls through, the locals stack must not be changed. The compiler generates the following code:

```
?branch-lp+!# <begin> current-locals-size — dest-locals-size
```

The locals stack pointer is only adjusted if the branch is taken.

THEN can produce somewhat inefficient code:

```
lp+!# current-locals-size — orig-locals-size
<orig target>:
lp+!# orig-locals-size — new-locals-size
```

The second `lp+!#` adjusts the locals stack pointer from the level at the *orig* point to the level after the THEN. The first `lp+!#` adjusts the locals stack pointer from the current level to the level at the orig point, so the complete effect is an adjustment from the current level to the right level after the THEN.

In a conventional Forth implementation a dest control-flow stack entry is just the target address and an orig entry is just the address to be patched. Our locals implementation adds a word list to every orig or dest item. It is the list of locals visible (or assumed visible) at the point described by the entry. Our implementation also adds a tag to identify the kind of entry, in particular to differentiate between live and dead (reachable and unreachable) orig entries.

A few unusual operations have to be performed on locals word lists:

```
common-list ( list1 list2 — list3 ) gforth-internal "common-list"
sub-list? ( list1 list2 — f ) gforth-internal "sub-list?"
list-size ( list — u ) gforth-internal "list-size"
```

Several features of our locals word list implementation make these operations easy to implement: The locals word lists are organised as linked lists; the tails of these lists are shared, if the lists contain some of the same locals; and the address of a name is greater than the address of the names behind it in the list.

Another important implementation detail is the variable `dead-code`. It is used by BEGIN and THEN to determine if they can be reached directly or only through the branch that they resolve. `dead-code` is set by UNREACHABLE, AHEAD, EXIT etc., and cleared at the start of a colon definition, by BEGIN and usually by THEN.

Counted loops are similar to other loops in most respects, but LEAVE requires special attention: It performs basically the same service as AHEAD, but it does not create a control-flow stack entry. Therefore the information has to be stored elsewhere; traditionally, the information was stored in the target fields of the branches created by the LEAVES, by organizing these fields into a linked list. Unfortunately, this clever trick does not provide enough space for storing our extended control flow information. Therefore, we introduce another stack, the leave stack. It contains the control-flow stack entries for all unresolved LEAVES.

Local names are kept until the end of the colon definition, even if they are no longer visible in any control-flow path. In a few cases this may lead to increased space needs for the locals name area, but usually less than reclaiming this space would cost in code size.

6.22.1.5 Closures

Gforth also provides basic closures. A closure is a combination of a quotation (see Section 6.10.7 [Quotations], page 102) and locals. Gforth's closures have locals which are filled with values at the closure's run-time, producing a trampoline xt. When executing that trampoline xt, the closure's code is executed, with access to the closure's locals on the locals stack. Modifications of the closure's locals aren't persistent, i.e. when the closure EXITS, the modified values are lost.

`[{: (- haddr u latest latestnt wid 0) gforth-experimental "start-closure"`

starts a closure. Closures first declare the locals frame they are going to use, and then the code that is executed with those locals. Closures end like quotations with a `;`. The locals declaration ends depending where the closure's locals are created. At run-time, the closure is created as trampoline xt, and fills the values of its local frame from the stack. At execution time of the xt, the local frame is copied to the locals stack, and used inside the closure's code. After return, those values are removed from the locals stack, and not updated in the closure itself.

`:}l (haddr u latest latestnt wid 0 a-addr1 u1 ... -) gforth-1.0 "close-brace-locals"`

end a closure's locals declaration. The closure will be allocated on the local's stack.

`:}d (haddr u latest latestnt wid 0 a-addr1 u1 ... -) gforth-1.0 "close-brace-dictionary"`

end a closure's locals declaration. The closure will be allocated in the dictionary.

`:}h (haddr u latest latestnt wid 0 a-addr1 u1 ... -) gforth-1.0 "close-brace-heap"`

end a closure's locals declaration. The closure will be allocated on the heap.

`>addr (xt - addr) gforth-experimental "to-addr"`

convert the xt of a closure on the heap to the *addr* with can be passed to **free** to get rid of the closure

```
: foo [{: a f: b d: c xt: d :}d a . b f. c d. d ;] ;
5 3.3e #1234. ' cr foo execute
```

foo creates a closure in the dictionary with a single cell, a floating point, a double, and an xt, and prints the first three values before executing the xt on invocation.

This allows to implement Donald Knuth's "Man or boy test" proposed in 1964 to test Algol compilers.

```
: A {: w^ k x1 x2 x3 xt: x4 xt: x5 | w^ B :} recursive
  k 0<= IF x4 x5 f+ ELSE
    B k x1 x2 x3 action-of x4 [{: B k x1 x2 x3 x4 :}L
      -1 k +!
      k B x1 x2 x3 x4 A ;] dup B !
    execute THEN ;
: man-or-boy? ( n -- ) [: 1e ;] [: -1e ;] 2dup swap [: 0e ;] A f. ;
```

Sometimes, closures need a permanent storage to be modified; it is even possible that more than one closure shares that permanent storage. In the example above, local variables of the outer procedure are used for this, but in some cases, the closure lives longer than the outer procedure; especially closures allocated in the dictionary or on the heap are designed to outlive their parent procedure.

For those, we have home locations, which are allocated like closures, but their code is directly executed at run-time and should provide us with the addresses of the home locations.

```
: bar ( a b c -- aaddr baddr caddr hl-addr )
  <{: w^ a w^ b w^ c :}h a b c ;> ;
```

This example creates a home location with three cells on the heap, and returns the addresses of the three locations and the address of the home location. This address can be used to **free** the home location when it is no longer needed.

```
<{: ( - hmaddr u latest latestnt wid 0 ) gforth-experimental "start-homelocation"
```

starts a home location

```
;> ( - ) gforth-experimental "end-homelocation"
```

end using a home location compare threaded-code cell with the primitive xt For the code address ca of a primitive, find the xt (or 0).

6.22.2 Standard Forth locals

The Forth-2012 standard defines a syntax for locals, that is similar to a subset of Gforth locals. Instead of using { and }, the standard decided to use {: and :}, as shown in the following examples:

```
{: local1 local2 ... -- comment :}
```

or

```
{: local1 local2 ... | local3 local4 ... -- comment :}
```

where local3 and local4 are uninitialized or

```
{: local1 local2 ... :}
```

The order of the locals corresponds to the order in a stack comment. The restrictions are:

- Locals can only be cell-sized values (no type specifiers are allowed).
- Locals can be defined only outside control structures.
- Locals can interfere with explicit usage of the return stack. For the exact (and long) rules, see the standard. If you don't use return stack accessing words in a definition using locals, you will be all right. The purpose of this rule is to make locals implementation on the return stack easier.
- The whole definition must be in one line.

Locals defined in Standard Forth behave like **VALUES** (see Section 6.10.4 [Values], page 100). I.e., they are initialized from the stack. Using their name produces their value. Their value can be changed using **T0**.

Since the syntax above is supported by Gforth directly, you need not do anything to use it. If you want to port a program using this syntax to another ANS Forth system, use **compat/anslocal.fs** to implement the syntax on the other system.

Note that a syntax shown in the standard, section A.13 looks similar, but is quite different in having the order of locals reversed. Beware!

The Standard Forth locals wordset itself consists of two words:

```
(local) ( addr u - ) local "paren-local-paren"
```

```
{: ( - hmaddr u latest latestnt wid 0 ) local-ext "brace-colon"
```

Start standard locals declaration. All Gforth locals extensions are supported by Gforth, though the standard only supports the subset of cells.

The ANS Forth locals extension wordset defines a syntax using `locals|`, but it is so awful that we strongly recommend not to use it. We have implemented this syntax to make porting to Gforth easy, but do not document it here. The problem with this syntax is that the locals are defined in an order reversed with respect to the standard stack comment notation, making programs harder to read, and easier to misread and miswrite. The only merit of this syntax is that it is easy to implement using the ANS Forth locals wordset.

6.23 Structures

This section presents the structure package that comes with Gforth. A version of the package implemented in Standard Forth is available in `compat/struct.fs`. This package was inspired by a posting on `comp.lang.forth` in 1989 (unfortunately I don't remember, by whom; possibly John Hayes). A version of this section has been published in M. Anton Ertl, Yet Another Forth Structures Package (<https://www.complang.tuwien.ac.at/forth/objects/structs.html>), Forth Dimensions 19(3), pages 13–16. Marcel Hendrix provided helpful comments.

6.23.1 Why explicit structure support?

If we want to use a structure containing several fields, we could simply reserve memory for it, and access the fields using address arithmetic (see Section 6.7.6 [Address arithmetic], page 75). As an example, consider a structure with the following fields

```
a      is a float
b      is a cell
c      is a float
```

Given the (float-aligned) base address of the structure we get the address of the field

```
a      without doing anything further.
b      with float+
c      with float+ cell+ faligned
```

It is easy to see that this can become quite tiring.

Moreover, it is not very readable, because seeing a `cell+` tells us neither which kind of structure is accessed nor what field is accessed; we have to somehow infer the kind of structure, and then look up in the documentation, which field of that structure corresponds to that offset.

Finally, this kind of address arithmetic also causes maintenance troubles: If you add or delete a field somewhere in the middle of the structure, you have to find and change all computations for the fields afterwards.

So, instead of using `cell+` and friends directly, how about storing the offsets in constants:

```
0 constant a-offset
0 float+ constant b-offset
0 float+ cell+ faligned c-offset
```


Now we can get the address of field `x` with `x-offset +`. This is much better in all respects. Of course, you still have to change all later offset definitions if you add a field. You can fix this by declaring the offsets in the following way:

```
0 constant a-offset
a-offset float+ constant b-offset
b-offset cell+ faligned constant c-offset
```

Since we always use the offsets with `+`, we could use a defining word `cfield` that includes the `+` in the action of the defined word:

```
: cfield ( n "name" -- )
  create ,
does> ( name execution: addr1 -- addr2 )
  @ + ;

0 cfield a
0 a float+ cfield b
0 b cell+ faligned cfield c
```

Instead of `x-offset +`, we now simply write `x`.

The structure field words now can be used quite nicely. However, their definition is still a bit cumbersome: We have to repeat the name, the information about size and alignment is distributed before and after the field definitions etc. The structure package presented here addresses these problems.

6.23.2 Structure Usage

You can define a structure for a (data-less) linked list with:

```
struct
  cell% field list-next
end-struct list%
```

With the address of the list node on the stack, you can compute the address of the field that contains the address of the next node with `list-next`. E.g., you can determine the length of a list with:

```
: list-length ( list -- n )
\ "list" is a pointer to the first element of a linked list
\ "n" is the length of the list
0 BEGIN ( list1 n1 )
  over
  WHILE ( list1 n1 )
    1+ swap list-next @ swap
  REPEAT
  nip ;
```

You can reserve memory for a list node in the dictionary with `list% %allot`, which leaves the address of the list node on the stack. For the equivalent allocation on the heap you can use `list% %alloc` (or, for an `allocate`-like stack effect (i.e., with `ior`), use `list% %allocate`). You can get the size of a list node with `list% %size` and its alignment with `list% %alignment`.

Note that in Standard Forth the body of a **created** word is **aligned** but not necessarily **faligned**; therefore, if you do a:

```
create name foo% %allot drop
```

then the memory allotted for **foo%** is guaranteed to start at the body of **name** only if **foo%** contains only character, cell and double fields. Therefore, if your structure contains floats, better use

```
foo% %allot constant name
```

You can include a structure **foo%** as a field of another structure, like this:

```
struct
...
    foo% field ...
...
end-struct ...
```

Instead of starting with an empty structure, you can extend an existing structure. E.g., a plain linked list without data, as defined above, is hardly useful; You can extend it to a linked list of integers, like this:²³

```
list%
    cell% field intlist-int
end-struct intlist%
```

intlist% is a structure with two fields: **list-next** and **intlist-int**.

You can specify an array type containing *n* elements of type **foo%** like this:

```
foo% n *
```

You can use this array type in any place where you can use a normal type, e.g., when defining a field, or with **%allot**.

The first field is at the base address of a structure and the word for this field (e.g., **list-next**) actually does not change the address on the stack. You may be tempted to leave it away in the interest of run-time and space efficiency. This is not necessary, because the structure package optimizes this case: If you compile a first-field words, no code is generated. So, in the interest of readability and maintainability you should include the word for the field when accessing the field.

6.23.3 Structure Naming Convention

The field names that come to (my) mind are often quite generic, and, if used, would cause frequent name clashes. E.g., many structures probably contain a **counter** field. The structure names that come to (my) mind are often also the logical choice for the names of words that create such a structure.

Therefore, I have adopted the following naming conventions:

- The names of fields are of the form **struct-field**, where **struct** is the basic name of the structure, and **field** is the basic name of the field. You can think of field words as converting the (address of the) structure into the (address of the) field.

²³ This feature is also known as *extended records*. It is the main innovation in the Oberon language; in other words, adding this feature to Modula-2 led Wirth to create a new language, write a new compiler etc. Adding this feature to Forth just required a few lines of code.

- The names of structures are of the form *struct%*, where *struct* is the basic name of the structure.

This naming convention does not work that well for fields of extended structures; e.g., the integer list structure has a field *intlist-int*, but has *list-next*, not *intlist-next*.

6.23.4 Structure Implementation

The central idea in the implementation is to pass the data about the structure being built on the stack, not in some global variable. Everything else falls into place naturally once this design decision is made.

The type description on the stack is of the form *align size*. Keeping the size on the top-of-stack makes dealing with arrays very simple.

field is a defining word that uses *Create* and *DOES>*. The body of the field contains the offset of the field, and the normal *DOES>* action is simply:

```
@ +
```

i.e., add the offset to the address, giving the stack effect *addr1* – *addr2* for a field.

This simple structure is slightly complicated by the optimization for fields with offset 0, which requires a different *DOES>*-part (because we cannot rely on there being something on the stack if such a field is invoked during compilation). Therefore, we put the different *DOES>*-parts in separate words, and decide which one to invoke based on the offset. For a zero offset, the field is basically a noop; it is immediate, and therefore no code is generated when it is compiled.

6.23.5 Structure Glossary

%align (*align size* –) gforth-0.4 “%align”

Align the data space pointer to the alignment *align*.

%alignment (*align size* – *align*) gforth-0.4 “%alignment”

The alignment of the structure.

%alloc (*align size* – *addr*) gforth-0.4 “%alloc”

Allocate *size* address units with alignment *align*, giving a data block at *addr*; **throw** an ior code if not successful. push to bottom of stack pop from bottom of stack

%allocate (*align size* – *addr ior*) gforth-0.4 “%allocate”

Allocate *size* address units with alignment *align*, similar to *allocate*.

%allot (*align size* – *addr*) gforth-0.4 “%allot”

Allot *size* address units of data space with alignment *align*; the resulting block of data is found at *addr*.

cell% (– *align size*) gforth-0.4 “cell%”

char% (– *align size*) gforth-0.4 “char%”

dfloat% (– *align size*) gforth-0.4 “dfloat%”

double% (– *align size*) gforth-0.4 “double%”

end-struct (*align size* “*name*” –) gforth-0.2 “end-struct”

Define a structure/type descriptor *name* with alignment *align* and size *size1* (*size* rounded up to be a multiple of *align*).

name execution: – *align size1*

field (*align1 offset1 align size "name" – align2 offset2*) gforth-0.2 “field”

Create a field *name* with offset *offset1*, and the type given by *align size*. *offset2* is the offset of the next field, and *align2* is the alignment of all fields.

name execution: *addr1 – addr2*.

addr2=addr1+offset1

float% (– *align size*) gforth-0.4 “float%”

naligned (*addr1 n – addr2*) gforth-0.5 “naligned”

addr2 is the aligned version of *addr1* with respect to the alignment *n*.

sfloat% (– *align size*) gforth-0.4 “sfloat%”

%size (*align size – size*) gforth-0.4 “%size”

The size of the structure.

struct (– *align size*) gforth-0.2 “struct”

An empty structure, used to start a structure definition.

6.23.6 Forth200x Structures

The Forth 2012 standard defines a slightly less convenient form of structures. In general (when using **field+**, you have to perform the alignment yourself, but there are a number of convenience words (e.g., **field:** that perform the alignment for you.

A typical usage example is:

```
0
  field:                s-a
  faligned 2 floats +field s-b
constant s-struct
```

An alternative way of writing this structure is:

```
begin-structure s-struct
  field:                s-a
  faligned 2 floats +field s-b
end-structure
```

begin-structure ("*name*" – *struct-sys 0*) facility-ext “begin-structure”

end-structure (*struct-sys +n –*) facility-ext “end-structure”

end a structure started with **begin-structure**

+field (*noffset1 nsize "name" – noffset2*) facility-ext “plus-field”

Defining word; defines *name* (*addr1 -- addr2*), where *addr2* is *addr1+noffset1*. *noffset2* is *noffset1+nsize*. set **+field** to standard behavior

cfield: (*u1 "name" – u2*) facility-ext “c-field-colon”

Define a char-sized field

field: (*u1 "name" – u2*) facility-ext “field-colon”

Define an aligned cell-sized field

2field: (*u1 "name" – u2*) gforth-0.7 “two-field-colon”

Define an aligned double-cell-sized field

```
ffield: ( u1 "name" – u2 ) floating-ext "f-field-colon"
```

Define a faligned float-sized field

```
sffield: ( u1 "name" – u2 ) floating-ext "s-f-field-colon"
```

Define a sfaigned sfloat-sized field

```
dffield: ( u1 "name" – u2 ) floating-ext "d-f-field-colon"
```

Define a dfaigned dfloat-sized field

6.24 Object-oriented Forth

Gforth comes with three packages for object-oriented programming: `objects.fs`, `oof.fs`, and `mini-oof.fs`; none of them is preloaded, so you have to **include** them before use. The most important differences between these packages (and others) are discussed in Section 6.24.7 [Comparison with other object models], page 196. All packages are written in Standard Forth and can be used with any other Standard Forth.

6.24.1 Why object-oriented programming?

Often we have to deal with several data structures (*objects*), that have to be treated similarly in some respects, but differently in others. Graphical objects are the textbook example: circles, triangles, dinosaurs, icons, and others, and we may want to add more during program development. We want to apply some operations to any graphical object, e.g., **draw** for displaying it on the screen. However, **draw** has to do something different for every kind of object.

We could implement **draw** as a big CASE control structure that executes the appropriate code depending on the kind of object to be drawn. This would be not be very elegant, and, moreover, we would have to change **draw** every time we add a new kind of graphical object (say, a spaceship).

What we would rather do is: When defining spaceships, we would tell the system: “Here’s how you **draw** a spaceship; you figure out the rest”.

This is the problem that all systems solve that (rightfully) call themselves object-oriented; the object-oriented packages presented here solve this problem (and not much else).

6.24.2 Object-Oriented Terminology

This section is mainly for reference, so you don’t have to understand all of it right away. The terminology is mainly Smalltalk-inspired. In short:

class a data structure definition with some extras.

object an instance of the data structure described by the class definition.

instance variables
 fields of the data structure.

selector (or *method selector*) a word (e.g., **draw**) that performs an operation on a variety of data structures (classes). A selector describes *what* operation to perform. In C++ terminology: a (pure) virtual function.

method the concrete definition that performs the operation described by the selector for a specific class. A method specifies *how* the operation is performed for a specific class.

selector invocation

a call of a selector. One argument of the call (the TOS (top-of-stack)) is used for determining which method is used. In Smalltalk terminology: a message (consisting of the selector and the other arguments) is sent to the object.

receiving object

the object used for determining the method executed by a selector invocation. In the **objects.fs** model, it is the object that is on the TOS when the selector is invoked. (*Receiving* comes from the Smalltalk *message* terminology.)

child class a class that has (*inherits*) all properties (instance variables, selectors, methods) from a *parent class*. In Smalltalk terminology: The subclass inherits from the superclass. In C++ terminology: The derived class inherits from the base class.

6.24.3 The **objects.fs** model

This section describes the **objects.fs** package. This material also has been published in M. Anton Ertl, *Yet Another Forth Objects Package* (<https://www.complang.tuwien.ac.at/forth/objects/objects.html>), Forth Dimensions 19(2), pages 37–43.

This section assumes that you have read Section 6.23 [Structures], page 173.

The techniques on which this model is based have been used to implement the parser generator, Gray, and have also been used in Gforth for implementing the various flavours of word lists (hashed or not, case-sensitive or not, special-purpose word lists for locals etc.).

Marcel Hendrix provided helpful comments on this section.

6.24.3.1 Properties of the **objects.fs** model

- It is straightforward to pass objects on the stack. Passing selectors on the stack is a little less convenient, but possible.
- Objects are just data structures in memory, and are referenced by their address. You can create words for objects with normal defining words like **constant**. Likewise, there is no difference between instance variables that contain objects and those that contain other data.
- Late binding is efficient and easy to use.
- It avoids parsing, and thus avoids problems with state-smartness and reduced extensibility; for convenience there are a few parsing words, but they have non-parsing counterparts. There are also a few defining words that parse. This is hard to avoid, because all standard defining words parse (except **:noname**); however, such words are not as bad as many other parsing words, because they are not state-smart.
- It does not try to incorporate everything. It does a few things and does them well (IMO). In particular, this model was not designed to support information hiding (although it has features that may help); you can use a separate package for achieving this.
- It is layered; you don't have to learn and use all features to use this model. Only a few features are necessary (see Section 6.24.3.2 [Basic Objects Usage], page 180,

see Section 6.24.3.3 [The Objects base class], page 181, see Section 6.24.3.4 [Creating objects], page 181.), the others are optional and independent of each other.

- An implementation in Standard Forth is available.

6.24.3.2 Basic `objects.fs` Usage

You can define a class for graphical objects like this:

```
object class \ "object" is the parent class
  selector draw ( x y graphical -- )
end-class graphical
```

This code defines a class `graphical` with an operation `draw`. We can perform the operation `draw` on any `graphical` object, e.g.:

```
100 100 t-rex draw
```

where `t-rex` is a word (say, a constant) that produces a graphical object.

How do we create a graphical object? With the present definitions, we cannot create a useful graphical object. The class `graphical` describes graphical objects in general, but not any concrete graphical object type (C++ users would call it an *abstract class*); e.g., there is no method for the selector `draw` in the class `graphical`.

For concrete graphical objects, we define child classes of the class `graphical`, e.g.:

```
graphical class \ "graphical" is the parent class
  cell% field circle-radius

:noname ( x y circle -- )
  circle-radius @ draw-circle ;
overrides draw

:noname ( n-radius circle -- )
  circle-radius ! ;
overrides construct

end-class circle
```

Here we define a class `circle` as a child of `graphical`, with field `circle-radius` (which behaves just like a field (see Section 6.23 [Structures], page 173); it defines (using `overrides`) new methods for the selectors `draw` and `construct` (`construct` is defined in `object`, the parent class of `graphical`).

Now we can create a circle on the heap (i.e., allocated memory) with:

```
50 circle heap-new constant my-circle
```

`heap-new` invokes `construct`, thus initializing the field `circle-radius` with 50. We can draw this new circle at (100,100) with:

```
100 100 my-circle draw
```

Note: You can only invoke a selector if the object on the TOS (the receiving object) belongs to the class where the selector was defined or one of its descendents; e.g., you can invoke `draw` only for objects belonging to `graphical` or its descendents (e.g., `circle`). Immediately before `end-class`, the search order has to be the same as immediately after `class`.

6.24.3.3 The `object.fs` base class

When you define a class, you have to specify a parent class. So how do you start defining classes? There is one class available from the start: `object`. It is ancestor for all classes and so is the only class that has no parent. It has two selectors: `construct` and `print`.

6.24.3.4 Creating objects

You can create and initialize an object of a class on the heap with `heap-new` (... class – object) and in the dictionary (allocation with `allot`) with `dict-new` (... class – object). Both words invoke `construct`, which consumes the stack items indicated by "..." above.

If you want to allocate memory for an object yourself, you can get its alignment and size with `class-inst-size 2@` (class – align size). Once you have memory for an object, you can initialize it with `init-object` (... class object –); `construct` does only a part of the necessary work.

6.24.3.5 Object-Oriented Programming Style

This section is not exhaustive.

In general, it is a good idea to ensure that all methods for the same selector have the same stack effect: when you invoke a selector, you often have no idea which method will be invoked, so, unless all methods have the same stack effect, you will not know the stack effect of the selector invocation.

One exception to this rule is methods for the selector `construct`. We know which method is invoked, because we specify the class to be constructed at the same place. Actually, I defined `construct` as a selector only to give the users a convenient way to specify initialization. The way it is used, a mechanism different from selector invocation would be more natural (but probably would take more code and more space to explain).

6.24.3.6 Class Binding

Normal selector invocations determine the method at run-time depending on the class of the receiving object. This run-time selection is called *late binding*.

Sometimes it's preferable to invoke a different method. For example, you might want to use the simple method for `printing objects` instead of the possibly long-winded `print` method of the receiver class. You can achieve this by replacing the invocation of `print` with:

```
[bind] object print
```

in compiled code or:

```
bind object print
```

in interpreted code. Alternatively, you can define the method with a name (e.g., `print-object`), and then invoke it through the name. Class binding is just a (often more convenient) way to achieve the same effect; it avoids name clutter and allows you to invoke methods directly without naming them first.

A frequent use of class binding is this: When we define a method for a selector, we often want the method to do what the selector does in the parent class, and a little more. There is a special word for this purpose: `[parent]; [parent] selector` is equivalent to `[bind] parent selector`, where `parent` is the parent class of the current class. E.g., a method definition might look like:

```
:noname
```



```

dup [parent] foo \ do parent's foo on the receiving object
... \ do some more
; overrides foo

```

In *Object-oriented programming in ANS Forth* (Forth Dimensions, March 1997), Andrew McKewan presents class binding as an optimization technique. I recommend not using it for this purpose unless you are in an emergency. Late binding is pretty fast with this model anyway, so the benefit of using class binding is small; the cost of using class binding where it is not appropriate is reduced maintainability.

While we are at programming style questions: You should bind selectors only to ancestor classes of the receiving object. E.g., say, you know that the receiving object is of class `foo` or its descendents; then you should bind only to `foo` and its ancestors.

6.24.3.7 Method conveniences

In a method you usually access the receiving object pretty often. If you define the method as a plain colon definition (e.g., with `:noname`), you may have to do a lot of stack gymnastics. To avoid this, you can define the method with `m: ... ;m`. E.g., you could define the method for drawing a circle with

```

m: ( x y circle -- )
  ( x y ) this circle-radius @ draw-circle ;m

```

When this method is executed, the receiver object is removed from the stack; you can access it with `this` (admittedly, in this example the use of `m: ... ;m` offers no advantage). Note that I specify the stack effect for the whole method (i.e. including the receiver object), not just for the code between `m:` and `;m`. You cannot use `exit` in `m:...;m`; instead, use `exitm`.²⁴

You will frequently use sequences of the form `this field` (in the example above: `this circle-radius`). If you use the field only in this way, you can define it with `inst-var` and eliminate the `this` before the field name. E.g., the `circle` class above could also be defined with:

```

graphical class
  cell% inst-var radius

m: ( x y circle -- )
  radius @ draw-circle ;m
overrides draw

m: ( n-radius circle -- )
  radius ! ;m
overrides construct

end-class circle

```

`radius` can only be used in `circle` and its descendent classes and inside `m:...;m`.

²⁴ Moreover, for any word that calls `catch` and was defined before loading `objects.fs`, you have to redefine it like I redefined `catch`: `: catch this >r catch r> to-this ;`

You can also define fields with `inst-value`, which is to `inst-var` what `value` is to `variable`. You can change the value of such a field with `[to-inst]`. E.g., we could also define the class `circle` like this:

```
graphical class
  inst-value radius

m: ( x y circle -- )
  radius draw-circle ;m
overrides draw

m: ( n-radius circle -- )
  [to-inst] radius ;m
overrides construct

end-class circle
```

6.24.3.8 Classes and Scoping

Inheritance is frequent, unlike structure extension. This exacerbates the problem with the field name convention (see Section 6.23.3 [Structure Naming Convention], page 175): One always has to remember in which class the field was originally defined; changing a part of the class structure would require changes for renaming in otherwise unaffected code.

To solve this problem, I added a scoping mechanism (which was not in my original charter): A field defined with `inst-var` (or `inst-value`) is visible only in the class where it is defined and in the descendent classes of this class. Using such fields only makes sense in `m:-`defined methods in these classes anyway.

This scoping mechanism allows us to use the unadorned field name, because name clashes with unrelated words become much less likely.

Once we have this mechanism, we can also use it for controlling the visibility of other words: All words defined after `protected` are visible only in the current class and its descendents. `public` restores the compilation (i.e. `current`) word list that was in effect before. If you have several `protected`s without an intervening `public` or `set-current`, `public` will restore the compilation word list in effect before the first of these `protected`s.

6.24.3.9 Dividing classes

You may want to do the definition of methods separate from the definition of the class, its selectors, fields, and instance variables, i.e., separate the implementation from the definition. You can do this in the following way:

```
graphical class
  inst-value radius
end-class circle

... \ do some other stuff

circle methods \ now we are ready
```

```

m: ( x y circle -- )
    radius draw-circle ;m
overrides draw

m: ( n-radius circle -- )
    [to-inst] radius ;m
overrides construct

end-methods

```

You can use several `methods...end-methods` sections. The only things you can do to the class in these sections are: defining methods, and overriding the class's selectors. You must not define new selectors or fields.

Note that you often have to override a selector before using it. In particular, you usually have to override `construct` with a new method before you can invoke `heap-new` and friends. E.g., you must not create a circle before the `overrides construct` sequence in the example above.

6.24.3.10 Object Interfaces

In this model you can only call selectors defined in the class of the receiving objects or in one of its ancestors. If you call a selector with a receiving object that is not in one of these classes, the result is undefined; if you are lucky, the program crashes immediately.

Now consider the case when you want to have a selector (or several) available in two classes: You would have to add the selector to a common ancestor class, in the worst case to `object`. You may not want to do this, e.g., because someone else is responsible for this ancestor class.

The solution for this problem is interfaces. An interface is a collection of selectors. If a class implements an interface, the selectors become available to the class and its descendents. A class can implement an unlimited number of interfaces. For the problem discussed above, we would define an interface for the selector(s), and both classes would implement the interface.

As an example, consider an interface `storage` for writing objects to disk and getting them back, and a class `foo` that implements it. The code would look like this:

```

interface
    selector write ( file object -- )
    selector read1 ( file object -- )
end-interface storage

bar class
    storage implementation

... overrides write
... overrides read1
...
end-class foo

```

(I would add a word `read (file – object)` that uses `read1` internally, but that's beyond the point illustrated here.)

Note that you cannot use `protected` in an interface; and of course you cannot define fields.

In the Neon model, all selectors are available for all classes; therefore it does not need interfaces. The price you pay in this model is slower late binding, and therefore, added complexity to avoid late binding.

6.24.3.11 `objects.fs` Implementation

An object is a piece of memory, like one of the data structures described with `struct...end-struct`. It has a field `object-map` that points to the method map for the object's class.

The *method map*²⁵ is an array that contains the execution tokens (*xts*) of the methods for the object's class. Each selector contains an offset into a method map.

`selector` is a defining word that uses `CREATE` and `DOES>`. The body of the selector contains the offset; the `DOES>` action for a class selector is, basically:

```
( object addr ) @ over object-map @ + @ execute
```

Since `object-map` is the first field of the object, it does not generate any code. As you can see, calling a selector has a small, constant cost.

A class is basically a `struct` combined with a method map. During the class definition the alignment and size of the class are passed on the stack, just as with `structs`, so `field` can also be used for defining class fields. However, passing more items on the stack would be inconvenient, so `class` builds a data structure in memory, which is accessed through the variable `current-interface`. After its definition is complete, the class is represented on the stack by a pointer (e.g., as parameter for a child class definition).

A new class starts off with the alignment and size of its parent, and a copy of the parent's method map. Defining new fields extends the size and alignment; likewise, defining new selectors extends the method map. `overrides` just stores a new *xt* in the method map at the offset given by the selector.

Class binding just gets the *xt* at the offset given by the selector from the class's method map and `compile,s` (in the case of `[bind]`) it.

I implemented `this` as a `value`. At the start of an `m:...;m` method the old `this` is stored to the return stack and restored at the end; and the object on the TOS is stored TO `this`. This technique has one disadvantage: If the user does not leave the method via `;m`, but via `throw` or `exit`, `this` is not restored (and `exit` may crash). To deal with the `throw` problem, I have redefined `catch` to save and restore `this`; the same should be done with any word that can catch an exception. As for `exit`, I simply forbid it (as a replacement, there is `exitm`).

`inst-var` is just the same as `field`, with a different `DOES>` action:

```
@ this +
```

Similar for `inst-value`.

²⁵ This is Self terminology; in C++ terminology: virtual function table.

Each class also has a word list that contains the words defined with `inst-var` and `inst-value`, and its protected words. It also has a pointer to its parent. `class` pushes the word lists of the class and all its ancestors onto the search order stack, and `end-class` drops them.

An interface is like a class without fields, parent and protected words; i.e., it just has a method map. If a class implements an interface, its method map contains a pointer to the method map of the interface. The positive offsets in the map are reserved for class methods, therefore interface map pointers have negative offsets. Interfaces have offsets that are unique throughout the system, unlike class selectors, whose offsets are only unique for the classes where the selector is available (invokable).

This structure means that interface selectors have to perform one indirection more than class selectors to find their method. Their body contains the interface map pointer offset in the class method map, and the method offset in the interface method map. The `does>` action for an interface selector is, basically:

```
( object selector-body )
2dup selector-interface @ ( object selector-body object interface-offset )
swap object-map @ + @ ( object selector-body map )
swap selector-offset @ + @ execute
```

where `object-map` and `selector-offset` are first fields and generate no code.

As a concrete example, consider the following code:

```
interface
  selector if1sel1
  selector if1sel2
end-interface if1

object class
  if1 implementation
  selector cl1sel1
  cell% inst-var cl1liv1

' m1 overrides construct
' m2 overrides if1sel1
' m3 overrides if1sel2
' m4 overrides cl1sel2
end-class cl1

create obj1 object dict-new drop
create obj2 cl1 dict-new drop
```

The data structure created by this code (including the data structure for `object`) is shown in the figure (`objects-implementation.eps`), assuming a cell size of 4.

6.24.3.12 `objects.fs` Glossary

`bind (... "class" "selector" - ...)` objects “bind”

Execute the method for `selector` in `class`.

`<bind> (class selector-xt - xt)` objects “<bind>”

xt is the method for the selector *selector-xt* in *class*.

bind' ("class" "selector" - *xt*) objects "bind"

xt is the method for *selector* in *class*.

[bind] (*compile-time*: "class" "selector" - ; *run-time*: ... *object* - ...) objects "[bind]"

Compile the method for *selector* in *class*.

class (*parent-class* - *align offset*) objects "class"

Start a new class definition as a child of *parent-class*. *align offset* are for use by *field* etc.

class->map (*class* - *map*) objects "class->map"

map is the pointer to *class*'s method map; it points to the place in the map to which the selector offsets refer (i.e., where *object-maps* point to).

class-inst-size (*class* - *addr*) objects "class-inst-size"

Give the size specification for an instance (i.e. an object) of *class*; used as **class-inst-size 2** (*class* -- *align size*).

class-override! (*xt sel-xt class-map* -) objects "class-override!"

xt is the new method for the selector *sel-xt* in *class-map*.

class-previous (*class* -) objects "class-previous"

Drop *class*'s wordlists from the search order. No checking is made whether *class*'s wordlists are actually on the search order.

class>order (*class* -) objects "class>order"

Add *class*'s wordlists to the head of the search-order.

construct (... *object* -) objects "construct"

Initialize the data fields of *object*. The method for the class *object* just does nothing: (*object* --).

current' ("selector" - *xt*) objects "current"

xt is the method for *selector* in the current class.

[current] (*compile-time*: "selector" - ; *run-time*: ... *object* - ...) objects "[current]"

Compile the method for *selector* in the current class.

current-interface (- *addr*) objects "current-interface"

Variable: contains the class or interface currently being defined.

dict-new (... *class* - *object*) objects "dict-new"

allot and initialize an object of class *class* in the dictionary.

end-class (*align offset* "name" -) objects "end-class"

name execution: -- **class**

End a class definition. The resulting class is *class*.

end-class-noname (*align offset* - *class*) objects "end-class-noname"

End a class definition. The resulting class is *class*.

end-interface ("name" -) objects "end-interface"

name execution: -- **interface**

End an interface definition. The resulting interface is *interface*.

end-interface-noname (- *interface*) objects "end-interface-noname"

End an interface definition. The resulting interface is *interface*.

end-methods (-) objects “end-methods”

Switch back from defining methods of a class to normal mode (currently this just restores the old search order).

exitm (-) objects “exitm”

exit from a method; restore old **this**.

heap-new (... *class* - *object*) objects “heap-new”

allocate and initialize an object of class *class*.

implementation (*interface* -) objects “implementation”

The current class implements *interface*. I.e., you can use all selectors of the interface in the current class and its descendents.

init-object (... *class* *object* -) objects “init-object”

Initialize a chunk of memory (*object*) to an object of class *class*; then performs **construct**.

inst-value (*align1* *offset1* "*name*" - *align2* *offset2*) objects “inst-value”

name execution: -- **w**

w is the value of the field *name* in **this** object.

inst-var (*align1* *offset1* *align* *size* "*name*" - *align2* *offset2*) objects “inst-var”

name execution: -- **addr**

addr is the address of the field *name* in **this** object.

interface (-) objects “interface”

Start an interface definition.

m: (- *xt* *colon-sys*; *run-time*: *object* -) objects “m:”

Start a method definition; *object* becomes new **this**.

:m ("*name*" - *xt*; *run-time*: *object* -) objects “:m”

Start a named method definition; *object* becomes new **this**. Has to be ended with **;m**.

;m (*colon-sys* -; *run-time*: -) objects “;m”

End a method definition; restore old **this**.

method (*xt* "*name*" -) objects “method”

name execution: ... **object** -- ...

Create selector *name* and makes *xt* its method in the current class.

methods (*class* -) objects “methods”

Makes *class* the current class. This is intended to be used for defining methods to override selectors; you cannot define new fields or selectors.

object (- *class*) objects “object”

the ancestor of all classes.

overrides (*xt* "*selector*" -) objects “overrides”

replace default method for *selector* in the current class with *xt*. **overrides** must not be used during an interface definition.

[parent] (*compile-time*: "*selector*" - ; *run-time*: ... *object* - ...) objects “[parent]”

Compile the method for *selector* in the parent of the current class.

print (*object* –) objects “print”

Print the object. The method for the class *object* prints the address of the object and the address of its class.

protected (–) objects “protected”

Set the compilation wordlist to the current class’s wordlist

public (–) objects “public”

Restore the compilation wordlist that was in effect before the last **protected** that actually changed the compilation wordlist.

selector ("*name*" –) objects “selector”

name execution: ... **object** -- ...

Create selector *name* for the current class and its descendents; you can set a method for the selector in the current class with **overrides**.

this (– *object*) objects “this”

the receiving object of the current method (aka active object).

<to-inst> (*w xt* –) objects “<to-inst>”

store *w* into the field *xt* in **this** object.

[to-inst] (*compile-time: "name" – ; run-time: w –*) objects “[to-inst]”

store *w* into field *name* in **this** object.

to-this (*object* –) objects “to-this”

Set **this** (used internally, but useful when debugging). method prologue; *object* becomes new **this**.

xt-new (... *class xt – object*) objects “xt-new”

Make a new object, using *xt* (**align size -- addr**) to get memory.

6.24.4 The oof.fs model

This section describes the **oof.fs** package.

The package described in this section has been used in bigFORTH since 1991, and used for two large applications: a chromatographic system used to create new medicaments, and a graphic user interface library (MINOS).

You can find a description (in German) of **oof.fs** in *Object oriented bigFORTH* by Bernd Paysan, published in *Vierte Dimension* 10(2), 1994.

6.24.4.1 Properties of the oof.fs model

- This model combines object oriented programming with information hiding. It helps you writing large application, where scoping is necessary, because it provides class-oriented scoping.
- Named objects, object pointers, and object arrays can be created, selector invocation uses the “object selector” syntax. Selector invocation to objects and/or selectors on the stack is a bit less convenient, but possible.
- Selector invocation and instance variable usage of the active object is straightforward, since both make use of the active object.

- Late binding is efficient and easy to use.
- State-smart objects parse selectors. However, extensibility is provided using a (parsing) selector `postpone` and a selector `'`.
- An implementation in Standard Forth is available.

6.24.4.2 Basic `oof.fs` Usage

This section uses the same example as for `objects` (see Section 6.24.3.2 [Basic Objects Usage], page 180).

You can define a class for graphical objects like this:

```
object class graphical \ "object" is the parent class
  method draw ( x y -- )
class;
```

This code defines a class `graphical` with an operation `draw`. We can perform the operation `draw` on any `graphical` object, e.g.:

```
100 100 t-rex draw
```

where `t-rex` is an object or object pointer, created with e.g. `graphical : t-rex`.

How do we create a graphical object? With the present definitions, we cannot create a useful graphical object. The class `graphical` describes graphical objects in general, but not any concrete graphical object type (C++ users would call it an *abstract class*); e.g., there is no method for the selector `draw` in the class `graphical`.

For concrete graphical objects, we define child classes of the class `graphical`, e.g.:

```
graphical class circle \ "graphical" is the parent class
  cell var circle-radius
how:
  : draw ( x y -- )
    circle-radius @ draw-circle ;

  : init ( n-radius -- )
    circle-radius ! ;
class;
```

Here we define a class `circle` as a child of `graphical`, with a field `circle-radius`; it defines new methods for the selectors `draw` and `init` (`init` is defined in `object`, the parent class of `graphical`).

Now we can create a circle in the dictionary with:

```
50 circle : my-circle
```

: invokes `init`, thus initializing the field `circle-radius` with 50. We can draw this new circle at (100,100) with:

```
100 100 my-circle draw
```

Note: You can only invoke a selector if the receiving object belongs to the class where the selector was defined or one of its descendents; e.g., you can invoke `draw` only for objects belonging to `graphical` or its descendents (e.g., `circle`). The scoping mechanism will check if you try to invoke a selector that is not defined in this class hierarchy, so you'll get an error at compilation time.

6.24.4.3 The `oof.fs` base class

When you define a class, you have to specify a parent class. So how do you start defining classes? There is one class available from the start: `object`. You have to use it as ancestor for all classes. It is the only class that has no parent. Classes are also objects, except that they don't have instance variables; class manipulation such as inheritance or changing definitions of a class is handled through selectors of the class `object`.

`object` provides a number of selectors:

- `class` for subclassing, `definitions` to add definitions later on, and `class?` to get type informations (is the class a subclass of the class passed on the stack?).
`class ("name" -) oof "class"`
`definitions (-) oof "definitions"`
`class? (o - flag) oof "class-query"`
- `init` and `dispose` as constructor and destructor of the object. `init` is invoked after the object's memory is allocated, while `dispose` also handles deallocation. Thus if you redefine `dispose`, you have to call the parent's `dispose` with `super dispose`, too.
`init (... -) oof "init"`
`dispose (-) oof "dispose"`
- `new`, `new[]`, `:`, `ptr`, `asptr`, and `[]` to create named and unnamed objects and object arrays or object pointers.
`new (- o) oof "new"`
`new[] (n - o) oof "new-array"`
`:` ("name" -) oof "define"
`ptr ("name" -) oof "ptr"`
`asptr (o "name" -) oof "asptr"`
`[] (n "name" -) oof "array"`
- `::` and `super` for explicit scoping. You should use explicit scoping only for super classes or classes with the same set of instance variables. Explicitly-scoped selectors use early binding.
`:: ("name" -) oof "scope"`
`super ("name" -) oof "super"`
- `self` to get the address of the object
`self (- o) oof "self"`
- `bind`, `bound`, `link`, and `is` to assign object pointers and instance defers.
`bind (o "name" -) oof "bind"`
`bound (class addr "name" -) oof "bound"`
`link ("name" - class addr) oof "link"`
`is (xt "name" -) oof "is"`
- `'` to obtain selector tokens, `send` to invoke selectors from the stack, and `postpone` to generate selector invocation code.
`' ("name" - xt) oof "tick"`
`postpone ("name" -) oof "postpone"`

- **with** and **endwith** to select the active object from the stack, and enable its scope. Using **with** and **endwith** also allows you to create code using selector **postpone** without being trapped by the state-smart objects.

with (*o* -) oof “with”

endwith (-) oof “endwith”

6.24.4.4 Class Declaration

- Instance variables

var (*size* -) oof “var”

Create an instance variable

- Object pointers

ptr (-) oof “ptr”

Create an instance pointer

asptr (*class* -) oof “asptr”

Create an alias to an instance pointer, cast to another class.

- Instance defers

defer (-) oof “defer”

Create an instance defer

- Method selectors

early (-) oof “early”

Create a method selector for early binding.

method (-) oof “method”

Create a method selector.

- Class-wide variables

static (-) oof “static”

Create a class-wide cell-sized variable.

- End declaration

how: (-) oof “how-to”

End declaration, start implementation

class; (-) oof “end-class”

End class declaration or implementation

6.24.4.5 Class Implementation

6.24.5 The mini-oof.fs model

Gforth’s third object oriented Forth package is a 12-liner. It uses a mixture of the **objects.fs** and the **oof.fs** syntax, and reduces to the bare minimum of features. This is based on a posting of Bernd Paysan in comp.lang.forth.

6.24.5.1 Basic mini-oof.fs Usage

There is a base class (`class`, which allocates one cell for the object pointer) plus seven other words: to define a method, a variable, a class; to end a class, to resolve binding, to allocate an object and to compile a class method.

`object (- a-addr)` mini-oof “object”

object is the base class of all objects.

`method (m v "name" - m' v')` mini-oof “method”

Define a selector.

`var (m v size "name" - m v')` mini-oof “var”

Define a variable with *size* bytes.

`class (class - class selectors vars)` mini-oof “class”

Start the definition of a class.

`end-class (class selectors vars "name" -)` mini-oof “end-class”

End the definition of a class.

`defines (xt class "name" -)` mini-oof “defines”

Bind *xt* to the selector *name* in class *class*.

`new (class - o)` mini-oof “new”

Create a new incarnation of the class *class*.

`:: (class "name" -)` mini-oof “colon-colon”

Compile the method for the selector *name* of the class *class* (not immediate!).

6.24.5.2 Mini-OOF Example

A short example shows how to use this package. This example, in slightly extended form, is supplied as `moof-exm.fs`

```
object class
  method init
  method draw
end-class graphical
```

This code defines a class `graphical` with an operation `draw`. We can perform the operation `draw` on any `graphical` object, e.g.:

```
100 100 t-rex draw
```

where `t-rex` is an object or object pointer, created with e.g. `graphical new Constant t-rex`.

For concrete graphical objects, we define child classes of the class `graphical`, e.g.:

```
graphical class
  cell var circle-radius
end-class circle \ "graphical" is the parent class

:noname ( x y -- )
  circle-radius @ draw-circle ; circle defines draw
:noname ( r -- )
```

```
circle-radius ! ; circle defines init
```

There is no implicit init method, so we have to define one. The creation code of the object now has to call init explicitly.

```
circle new Constant my-circle
50 my-circle init
```

It is also possible to add a function to create named objects with automatic call of init, given that all objects have init on the same place:

```
: new: ( .. o "name" -- )
  new dup Constant init ;
80 circle new: large-circle
```

We can draw this new circle at (100,100) with:

```
100 100 my-circle draw
```

6.24.5.3 mini-oof.fs Implementation

Object-oriented systems with late binding typically use a “vtable”-approach: the first variable in each object is a pointer to a table, which contains the methods as function pointers. The vtable may also contain other information.

So first, let’s declare selectors:

```
: method ( m v "name" -- m' v ) Create over , swap cell+ swap
DOES> ( ... o -- ... ) @ over @ + @ execute ;
```

During selector declaration, the number of selectors and instance variables is on the stack (in address units). `method` creates one selector and increments the selector number. To execute a selector, it takes the object, fetches the vtable pointer, adds the offset, and executes the method *xt* stored there. Each selector takes the object it is invoked with as top of stack parameter; it passes the parameters (including the object) unchanged to the appropriate method which should consume that object.

Now, we also have to declare instance variables

```
: var ( m v size "name" -- m v' ) Create over , +
DOES> ( o -- addr ) @ + ;
```

As before, a word is created with the current offset. Instance variables can have different sizes (cells, floats, doubles, chars), so all we do is take the size and add it to the offset. If your machine has alignment restrictions, put the proper `aligned` or `faligned` before the variable, to adjust the variable offset. That’s why it is on the top of stack.

We need a starting point (the base object) and some syntactic sugar:

```
Create object 1 cells , 2 cells ,
: class ( class -- class selectors vars ) dup 2@ ;
```

For inheritance, the vtable of the parent object has to be copied when a new, derived class is declared. This gives all the methods of the parent class, which can be overridden, though.

```
: end-class ( class selectors vars "name" -- )
  Create here >r , dup , 2 cells ?DO ['] noop , 1 cells +LOOP
  cell+ dup cell+ r> rot @ 2 cells /string move ;
```

The first line creates the vtable, initialized with `noops`. The second line is the inheritance mechanism, it copies the xts from the parent vtable.

We still have no way to define new methods, let's do that now:

```
: defines ( xt class "name" -- ) ' >body @ + ! ;
```

To allocate a new object, we need a word, too:

```
: new ( class -- o ) here over @ allot swap over ! ;
```

Sometimes derived classes want to access the method of the parent object. There are two ways to achieve this with Mini-OOF: first, you could use named words, and second, you could look up the vtable of the parent object.

```
: :: ( class "name" -- ) ' >body @ + @ compile, ;
```

Nothing can be more confusing than a good example, so here is one. First let's declare a text object (called `button`), that stores text and position:

```
object class
  cell var text
  cell var len
  cell var x
  cell var y
  method init
  method draw
end-class button
```

Now, implement the two methods, `draw` and `init`:

```
:noname ( o -- )
  >r r@ x @ r@ y @ at-xy r@ text @ r> len @ type ;
button defines draw
:noname ( addr u o -- )
  >r 0 r@ x ! 0 r@ y ! r@ len ! r> text ! ;
button defines init
```

To demonstrate inheritance, we define a class `bold-button`, with no new data and no new selectors:

```
button class
end-class bold-button

: bold 27 emit ." [1m" ;
: normal 27 emit ." [0m" ;
```

The class `bold-button` has a different draw method to `button`, but the new method is defined in terms of the draw method for `button`:

```
:noname bold [ button :: draw ] normal ; bold-button defines draw
```

Finally, create two objects and apply selectors:

```
button new Constant foo
s" thin foo" foo init
page
foo draw
bold-button new Constant bar
```

```
s" fat bar" bar init
1 bar y !
bar draw
```

6.24.6 Mini-OOF2

Mini-OOF2 is very similar to Mini-OOF in many respects, but differs significantly in a few aspects. In particular, Mini-OOF2 has a current object variable, and uses the primitives `>o` and `o>` to manipulate that object stack. All method invocations and instance variable accesses refer to the current object.

```
>o ( c-addr - r:c-old ) new "to-o"
```

Set the current object to `c-addr`, the previous current object is pushed to the return stack

```
o> ( r:c-addr - ) new "o-restore"
```

Restore the previous current object from the return stack

To ease passing an object pointer to method invocation or instance variable accesses, the additional recognizer `rec-moof2` is activated.

```
doc-rec-moof2
```

6.24.7 Comparison with other object models

Many object-oriented Forth extensions have been proposed (*A survey of object-oriented Forths* (SIGPLAN Notices, April 1996) by Bradford J. Rodriguez and W. F. S. Poehlman lists 17). This section discusses the relation of the object models described here to two well-known and two closely-related (by the use of method maps) models. Andras Zsoter helped us with this section.

The most popular model currently seems to be the Neon model (see *Object-oriented programming in ANS Forth* (Forth Dimensions, March 1997) by Andrew McKewan) but this model has a number of limitations²⁶:

- It uses a *selector object* syntax, which makes it unnatural to pass objects on the stack.
- It requires that the selector parses the input stream (at compile time); this leads to reduced extensibility and to bugs that are hard to find.
- It allows using every selector on every object; this eliminates the need for interfaces, but makes it harder to create efficient implementations.

Another well-known publication is *Object-Oriented Forth* (Academic Press, London, 1987) by Dick Pountain. However, it is not really about object-oriented programming, because it hardly deals with late binding. Instead, it focuses on features like information hiding and overloading that are characteristic of modular languages like Ada (83).

In *Does late binding have to be slow?* (<http://www.forth.org/oopf.html>) (Forth Dimensions 18(1) 1996, pages 31-35) Andras Zsoter describes a model that makes heavy use of an active object (like `this` in `objects.fs`): The active object is not only used for accessing all fields, but also specifies the receiving object of every selector invocation; you have to change the active object explicitly with `{ ... }`, whereas in `objects.fs` it changes more or

²⁶ A longer version of this critique can be found in *On Standardizing Object-Oriented Forth Extensions* (Forth Dimensions, May 1997) by Anton Ertl.

less implicitly at `m: ... ;m`. Such a change at the method entry point is unnecessary with Zsoter's model, because the receiving object is the active object already. On the other hand, the explicit change is absolutely necessary in that model, because otherwise no one could ever change the active object. An Standard Forth implementation of this model is available through <http://www.forth.org/oopf.html>.

The `oof.fs` model combines information hiding and overloading resolution (by keeping names in various word lists) with object-oriented programming. It sets the active object implicitly on method entry, but also allows explicit changing (with `>o...o>` or with `with...endwith`). It uses parsing and state-smart objects and classes for resolving overloading and for early binding: the object or class parses the selector and determines the method from this. If the selector is not parsed by an object or class, it performs a call to the selector for the active object (late binding), like Zsoter's model. Fields are always accessed through the active object. The big disadvantage of this model is the parsing and the state-smartness, which reduces extensibility and increases the opportunities for subtle bugs; essentially, you are only safe if you never tick or `postpone` an object or class (Bernd disagrees, but I (Anton) am not convinced).

The `mini-oof.fs` model is quite similar to a very stripped-down version of the `objects.fs` model, but syntactically it is a mixture of the `objects.fs` and `oof.fs` models.

6.25 Programming Tools

6.25.1 Locating source code definitions

Many programming systems are organized as an integrated development environment (IDE) where the editor is the hub of the system, and allows building and running programs. If you want that, Gforth has it, too (see Chapter 13 [Emacs and Gforth], page 259).

However, several Forth systems have a different kind of IDE: The Forth command line is the hub of the environment; you can view the source from there in various ways, and call an editor if needed.

Gforth also implements such an IDE. It mostly follows the conventions of SwiftForth where they exist, but implements features beyond them.

An advantage of this approach is that it allows you to use your favourite editor: set the environment variable `EDITOR` to your favourite editor, and the editing commands will call that editor; Gforth invokes some GUI editors in the background (so you do not need to finish editing to continue with your Forth session), terminal editors in the foreground (default for editors not known to Gforth is foreground). If you have not set `EDITOR`, the default editor is `vi`.

`locate ("name" -) gforth-1.0 "locate"`

Show the source code of the word *name* and set the current location there.

The *current location* is set by a number of other words in addition to `locate`. Also, when an error happens while loading a file, the location of the error becomes the current location.

A number of words work with the current location:

`l (-) gforth-1.0 "l"`

Display source code lines at the current location.

`n (-) gforth-1.0 "n"`

Display lines behind the current location, or behind the last **n** or **b** output (whichever was later).

b (-) gforth-1.0 “b”

Display lines before the current location, or before the last **n** or **b** output (whichever was later). Enter the external editor at the place of the latest error, **locate**, **n** or **b**.

g (-) gforth-0.7 “g”

Enter the editor at the current location, or at the start of the last **n** or **b** output (whichever was later).

You can control how many lines **l**, **n** and **b** show by changing the values:

before-locate (- *u*) gforth-1.0 “before-locate”

number of lines shown before current location (default 3).

after-locate (- *u*) gforth-1.0 “after-locate”

number of lines shown after current location (default 12). *filename*-number of view (obtained by *name*>view) see *filename*#>str line number in file of view (obtained by *name*>view)

Finally, you can directly go to the source code of a word in the editor with

edit ("*name*" -) gforth-1.0 “edit”

Enter the editor at the location of "*name*"

6.25.2 Locating documentation

help ("*rest-of-line*" -) gforth-1.0 “help”

If no name is given, show basic help. If a documentation node name is given followed by ":", show the start of the node. If the name of a word is given, show the documentation of the word if it exists, or its source code if not. Use **g** to enter the editor at the point shown by **help**. open command addr *u*, and read in the result

Help sets the current location, so you can use **n** and **b** to show more of the text, or **g** to visit the documentation in an editor (see Section 6.25.1 [Locating source code definitions], page 197).

6.25.3 Locating uses of a word

where ("*name*" -) gforth-1.0 “where”

Show all places where *name* is used (text-interpreted). You can then use **ww**, **nw** or **bw** to inspect specific occurrences more closely.

ww (*u* -) gforth-1.0 “ww”

The next **l** or **g** shows the **where** result with index *u*

nw (-) gforth-1.0 “nw”

The next **l** or **g** shows the next **where** result; if the current one is the last one, after **nw** there is no current one. If there is no current one, after **nw** the first one is the current one.

bw (-) gforth-1.0 “bw”

The next **l** or **g** shows the previous **where** result; if the current one is the first one, after **bw** there is no current one. If there is no current one, after **bw** the last one is the current one.

gg (-) gforth-1.0 “gg”

The next **ww**, **nw**, **bw**, **bb**, **nb**, **lb** (but not **locate**, **edit**, **l** or **g**) puts its result in the editor (like **g**). Use **gg gg** to make this permanent rather than one-shot.

ll (-) gforth-1.0 “ll”

The next **ww**, **nw**, **bw**, **bb**, **nb**, **lb** (but not **locate**, **edit**, **l** or **g**) displays in the Forth system (like **l**). Use **ll ll** to make this permanent rather than one-shot.

whereg ("name" -) gforth-1.0 “whereg”

Like **where**, but puts the output in the editor. In Emacs, you can then use the compilation-mode commands (see Section “Compilation Mode” in *GNU Emacs Manual*) to inspect specific occurrences more closely.

6.25.4 Locating exception source

tt (*u* -) gforth-1.0 “tt”

nt (-) gforth-1.0 “nt”

bt (-) gforth-1.0 “bt”

like **type**, but type a space for each tab type the part of the string that fits in *uwidth*; *uwidth1* is the remaining width; replaces tabs with spaces

6.25.5 Examining compiled code

And finally, **see** and friends show compiled code. Some of the things in the source code are not present in the compiled code (e.g., formatting and comments), but this is useful to see what threaded code or native code is produced by macros and Gforth’s optimization features.

see ("<spaces>name" -) tools “see”

Locate *name* using the current search order. Display the definition of *name*. Since this is achieved by decompiling the definition, the formatting is mechanised and some source information (comments, interpreted sequences within definitions etc.) is lost. add further cells to backtrace stack for non-debugging engine exceptions print a backtrace for the return stack *addr1..addr2* backtrace for interactive use

xt-see (*xt* -) gforth-0.2 “xt-see”

Decompile the definition represented by *xt*.

simple-see ("name" -) gforth-0.6 “simple-see”

Decompile the colon definition *name*, showing a line for each cell, and try to guess a meaning for the cell, and show that.

xt-simple-see (*xt* -) gforth-1.0 “xt-simple-see”

Decompile the colon definition *xt* like **simple-see**

simple-see-range (*addr1 addr2* -) gforth-0.6 “simple-see-range”

Decompile code in [*addr1,addr2*) like **simple-see**

see-code ("name" -) gforth-0.7 “see-code”

Like **simple-see**, but also shows the dynamic native code for the inlined primitives. For static superinstructions, it shows the primitive sequence instead of the first primitive (the other primitives of the superinstruction are shown, too). For primitives for which native code is generated, it shows the number of stack items in registers at the beginning and at

the end (e.g., 1->1 means 1 stack item is in a register at the start and at the end). For each primitive or superinstruction with native code, the inline arguments and component primitives are shown first, then the native code.

xt-see-code (*xt* -) gforth-1.0 “xt-see-code”

Decompile the colon definition *xt* like **see-code**.

see-code-range (*addr1 addr2* -) gforth-0.7 “see-code-range”

Decompile code in [*addr1,addr2*) like **see-code**.

As an example, consider:

```
: foo x f@ fsin drop over ;
```

This is not particularly useful, but it demonstrates the various code generation differences. Compiling this on **gforth-fast** on AMD64 and then using **see-code** *foo* outputs:

```
$7FD0CEE8C510 lit f@      1->1
$7FD0CEE8C518 x
$7FD0CEE8C520 f@
7FD0CEB51697:  movsd   [r12],xmm15
7FD0CEB5169D:  mov     rax,$00[r13]
7FD0CEB516A1:  sub     r12,$08
7FD0CEB516A5:  add     r13,$18
7FD0CEB516A9:  movsd   xmm15,[rax]
7FD0CEB516AE:  mov     rcx,-$08[r13]
7FD0CEB516B2:  jmp     ecx
$7FD0CEE8C528 fsin
$7FD0CEE8C530 drop      1->0
7FD0CEB516B4:  add     r13,$08
$7FD0CEE8C538 over      0->1
7FD0CEB516B8:  mov     r8,$10[r15]
7FD0CEB516BC:  add     r13,$08
$7FD0CEE8C540 ;s        1->1
7FD0CEB516C0:  mov     r10,[rbx]
7FD0CEB516C3:  add     rbx,$08
7FD0CEB516C7:  lea     r13,$08[r10]
7FD0CEB516CB:  mov     rcx,-$08[r13]
7FD0CEB516CF:  jmp     ecx
```

First, you see a threaded-code cell for a static superinstruction with the components **lit f@**, starting and ending with one data stack item in a register (1->1); this is followed by the cell for the argument **x** of **lit**, and the cell for the **f@** component of the superinstruction; the latter cell is not used, but is there for Gforth-internal reasons.

Next, the dynamically generated native code for the superinstruction **lit f@** is shown; note that this native code is not mixed with the threaded code in memory, as you can see by comparing the addresses.

If you want to understand the native code shown here: the threaded-code instruction pointer is in **r13**, the data stack pointer in **r15**; the first data stack register is **r8** (i.e., the top of stack resides there if there is one data stack item in a register); the return stack pointer is in **rbx**, the FP stack pointer in **r12**, and the top of the floating-point stack in

xmm15. Note that the register assignments vary between engines, so you may see a different register assignment for this code.

The dynamic native code for **lit f@** ends with a dispatch jump (aka NEXT), because the code for the next word **fsin** in the definition is not dynamically generated.

Next, you see the threaded-code cell for **fsin**. There is no dynamically-generated native code for this word, and **see-code** does not show the static native code for it (you can look at it with **see fsin**). Like all words with static native code in **gforth-fast**, the effect on the data stack representation is **1->1** (for **gforth**, **0->0**), but this is not shown.

Next, you see the threaded-code cell for **drop**; the native-code variant used here starts with one data stack item in registers, and ends with zero data stack items in registers (**1->0**). This is followed by the native code for this variant of **drop**. There is no NEXT here, because the native code falls through to the code for the next word.

Next, you see the threaded-code cell for **over** followed by the dynamically-generated native code in the **0->1** variant.

Finally, you see the threaded and native code for **;****s** (the primitive compiled for **;** in **foo**). **;****s** performs control flow (it returns), so it has to end with a NEXT.

6.25.6 Examining data and code

The following words inspect the stack non-destructively:

... (*x1 .. xn - x1 .. xn*) **gforth-1.0** “...”

.s (-) tools “dot-s”

Display the number of items on the data stack, followed by a list of the items (but not more than specified by **maxdepth-.s**; TOS is the right-most item.

f.s (-) **gforth-0.2** “f-dot-s”

Display the number of items on the floating-point stack, followed by a list of the items (but not more than specified by **maxdepth-.s**; TOS is the right-most item.

maxdepth-.s (- *addr*) **gforth-0.2** “maxdepth-dot-s”

A variable containing 9 by default. **.s** and **f.s** display at most that many stack items.

There is a word **.r** but it does *not* display the return stack! It is used for formatted numeric output (see Section 6.20.1 [Simple numeric output], page 148).

depth (- *+n*) **core** “depth”

+n is the number of values that were on the data stack before *+n* itself was placed on the stack.

fdepth (- *+n*) floating “f-depth”

+n is the current number of (floating-point) values on the floating-point stack.

clearstack (... -) **gforth-0.2** “clear-stack”

remove and discard all/any items from the data stack.

clearstacks (... -) **gforth-0.7** “clear-stacks”

empty data and FP stack

The following words inspect memory.

? (*a-addr* -) tools “question”

Display the contents of address *a-addr* in the current number base.

dump (*addr u* –) tools “dump”

Display *u* lines of memory starting at address *addr*. Each line displays the contents of 16 bytes. When Gforth is running under an operating system you may get **Invalid memory address** errors if you attempt to access arbitrary locations.

6.25.7 Forgetting words

Forth allows you to forget words (and everything that was allotted in the dictionary after them) in a LIFO manner.

marker ("<spaces> *name*" –) core-ext “marker”

Create a definition, *name* (called a *mark*) whose execution semantics are to remove itself and everything defined after it.

The most common use of this feature is during program development: when you change a source file, forget all the words it defined and load it again (since you also forget everything defined after the source file was loaded, you have to reload that, too). Note that effects like storing to variables and destroyed system words are not undone when you forget words. With a system like Gforth, that is fast enough at starting up and compiling, I find it more convenient to exit and restart Gforth, as this gives me a clean slate.

Here’s an example of using **marker** at the start of a source file that you are debugging; it ensures that you only ever have one copy of the file’s definitions compiled at any time:

```
[IFDEF] my-code
    my-code
[ENDIF]

marker my-code
init-included-files

\ .. definitions start here
\ .
\ .
\ end
```

6.25.8 Debugging

Languages with a slow edit/compile/link/test development loop tend to require sophisticated tracing/stepping debuggers to facilitate debugging.

A much better (faster) way in fast-compiling languages is to add printing code at well-selected places, let the program run, look at the output, see where things went wrong, add more printing code, etc., until the bug is found.

The simple debugging aids provided in **debugs.fs** are meant to support this style of debugging.

The word **~~** prints debugging information (by default the source location and the stack contents). It is easy to insert. If you use Emacs it is also easy to remove (**C-x ~** in the Emacs Forth mode to query-replace them with nothing). The deferred words **printdebugdata** and **.debugline** control the output of **~~**. The default source location output format works well

with Emacs' compilation mode, so you can step through the program at the source level using `C-x` ' (the advantage over a stepping debugger is that you can step in any direction and you know where the crash has happened or where the strange data has occurred).

`~~ (-) gforth-0.2 "tilde-tilde"`

Prints the source code location of the `~~` and the stack contents with `.debugline`. Value: Coverage check on/off turn coverage off temporarily end of temporary turned off coverage

`printdebugdata (-) gforth-0.2 "print-debug-data"`

`.debugline (nfile nline -) gforth-0.6 "print-debug-line"`

Print the source code location indicated by `nfile nline`, and additional debugging information; the default `.debugline` prints the additional information with `printdebugdata`.

`debug-fid (- file-id) gforth-1.0 "File-id"`

debugging words for output. By default it is the process's `stderr`.

`~~` (and assertions) will usually print the wrong file name if a marker is executed in the same file after their occurrence. They will print `*somewhere*` as file name if a marker is executed in the same file before their occurrence.

`once (-) gforth-1.0 "once"`

do the following up to THEN only once

`~~bt (-) gforth-1.0 "~~bt"`

print stackdump and backtrace

`~~1bt (-) gforth-1.0 "~~1bt"`

print stackdump and backtrace once

`??? (-) gforth-0.2 "???"`

Open a debugging shell

`WTF?? (-) gforth-1.0 "WTF??"`

Open a debugging shell with backtrace and stack dump

`!!FIXME!! (-) gforth-1.0 "!!FIXME!!"`

word that should never be reached prints a warning if the string is already present in the wordlist

`replace-word (xt1 xt2 -) gforth-1.0 "replace-word"`

make xt2 do xt1, both need to be colon definitions

`~~Variable ("name" -) gforth-1.0 "~~Variable"`

Variable that will be watched on every access

`~~Value (n "name" -) gforth-1.0 "~~Value"`

Value that will be watched on every access print source position and stack on every source line start

`+ltrace (-) gforth-1.0 "+ltrace"`

turn on line tracing

`-ltrace (-) gforth-1.0 "-ltrace"`

turn off line tracing

`view ("name" -) gforth-1.0 "view"`

`locate ("name" -) gforth-1.0 "locate"`

Show the source code of the word *name* and set the current location there.

```
edit ( "name" - ) gforth-1.0 "edit"
```

Enter the editor at the location of "name"

```
#loc ( nline nchar "file" - ) gforth-1.0 "#loc"
```

set next word's location to *nline nchar* in "file"

6.25.9 Assertions

It is a good idea to make your programs self-checking, especially if you make an assumption that may become invalid during maintenance (for example, that a certain field of a data structure is never zero). Gforth supports *assertions* for this purpose. They are used like this:

```
assert( flag )
```

The code between **assert**(and) should compute a flag, that should be true if everything is alright and false otherwise. It should not change anything else on the stack. The overall stack effect of the assertion is (--). E.g.

```
assert( 1 1 + 2 = ) \ what we learn in school
assert( dup 0<> ) \ assert that the top of stack is not zero
assert( false ) \ this code should not be reached
```

The need for assertions is different at different times. During debugging, we want more checking, in production we sometimes care more for speed. Therefore, assertions can be turned off, i.e., the assertion becomes a comment. Depending on the importance of an assertion and the time it takes to check it, you may want to turn off some assertions and keep others turned on. Gforth provides several levels of assertions for this purpose:

```
assert0( ( - ) gforth-0.2 "assert-zero"
```

Important assertions that should always be turned on.

```
assert1( ( - ) gforth-0.2 "assert-one"
```

Normal assertions; turned on by default.

```
assert2( ( - ) gforth-0.2 "assert-two"
```

Debugging assertions.

```
assert3( ( - ) gforth-0.2 "assert-three"
```

Slow assertions that you may not want to turn on in normal debugging; you would turn them on mainly for thorough checking.

```
assert( ( - ) gforth-0.2 "assert("
```

Equivalent to **assert1**(set deferred word xt2 to xt1 and execute xt3 restore afterwards

```
) ( - ) gforth-0.2 "close-paren"
```

End an assertion. Generic end, can be used for other similar purposes

The variable **assert-level** specifies the highest assertions that are turned on. I.e., at the default **assert-level** of one, **assert0**(and **assert1**(assertions perform checking, while **assert2**(and **assert3**(assertions are treated as comments.

The value of **assert-level** is evaluated at compile-time, not at run-time. Therefore you cannot turn assertions on or off at run-time; you have to set the **assert-level** appropriately

before compiling a piece of code. You can compile different pieces of code at different `assert-levels` (e.g., a trusted library at level 1 and newly-written code at level 3).

```
assert-level ( - a-addr ) gforth-0.2 "assert-level"
```

All assertions above this level are turned off.

If an assertion fails, a message compatible with Emacs' compilation mode is produced and the execution is aborted (currently with `ABORT`". If there is interest, we will introduce a special throw code. But if you intend to `catch` a specific condition, using `throw` is probably more appropriate than an assertion).

Assertions (and `~~`) will usually print the wrong file name if a marker is executed in the same file after their occurrence. They will print `'*somewhere*'` as file name if a marker is executed in the same file before their occurrence.

Definitions in Standard Forth for these assertion words are provided in `compat/assert.fs`.

6.25.10 Singlestep Debugger

The singlestep debugger works only with the engine `gforth-itc`.

When you create a new word there's often the need to check whether it behaves correctly or not. You can do this by typing `dbg badword`. A debug session might look like this:

```
: badword 0 DO i . LOOP ; ok
2 dbg badword
: badword
Scanning code...

Nesting debugger ready!

400D4738 8049BC4 0          -> [ 2 ] 00002 00000
400D4740 8049F68 DO        -> [ 0 ]
400D4744 804A0C8 i          -> [ 1 ] 00000
400D4748 400C5E60 .        -> 0 [ 0 ]
400D474C 8049D0C LOOP      -> [ 0 ]
400D4744 804A0C8 i          -> [ 1 ] 00001
400D4748 400C5E60 .        -> 1 [ 0 ]
400D474C 8049D0C LOOP      -> [ 0 ]
400D4758 804B384 ;         -> ok
```

Each line displayed is one step. You always have to hit return to execute the next word that is displayed. If you don't want to execute the next word in a whole, you have to type `n` for `nest`. Here is an overview what keys are available:

<code>RET</code>	Next; Execute the next word.
<code>n</code>	Nest; Single step through next word.
<code>u</code>	Unnest; Stop debugging and execute rest of word. If we got to this word with nest, continue debugging with the calling word.
<code>d</code>	Done; Stop debugging and execute rest.
<code>s</code>	Stop; Abort immediately.

Debugging large application with this mechanism is very difficult, because you have to nest very deeply into the program before the interesting part begins. This takes a lot of time.

To do it more directly put a **BREAK:** command into your source code. When program execution reaches **BREAK:** the single step debugger is invoked and you have all the features described above.

If you have more than one part to debug it is useful to know where the program has stopped at the moment. You can do this by the **BREAK "string"** command. This behaves like **BREAK:** except that string is typed out when the “breakpoint” is reached.

```
dbg ( "name" - ) gforth-0.2 "dbg"
```

```
break: ( - ) gforth-0.4 "break:"
```

```
break" ( 'ccc' - ) gforth-0.4 "break"
```

6.25.11 Code Coverage and Execution Frequency

If you run extensive tests on your code, you often want to figure out if the tests exercise all parts of the code. This is called (test) coverage. The file **coverage.fs** contains tools for measuring the coverage as well as execution frequency.

Code coverage inserts counting code in every basic block (straight-line code sequence) loaded after **coverage.fs**. Each time that code is run, it increments the counter for that basic block. Later you can show the source file with the counts inserted in these basic blocks.

```
.coverage ( - ) gforth-experimental ".coverage"
```

Show code with execution frequencies.

```
annotate-cov ( - ) gforth-experimental "annotate-cov"
```

For every file with coverage information, produce a **.cov** file that has the execution frequencies inserted. We recommend to use **bw-cover** first (with the default **color-cover** you get escape sequences in the files).

```
cov% ( - ) gforth-experimental "cov%"
```

Print the percentage of basic blocks loaded after **coverage.fs** that are executed at least once.

```
.cover-raw ( - ) gforth-experimental ".cover-raw"
```

Print raw execution counts.

By default, the counts are shown in colour (using ANSI escape sequences), but you can use **bw-cover** to show them in parenthesized form without escape sequences.

```
bw-cover ( - ) gforth-1.0 "bw-cover"
```

Print execution counts in parentheses (source-code compatible). Remove coverage comment.

```
color-cover ( - ) gforth-1.0 "color-cover"
```

Print execution counts in colours (default).

You can save and reload the coverage counters in binary format, to aggregate coverage counters across several test runs.

```
save-cov ( - ) gforth-experimental "save-cov"
```

Save coverage counters.

load-cov (-) gforth-experimental “load-cov”

Load coverage counters. obtains library handle obtains symbol address allocates and initializes proc stub stub format: linked list in library address of proc ptr to OS name of symbol as counted string threaded code for invocation Creates a named proc stub loads library "file" and creates a proc defining word "name" library format: linked list of libraries library handle linked list of library's procs OS name of library as counted string link between callbacks

cov+ (-) gforth-experimental “cov+”

Add a coverage tag here.

6.26 Multitasker

Gforth offers two multitaskers: a traditional, cooperative round-robin multitasker, and a pthread-based multitasker which allows to run several threads concurrently on multi-core machines. The pthread-based is now marked as experimental feature, as standardization of Forth multitaskers will likely change the names of words without changing their semantics.

6.26.1 Pthreads

Tasks can be created with **newtask** or **newtask4** with a given amount of stack space (either all the same or each stack's size specified); these tasks need to be **activated** or send an *xt* through **initiate**. Tasks can **stop** themselves when they are done or wait for new instructions.

newtask (*stacksize* - *task*) gforth-experimental “newtask”

creates a task, uses *stacksize* for stack, *rstack*, *fpstack*, *locals*

task (*stacksize* "name" -) gforth-experimental “task”

create a named task with *stacksize* *stacksize*

execute-task (*xt* - *task*) gforth-experimental “execute-task”

create a new task *task* and initiate it with *xt*

stacksize (- *n*) gforth-experimental “stacksize”

stacksize for data stack

newtask4 (*dsize* *rsize* *fsize* *lsize* - *task*) gforth-experimental “newtask4”

creates a task, each stack individually sized

stacksize4 (- *dsize* *fsize* *rsize* *lsize*) gforth-experimental “stacksize4”

This gives you the system stack sizes

activate (*task* -) gforth-experimental “activate”

activates a task. The remaining part of the word calling **activate** will be executed in the context of the task.

pass (*x1* .. *xn* *n* *task* -) gforth-experimental “pass”

activates task, and passes *n* parameters from the data stack

initiate (*xt* *task* -) gforth-experimental “initiate”

pass an *xt* to a task (VFX compatible)

pause (*-*) gforth-experimental “pause”

voluntarily switch to the next waiting task (**pause** is the traditional cooperative task switcher; in the pthread multitasker, you don’t need **pause** for cooperation, but you still can use it e.g. when you have to resort to polling for some reason). This also checks for events in the queue.

restart (*task -*) gforth-experimental “restart”

Wake a task

halt (*task -*) gforth-experimental “halt”

Stop a task

stop (*-*) gforth-experimental “stop”

stops the current task, and waits for events (which may restart it)

stop-ns (*timeout -*) gforth-experimental “stop-ns”

Stop with timeout (in nanoseconds), better replacement for ms

A cooperative multitasker can ensure that there is no other task interacting between two invocations of **pause**. Pthreads however are really concurrent tasks (at least on a multi-core CPU), and therefore, several techniques to avoid conflicts when accessing the same resources.

6.26.1.1 Special User Variables

Aside from the user variables that are already defined in the kernel, tasks may want to have user values and user defers, obtain the offset of a user variable, or the address of those related to another task to initialize that task’s user area.

UValue (*"name" -*) gforth-1.0 “UValue”

UDefer (*"name" -*) gforth-experimental “UDefer”

Define a per-thread deferred word wait for all spawned tasks to complete wait for a worker to become free, and spawn *xt* there wait for a worker to become free, and spawn *xt* there, with one argument wait for a worker to become free, and spawn *xt* there, with two arguments

user' (*'user' - n*) gforth-experimental “user”

USER' computes the task offset of a user variable

's (*user task - user'*) gforth-experimental “'s”

get the tasks’s address of our user variable

6.26.1.2 Semaphores

Semaphores can only be acquired by one thread, all other threads have to wait until the semaphore is released.

semaphore (*"name" -*) gforth-experimental “semaphore”

create a named semaphore *"name"* \ "name"-execution: (*- semaphore*)

lock (*semaphore -*) gforth-experimental “lock”

lock the semaphore

unlock (*semaphore -*) gforth-experimental “unlock”

unlock the semaphore

The other approach to prevent concurrent access is the critical section. Here, we implement a critical section with a semaphore, so you have to specify the semaphore which is used for the critical section. Only those critical sections which use the same semaphore are mutually exclusive.

critical-section (*xt semaphore* –) gforth-experimental “critical-section”

implement a critical section that will unlock the semaphore even in case there’s an exception within.

6.26.1.3 Atomic operations

Atomic operations can be used to synchronize tasks without using slow OS primitives.

!@ (*u1 a-addr* – *u2*) gforth-experimental “store-fetch”

load *u2* from *a-addr*, and store *u1* there, as atomic operation

+!@ (*u1 a-addr* – *u2*) gforth-experimental “add-store-fetch”

load *u2* from *a-addr*, and increment this location by *u1*, as atomic operation

?!@ (*unew uold a-addr* – *uprev*) gforth-experimental “question-store-fetch”

load *uprev* from *a-addr*, compare it to *uold*, and if equal, store *unew* there, as atomic operation

barrier (–) gforth-experimental “barrier”

Insert a full memory barrier

6.26.1.4 Message Queues

Gforth implements executable message queues for event driven programs: you send instructions to other tasks, enclosed in **<event** and **event>**; the entire event sequence is executed atomically. You can pass integers, floats, and strings (only the addresses, so treat the string as read-only after you have send it to another task). The messages you send are defined with **event: name**, which, when invoked, will add the code for its execution to the message queue, and when recieved, will execute the code following. The message queue is queried when you **stop** a task, or when you check for events with **?events**. You can define a maximum of 256 different events.

<event (–) gforth-experimental “<event”

starts a sequence of events.

event> (*task* –) gforth-experimental “event>”

ends a sequence and sends it to the mentioned task

event: ("*name*" –) gforth-experimental “event:”

defines an event and the reaction to it as Forth code. If **name** is invoked, the event gets assembled to the event buffer. If the event **name** is received, the Forth definition that follows the event declaration is executed.

?events (–) gforth-experimental “?events”

checks for events and executes them

event-loop (–) gforth-experimental “event-loop”

Tasks that are controlled by sending events to them should go into an event-loop

`elit, (x -) gforth-experimental "elit,"`

sends a literal

`e$, (addr u -) gforth-experimental "e$,"`

sends a string (actually only the address and the count, because it's shared memory)

`eflit, (x -) gforth-experimental "eflit,"`

sends a float

The naming conventions for events is `:>name`.

6.26.1.5 Conditions

The pthreads library also provides conditional variables, which allow to wait for a condition. Using the message queue is generally preferred.

`cond ("name" -) gforth-experimental "cond"`

create a named condition

`pthread_cond_signal (cond - r) gforth-experimental "pthread_cond_signal"`

`pthread_cond_broadcast (cond - r) gforth-experimental "pthread_cond_broadcast"`

`pthread_cond_wait (cond mutex - r) gforth-experimental "pthread_cond_wait"`

`pthread_cond_timedwait (cond mutex abstime - r) gforth-experimental "pthread_cond_timedwait"` ■

6.27 C Interface

Gforth's C interface works by compiling a wrapper library that contains C functions which take parameters from the Forth stacks and calls the C functions. This wrapper library is compiled by the C compiler. Compilation results are cached, so that Gforth only needs to rerun the C compilation if the wrapper library has to change. This build process is automatic, and done at the end of a interface declaration. Gforth uses libtool and GCC for that process.

The C interface is now mostly complete, callbacks have been added, but for structs, we use Forth2012 structs, which don't have independent scopes. The offsets of those structs are extracted from header files with a SWIG plugin.

6.27.1 Calling C functions

Once a C function is declared (see see Section 6.27.2 [Declaring C Functions], page 211), you can call it as follows: You push the arguments on the stack(s), and then call the word for the C function. The arguments have to be pushed in the same order as the arguments appear in the C documentation (i.e., the first argument is deepest on the stack). Integer and pointer arguments have to be pushed on the data stack, floating-point arguments on the FP stack; these arguments are consumed by the called C function.

On returning from the C function, the return value, if any, resides on the appropriate stack: an integer return value is pushed on the data stack, an FP return value on the FP stack, and a void return value results in not pushing anything. Note that most C functions have a return value, even if that is often not used in C; in Forth, you have to **drop** this return value explicitly if you do not use it.

The C interface automatically converts between the C type and the Forth type as necessary, on a best-effort basis (in some cases, there may be some loss).

As an example, consider the POSIX function `lseek()`:

```
off_t lseek(int fd, off_t offset, int whence);
```

This function takes three integer arguments, and returns an integer argument, so a Forth call for setting the current file offset to the start of the file could look like this:

```
fd @ 0 SEEK_SET lseek -1 = if
... \ error handling
then
```

You might be worried that an `off_t` does not fit into a cell, so you could not pass larger offsets to `lseek`, and might get only a part of the return values. In that case, in your declaration of the function (see Section 6.27.2 [Declaring C Functions], page 211) you should declare it to use double-cells for the `off_t` argument and return value, and maybe give the resulting Forth word a different name, like `dlseek`; the result could be called like this:

```
fd @ 0. SEEK_SET dlseek -1. d= if
... \ error handling
then
```

Passing and returning structs or unions is currently not supported by our interface²⁷.

Calling functions with a variable number of arguments (*variadic* functions, e.g., `printf()`) is only supported by having you declare one function-calling word for each argument pattern, and calling the appropriate word for the desired pattern.

6.27.2 Declaring C Functions

Before you can call `lseek` or `dlseek`, you have to declare it. The declaration consists of two parts:

The C part

is the C declaration of the function, or more typically and portably, a C-style `#include` of a file that contains the declaration of the C function.

The Forth part

declares the Forth types of the parameters and the Forth word name corresponding to the C function.

For the words `lseek` and `dlseek` mentioned earlier, the declarations are:

```
\c #define _FILE_OFFSET_BITS 64
\c #include <sys/types.h>
\c #include <unistd.h>
c-function lseek lseek n n n -- n
c-function dlseek lseek n d n -- d
```

The C part of the declarations is prefixed by `\c`, and the rest of the line is ordinary C code. You can use as many lines of C declarations as you like, and they are visible for all further function declarations.

²⁷ If you know the calling convention of your C compiler, you usually can call such functions in some way, but that way is usually not portable between platforms, and sometimes not even between C compilers.

The Forth part declares each interface word with `c-function`, followed by the Forth name of the word, the C name of the called function, and the stack effect of the word. The stack effect contains an arbitrary number of types of parameters, then `--`, and then exactly one type for the return value. The possible types are:

<code>n</code>	single-cell integer
<code>a</code>	address (single-cell)
<code>d</code>	double-cell integer
<code>r</code>	floating-point value
<code>func</code>	C function pointer
<code>void</code>	no value (used as return type for void functions)

To deal with variadic C functions, you can declare one Forth word for every pattern you want to use, e.g.:

```
\c #include <stdio.h>
c-function printf-nr printf a n r -- n
c-function printf-rn printf a r n -- n
```

Note that with C functions declared as variadic (or if you don't provide a prototype), the C interface has no C type to convert to, so no automatic conversion happens, which may lead to portability problems in some cases. You can add the C type cast in curly braces after the Forth type. This also allows to pass e.g. structs to C functions, which in Forth cannot live on the stack.

```
c-function printfll printf a n{(long long)} -- n
c-function pass-struct pass_struct a{*(struct foo *)} -- n
```

This typecasting is not available to return values, as C does not allow typecasts for lvalues.

```
\c ( "rest-of-line" - ) gforth-0.7 "backslash-c"
```

One line of C declarations for the C interface

```
c-function ( "forth-name" "c-name" "{type}" "—" "type" - ) gforth-0.7 "c-function"
```

Define a Forth word *forth-name*. *Forth-name* has the specified stack effect and calls the C function *c-name*.

```
c-value ( "forth-name" "c-name" "—" "type" - ) gforth-1.0 "c-value"
```

Define a Forth word *forth-name*. *Forth-name* has the specified stack effect and gives the C value of *c-name*.

```
c-variable ( "forth-name" "c-name" - ) gforth-1.0 "c-variable"
```

Define a Forth word *forth-name*. *Forth-name* returns the address of *c-name*.

In order to work, this C interface invokes GCC at run-time and uses dynamic linking. If these features are not available, there are other, less convenient and less portable C interfaces in `lib.fs` and `oldlib.fs`. These interfaces are mostly undocumented and mostly incompatible with each other and with the documented C interface; you can find some examples for the `lib.fs` interface in `lib.fs`.

6.27.3 Calling C function pointers from Forth

If you come across a C function pointer (e.g., in some C-constructed structure) and want to call it from your Forth program, you could use the structures as described above by defining a macro. Or you use `c-funptr`.

`c-funptr` ("*forth-name*" <{>"*c-typecast*"<}> "{*type*}" "—" "*type*" -) gforth-1.0 "c-funptr"

Define a Forth word *forth-name*. *Forth-name* has the specified stack effect plus the called pointer on top of stack, i.e. ({*type*} *ptr* -- *type*) and calls the C function pointer *ptr* using the typecast or struct access *c-typecast*.

Let us assume that there is a C function pointer type `func1` defined in some header file `func1.h`, and you know that these functions take one integer argument and return an integer result; and you want to call functions through such pointers. Just define

```
\c #include <func1.h>
c-funptr call-func1 {((func1)ptr)} n -- n
```

and then you can call a function pointed to by, say `func1a` as follows:

```
-5 func1a call-func1 .
```

The Forth word `call-func1` is similar to `execute`, except that it takes a C `func1` pointer instead of a Forth execution token, and it is specific to `func1` pointers. For each type of function pointer you want to call from Forth, you have to define a separate calling word.

6.27.4 Defining library interfaces

You can give a name to a bunch of C function declarations (a library interface), as follows:

```
c-library lseek-lib
\c #define _FILE_OFFSET_BITS 64
...
end-c-library
```

The effect of giving such a name to the interface is that the names of the generated files will contain that name, and when you use the interface a second time, it will use the existing files instead of generating and compiling them again, saving you time. The generated file contains a 128 bit hash (not cryptographically safe, but good enough for that purpose) of the source code, so changing the declarations will cause a new compilation. Normally these files are cached in `$HOME/.gforth/architecture/libcc-named`, so if you experience problems or have other reasons to force a recompilation, you can delete the files there.

Note that you should use `c-library` before everything else having anything to do with that library, as it resets some setup stuff. The idea is that the typical use is to put each `c-library...end-c-library` unit in its own file, and to be able to include these files in any order. All other words dealing with the C interface are hidden in the vocabulary `c-lib`, which is put on top of the search stack by `c-library` and removed by `end-c-library`.

Note that the library name is not allocated in the dictionary and therefore does not shadow dictionary names. It is used in the file system, so you have to use naming conventions appropriate for file systems. The name is also used as part of the C symbols, but characters outside the legal C symbol names are replaced with underscores. Also, you shall not call a function you declare after `c-library` before you perform `end-c-library`.

A major benefit of these named library interfaces is that, once they are generated, the tools used to generate them (in particular, the C compiler and `libtool`) are no longer needed,

so the interface can be used even on machines that do not have the tools installed. The build system of Gforth can even cross-compile these libraries, so that the libraries are available for platforms on which build tools aren't installed.

```
c-library-name ( c-addr u - ) gforth-0.7 “c-library-name”
```

Start a C library interface with name *c-addr u*. load lib if the OS needs it

```
c-library ( "name" - ) gforth-0.7 “c-library”
```

Parsing version of **c-library-name**

```
end-c-library ( - ) gforth-0.7 “end-c-library”
```

Finish and (if necessary) build the latest C library interface.

6.27.5 Declaring OS-level libraries

For calling some C functions, you need to link with a specific OS-level library that contains that function. E.g., the **sin** function requires linking a special library by using the command line switch **-lm**. In our C interface you do the equivalent thing by calling **add-lib** as follows:

```
clear-libs
s" m" add-lib
\c #include <math.h>
c-function sin sin r -- r
```

First, you clear any libraries that may have been declared earlier (you don't need them for **sin**); then you add the **m** library (actually **libm.so** or **somesuch**) to the currently declared libraries; you can add as many as you need. Finally you declare the function as shown above. Typically you will use the same set of library declarations for many function declarations; you need to write only one set for that, right at the beginning.

Note that you must not call **clear-libs** inside **c-library...end-c-library**; however, **c-library** performs the function of **clear-libs**, so **clear-libs** is not necessary, and you usually want to put **add-lib** calls inside **c-library...end-c-library**.

```
clear-libs ( - ) gforth-0.7 “clear-libs”
```

Clear the list of libs

```
add-lib ( c-addr u - ) gforth-0.7 “add-lib”
```

Add library *libstring* to the list of libraries, where *string* is represented by *c-addr u*.

```
add-libpath ( c-addr u - ) gforth-0.7 “add-libpath”
```

Add path *string* to the list of library search paths, where *string* is represented by *c-addr u*.

```
add-incdir ( c-addr u - ) gforth-1.0 “add-incdir”
```

Add path *c-addr u* to the list of include search paths

```
add-cflags ( c-addr u - ) gforth-1.0 “add-cflags”
```

add any kind of cflags to compilation

```
add-ldflags ( c-addr u - ) gforth-1.0 “add-ldflags”
```

add flag to linker

6.27.6 Callbacks

In some cases you have to pass a function pointer to a C function, i.e., the library wants to call back to your application (and the pointed-to function is called a callback function). You can pass the address of an existing C function (that you get with `lib-sym`, see Section 6.27.8 [Low-Level C Interface Words], page 215), but if there is no appropriate C function, you probably want to define the function as a Forth word. Then you need to generate a callback as described below:

You can generate C callbacks from Forth code with `c-callback`.

`c-callback ("forth-name" "{type}" "—" "type" -)` gforth-1.0 “c-callback”

Define a callback instantiator with the given signature. The callback instantiator *forth-name* (`xt -- addr`) takes an *xt*, and returns the *address* of the C function handling that callback.

This precompiles a number of callback functions (up to the value `callback#`). The prototype of the C function is deduced from its Forth signature. If this is not sufficient, you can add types in curly braces after the Forth type.

```
c-callback vector4double: f f f f -- void
c-callback vector4single: f{float} f{float} f{float} f{float} -- void
```

6.27.7 How the C interface works

The documented C interface works by generating a C code out of the declarations.

In particular, for every Forth word declared with `c-function`, it generates a wrapper function in C that takes the Forth data from the Forth stacks, and calls the target C function with these data as arguments. The C compiler then performs an implicit conversion between the Forth type from the stack, and the C type for the parameter, which is given by the C function prototype. After the C function returns, the return value is likewise implicitly converted to a Forth type and written back on the stack.

The `\c` lines are literally included in the C code (but without the `\c`), and provide the necessary declarations so that the C compiler knows the C types and has enough information to perform the conversion.

These wrapper functions are eventually compiled and dynamically linked into Gforth, and then they can be called.

The libraries added with `add-lib` are used in the compile command line to specify dependent libraries with `-llib`, causing these libraries to be dynamically linked when the wrapper function is linked.

6.27.8 Low-Level C Interface Words

`open-lib (c-addr1 u1 - u2)` gforth-0.4 “open-lib”

`lib-sym (c-addr1 u1 u2 - u3)` gforth-0.4 “lib-sym”

`lib-error (- c-addr u)` gforth-0.7 “lib-error”

Error message for last failed `open-lib` or `lib-sym`.

`call-c (... w - ...)` gforth-0.2 “call-c”

Call the C function pointed to by *w*. The C function has to access the stack itself. The stack pointers are exported into a `ptrpair` structure passed to the C function, and returned in that form.

6.27.9 Automated interface generation using SWIG

SWIG, the Simple Wrapper Interface Generator, is used to create C interfaces for a lot of programming languages. The SWIG version extended with a Forth module can be found on github (<https://github.com/GeraldWodni/swig>).

6.27.9.1 Basic operation

C-headers are parsed and converted to Forth-Sourcecode which uses the previously describe C interface functions.

6.27.9.2 Detailed operation:

1. Select a target, in this example we are using `example.h`
2. Create an interface file for the header. This can be used to pass options, switches and define variables. In the simplest case it just instructs to translate all of `example.h`:

```
%module example
%insert("include")
{
    #include "example.h"
}
%include "example.h"
```

3. Use SWIG to create a `.fsi-c` file.


```
swig -forth -stackcomments -use-structs -enumcomments -o example-fsi.c
example.i.
```

 FSI stands “Forth Source Independent” meaning it can be transferred to any host having a C-compiler. SWIG is not required past this point.
4. On the target machine compile the `.fsi-c` file to a `.fsx` (x stands for executable)


```
gcc -o example.fsx example-fsi.c
```

 The compilation will resolve all constants to the values on the target.
5. The last step is to run the executable and capture its output to a `.fs` “Forth Source” file.


```
./example.fsx -gforth > example.fs
```

 This code can now be used on the target platform.

6.27.9.3 Examples

You can find some examples in SWIG’s Forth Example section (<https://github.com/GeraldWodni/swig/tree/master/Examples/forth>).

A lot of interface files can be found in Forth Posix C-Interface (<https://github.com/GeraldWodni/posix>) and Forth C-Interface Modules (<https://github.com/GeraldWodni/forth-c-interfaces>).

Contribution to the Forth C-Interface Module repository (<https://github.com/GeraldWodni/forth-c-interfaces>) is always welcome.

6.27.10 Migrating from Gforth 0.7

In this version, you can use `\c`, `c-function` and `add-lib` only inside `c-library...end-c-library`. `add-lib` now always starts from a clean slate inside a `c-library`, so you don’t need to use `clear-libs` in most cases.

If you have a program that uses these words outside `c-library...end-c-library`, just wrap them in `c-library...end-c-library`. You may have to add some instances of `add-lib`, however.

6.28 Assembler and Code Words

6.28.1 Definitions in assembly language

Gforth provides ways to implement words in assembly language (using `abi-code...end-code`), and also ways to define defining words with arbitrary run-time behaviour (like `does>`), where (unlike `does>`) the behaviour is not defined in Forth, but in assembly language (with `;code`).

However, the machine-independent nature of Gforth poses a few problems: First of all, Gforth runs on several architectures, so it can provide no standard assembler. It does provide assemblers for several of the architectures it runs on, though. Moreover, you can use a system-independent assembler in Gforth, or compile machine code directly with `,` and `c,.`

Another problem is that the virtual machine registers of Gforth (the stack pointers and the virtual machine instruction pointer) depend on the installation and engine. Also, which registers are free to use also depend on the installation and engine. So any code written to run in the context of the Gforth virtual machine is essentially limited to the installation and engine it was developed for (it may run elsewhere, but you cannot rely on that).

Fortunately, you can define `abi-code` words in Gforth that are portable to any Gforth running on a platform with the same calling convention (ABI); typically this means portability to the same architecture/OS combination, sometimes crossing OS boundaries).

assembler (`-`) tools-ext “assembler”

A vocabulary: Replaces the wordlist at the top of the search order with the assembler wordlist.

init-asm (`-`) gforth-0.2 “init-asm”

Pushes the assembler wordlist on the search order.

abi-code (`"name" - colon-sys`) gforth-1.0 “abi-code”

Start a native code definition that is called using the platform’s ABI conventions corresponding to the C-prototype:

```
Cell *function(Cell *sp, Float **fpp);
```

The FP stack pointer is passed in by providing a reference to a memory location containing the FP stack pointer and is passed out by storing the changed FP stack pointer there (if necessary).

end-code (`colon-sys -`) gforth-0.2 “end-code”

End a code definition. Note that you have to assemble the return from the ABI call (for `abi-code`) or the dispatch to the next VM instruction (for `code` and `;code`) yourself.

code (`"name" - colon-sys`) tools-ext “code”

Start a native code definition that runs in the context of the Gforth virtual machine (engine). Such a definition is not portable between Gforth installations, so we recommend using `abi-code` instead of `code`. You have to end a `code` definition with a dispatch to the next virtual machine instruction.

;code (`compilation. colon-sys1 - colon-sys2`) tools-ext “semicolon-code”

The code after `;code` becomes the behaviour of the last defined word (which must be a `created` word). The same caveats apply as for `code`, so we recommend using `;abi-code` instead.

`flush-icache` (*c-addr u* -) gforth-0.2 “flush-icache”

Make sure that the instruction cache of the processor (if there is one) does not contain stale data at *c-addr* and *u* bytes afterwards. `END-CODE` performs a `flush-icache` automatically. Caveat: `flush-icache` might not work on your installation; this is usually the case if direct threading is not supported on your machine (take a look at your `machine.h`) and your machine has a separate instruction cache. In such cases, `flush-icache` does nothing instead of flushing the instruction cache.

If `flush-icache` does not work correctly, `abi-code` words etc. will not work (reliably), either.

The typical usage of these words can be shown most easily by analogy to the equivalent high-level defining words:

<code>: foo</code>	<code>abi-code foo</code>
<code><high-level Forth words></code>	<code><assembler></code>
<code>;</code>	<code>end-code</code>
<code>: bar</code>	<code>: bar</code>
<code><high-level Forth words></code>	<code><high-level Forth words></code>
<code>CREATE</code>	<code>CREATE</code>
<code><high-level Forth words></code>	<code><high-level Forth words></code>
<code>DOES></code>	<code>;code</code>
<code><high-level Forth words></code>	<code><assembler></code>
<code>;</code>	<code>end-code</code>

For using `abi-code`, take a look at the ABI documentation of your platform to see how the parameters are passed (so you know where you get the stack pointers) and how the return value is passed (so you know where the data stack pointer is returned). The ABI documentation also tells you which registers are saved by the caller (caller-saved), so you are free to destroy them in your code, and which registers have to be preserved by the called word (callee-saved), so you have to save them before using them, and restore them afterwards. For some architectures and OSs we give short summaries of the parts of the calling convention in the appropriate sections. More reverse-engineering oriented people can also find out about the passing and returning of the stack pointers through `see abi-call`.

Most ABIs pass the parameters through registers, but some (in particular the most common 386 (aka IA-32) calling conventions) pass them on the architectural stack. The common ABIs all pass the return value in a register.

Other things you need to know for using `abi-code` is that both the data and the FP stack grow downwards (towards lower addresses) in Gforth, with 1 `cells` size per cell, and 1 `floats` size per FP value.

Here’s an example of using `abi-code` on the 386 architecture:

```
abi-code my+ ( n1 n2 -- n )
4 sp d) ax mov \ sp into return reg
ax )    cx mov \ tos
4 #     ax add \ update sp (pop)
```

```

cx    ax ) add \ sec = sec+tos
ret           \ return from my+
end-code

```

An AMD64 variant of this example can be found in Section 6.28.5 [AMD64 Assembler], page 222.

Here's a 386 example that deals with FP values:

```

abi-code my-f+ ( r1 r2 -- r )
8 sp d) cx mov \ load address of fp
cx )    dx mov \ load fp
.fl dx ) fld \ r2
8 #     dx add \ update fp
.fl dx ) fadd \ r1+r2
.fl dx ) fstp \ store r
dx    cx ) mov \ store new fp
4 sp d) ax mov \ sp into return reg
ret           \ return from my-f+
end-code

```

6.28.2 Common Assembler

The assemblers in Gforth generally use a postfix syntax, i.e., the instruction name follows the operands.

The operands are passed in the usual order (the same that is used in the manual of the architecture). Since they all are Forth words, they have to be separated by spaces; you can also use Forth words to compute the operands.

The instruction names usually end with a `,.` This makes it easier to visually separate instructions if you put several of them on one line; it also avoids shadowing other Forth words (e.g., `and`).

Registers are usually specified by number; e.g., (decimal) 11 specifies registers R11 and F11 on the Alpha architecture (which one, depends on the instruction). The usual names are also available, e.g., `s2` for R11 on Alpha.

Control flow is specified similar to normal Forth code (see Section 6.9.6 [Arbitrary control structures], page 90), with `if,,`, `ahead,,`, `then,,`, `begin,,`, `until,,`, `again,,`, `cs-roll`, `cs-pick`, `else,,`, `while,,`, and `repeat,,`. The conditions are specified in a way specific to each assembler.

The rest of this section is of interest mainly for those who want to define `code` words (instead of the more portable `abi-code` words).

Note that the register assignments of the Gforth engine can change between Gforth versions, or even between different compilations of the same Gforth version (e.g., if you use a different GCC version). If you are using `CODE` instead of `ABI-CODE`, and you want to refer to Gforth's registers (e.g., the stack pointer or TOS), I recommend defining your own words for referring to these registers, and using them later on; then you can adapt to a changed register assignment.

The most common use of these registers is to end a `code` definition with a dispatch to the next word (the `next` routine). A portable way to do this is to jump to `' noop >code-address`

(of course, this is less efficient than integrating the `next` code and scheduling it well). When using `ABI-CODE`, you can just assemble a normal subroutine return (but make sure you return the data stack pointer).

Another difference between Gforth versions is that the top of stack is kept in memory in `gforth` and, on most platforms, in a register in `gforth-fast`. For `ABI-CODE` definitions, any stack caching registers are guaranteed to be flushed to the stack, allowing you to reliably access the top of stack in memory.

6.28.3 Common Disassembler

You can disassemble a `code` word with `see` (see Section 6.25.8 [Debugging], page 202). You can disassemble a section of memory with

```
discode ( addr u - ) gforth-0.2 "discode"
```

hook for the disassembler: disassemble u bytes of code at addr

There are two kinds of disassembler for Gforth: The Forth disassembler (available on some CPUs) and the gdb disassembler (available on platforms with `gdb` and `mktemp`). If both are available, the Forth disassembler is used by default. If you prefer the gdb disassembler, say

```
' disasm-gdb is discode
```

If neither is available, `discode` performs `dump`.

The Forth disassembler generally produces output that can be fed into the assembler (i.e., same syntax, etc.). It also includes additional information in comments. In particular, the address of the instruction is given in a comment before the instruction.

The gdb disassembler produces output in the same format as the gdb `disassemble` command (see Section “Source and machine code” in *Debugging with GDB*), in the default flavour (AT&T syntax for the 386 and AMD64 architectures).

`See` may display more or less than the actual code of the word, because the recognition of the end of the code is unreliable. You can use `discode` if it did not display enough. It may display more, if the code word is not immediately followed by a named word. If you have something else there, you can follow the word with `align latest`, to ensure that the end is recognized.

6.28.4 386 Assembler

The 386 assembler included in Gforth was written by Bernd Paysan, it's available under GPL, and originally part of bigFORTH.

The 386 disassembler included in Gforth was written by Andrew McKewan and is in the public domain.

The disassembler displays code in an Intel-like prefix syntax.

The assembler uses a postfix syntax with AT&T-style parameter order (i.e., destination last).

The assembler includes all instruction of the Athlon, i.e. 486 core instructions, Pentium and PPro extensions, floating point, MMX, 3Dnow!, but not ISSE. It's an integrated 16- and 32-bit assembler. Default is 32 bit, you can switch to 16 bit with `.86` and back to 32 bit with `.386`.

There are several prefixes to switch between different operation sizes, `.b` for byte accesses, `.w` for word accesses, `.d` for double-word accesses. Addressing modes can be switched with `.wa` for 16 bit addresses, and `.da` for 32 bit addresses. You don't need a prefix for byte register names (AL et al).

For floating point operations, the prefixes are `.fs` (IEEE single), `.fl` (IEEE double), `.fx` (extended), `.fw` (word), `.fd` (double-word), and `.fq` (quad-word). The default is `.fx`, so you need to specify `.fl` explicitly when dealing with Gforth FP values.

The MMX opcodes don't have size prefixes, they are spelled out like in the Intel assembler. Instead of move from and to memory, there are PLDQ/PLDD and PSTQ/PSTD.

The registers lack the 'e' prefix; even in 32 bit mode, `eax` is called `ax`. Immediate values are indicated by postfixing them with `#`, e.g., `3 #`. Here are some examples of addressing modes in various syntaxes:

Gforth	Intel (NASM)	AT&T (gas)	Name
<code>.w ax</code>	<code>ax</code>	<code>%ax</code>	register (16 bit)
<code>ax</code>	<code>eax</code>	<code>%eax</code>	register (32 bit)
<code>3 #</code>	<code>offset 3</code>	<code>\$3</code>	immediate
<code>1000 #)</code>	<code>byte ptr 1000</code>	<code>1000</code>	displacement
<code>bx)</code>	<code>[ebx]</code>	<code>(%ebx)</code>	base
<code>100 di d)</code>	<code>100[edi]</code>	<code>100(%edi)</code>	base+displacement
<code>20 ax *4 i#)</code>	<code>20[<i>eax</i>*4]</code>	<code>20(,<i>%eax</i>,4)</code>	(index*scale)+displacement
<code>di ax *4 i)</code>	<code>[edi][<i>eax</i>*4]</code>	<code>(%edi,<i>%eax</i>,4)</code>	base+(index*scale)
<code>4 bx cx di)</code>	<code>4[ebx][ecx]</code>	<code>4(%ebx,%ecx)</code>	base+index+displacement
<code>12 sp ax *2 di)</code>	<code>12[esp][<i>eax</i>*2]</code>	<code>12(%esp,<i>%eax</i>,2)</code>	base+(index*scale)+displacement

You can use `L` and `LI` instead of `D` and `DI` to enforce 32-bit displacement fields (useful for later patching).

Some example of instructions are:

```

ax bx mov      \ move ebx, eax
3 # ax mov     \ mov  eax, 3
100 di d) ax mov \ mov  eax, 100[edi]
4 bx cx di) ax mov \ mov  eax, 4[ebx][ecx]
.w ax bx mov    \ mov  bx, ax

```

The following forms are supported for binary instructions:

```

<reg> <reg> <inst>
<n> # <reg> <inst>
<mem> <reg> <inst>
<reg> <mem> <inst>
<n> # <mem> <inst>

```

The shift/rotate syntax is:

```

<reg/mem> 1 # shl \ shortens to shift without immediate
<reg/mem> 4 # shl
<reg/mem> cl shl

```

Precede string instructions (`movs` etc.) with `.b` to get the byte version.

The control structure words `IF` `UNTIL` etc. must be preceded by one of these conditions: `vs` `vc` `u<` `u>=` `0=` `0<` `u<=` `u>` `0<` `0>=` `ps` `pc` `<` `>=` `<=` `>`. (Note that most of these words shadow

some Forth words when `assembler` is in front of `forth` in the search path, e.g., in `code` words). Currently the control structure words use one stack item, so you have to use `roll` instead of `cs-roll` to shuffle them (you can also use `swap` etc.).

Based on the Intel ABI (used in Linux), `abi-code` words can find the data stack pointer at `4 sp d`, and the address of the FP stack pointer at `8 sp d`; the data stack pointer is returned in `ax`; `ax`, `cx`, and `dx` are caller-saved, so you do not need to preserve their values inside the word. You can return from the word with `ret`, the parameters are cleaned up by the caller.

For examples of 386 `abi-code` words, see Section 6.28.1 [Assembler Definitions], page 217.

6.28.5 AMD64 (x86_64) Assembler

The AMD64 assembler is a slightly modified version of the 386 assembler, and as such shares most of the syntax. Two new prefixes, `.q` and `.qa`, are provided to select 64-bit operand and address sizes respectively. 64-bit sizes are the default, so normally you only have to use the other prefixes. Also there are additional register operands `R8-R15`.

The registers lack the 'e' or 'r' prefix; even in 64 bit mode, `rax` is called `ax`. Additional register operands are available to refer to the lowest-significant byte of all registers: `R8L-R15L`, `SPL`, `BPL`, `SIL`, `DIL`.

The Linux-AMD64 calling convention is to pass the first 6 integer parameters in `rdi`, `rsi`, `rdx`, `rcx`, `r8` and `r9` and to return the result in `rax` and `rdx`; to pass the first 8 FP parameters in `xmm0-xmm7` and to return FP results in `xmm0-xmm1`. So `abi-code` words get the data stack pointer in `di` and the address of the FP stack pointer in `si`, and return the data stack pointer in `ax`. The other caller-saved registers are: `r10`, `r11`, `xmm8-xmm15`. This calling convention reportedly is also used in other non-Microsoft OSs.

Windows x64 passes the first four integer parameters in `rcx`, `rdx`, `r8` and `r9` and return the integer result in `rax`. The other caller-saved registers are `r10` and `r11`.

On the Linux platform, according to https://uclibc.org/docs/psABI-x86_64.pdf page 21 the registers `AX CX DX SI DI R8 R9 R10 R11` are available for scratch.

The addressing modes for the AMD64 are:

```
\ running word A produces a memory error as the registers are not initialised ;-)\
ABI-CODE A ( -- )
    500      #                AX MOV      \ immediate
        DX                AX MOV      \ register
    200      AX MOV      \ direct addressing
        DX )              AX MOV      \ indirect addressing
    40  DX D)              AX MOV      \ base with displacement
        DX CX      I)  AX MOV      \ scaled index
        DX CX *4  I)  AX MOV      \ scaled index
    40  DX CX *4  DI) AX MOV      \ scaled index with displacement

        DI                AX MOV      \ SP Out := SP in
                                RET
END-CODE
```

Here are a few examples of an AMD64 `abi-code` words:

```
abi-code my+ ( n1 n2 -- n3 )
```

```

\ SP passed in di, returned in ax, address of FP passed in si
8 di d) ax lea      \ compute new sp in result reg
di )    dx mov      \ get old tos
dx    ax ) add      \ add to new tos
ret
end-code

\ Do nothing
ABI-CODE aNOP  ( -- )
          DI )    AX      LEA      \ SP out := SP in
                               RET

END-CODE

\ Drop TOS
ABI-CODE aDROP ( n -- )
          8  DI D)    AX      LEA      \ SPout := SPin - 1
                               RET

END-CODE

\ Push 5 on the data stack
ABI-CODE aFIVE  ( -- 5 )
          -8 DI D)    AX      LEA      \ SPout := SPin + 1
          5  #        AX )    MOV      \ TOS := 5
                               RET

END-CODE

\ Push 10 and 20 into data stack
ABI-CODE aTOS2  ( -- n n )
          -16 DI D)   AX      LEA      \ SPout := SPin + 2
          10 #        8  AX D)  MOV      \ TOS - 1 := 10
          20 #        AX )    MOV      \ TOS := 20
                               RET

END-CODE

\ Get Time Stamp Counter as two 32 bit integers
\ The TSC is incremented every CPU clock pulse
ABI-CODE aRDTSC ( -- TSCl TSCh )
                               RDTSC      \ DX:AX := TSC
          $FFFFFFFF #    AX      AND      \ Clear upper 32 bit AX
          0xFFFFFFFF #  DX      AND      \ Clear upper 32 bit DX
          AX             R8      MOV      \ Tempory save AX
          -16 DI D)    AX      LEA      \ SPout := SPin + 2
          R8            8  AX D)  MOV      \ TOS-1 := saved AX = TSC low
          DX             AX )    MOV      \ TOS := Dx = TSC high
                               RET

END-CODE

\ Get Time Stamp Counter as 64 bit integer
ABI-CODE RDTSC  ( -- TSC )
                               RDTSC      \ DX:AX := TSC
          $FFFFFFFF #    AX      AND      \ Clear upper 32 bit AX

```

```

    32 #          DX      SHL          \ Move lower 32 bit DX to upper 32 bit
    AX          DX      OR           \ Combine AX wit DX in DX
    -8 DI D)     AX      LEA          \ SPout := SPin + 1
    DX          AX )    MOV          \ TOS := DX
                                RET

END-CODE
VARIABLE V

\ Assign 4 to variable V
ABI-CODE V=4 ( -- )
    BX          PUSH          \ Save BX, used by gforth
    V #          BX      MOV          \ BX := address of V
    4 #          BX )    MOV          \ Write 4 to V
    BX          POP          \ Restore BX
    DI )        AX      LEA          \ SPout := SPin
                                RET

END-CODE
VARIABLE V

\ Assign 5 to variable V
ABI-CODE V=5 ( -- )
    V #          CX      MOV          \ CX := address of V
    5 #          CX )    MOV          \ Write 5 to V
    DI )        AX      LEA          \ SPout := SPin
                                RET

END-CODE
ABI-CODE TEST2 ( -- n n )
    -16 DI D)   AX      LEA          \ SPout := SPin + 2
    5 #          CX      MOV          \ CX := 5
    5 #          CX      CMP
    0= IF
        1 #      8 AX D)    MOV          \ If CX = 5 then TOS - 1 := 1 <--
    ELSE
        2 #      8 AX D)    MOV          \ else TOS - 1 := 2
    THEN
    6 #          CX      CMP
    0= IF
        3 #          AX )    MOV          \ If CX = 6 then TOS := 3
    ELSE
        4 #          AX )    MOV          \ else TOS := 4 <--
    THEN
                                RET

END-CODE

\ Do four loops. Expect : ( 4 3 2 1 -- )
ABI-CODE LOOP4 ( -- n n n n )
    DI          AX      MOV          \ SPout := SPin

```

```

4   #           DX      MOV      \ DX := 4  loop counter
BEGIN
    8   #           AX      SUB      \ SP := SP + 1
      DX         AX  )  MOV      \ TOS := DX
    1   #           DX      SUB      \ DX := DX - 1
0= UNTIL

                                RET

END-CODE

```

Here's a AMD64 example that deals with FP values:

```

abi-code my-f+ ( r1 r2 -- r )
\ SP passed in di, returned in ax,  address of FP passed in si
si )      dx mov      \ load fp
8 dx d)  xmm0 movsd    \ r2
dx )      xmm0 addsd    \ r1+r2
xmm0 8 dx d) movsd     \ store r
8 #      si ) add      \ update fp
di      ax mov      \ sp into return reg
ret
end-code

```

6.28.6 Alpha Assembler

The Alpha assembler and disassembler were originally written by Bernd Thallner.

The register names **a0–a5** are not available to avoid shadowing hex numbers.

Immediate forms of arithmetic instructions are distinguished by a **#** just before the **,**, e.g., **and#**, (note: **lda**, does not count as arithmetic instruction).

You have to specify all operands to an instruction, even those that other assemblers consider optional, e.g., the destination register for **br**,, or the destination register and hint for **jmp**,.

You can specify conditions for **if**, by removing the first **b** and the trailing **,** from a branch with a corresponding name; e.g.,

```

11 fgt if, \ if F11>0e
...
endif,
fbgt, gives fgt.

```

6.28.7 MIPS assembler

The MIPS assembler was originally written by Christian Pirker.

Currently the assembler and disassembler covers most of the MIPS32 architecture and doesn't support FP instructions.

The register names **\$a0–\$a3** are not available to avoid shadowing hex numbers. Use register numbers **\$4–\$7** instead.

Nothing distinguishes registers from immediate values. Use explicit opcode names with the **i** suffix for instructions with immediate argument. E.g. **addiu**, in place of **addu**,.

Where the architecture manual specifies several formats for the instruction (e.g., for `jalr`), use the one with more arguments (i.e. two for `jalr`). When in doubt, see `arch/mips/testasm.fs` for an example of correct use.

Branches and jumps in the MIPS architecture have a delay slot. You have to fill it manually (the simplest way is to use `nop`), the assembler does not do it for you (unlike `as`). Even `if`, `ahead`, `until`, `again`, `while`, `else`, and `repeat`, need a delay slot. Since `begin`, and `then`, just specify branch targets, they are not affected. For branches the argument specifying the target is a relative address. Add the address of the delay slot to get the absolute address.

Note that you must not put branches nor jumps (nor control-flow instructions) into the delay slot. Also it is a bad idea to put pseudo-ops such as `li`, into a delay slot, as these may expand to several instructions. The MIPS I architecture also had load delay slots, and newer MIPSes still have restrictions on using `mfhi`, and `mflo`. Be careful to satisfy these restrictions, the assembler does not do it for you.

Some example of instructions are:

```
$ra 12 $sp sw,      \ sw    ra,12(sp)
$4   8 $s0 lw,      \ lw    a0,8(s0)
$v0  $0 lui,        \ lui   v0,0x0
$s0  $s4 $12 addiu, \ addiu s0,s4,0x12
$s0  $s4 $4 addu,   \ addu  s0,s4,$a0
$ra  $t9 jalr,      \ jalr  t9
```

You can specify the conditions for `if`, etc. by taking a conditional branch and leaving away the `b` at the start and the `,` at the end. E.g.,

```
4 5 eq if,
... \ do something if $4 equals $5
then,
```

The calling conventions for 32-bit MIPS machines is to pass the first 4 arguments in registers `$4..$7`, and to use `$v0-$v1` for return values. In addition to these registers, it is ok to clobber registers `$t0-$t8` without saving and restoring them.

If you use `jalr`, to call into dynamic library routines, you must first load the called function's address into `$t9`, which is used by position-indirect code to do relative memory accesses.

Here is an example of a MIPS32 abi-code word:

```
abi-code my+ ( n1 n2 -- n3 )
  \ SP passed in $4, returned in $v0
  $t0 4 $4 lw,      \ load n1, n2 from stack
  $t1 0 $4 lw,
  $t0 $t0 $t1 addu, \ add n1+n2, result in $t0
  $t0 4 $4 sw,      \ store result (overwriting n1)
  $ra jr,           \ return to caller
  $v0 $4 4 addiu,   \ (delay slot) return updated SP in $v0
end-code
```

6.28.8 PowerPC assembler

The PowerPC assembler and disassembler were contributed by Michal Revucky.

This assembler does not follow the convention of ending mnemonic names with a “,”, so some mnemonic names shadow regular Forth words (in particular: **and** or **xor** **fabs**); so if you want to use the Forth words, you have to make them visible first, e.g., with **also forth**.

Registers are referred to by their number, e.g., **9** means the integer register 9 or the FP register 9 (depending on the instruction).

Because there is no way to distinguish registers from immediate values, you have to explicitly use the immediate forms of instructions, i.e., **addi**, not just **add**.

The assembler and disassembler usually support the most general form of an instruction, but usually not the shorter forms (especially for branches).

6.28.9 ARM Assembler

The ARM assembler includes all instruction of ARM architecture version 4, and the BLX instruction from architecture 5. It does not (yet) have support for Thumb instructions. It also lacks support for any co-processors.

The assembler uses a postfix syntax with the same operand order as used in the ARM Architecture Reference Manual. Mnemonics are suffixed by a comma.

Registers are specified by their names **r0** through **r15**, with the aliases **pc**, **lr**, **sp**, **ip** and **fp** provided for convenience. Note that **ip** refers to the “intra procedure call scratch register” (**r12**) and does not refer to an instruction pointer. **sp** refers to the ARM ABI stack pointer (**r13**) and not the Forth stack pointer.

Condition codes can be specified anywhere in the instruction, but will be most readable if specified just in front of the mnemonic. The ‘S’ flag is not a separate word, but encoded into instruction mnemonics, ie. just use **adds**, instead of **add**, if you want the status register to be updated.

The following table lists the syntax of operands for general instructions:

Gforth	normal assembler	description
123 #	#123	immediate
r12	r12	register
r12 4 #LSL	r12, LSL #4	shift left by immediate
r12 r1 LSL	r12, LSL r1	shift left by register
r12 4 #LSR	r12, LSR #4	shift right by immediate
r12 r1 LSR	r12, LSR r1	shift right by register
r12 4 #ASR	r12, ASR #4	arithmetic shift right
r12 r1 ASR	r12, ASR r1	... by register
r12 4 #ROR	r12, ROR #4	rotate right by immediate
r12 r1 ROR	r12, ROR r1	... by register
r12 RRX	r12, RRX	rotate right with extend by 1

Memory operand syntax is listed in this table:

Gforth	normal assembler	description
r4]	[r4]	register
r4 4 #]	[r4, #+4]	register with immediate offset
r4 -4 #]	[r4, #-4]	with negative offset
r4 r1 +]	[r4, +r1]	register with register offset
r4 r1 -]	[r4, -r1]	with negated register offset

r4 r1 2 #LSL -]	[r4, -r1, LSL #2]	with negated and shifted offset
r4 4 #]!	[r4, #+4]!	immediate preincrement
r4 r1 +]!	[r4, +r1]!	register preincrement
r4 r1 -]!	[r4, +r1]!	register predecrement
r4 r1 2 #LSL +]!	[r4, +r1, LSL #2]!	shifted preincrement
r4 -4]#	[r4], #-4	immediate postdecrement
r4 r1]+	[r4], r1	register postincrement
r4 r1]-	[r4], -r1	register postdecrement
r4 r1 2 #LSL]-	[r4], -r1, LSL #2	shifted postdecrement
' xyz >body [#] xyz		PC-relative addressing

Register lists for load/store multiple instructions are started and terminated by using the words { and } respectively. Between braces, register names can be listed one by one or register ranges can be formed by using the postfix operator r-r. The ^ flag is not encoded in the register list operand, but instead directly encoded into the instruction mnemonic, ie. use ^ldm, and ^stm,.

Addressing modes for load/store multiple are not encoded as instruction suffixes, but instead specified like an addressing mode, Use one of DA, IA, DB, IB, DA!, IA!, DB! or IB!.

The following table gives some examples:

Gforth	normal assembler
r4 ia { r0 r7 r8 } stm,	stmia r4, {r0,r7,r8}
r4 db! { r0 r7 r8 } ldm,	ldmdb r4!, {r0,r7,r8}
sp ia! { r0 r15 r-r } ^ldm,	ldmfd sp!, {r0-r15}^

Control structure words typical for Forth assemblers are available: if, ahead, then, else, begin, until, again, while, repeat, repeat-until,. Conditions are specified in front of these words:

```

r1 r2 cmp,    \ compare r1 and r2
eq if,        \ equal?
...           \ code executed if r1 == r2
then,
```

Example of a definition using the ARM assembler:

```

abi-code my+ ( n1 n2 -- n3 )
  \ arm abi: r0=SP, r1=&FP, r2,r3,r12 saved by caller
  r0 IA! { r2 r3 } ldm,    \ pop r2 = n2, r3 = n1
  r3 r2 r3               add,    \ r3 = n1+n1
  r3 r0 -4 #]!           str,    \ push r3
  pc lr                 mov,    \ return to caller, new SP in r0
end-code
```

6.28.10 Other assemblers

If you want to contribute another assembler/disassembler, please contact us (anton@mips.complang.tuwien.ac.at) to check if we have such an assembler already. If you are writing them from scratch, please use a similar syntax style as the one we use (i.e., postfix, commas at the end of the instruction names, see Section 6.28.2 [Common Assembler], page 219); make the output of the disassembler be valid input for the assembler, and keep the style similar to the style we used.

Hints on implementation: The most important part is to have a good test suite that contains all instructions. Once you have that, the rest is easy. For actual coding you can take a look at `arch/mips/disasm.fs` to get some ideas on how to use data for both the assembler and disassembler, avoiding redundancy and some potential bugs. You can also look at that file (and see Section 6.10.9.5 [Advanced does> usage example], page 107) to get ideas how to factor a disassembler.

Start with the disassembler, because it's easier to reuse data from the disassembler for the assembler than the other way round.

For the assembler, take a look at `arch/alpha/asm.fs`, which shows how simple it can be.

6.29 Carnal words

These words deal with the mechanics of Gforth (in Forth circles called “carnal knowledge” of a Forth system), but we consider them stable enough to document them.

6.29.1 Header fields

In Gforth 1.0 we switched to a new word header layout. For a detailed description, read: Bernd Paysan and M. Anton Ertl. *The new Gforth header* (<http://www.euroforth.org/ef19/papers/paysan.pdf>). In 35th EuroForth Conference, pages 5-20, 2019. Since this paper was published, `xt` and `nt` have been changed to point to the parameter field, like the `body`, but otherwise it is still up-to-date.

This section explains just the data structure and the words used to access it. A header has the following fields:

```
name
>f+c
>link
>cfa
>namehm
>body
```

Currently Gforth has the names shown above for getting from the `xt/nt/body` to the field, but apart from the standard `>body` they are not stable Gforth words. Instead, we provide access words. Note that the documented access words have survived the reorganization of the header layout.

Some of the words expect an `nt`, some expect an `xt`. Given that both `nt` and `xt` point to the body of a word, what is the difference? For most words, the `xt` and `nt` use the same header, and with `nt=xt`, they point to the same place. However, for a synonym (see Section 6.10.12 [Aliases], page 114) there is a difference; consider the example

```
create x
synonym y x
synonym z y
```

In this case the `nt` of `z` points to the body of `z`, while the `xt` of `z` points to the body of `x`. Words defined with `alias` or `forward` (see Section 6.10.11 [Forward], page 114) also have different `nts` and `xts`.

The name field is variable-length and is accessed with `name>string` (see Section 6.12.2 [Name token], page 118).

The `>f+c` field contains flags and the name length (count). You read the count with `name>string`, and the flags with

```
compile-only? ( nt - flag ) gforth-1.0 "compile-only?"
```

true if `nt` is marked as compile-only.

The `>link` field contains a link to the previous word in the same word list. You can read it with

```
name>link ( nt1 - nt2 / 0 ) gforth-1.0 "name-to-link"
```

For a word `nt1`, returns the previous word `nt2` in the same wordlist, or 0 if there is no previous word.

The name, `>f+c` and `>link` fields are not present for `noname` words, but `name>string` and `name>link` work nevertheless, producing 0 0 and 0, respectively.

The `>cfa` field (aka code field) contains the code address used for `execute`ing the word; you can read it with `>code-address` and write it with `code-address!` (see Section 6.29.3 [Threading Words], page 233).

The `>namehm` field contains the address of the header methods table, described below. You access it by performing or accessing header methods (see Section 6.29.2 [Header methods], page 230).

The `>body` (aka parameter) field contains data or threaded code specific to the word type; its length depends on the word type. E.g., for a `constant` it contains a cell with the value of the constant. You can access it through `>body` (see Section 6.10.9.4 [CREATE..DOES> details], page 106), but this is only standard for words you defined with `create`.

6.29.2 Header methods

The new Gforth word header is object-oriented and supports the following methods (method selectors):

method	overrider	field
<code>execute</code>	<code>set-execute</code>	<code>>cfa</code>
<code>opt-compile,</code>	<code>set-optimizer</code>	<code>>hmcompile,</code>
<code>defer!</code>	<code>set-to</code>	<code>>hmto</code>
<code>defer@</code>	<code>set-defer@</code>	<code>>hmdefer@</code>
		<code>>hmextra</code>
<code>name>interpret</code>	<code>set->int</code>	<code>>hm>int</code>
<code>name>compile</code>	<code>set->comp</code>	<code>>hm>comp</code>
<code>name>string</code>	<code>set-name>string</code>	<code>>hm>string</code>
<code>name>link</code>	<code>set-name>link</code>	<code>>hm>link</code>

Many of these words are not stable Gforth words, but Gforth has stable higher-level words that we mention below.

Setter words change the most recent definition (which does not include completed quotations or closures).

The `execute` method is actually stored in the `>cfa` field in the header rather than in the header-methods table for performance reasons; also it is implemented through a native-code

address, while the other methods are implemented by calling an `xt`. The high-level way to set this method is

```
set-execute ( ca - ) gforth-1.0 "Changes"
```

jumps to the native code at `ca`. Also changes the `compile`, implementation to the most general (and slowest) one. Call `set-optimizer` afterwards if you want a more efficient implementation.

To get a code address for use with `set-execute`, you can use words like `docol:` or `>code-address`, See Section 6.29.3 [Threading Words], page 233.

There is also `set-does>` (see Section 6.10.9 [User-defined Defining Words], page 102), which takes an `xt`.

Moreover, there are the low-level `code-address!` and `definer!`, See Section 6.29.3 [Threading Words], page 233.

The `opt-compile`, method is what `compile`, does on most Gforth engines (`gforth-itc` uses `,` instead). You can define a more efficient implementation of `compile`, for the current word with `set-optimizer`. Note that the end result must be equivalent to `postpone literal postpone execute`.

```
set-optimizer ( xt - ) gforth-1.0 "set-optimizer"
```

Changes the current word such that `compile`,ing it executes `xt` (with the same stack contents as passed to `compile`,. Note that `compile`, must be consistent with `execute`, so you must use `set-optimizer` only to install a more efficient implementation of the same behaviour.

As an example of the use of `set-optimizer`, consider the following definition of `constant`:

```
: constant ( n "name" -- ; name: -- n )
  create ,
  ['] @ set-does>
;
```

```
5 constant five
: foo five ; see foo
```

The Forth system does not know that the value of a constant must not be changed, and just sees a `created` word (which can be changed with `>body`), and `foo` first pushes the body address of `five` and then fetches from there. With `set-optimizer` the definition of `constant` can be optimized as follows:

```
: constant ( n "name" -- ; name: -- n )
  create ,
  ['] @ set-does>
  [: >body @ postpone literal ;] set-optimizer
;
```

Now `foo` contains the literal 5 rather than a call to `five`.

Note that `set-execute` and `set-does>` perform `set-optimizer` themselves in order to ensure that `execute` and `compile`, agree, so if you want to add your own optimizer, you should add it afterwards.

The `defer!` (aka `(to)` method implements `defer!` for words defined with `defer` and similar words, but it is also the core of `to`. The general stack effect of the `defer!/(to)`

method is (*val* *xt* --), where *xt* identifies the word stored into, and *val* is the value (of appropriate type) stored there.

(to) (*val* *xt* -) gforth-1.0 “paren-to”

xt is of a value like word *name*. Stores *val* to *name*.

doc-set-to

E.g., one can implement `fvalue` as follows:

```
: fvalue-to ( r xt -- ) >body f! ;
```

```
: fvalue ( r -- )
  create f,
  ['] f@ set-does>
  ['] fvalue-to set-to ;
```

```
5e fvalue foo
: bar foo 1e f+ to foo ;
see bar
```

You can improve the generated code with `set-optimizer`:

```
: compile-fvalue-to ( xt-value-to -- )
  drop ]] >body f! [[ ;
```

```
: fvalue-to ( r xt -- ) >body f! ;
' compile-fvalue-to set-optimizer
```

```
: fvalue ( r -- )
  create f,
  ['] f@ set-does>
  [: >body ]] literal f@ [[ ;] set-optimizer
  ['] fvalue-to set-to ;
```

```
5e fvalue foo
: bar foo 1e f+ to foo ;
see bar
```

In practice Gforth has a few additional twists to implement, e.g., `+T0`.

`Set-defer@` allows to implement variants of the `defer@` (see Section 6.10.10 [Deferred Words], page 112) method for `defer`-like words.

doc-set-defer

The `>hmextra` field is used for cases where additional data needs to be stored in the header methods table. In particular, it stores the `xt` passed to `set-does>` (and `does>` calls `set-does>`) and the code address behind `;abi-code`.

The methods above all consume an `xt`, not an `nt`, but the override words work on the most recent definition. This means that if you use, e.g., `set-optimizer` on a synonym, the effect will probably not be what you intended: When `compile`,ing the `xt` of the word, the `opt-compile`, implementation of the original word will be used, not the freshly-set one of the synonym.

The following methods consume an *nt*.

The `name>interpret` method is implemented as `noop` for most words, except synonyms and similar words.

`doc-set->int`

The `name>compile` method produces the compilation semantics of the *nt*. By changing it with `set->comp`, you can change the compilation semantics, but it's not as simple as just pushing the *xt* of the desired compilation semantics, because of the stack effect of `name>compile`. Generally you should avoid changing the compilation semantics, and if you do, use a higher-level word like `immediate` or `interpret/compile:`, See Section 6.11.1 [Combined words], page 116.

`doc-set->comp`

`immediate? (nt - flag)` gforth-1.0 “immediate?”

true if the word *nt* has non-default compilation semantics (that's not quite according to the definition of immediacy, but many people mean that when they call a word “immediate”).

`Name>string` and `Name>link` are methods in order to make it possible to eliminate the *name*, *>f+c* and *link* fields from *noname* headers, but still produce meaningful results when using these words. You will typically not change the implementations of these methods except with `noname`, but we still have

`doc-set-name>string` `doc-set-name>link`

6.29.3 Threading Words

These words provide access to code addresses and other threading stuff in Gforth (and, possibly, other interpretive Forths). It more or less abstracts away the differences between direct and indirect threading (and, for direct threading, the machine dependences). However, at present this wordset is still incomplete. It is also pretty low-level; some day it will hopefully be made unnecessary by an *internals* wordset that abstracts implementation details away completely.

The terminology used here stems from indirect threaded Forth systems; in such a system, the *XT* of a word is represented by the *CFA* (code field address) of a word; the *CFA* points to a cell that contains the code address. The code address is the address of some machine code that performs the run-time action of invoking the word (e.g., the `dovar:` routine pushes the address of the body of the word (a variable) on the stack).

In an indirect threaded Forth, you can get the code address of *name* with '`name @`'; in Gforth you can get it with '`name >code-address`', independent of the threading method.

`threading-method (- n)` gforth-0.2 “threading-method”

0 if the engine is direct threaded. Note that this may change during the lifetime of an image.

`>code-address (xt - c_addr)` gforth-0.2 “>code-address”

c_addr is the code address of the word *xt*.

`code-address! (c_addr xt -)` gforth-obsolete “code-address!”

Change a code field with code address *c_addr* at *xt*.

For a word defined with `DOES>`, the code address usually points to a jump instruction (the *does-handler*) that jumps to the *dodoes* routine (in Gforth on some platforms, it can

also point to the `dodoes` routine itself). What you are typically interested in, though, is whether a word is a `DOES>`-defined word, and what Forth code it executes; `>does-code` tells you that.

```
>does-code ( xt - a-addr ) gforth-0.2 ">does-code"
```

If *xt* is the execution token of a child of a `DOES>` word, *a-addr* is the start of the Forth code after the `DOES>`; Otherwise *a-addr* is 0.

To create a `DOES>`-defined word with the following basic words, you have to set up a `DOES>`-handler with `does-handler!`; `/does-handler` aus behind you have to place your executable Forth code. Finally you have to create a word and modify its behaviour with `does-handler!`.

```
does-code! ( xt1 xt2 - ) gforth-0.2 "does-code!"
```

Create a code field at *xt2* for a child of a `DOES>`-word; *xt1* is the execution token of the assigned Forth code.

The code addresses produced by various defining words are produced by the following words:

```
docol: ( - addr ) gforth-0.2 "docol:"
```

The code address of a colon definition.

```
docon: ( - addr ) gforth-0.2 "docon:"
```

The code address of a `CONSTANT`.

```
dovar: ( - addr ) gforth-0.2 "dovar:"
```

The code address of a `CREATED` word.

```
douser: ( - addr ) gforth-0.2 "douser:"
```

The code address of a `USER` variable.

```
dodefer: ( - addr ) gforth-0.2 "dodefer:"
```

The code address of a `deferred` word.

```
dofield: ( - addr ) gforth-0.2 "dofield:"
```

The code address of a `field`.

The following two words generalize `>code-address`, `>does-code`, `code-address!`, and `does-code!`:

```
>definer ( xt - definer ) gforth-0.2 ">definer"
```

Definer is a unique identifier for the way the *xt* was defined. Words defined with different `does>`-codes have different definers. The definer can be used for comparison and in `definer!`.

```
definer! ( definer xt - ) gforth-obsolete "definer!"
```

The word represented by *xt* changes its behaviour to the behaviour associated with *definer*.

Note that `code-address!`, `does-code!`, and `definer!` currently do not update the `opt-compile`, `method`, so the result is probably a word that has an incorrect `compile`, and you need to use `set-optimizer` to fix this. It is probably better to use the higher-level `set-execute` or `set-does>` instead.

6.30 Passing Commands to the Operating System

Gforth allows you to pass an arbitrary string to the host operating system shell (if such a thing exists) for execution.

sh (*"..."* –) gforth-0.2 “sh”

Execute the rest of the command line as shell command(s). Afterwards, **\$?** produces the exit status of the command.

system (*c-addr u* –) gforth-0.2 “system”

Pass the string specified by *c-addr u* to the host operating system for execution in a sub-shell. Afterwards, **\$?** produces the exit status of the command. The value of the environment variable **GFORTHSYSTEMPREFIX** (or its default value) is prepended to the string (mainly to support using **command.com** as shell in Windows instead of whatever shell Cygwin uses by default; see Section 2.5 [Environment variables], page 7).

\$? (– *n*) gforth-0.2 “dollar-question”

Value – the exit status returned by the most recently executed **system** command.

getenv (*c-addr1 u1* – *c-addr2 u2*) gforth-0.2 “getenv”

The string *c-addr1 u1* specifies an environment variable. The string *c-addr2 u2* is the host operating system’s expansion of that environment variable. If the environment variable does not exist, *c-addr2 u2* specifies a string 0 characters in length.

6.31 Keeping track of Time

ms (*n* –) facility-ext “ms”

ns (*d* –) gforth-1.0 “ns”

time&date (– *nsec nmin nhour nday nmonth nyear*) facility-ext “time-and-date”

Report the current time of day. Seconds, minutes and hours are numbered from 0. Months are numbered from 1.

>time&date&tz (*udtime* – *nsec nmin nhour nday nmonth nyear fdst ndstoffs c-addrtz utz*) gforth-1.0 “to-time-and-date”

Convert time in seconds since 1.1.1970 0:00Z to the current time of day. Seconds, minutes and hours are numbered from 0. Months are numbered from 1.

utime (– *dtime*) gforth-0.5 “utime”

Report the current time in microseconds since some epoch. Use **#1000000 um/mod nip** to convert to seconds

ntime (– *dtime*) gforth-1.0 “ntime”

Report the current time in nanoseconds since some epoch.

cputime (– *duser dsystem*) gforth-0.5 “cputime”

duser and **dsystem** are the respective user- and system-level CPU times used since the start of the Forth system (excluding child processes), in microseconds (the granularity may be much larger, however). On platforms without the **getrusage** call, it reports elapsed time (since some epoch) for **duser** and 0 for **dsystem**.

6.32 Miscellaneous Words

This section lists the Standard Forth words that are not documented elsewhere in this manual. Ultimately, they all need proper homes.

quit (?? – ??) core “quit”

Empty the return stack, make the user input device the input source, enter interpret state and start the text interpreter.

The following Standard Forth words are not currently supported by Gforth (see Chapter 9 [Standard conformance], page 240):

EDITOR EMIT? FORGET

7 Error messages

A typical Gforth error message looks like this:

```
in file included from \evaluated string/:-1
in file included from ./yyy.fs:1
./xxx.fs:4: Invalid memory address
>>>bar<<<
Backtrace:
$400E664C @
$400E6664 foo
```

The message identifying the error is *Invalid memory address*. The error happened when text-interpreting line 4 of the file *./xxx.fs*. This line is given (it contains *bar*), and the word on the line where the error happened, is pointed out (with *>>>* and *<<<*).

The file containing the error was included in line 1 of *./yyy.fs*, and *yyy.fs* was included from a non-file (in this case, by giving *yyy.fs* as command-line parameter to Gforth).

At the end of the error message you find a return stack dump that can be interpreted as a backtrace (possibly empty). On top you find the top of the return stack when the *throw* happened, and at the bottom you find the return stack entry just above the return stack of the topmost text interpreter.

To the right of most return stack entries you see a guess for the word that pushed that return stack entry as its return address. This gives a backtrace. In our case we see that *bar* called *foo*, and *foo* called *@* (and *@* had an *Invalid memory address* exception).

Note that the backtrace is not perfect: We don't know which return stack entries are return addresses (so we may get false positives); and in some cases (e.g., for *abort*) we cannot determine from the return address the word that pushed the return address, so for some return addresses you see no names in the return stack dump.

The return stack dump represents the return stack at the time when a specific *throw* was executed. In programs that make use of *catch*, it is not necessarily clear which *throw* should be used for the return stack dump (e.g., consider one *throw* that indicates an error, which is caught, and during recovery another error happens; which *throw* should be used for the stack dump?). Gforth presents the return stack dump for the first *throw* after the last executed (not returned-to) *catch* or *nothrow*; this works well in the usual case. To get the right backtrace, you usually want to insert *nothrow* or *['] false catch 2drop* after a *catch* if the error is not rethrown.

Gforth is able to do a return stack dump for throws generated from primitives (e.g., invalid memory address, stack empty etc.); *gforth-fast* is only able to do a return stack dump from a directly called *throw* (including *abort* etc.). Given an exception caused by a primitive in *gforth-fast*, you will typically see no return stack dump at all; however, if the exception is caught by *catch* (e.g., for restoring some state), and then *thrown* again, the return stack dump will be for the first such *throw*.

gforth-fast also does not attempt to differentiate between division by zero and division overflow, because that costs time in every division.

8 Tools

See also Chapter 13 [Emacs and Gforth], page 259.

8.1 `ans-report.fs`: Report the words used, sorted by wordset

If you want to label a Forth program as Standard Program, you must document which wordsets the program uses.

The `ans-report.fs` tool makes it easy for you to determine which words from which wordset and which non-standard words your application uses. You simply have to include `ans-report.fs` before loading the program you want to check. After loading your program, you can get the report with `print-ans-report`. A typical use is to run this as batch job like this:

```
gforth ans-report.fs myprog.fs -e "print-ans-report bye"
```

The output looks like this (for `compat/control.fs`):

```
The program uses the following words
from CORE :
: POSTPONE THEN ; immediate ?dup IF 0=
from BLOCK-EXT :
\
from FILE :
(
```

`ans-report.fs` reports both Forth-94 and Forth-2012 wordsets. For words that are in both standards, it reports the wordset without suffix (e.g., `CORE-EXT`). For Forth-2012-only words, it reports the wordset with a `-2012` suffix (e.g., `CORE-EXT-2012`); and likewise for the words that are Forth-94-only (i.e., that have been removed in Forth-2012).

8.1.1 Caveats

Note that `ans-report.fs` just checks which words are used, not whether they are used in a standard-conforming way!

Some words are defined in several wordsets in the standard. `ans-report.fs` reports them for only one of the wordsets, and not necessarily the one you expect. It depends on usage which wordset is the right one to specify. E.g., if you only use the compilation semantics of `S`, it is a Core word; if you also use its interpretation semantics, it is a File word.

8.2 Stack depth changes during interpretation

Sometimes you notice that, after loading a file, there are items left on the stack. The tool `depth-changes.fs` helps you find out quickly where in the file these stack items are coming from.

The simplest way of using `depth-changes.fs` is to include it before the file(s) you want to check, e.g.:

```
gforth depth-changes.fs my-file.fs
```

This will compare the stack depths of the data and FP stack at every empty line (in interpretation state) against these depths at the last empty line (in interpretation state). If

the depths are not equal, the position in the file and the stack contents are printed with `~~` (see Section 6.25.8 [Debugging], page 202). This indicates that a stack depth change has occurred in the paragraph of non-empty lines before the indicated line. It is a good idea to leave an empty line at the end of the file, so the last paragraph is checked, too.

Checking only at empty lines usually works well, but sometimes you have big blocks of non-empty lines (e.g., when building a big table), and you want to know where in this block the stack depth changed. You can check all interpreted lines with

```
gforth depth-changes.fs -e "' all-lines is depth-changes-filter" my-file.fs■
```

This checks the stack depth at every end-of-line. So the depth change occurred in the line reported by the `~~` (not in the line before).

Note that, while this offers better accuracy in indicating where the stack depth changes, it will often report many intentional stack depth changes (e.g., when an interpreted computation stretches across several lines). You can suppress the checking of some lines by putting backslashes at the end of these lines (not followed by white space), and using

```
gforth depth-changes.fs -e "' most-lines is depth-changes-filter" my-file.fs■
```

9 Standard conformance

To the best of our knowledge, Gforth is a

ANS Forth System and a Forth-2012 System

- providing the Core Extensions word set
- providing the Block word set
- providing the Block Extensions word set
- providing the Double-Number word set
- providing the Double-Number Extensions word set
- providing the Exception word set
- providing the Exception Extensions word set
- providing the Facility word set
- providing the Facility Extensions word set, except `EMIT?`
- providing the File Access word set
- providing the File Access Extensions word set
- providing the Floating-Point word set
- providing the Floating-Point Extensions word set
- providing the Locals word set
- providing the Locals Extensions word set
- providing the Memory-Allocation word set
- providing the Memory-Allocation Extensions word set
- providing the Programming-Tools word set
- providing the Programming-Tools Extensions word set, except `EDITOR` and `FORGET`
- providing the Search-Order word set
- providing the Search-Order Extensions word set
- providing the String word set
- providing the String Extensions word set
- providing the Extended-Character wordset

Gforth has the following environmental restrictions:

- While processing the OS command line, if an exception is not caught, Gforth exits with a non-zero exit code instead of performing `QUIT`.
- When an `throw` is performed after a `query`, Gforth does not always restore the input source specification in effect at the corresponding catch.

In addition, Standard Forth systems are required to document certain implementation choices. This chapter tries to meet these requirements for the Forth-94 standard. For the Forth-2012 standard, we decided to produce the additional documentation only if there is demand. So if you are really missing this documentation, please let us know.

In many cases, the following documentation gives a way to ask the system for the information instead of providing the information directly, in particular, if the information depends on the processor, the operating system or the installation options chosen, or if they are likely to change during the maintenance of Gforth.

9.1 The Core Words

9.1.1 Implementation Defined Options

(Cell) aligned addresses:

processor-dependent. Gforth's alignment words perform natural alignment (e.g., an address aligned for a datum of size 8 is divisible by 8). Unaligned accesses usually result in a `-23 THROW`.

EMIT and *non-graphic characters:*

The character is output using the C library function (actually, macro) `putc`.

character editing of ACCEPT and EXPECT:

This is modeled on the GNU readline library (see Section “Command Line Editing” in *The GNU Readline Library*) with Emacs-like key bindings. **Tab** deviates a little by producing a full word completion every time you type it (instead of producing the common prefix of all completions). See Section 2.4 [Command-line editing], page 7.

character set:

The character set of your computer and display device. Gforth is 8-bit-clean (but some other component in your system may make trouble).

Character-aligned address requirements:

installation-dependent. Currently a character is represented by a C **unsigned char**; in the future we might switch to **wchar_t** (Comments on that requested).

character-set extensions and matching of names:

Any character except the ASCII NUL character can be used in a name. Matching is case-insensitive (except in **TABLEs**). The matching is performed using the C library function `strncasecmp`, whose function is probably influenced by the locale. E.g., the C locale does not know about accents and umlauts, so they are matched case-sensitively in that locale. For portability reasons it is best to write programs such that they work in the C locale. Then one can use libraries written by a Polish programmer (who might use words containing ISO Latin-2 encoded characters) and by a French programmer (ISO Latin-1) in the same program (of course, **WORDS** will produce funny results for some of the words (which ones, depends on the font you are using)). Also, the locale you prefer may not be available in other operating systems. Hopefully, Unicode will solve these problems one day.

conditions under which control characters match a space delimiter:

If **word** is called with the space character as a delimiter, all white-space characters (as identified by the C macro `isspace()`) are delimiters. **Parse**, on the other hand, treats space like other delimiters. **Parse-name**, which is used by the outer interpreter (aka text interpreter) by default, treats all white-space characters as delimiters.

format of the control-flow stack:

The data stack is used as control-flow stack. The size of a control-flow stack item in cells is given by the constant `cs-item-size`. At the time of this writing,

an item consists of a (pointer to a) locals list (third), an address in the code (second), and a tag for identifying the item (TOS). The following tags are used: `defstart`, `live-orig`, `dead-orig`, `dest`, `do-dest`, `scopestart`.

conversion of digits > 35

The characters `[\]^_'` are the digits with the decimal value 36–41. There is no way to input many of the larger digits.

display after input terminates in ACCEPT and EXPECT:

The cursor is moved to the end of the entered string. If the input is terminated using the `Return` key, a space is typed.

exception abort sequence of ABORT":

The error string is stored into the variable `"error` and a `-2 throw` is performed.

input line terminator:

For interactive input, `C-m` (CR) and `C-j` (LF) terminate lines. One of these characters is typically produced when you type the `Enter` or `Return` key.

maximum size of a counted string:

`s" /counted-string" environment? drop ..` Currently 255 characters on all platforms, but this may change.

maximum size of a parsed string:

Given by the constant `/line`. Currently 255 characters.

maximum size of a definition name, in characters:

`MAXU/8`

maximum string length for ENVIRONMENT?, in characters:

`MAXU/8`

method of selecting the user input device:

The user input device is the standard input. There is currently no way to change it from within Gforth. However, the input can typically be redirected in the command line that starts Gforth.

method of selecting the user output device:

`EMIT` and `TYPE` output to the file-id stored in the value `outfile-id` (`stdout` by default). Gforth uses unbuffered output when the user output device is a terminal, otherwise the output is buffered.

methods of dictionary compilation:

What are we expected to document here?

number of bits in one address unit:

`s" address-units-bits" environment? drop ..` 8 in all current platforms.

number representation and arithmetic:

Processor-dependent. Binary two's complement on all current platforms.

ranges for integer types:

Installation-dependent. Make environmental queries for `MAX-N`, `MAX-U`, `MAX-D` and `MAX-UD`. The lower bounds for unsigned (and positive) types is 0. The lower bound for signed types on two's complement and one's complement machines can be computed by adding 1 to the upper bound.

read-only data space regions:

The whole Forth data space is writable.

size of buffer at WORD:

PAD HERE - .. 104 characters on 32-bit machines. The buffer is shared with the pictured numeric output string. If overwriting **PAD** is acceptable, it is as large as the remaining dictionary space, although only as much can be sensibly used as fits in a counted string.

size of one cell in address units:

1 cells ..

size of one character in address units:

1 chars .. 1 on all current platforms.

size of the keyboard terminal buffer:

Varies. You can determine the size at a specific time using **lp@tib** - .. It is shared with the locals stack and TIBs of files that include the current file. You can change the amount of space for TIBs and locals stack at Gforth startup with the command line option **-l**.

size of the pictured numeric output buffer:

PAD HERE - .. 104 characters on 32-bit machines. The buffer is shared with **WORD**.

size of the scratch area returned by PAD:

The remainder of dictionary space. **unused pad here** - - ..

system case-sensitivity characteristics:

Dictionary searches are case-insensitive (except in **TABLEs**). However, as explained above under *character-set extensions*, the matching for non-ASCII characters is determined by the locale you are using. In the default **C** locale all non-ASCII characters are matched case-sensitively.

system prompt:

ok in interpret state, **compiled** in compile state.

division rounding:

The ordinary division words **/ mod /mod */ */mod** perform floored division (with the default installation of Gforth). You can check this with **s" floored" environment? drop** .. If you write programs that need a specific division rounding, best use **fm/mod** or **sm/rem** for portability.

values of STATE when true:

-1.

values returned after arithmetic overflow:

On two's complement machines, arithmetic is performed modulo $2^{**}\text{bits-per-cell}$ for single arithmetic and $4^{**}\text{bits-per-cell}$ for double arithmetic (with appropriate mapping for signed types). Division by zero typically results in a **-55 throw** (Floating-point unidentified fault) or **-10 throw** (divide by zero). Integer division overflow can result in these throws, or in **-11 throw**; in **gforth-fast** division overflow and divide by zero may also result in returning bogus results without producing an exception.

whether the current definition can be found after DOES>:
No.

9.1.2 Ambiguous conditions

a name is neither a word nor a number:
-13 **throw** (Undefined word).

a definition name exceeds the maximum length allowed:
-19 **throw** (Word name too long)

addressing a region not inside the various data spaces of the forth system:

The stacks, code space and header space are accessible. Machine code space is typically readable. Accessing other addresses gives results dependent on the operating system. On decent systems: -9 **throw** (Invalid memory address).

argument type incompatible with parameter:

This is usually not caught. Some words perform checks, e.g., the control flow words, and issue a **ABORT**" or -12 **THROW** (Argument type mismatch).

attempting to obtain the execution token of a word with undefined execution semantics:

The execution token represents the interpretation semantics of the word. Gforth defines interpretation semantics for all words; for words where the standard does not define interpretation semantics, but defines the execution semantics (except **LEAVE**), the interpretation semantics are to perform the execution semantics. For words where the standard defines no interpretation semantics, but defined compilation semantics (plus **LEAVE**), the interpretation semantics are to perform the compilation semantics. Some words are marked as compile-only, and ' gives a warning for these words.

dividing by zero:

On some platforms, this produces a -10 **throw** (Division by zero); on other systems, this typically results in a -55 **throw** (Floating-point unidentified fault).

insufficient data stack or return stack space:

Depending on the operating system, the installation, and the invocation of Gforth, this is either checked by the memory management hardware, or it is not checked. If it is checked, you typically get a -3 **throw** (Stack overflow), -5 **throw** (Return stack overflow), or -9 **throw** (Invalid memory address) (depending on the platform and how you achieved the overflow) as soon as the overflow happens. If it is not checked, overflows typically result in mysterious illegal memory accesses, producing -9 **throw** (Invalid memory address) or -23 **throw** (Address alignment exception); they might also destroy the internal data structure of **ALLOCATE** and friends, resulting in various errors in these words.

insufficient space for loop control parameters:

Like other return stack overflows.

insufficient space in the dictionary:

If you try to allot (either directly with **allot**, or indirectly with **,**, **create** etc.) more memory than available in the dictionary, you get a -8 **throw** (Dictionary overflow). If you try to access memory beyond the end of the dictionary, the results are similar to stack overflows.

interpreting a word with undefined interpretation semantics:

Gforth defines interpretation semantics for all words; for words where the standard defines execution semantics (except **LEAVE**), the interpretation semantics are to perform the execution semantics. For words where the standard defines no interpretation semantics, but defined compilation semantics (plus **LEAVE**), the interpretation semantics are to perform the compilation semantics. Some words are marked as compile-only, and text-interpreting them gives a warning.

modifying the contents of the input buffer or a string literal:

These are located in writable memory and can be modified.

overflow of the pictured numeric output string:

-17 throw (Pictured numeric output string overflow).

parsed string overflow:

PARSE cannot overflow. **WORD** does not check for overflow.

producing a result out of range:

On two's complement machines, arithmetic is performed modulo $2^{\text{bits-per-cell}}$ for single arithmetic and $4^{\text{bits-per-cell}}$ for double arithmetic (with appropriate mapping for signed types). Division by zero typically results in a **-10 throw** (divide by zero) or **-55 throw** (floating point unidentified fault). Overflow on division may result in these errors or in **-11 throw** (result out of range). **Gforth-fast** may silently produce bogus results on division overflow or division by zero. **Convert** and **>number** currently overflow silently.

reading from an empty data or return stack:

The data stack is checked by the outer (aka text) interpreter after every word executed. If it has underflowed, a **-4 throw** (Stack underflow) is performed. Apart from that, stacks may be checked or not, depending on operating system, installation, and invocation. If they are caught by a check, they typically result in **-4 throw** (Stack underflow), **-6 throw** (Return stack underflow) or **-9 throw** (Invalid memory address), depending on the platform and which stack underflows and by how much. Note that even if the system uses checking (through the MMU), your program may have to underflow by a significant number of stack items to trigger the reaction (the reason for this is that the MMU, and therefore the checking, works with a page-size granularity). If there is no checking, the symptoms resulting from an underflow are similar to those from an overflow. Unbalanced return stack errors can result in a variety of symptoms, including **-9 throw** (Invalid memory address) and Illegal Instruction (typically **-260 throw**).

unexpected end of the input buffer, resulting in an attempt to use a zero-length string as a name:

Create and its descendants perform a **-16 throw** (Attempt to use zero-length string as a name). Words like **'** probably will not find what they search. Note that it is possible to create zero-length names with **nextname** (should it not?).

>IN *greater than input buffer:*

The next invocation of a parsing word returns a string with length 0.

RECURSE *appears after DOES>:*

Compiles a recursive call to the code after **DOES>**.

*argument input source different than current input source for **RESTORE-INPUT**:*

-12 THROW. Note that, once an input file is closed (e.g., because the end of the file was reached), its source-id may be reused. Therefore, restoring an input source specification referencing a closed file may lead to unpredictable results instead of a **-12 THROW**.

In the future, Gforth may be able to restore input source specifications from other than the current input source.

data space containing definitions gets de-allocated:

Deallocation with **allot** is not checked. This typically results in memory access faults or execution of illegal instructions.

data space read/write with incorrect alignment:

Processor-dependent. Typically results in a **-23 throw** (Address alignment exception). Under Linux-Intel on a 486 or later processor with alignment turned on, incorrect alignment results in a **-9 throw** (Invalid memory address). There are reportedly some processors with alignment restrictions that do not report violations.

*data space pointer not properly aligned, **,, C,:***

Like other alignment errors.

*less than $u+2$ stack items (**PICK** and **ROLL**):*

Like other stack underflows.

loop control parameters not available:

Not checked. The counted loop words simply assume that the top of return stack items are loop control parameters and behave accordingly.

*most recent definition does not have a name (**IMMEDIATE**):*

abort " last word was headerless".

*name not defined by **VALUE** used by **TO**:*

-32 throw (Invalid name argument) (unless name is a local or was defined by **CONSTANT**; in the latter case it just changes the constant).

*name not found (**'**, **POSTPONE**, **[']**, **[COMPILE]**):*

-13 throw (Undefined word)

*parameters are not of the same type (**DO**, **?DO**, **WITHIN**):*

Gforth behaves as if they were of the same type. I.e., you can predict the behaviour by interpreting all parameters as, e.g., signed.

POSTPONE or **[COMPILE]** applied to **TO**:

Assume **: X POSTPONE TO ; IMMEDIATE**. X performs the compilation semantics of **TO**.

*String longer than a counted string returned by **WORD**:*

Not checked. The string will be ok, but the count will, of course, contain only the least significant bits of the length.

*u greater than or equal to the number of bits in a cell (**LSHIFT**, **RSHIFT**):*

Processor-dependent. Typical behaviours are returning 0 and using only the low bits of the shift count.

word not defined via CREATE:

>BODY produces the PFA of the word no matter how it was defined.

DOES> changes the execution semantics of the last defined word no matter how it was defined. E.g., CONSTANT DOES> is equivalent to CREATE , DOES>.

words improperly used outside <# and #>:

Not checked. As usual, you can expect memory faults.

9.1.3 Other system documentation

nonstandard words using PAD:

None.

operator's terminal facilities available:

After processing the OS's command line, Gforth goes into interactive mode, and you can give commands to Gforth interactively. The actual facilities available depend on how you invoke Gforth.

program data space available:

UNUSED . gives the remaining dictionary space. The total dictionary space can be specified with the -m switch (see Section 2.1 [Invoking Gforth], page 3) when Gforth starts up.

return stack space available:

You can compute the total return stack space in cells with s" RETURN-STACK-CELLS" environment? drop .. You can specify it at startup time with the -r switch (see Section 2.1 [Invoking Gforth], page 3).

stack space available:

You can compute the total data stack space in cells with s" STACK-CELLS" environment? drop .. You can specify it at startup time with the -d switch (see Section 2.1 [Invoking Gforth], page 3).

system dictionary space required, in address units:

Type here forthstart - . after startup. At the time of this writing, this gives 80080 (bytes) on a 32-bit system.

9.2 The optional Block word set

9.2.1 Implementation Defined Options

the format for display by LIST:

First the screen number is displayed, then 16 lines of 64 characters, each line preceded by the line number.

the length of a line affected by \:

64 characters.

9.2.2 Ambiguous conditions

correct block read was not possible:

Typically results in a **throw** of some OS-derived value (between -512 and -2048). If the blocks file was just not long enough, blanks are supplied for the missing portion.

I/O exception in block transfer:

Typically results in a **throw** of some OS-derived value (between -512 and -2048).

invalid block number:

-35 throw (Invalid block number)

a program directly alters the contents of BLK:

The input stream is switched to that other block, at the same position. If the storing to BLK happens when interpreting non-block input, the system will get quite confused when the block ends.

no current block buffer for UPDATE:

UPDATE has no effect.

9.2.3 Other system documentation

any restrictions a multiprogramming system places on the use of buffer addresses:

No restrictions (yet).

the number of blocks available for source and data:

depends on your disk space.

9.3 The optional Double Number word set

9.3.1 Ambiguous conditions

d outside of range of n in D>S:

The least significant cell of *d* is produced.

9.4 The optional Exception word set

9.4.1 Implementation Defined Options

THROW-codes used in the system:

The codes -256--511 are used for reporting signals. The mapping from OS signal numbers to throw codes is -256--*signal*. The codes -512--2047 are used for OS errors (for file and memory allocation operations). The mapping from OS error numbers to throw codes is -512--**errno**. One side effect of this mapping is that undefined OS errors produce a message with a strange number; e.g., -1000 THROW results in **Unknown error 488** on my system.

9.5 The optional Facility word set

9.5.1 Implementation Defined Options

encoding of keyboard events (EKEY):

Keys corresponding to ASCII characters are encoded as ASCII characters. Other keys are encoded with the constants `k-left`, `k-right`, `k-up`, `k-down`, `k-home`, `k-end`, `k1`, `k2`, `k3`, `k4`, `k5`, `k6`, `k7`, `k8`, `k9`, `k10`, `k11`, `k12`, `k-winch`, `k-eof`.

duration of a system clock tick:

System dependent. With respect to `MS`, the time is specified in microseconds. How well the OS and the hardware implement this, is another question.

repeatability to be expected from the execution of MS:

System dependent. On Unix, a lot depends on load. If the system is lightly loaded, and the delay is short enough that Gforth does not get swapped out, the performance should be acceptable. Under MS-DOS and other single-tasking systems, it should be good.

9.5.2 Ambiguous conditions

AT-XY can't be performed on user output device:

Largely terminal dependent. No range checks are done on the arguments. No errors are reported. You may see some garbage appearing, you may see simply nothing happen.

9.6 The optional File-Access word set

9.6.1 Implementation Defined Options

file access methods used:

`R/O`, `R/W` and `BIN` work as you would expect. `W/O` translates into the C file opening mode `w` (or `wb`): The file is cleared, if it exists, and created, if it does not (with both `open-file` and `create-file`). Under Unix `create-file` creates a file with 666 permissions modified by your `umask`.

file exceptions:

The file words do not raise exceptions (except, perhaps, memory access faults when you pass illegal addresses or file-ids).

file line terminator:

System-dependent. Gforth uses C's newline character as line terminator. What the actual character code(s) of this are is system-dependent.

file name format:

System dependent. Gforth just uses the file name format of your OS.

information returned by FILE-STATUS:

`FILE-STATUS` returns the most powerful file access mode allowed for the file: Either `R/O`, `W/O` or `R/W`. If the file cannot be accessed, `R/O BIN` is returned. `BIN` is applicable along with the returned mode.

input file state after an exception when including source:

All files that are left via the exception are closed.

ior values and meaning:

The *iors* returned by the file and memory allocation words are intended as throw codes. They typically are in the range -512--2047 of OS errors. The mapping from OS error numbers to *iors* is -512-*errno*.

maximum depth of file input nesting:

limited by the amount of return stack, locals/TIB stack, and the number of open files available. This should not give you troubles.

maximum size of input line:

/line. Currently 255.

methods of mapping block ranges to files:

By default, blocks are accessed in the file `blocks.fb` in the current working directory. The file can be switched with `USE`.

number of string buffers provided by S":

As many as memory available; the strings are stored in memory blocks allocated with `ALLOCATE` indefinitely.

size of string buffer used by S":

/line. currently 255.

9.6.2 Ambiguous conditions

attempting to position a file outside its boundaries:

`REPOSITION-FILE` is performed as usual: Afterwards, `FILE-POSITION` returns the value given to `REPOSITION-FILE`.

attempting to read from file positions not yet written:

End-of-file, i.e., zero characters are read and no error is reported.

file-id is invalid (INCLUDE-FILE):

An appropriate exception may be thrown, but a memory fault or other problem is more probable.

I/O exception reading or closing file-id (INCLUDE-FILE, INCLUDED):

The *ior* produced by the operation, that discovered the problem, is thrown.

named file cannot be opened (INCLUDED):

The *ior* produced by `open-file` is thrown.

requesting an unmapped block number:

There are no unmapped legal block numbers. On some operating systems, writing a block with a large number may overflow the file system and have an error message as consequence.

using source-id when blk is non-zero:

`source-id` performs its function. Typically it will give the id of the source which loaded the block. (Better ideas?)

9.7 The optional Floating-Point word set

9.7.1 Implementation Defined Options

format and range of floating point numbers:

System-dependent; the `double` type of C.

results of `REPRESENT` when float is out of range:

System dependent; `REPRESENT` is implemented using the C library function `ecvt()` and inherits its behaviour in this respect.

rounding or truncation of floating-point numbers:

System dependent; the rounding behaviour is inherited from the hosting C compiler. IEEE-FP-based (i.e., most) systems by default round to nearest, and break ties by rounding to even (i.e., such that the last bit of the mantissa is 0).

size of floating-point stack:

`s" FLOATING-STACK" environment? drop .` gives the total size of the floating-point stack (in floats). You can specify this on startup with the command-line option `-f` (see Section 2.1 [Invoking Gforth], page 3).

width of floating-point stack:

1 floats.

9.7.2 Ambiguous conditions

`df@` or `df!` used with an address that is not double-float aligned:

System-dependent. Typically results in a `-23 THROW` like other alignment violations.

`f@` or `f!` used with an address that is not float aligned:

System-dependent. Typically results in a `-23 THROW` like other alignment violations.

floating-point result out of range:

System-dependent. Can result in a `-43 throw` (floating point overflow), `-54 throw` (floating point underflow), `-41 throw` (floating point inexact result), `-55 THROW` (Floating-point unidentified fault), or can produce a special value representing, e.g., Infinity.

`sf@` or `sf!` used with an address that is not single-float aligned:

System-dependent. Typically results in an alignment fault like other alignment violations.

`base` is not decimal (`REPRESENT`, `F.`, `FE.`, `FS.`):

The floating-point number is converted into decimal nonetheless.

Both arguments are equal to zero (`FATAN2`):

System-dependent. `FATAN2` is implemented using the C library function `atan2()`.

Using `FTAN` on an argument `r1` where $\cos(r1)$ is zero:

System-dependent. Anyway, typically the \cos of `r1` will not be zero because of small errors and the \tan will be a very large (or very small) but finite number.

`d` cannot be presented precisely as a float in `D>F`:

The result is rounded to the nearest float.

dividing by zero:

Platform-dependent; can produce an Infinity, NaN, **-42 throw** (floating point divide by zero) or **-55 throw** (Floating-point unidentified fault).

exponent too big for conversion (DF!, DF@, SF!, SF@):

System dependent. On IEEE-FP based systems the number is converted into an infinity.

float<1 (FACOSH):

Platform-dependent; on IEEE-FP systems typically produces a NaN.

float<=-1 (FLNP1):

Platform-dependent; on IEEE-FP systems typically produces a NaN (or a negative infinity for *float=-1*).

float<=0 (FLN, FLOG):

Platform-dependent; on IEEE-FP systems typically produces a NaN (or a negative infinity for *float=0*).

float<0 (FASINH, FSQRT):

Platform-dependent; for **fsqrt** this typically gives a NaN, for **fasinh** some platforms produce a NaN, others a number (bug in the C library?).

|float|>1 (FACOS, FASIN, FATANH):

Platform-dependent; IEEE-FP systems typically produce a NaN.

integer part of float cannot be represented by d in F>D:

Platform-dependent; typically, some double number is produced and no error is reported.

string larger than pictured numeric output area (f., fe., fs.):

Precision characters of the numeric output area are used. If **precision** is too high, these words will smash the data or code close to **here**.

9.8 The optional Locals word set

9.8.1 Implementation Defined Options

maximum number of locals in a definition:

s" #locals" environment? drop .. Currently 15. This is a lower bound, e.g., on a 32-bit machine there can be 41 locals of up to 8 characters. The number of locals in a definition is bounded by the size of locals-buffer, which contains the names of the locals.

9.8.2 Ambiguous conditions

executing a named local in interpretation state:

Compiles the local into the current definition (just as in compile state); in addition text-interpreting a local in interpretation state gives an “is compile-only” warning.

name not defined by VALUE or (LOCAL) (TO):

-32 throw (Invalid name argument)

9.9 The optional Memory-Allocation word set

9.9.1 Implementation Defined Options

values and meaning of ior:

The *iors* returned by the file and memory allocation words are intended as throw codes. They typically are in the range -512--2047 of OS errors. The mapping from OS error numbers to *iors* is -512--*errno*.

9.10 The optional Programming-Tools word set

9.10.1 Implementation Defined Options

ending sequence for input following ;CODE and CODE:

END-CODE

manner of processing input following ;CODE and CODE:

The ASSEMBLER vocabulary is pushed on the search order stack, and the input is processed by the text interpreter, (starting) in interpret state.

search order capability for EDITOR and ASSEMBLER:

The Search-Order word set.

source and format of display by SEE:

The source for **see** is the executable code used by the inner interpreter. The current **see** tries to output Forth source code (and on some platforms, assembly code for primitives) as well as possible.

9.10.2 Ambiguous conditions

deleting the compilation word list (FORGET):

Not implemented (yet).

fewer than u+1 items on the control-flow stack (CS-PICK, CS-ROLL):

This typically results in an **abort** with a descriptive error message (may change into a -22 **throw** (Control structure mismatch) in the future). You may also get a memory access error. If you are unlucky, this ambiguous condition is not caught.

name can't be found (FORGET):

Not implemented (yet).

name not defined via CREATE:

;CODE behaves like DOES> in this respect, i.e., it changes the execution semantics of the last defined word no matter how it was defined.

POSTPONE *applied to [IF]:*

After defining : X **POSTPONE** [IF] ; IMMEDIATE. X is equivalent to [IF].

reaching the end of the input source before matching [ELSE] or [THEN]:

Continue in the same state of conditional compilation in the next outer input source. Currently there is no warning to the user about this.

removing a needed definition (FORGET):
Not implemented (yet).

9.11 The optional Search-Order word set

9.11.1 Implementation Defined Options

maximum number of word lists in search order:
`s" wordlists" environment? drop ..` Currently 16.

minimum search order:
`root root.`

9.11.2 Ambiguous conditions

changing the compilation word list (during compilation):
The word is entered into the word list that was the compilation word list at the start of the definition. Any changes to the name field (e.g., `immediate`) or the code field (e.g., when executing `DOES>`) are applied to the latest defined word (as reported by `latest` or `latesttxt`), if possible, irrespective of the compilation word list.

search order empty (previous):
`abort" Vocstack empty".`

too many word lists in search order (also):
`abort" Vocstack full".`

10 Should I use Gforth extensions?

As you read through the rest of this manual, you will see documentation for *Standard* words, and documentation for some appealing Gforth *extensions*. You might ask yourself the question: “*Should I restrict myself to the standard, or should I use the extensions?*”

The answer depends on the goals you have for the program you are working on:

- Is it just for yourself or do you want to share it with others?
- If you want to share it, do the others all use Gforth?
- If it is just for yourself, do you want to restrict yourself to Gforth?

If restricting the program to Gforth is ok, then there is no reason not to use extensions. It is still a good idea to keep to the standard where it is easy, in case you want to reuse these parts in another program that you want to be portable.

If you want to be able to port the program to other Forth systems, there are the following points to consider:

- Most Forth systems that are being maintained support Standard Forth. So if your program complies with the standard, it will be portable among many systems.
- A number of the Gforth extensions can be implemented in Standard Forth using public-domain files provided in the `compat/` directory. These are mentioned in the text in passing. There is no reason not to use these extensions, your program will still be Standard Forth compliant; just include the appropriate `compat` files with your program.
- The tool `ans-report.fs` (see Section 8.1 [Standard Report], page 238) makes it easy to analyse your program and determine what non-Standard words it relies upon. However, it does not check whether you use standard words in a non-standard way.
- Some techniques are not standardized by Standard Forth, and are hard or impossible to implement in a standard way, but can be implemented in most Forth systems easily, and usually in similar ways (e.g., accessing word headers). Forth has a rich historical precedent for programmers taking advantage of implementation-dependent features of their tools (for example, relying on a knowledge of the dictionary structure). Sometimes these techniques are necessary to extract every last bit of performance from the hardware, sometimes they are just a programming shorthand.
- Does using a Gforth extension save more work than the porting this part to other Forth systems (if any) will cost?
- Is the additional functionality worth the reduction in portability and the additional porting problems?

In order to perform these considerations, you need to know what’s standard and what’s not. This manual generally states if something is non-standard, but the authoritative source is the standard document (<https://forth-standard.org/standard/words>). Appendix A of the Standard (*Rationale*) provides a valuable insight into the thought processes of the technical committee.

Note also that portability between Forth systems is not the only portability issue; there is also the issue of portability between different platforms (processor/OS combinations).

11 Model

This chapter has yet to be written. It will contain information, on which internal structures you can rely.

12 Integrating Gforth into C programs

Several people like to use Forth as scripting language for applications that are otherwise written in C, C++, or some other language.

The Forth system ATLAST provides facilities for embedding it into applications; unfortunately it has several disadvantages: most importantly, it is not based on Standard Forth, and it is apparently dead (i.e., not developed further and not supported). The facilities provided by Gforth in this area are inspired by ATLAST's facilities, so making the switch should not be hard.

We also tried to design the interface such that it can easily be implemented by other Forth systems, so that we may one day arrive at a standardized interface. Such a standard interface would allow you to replace the Forth system without having to rewrite C code.

You embed the Gforth interpreter by linking with the library `libgforth.a` or `libgforth.so` (give the compiler the option `-lgforth`, or for one of the other engines `-lgforth-fast`, `-lgforth-itc`, or `-lgforth-ditc`). All global symbols in this library that belong to the interface, have the prefix `gforth_`; if a common interface emerges, the functions may also be available through `#defines` with the prefix `forth_`.

You can include the declarations of Forth types, the functions and variables of the interface with `#include <gforth.h>`.

You can now run a Gforth session by either calling `gforth_main` or using the components:

```
Cell gforth_main(int argc, char **argv, char **env)
{
    Cell retvalue=gforth_start(argc, argv);

    if(retvalue == -56) { /* throw-code for quit */
        gforth_setwinch();          // set winch signal handler
        gforth_bootmessage();       // show boot message
        retvalue = gforth_quit();   // run quit loop
    }
    gforth_cleanup();
    gforth_printmetrics();
    // gforth_free_dict(); // if you want to restart, do this

    return retvalue;
}
```

To interact with the Forth interpreter, there's `Xt gforth_find(Char * name)` and `Cell gforth_execute(Xt xt)`.

More documentation needs to be put here.

12.1 Types

`Cell`, `UCell`: data stack elements.

`Float`: float stack element.

`Address`, `Xt`, `Label`: pointer typies to memory, Forth words, and Forth instructions inside the VM.

12.2 Variables

Data and FP Stack pointer. Area sizes. Accessing the Stacks

`gforth_SP`, `gforth_FP`.

12.3 Functions

```
void *gforth_engine(Xt *, stackpointers *);
Cell gforth_main(int argc, char **argv, char **env);
int gforth_args(int argc, char **argv, char **path, char **imagename);
ImageHeader* gforth_loader(char* imagename, char* path);
user_area* gforth_stacks(Cell dsize, Cell rsize, Cell fsize, Cell lsize);
void gforth_free_stacks(user_area* t);
void gforth_setstacks(user_area * t);
void gforth_free_dict();
Cell gforth_go(Xt* ip0);
Cell gforth_boot(int argc, char** argv, char* path);
void gforth_bootmessage();
Cell gforth_start(int argc, char ** argv);
Cell gforth_quit();
Xt gforth_find(Char * name);
Cell gforth_execute(Xt xt);
void gforth_cleanup();
void gforth_printmetrics();
void gforth_setwinch();
```

12.4 Signals

Gforth sets up signal handlers to catch exceptions and window size changes. This may interfere with your C program.

13 Emacs and Gforth

Gforth comes with `gforth.el`, an improved version of `forth.el` by Goran Rydqvist (included in the TILE package). The improvements are:

- A better handling of indentation.
- A custom highlighting engine for Forth-code.
- Comment paragraph filling (*M-q*)
- Commenting (*C-x *) and uncommenting (*C-u C-x *) of regions
- Removal of debugging tracers (*C-x ~*, see Section 6.25.8 [Debugging], page 202).
- Support of the `info-lookup` feature for looking up the documentation of a word.
- Support for reading and writing blocks files.

To get a basic description of these features, enter Forth mode and type *C-h m*.

In addition, Gforth supports Emacs quite well: The source code locations given in error messages, debugging output (from *~~*) and failed assertion messages are in the right format for Emacs' compilation mode (see Section "Running Compilations under Emacs" in *Emacs Manual*) so the source location corresponding to an error or other message is only a few keystrokes away (*C-x '* for the next error, *C-c C-c* for the error under the cursor).

Moreover, for words documented in this manual, you can look up the glossary entry quickly by using *C-h TAB* (`info-lookup-symbol`, see Section "Documentation Commands" in *Emacs Manual*). This feature requires Emacs 20.3 or later and does not work for words containing `:`.

13.1 Installing gforth.el

To make the features from `gforth.el` available in Emacs, add the following lines to your `.emacs` file:

```
(autoload 'forth-mode "gforth.el")
(setq auto-mode-alist (cons '("\\.fs\\'" . forth-mode)
  auto-mode-alist))
(autoload 'forth-block-mode "gforth.el")
(setq auto-mode-alist (cons '("\\.fb\\'" . forth-block-mode)
  auto-mode-alist))
(add-hook 'forth-mode-hook (function (lambda ()
  ;; customize variables here:
  (setq forth-indent-level 4)
  (setq forth-minor-indent-level 2)
  (setq forth-highlight-level 3)
  ;;; ...
)))
```

13.2 Emacs Tags

If you require `etags.fs`, a new TAGS file will be produced (see Section "Tags Tables" in *Emacs Manual*) that contains the definitions of all words defined afterwards. You can then find the source for a word using *M-..* Note that Emacs can use several tags

files at the same time (e.g., one for the Gforth sources and one for your program, see Section “Selecting a Tags Table” in *Emacs Manual*). The TAGS file for the preloaded words is `$(datadir)/gforth/$(VERSION)/TAGS` (e.g., `/usr/local/share/gforth/0.2.0/TAGS`). To get the best behaviour with `etags.fs`, you should avoid putting definitions both before and after `require etc.`, otherwise you will see the same file visited several times by commands like `tags-search`.

13.3 Hilighting

`gforth.el` comes with a custom source hilighting engine. When you open a file in `forth-mode`, it will be completely parsed, assigning faces to keywords, comments, strings etc. While you edit the file, modified regions get parsed and updated on-the-fly.

Use the variable ‘`forth-highlight-level`’ to change the level of decoration from 0 (no hilighting at all) to 3 (the default). Even if you set the hilighting level to 0, the parser will still work in the background, collecting information about whether regions of text are “compiled” or “interpreted”. Those information are required for auto-indentation to work properly. Set ‘`forth-disable-parser`’ to non-nil if your computer is too slow to handle parsing. This will have an impact on the smartness of the auto-indentation engine, though.

Sometimes Forth sources define new features that should be hilighted, new control structures, defining-words etc. You can use the variable ‘`forth-custom-words`’ to make `forth-mode` hilight additional words and constructs. See the docstring of ‘`forth-words`’ for details (in Emacs, type `C-h v forth-words`).

‘`forth-custom-words`’ is meant to be customized in your `.emacs` file. To customize hilighting in a file-specific manner, set ‘`forth-local-words`’ in a local-variables section at the end of your source file (see Section “Variables” in *Emacs Manual*).

Example:

```
0 [IF]
  Local Variables:
  forth-local-words:
    (((("t:") definition-starter (font-lock-keyword-face . 1)
        "[ \t\n]" t name (font-lock-function-name-face . 3))
      ((";t") definition-ender (font-lock-keyword-face . 1)))
  End:
[THEN]
```

13.4 Auto-Indentation

`forth-mode` automatically tries to indent lines in a smart way, whenever you type `TAB` or break a line with `C-m`.

Simple customization can be achieved by setting ‘`forth-indent-level`’ and ‘`forth-minor-indent-level`’ in your `.emacs` file. For historical reasons `gforth.el` indents per default by multiples of 4 columns. To use the more traditional 3-column indentation, add the following lines to your `.emacs`:

```
(add-hook 'forth-mode-hook (function (lambda ()
;; customize variables here:
(setq forth-indent-level 3)
```

```
(setq forth-minor-indent-level 1)
)))
```

If you want indentation to recognize non-default words, customize it by setting ‘forth-custom-indent-words’ in your `.emacs`. See the docstring of ‘forth-indent-words’ for details (in Emacs, type `C-h v forth-indent-words`).

To customize indentation in a file-specific manner, set ‘forth-local-indent-words’ in a local-variables section at the end of your source file (see Section “Local Variables in Files” in *Emacs Manual*).

Example:

```
0 [IF]
  Local Variables:
  forth-local-indent-words:
    (((("t:") (0 . 2) (0 . 2))
      ((";t") (-2 . 0) (0 . -2)))
  End:
[THEN]
```

13.5 Blocks Files

`forth-mode` Autodetects blocks files by checking whether the length of the first line exceeds 1023 characters. It then tries to convert the file into normal text format. When you save the file, it will be written to disk as normal stream-source file.

If you want to write blocks files, use `forth-blocks-mode`. It inherits all the features from `forth-mode`, plus some additions:

- Files are written to disk in blocks file format.
- Screen numbers are displayed in the mode line (enumerated beginning with the value of ‘forth-block-base’)
- Warnings are displayed when lines exceed 64 characters.
- The beginning of the currently edited block is marked with an overlay-arrow.

There are some restrictions you should be aware of. When you open a blocks file that contains tabulator or newline characters, these characters will be translated into spaces when the file is written back to disk. If tabs or newlines are encountered during blocks file reading, an error is output to the echo area. So have a look at the ‘*Messages*’ buffer, when Emacs’ bell rings during reading.

Please consult the docstring of `forth-blocks-mode` for more information by typing `C-h v forth-blocks-mode`).

14 Image Files

An image file is a file containing an image of the Forth dictionary, i.e., compiled Forth code and data residing in the dictionary. By convention, we use the extension `.fi` for image files.

14.1 Image Licensing Issues

An image created with `gforthmi` (see Section 14.5.1 [gforthmi], page 264) or `savesystem` (see Section 14.3 [Non-Relocatable Image Files], page 263) includes the original image; i.e., according to copyright law it is a derived work of the original image.

Since Gforth is distributed under the GNU GPL, the newly created image falls under the GNU GPL, too. In particular, this means that if you distribute the image, you have to make all of the sources for the image available, including those you wrote. For details see Section D.2 [GNU General Public License (Section 3)], page 291.

If you create an image with `cross` (see Section 14.5.2 [cross.fs], page 265), the image contains only code compiled from the sources you gave it; if none of these sources is under the GPL, the terms discussed above do not apply to the image. However, if your image needs an engine (a gforth binary) that is under the GPL, you should make sure that you distribute both in a way that is at most a *mere aggregation*, if you don't want the terms of the GPL to apply to the image.

14.2 Image File Background

Gforth consists not only of primitives (in the engine), but also of definitions written in Forth. Since the Forth compiler itself belongs to those definitions, it is not possible to start the system with the engine and the Forth source alone. Therefore we provide the Forth code as an image file in nearly executable form. When Gforth starts up, a C routine loads the image file into memory, optionally relocates the addresses, then sets up the memory (stacks etc.) according to information in the image file, and (finally) starts executing Forth code.

The default image file is `gforth.fi` (in the `GFORTHPATH`). You can use a different image by using the `-i`, `--image-file` or `--appl-image` options (see Section 2.1 [Invoking Gforth], page 3), e.g.:

```
gforth-fast -i myimage.fi
```

There are different variants of image files, and they represent different compromises between the goals of making it easy to generate image files and making them portable.

Win32Forth 3.4 and Mitch Bradley's `cforth` use relocation at run-time. This avoids many of the complications discussed below (image files are data relocatable without further ado), but costs performance (one addition per memory access) and makes it difficult to pass addresses between Forth and library calls or other programs.

By contrast, the Gforth loader performs relocation at image load time. The loader also has to replace tokens that represent primitive calls with the appropriate code-field addresses (or code addresses in the case of direct threading).

There are three kinds of image files, with different degrees of relocatability: non-relocatable, data-relocatable, and fully relocatable image files.

These image file variants have several restrictions in common; they are caused by the design of the image file loader:

- There is only one segment; in particular, this means, that an image file cannot represent **ALLOCATED** memory chunks (and pointers to them). The contents of the stacks are not represented, either.
- The only kinds of relocation supported are: adding the same offset to all cells that represent data addresses; and replacing special tokens with code addresses or with pieces of machine code.

If any complex computations involving addresses are performed, the results cannot be represented in the image file. Several applications that use such computations come to mind:

- Hashing addresses (or data structures which contain addresses) for table lookup. If you use Gforth's **tables** or **wordlists** for this purpose, you will have no problem, because the hash tables are recomputed automatically when the system is started. If you use your own hash tables, you will have to do something similar.
- There's a cute implementation of doubly-linked lists that uses **XORed** addresses. You could represent such lists as singly-linked in the image file, and restore the doubly-linked representation on startup.¹
- The code addresses of run-time routines like **docol:** cannot be represented in the image file (because their tokens would be replaced by machine code in direct threaded implementations). As a workaround, compute these addresses at run-time with **>code-address** from the executions tokens of appropriate words (see the definitions of **docol:** and friends in **kernel/getdoers.fs**).
- On many architectures addresses are represented in machine code in some shifted or mangled form. You cannot put **CODE** words that contain absolute addresses in this form in a relocatable image file. Workarounds are representing the address in some relative form (e.g., relative to the CFA, which is present in some register), or loading the address from a place where it is stored in a non-mangled form.

14.3 Non-Relocatable Image Files

These files are simple memory dumps of the dictionary. They are specific to the executable (i.e., **gforth** file) they were created with. What's worse, they are specific to the place on which the dictionary resided when the image was created. Now, there is no guarantee that the dictionary will reside at the same place the next time you start Gforth, so there's no guarantee that a non-relocatable image will work the next time (Gforth will complain instead of crashing, though). Indeed, on OSs with (enabled) address-space randomization non-relocatable images are unlikely to work.

You can create a non-relocatable image file with **savesystem**, e.g.:

```
gforth app.fs -e "savesystem app.fi bye"
savesystem ( "name" - ) gforth-0.2 "savesystem"
```

¹ In my opinion, though, you should think thrice before using a doubly-linked list (whatever implementation).

14.4 Data-Relocatable Image Files

These files contain relocatable data addresses, but fixed code addresses (instead of tokens). They are specific to the executable (i.e., `gforth` file) they were created with. Also, they disable dynamic native code generation (typically a factor of 2 in speed). You get a data-relocatable image, if you pass the engine you want to use through the `GFORTHHD` environment variable to `gforthmi` (see Section 14.5.1 [`gforthmi`], page 264), e.g.

```
GFORTHHD="/usr/bin/gforth-fast --no-dynamic" gforthmi myimage.fi source.fs
```

Note that the `--no-dynamic` is required here for the image to work (otherwise it will contain references to dynamically generated code that is not saved in the image).

14.5 Fully Relocatable Image Files

These image files have relocatable data addresses, and tokens for code addresses. They can be used with different binaries (e.g., with and without debugging) on the same machine, and even across machines with the same data formats (byte order, cell size, floating point format), and they work with dynamic native code generation. However, they are usually specific to the version of Gforth they were created with. The files `gforth.fi` and `kernl*.fi` are fully relocatable.

There are two ways to create a fully relocatable image file:

14.5.1 `gforthmi`

You will usually use `gforthmi`. If you want to create an image *file* that contains everything you would load by invoking Gforth with `gforth options`, you simply say:

```
gforthmi file options
```

E.g., if you want to create an image `asm.fi` that has the file `asm.fs` loaded in addition to the usual stuff, you could do it like this:

```
gforthmi asm.fi asm.fs
```

`gforthmi` is implemented as a sh script and works like this: It produces two non-relocatable images for different addresses and then compares them. Its output reflects this: first you see the output (if any) of the two Gforth invocations that produce the non-relocatable image files, then you see the output of the comparing program: It displays the offset used for data addresses and the offset used for code addresses; moreover, for each cell that cannot be represented correctly in the image files, it displays a line like this:

```
78DC          BFFFFA50          BFFFFA40
```

This means that at offset `$78dc` from `forthstart`, one input image contains `$bffffa50`, and the other contains `$bffffa40`. Since these cells cannot be represented correctly in the output image, you should examine these places in the dictionary and verify that these cells are dead (i.e., not read before they are written).

If you insert the option `--application` in front of the image file name, you will get an image that uses the `--appl-image` option instead of the `--image-file` option (see Section 2.1 [Invoking Gforth], page 3). When you execute such an image on Unix (by typing the image name as command), the Gforth engine will pass all options to the image instead of trying to interpret them as engine options.

If you type `gforthmi` with no arguments, it prints some usage instructions.

There are a few wrinkles: After processing the passed *options*, the words **savesystem** and **bye** must be visible. A special doubly indirect threaded version of the **gforth** executable is used for creating the non-relocatable images; you can pass the exact filename of this executable through the environment variable **GFORTH** (default: **gforth-ditc**); if you pass a version that is not doubly indirect threaded, you will not get a fully relocatable image, but a data-relocatable image (see Section 14.4 [Data-Relocatable Image Files], page 264), because there is no code address offset). The normal **gforth** executable is used for creating the relocatable image; you can pass the exact filename of this executable through the environment variable **GFORTH**.

14.5.2 cross.fs

You can also use **cross**, a batch compiler that accepts a Forth-like programming language (see Chapter 16 [Cross Compiler], page 277).

cross allows you to create image files for machines with different data sizes and data formats than the one used for generating the image file. You can also use it to create an application image that does not contain a Forth compiler. These features are bought with restrictions and inconveniences in programming. E.g., addresses have to be stored in memory with special words (**A!**, **A**, etc.) in order to make the code relocatable.

14.6 Stack and Dictionary Sizes

If you invoke Gforth with a command line flag for the size (see Section 2.1 [Invoking Gforth], page 3), the size you specify is stored in the dictionary. If you save the dictionary with **savesystem** or create an image with **gforthmi**, this size will become the default for the resulting image file. E.g., the following will create a fully relocatable version of **gforth.fi** with a 1MB dictionary:

```
gforthmi gforth.fi -m 1M
```

In other words, if you want to set the default size for the dictionary and the stacks of an image, just invoke **gforthmi** with the appropriate options when creating the image.

Note: For cache-friendly behaviour (i.e., good performance), you should make the sizes of the stacks modulo, say, 2K, somewhat different. E.g., the default stack sizes are: data: 16k (mod 2k=0); fp: 15.5k (mod 2k=1.5k); return: 15k(mod 2k=1k); locals: 14.5k (mod 2k=0.5k).

14.7 Running Image Files

You can invoke Gforth with an image file *image* instead of the default **gforth.fi** with the **-i** flag (see Section 2.1 [Invoking Gforth], page 3):

```
gforth -i image
```

If your operating system supports starting scripts with a line of the form **#! ...**, you just have to type the image file name to start Gforth with this image file (note that the file extension **.fi** is just a convention). I.e., to run Gforth with the image file *image*, you can just type *image* instead of **gforth -i image**. This works because every **.fi** file starts with a line of this format:

```
#! /usr/local/bin/gforth-0.4.0 -i
```

The file and pathname for the Gforth engine specified on this line is the specific Gforth executable that it was built against; i.e. the value of the environment variable `GFORTH` at the time that `gforthmi` was executed.

You can make use of the same shell capability to make a Forth source file into an executable. For example, if you place this text in a file:

```
#! /usr/local/bin/gforth

." Hello, world" CR
bye
```

and then make the file executable (`chmod +x` in Unix), you can run it directly from the command line. The sequence `#!` is used in two ways; firstly, it is recognised as a “magic sequence” by the operating system² secondly it is treated as a comment character by Gforth. Because of the second usage, a space is required between `#!` and the path to the executable (moreover, some Unixes require the sequence `#! /`).

Most Unix systems (including Linux) support exactly one option after the binary name. If that is not enough, you can use the following trick:

```
#! /bin/sh
: ## ; 0 [if]
exec gforth -m 10M -d 1M $0 "$@"
[then]
." Hello, world" cr
bye \ caution: this prevents (further) processing of "$@"
```

First this script is interpreted as shell script, which treats the first two lines as (mostly) comments, then performs the third line, which invokes `gforth` with this script (`$0`) as parameter and its parameters as additional parameters (`"$@"`). Then this script is interpreted as Forth script, which first defines a colon definition `##`, then ignores everything up to `[then]` and finally processes the following Forth code. You can also use

```
#0 [if]
```

in the second line, but this works only in Gforth-0.7.0 and later.

The `gforthmi` approach is the fastest one, the shell-based one is slowest (needs to start an additional shell). An additional advantage of the shell approach is that it is unnecessary to know where the Gforth binary resides, as long as it is in the `$PATH`.

`#! (-) gforth-0.2 “hash-bang”`

An alias for \

14.8 Modifying the Startup Sequence

You can add your own initialization to the startup sequence of an image through the deferred word `'cold`. `'cold` is invoked just before the image-specific command line processing (i.e., loading files and evaluating `(-e)` strings) starts.

² The Unix kernel actually recognises two types of files: executable files and files of data, where the data is processed by an interpreter that is specified on the “interpreter line” – the first line of the file, starting with the sequence `#!`. There may be a small limit (e.g., 32) on the number of characters that may be specified on the interpreter line.

A sequence for adding your initialization usually looks like this:

```
:noname
  Defers 'cold \ do other initialization stuff (e.g., rehashing wordlists)
  ... \ your stuff
; IS 'cold
```

After `'cold`, Gforth processes the image options (see Section 2.1 [Invoking Gforth], page 3), and then it performs `bootmessage`, another deferred word. This normally prints Gforth's startup message and does nothing else.

So, if you want to make a turnkey image (i.e., an image for an application instead of an extended Forth system), you can do this in two ways:

- If you want to do your interpretation of the OS command-line arguments, hook into `'cold`. In that case you probably also want to build the image with `gforthmi --application` (see Section 14.5.1 [gforthmi], page 264) to keep the engine from processing OS command line options. You can then do your own command-line processing with `next-arg`
- If you want to have the normal Gforth processing of OS command-line arguments, hook into `bootmessage`.

In either case, you probably do not want the word that you execute in these hooks to exit normally, but use `bye` or `throw`. Otherwise the Gforth startup process would continue and eventually present the Forth command line to the user.

`'cold` (-) gforth-0.2 “tick-cold”

Hook (deferred word) for things to do right before interpreting the OS command-line arguments. Normally does some initializations that you also want to perform.

`bootmessage` (-) gforth-0.4 “bootmessage”

Hook (deferred word) executed right after interpreting the OS command-line arguments. Normally prints the Gforth startup message.

15 Engine

Reading this chapter is not necessary for programming with Gforth. It may be helpful for finding your way in the Gforth sources.

The ideas in this section have also been published in the following papers: Bernd Paysan, *ANS fig/GNU/??? Forth* (in German), Forth-Tagung '93; M. Anton Ertl, *A Portable Forth Engine* (<https://www.complang.tuwien.ac.at/papers/ertl93.ps.Z>), EuroForth '93; M. Anton Ertl, *Threaded code variations and optimizations (extended version)* (<https://www.complang.tuwien.ac.at/papers/ertl02.ps.gz>), Forth-Tagung '02.

15.1 Portability

An important goal of the Gforth Project is availability across a wide range of personal machines. fig-Forth, and, to a lesser extent, F83, achieved this goal by manually coding the engine in assembly language for several then-popular processors. This approach is very labor-intensive and the results are short-lived due to progress in computer architecture.

Others have avoided this problem by coding in C, e.g., Mitch Bradley (cforth), Mikael Patel (TILE) and Dirk Zoller (pfe). This approach is particularly popular for UNIX-based Forths due to the large variety of architectures of UNIX machines. Unfortunately an implementation in C does not mix well with the goals of efficiency and with using traditional techniques: Indirect or direct threading cannot be expressed in C, and switch threading, the fastest technique available in C, is significantly slower. Another problem with C is that it is very cumbersome to express double integer arithmetic.

Fortunately, there is a portable language that does not have these limitations: GNU C, the version of C processed by the GNU C compiler (see Section “Extensions to the C Language Family” in *GNU C Manual*). Its labels as values feature (see Section “Labels as Values” in *GNU C Manual*) makes direct and indirect threading possible, its `long long` type (see Section “Double-Word Integers” in *GNU C Manual*) corresponds to Forth’s double numbers on many systems. GNU C is freely available on all important (and many unimportant) UNIX machines, VMS, 80386s running MS-DOS, the Amiga, and the Atari ST, so a Forth written in GNU C can run on all these machines.

Writing in a portable language has the reputation of producing code that is slower than assembly. For our Forth engine we repeatedly looked at the code produced by the compiler and eliminated most compiler-induced inefficiencies by appropriate changes in the source code.

However, register allocation cannot be portably influenced by the programmer, leading to some inefficiencies on register-starved machines. We use explicit register declarations (see Section “Variables in Specified Registers” in *GNU C Manual*) to improve the speed on some machines. They are turned on by using the configuration flag `--enable-force-reg` (gcc switch `-DFORCE_REG`). Unfortunately, this feature not only depends on the machine, but also on the compiler version: On some machines some compiler versions produce incorrect code when certain explicit register declarations are used. So by default `-DFORCE_REG` is not used.

15.2 Threading

GNU C’s labels as values extension (available since gcc-2.0, see Section “Labels as Values” in *GNU C Manual*) makes it possible to take the address of *label* by writing `&&label`. This

address can then be used in a statement like `goto *address`. I.e., `goto *&&x` is the same as `goto x`.

With this feature an indirect threaded NEXT looks like:

```
cfa = *ip++;
ca = *cfa;
goto *ca;
```

For those unfamiliar with the names: `ip` is the Forth instruction pointer; the `cfa` (code-field address) corresponds to Standard Forth's execution token and points to the code field of the next word to be executed; The `ca` (code address) fetched from there points to some executable code, e.g., a primitive or the colon definition handler `docol`.

Direct threading is even simpler:

```
ca = *ip++;
goto *ca;
```

Of course we have packaged the whole thing neatly in macros called `NEXT` and `NEXT1` (the part of `NEXT` after fetching the `cfa`).

15.2.1 Scheduling

There is a little complication: Pipelined and superscalar processors, i.e., RISC and some modern CISC machines can process independent instructions while waiting for the results of an instruction. The compiler usually reorders (schedules) the instructions in a way that achieves good usage of these delay slots. However, on our first tries the compiler did not do well on scheduling primitives. E.g., for `+` implemented as

```
n=sp[0]+sp[1];
sp++;
sp[0]=n;
NEXT;
```

the `NEXT` comes strictly after the other code, i.e., there is nearly no scheduling. After a little thought the problem becomes clear: The compiler cannot know that `sp` and `ip` point to different addresses (and the version of `gcc` we used would not know it even if it was possible), so it could not move the load of the `cfa` above the store to the TOS. Indeed the pointers could be the same, if code on or very near the top of stack were executed. In the interest of speed we chose to forbid this probably unused “feature” and helped the compiler in scheduling: `NEXT` is divided into several parts: `NEXT_P0`, `NEXT_P1` and `NEXT_P2`). `+` now looks like:

```
NEXT_P0;
n=sp[0]+sp[1];
sp++;
NEXT_P1;
sp[0]=n;
NEXT_P2;
```

There are various schemes that distribute the different operations of `NEXT` between these parts in several ways; in general, different schemes perform best on different processors. We use a scheme for most architectures that performs well for most processors of this architecture; in the future we may switch to benchmarking and choosing the scheme on installation time.

15.2.2 Direct or Indirect Threaded?

Threaded forth code consists of references to primitives (simple machine code routines like `+`) and to non-primitives (e.g., colon definitions, variables, constants); for a specific class of non-primitives (e.g., variables) there is one code routine (e.g., `dovar`), but each variable needs a separate reference to its data.

Traditionally Forth has been implemented as indirect threaded code, because this allows to use only one cell to reference a non-primitive (basically you point to the data, and find the code address there).

However, threaded code in Gforth (since 0.6.0) uses two cells for non-primitives, one for the code address, and one for the data address; the data pointer is an immediate argument for the virtual machine instruction represented by the code address. We call this *primitive-centric* threaded code, because all code addresses point to simple primitives. E.g., for a variable, the code address is for `lit` (also used for integer literals like `99`).

Primitive-centric threaded code allows us to use (faster) direct threading as dispatch method, completely portably (direct threaded code in Gforth before 0.6.0 required architecture-specific code). It also eliminates the performance problems related to I-cache consistency that 386 implementations have with direct threaded code, and allows additional optimizations.

There is a catch, however: the `xt` parameter of `execute` can occupy only one cell, so how do we pass non-primitives with their code *and* data addresses to them? Our answer is to use indirect threaded dispatch for `execute` and other words that use a single-cell `xt`. So, normal threaded code in colon definitions uses direct threading, and `execute` and similar words, which dispatch to `xts` on the data stack, use indirect threaded code. We call this *hybrid direct/indirect* threaded code.

The engines `gforth` and `gforth-fast` use hybrid direct/indirect threaded code. This means that with these engines you cannot use `,` to compile an `xt`. Instead, you have to use `compile,.`

If you want to compile `xts` with `,`, use `gforth-itc`. This engine uses plain old indirect threaded code. It still compiles in a primitive-centric style, so you cannot use `compile,` instead of `,` (e.g., for producing tables of `xts` with `] word1 word2 ... [`). If you want to do that, you have to use `gforth-itc` and execute `' , is compile,.` Your program can check if it is running on a hybrid direct/indirect threaded engine or a pure indirect threaded engine with `threading-method` (see Section 6.29.3 [Threading Words], page 233).

15.2.3 Dynamic Superinstructions

The engines `gforth` and `gforth-fast` use another optimization: Dynamic superinstructions with replication. As an example, consider the following colon definition:

```
: squared ( n1 -- n2 )
  dup * ;
```

Gforth compiles this into the threaded code sequence

```
dup
*
;s
```

In normal direct threaded code there is a code address occupying one cell for each of these primitives. Each code address points to a machine code routine, and the interpreter

jumps to this machine code in order to execute the primitive. The routines for these three primitives are (in `gforth-fast` on the 386):

```
Code dup
( $804B950 ) add    esi , # -4 \ $83 $C6 $FC
( $804B953 ) add    ebx , # 4  \ $83 $C3 $4
( $804B956 ) mov     dword ptr 4 [esi] , ecx \ $89 $4E $4
( $804B959 ) jmp     dword ptr FC [ebx] \ $FF $63 $FC
end-code
Code *
( $804ACC4 ) mov     eax , dword ptr 4 [esi] \ $8B $46 $4
( $804ACC7 ) add     esi , # 4  \ $83 $C6 $4
( $804ACCA ) add     ebx , # 4  \ $83 $C3 $4
( $804ACCD ) imul    ecx , eax \ $F $AF $C8
( $804ACD0 ) jmp     dword ptr FC [ebx] \ $FF $63 $FC
end-code
Code ;s
( $804A693 ) mov     eax , dword ptr [edi] \ $8B $7
( $804A695 ) add     edi , # 4  \ $83 $C7 $4
( $804A698 ) lea     ebx , dword ptr 4 [eax] \ $8D $58 $4
( $804A69B ) jmp     dword ptr FC [ebx] \ $FF $63 $FC
end-code
```

With dynamic superinstructions and replication the compiler does not just lay down the threaded code, but also copies the machine code fragments, usually without the jump at the end.

```
( $4057D27D ) add    esi , # -4 \ $83 $C6 $FC
( $4057D280 ) add    ebx , # 4  \ $83 $C3 $4
( $4057D283 ) mov     dword ptr 4 [esi] , ecx \ $89 $4E $4
( $4057D286 ) mov     eax , dword ptr 4 [esi] \ $8B $46 $4
( $4057D289 ) add     esi , # 4  \ $83 $C6 $4
( $4057D28C ) add     ebx , # 4  \ $83 $C3 $4
( $4057D28F ) imul    ecx , eax \ $F $AF $C8
( $4057D292 ) mov     eax , dword ptr [edi] \ $8B $7
( $4057D294 ) add     edi , # 4  \ $83 $C7 $4
( $4057D297 ) lea     ebx , dword ptr 4 [eax] \ $8D $58 $4
( $4057D29A ) jmp     dword ptr FC [ebx] \ $FF $63 $FC
```

Only when a threaded-code control-flow change happens (e.g., in `;s`), the jump is appended. This optimization eliminates many of these jumps and makes the rest much more predictable. The speedup depends on the processor and the application; on the Athlon and Pentium III this optimization typically produces a speedup by a factor of 2.

The code addresses in the direct-threaded code are set to point to the appropriate points in the copied machine code, in this example like this:

```
primitive  code address
dup        $4057D27D
*          $4057D286
;s         $4057D292
```

Thus there can be threaded-code jumps to any place in this piece of code. This also simplifies decompilation quite a bit.

You can disable this optimization with `--no-dynamic`. You can use the copying without eliminating the jumps (i.e., dynamic replication, but without superinstructions) with `--no-super`; this gives the branch prediction benefit alone; the effect on performance depends on the CPU; on the Athlon and Pentium III the speedup is a little less than for dynamic superinstructions with replication.

One use of these options is if you want to patch the threaded code. With superinstructions, many of the dispatch jumps are eliminated, so patching often has no effect. These options preserve all the dispatch jumps.

On some machines dynamic superinstructions are disabled by default, because it is unsafe on these machines. However, if you feel adventurous, you can enable it with `--dynamic`.

15.2.4 DOES>

One of the most complex parts of a Forth engine is `dodoes`, i.e., the chunk of code executed by every word defined by a `CREATE...DOES>` pair; actually with primitive-centric code, this is only needed if the xt of the word is `executed`. The main problem here is: How to find the Forth code to be executed, i.e. the code after the `DOES>` (the `DOES>`-code)? There are two solutions:

In fig-Forth the code field points directly to the `dodoes` and the `DOES>`-code address is stored in the cell after the code address (i.e. at `CFA cell+`). It may seem that this solution is illegal in the Forth-79 and all later standards, because in fig-Forth this address lies in the body (which is illegal in these standards). However, by making the code field larger for all words this solution becomes legal again. We use this approach. Leaving a cell unused in most words is a bit wasteful, but on the machines we are targeting this is hardly a problem.

15.3 Primitives

15.3.1 Automatic Generation

Since the primitives are implemented in a portable language, there is no longer any need to minimize the number of primitives. On the contrary, having many primitives has an advantage: speed. In order to reduce the number of errors in primitives and to make programming them easier, we provide a tool, the primitive generator (`prims2x.fs` aka `Vmgen`, see Section “Introduction” in `Vmgen`), that automatically generates most (and sometimes all) of the C code for a primitive from the stack effect notation. The source for a primitive has the following form:

```
Forth-name ( stack-effect )      category  [pronounc.]  
["glossary entry"]  
C code  
[:  
Forth code]
```

The items in brackets are optional. The category and glossary fields are there for generating the documentation, the Forth code is there for manual implementations on machines without GNU C. E.g., the source for the primitive `+` is:

```
+      ( n1 n2 -- n )    core    plus
```

```
n = n1+n2;
```

This looks like a specification, but in fact `n = n1+n2` is C code. Our primitive generation tool extracts a lot of information from the stack effect notations¹: The number of items popped from and pushed on the stack, their type, and by what name they are referred to in the C code. It then generates a C code prelude and postlude for each primitive. The final C code for `+` looks like this:

```
I_plus: /* + ( n1 n2 -- n ) */ /* label, stack effect */
/* */ /* documentation */
NAME("+") /* debugging output (with -DDEBUG) */
{
  DEF_CA /* definition of variable ca (indirect threading) */
  Cell n1; /* definitions of variables */
  Cell n2;
  Cell n;
  NEXT_P0; /* NEXT part 0 */
  n1 = (Cell) sp[1]; /* input */
  n2 = (Cell) TOS;
  sp += 1; /* stack adjustment */
  {
    n = n1+n2; /* C code taken from the source */
  }
  NEXT_P1; /* NEXT part 1 */
  TOS = (Cell)n; /* output */
  NEXT_P2; /* NEXT part 2 */
}
```

This looks long and inefficient, but the GNU C compiler optimizes quite well and produces optimal code for `+` on, e.g., the R3000 and the HP RISC machines: Defining the `ns` does not produce any code, and using them as intermediate storage also adds no cost.

There are also other optimizations that are not illustrated by this example: assignments between simple variables are usually for free (copy propagation). If one of the stack items is not used by the primitive (e.g. in `drop`), the compiler eliminates the load from the stack (dead code elimination). On the other hand, there are some things that the compiler does not do, therefore they are performed by `prims2x.fs`: The compiler does not optimize code away that stores a stack item to the place where it just came from (e.g., `over`).

While programming a primitive is usually easy, there are a few cases where the programmer has to take the actions of the generator into account, most notably `?dup`, but also words that do not (always) fall through to `NEXT`.

For more information

15.3.2 TOS Optimization

An important optimization for stack machine emulators, e.g., Forth engines, is keeping one or more of the top stack items in registers. If a word has the stack effect *in1...inx -- out1...outy*, keeping the top *n* items in registers

¹ We use a one-stack notation, even though we have separate data and floating-point stacks; The separate notation can be generated easily from the unified notation.

- is better than keeping $n-1$ items, if $x \geq n$ and $y \geq n$, due to fewer loads from and stores to the stack.
- is slower than keeping $n-1$ items, if $x < y$ and $x < n$ and $y < n$, due to additional moves between registers.

In particular, keeping one item in a register is never a disadvantage, if there are enough registers. Keeping two items in registers is a disadvantage for frequent words like `?branch`, constants, variables, literals and `i`. Therefore our generator only produces code that keeps zero or one items in registers. The generated C code covers both cases; the selection between these alternatives is made at C-compile time using the switch `-DUSE_TOS`. `TOS` in the C code for `+` is just a simple variable name in the one-item case, otherwise it is a macro that expands into `sp[0]`. Note that the GNU C compiler tries to keep simple variables like `TOS` in registers, and it usually succeeds, if there are enough registers.

The primitive generator performs the TOS optimization for the floating-point stack, too (`-DUSE_FTOS`). For floating-point operations the benefit of this optimization is even larger: floating-point operations take quite long on most processors, but can be performed in parallel with other operations as long as their results are not used. If the FP-TOS is kept in a register, this works. If it is kept on the stack, i.e., in memory, the store into memory has to wait for the result of the floating-point operation, lengthening the execution time of the primitive considerably.

The TOS optimization makes the automatic generation of primitives a bit more complicated. Just replacing all occurrences of `sp[0]` by `TOS` is not sufficient. There are some special cases to consider:

- In the case of `dup (w -- w w)` the generator must not eliminate the store to the original location of the item on the stack, if the TOS optimization is turned on.
- Primitives with stack effects of the form `-- out1...outy` must store the TOS to the stack at the start. Likewise, primitives with the stack effect `in1...inx --` must load the TOS from the stack at the end. But for the null stack effect `--` no stores or loads should be generated.

15.3.3 Produced code

To see what assembly code is produced for the primitives on your machine with your compiler and your flag settings, type `make engine.s` and look at the resulting file `engine.s`. Alternatively, you can also disassemble the code of primitives with `see` on some architectures.

15.4 Performance

On RISCs the Gforth engine is very close to optimal; i.e., it is usually impossible to write a significantly faster threaded-code engine.

On register-starved machines like the 386 architecture processors improvements are possible, because `gcc` does not utilize the registers as well as a human, even with explicit register declarations; e.g., Bernd Beuster wrote a Forth system fragment in assembly language and hand-tuned it for the 486; this system is 1.19 times faster on the Sieve benchmark on a 486DX2/66 than Gforth compiled with `gcc-2.6.3` with `-DFORCE_REG`. The situation has improved with `gcc-2.95` and `gforth-0.4.9`; now the most important virtual machine registers fit in real registers (and we can even afford to use the TOS optimization), resulting in a

speedup of 1.14 on the sieve over the earlier results. And dynamic superinstructions provide another speedup (but only around a factor 1.2 on the 486).

The potential advantage of assembly language implementations is not necessarily realized in complete Forth systems: We compared Gforth-0.5.9 (direct threaded, compiled with `gcc-2.95.1` and `-DFORCE_REG`) with Win32Forth 1.2093 (newer versions are reportedly much faster), LMI's NT Forth (Beta, May 1994) and Eforth (with and without peephole (aka pinhole) optimization of the threaded code); all these systems were written in assembly language. We also compared Gforth with three systems written in C: PFE-0.9.14 (compiled with `gcc-2.6.3` with the default configuration for Linux: `-O2 -fomit-frame-pointer -DUSE_REGS -DUNROLL_NEXT`), ThisForth Beta (compiled with `gcc-2.6.3 -O3 -fomit-frame-pointer`; ThisForth employs peephole optimization of the threaded code) and TILE (compiled with `make opt`). We benchmarked Gforth, PFE, ThisForth and TILE on a 486DX2/66 under Linux. Kenneth O'Heskin kindly provided the results for Win32Forth and NT Forth on a 486DX2/66 with similar memory performance under Windows NT. Marcel Hendrix ported Eforth to Linux, then extended it to run the benchmarks, added the peephole optimizer, ran the benchmarks and reported the results.

We used four small benchmarks: the ubiquitous Sieve; bubble-sorting and matrix multiplication come from the Stanford integer benchmarks and have been translated into Forth by Martin Fraeman; we used the versions included in the TILE Forth package, but with bigger data set sizes; and a recursive Fibonacci number computation for benchmarking calling performance. The following table shows the time taken for the benchmarks scaled by the time taken by Gforth (in other words, it shows the speedup factor that Gforth achieved over the other systems).

relative time	Gforth	Win32- Forth	NT Forth	eforth eforth	+opt	This- PFE Forth	TILE
sieve	1.00	2.16	1.78	2.16	1.32	2.46	4.96
bubble	1.00	1.93	2.07	2.18	1.29	2.21	5.70
matmul	1.00	1.92	1.76	1.90	0.96	2.06	5.32
fib	1.00	2.32	2.03	1.86	1.31	2.64	4.55

You may be quite surprised by the good performance of Gforth when compared with systems written in assembly language. One important reason for the disappointing performance of these other systems is probably that they are not written optimally for the 486 (e.g., they use the `lods` instruction). In addition, Win32Forth uses a comfortable, but costly method for relocating the Forth image: like `cforth`, it computes the actual addresses at run time, resulting in two address computations per `NEXT` (see Section 14.2 [Image File Background], page 262).

The speedup of Gforth over PFE, ThisForth and TILE can be easily explained with the self-imposed restriction of the latter systems to standard C, which makes efficient threading impossible (however, the measured implementation of PFE uses a GNU C extension: see Section “Defining Global Register Variables” in *GNU C Manual*). Moreover, current C compilers have a hard time optimizing other aspects of the ThisForth and the TILE source.

The performance of Gforth on 386 architecture processors varies widely with the version of `gcc` used. E.g., `gcc-2.5.8` failed to allocate any of the virtual machine registers into real machine registers by itself and would not work correctly with explicit register declarations, giving a significantly slower engine (on a 486DX2/66 running the Sieve) than the one measured above.

Note that there have been several releases of Win32Forth since the release presented here, so the results presented above may have little predictive value for the performance of Win32Forth today (results for the current release on an i486DX2/66 are welcome).

In *Translating Forth to Efficient C* ([https://www.complang.tuwien.ac.at/papers/ertl&maierhofer95.p](https://www.complang.tuwien.ac.at/papers/ertl&maierhofer95.pdf)) by M. Anton Ertl and Martin Maierhofer (presented at EuroForth '95), an indirect threaded version of Gforth is compared with Win32Forth, NT Forth, PFE, ThisForth, and several native code systems; that version of Gforth is slower on a 486 than the version used here. You can find a newer version of these measurements at <https://www.complang.tuwien.ac.at/forth/performance.html>. You can find numbers for Gforth on various machines in *Benchres*.

16 Cross Compiler

The cross compiler is used to bootstrap a Forth kernel. Since Gforth is mostly written in Forth, including crucial parts like the outer interpreter and compiler, it needs compiled Forth code to get started. The cross compiler allows to create new images for other architectures, even running under another Forth system.

16.1 Using the Cross Compiler

The cross compiler uses a language that resembles Forth, but isn't. The main difference is that you can execute Forth code after definition, while you usually can't execute the code compiled by cross, because the code you are compiling is typically for a different computer than the one you are compiling on.

The Makefile is already set up to allow you to create kernels for new architectures with a simple make command. The generic kernels using the GCC compiled virtual machine are created in the normal build process with `make`. To create an embedded Gforth executable for e.g. the 8086 processor (running on a DOS machine), type

```
make kernl-8086.fi
```

This will use the machine description from the `arch/8086` directory to create a new kernel. A machine file may look like that:

```
\ Parameter for target systems                                06oct92py

4 Constant cell                \ cell size in bytes
2 Constant cell<<              \ cell shift to bytes
5 Constant cell>bit            \ cell shift to bits
8 Constant bits/char           \ bits per character
8 Constant bits/byte           \ bits per byte [default: 8]
8 Constant float               \ bytes per float
8 Constant /maxalign           \ maximum alignment in bytes
false Constant bigendian       \ byte order
( true=big, false=little )

include machpc.fs           \ feature list
```

This part is obligatory for the cross compiler itself, the feature list is used by the kernel to conditionally compile some features in and out, depending on whether the target supports these features.

There are some optional features, if you define your own primitives, have an assembler, or need special, nonstandard preparation to make the boot process work. `asm-include` includes an assembler, `prims-include` includes primitives, and `>boot` prepares for booting.

```
: asm-include    ." Include assembler" cr
  s" arch/8086/asm.fs" included ;

: prims-include  ." Include primitives" cr
  s" arch/8086/prim.fs" included ;
```



```
: >boot      ." Prepare booting" cr
s" ' boot >body into-forth 1+ !" evaluate ;
```

These words are used as sort of macro during the cross compilation in the file `kernel/main.fs`. Instead of using these macros, it would be possible — but more complicated — to write a new kernel project file, too.

`kernel/main.fs` expects the machine description file name on the stack; the cross compiler itself (`cross.fs`) assumes that either `mach-file` leaves a counted string on the stack, or `machine-file` leaves an address, count pair of the filename on the stack.

The feature list is typically controlled using `SetValue`, generic files that are used by several projects can use `DefaultValue` instead. Both functions work like `Value`, when the value isn't defined, but `SetValue` works like `to` if the value is defined, and `DefaultValue` doesn't set anything, if the value is defined.

```
\ generic mach file for pc gforth                                03sep97jaw

true DefaultValue NIL \ relocating

>ENVIRON

true DefaultValue file      \ controls the presence of the
                             \ file access wordset
true DefaultValue OS        \ flag to indicate a operating system

true DefaultValue prims     \ true: primitives are c-code

true DefaultValue floating  \ floating point wordset is present

true DefaultValue glocals   \ gforth locals are present
                             \ will be loaded
true DefaultValue dcomps    \ double number comparisons

true DefaultValue hash      \ hashing primitives are loaded/present

true DefaultValue xconds    \ used together with glocals,
                             \ special conditionals supporting gforths'
                             \ local variables
true DefaultValue header    \ save a header information

true DefaultValue backtrace \ enables backtrace code

false DefaultValue ec
false DefaultValue crlf

cell 2 = [IF] &32 [ELSE] &256 [THEN] KB DefaultValue kernel-size

&16 KB      DefaultValue stack-size
&15 KB &512 + DefaultValue fstack-size
```

```
&15 KB          DefaultValue rstack-size  
&14 KB &512 +    DefaultValue lstack-size
```

16.2 How the Cross Compiler Works

17 MINOS2, a GUI library

17.1 MINOS2 object framework

MINOS2 is a GUI library, written in `mini-oof2.fs`'s object model. It has two main class hierarchies:

`doc-actor doc-widget`

17.1.1 actor methods:

`doc-caller-w doc-active-w doc-act-name$ doc-clicked doc-scrolled doc-touchdown doc-touchup doc-ukeyed doc-ekeyed doc-?inside doc-focus doc-defocus doc-entered doc-left doc-show doc-hide doc-get doc-set doc-show-you`

17.1.2 widget methods:

`doc-parent-w doc-act doc-name$ doc-x doc-y doc-w doc-h doc-d doc-gap doc-baseline doc-kerning doc-raise doc-border doc-borderv doc-bordert doc-borderl doc-w-color doc-draw-init doc-draw doc-split doc-lastfit doc-hglue doc-dglue doc-vglue doc-hglue doc-dglue doc-vglue doc-xywh doc-xywhd doc-lresize doc-lsize doc-dispose-widget doc-.widget doc-par-split doc-resized`

Components are composed using a `boxes&glue` model similar to \LaTeX , including paragraph breaking. For the sake of simplicity and portability, MINOS2 only supports a single window, and uses OpenGL for rendering.

MINOS2 furthermore supports animations with the `animation` class. A color index texture is used for different color schemes, and transition between neighboring schemes can also be animated.

`doc->animate`

You can create named color indexes and assign them color values for the currently active color scheme.

`doc-color: doc-new-color: doc-text-color: doc-text-emoji-color: doc-fade-color: doc-text-emoji-fade-color: doc-re-color doc-re-text-color doc-re-emoji-color doc-re-fade-color doc-re-text-emoji-fade-color`

For a number of specific objects, there are early bound methods, that only work on these objects

- Viewport

`doc-vp-top doc-vp-bottom doc-vp-left doc-vp-right doc-vp-reslide doc-vp-needed`

17.2 MINOS2 tutorial

Tutorials are small files, each showing a bit of MINOS2. For the common framework, the file `minos2/tutorial/tutorial.fs` needs to be loaded first; all other tutorials in the command line argument are included from within that file. Scroll wheel or previous/next mouse buttons as well as clicking on the left or right edge of the window allow navigation between the different tutorials loaded.

I.e. to load the buttons tutorial, you start Gforth with

```
gforth minos2/tutorial/tutorial.fs buttons.fs
```

Available tutorials:

- `buttons.fs`: Clickable buttons
- `plots.fs`: Plot functions
- `markdown.fs`: Markdown document viewer
- `screenshot.fs`: Screenshot function

Appendix A Bugs

Known bugs are described in the file `BUGS` in the Gforth distribution.

If you find a bug, please submit a bug report through <https://savannah.gnu.org/bugs/?func=addbug&group=gforth>.

- A program (or a sequence of keyboard commands) that reproduces the bug.
- A description of what you think constitutes the buggy behaviour.
- The Gforth version used (it is announced at the start of an interactive Gforth session).
- The machine and operating system (on Unix systems `uname -a` will report this information).
- The installation options (you can find the configure options at the start of `config.status`) and configuration (`configure` output or `config.cache`).
- A complete list of changes (if any) you (or your installer) have made to the Gforth sources.

For a thorough guide on reporting bugs read Section “How to Report Bugs” in *GNU C Manual*.

Appendix B Authors and Ancestors of Gforth

B.1 Authors and Contributors

The Gforth project was started in mid-1992 by Bernd Paysan and Anton Ertl. The third major author was Jens Wilke. Neal Crook contributed a lot to the manual. Assemblers and disassemblers were contributed by Andrew McKewan, Christian Pirker, Bernd Thallner, and Michal Revucky. Lennart Benschop (who was one of Gforth's first users, in mid-1993) and Stuart Ramsden inspired us with their continuous feedback. Lennart Benschop contributed `glosgen.fs`, while Stuart Ramsden has been working on automatic support for calling C libraries. Helpful comments also came from Paul Kleinrubatscher, Christian Pirker, Dirk Zoller, Marcel Hendrix, John Wavrik, Barrie Stott, Marc de Groot, Jorge Acerada, Bruce Hoyt, Robert Epprecht, Dennis Ruffer and David N. Williams. Since the release of Gforth-0.2.1 there were also helpful comments from many others; thank you all, sorry for not listing you here (but digging through my mailbox to extract your names is on my to-do list).

Gforth also owes a lot to the authors of the tools we used (GCC, CVS, and autoconf, among others), and to the creators of the Internet: Gforth was developed across the Internet, and its authors did not meet physically for the first 4 years of development.

B.2 Pedigree

Gforth descends from bigFORTH (1993) and fig-Forth. Of course, a significant part of the design of Gforth was prescribed by Standard Forth.

Bernd Paysan wrote bigFORTH, a descendent from TurboForth, an unreleased 32 bit native code version of VolksForth for the Atari ST, written mostly by Dietrich Weineck.

VolksForth was written by Klaus Schleisiek, Bernd Pennemann, Georg Rehfeld and Dietrich Weineck for the C64 (called UltraForth there) in the mid-80s and ported to the Atari ST in 1986. It descends from fig-Forth.

A team led by Bill Ragsdale implemented fig-Forth on many processors in 1979. Robert Selzer and Bill Ragsdale developed the original implementation of fig-Forth for the 6502 based on microForth.

The principal architect of microForth was Dean Sanderson. microForth was FORTH, Inc.'s first off-the-shelf product. It was developed in 1976 for the 1802, and subsequently implemented on the 8080, the 6800 and the Z80.

All earlier Forth systems were custom-made, usually by Charles Moore, who discovered (as he puts it) Forth during the late 60s. The first full Forth existed in 1971.

A part of the information in this section comes from *The Evolution of Forth* (<https://www.forth.com/resources/evolution/index.html>) by Elizabeth D. Rather, Donald R. Colburn and Charles H. Moore, presented at the HOPL-II conference and preprinted in SIGPLAN Notices 28(3), 1993. You can find more historical and genealogical information about Forth there. For a more general (and graphical) Forth family tree look see <https://www.complang.tuwien.ac.at/forth/family-tree/>, *Forth Family Tree and Timeline*.

Appendix C Other Forth-related information

There is an active news group (`comp.lang.forth`) discussing Forth (including Gforth) and Forth-related issues. Its FAQs (<https://www.complang.tuwien.ac.at/forth/faq/faq-general-2.html>) (frequently asked questions and their answers) contains a lot of information on Forth. You should read it before posting to `comp.lang.forth`.

The Forth standard is most usable in its HTML form (<https://forth-standard.org/>).

Appendix D Licenses

D.1 GNU Free Documentation License

Version 1.2, November 2002

Copyright © 2000,2001,2002 Free Software Foundation, Inc.
59 Temple Place, Suite 330, Boston, MA 02111-1307, USA

Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

0. PREAMBLE

The purpose of this License is to make a manual, textbook, or other functional and useful document *free* in the sense of freedom: to assure everyone the effective freedom to copy and redistribute it, with or without modifying it, either commercially or noncommercially. Secondly, this License preserves for the author and publisher a way to get credit for their work, while not being considered responsible for modifications made by others.

This License is a kind of “copyleft”, which means that derivative works of the document must themselves be free in the same sense. It complements the GNU General Public License, which is a copyleft license designed for free software.

We have designed this License in order to use it for manuals for free software, because free software needs free documentation: a free program should come with manuals providing the same freedoms that the software does. But this License is not limited to software manuals; it can be used for any textual work, regardless of subject matter or whether it is published as a printed book. We recommend this License principally for works whose purpose is instruction or reference.

1. APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work, in any medium, that contains a notice placed by the copyright holder saying it can be distributed under the terms of this License. Such a notice grants a world-wide, royalty-free license, unlimited in duration, to use that work under the conditions stated herein. The “Document”, below, refers to any such manual or work. Any member of the public is a licensee, and is addressed as “you”. You accept the license if you copy, modify or distribute the work in a way requiring permission under copyright law.

A “Modified Version” of the Document means any work containing the Document or a portion of it, either copied verbatim, or with modifications and/or translated into another language.

A “Secondary Section” is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document’s overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (Thus, if the Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political position regarding them.

The “Invariant Sections” are certain Secondary Sections whose titles are designated, as being those of Invariant Sections, in the notice that says that the Document is released under this License. If a section does not fit the above definition of Secondary then it is not allowed to be designated as Invariant. The Document may contain zero Invariant Sections. If the Document does not identify any Invariant Sections then there are none.

The “Cover Texts” are certain short passages of text that are listed, as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License. A Front-Cover Text may be at most 5 words, and a Back-Cover Text may be at most 25 words.

A “Transparent” copy of the Document means a machine-readable copy, represented in a format whose specification is available to the general public, that is suitable for revising the document straightforwardly with generic text editors or (for images composed of pixels) generic paint programs or (for drawings) some widely available drawing editor, and that is suitable for input to text formatters or for automatic translation to a variety of formats suitable for input to text formatters. A copy made in an otherwise Transparent file format whose markup, or absence of markup, has been arranged to thwart or discourage subsequent modification by readers is not Transparent. An image format is not Transparent if used for any substantial amount of text. A copy that is not “Transparent” is called “Opaque”.

Examples of suitable formats for Transparent copies include plain ASCII without markup, Texinfo input format, LaTeX input format, SGML or XML using a publicly available DTD, and standard-conforming simple HTML, PostScript or PDF designed for human modification. Examples of transparent image formats include PNG, XCF and JPG. Opaque formats include proprietary formats that can be read and edited only by proprietary word processors, SGML or XML for which the DTD and/or processing tools are not generally available, and the machine-generated HTML, PostScript or PDF produced by some word processors for output purposes only.

The “Title Page” means, for a printed book, the title page itself, plus such following pages as are needed to hold, legibly, the material this License requires to appear in the title page. For works in formats which do not have any title page as such, “Title Page” means the text near the most prominent appearance of the work’s title, preceding the beginning of the body of the text.

A section “Entitled XYZ” means a named subunit of the Document whose title either is precisely XYZ or contains XYZ in parentheses following text that translates XYZ in another language. (Here XYZ stands for a specific section name mentioned below, such as “Acknowledgements”, “Dedications”, “Endorsements”, or “History”.) To “Preserve the Title” of such a section when you modify the Document means that it remains a section “Entitled XYZ” according to this definition.

The Document may include Warranty Disclaimers next to the notice which states that this License applies to the Document. These Warranty Disclaimers are considered to be included by reference in this License, but only as regards disclaiming warranties: any other implication that these Warranty Disclaimers may have is void and has no effect on the meaning of this License.

2. VERBATIM COPYING

You may copy and distribute the Document in any medium, either commercially or noncommercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and that you add no other conditions whatsoever to those of this License. You may not use technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

3. COPYING IN QUANTITY

If you publish printed copies (or copies in media that commonly have printed covers) of the Document, numbering more than 100, and the Document's license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible. You may add other material on the covers in addition. Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a computer-network location from which the general network-using public has access to download using public-standard network protocols a complete Transparent copy of the Document, free of added material. If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that edition to the public.

It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated version of the Document.

4. MODIFICATIONS

You may copy and distribute a Modified Version of the Document under the conditions of sections 2 and 3 above, provided that you release the Modified Version under precisely this License, with the Modified Version filling the role of the Document, thus licensing distribution and modification of the Modified Version to whoever possesses a copy of it. In addition, you must do these things in the Modified Version:

- A. Use in the Title Page (and on the covers, if any) a title distinct from that of the Document, and from those of previous versions (which should, if there were any,

be listed in the History section of the Document). You may use the same title as a previous version if the original publisher of that version gives permission.

- B. List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has fewer than five), unless they release you from this requirement.
- C. State on the Title page the name of the publisher of the Modified Version, as the publisher.
- D. Preserve all the copyright notices of the Document.
- E. Add an appropriate copyright notice for your modifications adjacent to the other copyright notices.
- F. Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the terms of this License, in the form shown in the Addendum below.
- G. Preserve in that license notice the full lists of Invariant Sections and required Cover Texts given in the Document's license notice.
- H. Include an unaltered copy of this License.
- I. Preserve the section Entitled "History", Preserve its Title, and add to it an item stating at least the title, year, new authors, and publisher of the Modified Version as given on the Title Page. If there is no section Entitled "History" in the Document, create one stating the title, year, authors, and publisher of the Document as given on its Title Page, then add an item describing the Modified Version as stated in the previous sentence.
- J. Preserve the network location, if any, given in the Document for public access to a Transparent copy of the Document, and likewise the network locations given in the Document for previous versions it was based on. These may be placed in the "History" section. You may omit a network location for a work that was published at least four years before the Document itself, or if the original publisher of the version it refers to gives permission.
- K. For any section Entitled "Acknowledgements" or "Dedications", Preserve the Title of the section, and preserve in the section all the substance and tone of each of the contributor acknowledgements and/or dedications given therein.
- L. Preserve all the Invariant Sections of the Document, unaltered in their text and in their titles. Section numbers or the equivalent are not considered part of the section titles.
- M. Delete any section Entitled "Endorsements". Such a section may not be included in the Modified Version.
- N. Do not retitle any existing section to be Entitled "Endorsements" or to conflict in title with any Invariant Section.
- O. Preserve any Warranty Disclaimers.

If the Modified Version includes new front-matter sections or appendices that qualify as Secondary Sections and contain no material copied from the Document, you may at your option designate some or all of these sections as invariant. To do this, add their

titles to the list of Invariant Sections in the Modified Version’s license notice. These titles must be distinct from any other section titles.

You may add a section Entitled “Endorsements”, provided it contains nothing but endorsements of your Modified Version by various parties—for example, statements of peer review or that the text has been approved by an organization as the authoritative definition of a standard.

You may add a passage of up to five words as a Front-Cover Text, and a passage of up to 25 words as a Back-Cover Text, to the end of the list of Cover Texts in the Modified Version. Only one passage of Front-Cover Text and one of Back-Cover Text may be added by (or through arrangements made by) any one entity. If the Document already includes a cover text for the same cover, previously added by you or by arrangement made by the same entity you are acting on behalf of, you may not add another; but you may replace the old one, on explicit permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License give permission to use their names for publicity for or to assert or imply endorsement of any Modified Version.

5. COMBINING DOCUMENTS

You may combine the Document with other documents released under this License, under the terms defined in section 4 above for modified versions, provided that you include in the combination all of the Invariant Sections of all of the original documents, unmodified, and list them all as Invariant Sections of your combined work in its license notice, and that you preserve all their Warranty Disclaimers.

The combined work need only contain one copy of this License, and multiple identical Invariant Sections may be replaced with a single copy. If there are multiple Invariant Sections with the same name but different contents, make the title of each such section unique by adding at the end of it, in parentheses, the name of the original author or publisher of that section if known, or else a unique number. Make the same adjustment to the section titles in the list of Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections Entitled “History” in the various original documents, forming one section Entitled “History”; likewise combine any sections Entitled “Acknowledgements”, and any sections Entitled “Dedications”. You must delete all sections Entitled “Endorsements.”

6. COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents released under this License, and replace the individual copies of this License in the various documents with a single copy that is included in the collection, provided that you follow the rules of this License for verbatim copying of each of the documents in all other respects.

You may extract a single document from such a collection, and distribute it individually under this License, provided you insert a copy of this License into the extracted document, and follow this License in all other respects regarding verbatim copying of that document.

7. AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives with other separate and independent documents or works, in or on a volume of a storage or distribution medium, is called an “aggregate” if the copyright resulting from the compilation is not used to limit the legal rights of the compilation’s users beyond what the individual works permit. When the Document is included in an aggregate, this License does not apply to the other works in the aggregate which are not themselves derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these copies of the Document, then if the Document is less than one half of the entire aggregate, the Document’s Cover Texts may be placed on covers that bracket the Document within the aggregate, or the electronic equivalent of covers if the Document is in electronic form. Otherwise they must appear on printed covers that bracket the whole aggregate.

8. TRANSLATION

Translation is considered a kind of modification, so you may distribute translations of the Document under the terms of section 4. Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all Invariant Sections in addition to the original versions of these Invariant Sections. You may include a translation of this License, and all the license notices in the Document, and any Warranty Disclaimers, provided that you also include the original English version of this License and the original versions of those notices and disclaimers. In case of a disagreement between the translation and the original version of this License or a notice or disclaimer, the original version will prevail.

If a section in the Document is Entitled “Acknowledgements”, “Dedications”, or “History”, the requirement (section 4) to Preserve its Title (section 1) will typically require changing the actual title.

9. TERMINATION

You may not copy, modify, sublicense, or distribute the Document except as expressly provided for under this License. Any other attempt to copy, modify, sublicense or distribute the Document is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

10. FUTURE REVISIONS OF THIS LICENSE

The Free Software Foundation may publish new, revised versions of the GNU Free Documentation License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns. See <http://www.gnu.org/copyleft/>.

Each version of the License is given a distinguishing version number. If the Document specifies that a particular numbered version of this License “or any later version” applies to it, you have the option of following the terms and conditions either of that specified version or of any later version that has been published (not as a draft) by the Free Software Foundation. If the Document does not specify a version number of this License, you may choose any version ever published (not as a draft) by the Free Software Foundation.

D.1.1 ADDENDUM: How to use this License for your documents

To use this License in a document you have written, include a copy of the License in the document and put the following copyright and license notices just after the title page:

```
Copyright (C)  year  your name.
Permission is granted to copy, distribute and/or modify this document
under the terms of the GNU Free Documentation License, Version 1.2
or any later version published by the Free Software Foundation;
with no Invariant Sections, no Front-Cover Texts, and no Back-Cover
Texts.  A copy of the license is included in the section entitled ‘‘GNU
Free Documentation License’’.
```

If you have Invariant Sections, Front-Cover Texts and Back-Cover Texts, replace the “with...Texts.” line with this:

```
with the Invariant Sections being list their titles, with
the Front-Cover Texts being list, and with the Back-Cover Texts
being list.
```

If you have Invariant Sections without Cover Texts, or some other combination of the three, merge those two alternatives to suit the situation.

If your document contains nontrivial examples of program code, we recommend releasing these examples in parallel under your choice of free software license, such as the GNU General Public License, to permit their use in free software.

D.2 GNU GENERAL PUBLIC LICENSE

Version 3, 29 June 2007

Copyright © 2007 Free Software Foundation, Inc. <http://fsf.org/>

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program—to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps: (1) assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To “convey” a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays “Appropriate Legal Notices” to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The “source code” for a work means the preferred form of the work for making modifications to it. “Object code” means any non-source form of a work.

A “Standard Interface” means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The “System Libraries” of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A “Major Component”, in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The “Corresponding Source” for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work’s System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed; section 10 makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice; keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

- a. The work must carry prominent notices stating that you modified it, and giving a relevant date.
- b. The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".
- c. You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license

the work in any other way, but it does not invalidate such permission if you have separately received it.

- d. If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an “aggregate” if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation’s users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

- a. Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.
- b. Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.
- c. Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.
- d. Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.
- e. Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A “User Product” is either (1) a “consumer product”, which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, “normally used” refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

“Installation Information” for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

“Additional permissions” are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

- a. Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or
- b. Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or
- c. Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or
- d. Limiting the use for publicity purposes of names of licensors or authors of the material; or
- e. Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or
- f. Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on those licensors and authors.

All other non-permissive additional terms are considered “further restrictions” within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright

holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An “entity transaction” is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party’s predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A “contributor” is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor’s “contributor version”.

A contributor’s “essential patent claims” are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a

consequence of further modification of the contributor version. For purposes of this definition, “control” includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor’s essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a “patent license” is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To “grant” such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. “Knowingly relying” means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient’s use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is “discriminatory” if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others’ Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously

your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License “or any later version” applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy’s public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM “AS IS” WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS

OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17. Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the “copyright” line and a pointer to where the full notice is found.

```
one line to give the program's name and a brief idea of what it does.
Copyright (C) year name of author
```

```
This program is free software: you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation, either version 3 of the License, or (at
your option) any later version.
```

```
This program is distributed in the hope that it will be useful, but
WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
General Public License for more details.
```

```
You should have received a copy of the GNU General Public License
along with this program. If not, see http://www.gnu.org/licenses/.
```

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice like this when it starts in an interactive mode:

```
program Copyright (C) year name of author
This program comes with ABSOLUTELY NO WARRANTY; for details type 'show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type 'show c' for details.
```

The hypothetical commands ‘show w’ and ‘show c’ should show the appropriate parts of the General Public License. Of course, your program’s commands might be different; for a GUI interface, you would use an “about box”.

You should also get your employer (if you work as a programmer) or school, if any, to sign a “copyright disclaimer” for the program, if necessary. For more information on this, and how to apply and follow the GNU GPL, see <http://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License. But first, please read <http://www.gnu.org/philosophy/why-not-lgpl.html>.

Word Index

This index is a list of Forth words that have “glossary” entries within this manual. Each word is listed with its stack effect and wordset.

!		
!!FIXME!!(--) gforth-1.0	203	
!(w a-addr --) core	72	
!@(u1 a-addr -- u2)		
gforth-experimental	209	
#		
#!(--) gforth-0.2	266	
#(ud1 -- ud2) core	149	
#>(xd -- addr u) core	149	
#>>(--) gforth-0.5	150	
#bell(-- c) gforth-0.2	80	
#bs(-- c) gforth-0.2	80	
#cr(-- c) gforth-0.2	80	
#del(-- c) gforth-0.2	80	
#eof(-- c) gforth-0.7	80	
#esc(-- c) gforth-0.5	80	
#ff(-- c) gforth-0.2	80	
#lf(-- c) gforth-0.2	80	
#loc(nline nchar "file" --		
) gforth-1.0	204	
#s(ud -- 0 0) core	149	
#tab(-- c) gforth-0.2	80	
#tib(-- addr) core-ext-obsolescent	127	
\$		
\$(addr1 u \$addr --) gforth-0.7	81	
\$!len(u \$addr --) gforth-0.7	81	
\$+!(addr1 u \$addr --) gforth-0.7	82	
\$+!len(u \$addr -- addr) gforth-1.0	81	
\$(addr --) gforth-1.0	82	
\$(-- n) gforth-0.2	235	
\$[]!(addr u n \$[]addr --) gforth-1.0	82	
\$[]#(addr -- len) gforth-1.0	83	
\$[] (u \$[]addr -- addr') gforth-1.0	82	
\$[]+!(addr u n \$[]addr --) gforth-1.0	83	
\$[].(addr --) gforth-1.0	83	
\$[]@(n \$[]addr -- addr u) gforth-1.0	83	
\$[]boot(addr --) gforth-1.0	83	
\$[]free(addr --) gforth-1.0	83	
\$[]map(addr xt --) gforth-1.0	83	
\$[]save(addr --) gforth-1.0	83	
\$[]saved(addr --) gforth-1.0	83	
\$[]slurp(fid addr --) gforth-1.0	83	
\$[]slurp-file(addr u \$addr --		
) gforth-1.0	83	
\$[]Variable(--) gforth-1.0	83	
\$@ (\$addr -- addr2 u) gforth-0.7	81	
\$@len(\$addr -- u) gforth-0.7	81	
\$boot(\$addr --) gforth-1.0	83	
\$del(addr off u --) gforth-0.7	82	
\$exec(xt addr --) gforth-1.0	82	
\$free(\$addr --) gforth-1.0	82	
\$init(\$addr --) gforth-1.0	82	
\$ins(addr1 u \$addr off --) gforth-0.7	82	
\$iter(.. \$addr char xt -- ..		
) gforth-0.7	82	
\$over(addr u \$addr off --) gforth-1.0	82	
\$save(\$addr --) gforth-1.0	83	
\$saved(addr --) gforth-1.0	83	
\$slurp(fid addr --) gforth-1.0	82	
\$slurp-file(addr1 u1 addr2 --		
) gforth-1.0	82	
\$split(addr u char -- addr1 u1 addr2		
u2) gforth-0.7	82	
\$substitute(addr1 len1 -- addr2 len2 n/ior)		
gforth-experimental	162	
\$tmp(xt -- addr u) gforth-1.0	82	
\$unescape(addr1 u1 -- addr2 u2)		
gforth-experimental	162	
\$Variable(--) gforth-1.0	83	
%		
%align(align size --) gforth-0.4	176	
%alignment(align size --		
align) gforth-0.4	176	
%alloc(align size -- addr) gforth-0.4 ..	176	
%allocate(align size -- addr		
ior) gforth-0.4	176	
%allot(align size -- addr) gforth-0.4 ..	176	
%size(align size -- size) gforth-0.4 ..	177	
,		
'("name" -- xt) core	117, 191	
'cold(--) gforth-0.2	267	
's(user task -- user')		
gforth-experimental	208	
(
((compilation 'ccc<close-paren>' -- ;		
run-time --) core,file	56	
(local)(addr u --) local	172	
(to)(val xt --) gforth-1.0	109, 232	
)		
)(--) gforth-0.2	204	

*

*(n1 n2 -- n) core 57
 */((n1 n2 n3 -- n4) core 59
 */f(n1 n2 n3 -- n4) gforth-1.0 59
 */mod(n1 n2 n3 -- n4 n5) core 60
 */modf(n1 n2 n3 -- n4 n5) gforth-1.0 60
 */mods(n1 n2 n3 -- n4 n5) gforth-1.0 60
 */s(n1 n2 n3 -- n4) gforth-1.0 59

+

+!(n a-addr --) core 72
 +!@(u1 a-addr -- u2)
 gforth-experimental 209
 +(n1 n2 -- n) core 57
 +DO(compilation -- do-sys ; run-time n1 n2 --
 | loop-sys) gforth-0.2 91
 +field(noffset1 nsize "name" --
 noffset2) facility-ext 177
 +fmode(fam1 rwxrwxrwx -- fam2
) gforth-1.0 140
 +load(i*x n -- j*x) gforth-0.2 147
 +LOOP(compilation do-sys -- ; run-time
 loop-sys1 n -- | loop-sys2) core 92
 +ltrace(--) gforth-1.0 203
 +thru(i*x n1 n2 -- j*x) gforth-0.2 147
 +T0(value "name" --) gforth-1.0 100
 +x/string(xc-addr1 u1 -- xc-addr2
 u2) xchar-ext 160

,

,(w --) core 71

—

-(n1 n2 -- n) core 57
 -->(--) gforth-0.2 147
 ->here(addr --) gforth-1.0 71
 -DO(compilation -- do-sys ; run-time n1 n2 --
 | loop-sys) gforth-0.2 91
 -LOOP(compilation do-sys -- ; run-time
 loop-sys1 u -- | loop-sys2) gforth-0.2.. 92
 -ltrace(--) gforth-1.0 203
 -rot(w1 w2 w3 -- w3 w1 w2) gforth-0.2 68
 -trailing(c-addr u1 --
 c-addr u2) string 81
 -trailing-garbage(xc-addr u1 --
 xc-addr u2) xchar-ext 160

.

."(compilation 'ccc' -- ;
 run-time --) core 153
 .(n --) core 148
 .((compilation&interpretation
 "ccc<paren>" --) core-ext 153
 ... (x1 .. xn -- x1 .. xn) gforth-1.0 201
 .\"(compilation 'ccc' -- ; run-time
 --) gforth-0.6 153
 .cover-raw(--) gforth-experimental 206
 .coverage(--) gforth-experimental 206
 .debugline(nfile nline --) gforth-0.6.. 203
 .locale-csv(--) gforth-experimental ... 162
 .path(path-addr --) gforth-0.4 144
 .r(n1 n2 --) core-ext 148
 .s(--) tools 201
 .substitute(addr1 len1 -- n / ior)
 gforth-experimental 162
 .unresolved(--) gforth-1.0 114

/

/(n1 n2 -- n) core 59
 /f(n1 n2 -- n) gforth-1.0 59
 /f-stage1m(n addr-reci --) gforth-1.0... 61
 /f-stage2m(n1 a-reci --
 nquotient) gforth-1.0 61
 /l(-- u) gforth-0.7 77
 /mod(n1 n2 -- n3 n4) core 59
 /modf(n1 n2 -- n3 n4) gforth-1.0 59
 /modf-stage2m(n1 a-reci -- umodulus
 nquotient) gforth-1.0 61
 /mods(n1 n2 -- n3 n4) gforth-1.0 59
 /s(n1 n2 -- n) gforth-1.0 59
 /string(c-addr1 u1 n --
 c-addr2 u2) string 81
 /w(-- u) gforth-0.7 77
 /x(-- u) gforth-1.0 77

:

:("name" -- colon-sys) core 101, 191
 ::("name" --) oof 191, 193
 :}d(haddr u latest latestnt wid 0 a-addr1 u1
 ... --) gforth-1.0 171
 :}h(haddr u latest latestnt wid 0 a-addr1 u1
 ... --) gforth-1.0 171
 :}l(haddr u latest latestnt wid 0 a-addr1 u1
 ... --) gforth-1.0 171
 :m("name" -- xt ; run-time:
 object --) objects 188
 :noname(-- xt colon-sys) core-ext 101

```

;
;( compilation colon-sys -- ;
  run-time nest-sys ) core..... 101
;>( -- ) gforth-experimental..... 172
;]( compile-time: quotation-sys -- ;
  run-time: -- xt ) gforth-1.0..... 102
;code( compilation. colon-sys1 --
  colon-sys2 ) tools-ext..... 217
;m( colon-sys --; run-time:
  -- ) objects..... 188
;s( R:w -- ) gforth-0.2..... 94

<
<#( -- ) core..... 149
<( n1 n2 -- f ) core..... 64
<<#( -- ) gforth-0.5..... 149
<=( n1 n2 -- f ) gforth-0.2..... 64
<>( n1 n2 -- f ) core-ext..... 64
<{:( -- haddr u latest latestnt wid 0 )
  gforth-experimental..... 172
<bind>( class selector-xt --
  xt ) objects..... 186
<event( -- ) gforth-experimental..... 209
<to-inst>( w xt -- ) objects..... 189

=
=( n1 n2 -- f ) core..... 64
=mkdir( c-addr u wmode -- wior
  ) gforth-0.7..... 142

>
>( n1 n2 -- f ) core..... 64
>=( n1 n2 -- f ) gforth-0.2..... 64
>addr( xt -- addr ) gforth-experimental.. 171
>body( xt -- a_addr ) core..... 107
>code-address( xt -- c_addr
  ) gforth-0.2..... 233
>definer( xt -- definer ) gforth-0.2..... 234
>does-code( xt -- a_addr ) gforth-0.2..... 234
>float( c-addr u -- f:...
  flag ) floating..... 158
>float1( c-addr u c -- f:...
  flag ) gforth-1.0..... 158
>in( -- addr ) core..... 127
>l( w -- ) gforth-0.2..... 169
>name( xt -- nt|0 ) gforth-0.2..... 119
>number( ud1 c-addr1 u1 -- ud2
  c-addr2 u2 ) core..... 158
>o( c-addr -- r:c-old ) new..... 196
>order( wid -- ) gforth-0.5..... 134
>pow2( u1 -- u2 ) gforth-1.0..... 63
>r( w -- R:w ) core..... 69
>time&date&tz( udttime -- nsec nmin nhour nday
  nmonth nyear fdst ndstoffs c-addrtz utz )
  gforth-1.0..... 235

```

?

```

?!@ ( anew uold a-addr -- uprev )
  gforth-experimental..... 209
?( a-addr -- ) tools..... 201
???( -- ) gforth-0.2..... 203
?DO( compilation -- do-sys ; run-time w1 w2 --
  | loop-sys ) core-ext..... 91
?dup( w -- S:... w ) core..... 68
?dup-IF( compilation -- orig ; run-time n
  -- n| ) gforth-0.2..... 91
?DUP-0=-IF( compilation -- orig ; run-time n
  -- n| ) gforth-0.2..... 91
?events( -- ) gforth-experimental..... 209
?LEAVE( compilation -- ; run-time f | f
  loop-sys -- ) gforth-0.2..... 92
?of( compilation -- of-sys ; run-time
  f -- ) gforth-1.0..... 92

[
[']( compilation. "name" -- ;
  run-time. -- xt ) core..... 117
[( -- ) core..... 121
[+LOOP]( n -- ) gforth-0.2..... 130
[:( compile-time: -- quotation-sys flag
  colon-sys ) gforth-1.0..... 102
[?DO]( n-limit n-index -- ) gforth-0.2... 130
[] ( n "name" -- ) oof..... 191
[{: ( -- haddr u latest latestnt wid 0 )
  gforth-experimental..... 171
[AGAIN]( -- ) gforth-0.2..... 130
[BEGIN]( -- ) gforth-0.2..... 130
[bind]( compile-time: "class" "selector" -- ;
  run-time: ... object -- ... ) objects... 187
[char]( compilation '<spaces>ccc' -- ;
  run-time -- c ) core,xchar-ext..... 79
[COMP']( compilation "name" -- ; run-time
  -- w xt ) gforth-0.2..... 120
[current]( compile-time: "selector" -- ;
  run-time: ... object -- ... ) objects... 187
[DO]( n-limit n-index -- ) gforth-0.2.... 130
[ELSE]( -- ) tools-ext..... 129
[ENDIF]( -- ) gforth-0.2..... 129
[FOR]( n -- ) gforth-0.2..... 130
[IF]( flag -- ) tools-ext..... 129
[IFDEF]( "<spaces>name" --
  ) gforth-0.2..... 129
[IFUNDEF]( "<spaces>name" --
  ) gforth-0.2..... 130
[LOOP]( -- ) gforth-0.2..... 130
[NEXT]( n -- ) gforth-0.2..... 130
[parent]( compile-time: "selector" -- ;
  run-time: ... object -- ... ) objects... 188
[REPEAT]( -- ) gforth-0.2..... 130
[THEN]( -- ) tools-ext..... 129
[to-inst]( compile-time: "name" -- ;
  run-time: w -- ) objects..... 189
[UNTIL]( flag -- ) gforth-0.2..... 130

```

[WHILE](flag --) gforth-0.2..... 130

]

](--) core..... 121

]](--) gforth-0.6..... 122

]L(compilation: n -- ; run-time:
-- n) gforth-0.5..... 121

@

@(a-addr -- w) core..... 72

@local#(#noffset -- w) gforth-0.2..... 169

\

\(compilation 'ccc<newline>' -- ; run-time
--) core-ext,block-ext..... 56

\c("rest-of-line" --) gforth-0.7..... 212

\G(compilation 'ccc<newline>' -- ;
run-time --) gforth-0.2..... 56

{

{:(-- haddr u latest latestnt
wid 0) local-ext..... 172

~

~~(--) gforth-0.2..... 203

~~1bt(--) gforth-1.0..... 203

~~bt(--) gforth-1.0..... 203

~~Value(n "name" --) gforth-1.0..... 203

~~Variable("name" --) gforth-1.0..... 203

0

0<(n -- f) core..... 64

0<=(n -- f) gforth-0.2..... 64

0<>(n -- f) core-ext..... 64

0=(n -- f) core..... 64

0>(n -- f) core-ext..... 64

0>=(n -- f) gforth-0.2..... 64

1

1+(n1 -- n2) core..... 57

1-(n1 -- n2) core..... 57

1/f(r1 -- r2) gforth-0.2..... 66

2

2!(w1 w2 a-addr --) core..... 72

2*(n1 -- n2) core..... 63

2,(w1 w2 --) gforth-0.2..... 71

2/(n1 -- n2) core..... 63

2>r(w1 w2 -- R:w1 R:w2) core-ext..... 69

2@(a-addr -- w1 w2) core..... 72

2Constant(w1 w2 "name" --) double..... 100

2drop(w1 w2 --) core..... 68

2dup(w1 w2 -- w1 w2 w1 w2) core..... 68

2field:(u1 "name" -- u2) gforth-0.7..... 177

2Literal(compilation w1 w2 -- ;
run-time -- w1 w2) double..... 121

2nip(w1 w2 w3 w4 -- w3 w4) gforth-0.2..... 68

2over(w1 w2 w3 w4 -- w1 w2 w3
w4 w1 w2) core..... 68

2r>(R:w1 R:w2 -- w1 w2) core-ext..... 69

2r@(R:w1 R:w2 -- R:w1 R:w2 w1
w2) core-ext..... 69

2rdrop(R:w1 R:w2 --) gforth-0.2..... 69

2rot(w1 w2 w3 w4 w5 w6 -- w3 w4 w5 w6
w1 w2) double-ext..... 68

2swap(w1 w2 w3 w4 -- w3 w4 w1 w2) core.... 68

2tuck(w1 w2 w3 w4 -- w3 w4 w1 w2 w3
w4) gforth-0.2..... 68

2Variable("name" --) double..... 99

A

abi-code("name" -- colon-sys
) gforth-1.0..... 217

abort(?? -- ??) core,exception-ext..... 97

ABORT"(compilation 'ccc' -- ; run-time f --
) core,exception-ext..... 97

abs(n -- u) core..... 57

accept(c-addr +n1 -- +n2) core..... 157

action-of(interpretation "name" -- xt;
compilation "name" -- ; run-time -- xt)
core-ext..... 114

activate(task --)

gforth-experimental..... 207

add-cflags(c-addr u --) gforth-1.0..... 214

add-incdir(c-addr u --) gforth-1.0..... 214

add-ldflags(c-addr u --) gforth-1.0..... 214

add-lib(c-addr u --) gforth-0.7..... 214

add-libpath(c-addr u --) gforth-0.7..... 214

addr("name" -- addr) gforth-1.0..... 101

ADDRESS-UNIT-BITS(-- n) environment..... 76

after-locate(-- u) gforth-1.0..... 198

AGAIN(compilation dest -- ;
run-time --) core-ext..... 90

AHEAD(compilation -- orig ;
run-time --) tools-ext..... 90

Alias(xt "name" --) gforth-0.2..... 115

align(--) core..... 71

aligned(c-addr -- a-addr) core..... 76

allocate(u -- a_addr wior) memory..... 72

allot(n --) core..... 71

also(--) search-ext 134
 also-path(c-addr len path-addr
 --) gforth-0.4 144
 and(w1 w2 -- w) core 62
 annotate-cov(--) gforth-experimental .. 206
 arg(u -- addr count) gforth-0.2 163
 argc(-- addr) gforth-0.2 163
 argv(-- addr) gforth-0.2 163
 arshift(n1 u -- n2) gforth-1.0 62
 asptr(o "name" --) oof 191, 192
 assembler(--) tools-ext 217
 assert((--) gforth-0.2 204
 assert-level(-- a-addr) gforth-0.2 205
 assert0((--) gforth-0.2 204
 assert1((--) gforth-0.2 204
 assert2((--) gforth-0.2 204
 assert3((--) gforth-0.2 204
 ASSUME-LIVE(orig -- orig) gforth-0.2 ... 167
 at-deltaxy(dx dy --) gforth-0.7 154
 at-xy(x y --) facility 154
 authors(--) gforth-1.0 6

B

b(--) gforth-1.0 198
 barrier(--) gforth-experimental 209
 base(-- a-addr) core 128
 base-execute(i*x xt u -- j*x
) gforth-0.7 128
 before-locate(-- u) gforth-1.0 198
 begin-structure("name" -- struct-sys
 0) facility-ext 177
 BEGIN(compilation -- dest ;
 run-time --) core 90
 bin(fam1 -- fam2) file 140
 bind'("class" "selector" --
 xt) objects 187
 bind(... "class" "selector" --
 ...) objects 186, 191
 bl(-- c-char) core 80
 blank(c-addr u --) string 77
 blk(-- addr) block 127
 block(u -- a-addr) block 146
 block-included(a-addr u --
) gforth-0.2 147
 block-offset(-- addr) gforth-0.5 146
 block-position(u --) block 146
 bootmessage(--) gforth-0.4 267
 bound(class addr "name" --) oof 191
 bounds(addr u -- addr+u addr
) gforth-0.2 77
 break('ccc' --) gforth-0.4 206
 break:(--) gforth-0.4 206
 broken-pipe-error(-- n) gforth-0.6 159
 bt(--) gforth-1.0 199
 buffer(u -- a-addr) block 146
 bw(--) gforth-1.0 198
 bw-cover(--) gforth-1.0 206

bye(--) tools-ext 6

C

c!(c c-addr --) core 72
 c\$+!(char \$addr --) gforth-1.0 82
 c,(c --) core 71
 c-callback("forth-name" "{type}" "----"
 "type" --) gforth-1.0 215
 c-function("forth-name" "c-name" "{type}"
 "----" "type" --) gforth-0.7 212
 c-funptr("forth-name" <{}>"c-typecast"<{}>
 "{type}" "----" "type" --) gforth-1.0... 213
 c-library("name" --) gforth-0.7 214
 c-library-name(c-addr u --
) gforth-0.7 214
 c-value("forth-name" "c-name" "----"
 "type" --) gforth-1.0 212
 c-variable("forth-name" "c-name"
 --) gforth-1.0 212
 c>s(x -- n) gforth-1.0 74
 c@(c-addr -- c) core 72
 C(compilation "ccc<quote>" -- ; run-time
 -- c-addr) core-ext 84
 call-c(... w -- ...) gforth-0.2 215
 capscompare(c-addr1 u1 c-addr2 u2
 -- n) gforth-0.7 80
 case(compilation -- case-sys ;
 run-time --) core-ext 92
 catch(x1 .. xn xt -- y1 .. ym 0 / z1 .. zn
 error) exception 95
 cell%(-- align size) gforth-0.4 176
 cell(-- u) gforth-0.2 75
 cell+(a-addr1 -- a-addr2) core 75
 cell-(a-addr1 -- a-addr2) core 75
 cell/(n1 -- n2) gforth-1.0 75
 cells(n1 -- n2) core 75
 cfa1ign(--) gforth-0.2 71
 cfa1igned(addr1 -- addr2) gforth-0.2 76
 cfield:(u1 "name" -- u2) facility-ext .. 177
 char%(-- align size) gforth-0.4 176
 char('<spaces>ccc' -- c)
 core,xchar-ext 79
 char+(c-addr1 -- c-addr2) core 75
 chars(n1 -- n2) core 75
 class(parent-class -- align
 offset) objects 187, 191, 193
 class->map(class -- map) objects 187
 class-inst-size(class --
 addr) objects 187
 class-override!(xt sel-xt
 class-map --) objects 187
 class-previous(class --) objects 187
 class;(--) oof 192
 class>order(class --) objects 187
 class?(o -- flag) oof 191
 clear-libs(--) gforth-0.7 214
 clear-path(path-addr --) gforth-0.5 143

clearstack(... --) gforth-0.2..... 201
clearstacks(... --) gforth-0.7..... 201
close-dir(wdirid -- wior) gforth-0.5... 142
close-file(wfileid -- wior) file..... 140
close-pipe(wfileid -- wretval
wior) gforth-0.2..... 159
cmove(c-from c-to u --) string..... 77
cmove>(c-from c-to u --) string..... 77
code("name" -- colon-sys) tools-ext.... 217
code-address!(c_addr xt --)
gforth-obsolete..... 233
color-cover(--) gforth-1.0..... 206
common-list(list1 list2 -- list3)
gforth-internal..... 170
COMP' ("name" -- w xt) gforth-0.2..... 120
compare(c-addr1 u1 c-addr2 u2
-- n) string..... 77
compile, (xt --) core-ext..... 124
compile-lp+!(n --) gforth-0.2..... 169
compile-only(--) gforth-0.2..... 116
compile-only?(nt -- flag) gforth-1.0... 230
cond("name" --) gforth-experimental.... 210
const-does>(run-time: w*uw r*ur uw ur
"name" --) gforth-0.6..... 112
Constant(w "name" --) core..... 99
construct(... object --) objects..... 187
context(-- addr) gforth-0.2..... 135
contof(compilation case-sys1 of-sys --
case-sys2 ; run-time --) gforth-1.0.... 93
convert(ud1 c-addr1 -- ud2 c-addr2)
core-ext-obsolescent..... 158
count(c-addr1 -- c-addr2 u) core..... 84
Country(<lang> "name" --)
gforth-experimental..... 161
cov%(--) gforth-experimental..... 206
cov+(--) gforth-experimental..... 207
cputime(-- duser dsystem) gforth-0.5... 235
cr(--) core..... 153
Create("name" --) core..... 98
create-file(c-addr u wfam --
wfileid wior) file..... 140
create-from(nt "name" --) gforth-1.0... 111
critical-section(xt semaphore --)
gforth-experimental..... 209
cs-vocabulary("name" --) gforth-1.0.... 134
cs-wordlist(-- wid) gforth-1.0..... 134
CS-DROP(dest --) gforth-1.0..... 91
CS-PICK(orig0/dest0 orig1/dest1 ...
origu/destu u -- ... orig0/dest0)
tools-ext..... 91
CS-ROLL(destu/origu .. dest0/orig0 u -- ..
dest0/orig0 destu/origu) tools-ext.... 91
ctz(x -- u) gforth-1.0..... 63
current'("selector" -- xt) objects..... 187
current(-- addr) gforth-0.2..... 135
current-interface(-- addr) objects..... 187

D

d+(ud1 ud2 -- ud) double..... 58
d-(d1 d2 -- d) double..... 58
d.(d --) double..... 148
d.r(d n --) double..... 148
d<(d1 d2 -- f) double..... 64
d<=(d1 d2 -- f) gforth-0.2..... 64
d<>(d1 d2 -- f) gforth-0.2..... 64
d=(d1 d2 -- f) double..... 64
d>(d1 d2 -- f) gforth-0.2..... 64
d>=(d1 d2 -- f) gforth-0.2..... 65
d>f(d -- r) floating..... 65
d>s(d -- n) double..... 58
d0<(d -- f) double..... 65
d0<=(d -- f) gforth-0.2..... 65
d0<>(d -- f) gforth-0.2..... 65
d0=(d -- f) double..... 65
d0>(d -- f) gforth-0.2..... 65
d0>=(d -- f) gforth-0.2..... 65
d2*(d1 -- d2) double..... 63
d2/(d1 -- d2) double..... 63
dabs(d -- ud) double..... 58
dark-mode(--) gforth-1.0..... 155
darshift(d1 u -- d2) gforth-1.0..... 63
dbg("name" --) gforth-0.2..... 206
debug-fid(-- file-id) gforth-1.0..... 203
dec.(n --) gforth-0.2..... 148
decimal(--) core..... 128
default-color(--) gforth-1.0..... 154
defer!(xt xt-deferred --) core-ext.... 114
defer(--) oof..... 192
Defer("name" --) core-ext..... 114
defer@(xt-deferred -- xt) core-ext.... 114
defers(compilation "name" -- ; run-time ...
-- ...) gforth-0.2..... 114
definer!(definer xt --)
gforth-obsolete..... 234
defines(xt class "name" --) mini-oof... 193
definitions(--) search..... 133, 191
delete(buffer size u --) gforth-0.7..... 81
delete-file(c-addr u -- wior) file..... 140
depth(-- +n) core..... 201
df!(r df-addr --) floating-ext..... 73
df@(df-addr -- r) floating-ext..... 73
dfalign(--) floating-ext..... 71
dfaligned(c-addr -- df-addr
) floating-ext..... 76
dffield:(u1 "name" -- u2)
floating-ext..... 178
dfloat%(-- align size) gforth-0.4..... 176
dfloat+(df-addr1 -- df-addr2
) floating-ext..... 76
dfloat/(n1 -- n2) gforth-1.0..... 76
dfloats(n1 -- n2) floating-ext..... 76
dict-new(... class -- object) objects.. 187
discode(addr u --) gforth-0.2..... 220
dispose(--) oof..... 191
dlshift(ud1 u -- ud2) gforth-1.0..... 63

dmax(d1 d2 -- d) double..... 58
 dmin(d1 d2 -- d) double..... 58
 dnegate(d1 -- d2) double..... 58
 DO(compilation -- do-sys ; run-time w1 w2
 -- loop-sys) core..... 92
 docol:(-- addr) gforth-0.2..... 234
 docon:(-- addr) gforth-0.2..... 234
 dodefer:(-- addr) gforth-0.2..... 234
 does-code!(xt1 xt2 --) gforth-0.2..... 234
 DOES>(compilation colon-sys1 --
 colon-sys2) core..... 106
 dofield:(-- addr) gforth-0.2..... 234
 DONE(compilation orig -- ; run-time
 --) gforth-0.2..... 92
 double%(-- align size) gforth-0.4..... 176
 douser:(-- addr) gforth-0.2..... 234
 dovar:(-- addr) gforth-0.2..... 234
 dpl(-- a-addr) gforth-0.2..... 128
 drol(ud1 u -- ud2) gforth-1.0..... 64
 drop(w --) core..... 68
 dror(ud1 u -- ud2) gforth-1.0..... 64
 drshift(ud1 u -- ud2) gforth-1.0..... 63
 du/mod(d u -- n u1) gforth-1.0..... 59
 du<(ud1 ud2 -- f) double-ext..... 65
 du<=(ud1 ud2 -- f) gforth-0.2..... 65
 du>(ud1 ud2 -- f) gforth-0.2..... 65
 du>=(ud1 ud2 -- f) gforth-0.2..... 65
 dump(addr u --) tools..... 202
 dup(w -- w w) core..... 68

E

e\$, (addr u --) gforth-experimental..... 210
 early(--) oof..... 192
 edit("name" --) gforth-1.0..... 198, 204
 edit-line(c-addr n1 n2 -- n3
) gforth-0.6..... 158
 eflit,(x --) gforth-experimental..... 210
 ekey(-- u) facility-ext..... 156
 ekey>char(u -- u false | c true
) facility-ext..... 156
 ekey>fkey(u1 -- u2 f) facility-ext..... 156
 ekey?(-- flag) facility-ext..... 156
 elit,(x --) gforth-experimental..... 210
 ELSE(compilation orig1 -- orig2 ;
 run-time --) core..... 91
 emit(c --) core..... 154
 emit-file(c wfileid -- wior
) gforth-0.2..... 141
 empty-buffer(buffer --) gforth-0.2..... 147
 empty-buffers(--) block-ext..... 147
 end-c-library(--) gforth-0.7..... 214
 end-class(align offset
 "name" --) objects..... 187, 193
 end-class-noname(align offset --
 class) objects..... 187
 end-code(colon-sys --) gforth-0.2..... 217
 end-interface("name" --) objects..... 187

end-interface-noname(--
 interface) objects..... 187
 end-methods(--) objects..... 188
 end-struct(align size "name"
 --) gforth-0.2..... 176
 end-structure(struct-sys +n --
) facility-ext..... 177
 endcase(compilation case-sys -- ;
 run-time x --) core-ext..... 92
 ENDIF(compilation orig -- ; run-time
 --) gforth-0.2..... 91
 endof(compilation case-sys1 of-sys --
 case-sys2 ; run-time --) core-ext..... 92
 endscope(compilation scope -- ;
 run-time --) gforth-0.2..... 165
 endtry(compilation -- ; run-time
 R:sys1 --) gforth-0.5..... 96
 endtry-iferror(compilation orig1 -- orig2 ;
 run-time R:sys1 --) gforth-0.7..... 97
 endwith(--) oof..... 192
 environment-wordlist(-- wid
) gforth-0.2..... 137
 environment?(c-addr u -- false /
 ... true) core..... 137
 erase(addr u --) core-ext..... 77
 error-color(--) gforth-1.0..... 155
 error-hl-inv(--) gforth-1.0..... 155
 error-hl-ul(--) gforth-1.0..... 155
 evaluate(... addr u -- ...
) core,block..... 127
 event-loop(--) gforth-experimental..... 209
 event:("name" --)
 gforth-experimental..... 209
 event>(task --) gforth-experimental..... 209
 exception(addr u -- n) gforth-0.2..... 94
 execute(xt --) core..... 118
 execute-parsing(... addr u xt --
 ...) gforth-0.6..... 132
 execute-parsing-file(i*x fileid xt --
 j*x) gforth-0.6..... 133
 execute-task(xt -- task)
 gforth-experimental..... 207
 EXIT(compilation -- ; run-time
 nest-sys --) core..... 94
 exitm(--) objects..... 188
 expect(c-addr +n --)
 core-ext-obsoloescent..... 158

F

f!(r f-addr --) floating.....	72
f*(r1 r2 -- r3) floating.....	65
f** (r1 r2 -- r3) floating-ext.....	66
f+ (r1 r2 -- r3) floating.....	65
f,(f --) gforth-0.2.....	71
f- (r1 r2 -- r3) floating.....	65
f-rot(r1 r2 r3 -- r3 r1 r2) floating.....	69
f.(r --) floating-ext.....	151
f.rdp(rf +nr +nd +np --) gforth-0.6.....	152
f.s(--) gforth-0.2.....	201
f/(r1 r2 -- r3) floating.....	65
f<(r1 r2 -- f) floating.....	67
f<=(r1 r2 -- f) gforth-0.2.....	67
f<>(r1 r2 -- f) gforth-0.2.....	67
f=(r1 r2 -- f) gforth-0.2.....	67
f>(r1 r2 -- f) gforth-0.2.....	67
f>=(r1 r2 -- f) gforth-0.2.....	67
f>buf-rdp(rf c-addr +nr +nd +np --) gforth-0.6.....	152
f>d(r -- d) floating.....	65
f>l(r --) gforth-0.2.....	169
f>s(r -- n) floating-ext.....	65
f>str-rdp(rf +nr +nd +np -- c-addr nr) gforth-0.6.....	152
f@(f-addr -- r) floating.....	72
f@local#(#noffset -- r) gforth-0.2.....	169
f~(r1 r2 r3 -- flag) floating-ext.....	67
f~abs(r1 r2 r3 -- flag) gforth-0.5.....	67
f~rel(r1 r2 r3 -- flag) gforth-0.5.....	67
f0<(r -- f) floating.....	67
f0<=(r -- f) gforth-0.2.....	67
f0<>(r -- f) gforth-0.2.....	67
f0=(r -- f) floating.....	67
f0>(r -- f) gforth-0.2.....	67
f0>=(r -- f) gforth-0.2.....	67
f2*(r1 -- r2) gforth-0.2.....	66
f2/(r1 -- r2) gforth-0.2.....	66
fabs(r1 -- r2) floating-ext.....	65
facos(r1 -- r2) floating-ext.....	67
facosh(r1 -- r2) floating-ext.....	67
falign(--) floating.....	71
faligned(c-addr -- f-addr) floating.....	76
falog(r1 -- r2) floating-ext.....	66
false(-- f) core-ext.....	56
fasin(r1 -- r2) floating-ext.....	67
fasinh(r1 -- r2) floating-ext.....	67
fast-throw(... wball -- ... wball) gforth-experimental.....	94
fatan(r1 -- r2) floating-ext.....	67
fatan2(r1 r2 -- r3) floating-ext.....	67
fatanh(r1 -- r2) floating-ext.....	67
faxpy(ra f-x nstride f-y nstride y ucount --) gforth-0.5.....	66
fconstant(r "name" --) floating.....	100
fcos(r1 -- r2) floating-ext.....	66
fcosh(r1 -- r2) floating-ext.....	67
fdepth(-- +n) floating.....	201
fdrop(r --) floating.....	68
fdup(r -- r r) floating.....	68
fe.(r --) floating-ext.....	151
fexp(r1 -- r2) floating-ext.....	66
fexpm1(r1 -- r2) floating-ext.....	66
ffield:(u1 "name" -- u2) floating-ext ..	178
ffourth(r1 r2 r3 r4 -- r1 r2 r3 r4 r1) gforth-1.0.....	69
field(align1 offset1 align size "name" -- align2 offset2) gforth-0.2.....	177
field:(u1 "name" -- u2) facility-ext ...	177
file-eof?(wfileid -- flag) gforth-0.6..	141
file-position(wfileid -- ud wior) file.....	141
file-size(wfileid -- ud wior) file.....	141
file-status(c-addr u -- wfam wior) file-ext.....	141
filename-match(c-addr1 u1 c-addr2 u2 -- flag) gforth-0.5.....	142
fill(c-addr u c --) core.....	77
find(c-addr -- xt +-1 c-addr 0) core,search.....	134
find-name(c-addr u -- nt 0) gforth-0.2.....	119
find-name-in(c-addr u wid -- nt 0) gforth-1.0.....	119
fkey.(u --) gforth-1.0.....	157
FLiteral(compilation r -- ; run-time -- r) floating.....	121
fln(r1 -- r2) floating-ext.....	66
flnp1(r1 -- r2) floating-ext.....	66
float%(-- align size) gforth-0.4.....	177
float(-- u) gforth-0.3.....	76
float+(f-addr1 -- f-addr2) floating.....	76
float/(n1 -- n2) gforth-1.0.....	76
floating-stack(-- n) environment.....	68
floats(n1 -- n2) floating.....	76
flog(r1 -- r2) floating-ext.....	66
floor(r1 -- r2) floating.....	66
FLOORED(-- f) environment.....	60
flush(--) block.....	147
flush-file(wfileid -- wior) file-ext...	141
flush-icache(c-addr u --) gforth-0.2...	218
fm/mod(d1 n1 -- n2 n3) core.....	59
fmax(r1 r2 -- r3) floating.....	65
fmin(r1 r2 -- r3) floating.....	66
fnegate(r1 -- r2) floating.....	65
fnip(r1 r2 -- r2) gforth-0.2.....	68
FOR(compilation -- do-sys ; run-time u -- loop-sys) gforth-0.2.....	92
form(-- nlines ncols) gforth-0.2.....	154
Forth(--) search-ext.....	134
forth-recognize(c-addr u -- ... translate-xt) recognizer.....	131
forth-recognizer(-- xt) gforth-experimental.....	131
forth-wordlist(-- wid) search.....	133
forward("name" --) gforth-1.0.....	114

fourth(w1 w2 w3 w4 -- w1 w2 w3 w4
 w1) gforth-1.0..... 68
 fover(r1 r2 -- r1 r2 r1) floating..... 68
 fp!(f-addr -- f:...) gforth-0.2..... 69
 fp.(r --) floating-ext..... 151
 fp0(f:... -- f-addr) gforth-0.2..... 69
 fp0(-- a-addr) gforth-0.4..... 69
 fpath(-- path-addr) gforth-0.4..... 143
 fpick(f:... u -- f:... r) gforth-0.4..... 69
 free(a_addr -- wior) memory..... 72
 frot(r1 r2 r3 -- r2 r3 r1) floating..... 69
 fround(r1 -- r2) floating..... 66
 fs.(r --) floating-ext..... 151
 fsin(r1 -- r2) floating-ext..... 66
 fsincos(r1 -- r2 r3) floating-ext..... 66
 fsinh(r1 -- r2) floating-ext..... 67
 fsqrt(r1 -- r2) floating-ext..... 66
 fswap(r1 r2 -- r2 r1) floating..... 69
 ftan(r1 -- r2) floating-ext..... 67
 ftanh(r1 -- r2) floating-ext..... 67
 fthird(r1 r2 r3 -- r1 r2 r3 r1
) gforth-1.0..... 69
 ftuck(r1 r2 -- r2 r1 r2) gforth-0.2..... 69
 fvariable("name" --) floating..... 99

G

g(--) gforth-0.7..... 198
 get-block-fid(-- wfileid) gforth-0.2... 146
 get-current(-- wid) search..... 133
 get-dir(c-addr1 u1 -- c-addr2
 u2) gforth-0.7..... 142
 get-order(-- widn .. wid1 n) search..... 133
 get-recognizers(-- xt1 .. xtn n)
 gforth-experimental..... 131
 getenv(c-addr1 u1 -- c-addr2
 u2) gforth-0.2..... 235
 gforth(-- c-addr u)
 gforth-environment..... 137
 gg(--) gforth-1.0..... 198

H

halt(task --) gforth-experimental..... 208
 heap-new(... class -- object) objects.. 188
 help("rest-of-line" --) gforth-1.0.. 6, 198
 here(-- addr) core..... 70
 hex(--) core-ext..... 128
 hex.(u --) gforth-0.2..... 148
 hold(char --) core..... 149
 holds(addr u --) core-ext..... 149
 how:(--) oof..... 192

I

i'(R:w R:w2 -- R:w R:w2 w) gforth-0.2.... 86
 i(R:n -- R:n n) core..... 86
 id.(nt --) gforth-0.6..... 119
 IF(compilation -- orig ;
 run-time f --) core..... 90
 iferror(compilation orig1 -- orig2 ;
 run-time --) gforth-0.7..... 96
 immediate(--) core..... 116
 immediate?(nt -- flag) gforth-1.0..... 233
 implementation(interface --) objects... 188
 include(... "file" -- ...) file-ext.... 139
 include-file(i*x wfileid -- j*x) file.. 139
 include-locale("name" --)
 gforth-experimental..... 161
 included(i*x c-addr u -- j*x) file..... 139
 included-locale(addr u --)
 gforth-experimental..... 161
 included?(c-addr u -- f) gforth-0.2.... 139
 infile-execute(... xt file-id --
 ...) gforth-0.7..... 142
 infile-id(-- file-id) gforth-0.4..... 142
 info-color(--) gforth-1.0..... 155
 init(... --) oof..... 191
 init-asm(--) gforth-0.2..... 217
 init-object(... class object
 --) objects..... 188
 initiate(xt task --)
 gforth-experimental..... 207
 input-color(--) gforth-1.0..... 155
 insert(string length buffer size
 --) gforth-0.7..... 81
 inst-value(align1 offset1 "name" --
 align2 offset2) objects..... 188
 inst-var(align1 offset1 align size "name" --
 align2 offset2) objects..... 188
 interface(--) objects..... 188
 interpret/compile:(interp-xt comp-xt
 "name" --) gforth-0.2..... 116
 invert(w1 -- w2) core..... 62
 is(xt "name" --) oof..... 191
 IS(value "name" --) core-ext..... 114

J

j(R:n R:w1 R:w2 -- n R:n
 R:w1 R:w2) core..... 86

K

k(*R:n R:w1 R:w2 R:w3 R:w4 -- n R:n R:w1 R:w2
 R:w3 R:w4*) gforth-0.3 86
 k-alt-mask(-- *u*) facility-ext 157
 k-ctrl-mask(-- *u*) facility-ext 157
 k-delete(-- *u*) facility-ext 156
 k-down(-- *u*) facility-ext 156
 k-end(-- *u*) facility-ext 156
 k-f1(-- *u*) facility-ext 156
 k-f10(-- *u*) facility-ext 157
 k-f11(-- *u*) facility-ext 157
 k-f12(-- *u*) facility-ext 157
 k-f2(-- *u*) facility-ext 156
 k-f3(-- *u*) facility-ext 156
 k-f4(-- *u*) facility-ext 156
 k-f5(-- *u*) facility-ext 156
 k-f6(-- *u*) facility-ext 157
 k-f7(-- *u*) facility-ext 157
 k-f8(-- *u*) facility-ext 157
 k-f9(-- *u*) facility-ext 157
 k-home(-- *u*) facility-ext 156
 k-insert(-- *u*) facility-ext 156
 k-left(-- *u*) facility-ext 156
 k-next(-- *u*) facility-ext 156
 k-prior(-- *u*) facility-ext 156
 k-right(-- *u*) facility-ext 156
 k-shift-mask(-- *u*) facility-ext 157
 k-up(-- *u*) facility-ext 156
 key(-- *char*) core 155
 key-file(*fd* -- *key*) gforth-0.4 140
 key-ior(-- *char* *ior*) gforth-1.0 155
 key?(-- *flag*) facility 155
 key?-file(*wfileid* -- *f*) gforth-0.4 141

L

l!(*w c-addr* --) gforth-0.7 73
 l(--) gforth-1.0 197
 l,(*l* --) gforth-1.0 71
 l>s(*x* -- *n*) gforth-1.0 74
 l@ (*c-addr* -- *u*) gforth-0.7 73
 L("*lsid*<">" -- *lsid*)
 gforth-experimental 161
 laddr#(*#noffset* -- *c-addr*) gforth-0.2.. 169
 laligned(*addr* -- *addr'*) gforth-1.0 76
 Language("*name*" --)
 gforth-experimental 161
 latest(-- *nt*) gforth-0.6 119
 latestnt(-- *nt*) gforth-1.0 119
 latestxt(-- *xt*) gforth-0.6 101
 lbe(*u1* -- *u2*) gforth-1.0 74
 LEAVE(*compilation* -- ; *run-time*
 loop-sys --) core 92
 lib-error(-- *c-addr u*) gforth-0.7 215
 lib-sym(*c-addr1 u1 u2* -- *u3*
) gforth-0.4 215
 license(--) gforth-0.2 6
 light-mode(--) gforth-1.0 155

link("*name*" -- *class addr*) oof 191
 list(*u* --) block-ext 146
 list-size(*list* -- *u*) gforth-internal... 170
 Literal(*compilation n* -- ;
 run-time -- *n*) core 121
 ll(--) gforth-1.0 199
 lle(*u1* -- *u2*) gforth-1.0 74
 load(*i*x u* -- *j*x*) block 147
 load-cov(--) gforth-experimental 207
 locale!(*addr u lsid* --)
 gforth-experimental 161
 locale-csv("*name*" --)
 gforth-experimental 161
 locale-csv-out("*name*" --)
 gforth-experimental 162
 locale-file(*fid* --)
 gforth-experimental 161
 locale@(*lsid* -- *addr u*)
 gforth-experimental 161
 locate("*name*" --) gforth-1.0 197, 203
 lock(*semaphore* --)
 gforth-experimental 208
 log2(*u* -- *n*) gforth-1.0 63
 LOOP(*compilation do-sys* -- ; *run-time*
 loop-sys1 -- | *loop-sys2*) core 92
 lp!(*c-addr* --) gforth-internal 70, 169
 lp+!#(*#noffset* --) gforth-0.2 169
 lp@ (-- *addr*) gforth-0.2 70
 lp0(-- *a-addr*) gforth-0.4 70
 lrol(*u1 u* -- *u2*) gforth-1.0 63
 lror(*u1 u* -- *u2*) gforth-1.0 63
 lshift(*u1 u* -- *u2*) core 62
 LU("*lsid*<">" -- *lsid*)
 gforth-experimental 161

M

m*(*n1 n2* -- *d*) core 58
 m*/(*d1 n2 u3* -- *dquot*) double 60
 m+(*d1 n* -- *d2*) double 58
 m:(-- *xt colon-sys*; *run-time*:
 object --) objects 188
 macros-wordlist(-- *wid*)
 gforth-experimental 162
 marker("<*spaces*> *name*" --) core-ext 202
 max(*n1 n2* -- *n*) core 57
 maxalign(--) gforth-0.2 71
 maxaligned(*addr1* -- *addr2*) gforth-0.2... 76
 maxdepth-.s(-- *addr*) gforth-0.2 201
 method(*xt "name"* --) objects... 188, 192, 193
 methods(*class* --) objects 188
 min(*n1 n2* -- *n*) core 57
 mkdir-parents(*c-addr u mode* --
 ior) gforth-0.7 143
 mod(*n1 n2* -- *n*) core 59
 modf(*n1 n2* -- *n*) gforth-1.0 59
 modf-stage2m(*n1 a-reci* --
 umodulus) gforth-1.0 61

mods(*n1 n2 -- n*) gforth-1.0..... 59
 move(*c-from c-to ucount --*) core..... 77
 ms(*n --*) facility-ext..... 235
 mux(*u1 u2 u3 -- u*) gforth-1.0..... 62

N

n(*--*) gforth-1.0..... 197
 naligned(*addr1 n -- addr2*
) gforth-0.5..... 76, 177
 name(*-- c-addr u*) gforth-obsolete..... 132
 name>compile(*nt -- w xt*) tools-ext..... 119
 name>interpret(*nt -- xt|0*) tools-ext... 119
 name>link(*nt1 -- nt2 / 0*
) gforth-1.0..... 119, 230
 name>string(*nt -- addr u*) tools-ext..... 119
 native@ (*lsid -- addr u*)
 gforth-experimental..... 161
 needs(... "name" -- ...) gforth-0.2.... 139
 negate(*n1 -- n2*) core..... 57
 new(*-- o*) oof..... 191, 193
 new[] (*n -- o*) oof..... 191
 newline(*-- c-addr u*) gforth-0.5..... 80
 newtask(*stacksize -- task*)
 gforth-experimental..... 207
 newtask4(*dsize rsize fsize lsize -- task*)
 gforth-experimental..... 207
 next-arg(*-- addr u*) gforth-0.7..... 163
 next-case(*compilation case-sys -- ;*
 run-time --) gforth-1.0..... 92
 NEXT(*compilation do-sys -- ; run-time*
 loop-sys1 -- | loop-sys2) gforth-0.2.... 92
 nextname(*c-addr u --*) gforth-0.2..... 102
 nip(*w1 w2 -- w2*) core-ext..... 68
 noname(*--*) gforth-0.2..... 101
 noname-from(*xt --*) gforth-1.0..... 112
 noop(*--*) gforth-0.2..... 118
 notfound(*state --*)
 gforth-experimental..... 130
 nothrow(*--*) gforth-0.7..... 95
 ns(*d --*) gforth-1.0..... 235
 nt(*--*) gforth-1.0..... 199
 ntime(*-- dtime*) gforth-1.0..... 235
 nw(*--*) gforth-1.0..... 198

O

o>(*r:c-addr --*) new..... 196
 object(*-- class*) objects..... 188, 193
 of(*compilation -- of-sys ; run-time x1 x2*
 -- |x1) core-ext..... 92
 off(*a-addr --*) gforth-0.2..... 57
 on(*a-addr --*) gforth-0.2..... 56
 once(*--*) gforth-1.0..... 203
 Only(*--*) search-ext..... 134
 open-blocks(*c-addr u --*) gforth-0.2.... 146
 open-dir(*c-addr u -- wdirid*
 wior) gforth-0.5..... 142

open-file(*c-addr u wfam --*
 wfileid wior) file..... 140
 open-lib(*c-addr1 u1 -- u2*) gforth-0.4.. 215
 open-path-file(*addr1 u1 path-addr -- wfileid*
 addr2 u2 0 | ior) gforth-0.2..... 143
 open-pipe(*c-addr u wfam -- wfileid*
 wior) gforth-0.2..... 159
 or(*w1 w2 -- w*) core..... 62
 order(*--*) search-ext..... 134
 os-class(*-- c-addr u*)
 gforth-environment..... 137
 out(*-- addr*) gforth-1.0..... 153
 outfile-execute(... *xt file-id --*
 ...) gforth-0.7..... 141
 outfile-id(*-- file-id*) gforth-0.2..... 142
 over(*w1 w2 -- w1 w2 w1*) core..... 68
 overrides(*xt "selector" --*) objects.... 188

P

pad(*-- c-addr*) core-ext..... 77
 page(*--*) facility..... 154
 parse(*xchar "ccc<xchar>" -- c-addr u*)
 core-ext, xchar-ext..... 132
 parse-name(*"name" -- c-addr*
 u) core-ext..... 132
 parse-word(*-- c-addr u*)
 gforth-obsolete..... 132
 pass(*x1 .. xn n task --*)
 gforth-experimental..... 207
 path+(*path-addr "dir" --*) gforth-0.4... 144
 path=(*path-addr "dir1|dir2|dir3"*
 --) gforth-0.4..... 144
 pause(*--*) gforth-experimental..... 208
 perform(*a-addr --*) gforth-0.2..... 118
 pi(*-- r*) gforth-0.2..... 67
 pick(*S:... u -- S:... w*) core-ext..... 68
 postpone(*"name" --*) core..... 122, 191
 postpone,(*w xt --*) gforth-0.2..... 120
 pow2?(*u -- f*) gforth-1.0..... 63
 precision(*-- u*) floating-ext..... 151
 previous(*--*) search-ext..... 134
 print(*object --*) objects..... 189
 printdebugdata(*--*) gforth-0.2..... 203
 protected(*--*) objects..... 189
 pthread_cond_broadcast(*cond -- r*)
 gforth-experimental..... 210
 pthread_cond_signal(*cond -- r*)
 gforth-experimental..... 210
 pthread_cond_timedwait(*cond mutex abstime*
 -- r) gforth-experimental..... 210
 pthread_cond_wait(*cond mutex -- r*)
 gforth-experimental..... 210
 ptr(*"name" --*) oof..... 191, 192
 public(*--*) objects..... 189

Q

query(--) core-ext-obsolete... 127
 quit(?? -- ??) core... 236

R

r/o(-- fam) file... 140
 r/w(-- fam) file... 140
 r>(R:w -- w) core... 69
 r@(-- w ; R:w -- w) core... 69
 rdrop(R:w --) gforth-0.2... 69
 read-csv(addr u xt --)
 gforth-experimental... 162
 read-dir(c-addr u1 wdirid -- u2 flag
 wior) gforth-0.5... 142
 read-file(c-addr u1 wfileid --
 u2 wior) file... 140
 read-line(c-addr u1 wfileid -- u2
 flag wior) file... 140
 rec-body(addr u -- xt translate-tick |
 translate-null) gforth-experimental... 131
 rec-dtick(addr u -- nt rectype-num |
 rectype-null) gforth-experimental... 131
 rec-float(addr u -- r translate-float |
 notfound) gforth-experimental... 130
 rec-nt(addr u -- nt translate-nt | notfound
) gforth-experimental... 130
 rec-num(addr u -- n/d table | notfound)
 gforth-experimental... 130
 rec-string(addr u -- addr u' r:string |
 rectype-null) gforth-experimental... 130
 rec-tick(addr u -- xt rectype-num |
 rectype-null) gforth-experimental... 131
 rec-to(addr u -- xt r:to | rectype-null)
 gforth-experimental... 131
 recognize(addr u rec-addr -- ... rectype)
 gforth-experimental... 131
 recurse(... -- ...) core... 93
 recursive(compilation -- ; run-time
 --) gforth-0.2... 93
 refill(-- flag)
 core-ext,block-ext,file-ext... 132
 rename-file(c-addr1 u1 c-addr2 u2 --
 wior) file-ext... 140
 REPEAT(compilation orig dest -- ;
 run-time --) core... 91
 replace-word(xt1 xt2 --) gforth-1.0... 203
 replaces(addr1 len1 addr2 len2
 --) string-ext... 162
 reposition-file(ud wfileid
 -- wior) file... 141
 represent(r c-addr u -- n f1
 f2) floating... 153
 require(... "file" -- ...) file-ext... 139
 required(i*x addr u -- i*x) file-ext... 139
 resize(a-addr1 u -- a-addr2
 wior) memory... 72
 resize-file(ud wfileid -- wior) file... 141

restart(task --) gforth-experimental... 208
 restore(compilation orig1 -- ;
 run-time --) gforth-0.7... 97
 restore-input(x1 .. xn n --
 flag) core-ext... 127
 restrict(--) gforth-0.2... 116
 rol(u1 u -- u2) gforth-1.0... 64
 roll(x0 x1 .. xn n -- x1 .. xn
 x0) core-ext... 68
 Root(--) gforth-0.2... 135
 ror(u1 u -- u2) gforth-1.0... 64
 rot(w1 w2 w3 -- w2 w3 w1) core... 68
 rp!(a-addr --) gforth-0.2... 70
 rp@(-- a-addr) gforth-0.2... 70
 rp0(-- a-addr) gforth-0.4... 69
 rshift(u1 u -- u2) core... 62

S

s>d(n -- d) core... 58
 s>f(n -- r) floating-ext... 65
 s>number?(addr u -- d f) gforth-0.5... 158
 s>unnumber?(c-addr u -- ud flag
) gforth-0.5... 158
 s\"(compilation 'ccc' -- ; run-time --
 c-addr u) core-ext,file-ext... 79
 S\"(compilation 'ccc' -- ; run-time --
 c-addr u) core,file... 79
 safe/string(c-addr1 u1 n -- c-addr2
 u2) gforth-1.0... 81
 save-buffer(buffer --) gforth-0.2... 147
 save-buffers(--) block... 147
 save-cov(--) gforth-experimental... 206
 save-input(-- x1 .. xn n) core-ext... 127
 savesystem("name" --) gforth-0.2... 263
 scan(c-addr1 u1 c -- c-addr2
 u2) gforth-0.2... 80
 scope(compilation -- scope ;
 run-time --) gforth-0.2... 165
 scr(-- a-addr) block-ext... 146
 seal(--) gforth-0.2... 135
 search(c-addr1 u1 c-addr2 u2 --
 c-addr3 u3 flag) string... 80
 search-wordlist(c-addr count wid -- 0
 | xt +-1) search... 135
 see("<spaces>name" --) tools... 199
 see-code("name" --) gforth-0.7... 199
 see-code-range(addr1 addr2 --
) gforth-0.7... 200
 select(u1 u2 f -- u) gforth-1.0... 57
 selector("name" --) objects... 189
 self(-- o) oof... 191
 semaphore("name" --)
 gforth-experimental... 208
 set-current(wid --) search... 133
 set-dir(c-addr u -- wior) gforth-0.7... 142
 set-does>(xt --) gforth-1.0... 107
 set-execute(ca --) gforth-1.0... 231

```

set-forth-recognize( xt --
  ) recognizer..... 131
set-optimizer( xt -- ) gforth-1.0.... 110, 231
set-order( widn .. wid1 n -- ) search..... 133
set-precision( u -- ) floating-ext..... 152
set-recognizers( xt1 .. xtn n -- )
  gforth-experimental..... 131
sf!( r sf-addr -- ) floating-ext..... 73
sf0( sf-addr -- r ) floating-ext..... 73
salign( -- ) floating-ext..... 71
saligned( c-addr -- sf-addr
  ) floating-ext..... 76
sffield:( u1 "name" -- u2 )
  floating-ext..... 178
sfloat%( -- align size ) gforth-0.4..... 177
sfloat+( sf-addr1 -- sf-addr2
  ) floating-ext..... 76
sfloat/( n1 -- n2 ) gforth-1.0..... 76
sfloats( n1 -- n2 ) floating-ext..... 76
sh( "... " -- ) gforth-0.2..... 235
shift-args( -- ) gforth-0.7..... 163
sign( n -- ) core..... 149
simple-fkey-string( u1 -- c-addr
  u ) gforth-1.0..... 157
simple-see( "name" -- ) gforth-0.6..... 199
simple-see-range( addr1 addr2
  -- ) gforth-0.6..... 199
skip( c-addr1 u1 c -- c-addr2
  u2 ) gforth-0.2..... 81
SLiteral( Compilation c-addr1 u ; run-time
  -- c-addr2 u ) string..... 121
slurp-fid( fid -- addr u ) gforth-0.6..... 141
slurp-file( c-addr1 u1 -- c-addr2
  u2 ) gforth-0.6..... 141
sm/rem( d1 n1 -- n2 n3 ) core..... 59
source( -- addr u ) core..... 127
source-id( -- 0 | -1 | fileid )
  core-ext,file..... 127
sourcefilename( -- c-addr u
  ) gforth-0.2..... 139
sourceline#( -- u ) gforth-0.2..... 140
sp!( a-addr -- S:... ) gforth-0.2..... 69
sp@( S:... -- a-addr ) gforth-0.2..... 69
sp0( -- a-addr ) gforth-0.4..... 69
space( -- ) core..... 153
spaces( u -- ) core..... 153
span( -- c-addr ) core-ext-obsolete... 158
stacksize( -- n ) gforth-experimental.... 207
stacksize4( -- dsize fsize rsize lsize )
  gforth-experimental..... 207
staged/-divisor( addr1 --
  addr2 ) gforth-1.0..... 62
staged/-size( -- u ) gforth-1.0..... 61
static( -- ) oof..... 192
status-color( -- ) gforth-1.0..... 155
stderr( -- wfileid ) gforth-0.2..... 141
stdin( -- wfileid ) gforth-0.4..... 141
stdout( -- wfileid ) gforth-0.2..... 141

```

```

stop( -- ) gforth-experimental..... 208
stop-ns( timeout -- )
  gforth-experimental..... 208
str<( c-addr1 u1 c-addr2 u2 --
  f ) gforth-0.6..... 80
str=( c-addr1 u1 c-addr2 u2 --
  f ) gforth-0.6..... 80
string-prefix?( c-addr1 u1 c-addr2 u2
  -- f ) gforth-0.6..... 80
string-suffix?( c-addr1 u1 c-addr2 u2
  -- f ) gforth-1.0..... 80
struct( -- align size ) gforth-0.2..... 177
sub-list?( list1 list2 -- f )
  gforth-internal..... 170
substitute( addr1 len1 addr2 len2 -- addr2
  len3 n/ior ) string-ext..... 162
success-color( -- ) gforth-1.0..... 155
super( "name" -- ) oof..... 191
swap( w1 w2 -- w2 w1 ) core..... 68
Synonym( "name" "oldname" --
  ) tools-ext..... 114
system( c-addr u -- ) gforth-0.2..... 235

```

T

```

table( -- wid ) gforth-0.2..... 134
task( stacksize "name" -- )
  gforth-experimental..... 207
THEN( compilation orig -- ;
  run-time -- ) core..... 90
third( w1 w2 w3 -- w1 w2 w3 w1
  ) gforth-1.0..... 68
this( -- object ) objects..... 189
threading-method( -- n ) gforth-0.2..... 233
throw( y1 .. ym nerror -- y1 .. ym / z1 ..
  zn error ) exception..... 94
thru( i*x n1 n2 -- j*x ) block-ext..... 147
tib( -- addr ) core-ext-obsolete... 127
time&date( -- nsec nmin nhour nday nmonth
  nyear ) facility-ext..... 235
to-this( object -- ) objects..... 189
TO( value "name" -- ) core-ext..... 100
toupper( c1 -- c2 ) gforth-0.2..... 78
translate-nt( i*x nt -- j*x )
  gforth-experimental..... 131
translate-num( x -- | x )
  gforth-experimental..... 131
translate:( int-xt comp-xt post-xt "name" --
  ) gforth-experimental..... 131
true( -- f ) core-ext..... 56
try( compilation -- orig ; run-time --
  R:sys1 ) gforth-0.5..... 96
tt( u -- ) gforth-1.0..... 199
tuck( w1 w2 -- w2 w1 w2 ) core-ext..... 68
type( c-addr u -- ) core..... 154
typewhite( addr n -- ) gforth-0.2..... 154

```

U

u*/(u1 u2 u3 -- u4) gforth-1.0..... 60
 u*/mod(u1 u2 u3 -- u4 u5) gforth-1.0..... 60
 u.(u --) core..... 148
 u.r(u n --) core-ext..... 148
 u/(u1 u2 -- u) gforth-1.0..... 59
 u/-stage1m(u addr-reci --) gforth-1.0... 61
 u/-stage2m(u1 a-reci --
 uquotient) gforth-1.0..... 61
 u/mod(u1 u2 -- u3 u4) gforth-1.0..... 59
 u/mod-stage2m(u1 a-reci -- umodulus
 uquotient) gforth-1.0..... 62
 u<(u1 u2 -- f) core..... 64
 u<=(u1 u2 -- f) gforth-0.2..... 64
 u>(u1 u2 -- f) core-ext..... 64
 u>=(u1 u2 -- f) gforth-0.2..... 64
 U+DO(compilation -- do-sys ; run-time u1 u2
 -- | loop-sys) gforth-0.2..... 91
 U-DO(compilation -- do-sys ; run-time u1 u2
 -- | loop-sys) gforth-0.2..... 91
 ud.(ud --) gforth-0.2..... 148
 ud.r(ud n --) gforth-0.2..... 148
 ud/mod(ud1 u2 -- urem udquot
) gforth-0.2..... 60
 UDefer("name" --)
 gforth-experimental..... 208
 um*(u1 u2 -- ud) core..... 58
 um/mod(ud u1 -- u2 u3) core..... 59
 umax(u1 u2 -- u) gforth-1.0..... 57
 umin(u1 u2 -- u) gforth-0.5..... 57
 umod(u1 u2 -- u) gforth-1.0..... 59
 umod-stage2m(u1 a-reci --
 umodulus) gforth-1.0..... 61
 under+(n1 n2 n3 -- n2) gforth-0.3..... 57
 unescape(addr1 u1 dest -- dest
 u2) string-ext..... 162
 unlock(semaphore --)
 gforth-experimental..... 208
 unloop(R:w1 R:w2 --) core..... 92
 UNREACHABLE(--) gforth-0.2..... 166
 UNTIL(compilation dest -- ;
 run-time f --) core..... 90
 unused(-- u) core-ext..... 70
 update(--) block..... 147
 updated?(n -- f) gforth-0.2..... 147
 use("file" --) gforth-0.2..... 146
 user'('user' -- n)
 gforth-experimental..... 208
 User("name" --) gforth-0.2..... 99
 uthme(-- dtime) gforth-0.5..... 235
 UValue("name" --) gforth-1.0..... 208

V

v*(f-addr1 nstride1 f-addr2 nstride2
 ucount -- r) gforth-0.5..... 66
 Value(w "name" --) core-ext..... 100
 var(size --) oof..... 192, 193
 Variable("name" --) core..... 99
 view("name" --) gforth-1.0..... 203
 vlist(--) gforth-0.2..... 135
 Vocabulary("name" --) gforth-0.2..... 135
 vocs(--) gforth-0.2..... 135

W

w!(w c-addr --) gforth-0.7..... 73
 w,(w --) gforth-1.0..... 71
 w/o(-- fam) file..... 140
 w>s(x -- n) gforth-1.0..... 74
 w@(c-addr -- u) gforth-0.5..... 73
 waligned(addr -- addr') gforth-1.0..... 76
 warning-color(--) gforth-1.0..... 155
 WARNING(compilation 'ccc' -- ;
 run-time f --) gforth-1.0..... 97
 warnings(-- addr) gforth-0.2..... 98
 wbe(u1 -- u2) gforth-1.0..... 74
 where("name" --) gforth-1.0..... 198
 whereg("name" --) gforth-1.0..... 199
 WHILE(compilation dest -- orig dest ;
 run-time f --) core..... 91
 with(o --) oof..... 192
 within(u1 u2 u3 -- f) core-ext..... 64
 wle(u1 -- u2) gforth-1.0..... 74
 word(char "<chars>ccc<char>--
 c-addr) core..... 132
 wordlist(-- wid) search..... 134
 words(--) tools..... 135
 write-file(c-addr u1 wfileid
 -- wior) file..... 141
 write-line(c-addr u wfileid
 -- ior) file..... 141
 wrol(u1 u -- u2) gforth-1.0..... 63
 wror(u1 u -- u2) gforth-1.0..... 63
 WTF??(--) gforth-1.0..... 203
 ww(u --) gforth-1.0..... 198

X

x!(w c-addr --) gforth-1.0..... 73
 x,(x --) gforth-1.0..... 71
 x-size(xc-addr u1 -- u2) xchar..... 160
 x-width(xc-addr u -- n) xchar-ext..... 160
 x>s(x -- n) gforth-1.0..... 74
 x@(c-addr -- u) gforth-1.0..... 73
 x\string-(xc-addr u1 -- xc-addr
 u2) xchar-ext..... 160
 xaligned(addr -- addr') gforth-1.0..... 76
 xbe(u1 -- u2) gforth-1.0..... 74
 xc!+?(xc xc-addr1 u1 --
 xc-addr2 u2 f) xchar..... 160

<code>xc-size(xc -- u) xchar</code>	159	<code>xdbe(ud1 -- ud2) gforth-1.0</code>	74
<code>xc-width(xc -- n) xchar-ext</code>	160	<code>xdle(ud1 -- ud2) gforth-1.0</code>	74
<code>xc@+(xc-addr1 -- xc-addr2 xc) xchar</code>	160	<code>xemit(xc --) xchar</code>	154
<code>xchar+(xc-addr1 -- xc-addr2) xchar</code>	160	<code>xkey(-- xc) xchar</code>	160
<code>xchar-(xc-addr1 -- xc-addr2</code>		<code>xle(u1 -- u2) gforth-1.0</code>	74
<code>) xchar-ext</code>	160	<code>xor(w1 w2 -- w) core</code>	62
<code>xchar-encoding(-- addr u) xchar-ext</code>	160	<code>xt-new(... class xt --</code>	
<code>xd!(ud c-addr --) gforth-1.0</code>	74	<code>object) objects</code>	189
<code>xd,(xd --) gforth-1.0</code>	71	<code>xt-see(xt --) gforth-0.2</code>	199
<code>xd>s(xd -- d) gforth-1.0</code>	75	<code>xt-see-code(xt --) gforth-1.0</code>	200
<code>xd@(c-addr -- ud) gforth-1.0</code>	74	<code>xt-simple-see(xt --) gforth-1.0</code>	199

Concept and Word Index

Not all entries listed in this index are present verbatim in the text. This index also duplicates, in abbreviated form, all of the words listed in the Word Index (only the names are listed for the words here).

!		<code>[]slurp-file</code>	83
<code>!</code>	72	<code>[]Variable</code>	83
<code>!!FIXME!!</code>	203	<code>\$@</code>	81
<code>!@</code>	209	<code>\$@len</code>	81
		<code>\$boot</code>	83
"		<code>\$del</code>	82
<code>",</code> stack item type	55	<code>\$exec</code>	82
		<code>\$free</code>	82
#		<code>\$init</code>	82
<code>#</code>	149	<code>\$ins</code>	82
<code>#!</code>	266	<code>\$iter</code>	82
<code>#-</code> prefix for decimal numbers	51	<code>\$over</code>	82
<code>#></code>	149	<code>\$save</code>	83
<code>#>></code>	150	<code>\$saved</code>	83
<code>#bell</code>	80	<code>\$slurp</code>	82
<code>#bs</code>	80	<code>\$slurp-file</code>	82
<code>#cr</code>	80	<code>\$split</code>	82
<code>#del</code>	80	<code>\$substitute</code>	162
<code>#eof</code>	80	<code>\$tmp</code>	82
<code>#esc</code>	80	<code>\$unescape</code>	162
<code>#ff</code>	80	<code>\$Variable</code>	83
<code>#lf</code>	80		
<code>#loc</code>	204	%	
<code>#s</code>	149	<code>%-</code> prefix for binary numbers	51
<code>#tab</code>	80	<code>%align</code>	176
<code>#tib</code>	127	<code>%alignment</code>	176
		<code>%alloc</code>	176
\$		<code>%allocate</code>	176
<code>\$!</code>	81	<code>%allot</code>	176
<code>\$!len</code>	81	<code>%size</code>	177
<code>\$+!</code>	82		
<code>\$+!len</code>	81	&	
<code>\$-</code> prefix for hexadecimal numbers	51	<code>&-</code> prefix for decimal numbers	51
<code>\$.</code>	82		
<code>\$?</code>	235	,	
<code>\$[]</code>	82	<code>,</code>	117, 191
<code>\$[]!</code>	82	<code>'-</code> prefix for characters/code points	51
<code>\$[]#</code>	83	<code>'cold</code>	267
<code>\$[]+!</code>	83	<code>'s</code>	208
<code>\$[]</code>	83		
<code>\$[]@</code>	83	(
<code>\$[]boot</code>	83	<code>(</code>	56
<code>\$[]free</code>	83	<code>(local)</code>	172
<code>\$[]map</code>	83	<code>(to)</code>	109, 232
<code>\$[]save</code>	83		
<code>\$[]saved</code>	83		
<code>\$[]slurp</code>	83		

-)
) 204
- ***
- * 57
 */ 59
 */f 59
 */mod 60
 */modf 60
 */mods 60
 */s 59
- +**
- + 57
 +! 72
 +!@ 209
 +D0 91
 +field 177
 +fmode 140
 +load 147
 +LOOP 92
 +ltrace 203
 +thru 147
 +T0 100
 +x/string 160
- ,**
- , 71
-
- 57
 -, tutorial 15
 --> 147
 -appl-image, command-line option 3
 -application, gforthmi option 264
 -clear-dictionary, command-line option 4
 -data-stack-size, command-line option 4
 -debug, command-line option 4
 -dictionary-size, command-line option 3
 -die-on-signal, command-line option 4
 -dynamic command-line option 272
 -dynamic, command-line option 5
 -enable-force-reg, configuration flag 268
 -fp-stack-size, command-line option 4
 -help, command-line option 4
 -image file, invoke image file 265
 -image-file, command-line option 3
 -locals-stack-size, command-line option 4
 -no-dynamic command-line option 272
 -no-dynamic, command-line option 5
 -no-offset-im, command-line option 4
 -no-super command-line option 272
 -no-super, command-line option 5
 -offset-image, command-line option 4
 -path, command-line option 3
 -print-metrics, command-line option 5
 -return-stack-size, command-line option 4
 -ss-greedy, command-line option 5
 -ss-min-..., command-line options 5
 -ss-number, command-line option 5
 -version, command-line option 4
 -vm-commit, command-line option 4
 ->here 71
 -d, command-line option 4
 -DFORCE_REG 268
 -D0 91
 -DUSE_FTOS 274
 -DUSE_NO_FTOS 274
 -DUSE_NO_TOS 274
 -DUSE_TOS 274
 -f, command-line option 4
 -h, command-line option 4
 -i, command-line option 3
 -i, invoke image file 265
 -l, command-line option 4
 -LOOP 92
 -ltrace 203
 -m, command-line option 3
 -p, command-line option 3
 -r, command-line option 4
 -rot 68
 -trailing 81
 -trailing-garbage 160
 -v, command-line option 4
 -W, command-line option 6
 -Wall, command-line option 6
 -Werror, command-line option 6
 -Won, command-line option 6
 -Wpedantic, command-line option 6
- .**
- 148
 ." 153
 .", how it works 48
 .(..... 153
 201
 ." 153
 .cover-raw 206
 .coverage 206
 .debugline 203
 .emacs 259
 .fi files 262
 .gforth-history 7
 .locale-csv 162
 .path 144
 .r 148
 .s 201
 .substitute 162
 .unresolved 114

/		>	
/	59	>	64
/f	59	>=	64
/f-stage1m	61	>addr	171
/f-stage2m	61	>body	107
/l	77	>BODY of non-CREATED words	247
/mod	59	>code-address	233
/modf	59	>definer	234
/modf-stage2m	61	>does-code	234
/mods	59	>float	158
/s	59	>float1	158
/string	81	>in	127
/w	77	>IN greater than input buffer	245
/x	77	>l	169
		>name	119
:		>number	158
:	101, 191	>o	196
:, passing data across	121	>order	134
::	191, 193	>pow2	63
:}d	171	>r	69
:}h	171	>time&date&tz	235
:}l	171		
:m	188	?	
:noname	101	?	201
		?!@	209
;		???	203
;	101	?DO	91
>	172	?dup	68
>]	102	?dup-IF	91
;code	217	?DUP-0=-IF	91
;CODE ending sequence	253	?events	209
;CODE, <i>name</i> not defined via CREATE	253	?LEAVE	92
;CODE, processing input	253	?of	92
;m	188		
;m usage	182	[
;s	94	[121
		[']	117
<		[+LOOP]	130
<	64	[:	102
<#	149	[?DO]	130
<<#	149	[]	191
<=	64	[{:	171
<>	64	[AGAIN]	130
<{:	172	[BEGIN]	130
<bind>	186	[bind]	187
<event	209	[bind] usage	181
<to-inst>	189	[char]	79
		[COMP']	120
=		[current]	187
=	64	[DO]	130
=mkdir	142	[ELSE]	129
		[ENDIF]	129
		[FOR]	130
		[IF]	129
		[IF] and POSTPONE	253

[IF], end of the input source before matching [ELSE] or [THEN]	253
[IFDEF]	129
[IFUNDEF]	130
[LOOP]	130
[NEXT]	130
[parent]	188
[parent] usage	181
[REPEAT]	130
[THEN]	129
[to-inst]	189
[UNTIL]	130
[WHILE]	130

]	
]	121
]]	122
]L	121

‘	
‘ prefix	117
‘ prefix of word	52
‘‘ prefix of word	52

@	
@	72
@local#	169

\	
\	56
\, editing with Emacs	259
\, line length in blocks	247
\c	212
\G	56

{	
{:	172

~	
~~	203
~~, removal with Emacs	259
~~1bt	203
~~bt	203
~~Value	203
~~Variable	203

0

0<	64
0<=	64
0<>	64
0=	64
0>	64
0>=	64
0x-prefix for hexadecimal numbers	51

1

1+	57
1-	57
1/f	66

2

2!	72
2*	63
2,	71
2/	63
2>r	69
2@	72
2Constant	100
2drop	68
2dup	68
2field:	177
2Literal	121
2nip	68
2over	68
2r>	69
2r@	69
2rdrop	69
2rot	68
2swap	68
2tuck	68
2Variable	99

A

a_, stack item type	55
abi-code	217
abort	97
ABORT"	97
ABORT", exception abort sequence	242
abs	57
abstract class	180, 190
accept	157
ACCEPT, display after end of input	242
ACCEPT, editing	241
action-of	114
activate	207
add-cflags	214
add-incdir	214
add-ldflags	214
add-lib	214
add-libpath	214
addr	101

address alignment exception 246
 address alignment exception, stack overflow ... 244
 address arithmetic for structures 173
 address arithmetic words 75
 address unit 75
 address unit, size in bits 242
ADDRESS-UNIT-BITS 76
after-locate 198
AGAIN 90
AHEAD 90
Alias 115
 aliases 114
align 71
aligned 76
 aligned addresses 241
 alignment faults 246
 alignment of addresses for types 75
 alignment tutorial 27
allocate 72
allot 71
also 134
 also, too many word lists in search order 254
also-path 144
 ambiguous conditions, block words 248
 ambiguous conditions, core words 244
 ambiguous conditions, double words 248
 ambiguous conditions, facility words 249
 ambiguous conditions, file words 250
 ambiguous conditions, floating-point words 251
 ambiguous conditions, locals words 252
 ambiguous conditions,
 programming-tools words 253
 ambiguous conditions, search-order words 254
and 62
 angles in trigonometric operations 66
annotate-cov 206
ans-report.fs 238
arg 163
argc 163
 argument input source different than current input
 source for **RESTORE-INPUT** 246
 argument type mismatch 244
 argument type mismatch, **RESTORE-INPUT** 246
 arguments, OS command line 163
argv 163
 arithmetic words 57
 arithmetics tutorial 12
 arrays 98
 arrays tutorial 35
arshift 62
asptr 191, 192
 assembler 217
ASSEMBLER, search order capability 253
assert(..... 204
assert-level 205
assert0(..... 204
assert1(..... 204
assert2(..... 204

assert3(..... 204
 assertions 204
ASSUME-LIVE 167
at-deltaxy 154
at-xy 154
AT-XY can't be performed on user
 output device 249
 Attempt to use zero-length string as a name... 245
 au (address unit) 75
authors 6
 authors of Gforth 283
 auto-indentation of Forth code in Emacs 260

B

b 198
 backtrace 237
 backtrace examination 199
 backtraces with **gforth-fast** 237
barrier 209
base 128
base is not decimal (**REPRESENT**,
 F., **FE.**, **FS.**) 251
base-execute 128
 basic objects usage 180
 batch processing with Gforth 6
before-locate 198
begin-structure 177
BEGIN 90
 benchmarking Forth systems 274
Benchres 276
 big-endian 73
bin 140
bind 186, 191
 bind usage 181
bind' 187
 bitwise operation words 62
bl 80
blank 77
blk 127
BLK, altering **BLK** 248
block 146
 block buffers 144
 block number invalid 248
 block read not possible 248
 block transfer, I/O exception 248
 block words, ambiguous conditions 248
 block words, implementation-defined options .. 247
 block words, other system documentation 248
 block words, system documentation 247
block-included 147
block-offset 146
block-position 146
 blocks 144
 blocks file 144
 blocks files, use with Emacs 261
 blocks in files 250
blocks.fb 144

body-relative address input format	52
Boolean flags	56
bootmessage	267
bound	191
bounds	77
break"	206
break:	206
broken-pipe-error	159
bt	199
buffer	146
bug reporting	282
bw	198
bw-cover	206
bye	6
bye during gforthmi	264
byte order	73

C

c!	72
c\$+!	82
c,	71
c, stack item type	55
c-callback	215
c-function	212
c-funptr	213
c-library	214
c-library-name	214
c-value	212
c-variable	212
c>s	74
c_, stack item type	55
c@	72
C function pointers to Forth words	215
C function pointers, calling from Forth	213
C functions, calls to	210
C functions, declarations	211
C interface	210
C"	84
C, using C for the engine	268
call-c	215
Callback functions written in Forth	215
calling a definition	93
calling C functions	210
capscompare	80
case	92
case as generalized control structure	89
case sensitivity	56
case-sensitivity characteristics	243
case-sensitivity for name lookup	241
CASE control structure	85
catch	95
catch and backtraces	237
catch and this	185
catch in m: ... ;m	182
cell	75
cell size	243
cell%	176

cell+	75
cell-	75
cell-aligned addresses	241
cell/	75
cells	75
cfalign	71
cfaligned	76
cfield:	177
changing the compilation word list (during compilation)	254
char	79
char size	243
char%	176
char+	75
character editing of ACCEPT and EXPECT	241
character encoding	78
character literals	79
character set	241
character strings - displaying	154
character strings - moving and copying	77
character strings - representations	78
character-aligned address requirements	241
character-set extensions and matching of names	241
Characters - chars/bytes vs. extended characters	78
characters - displaying	154
characters tutorial	26
chars	75
child class	179
child words	104
class	178, 187, 191, 193
class binding	181
class binding as optimization	182
class binding, alternative to	181
class binding, implementation	185
class declaration	192
class definition, restrictions	180, 190
class implementation	192
class implementation and representation	185
class scoping implementation	185
class usage	180, 190
class->map	187
class-inst-size	187
class-inst-size discussion	181
class-override!	187
class-previous	187
class;	192
class; usage	190
class>order	187
class?	191
classes and scoping	183
clear screen	154
clear-libs	214
clear-path	143
clearstack	201
clearstacks	201
clock tick duration	249

<code>close-dir</code>	142	<code>context</code>	135
<code>close-file</code>	140	context-sensitive help	259
<code>close-pipe</code>	159	contiguous regions and heap allocation	72
closures	171	contiguous regions in dictionary allocation	70
<code>cmove</code>	77	<code>contof</code>	93
<code>cmove></code>	77	contributors to Gforth	283
<code>code</code>	217	control characters as delimiters	241
code address	233	control structures	84
code coverage	206	control structures for selection	84
code field address	233	control structures programming style	93
code words	217	control structures, user-defined	90
<code>code-address!</code>	233	control-flow stack	90
CODE ending sequence	253	control-flow stack items, locals information	170
CODE, processing input	253	control-flow stack underflow	253
colon definitions	101	control-flow stack, format	241
colon definitions, nesting	102	<code>convert</code>	158
colon definitions, tutorial	14	convertin strings to numbers	157
colon-sys, passing data across :	121	core words, ambiguous conditions	244
<code>color-cover</code>	206	core words, implementation-defined options	241
combined words	116	core words, other system documentation	247
command line arguments, OS	163	core words, system documentation	241
command-line editing	7	<code>count</code>	84
command-line options	3	counted loops	86
comment editing commands	259	counted loops with negative increment	87
comments	56	counted string, maximum size	242
comments tutorial	14	counted strings	78
<code>common-list</code>	170	<code>Country</code>	161
<code>comp-i.fs</code>	264	<code>cov%</code>	206
<code>comp.lang.forth</code>	284	<code>cov+</code>	207
COMP'	120	<code>cputime</code>	235
<code>compare</code>	77	<code>cr</code>	153
comparison of object models	196	<code>Create</code>	98
comparison tutorial	19	<code>create-file</code>	140
compilation semantics	47, 115	<code>create-from</code>	111
compilation semantics tutorial	30	<code>create...does></code> tutorial	34
compilation token	120	CREATE ... DOES>	103
compilation tokens, tutorial	38	CREATE ... DOES>, applications	105
compilation word list	133	CREATE ... DOES>, details	106
compilation word list, change before		CREATE ... SET-DOES>	104
definition ends	254	CREATE and alignment	75
compile state	125	creating objects	181
<code>compile,</code>	124	<code>critical-section</code>	209
<code>compile-lp+!</code>	169	cross-compiler	265, 277
<code>compile-only</code>	116	<code>cross.fs</code>	265, 277
compile-only warning, for ' etc.	244	<code>cs-vocabulary</code>	134
compile-only words	116	<code>cs-wordlist</code>	134
<code>compile-only?</code>	230	CS-DROP	91
compiled code examination	199	CS-PICK	91
compiling compilation semantics	122	CS-PICK, fewer than <i>u</i> +1 items on the	
compiling words	120	control flow-stack	253
<code>cond</code>	210	CS-ROLL	91
conditional compilation	129	CS-ROLL, fewer than <i>u</i> +1 items on the	
conditionals, tutorial	19	control flow-stack	253
<code>const-does></code>	112	ct (compilation token)	120
Constant	99	CT, tutorial	38
constants	99	<code>ctz</code>	63
<code>construct</code>	187	<code>current</code>	135
<code>construct</code> discussion	181	<code>current'</code>	187

current-interface	187
current-interface discussion	185
currying	106
cursor positioning.....	154

D

d+	58
d , stack item type.....	55
d-	58
d	148
d.r	148
d<	64
d<=	64
d<>	64
d=	64
d>	64
d>=	65
d>f	65
d>s	58
d0<	65
d0<=	65
d0<>	65
d0=	65
d0>	65
d0>=	65
d2*	63
d2/	63
D>F , <i>d</i> cannot be presented precisely as a float.....	251
D>S , <i>d</i> out of range of <i>n</i>	248
dabs	58
dark-mode	155
darshift	63
data space - reserving some	70
data space available.....	247
data space containing definitions gets de-allocated	246
data space pointer not properly aligned, , , C ,	246
data space read/write with incorrect alignment	246
data stack	68
data stack manipulation words	68
data structure locals	164
data-relocatable image files	264
data-space, read-only regions.....	243
dbg	206
debug tracer editing commands	259
debug-fid	203
debugging	202
debugging output, finding the source location in Emacs	259
debugging Singlestep.....	205
dec	148
decimal	128
declaring C functions	211
decompilation tutorial.....	15

default type of locals.....	164
default-color	154
defer	192
Defer	114
defer!	114
defer@	114
deferred words.....	112
defers	114
definer	234
definer!	234
defines	193
defining defining words.....	102
defining words	98
defining words tutorial	34
defining words without name.....	101
defining words, name given in a string.....	102
defining words, simple.....	98
defining words, user-defined	102
definition	41
definitions	133, 191
definitions, tutorial.....	14
delete	81
delete-file	140
depth	201
depth changes during interpretation	238
depth-changes.fs	238
design of stack effects, tutorial	17
dest , control-flow stack item	90
df!	73
df_ , stack item type	55
df@	73
df@ or df! used with an address that is not double-float aligned.....	251
dfalign	71
dfaligned	76
dffield:	178
dfloat%	176
dfloat+	76
dfloat/	76
dfloats	76
dict-new	187
dict-new discussion.....	181
dictionary	125
dictionary in persistent form	262
dictionary overflow.....	244
dictionary size default.....	265
digits > 35	242
direct threaded inner interpreter	269
Directories	142
disassembler, general.....	220
discode	220
dispose	191
dividing by zero	244
dividing by zero, floating-point	252
Dividing classes.....	183
dividing integers	58
dividing many integers with the same divisor ...	60
Division by zero	58, 60

division rounding	243
division with potentially negative operands	57
dlshift	63
dmax	58
dmin	58
dnegate	58
DO loops	86
docol:	234
docon:	234
documentation for a word	198
dodefer:	234
dodoes routine	272
does-code!	234
does> tutorial	34
does>-code	233
does>-handler	233
DO	92
DOES>	106
DOES> implementation	272
DOES> in a separate definition	106
DOES> in interpretation state	107
DOES> of non-CREATED words	247
DOES> , visibility of current definition	244
DOES>-code	272
DOES>-parts , stack effect	105
dofield:	234
DONE	92
double precision arithmetic words	57
double words, ambiguous conditions	248
double words, system documentation	248
double%	176
double-cell numbers, input format	51
doubly indirect threaded code	264
douser:	234
dovar:	234
dpl	128
drol	64
drop	68
dror	64
drshift	63
du/mod	59
du<	65
du<=	65
du>	65
du>=	65
dump	202
dup	68
duration of a system clock tick	249
dynamic allocation of memory	72
Dynamic superinstructions with replication	270
Dynamically linked libraries in C interface	214

E

e\$,	210
early	192
early binding	181
edit	198, 204
edit-line	158
editing in ACCEPT and EXPECT	241
eflit ,	210
eforth performance	275
ekey	156
ekey>char	156
ekey>fkey	156
ekey?	156
EKEY , encoding of keyboard events	249
elements of a Forth system	49
elit ,	210
ELSE	91
Emacs and Gforth	259
emit	154
emit-file	141
EMIT and non-graphic characters	241
empty-buffer	147
empty-buffers	147
end-c-library	214
end-class	187, 193
end-class usage	180
end-class-noname	187
end-code	217
end-interface	187
end-interface usage	184
end-interface-noname	187
end-methods	188
end-struct	176
end-struct usage	174
end-structure	177
endcase	92
ENDIF	91
endless loop	86
endof	92
endscope	165
endtry	96
endtry-iferror	97
endwith	192
engine	268
engine performance	274
engine portability	268
engine.s	274
engines, gforth vs. gforth-fast vs. gforth-etc	270
environment variable input format	52
environment variables	7, 264
environment wordset	54
environment-wordlist	137
environment?	137
ENVIRONMENT? string length, maximum	242
environmental queries	137
environmental restrictions	240
equality of floats	67
erase	77

error messages	237
error output, finding the source	
location in Emacs	259
error-color	155
error-hl-inv	155
error-hl-ul	155
etags.fs	259
evaluate	127
event-loop	209
event:	209
event>	209
examining data and code	201
exception	94
exception abort sequence of ABORT"	242
exception source code	199
exception when including source	249
exception words,	
implementation-defined options	248
exception words, system documentation	248
exceptions	94
exceptions tutorial	33
executable image file	265
execute	118
execute-parsing	132
execute-parsing-file	133
execute-task	207
executing code on startup	6
execution frequency	206
execution semantics	115
execution token	41, 117
execution token input format	52
execution token of last defined word	101
execution token of words with undefined	
execution semantics	244
execution tokens tutorial	31
exercises	50
exit in m: ... ;m	182
exitm	188
exitm discussion	182
EXIT	94
expect	158
EXPECT, display after end of input	242
EXPECT, editing	241
explicit register declarations	268
exponent too big for conversion	
(DF!, DF@, SF!, SF@)	252
extended records	175

F

f!	72
f! used with an address that is	
not float aligned	251
f*	65
f**	66
f+	65
f,	71
f, stack item type	55

f-	65
f-rot	69
f.	151
f.rdp	152
f.s	201
f/	65
f<	67
f<=	67
f<>	67
f=	67
f>	67
f>=	67
f>buf-rdp	152
f>d	65
f>l	169
f>s	65
f>str-rdp	152
f_, stack item type	55
f@	72
f@ used with an address that is	
not float aligned	251
f@local#	169
f~	67
f~abs	67
f~rel	67
f0<	67
f0<=	67
f0<>	67
f0=	67
f0>	67
f0>=	67
f2*	66
f2/	66
f83name, stack item type	55
F>D, integer part of float cannot be	
represented by <i>d</i>	252
fabs	65
facility words, ambiguous conditions	249
facility words,	
implementation-defined options	249
facility words, system documentation	248
facos	67
FACOS, float >1	252
facosh	67
FACOSH, float<1	252
factoring	40
factoring similar colon definitions	105
factoring tutorial	17
falign	71
faligned	76
falog	66
false	56
fam (file access method)	140
fasin	67
FASIN, float >1	252
fasinh	67
FASINH, float<0	252
fast-throw	94

fatan	67	FLN , <i>float</i> <= 0	252
fatan2	67	flnp1	66
FATAN2 , both arguments are equal to zero	251	FLNP1 , <i>float</i> <= -1	252
fatanh	67	float	76
FATANH , <i> float </i> > 1	252	float%	177
faxpy	66	float+	76
fconstant	100	float/	76
fcos	66	floating point arithmetic words.....	65
fcosh	67	floating point numbers, format and range	251
fddepth	201	floating point tutorial.....	27
FDL , GNU Free Documentation License	285	floating point unidentified fault, integer division	244
fdrop	68	floating-point arithmetic, pitfalls	65
fdup	68	floating-point comparisons	67
fe	151	floating-point dividing by zero	252
fexp	66	floating-point numbers, input format	51
fexpm1	66	floating-point numbers, rounding or truncation.....	251
ffield:	178	floating-point output.....	151
ffourth	69	floating-point result out of range	251
field	177	floating-point stack	68
field naming convention.....	175	floating-point stack in the standard	68
field usage	174	floating-point stack manipulation words	68
field usage in class definition	180	floating-point stack size	251
field:	177	floating-point stack width	251
file access methods used.....	249	floating-point unidentified fault.....	58
file exceptions	249	Floating-point unidentified fault (on integer division).....	60
file input nesting, maximum depth	250	floating-point unidentified fault, F>D	252
file line terminator.....	249	floating-point unidentified fault, FACOS , FASIN or FATANH	252
file name format.....	249	floating-point unidentified fault, FACOSH	252
file search path	143	floating-point unidentified fault, FASINH or FSQRT	252
file words, ambiguous conditions	250	floating-point unidentified fault, FLN or FLOG ..	252
file words, implementation-defined options.....	249	floating-point unidentified fault, FLNP1	252
file words, system documentation	249	floating-point unidentified fault, FP divide-by-zero	252
file-eof?	141	floating-point words, ambiguous conditions.....	251
file-handling.....	140	floating-point words, implementation-defined options	251
file-position	141	floating-point words, system documentation ...	250
file-size	141	floating-stack	68
file-status	141	floats	76
FILE-STATUS , returned information.....	249	flog	66
filename-match	142	FLOG , <i>float</i> <= 0	252
filenames in ~~ output	203	floor	66
filenames in assertion output	205	floored division	58
files.....	138	FLOORED	60
files containing blocks.....	250	flush	147
files containing Forth code, tutorial.....	13	flush-file	141
files tutorial.....	28	flush-icache	218
fill	77	fm/mod	59
find	134	fmax	65
find-name	119	fmin	66
find-name-in	119	fnegate	65
first definition.....	45	fnip	68
first field optimization	175	FOR loops	88
first field optimization, implementation.....	176		
fkey	157		
flags on the command line.....	3		
flags tutorial.....	19		
flavours of locals.....	164		
FLiteral	121		
fln	66		

foreign language interface	210
FORGET, deleting the compilation word list	253
FORGET, <i>name</i> can't be found	253
FORGET, removing a needed definition	254
forgetting words	202
form	154
format and range of floating point numbers	251
format of glossary entries	54
formatted numeric output	148
Forth	134
Forth - an introduction	40
Forth mode in Emacs	259
Forth source files	139
Forth Tutorial	11
forth-recognize	131
forth-recognizer	131
Forth-related information	284
forth-wordlist	133
forth.el	259
forward	114
FOR	92
fourth	68
fover	68
fp!	69
fp	151
fp@	69
fp0	69
FP output	151
FP tutorial	27
fpath	143
fpick	69
free	72
frequently asked questions	284
frot	69
fround	66
fs	151
fsin	66
fsincos	66
fsinh	67
fsqrt	66
FSQRT, <i>float</i> <0	252
fswap	69
ftan	67
FTAN on an argument <i>r1</i> where cos(<i>r1</i>) is zero	251
ftanh	67
fthird	69
ftuck	69
fully relocatable image files	264
functions, tutorial	14
fvariable	99

G

g	198
gdb disassembler	220
general control structures (<i>case</i>)	89
general files	140
get-block-fid	146
get-current	133
get-dir	142
get-order	133
get-recognizers	131
getenv	235
gforth	137
Gforth - leaving	6
gforth engine	270
Gforth environment	3
Gforth extensions	255
Gforth files	8
Gforth locals	164
Gforth performance	274
Gforth stability	2
gforth-ditc	264
gforth-fast and backtraces	237
gforth-fast engine	270
gforth-fast, difference from gforth	237
gforth-ipc engine	270
gforth.el	259
gforth.el, installation	259
gforth.fi, relocatability	264
GFORTH - environment variable	8, 264
GFORTH - environment variable	8, 264
GFORTH - environment variable	7
gforthmi	264
GFORTH - environment variable	8
GFORTH - environment variable	8
gg	198
giving a name to a library interface	213
glossary notation format	54
GNU C for the engine	268
goals of the Gforth project	2

H

halt	208
header fields	229
header methods	230
header space	133
heap allocation	72
heap-new	188
heap-new discussion	181
heap-new usage	180
help	6, 198
here	70
hex	128
hex	148
highlighting Forth code in Emacs	260
highlighting Forth code in Emacs	260
history file	7
hold	149

holds 149
how: 192
 hybrid direct/indirect threaded code 270

I

i 86
i' 86
 I/O - blocks 144
 I/O - file-handling 138
 I/O - keyboard and display 147
 I/O - see input 157
 I/O exception in block transfer 248
id. 119
 IDE (integrated development environment) 197
 if, tutorial 19
 IF control structure 84
iferror 96
IF 90
 image file 262
 image file background 262
 image file initialization sequence 266
 image file invocation 265
 image file loader 262
 image file, data-relocatable 264
 image file, executable 265
 image file, fully relocatable 264
 image file, non-relocatable 263
 image file, stack and dictionary sizes 265
 image file, turnkey applications 267
 image license 262
immediate 116
 immediate words 47, 116
 immediate, tutorial 30
immediate? 233
implementation 188
 implementation of locals 169
 implementation of structures 176
implementation usage 184
 implementation-defined options, block words .. 247
 implementation-defined options, core words ... 241
 implementation-defined options,
 exception words 248
 implementation-defined options,
 facility words 249
 implementation-defined options, file words 249
 implementation-defined options,
 floating-point words 251
 implementation-defined options, locals words .. 252
 implementation-defined options,
 memory-allocation words 253
 implementation-defined options,
 programming-tools words 253
 implementation-defined options,
 search-order words 254
 in-lining of constants 100
include 139
include search path 143

include, placement in files 259
include-file 139
include-locale 161
 INCLUDE-FILE, *file-id* is invalid 250
 INCLUDE-FILE, I/O exception reading
 or closing *file-id* 250
included 139
included-locale 161
included? 139
 INCLUDED, I/O exception reading
 or closing *file-id* 250
 INCLUDED, named file cannot be opened 250
 including files 139
 including files, stack effect 139
 indentation of Forth code in Emacs 260
 indirect threaded inner interpreter 269
infile-execute 142
infile-id 142
info-color 155
 inheritance 179
init 191
init-asm 217
init-object 188
init-object discussion 181
 initialization sequence of image file 266
initiate 207
 inner interpreter implementation 268
 inner interpreter optimization 269
 inner interpreter, direct threaded 269
 inner interpreter, indirect threaded 269
 input buffer 125
 input format for body-relative addresses 52
 input format for characters/code points 51
 input format for double-cell numbers 51
 input format for environment variables 52
 input format for execution tokens 52
 input format for floating-point numbers 51
 input format for name tokens 52
 input format for single-cell numbers 51
 input format for strings 52
 input from pipes 8
 input line size, maximum 250
 input line terminator 242
 Input Redirection 141
 input sources 127
 input stream 132
 input, linewise from terminal 157
 input, single-key 155
input-color 155
insert 81
inst-value 188
inst-value usage 182
inst-value visibility 183
inst-var 188
inst-var implementation 185
inst-var usage 182
inst-var visibility 183
 instance variables 178

instruction pointer 269
 insufficient data stack or return stack space ... 244
 insufficient space for loop control parameters .. 244
 insufficient space in the dictionary 244
 integer types, ranges 242
 integrated development environment 197
interface 188
 interface implementation 186
 interface to C functions 210
interface usage 184
 interfaces for objects 184
 interpret state 125
 Interpret/Compile states 128
interpret/compile: 116
 interpretation semantics 47, 115
 interpretation semantics tutorial 30
 interpreter - outer 125
 interpreter directives 129
 Interpreting a compile-only word 245
 Interpreting a compile-only word, for a local ... 252
 interpreting a word with undefined
 interpretation semantics 245
 invalid block number 248
 Invalid memory address 244
 Invalid memory address, stack overflow 244
 Invalid name argument, **TO** 246, 252
invert 62
 invoking a selector 179
 invoking Gforth 3
 invoking image files 265
 ior type description 55
ior values and meaning 250, 253
is 191
IS 114
 items on the stack after interpretation 238

J

j 86

K

k 86
k-alt-mask 157
k-ctrl-mask 157
k-delete 156
k-down 156
k-end 156
k-f1 156
k-f10 157
k-f11 157
k-f12 157
k-f2 156
k-f3 156
k-f4 156
k-f5 156
k-f6 157
k-f7 157

k-f8 157
k-f9 157
k-home 156
k-insert 156
k-left 156
k-next 156
k-prior 156
k-right 156
k-shift-mask 157
k-up 156
kern*.fi, relocatability 264
key 155
key-file 140
key-ior 155
key? 155
key?-file 141
 keyboard events, encoding in **EKEY** 249
 Kuehling, David 259

L

l 197
l! 73
l, 71
l>s 74
l@ 73
L" 161
 labels as values 268
laddr# 169
laligned 76
LANG – environment variable 8
Language 161
 last word was headerless 246
 late binding 181
latest 119
latestnt 119
latesttxt 101
lbe 74
LC_ALL – environment variable 8
LC_CTYPE – environment variable 8
LEAVE 92
 leaving definitions, tutorial 23
 leaving Gforth 6
 leaving loops, tutorial 23
 length of a line affected by **** 247
lib-error 215
lib-sym 215
 Libraries in C interface 214
 library interface names 213
license 6
 license for images 262
 lifetime of locals 167
light-mode 155
 line input from terminal 157
 line terminator on input 242
link 191
list 146
list-size 170

LIST display format	247
Literal	121
literal tutorial	36
Literals	120
Literals (in source code)	51
literals for characters and strings	79
little-endian	73
ll	199
lle	74
load	147
load-cov	207
loader for image files	262
loading files at startup	6
loading Forth code, tutorial	13
local in interpretation state	252
local variables, tutorial	18
locale and case-sensitivity	241
locale!	161
locale-csv	161
locale-csv-out	162
locale-file	161
locale@	161
locals	164
locals and return stack	69
locals flavours	164
locals implementation	169
locals information on the control-flow stack	170
locals lifetime	167
locals programming style	168
locals stack	68, 169
locals types	164
locals visibility	165
locals words, ambiguous conditions	252
locals words, implementation-defined options	252
locals words, system documentation	252
locals, default type	164
locals, Gforth style	164
locals, maximum number in a definition	252
locals, Standard Forth style	172
locate	197, 203
lock	208
log2	63
long long	268
loop control parameters not available	246
loops without count	85
loops, counted	86
loops, counted, tutorial	22
loops, endless	86
loops, indefinite, tutorial	21
LOOP	92
lp!	70, 169
lp+!#	169
lp@	70
lp0	70
lrol	63
lror	63
lshift	62
LSHIFT , large shift counts	246

LU" 161

M

m*	58
m*/	60
m+	58
m:	188
m: usage	182
Macros	122
macros	120
macros , advanced tutorial	37
macros-wordlist	162
mapping block ranges to files	25
marker	202
max	57
maxalign	71
maxaligned	76
maxdepth-.s	201
maximum depth of file input nesting	250
maximum number of locals in a definition	252
maximum number of word lists	
in search order	254
maximum size of a counted string	242
maximum size of a definition	
name, in characters	242
maximum size of a parsed string	242
maximum size of input line	250
maximum string length for	
ENVIRONMENT? , in characters	242
memory access words	72
memory access/allocation tutorial	25
memory alignment tutorial	27
memory block words	77
memory overcommit for dictionary and stacks ...	4
memory words	70
memory-allocation word set	72
memory-allocation words,	
implementation-defined options	253
memory-allocation words, system	
documentation	253
message send	179
metacompiler	265, 277
method	178, 188, 192, 193
method conveniences	182
method map	185
method selector	178
method usage	190
methods	188
methods...end-methods	183
min	57
mini-oof	192
mini-oof example	193
mini-oof usage	193
mini-oof.fs , differences to other models	197
minimum search order	254
miscellaneous words	236
mixed precision arithmetic words	58

mkdir-parents	143
mod	59
modf	59
modf-stage2m	61
modifying >IN	46
modifying the contents of the input buffer or a string literal	245
mods	59
modulus	58
most recent definition does not have a name (IMMEDIATE)	246
motivation for object-oriented programming ...	178
move	77
ms	235
MS , repeatability to be expected	249
Multiple exits from begin	88
multitasker	207
Must now be used inside C-LIBRARY, see C interface doc	216
mux	62

N

n	197
n , stack item type	55
naligned	76, 177
name	132
name dictionary	41
name field address	119
name lookup, case-sensitivity	241
name not defined by VALUE or (LOCAL) used by TO	252
name not defined by VALUE used by TO	246
name not found	244
name not found (' , POSTPONE , ['], [COMPILE])	246
name token	118
name, maximum length	242
name>compile	119
name>interpret	119
name>link	119, 230
name>string	119
names for defined words	102
native@	161
needs	139
negate	57
negative increment for counted loops	87
Neon model	196
nested colon definitions	102
new	191, 193
new[]	191
newline	80
newline character on input	242
newtask	207
newtask4	207
next-arg	163
next-case	92
nextname	102

NEXT	92
NEXT , direct threaded	269
NEXT , indirect threaded	269
NFA	119
nip	68
non-graphic characters and EMIT	241
non-relocatable image files	263
noname	101
noname-from	112
noop	118
notation of glossary entries	54
notfound	130
nothrow	95
ns	235
nt	199
nt (name token)	118
nt input format	52
nt token input format	52
NT Forth performance	275
ntime	235
number conversion	128
number conversion - traps for the unwary	128
number of bits in one address unit	242
number representation and arithmetic	242
numeric comparison words	64
numeric output - formatted	148
numeric output - simple/free-format	148
numeric output, FP	151
nw	198

O

o>	196
object	178, 188, 193
object allocation options	181
object class	181
object creation	181
object interfaces	184
object models, comparison	196
object-map discussion	185
object-oriented programming	179, 189
object-oriented programming motivation	178
object-oriented programming style	181
object-oriented terminology	178
objects	179
objects, basic usage	180
objects.fs	179, 189
objects.fs Glossary	186
objects.fs implementation	185
objects.fs properties	179
of	92
off	57
on	56
once	203
Only	134
oof	189
oof.fs	179, 189
oof.fs base class	191

oof.fs properties.....	189
oof.fs usage.....	190
oof.fs , differences to other models.....	197
open-blocks	146
open-dir	142
open-file	140
open-lib	215
open-path-file	143
open-pipe	159
operating system - passing commands.....	235
operator's terminal facilities available.....	247
options on the command line.....	3
or	62
order	134
orig , control-flow stack item.....	90
os-class	137
OS command line arguments.....	163
other system documentation, block words.....	248
other system documentation, core words.....	247
out	153
outer interpreter.....	40, 42, 125
outfile-execute	141
outfile-id	142
output in pipes.....	9
Output Redirection.....	141
output to terminal.....	154
over	68
overcommit memory for dictionary and stacks...	4
overflow of the pictured numeric output string.....	245
overrides	188
overrides usage.....	180

P

pad	77
PAD size.....	243
PAD use by nonstandard words.....	247
page	154
parameter stack.....	68
parameters are not of the same type (DO , ?DO , WITHIN).....	246
parent class.....	179
parent class binding.....	181
parse	132
parse area.....	125
parse-name	132
parse-word	132
parsed string overflow.....	245
parsed string, maximum size.....	242
parsing words.....	46, 126
pass	207
patching threaded code.....	272
path for included.....	143
path+	144
path=	144
pause	208
pedigree of Gforth.....	283

perform	118
performance of some Forth interpreters.....	274
persistent form of dictionary.....	262
PFE performance.....	275
pi	67
pick	68
pictured numeric output.....	148
pictured numeric output buffer, size.....	243
pictured numeric output string, overflow.....	245
pipes, creating your own.....	159
pipes, Gforth as part of.....	8
postpone	122, 191
postpone tutorial.....	35
postpone ,.....	120
POSTPONE applied to [IF]	253
POSTPONE or [COMPILE] applied to T0	246
Pountain's object-oriented model.....	196
pow2?	63
precision	151
precompiled Forth code.....	262
Preface.....	1
prefix '.....	117
previous	134
previous , search order empty.....	254
primitive source format.....	272
primitive-centric threaded code.....	270
primitives, assembly code listing.....	274
primitives, automatic generation.....	272
primitives, implementation.....	272
primitives, keeping the TOS in a register.....	273
prims2x.fs	272
print	189
printdebugdata	203
private discussion.....	183
procedures, tutorial.....	14
program data space available.....	247
programming style, arbitrary control structures.....	93
programming style, locals.....	168
programming style, object-oriented.....	181
programming tools.....	197
programming-tools words, ambiguous conditions.....	253
programming-tools words, implementation-defined options.....	253
programming-tools words, system documentation.....	253
prompt	243
pronunciation of words.....	54
protected	189
protected discussion.....	183
pthread	207
pthread_cond_broadcast	210
pthread_cond_signal	210
pthread_cond_timedwait	210
pthread_cond_wait	210
ptr	191, 192
public	189

Q

query.....	127
quit.....	236
quotations.....	102

R

r, stack item type.....	55
r/o.....	140
r/w.....	140
r>.....	69
r@.....	69
ranges for integer types.....	242
rdrop.....	69
read-csv.....	162
read-dir.....	142
read-file.....	140
read-line.....	140
read-only data space regions.....	243
reading from file positions not yet written.....	250
rec-body.....	131
rec-dtick.....	131
rec-float.....	130
rec-nt.....	130
rec-num.....	130
rec-string.....	130
rec-tick.....	131
rec-to.....	131
receiving object.....	179
reciprocal of integer.....	60
recognize.....	131
recongizers.....	130
records.....	173
records tutorial.....	35
recover (old Gforth versions).....	96
recurse.....	93
RECURSE appears after DOES>.....	245
recursion tutorial.....	23
recursive.....	93
recursive definitions.....	93
Redirection.....	141
refill.....	132
relocating loader.....	262
relocation at load-time.....	262
relocation at run-time.....	262
remainder.....	58
rename-file.....	140
repeatability to be expected from the execution of MS.....	249
REPEAT.....	91
replace-word.....	203
replaces.....	162
Replication.....	270
report the words used in your program.....	238
reposition-file.....	141
REPOSITION-FILE, outside the file's boundaries.....	250
represent.....	153

REPRESENT, results when <i>float</i> is out of range..	251
require.....	139
require, placement in files.....	259
required.....	139
reserving data space.....	70
resize.....	72
resize-file.....	141
restart.....	208
restore.....	97
restore-input.....	127
RESTORE-INPUT, Argument type mismatch.....	246
restrict.....	116
result out of range.....	245
Result out of range.....	58
Result out of range (on integer division).....	60
return stack.....	68
return stack and locals.....	69
return stack dump with <i>gforth-fast</i>	237
return stack manipulation words.....	69
return stack space available.....	247
return stack tutorial.....	24
return stack underflow.....	245
returning from a definition.....	93
rol.....	64
roll.....	68
Root.....	135
ror.....	64
rot.....	68
rounding of floating-point numbers.....	251
rp!.....	70
rp@.....	70
rp0.....	69
rshift.....	62
RSHIFT, large shift counts.....	246
run-time code generation, tutorial.....	37
running Gforth.....	3
running image files.....	265
Rydvqvist, Goran.....	259

S

s>d.....	58
s>f.....	65
s>number?.....	158
s>unnumber?.....	158
s\".....	79
S\".....	79
S\", number of string buffers.....	250
S\", size of string buffer.....	250
safe/string.....	81
save-buffer.....	147
save-buffers.....	147
save-cov.....	206
save-input.....	127
savesystem.....	263
savesystem during <i>gforthmi</i>	264
scan.....	80
scope.....	165

scope of locals	165	shift-args	163
scoping and classes	183	sign	149
scr	146	sign extension	73
seal	135	silent exiting from Gforth	9
search	80	simple defining words	98
search order stack	133	simple loops	85
search order, maximum depth	254	simple-fkey-string	157
search order, minimum	254	simple-see	199
search order, tutorial	38	simple-see-range	199
search path control, source files	143	single precision arithmetic words	57
search path for files	143	single-assignment style for locals	168
search-order words, ambiguous conditions	254	single-cell numbers, input format	51
search-order words,		single-key input	155
implementation-defined options	254	singlestep Debugger	205
search-order words, system documentation	254	size of buffer at WORD	243
search-wordlist	135	size of the dictionary and the stacks	3
see	199	size of the keyboard terminal buffer	243
see tutorial	15	size of the pictured numeric output buffer	243
see-code	199	size of the scratch area returned by PAD	243
see-code-range	200	<i>size</i> parameters for command-line options	3
SEE , source and format of output	253	skip	81
select	57	SLiteral	121
selection control structures	84	slurp-fid	141
selector	178, 189	slurp-file	141
selector implementation, class	185	sm/rem	59
selector invocation	179	source	127
selector invocation, restrictions	180, 190	source code for exception	199
selector usage	180	source code of a word	197
selectors and stack effects	181	source location of error or debugging	
selectors common to hardly-related classes	184	output in Emacs	259
self	191	source-id	127
semantics tutorial	30	SOURCE-ID , behaviour when BLK is non-zero	250
semantics, interpretation and compilation	115	sourcefilename	139
semaphore	208	sourcecodeline#	140
set-current	133	sp!	69
set-dir	142	sp@	69
set-does>	107	sp0	69
set-execute	231	space	153
set-forth-recognize	131	space delimiters	241
set-optimizer	110, 231	spaces	153
set-order	133	span	158
set-precision	152	speed, startup	9
set-recognizers	131	stability of Gforth	2
sf!	73	stack depth changes during interpretation	238
sf_ , stack item type	55	stack effect	54
sf@	73	Stack effect design, tutorial	17
sf@ or sf! used with an address that is not		stack effect of DOES> -parts	105
single-float aligned	251	stack effect of included files	139
sfa!ign	71	stack effects of selectors	181
sfa!igned	76	stack empty	245
sf!ield:	178	stack item types	55
sf!oat%	177	stack manipulation tutorial	13
sf!oat+	76	stack manipulation words	68
sf!oat/	76	stack manipulation words, floating-point stack	68
sf!oats	76	stack manipulation words, return stack	69
sh	235	stack manipulations words, data stack	68
Shared libraries in C interface	214	stack overflow	244
shell commands	235	stack pointer manipulation words	69

stack size default	265	swap	68
stack size, cache-friendly	265	symmetric division	58
stack space available	247	Synonym	114
stack tutorial	12	synonyms	114
stack underflow	245	syntax tutorial	11
stack-effect comments, tutorial	15	system	235
stacksize	207	system dictionary space required,	
stacksize4	207	in address units	247
staged/-divisor	62	system documentation	240
staged/-size	61	system documentation, block words	247
Standard conformance of Gforth	240	system documentation, core words	241
starting Gforth tutorial	11	system documentation, double words	248
startup sequence for image file	266	system documentation, exception words	248
Startup speed	9	system documentation, facility words	248
state - effect on the text interpreter	46	system documentation, file words	249
state-smart words (are a bad idea)	116	system documentation, floating-point words	250
STATE values	243	system documentation, locals words	252
static	192	system documentation,	
status-color	155	memory-allocation words	253
stderr	141	system documentation,	
stderr and pipes	9	programming-tools words	253
stdin	141	system documentation, search-order words	254
stdout	141	system prompt	243
stop	208		
stop-ns	208		
str<	80		
str=	80		
String input format	52		
string larger than pictured numeric output			
area (f. , fe. , fs.)	252		
string literals	79		
string longer than a counted string			
returned by WORD	246		
string words with \$	81		
string-prefix?	80		
string-suffix?	80		
strings - see character strings	78		
strings tutorial	26		
struct	177		
struct usage	174		
structs tutorial	35		
structure extension	175		
structure glossary	176		
structure implementation	176		
structure naming convention	175		
structure of Forth programs	48		
structure usage	174		
structures	173		
structures containing arrays	175		
structures containing structures	175		
Structures in Forth200x	177		
structures using address arithmetic	173		
sub-list?	170		
substitute	162		
success-color	155		
super	191		
superclass binding	181		
Superinstructions	270		
		T	
		table	134
		TAGS file	259
		target compiler	265, 277
		task	207
		terminal buffer, size	243
		terminal input buffer	125
		terminal output	154
		terminal size	154
		terminology for object-oriented	
		programming	178
		text interpreter	40, 42, 125
		text interpreter - effect of state	46
		text interpreter - input sources	126, 127
		THEN	90
		third	68
		this	189
		this and catch	185
		this implementation	185
		this usage	182
		ThisForth performance	275
		threaded code implementation	268
		threading words	233
		threading, direct or indirect?	270
		threading-method	233
		throw	94
		THROW -codes used in the system	248
		thru	147
		tib	127
		tick (')	117
		TILE performance	275
		time&date	235
		time-related words	235

TMP, TEMP - environment variable	8
to-this	189
TO	100
TO on non-VALUES	246
TO on non-VALUES and non-locals	252
tokens for words	117
TOS definition	42
TOS optimization for primitives	273
toupper	78
translate-nt	131
translate-num	131
translate:	131
trigonometric operations	66
true	56
truncation of floating-point numbers	251
try	96
tt	199
tuck	68
turnkey image files	267
Tutorial	11
type	154
types of locals	164
types of stack items	55
types tutorial	16
typewhite	154

U

u*/	60
u*/mod	60
u, stack item type	55
u.	148
u.r	148
u/	59
u/-stage1m	61
u/-stage2m	61
u/mod	59
u/mod-stage2m	62
u<	64
u<=	64
u>	64
u>=	64
U+D0	91
U-D0	91
ud, stack item type	55
ud.	148
ud.r	148
ud/mod	60
UDefer	208
um*	58
um/mod	59
umax	57
umin	57
umod	59
umod-stage2m	61
unaligned memory access	73
undefined word	244

undefined word, ', POSTPONE, ['], [COMPILE]	246
under+	57
unescape	162
unexpected end of the input buffer	245
unlock	208
unloop	92
unmapped block numbers	250
UNREACHABLE	166
UNTIL	90
UNTIL loop	86
unused	70
unwind-protect	96
update	147
UPDATE, no current block buffer	248
updated?	147
upper and lower case	56
use	146
User	99
user input device, method of selecting	242
user output device, method of selecting	242
user space	99
user variables	99
user'	208
user-defined defining words	102
Uses of a word	198
utime	235
UValue	208

V

v*	66
Value	100
value-flavoured locals	164
values	100
var	192, 193
Variable	99
variable-flavoured locals	164
variables	99
variadic C functions	212
versions, invoking other versions of Gforth	6
view	203
view (called locate in Gforth)	197
viewing the documentation of a word in Emacs	259
viewing the source of a word in Emacs	259
virtual function	178
virtual function table	185
virtual machine	268
virtual machine instructions, implementation ..	272
visibility of locals	165
vlist	135
Vocabularies, detailed explanation	135
Vocabulary	135
vocs	135
vocstack empty, previous	254
vocstack full, also	254

W

w!	73
w,	71
w, stack item type	55
w/o	140
w>s	74
w@	73
waligned	76
warning-color	155
WARNING"	97
warnings	98
wbe	74
where	198
where to go next	49
whereg	199
WHILE	91
WHILE loop	85
wid	133
wid, stack item type	55
Win32Forth performance	275
wior type description	55
wior values and meaning	250
with	192
within	64
wle	74
word	41, 132
word glossary entry format	54
word list for defining locals	169
word lists	133
word lists - example	137
word lists - why use them?	136
word name too long	244
WORD buffer size	243
WORD, string overflow	246
wordlist	134
wordlists tutorial	38
words	54, 135
words used in your program	238
words, forgetting	202
wordset	54
write-file	141
write-line	141
wrol	63
wror	63

WTF??	203
ww	198

X

x!	73
x,	71
x-size	160
x-width	160
x>s	74
x@	73
x\string-	160
xaligned	76
xbe	74
xc!+?	160
xc-size	159
xc-width	160
xc@+	160
xchar+	160
xchar-	160
xchar-encoding	160
xd!	74
xd,	71
xd>s	75
xd@	74
xdbe	74
xdle	74
xemit	154
xkey	160
xle	74
xor	62
xt	41, 117
xt input format	52
xt, stack item type	55
xt-new	189
xt-see	199
xt-see-code	200
xt-simple-see	199
XT tutorial	31

Z

zero-length string as a name	245
Zsoter's object-oriented model	196