

The automultiplechoice package*

Alexis Bienvenue
paamc@passoire.fr

July 6, 2026

Abstract

This package helps designing multiple choice exams ready for automated marking from papers scans.

Answers and questions are optionally shuffled, creating different sheets for every student.

1 Introduction

The package `automultiplechoice` helps formatting multiple choice questionnaires with automated marking from papers scans in mind:

- The package can produce different copies of the question sheet for each student, optionally shuffling answers and questions for each student.
- Markers can be printed on each sheet, so as to be able to analyse scans after examination. All the needed information about the position of the markers and the boxes to be checked by the students is given in an auxiliary file during $\text{\LaTeX}$ run.

See Auto Multiple Choice (AMC) software (<https://www.auto-multiple-choice.net/>) for an integration of this package, with user interface for automated marking.

2 Samples

We begin with several samples to see what can be done with the `automultiplechoice` package. All `automultiplechoice` commands and options will be detailed further.

For all these samples, two sets of questions are used: a group of geography questions, and a group of history questions. These are defined in a common $\text{\LaTeX}$ file named `questions.tex`:

```
\element{geography}{  
  \begin{question}{Ghana}  
    What is the capital of Ghana?  
    \begin{choiceshoriz}  
      \correctchoice{Accra}  
      \wrongchoice{Addis Abeba}  
      \wrongchoice{Ankara}  
      \wrongchoice{Apia}
```

*This document corresponds to version revision: `r:dcff9ca9` from AMC 1.7.0+git20260706163316

```

        \end{choiceshoriz}
    \end{question}
}

\element{geography}{
    \begin{question}{Thailand}
        What is the capital of Thailand?
        \begin{choiceshoriz}
            \correctchoice{Bangkok}
            \wrongchoice{Banjul}
            \wrongchoice{Beijing}
            \wrongchoice{Beirut}
            \wrongchoice{Berlin}
        \end{choiceshoriz}
    \end{question}
}

\element{geography}{
    \begin{question}{Egypt}
        What is the capital of Egypt?
        \begin{choices}
            \correctchoice{Cairo}
            \wrongchoice{Caracas}
            \wrongchoice{Cayenne}
            \wrongchoice{Chisinau}
            \wrongchoice{Conakry}
        \end{choices}
    \end{question}
}

\element{geography}{
    \begin{question}{Ireland}
        What is the capital of Ireland?
        \begin{multicols}{3}
            \begin{choices}
                \correctchoice{Dublin}
                \wrongchoice{Dili}
                \wrongchoice{Djibouti}
                \wrongchoice{Doha}
                \wrongchoice{Dakar}
                \wrongchoice{Dhaka}
            \end{choices}
        \end{multicols}
    \end{question}
}

\element{history}{
    \begin{questionmult}{1901}
        Which of the following events are taking place during the year

```

```

1901?
\begin{choices}
  \correctchoice{Funeral of Queen Victoria in London}
  \correctchoice{Official end of the Caste War of Yucat\'an}
  \wrongchoice{King George of Greece becomes absolute monarch of Crete}
  \wrongchoice{The first line of the Paris M\'etro is opened}
\end{choices}
\end{questionmult}
}

\element{history}{
  \begin{questionmult}{1850}
    Which of the following events are taking place during the year
    1850?
    \begin{choices}
      \correctchoice{American Express is founded by Henry Wells \& William Fargo}
      \wrongchoice{Napoleon Bonaparte crosses the Alps and invades Italy}
      \wrongchoice{Kwang-su becomes emperor of China}
      \wrongchoice{First horse-drawn omnibuses established in London}
    \end{choices}
  \end{questionmult}
}

\element{history}{
  \begin{questionmult}{1971}
    Which of the following events are taking place during the year
    1971?
    \begin{choices}
      \correctchoice{Apollo 14 lands on the Moon}
      \correctchoice{The Soviet Union launches Salyut 1}
      \correctchoice{Death of Louis Armstrong}
      \wrongchoice{The first commercial Concorde flight takes off}
    \end{choices}
  \end{questionmult}
}

```

We will ask automultiplechoice package to include two geography questions and two history questions at random for each student, shuffling questions and answers, with the following code:

```

\cleargroup{all}
\shufflegroup{geography}
\copygroup[2]{geography}{all}
\shufflegroup{history}
\copygroup[2]{history}{all}
\shufflegroup{all}
\insertgroup{all}

```

You can read these commands as “clear group **all**, shuffle questions inside group **geography** and copy the first two to group **all**, do the same for group **history**, shuffle the four questions copied into **all** and print them”.

2.1 Standard layout

A set of 30 students sheets can be produced from the following L^AT_EX source named `sample-amc.tex`:

```
\documentclass{article}
\usepackage{automultiplechoice}
\usepackage{multicol}
\begin{document}

\input{questions.tex}

\onecopy{30}{

\noindent{\bf AMC \hfill SAMPLE TEST}

\vspace{3ex}
```

For this test, package `{\sf automultiplechoice}` is used without any option. Page markers are printed in view of an automated marking from papers scans. DRAFT indications can be cancelled using `{\tt nowatermark}` option.

Commands from `{\sf automultiplechoice}` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

```
\vspace{3ex}

\cleargroup{all}

\shufflegroup{geography}
\copygroup[2]{geography}{all}
\shufflegroup{history}
\copygroup[2]{history}{all}
\shufflegroup{all}
\insertgroup{all}


}
\end{document}
```

producing a 30-pages document (every page has number 1), from which we show the first pages on page 7.

Note that “DRAFT” indications can be cancelled using option `nowatermark`, or using AMC software.

You can see on each page markers that can be used for automated completed answer sheets scans analysis:

- Four circles ● are printed in the corners, to be able to analyse any rotation or scaling of the scans.
- Binary boxes are printed in the header area, so as to be able to read student sheet number and page number. On page 2 for example, you can see that these binary boxes are coding 2/1/59:



+2/1/59+

Here, 2 is the student sheet number, 1 is the page number for this student, and 59 is a checking value that can be used for checking correct identification from a scan.

If you also use `calibration` option, `automultiplechoice` will produce a `.xy` file with informations about the exact position in the page of all the markers, and all the boxes. This option is automatically set by AMC software, which then use the information in the `.xy` file for automated marking.

2.2 Separate answer sheet

In some situations, you may need a separate answer sheet:

- this makes cheating even more difficult;
- this can reduce the number of pages to scan.

This is done using `separateanswersheet` option of `automultiplechoice` package. You also have to use commands `\AMCformBegin` to indicate the beginning of this separate answer sheet (usually after a `\clearpage` or `\AMCcleardoublepage` command), and `\AMCform` to insert the form to be completed by the students, as in the following example (`sample-separate.tex`):

```
\documentclass{article}
\usepackage[separateanswersheet]{automultiplechoice}
\usepackage{multicol}
\begin{document}
```

```
\input{questions.tex}
```

```
\onecopy{30}{
```

```
\noindent{\bf AMC \hfill SAMPLE TEST}
```

```
\vspace{3ex}
```

For this test, package `{\sf automultiplechoice}` is used with `{\tt separateanswersheet}` option, so that all answers are to be filled on a separate sheet by students. Page markers are printed in view of an automated marking from papers scans. DRAFT indications can be cancelled using `{\tt nowatermark}` option.

Commands from `{\sf automultiplechoice}` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

```
\vspace{3ex}
```

```
\cleargroup{all}
```

```

\shufflegroup{geography}
\copygroup[2]{geography}{all}
\shufflegroup{history}
\copygroup[2]{history}{all}
\shufflegroup{all}
\insertgroup{all}

```

```

\clearpage

```

```

\AMCformBegin

```

This is the answer sheet: all answers are to be ticked on this page to be taken into account.

```

\vspace{2ex}

```

```

\AMCform

```

```

}
\end{document}

```

First pages of the result are shown on page 8. There are now 2 pages per student: the first with questions, and the second for answers. Only the second will be completed by the students, and scanned for analysis.

2.3 Without markers

With the `nopage` option, package `automultiplechoice` does not include any page markers for scan processing. I'm afraid you can't use any automated marking software with this layout, but you can still use answer sheet and corrected answer sheet (option `indivanswers`, added here) for a manual marking...

The $\text{\LaTeX}$ source `sample-plain.tex` that only differs from `sample-amc.tex` by its options passed to `automultiplechoice`:

```

\usepackage[nopage,indivanswers]{automultiplechoice}

```

produces a 30-pages document, from which we show the first pages on page 9.

First pages from L^AT_EX source detailed in section 2.1 – see sample-amc.pdf

●  ● +1/1/60+

AMC SAMPLE TEST

For this test, package `automultiplechoice` is used without any option. Page markers are printed in view of an automated marking from papers scans. DRAFT indications can be cancelled using `\nocancelmark` option.

Commands from `automultiplechoice` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

Question 1 Which of the following events are taking place during the year 1971?

☐ The Soviet Union launches Salyut 1
☐ The first commercial Concorde flight takes off
☐ Death of Louis Armstrong
☐ Apollo 14 lands on the Moon

Question 2 What is the capital of Egypt?

☐ Cayenne
☐ Caracas
☐ Cuito
☐ Conakry
☐ Chisinau

Question 3 Which of the following events are taking place during the year 1850?

☐ Napoleon Bonaparte crosses the Alps and invades Italy
☐ First horse-drawn omnibuses established in London
☐ American Express is founded by Henry Wells & William Fargo
☐ Kwang-on becomes emperor of China

Question 4 What is the capital of Ghana?

☐ Accra ☐ Addis Ababa ☐ Ankara ☐ Apia

● For your examination, preferably print documents compiled from `automultiple-choice`. ●

●  ● +2/1/60+

AMC SAMPLE TEST

For this test, package `automultiplechoice` is used without any option. Page markers are printed in view of an automated marking from papers scans. DRAFT indications can be cancelled using `\nocancelmark` option.

Commands from `automultiplechoice` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

Question 1 Which of the following events are taking place during the year 1901?

☐ The first line of the Paris Métro is opened
☐ Official end of the Caste War of Yucatán
☐ King George of Greece becomes absolute monarch of Creta
☐ Funeral of Queen Victoria in London

Question 2 What is the capital of Ireland?

☐ Djibouti ☐ Dhaka ☐ Dhaka
☐ Dublin ☐ Dili ☐ Dakar

Question 3 What is the capital of Ghana?

☐ Apia ☐ Accra ☐ Addis Ababa ☐ Ankara

Question 4 Which of the following events are taking place during the year 1850?

☐ Napoleon Bonaparte crosses the Alps and invades Italy
☐ First horse-drawn omnibuses established in London
☐ American Express is founded by Henry Wells & William Fargo
☐ Kwang-on becomes emperor of China

● For your examination, preferably print documents compiled from `automultiple-choice`. ●

●  ● +3/1/52+

AMC SAMPLE TEST

For this test, package `automultiplechoice` is used without any option. Page markers are printed in view of an automated marking from papers scans. DRAFT indications can be cancelled using `\nocancelmark` option.

Commands from `automultiplechoice` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

Question 1 Which of the following events are taking place during the year 1971?

☐ The Soviet Union launches Salyut 1
☐ The first commercial Concorde flight takes off
☐ Apollo 14 lands on the Moon
☐ The Soviet Union launches Salyut 1
☐ Death of Louis Armstrong

Question 2 Which of the following events are taking place during the year 1850?

☐ First horse-drawn omnibuses established in London
☐ Kwang-on becomes emperor of China
☐ Napoleon Bonaparte crosses the Alps and invades Italy
☐ American Express is founded by Henry Wells & William Fargo

Question 3 What is the capital of Ireland?

☐ Dhaka ☐ Dhaka ☐ Dakar
☐ Dili ☐ Djibouti

Question 4 What is the capital of Thailand?

☐ Beijing ☐ Bangor ☐ Bangkok ☐ Beirut ☐ Berlin

● For your examination, preferably print documents compiled from `automultiple-choice`. ●

●  ● +4/1/52+

AMC SAMPLE TEST

For this test, package `automultiplechoice` is used without any option. Page markers are printed in view of an automated marking from papers scans. DRAFT indications can be cancelled using `\nocancelmark` option.

Commands from `automultiplechoice` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

Question 1 Which of the following events are taking place during the year 1971?

☐ The Soviet Union launches Salyut 1
☐ Apollo 14 lands on the Moon
☐ Death of Louis Armstrong
☐ The first commercial Concorde flight takes off

Question 2 What is the capital of Egypt?

☐ Caracas
☐ Cayenne
☐ Cuito
☐ Conakry
☐ Chisinau

Question 3 Which of the following events are taking place during the year 1850?

☐ American Express is founded by Henry Wells & William Fargo
☐ Napoleon Bonaparte crosses the Alps and invades Italy
☐ First horse-drawn omnibuses established in London
☐ Kwang-on becomes emperor of China

Question 4 What is the capital of Ireland?

☐ Djibouti ☐ Dhaka ☐ Dakar
☐ Dili ☐ Dhaka ☐ Dublin

● For your examination, preferably print documents compiled from `automultiple-choice`. ●

First pages from L^AT_EX source detailed in section 2.2 – see sample-separate.pdf

•  • +1/1/60+

AMC SAMPLE TEST

For this test, package `automultiplechoice` is used with `separateanswersheet` option, so that all answers are to be filled on a separate sheet by students. Page markers are printed in view of an automated marking from papers scans. DRAFT indications can be cancelled using `nowatermark` option.

Commands from `automultiplechoice` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

Question 1 • Which of the following events are taking place during the year 1971?

☐ A The Soviet Union launches Salyut 1
☐ B The first commercial Concorde flight takes off
☐ C Death of Louis Armstrong
☐ D Apollo 14 lands on the Moon

Question 2 • What is the capital of Egypt?

☐ A Cayenne
☐ B Caracas
☐ C Cairo
☐ D Cusack
☐ E Chisum

Question 3 • Which of the following events are taking place during the year 1850?

☐ A Napoleon Bonaparte crosses the Alps and invades Italy
☐ B First horse-drawn omnibuses established in London
☐ C American Express is founded by Henry Wells & William Fargo
☐ D Kwang-on becomes emperor of China

Question 4 • What is the capital of Ghana?

☐ A Accra ☐ B Addis Ababa ☐ C Ankara ☐ D Apia

• For your examination, preferably print documents compiled from `automultiple-choice`. •

•  • +1/2/60+

This is the answer sheet: all answers are to be ticked on this page to be taken into account.

Question 1: ☐ A ☐ B ☐ C ☐ D
Question 2: ☐ A ☐ B ☐ C ☐ D
Question 3: ☐ A ☐ B ☐ C ☐ D
Question 4: ☐ A ☐ B ☐ C ☐ D

• For your examination, preferably print documents compiled from `automultiple-choice`. •

•  • +2/1/52+

AMC SAMPLE TEST

For this test, package `automultiplechoice` is used with `separateanswersheet` option, so that all answers are to be filled on a separate sheet by students. Page markers are printed in view of an automated marking from papers scans. DRAFT indications can be cancelled using `nowatermark` option.

Commands from `automultiplechoice` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

Question 1 • Which of the following events are taking place during the year 1901?

☐ A The first line of the Paris Metro is opened
☐ B Official end of the Cato War of Yunan
☐ C King George of Greece becomes absolute monarch of Crete
☐ D Funeral of Queen Victoria in London

Question 2 • What is the capital of Ireland?

☐ A Djibouti ☐ B Dhaka ☐ C Doha
☐ D Dublin ☐ E Dili ☐ F Dakar

Question 3 • What is the capital of Ghana?

☐ A Apia ☐ B Accra ☐ C Addis Ababa ☐ D Ankara

Question 4 • Which of the following events are taking place during the year 1850?

☐ A Napoleon Bonaparte crosses the Alps and invades Italy
☐ B First horse-drawn omnibuses established in London
☐ C American Express is founded by Henry Wells & William Fargo
☐ D Kwang-on becomes emperor of China

• For your examination, preferably print documents compiled from `automultiple-choice`. •

•  • +2/2/52+

This is the answer sheet: all answers are to be ticked on this page to be taken into account.

Question 1: ☐ A ☐ B ☐ C ☐ D
Question 2: ☐ A ☐ B ☐ C ☐ D
Question 3: ☐ A ☐ B ☐ C ☐ D
Question 4: ☐ A ☐ B ☐ C ☐ D

• For your examination, preferably print documents compiled from `automultiple-choice`. •

First pages from L^AT_EX source detailed in section 2.3 – see sample-plain.pdf

AMC

SAMPLE TEST

For this test, package `automultiplechoice` is used with the following options:

- `nopage`, so that no page markers are printed: nothing is planned for future automated marking from papers scans.
- `indivanswers`, so that correct answers are indicated (this is the corrected answer sheet. Without this option, you get the question sheet).

Commands from `automultiplechoice` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

Question 1 Which of the following events are taking place during the year 1971?

☒ The Soviet Union launches Salyut 1
☐ The first commercial Concorde flight takes off
☐ Death of Louis Armstrong
☒ Apollo 14 lands on the Moon

Question 2 What is the capital of Egypt?

☐ Cayenne
☐ Caracas
☒ Cairo
☐ Cusquey
☐ Chisinau

Question 3 Which of the following events are taking place during the year 1850?

☐ Napoleon Bonaparte crosses the Alps and invades Italy
☐ First horse-drawn omnibuses established in London
☒ American Express is founded by Henry Wells & William Fargo
☐ Kwang-sun becomes emperor of China

Question 4 What is the capital of Ghana?

☒ Accra ☐ Addis Ababa ☐ Ankara ☐ Apia

1

AMC

SAMPLE TEST

For this test, package `automultiplechoice` is used with the following options:

- `nopage`, so that no page markers are printed: nothing is planned for future automated marking from papers scans.
- `indivanswers`, so that correct answers are indicated (this is the corrected answer sheet. Without this option, you get the question sheet).

Commands from `automultiplechoice` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

Question 1 Which of the following events are taking place during the year 1901?

☐ The first line of the Paris Metro is opened
☒ Official end of the Cretan War of Vassilata
☐ King George of Greece becomes absolute monarch of Crete
☒ Funeral of Queen Victoria in London

Question 2 What is the capital of Iceland?

☐ Djibouti ☐ Dhaka ☐ Doha
☒ Dili ☐ Dkar

Question 3 What is the capital of Ghana?

☐ Apia ☒ Accra ☐ Addis Ababa ☐ Ankara

Question 4 Which of the following events are taking place during the year 1850?

☐ Napoleon Bonaparte crosses the Alps and invades Italy
☐ First horse-drawn omnibuses established in London
☒ American Express is founded by Henry Wells & William Fargo
☐ Kwang-sun becomes emperor of China

1

AMC

SAMPLE TEST

For this test, package `automultiplechoice` is used with the following options:

- `nopage`, so that no page markers are printed: nothing is planned for future automated marking from papers scans.
- `indivanswers`, so that correct answers are indicated (this is the corrected answer sheet. Without this option, you get the question sheet).

Commands from `automultiplechoice` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

Question 1 Which of the following events are taking place during the year 1971?

☐ The first commercial Concorde flight takes off
☒ Apollo 14 lands on the Moon
☒ The Soviet Union launches Salyut 1
☒ Death of Louis Armstrong

Question 2 Which of the following events are taking place during the year 1850?

☐ First horse-drawn omnibuses established in London
☐ Kwang-sun becomes emperor of China
☐ Napoleon Bonaparte crosses the Alps and invades Italy
☒ American Express is founded by Henry Wells & William Fargo

Question 3 What is the capital of Iceland?

☐ Dhaka ☐ Doha ☐ Dkar
☐ Dili ☒ Dhabla ☐ Djibouti

Question 4 What is the capital of Thailand?

☐ Beijing ☐ Banjul ☒ Bangkok ☐ Beirut ☐ Berlin

1

AMC

SAMPLE TEST

For this test, package `automultiplechoice` is used with the following options:

- `nopage`, so that no page markers are printed: nothing is planned for future automated marking from papers scans.
- `indivanswers`, so that correct answers are indicated (this is the corrected answer sheet. Without this option, you get the question sheet).

Commands from `automultiplechoice` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

Question 1 Which of the following events are taking place during the year 1971?

☒ The Soviet Union launches Salyut 1
☒ Apollo 14 lands on the Moon
☒ Death of Louis Armstrong
☐ The first commercial Concorde flight takes off

Question 2 What is the capital of Egypt?

☐ Caracas
☐ Cayenne
☒ Cairo
☐ Cusquey
☐ Chisinau

Question 3 Which of the following events are taking place during the year 1850?

☒ American Express is founded by Henry Wells & William Fargo
☐ Napoleon Bonaparte crosses the Alps and invades Italy
☐ First horse-drawn omnibuses established in London
☐ Kwang-sun becomes emperor of China

Question 4 What is the capital of Iceland?

☐ Djibouti ☐ Dhaka ☐ Dkar
☐ Dili ☐ Doha ☒ Dhabla

1

3 Usage

3.1 Package options

The following options are available for package `automultiplechoice`:

`noshuffle` cancels answers shuffling for all questions.

`noshufflegroups` cancels groups shuffling.

`answers` produces a common corrected answers sheet.

`indivanswers` shows the boxes that corresponds to correct choices on the question sheet.

`box` includes every question in a $\text{\LaTeX}$ box, so that they can't be cutted on two different pages.

`asbox` does the same for questions in the separate answer sheet.

`separateanswersheet` asks for a separate answer sheet (see section 2.2 for an example). Commands `\AMCformBegin` and `\AMCform` must be used to describe the separate answer sheet (see section 3.6).

`digits` puts digits instead of letters in the boxes, when `separateanswersheet` (or `insidebox`) is used.

`outsidebox` prints boxes labels outside the boxes on the answersheet when `separateanswersheet` is set.

`init` initializes the random generator from time. *This option is only for testing: don't use it for a real exam!*

`completemulti` adds an answer "None of these answers are correct." at the end of each multiple question (question with no, one or several correct answers), so as to make the difference between "I don't know" and "I think none of the answers are correct".

`insidebox` puts a letter (or a digit if `digits` option is used) inside the boxes, even if `separateanswersheet` is not used. The `insidebox` option is implicitly called when using `separateanswersheet`: no need to call it then.

`calibration` asks for logging positions of boxes and markers in the `.xy` file. Without this option, a $\text{\LaTeX}$ run updates the document but not the `.xy` file.

`nowatermark` cancels the "DRAFT" indications above pages.

`catalog` is used for formatting a catalog of questions, not an exam. Then the question identifiers will be printed.

`keys` defines the way the question identifiers will be printed on the catalog file. With `keys=next` (the default), the question identifiers will be printed next to the questions numbers. With `keys=line`, the question identifiers will be printed on one line before the question text, so that the question will look close to the final result on the exam copies.

`francais` asks for french localisation.

`lang=XX` asks for localisation in XX language. At present, only CA (Catalan), DE (German), ES (Spanish), FR (French), IT (Italian), JA (Japanese), NO (Norwegian) and NL (Dutch) are available.

`plain` cancels `environ` and `etex` automatic loading. The default behaviour is to load `environ` and `etex` packages if available, as they improve `automultiplechoice`. This is not done when `plain` option is set.

`nopage` cancels markers print and page layout definition (see sample in section 2.3).

`automarks` , when used with `separateanswersheet`, cancels markers print on the subject page (they are only shown on the answer sheet pages).

`postcorrect` tells that correct answers won't be given in the LaTeX source. The teacher will fill one answer sheet for AMC to analyse the scan and set correct answers from it.

`fullgroups` cancels the use of the optional parameter of `\insertgroup` and `\copygroup`, so that each group is always fully inserted and fully copied.

`storebox` asks to use `\storebox` instead of `\savebox` to handle ovals (when using oval shape). The package `storebox` will be loaded.

`pdfform` use this option to produce PDF forms. The PDF sheet won't be printed, but filled by each student with a PDF reader. The completed PDF will then be sent to the teacher, and given to AMC for data capture.

See also section 3.8 for a french version of some of these options.

3.2 Questions and answers

We make a difference between two kind of multiple choice questions:

- **Simple questions:** there is one and only one correct choices among the proposed choices, *and this is announced to the student*. Thus, the student is asked to check one answer if he thinks this is the good one, and to check none if he has no idea.
- **Multiple questions:** there can be zero, one or several correct choices among the proposed choices. This is also announced to the student (using the `\multiSymbole` sign, with default ♣), so that the student is asked to check all the boxes corresponding to correct choices, and to let unchecked all boxes corresponding to wrong choices.

`question (env.)` Simple questions are enclosed in a `{question}{<id>}` environment, and multiple questions `questionmult (env.)` are enclosed in a `{questionmult}{<id>}` environment. These environments contain the question text, and the proposed choices inside a `choices`-like environment (see next). The `<id>` argument is a question identifier. Each question must have a unique identifier, different from the other questions identifiers.

Questions environments

Question 1 What is the elevation of Mount Everest?

- ☐ 8,253 m
☐ 8,810 m
☐ 8,848 m

Question 2 ♣ Which contries are in the Americas?

- ☐ Cambodia
☐ Guatemala
☐ Canada
☐ Switzerland

```
\begin{question}{everest}
  What is the elevation of
  Mount Everest?
  \begin{choices}
    \correctchoice{8,848\,m}
    \wrongchoice{8,253\,m}
    \wrongchoice{8,810\,m}
  \end{choices}
\end{question}

\begin{questionmult}{americas}
  Which contries are in the Americas?
  \begin{choices}
    \correctchoice{Guatemala}
    \correctchoice{Canada}
    \wrongchoice{Switzerland}
    \wrongchoice{Cambodia}
  \end{choices}
\end{questionmult}
```

`\AMCcompleteMulti` For multiple questions, it is sometimes useful to make the difference between a student who thinks that none of he choices are correct, and a student who did not answer the question. `\AMCnoCompleteMulti` The use of package option `completemulti` can be used in this case: it adds a choice to all multiple questions. Commands `\AMCcompleteMulti` and `\AMCnoCompleteMulti` can also be used to change this behaviour for a single question.

Additional answer “none” for a single question

Question 3 ♣ Which contries are in the Americas?

- ☐ Guatemala
☐ Cambodia
☐ Canada
☐ Switzerland
☐ *None of these answers are correct.*

```
\begin{questionmult}{americas}
  \AMCcompleteMulti
  Which contries are in the Americas?
  \begin{choices}
    \correctchoice{Guatemala}
    \correctchoice{Canada}
    \wrongchoice{Switzerland}
    \wrongchoice{Cambodia}
  \end{choices}
\end{questionmult}
```

`choices (env.)`
`choiceshoriz (env.)`
`choicescustom (env.)`

Depending on the formatting style for answers, one can choose one of the following ones:

- Environment `choices` is usually chosen for long answers:

The choices environment

Question 4 ♣ What are the possible uses of latex?

- ☐ Latex is used as a fuel for some space launch vehicles.
- ☐ Latex from the chicle and jelutong trees is used in chewing gum.
- ☐ Natural rubber is the most important product obtained from latex.

```
\begin{questionmult}{latex}
What are the possible uses of latex?
\begin{choices}
\correctchoice{Natural rubber is
the most important product
obtained from latex.}
\correctchoice{Latex from the chicle
and jelutong trees is used in
chewing gum.}
\wrongchoice{Latex is used as a fuel
for some space launch vehicles.}
\end{choices}
\end{questionmult}
```

- environment `choiceshoriz` is chosen for short answers:

The choiceshoriz environment

Question 5 How many legs for an insect?

- ☐ 2 ☐ 6 ☐ 8

```
\begin{question}{insect}
How many legs for an insect?
\begin{choiceshoriz}
\correctchoice{6}
\wrongchoice{2}
\wrongchoice{8}
\end{choiceshoriz}
\end{question}
```

- environment `choicescustom` is provided to customize answers formatting. See 3.9.3 for details.

`\correctchoice` As you have seen in these examples, the `choices`-like environments contain `\correctchoice{<text>}` and `\wrongchoice` and `\wrongchoice{<text>}` commands, with the text of the proposed choice as argument.

3.3 Scoring

`\scoring` Scoring strategies can be given in the L^AT_EX source. They don't have any impact on the question sheet: they are only transmitted to the analysis software through the `.amc` file. See AMC `\scoringDefaultM` documentation to write proper commands for your needs. `\scoring{<score>}` can be used inside a `\scoringDefaultS` `question` or `questionmult` environment to describe the scoring strategy for the question, or after a `\correctchoice` or `\wrongchoice` command to describe score associated to a particular choice. `\scoringDefaultM{<score>}` and `\scoringDefaultS{<score>}` define default scoring strategies for multiple and simple questions. `\QuestionIndicative` tags a question that is not taken into account to compute the mark – for example, it can be used for a question about the way students have enjoyed the course.

3.4 Groups of questions

Several commands are available that allows shuffling questions for each question sheet. They handle groups of questions. These groups will usually contain questions, but can be made of any L^AT_EX content.

\element The command `\element{⟨groupname⟩}{⟨content⟩}` adds element with content `⟨content⟩` to the group named `⟨groupname⟩`. The command `\shufflegroup{⟨groupname⟩}` shuffles elements of group named `⟨groupname⟩`. The command `\insertgroup[⟨n⟩]{⟨groupname⟩}` inserts elements of group `⟨groupname⟩` one after one. If optional parameter `⟨n⟩` is given, only the first `⟨n⟩` elements of the group are inserted in the document. If not, or if `⟨n⟩` is negative, all the elements are inserted. The command `\insertgroupfrom[⟨n⟩]{⟨groupname⟩}{⟨i⟩}` does the same, starting from element at index `⟨i⟩` (the first element has index 0).

As an example without questions in groups elements, let us create a small group named **serie**, containing five elements, and play with it:

Managing groups	
Numbers: one two three four five. Three numbers from the second (index=1) one: two three four. Two of them after shuffling: two four.	<pre> \element{serie}{ one} \element{serie}{ two} \element{serie}{ three} \element{serie}{ four} \element{serie}{ five} Numbers:\insertgroup{serie}. Three numbers from the second (index=1) one:\insertgroupfrom[3]{serie}{1}. \shufflegroup{serie} Two of them after shuffling:\insertgroup[2]{serie}. </pre>

\cleargroup The command `\cleargroup{⟨groupname⟩}` clears all the elements of group `⟨groupname⟩`, making an empty group. The command `\copygroup[⟨n⟩]{⟨from⟩}{⟨to⟩}` copies the elements of group `⟨from⟩` to group `⟨to⟩` – if optional parameter `⟨n⟩` is given, only the `⟨n⟩` first elements are copied. If not, or if `⟨n⟩` is negative, all the elements are copied. The command `\copygroupfrom[⟨n⟩]{⟨from⟩}{⟨to⟩}{⟨i⟩}` does the same, starting from element at index `⟨i⟩` (the first element has index 0).

As an example again without questions:

Three digits from 2 to 4 and two letters: A 2 3 F 4.

Three digits and two letters: 2 8 4 E D.

Three digits and two letters: 4 E 2 5 A.

```

\element{digits}{ 1}\element{digits}{ 2}\element{digits}{ 3}
\element{digits}{ 4}\element{digits}{ 5}\element{digits}{ 6}
\element{digits}{ 7}\element{digits}{ 8}\element{digits}{ 9}
\element{letters}{ A}\element{letters}{ B}\element{letters}{ C}
\element{letters}{ D}\element{letters}{ E}\element{letters}{ F}

\shufflegroup{letters}
\cleargroup{mixed}
\copygroupfrom[3]{digits}{mixed}{1}\copygroup[2]{letters}{mixed}
\shufflegroup{mixed}
Three digits from 2 to 4 and two letters:\insertgroup{mixed}.

\shufflegroup{digits}\shufflegroup{letters}
\cleargroup{mixed}
\copygroup[3]{digits}{mixed}\copygroup[2]{letters}{mixed}
\shufflegroup{mixed}
Three digits and two letters:\insertgroup{mixed}.

\shufflegroup{digits}\shufflegroup{letters}
\cleargroup{mixed}
\copygroup[3]{digits}{mixed}\copygroup[2]{letters}{mixed}
\shufflegroup{mixed}
Three digits and two letters:\insertgroup{mixed}.

```

You can find an example involving questions in [section 2](#).

3.5 Students identification

`\namefield` There are two ways to associate students to their sheets.

- Always add to one page of each copy some place for the student to write down his name. If you want AMC software to be able to cut the scan around this area to present it to you and ask you to read the written name (this is called manual association), you must use the `\namefield{<descr>}` command. The `<descr>` argument contains the $\text{\LaTeX}$ code used to format the name field on the page. For example:

Name and surname:

.....

```

\namefield{\fbox{
  \begin{minipage}{15em}
    Name and surname:\vspace*{3ex}\par
    \noindent\dotfill\vspace{2mm}
  \end{minipage}
}}
```

You can see that the `\namefield` command has no effect on the produced document. In fact, its only purpose is to log in the `.xy` file information about the position of the name field on the page, to be used by the software analysing the scans.

- For automated student identification, if for example students have a 6-digits student number, you can ask them to code it somewhere on the question sheet. This can be done using the `\AMCcodeGridInt[⟨opts⟩]{⟨key⟩}{⟨ndigits⟩}` command, where `⟨key⟩` is the key identifier, that can be used to retrieve coded student numbers from the scans, and `⟨ndigits⟩` is the number of digits for numbers to be coded.

Student ID											
☐ 0	☐ 0	☐ 0	☐ 0	☐ 0	☐ 0	<code>\AMCcodeGridInt{student}{6}</code>					
☐ 1	☐ 1	☐ 1	☐ 1	☐ 1	☐ 1						
☐ 2	☐ 2	☐ 2	☐ 2	☐ 2	☐ 2						
☐ 3	☐ 3	☐ 3	☐ 3	☐ 3	☐ 3						
☐ 4	☐ 4	☐ 4	☐ 4	☐ 4	☐ 4						
☐ 5	☐ 5	☐ 5	☐ 5	☐ 5	☐ 5						
☐ 6	☐ 6	☐ 6	☐ 6	☐ 6	☐ 6						
☐ 7	☐ 7	☐ 7	☐ 7	☐ 7	☐ 7						
☐ 8	☐ 8	☐ 8	☐ 8	☐ 8	☐ 8						
☐ 9	☐ 9	☐ 9	☐ 9	☐ 9	☐ 9						

For smaller number of digits, the “horizontal” form can be preferred:

Student ID, horizontal form											
☐ 0	☐ 1	☐ 2	☐ 3	☐ 4	☐ 5	☐ 6	☐ 7	☐ 8	☐ 9		
☐ 0	☐ 1	☐ 2	☐ 3	☐ 4	☐ 5	☐ 6	☐ 7	☐ 8	☐ 9		
☐ 0	☐ 1	☐ 2	☐ 3	☐ 4	☐ 5	☐ 6	☐ 7	☐ 8	☐ 9		

`\AMCcodeGridInt[h]{student}{3}`

3.6 Separate answer sheet

`\AMCformBegin` To produce separate answer sheets as seen in section 2.2,

`\AMCform`

`\AMCcleardoublepage`

1. use the `separateanswersheet` package option.
2. use the `\AMCformBegin` command at the beginning of the answer sheet description. This command usually follows a command to get a new page. This command can be the classical `\clearpage` for single-sided question sheets, or the `\AMCcleardoublepage` command, that

go to the next odd numbered page, so that the answer sheet is on a separate sheet even when printing in duplex mode.

3. use the `\AMCform` command to insert all boxes for all questions.

See section 2.2 for an example.

3.7 Random computation questions

One can use the $\text{\LaTeX}$ package `fp` to make random computation questions, as can be seen in the following example (don't forget to load package `fp`):

Random computation questions

Question 6 How much are 2 plus 8?

☐ 9 ☒ 10 ☐ 16 ☐ -6

```

\begin{question}{\simplesum}
  \FPeval\VQa{trunc(1+random*8,0)}
  \FPeval\VQb{trunc(4+random*5,0)}
  \FPeval\VQsum{clip(VQa+VQb)}
  \FPeval\VQnoA{clip(VQa+VQb-1)}
  \FPeval\VQnoB{clip(VQa*VQb)}
  \FPeval\VQnoC{clip(VQa-VQb)}
  How much are \VQa{} plus \VQb{}?
  \begin{choiceshoriz}
    \correctchoice{\VQsum}
    \wrongchoice{\VQnoA}
    \wrongchoice{\VQnoB}
    \wrongchoice{\VQnoC}
  \end{choiceshoriz}
\end{question}

```

In this example, `\VQa` and `\VQb` are used to store two random integers (the first between 1 and 8, and the second between 4 and 8). Then `\VQsum` stores the sum of these two integers, and `\VQnoA`, `\VQnoB` and `\VQnoC` are other values that will be used as distractors in the multiple choice question.

\AMCIntervals In some cases, command `\AMCIntervals{\langle x \rangle}{\langle x0 \rangle}{\langle x1 \rangle}{\langle \delta \rangle}` from `automultiplechoice` can be useful. It adds a sequence of choices made of intervals $[x_i, x_i + \delta[$ of length $\langle \delta \rangle$ covering the interval $[\langle x0 \rangle, \langle x1 \rangle[$, using `\correctchoice` when $\langle x \rangle$ lies in the interval, and `\wrongchoice` otherwise.

Pick the right interval

Question 7 Let X and Y be two independent random variables, following exponential laws with respective parameters 5 and 8. In which interval lies the probability $P[X < Y]$?

- | | | | | |
|-------------------------------------|--|-------------------------------------|-------------------------------------|-------------------------------------|
| ☐ [0, 0.1[| ☐ [0.2, 0.3[| ☐ [0.4, 0.5[| ☐ [0.6, 0.7[| ☐ [0.8, 0.9[|
| ☐ [0.1, 0.2[| ☒ [0.3, 0.4[| ☐ [0.5, 0.6[| ☐ [0.7, 0.8[| ☐ [0.9, 1[|

```
\begin{question}{inf-expo-indep}
  \FPeval\VQa{trunc(2 + random * 4,0)}
  \FPeval\VQb{trunc(6 + random * 5,0)}
  \FPeval\VQr{VQa/(VQa+VQb)}
  Let  $X$  and  $Y$  be two independent random variables, following
  exponential laws with respective parameters  $\VQa$  and  $\VQb$ .
  In which interval lies the probability  $\text{P}[X < Y]$ ?
  \begin{multicols}{5}
    \begin{choices}[o]
      \AMCIntervals{\VQr}{0}{1}{0.1}
    \end{choices}
  \end{multicols}
\end{question}
```

One can also use the `\AMCnumericChoices` command to ask the student to enter a numerical value as his answer, as in the following example:

Numeric choices

Question 8

Compute $\sqrt{11}$ and round it with two digits after period.

	☐ 0	☐ 1	☐ 2	☒ 3	☐ 4	☐ 5	☐ 6	☐ 7	☐ 8	☐ 9
	.									
☒ +	☐ 0	☐ 1	☐ 2	☒ 3	☐ 4	☐ 5	☐ 6	☐ 7	☐ 8	☐ 9
☐ -	☐ 0	☐ 1	☒ 2	☐ 3	☐ 4	☐ 5	☐ 6	☐ 7	☐ 8	☐ 9

```
\begin{questionmultx}{sqrt}
  \FPeval\VQa{trunc(5+random*15,0)}
  \FPeval\VQs{VQa^0.5}

  Compute  $\sqrt{\VQa}$  and round it with two digits after period.

  \AMCnumericChoices{\VQs}{digits=3,decimals=2,sign=true,
    borderwidth=0pt,backgroundcol=lightgray,approx=5}
\end{questionmultx}
```

Note the use of `questionmultx` environment: we need this question to be *multiple* as several boxes has to be ticked, but we can't say that *several answers are correct*, so we don't show the ♣.

Available options that can be used in the second argument of the `\AMCnumericChoices` command are the following ($\langle bool \rangle$ can be `true` or `false`, and $\langle color \rangle$ must be a color known by the `xcolor` package):

`digits= $\langle num \rangle$` gives the number of digits to request (defaults to 3).

`decimals= $\langle num \rangle$` gives the number of digits after period to request (defaults to 0). Note that when `decimals` is positive, the LaTeX package `fp` must be loaded.

`base= $\langle num \rangle$` gives the base for digits and decimals (defaults to 10).

`significant= $\langle bool \rangle$` if `true`, the numbers to code are the first *significant* digits from the first argument of `\AMCnumericChoices`. For example, the right answer to `\AMCnumericChoices{56945.23}{digits=2,significant=true}` is 57.

`exponent= $\langle num \rangle$` gives the number of digits for the exponent, when requesting to enter the result in scientific notation.

`nozero= $\langle bool \rangle$` if `true`, the choice 0 is removed for all digits. May be useful when `\AMCnumericChoices` is used to get a small (< 10) positive value.

`sign= $\langle bool \rangle$` requests (or not) a signed value (default to `true`).

`exposign= $\langle bool \rangle$` requests (or not) a signed value of the exponent (default to `true`).

`strict= $\langle bool \rangle$` if `true`, a box has to be ticked for every digit and for the sign. If `false`, if some digits has no ticked box, they will be set to zero. Defaults to `false`.

`vertical= $\langle bool \rangle$` if `true`, each digit is represented on one raw. If `false` (default), each digit is represented on one line.

`expovetical= $\langle bool \rangle$` if `true`, the mantissa is above the exponent. If `false` (default), the mantissa is beside the exponent.

`reverse= $\langle bool \rangle$` if `true`, place higher values of the digits on the top in vertical mode (defaults to `true`).

`vhead= $\langle bool \rangle$` if `true`, in vertical mode, a header is placed over all digits rows, made using the command `\AMCncontextVHead` that is originally defined as `\def\AMCncontextVHead#1{\emph{b#1}}`. This default value is useful to number the binary digits. Default value is `false`.

`Tvhead= $\langle text \rangle$` A coma separated list as `{H,T,0,t,h,th}` for header in `vhead` vertical mode. Needs `vhead` to be set (defaults to the empty list `{}`).

`vheadunitindex= $\langle num \rangle$` The index of the Ones place in the `Tvhead` list, counting from the right. If zero, changed to `decimals + 1` (defaults to zero). For example, if `Tvhead={H,T,0,t,h,th}`, should be set as `vheadunitindex=4` (at least if `decimals` is not set to 3).

`hspace= $\langle space \rangle$` sets the horizontal space between boxes (defaults to `.5em`).

`vspace= $\langle space \rangle$` sets the vertical space between boxes (defaults to `1ex`).

`borderwidth= $\langle space \rangle$` sets the width of the frame around all the boxes (defaults to `1mm`).

`bordercol=<color>` sets the color of the frame (defaults to `lightgray`).

`backgroundcol=<color>` sets the background color (defaults to `white`).

`Tsign=<text>` sets the text to print at the top of the boxes to set the sign (Can also be redefined by `\def\AMCtextSign{<text>}`, and defaults to be empty).

`Tpoint=<text>` sets the text for the period. Can also be redefined by `\def\AMCdecimalPoint{<text>}`, and defaults to `\raisebox{1ex}{\bf .}`.

`Texponent=<text>` sets the text before the exponent. Can also be redefined by `\def\AMCexponent{<text>}`, and defaults to `\times 10^{\textasciicircum}`.

`scoring=<bool>` if `true`, a scoring strategy is given to AMC for this question. Defaults to `true`.

`scoreexact=<num>` gives the score for an exact answer (defaults to 2).

`exact=<num>` sets the maximal distance to the correct integer value (value without the decimal point) for an answer to be said *exact* and be rewarded to `scoreexact` points (defaults to 0).

`scoreapprox=<num>` gives the score for an approximative answer (defaults to 1).

`approx=<num>` sets the maximal distance to the correct integer value (value without the decimal point) for an answer to be said *approximative* and be rewarded to `scoreapprox` points (defaults to 0).

`scorewrong=<num>` gives the score for a wrong answer (defaults to 0).

`ignoreblank` can be used (only with number base 10) to ignore digits for which no box has been ticked. This way, ticking 5 for the first digit, no box for the second and 3 for the third digit will code the number 53, while this would have coded 503 without the `ignoreblank` option (because the default value for the second digit is 0).

`keepas=<name>` keeps the value entered by the student in variable `{<name>}`, for future use with `alsocorrect` in another question.

`alsocorrect=<expression>` gives another acceptable answer, that can be based on the values entered by the student in the previous questions.

The text added at the end of the questions using `\AMCnumericChoices` when not in the separate answer sheet (and when a separate answer sheet is requested by the `separateanswersheet` package option) can also be set redefining the `\AMCtextGoto` command, as:

```
\def\AMCtextGoto{\par{\bf\emph{Please code the answer on  
the separate answer sheet.}}}
```

3.8 French command names

For backward compatibility, some of `automultiplechoice` commands, environments and package option have their French counterpart. You can always use either the English command or the French equivalent. See table 1 for details.

type	English	French
command	<code>\namefield</code>	<code>\champnom</code>
environment	<code>choices</code>	<code>reponses</code>
environment	<code>choiceshoriz</code>	<code>reponseshoriz</code>
environment	<code>choicescustom</code>	<code>reponsesperso</code>
command	<code>\correctchoice</code>	<code>\bonne</code>
command	<code>\wrongchoice</code>	<code>\mauvaise</code>
command	<code>\lastchoices</code>	<code>\alafin</code>
command	<code>\AMCIntervals</code>	<code>\choixIntervalles</code>
command	<code>\scoring</code>	<code>\bareme</code>
command	<code>\scoringDefaultM</code>	<code>\baremeDefaultM</code>
command	<code>\scoringDefaultS</code>	<code>\baremeDefaultS</code>
command	<code>\onecopy</code>	<code>\exemplaire</code>
environment	<code>examcopy</code>	<code>copieexamen</code>
command	<code>\shufflegroup</code>	<code>\melangegroupe</code>
command	<code>\insertgroup</code>	<code>\restituegroupe</code>
command	<code>\AMCform</code>	<code>\formulaire</code>
command	<code>\AMCformBegin</code>	<code>\AMCdebutFormulaire</code>
option	<code>noshuffle</code>	<code>ordre</code>
option	<code>answers</code>	<code>correc</code>
option	<code>indivanswers</code>	<code>correcindiv</code>
option	<code>box</code>	<code>bloc</code>
option	<code>separateanswersheet</code>	<code>ensemble</code>
option	<code>digits</code>	<code>chiffres</code>

Table 1: French equivalent commands

3.9 Customisation

3.9.1 Boxes

`\AMCboxStyle` The command `\AMCboxStyle{<style>}` can be used to specify the shape, color and dimensions of the boxes to be ticked. The argument `<style>` is a coma-separated list of `<key>=<value>` pairs, with the following possible `<key>`s:

shape for the shape to be used: either **square** or **oval**. Note that if **oval** is used, the $\text{\LaTeX}$ package **tikz** must be loaded.

width for the width of the boxes.

height for the height of the boxes.

size for the size of the boxes (sets **width** and **height**).

down for the length the boxes are to be moved down.

rule for the rule width.

outsidesep for the distance between the box and the letter when printed outside the box.

color for the color (only the box that are to be filled by the students and will be used for data capture). Use something that will be understood by the **xcolor** package.

Default values are

```
\AMCboxStyle{shape=square,size=2.5ex,down=.4ex,
rule=.5pt,outsidesep=.1em,color=black}
```

Setting the box color allows to print the boxes with some color that won't disturb too much the data capture (for example red, but some light grey can also be considered).

Boxes styling	
Question 9 $2 + 2 =$ Ⓐ 1 Ⓑ 4 Ⓒ 10	<pre>\AMCboxStyle{shape=oval,color=red} \begin{question}{sum}\$2+2={}\$ \begin{choiceshoriz}[o] \wrongchoice{1}\correctchoice{4} \wrongchoice{10} \end{choiceshoriz} \end{question}</pre>

3.9.2 Codes

One may adapt the codes rendering from `\AMCcodeGrid` to one's needs modifying the following lengths:

- `\AMCcodeHspace` is the amount of horizontal space between two columns of digits,
- `\AMCcodeVspace` is the amount of vertical space between two rows of digits,

Default values are `\AMCcodeHspace=.5em` `\AMCcodeVspace=.5em`

3.9.3 Answers

Environment `choicescustom` will make use of the three commands `\AMCbeginAnswer` (before the first answer), `\AMCendAnswer` (after the last answer) and `\AMCanswer{<box>}{<text>}` (for each answer) to format the answers. Redefining them properly, some different answers formatting can be achieved. However, this does not seem to work with non-trivial settings...

The <code>choicescustom</code> environment	
Question 10 $2+2=$ $\left(\begin{array}{ccc} \square & 4 & \square & 3 & \square & 2 \end{array} \right)$	<pre>\begin{question}{add} \def\AMCbeginAnswer{\$\Big(\$} \def\AMCendAnswer{\$\Big)\$} \def\AMCanswer#1#2{#1 #2\hfill} 2+2= \begin{choicescustom} \correctchoice{4} \wrongchoice{2} \wrongchoice{3} \end{choicescustom} \end{question}</pre>

4 Implementation

This package uses the following other packages:

```

1 \RequirePackage{xcolor} % \fcolorbox to fill (or not) a box
2 \RequirePackage{fancyhdr} % \pagestyle{empty}
3 \@ifl@t@r\fmtversion{2020/10/01}
4 {}
5 {\RequirePackage{atbegshi}} % \AtBeginShipout
6 \RequirePackage{xkeyval} % \setkeys
7 \RequirePackage{rotating} % \rotatebox
8 \RequirePackage{fancybox} % \boxput
9 \RequirePackage{expl3}
10 \RequirePackage{csvsimple}
11 \RequirePackage{environ}
12 % \end{macrocode}
13 %
14 % First, we read the options that can be given by AMC through the
15 % |jobname-config.tex| file:
16 % \begin{macrocode}
17 \InputIfFileExists{\jobname-config.tex}%
18 {\message{Loading configuration file...^^J}}{}

```

`\AMC@amclog` Informations about questions and choices will be logged to a file with extension `amc`, to be parsed later. Macro `\AMCmessage` writes to this file.

```

19 \newwrite\AMC@logfile
20 \immediate\openout\AMC@logfile=\jobname.amc
21 \def\AMC@amclog#1{\immediate\write\AMC@logfile{#1}}
22 \def\AMCmessage#1{\AMC@amclog{\string\message{#1}}}

```

`\AMC@LR` Colours management can be faulty in right-to-left mode: in these situations, we will make use of `\LR` from package `bidi` to get back to left-to-right mode. `\AMC@LR` is `\LR` if `bidi` is loaded.

```

23 \AtBeginDocument{\@ifpackageloaded{bidi}{%
24 \PackageInfo{automultiplechoice}{Package bidi loaded: using LR for boxes.}%
25 \let\AMC@LR=\LR}%
26 {\let\AMC@LR=\relax}}%

```

4.1 Variables

Counters and boolean variables defined here are internal and should not be modified by the user.

The package defines the following counters:

`\AMCload@counter` number of choices already loaded for current question.

`\AMCid@quest` current question ID number (see section 4.7).

`\AMCid@etud` current student sheet number.

`\AMCid@etudstart` starting student sheet number of the current `onecopy` bloc.

`\AMCid@check` current page checking number.

`\AMCid@etudfin` last student sheet number for the exam.

`\AMCnum@copies` number of exam sheets to produce.

It also defines the following switches:

`\ifAMC@ordre` if choices are never to be shuffled.

`\ifAMC@shuffleG` if groups shuffling is allowed.

`\ifAMC@fullGroups` if groups are always fully inserted by `\insertgroup` and fully copied by `\copygroup`, irrespective to the optional parameter.

`\ifAMC@correthead` if some correction header is to be printed at the beginning.

`\ifAMC@affichekeys` if questions keys are to be printed.

`\ifAMC@keyslines` if questions keys should be printed on a single line before the question text.

`\ifAMC@correc` if correct choices are to be checked on the produced document.

`\ifAMC@qbloc` if questions are to be included in $\text{\LaTeX}$ boxes (so that they can't be splitted on two different pages).

`\ifAMC@asqbloc` if questions are to be included in $\text{\LaTeX}$ boxes in the answer sheet (so that they can't be splitted on two different pages).

`\ifAMC@rbloc` if answers are to be included in $\text{\LaTeX}$ boxes (so that they can't be splitted on two different columns for example).

`\ifAMC@textPos` if questions and answers positions are to be logged.

`\ifAMC@extractOnly` if the PDF is only built to extract questions and answers images.

`\ifAMCcomplete@multi` if a choice "None of these answers are correct." is to be added to every multiple question.

`\ifAMCquestionNumber` if AMC should step up the question number for each new question.

`\ifAMC@calibration` if this $\text{\LaTeX}$ run is used to get page layouts.

`\ifAMC@plain` if `automultiplechoice` won't try to load useful packages (`etex`, `environ`) that extend `automultiplechoice` capabilities.

`\ifAMCune@bonne` if there is at least one correct answer for the current question.

`\ifAMCtype@multi` if the current question is a multiple question.

`\ifAMC@watermark` if the document is a draft, not to be used for exam.

`\ifAMC@ensemble` if answers are to be given on a separate answers sheet.

`\ifAMC@inside@box` if a letter or digit is to be printed inside all boxes.

`\ifAMC@inside@digit` if digits are to be written inside boxes instead of letters (when using a separate answer sheet for example).

`\ifAMC@outside@box` if labels for boxes are to be printed outside the box on the answer sheet.

`\ifAMCformulaire@dedans` is true for questions inside separate answer sheet.

`\ifAMC@zoneformulaire` is true for codes (made by `\AMCcodeGrid`) inside separate answer sheet.

`\ifAMC@pagelayout` is true if the AMC page layout, with signs for scan analysis, is to be used.

`\ifAMC@postcorrect` corresponds to the use of the `postcorrect` package option.

`\ifAMC@automarks` corresponds to the use of the `automarks` package option.

`\ifAMC@invisible` is true if the DVI/PDF output is not important (used for example for scoring strategy extraction).

`\ifAMC@pdfform` is true if the output is a PDF form. This PDF will not be printed but will be filled by the students with a PDF reader and sent back to the teacher.

```
27 \newcount\AMCload@counter
28 \newcount\AMCid@quest\AMCid@quest=-1
29 \newcount\AMCid@check
30 \newcount\AMCid@etud\AMCid@etud=0
31 \newcount\AMCid@etudstart\AMCid@etudstart=0
32 \newcount\AMCid@etudfin
33 \newcount\AMCnum@copies

34 \newif\ifAMC@ordre\AMC@ordrefalse
35 \newif\ifAMC@shuffleG\AMC@shuffleGtrue
36 \newif\ifAMC@fullGroups\AMC@fullGroupsfalse
37 \newif\ifAMC@correthead\AMC@corretheadfalse
38 \newif\ifAMC@affichekeys\AMC@affichekeysfalse
39 \newif\ifAMC@keyline\AMC@keylinefalse
40 \newif\ifAMC@correc\AMC@correcfalse
41 \newif\ifAMC@textPos\AMC@textPosfalse
42 \newif\ifAMC@extractOnly\AMC@extractOnlyfalse
43 \newif\ifAMC@qbloc\AMC@qblocfalse
44 \newif\ifAMC@asqbloc\AMC@asqblocfalse
45 \newif\ifAMC@rbloc\AMC@rblocfalse
46 \newif\ifAMC@complete@multi\AMC@complete@multifalse
47 \newif\ifAMC@questionNumber\AMC@questionNumbertrue
48 \newif\ifAMC@calibration\AMC@calibrationfalse
49 \newif\ifAMC@catalog\AMC@catalogfalse
50 \newif\ifAMC@plain\AMC@plainfalse
51 \newif\ifAMC@bonne
52 \newif\ifAMC@type@multi
53 \newif\ifAMC@watermark\AMC@watermarktrue
54 \newif\ifAMC@inside@box\AMC@inside@boxfalse
55 \newif\ifAMC@outside@box\AMC@outside@boxfalse
56 \newif\ifAMC@ensemble\AMC@ensemblefalse
57 \newif\ifAMC@inside@digit\AMC@inside@digitfalse
58 \newif\ifAMC@formulaire@dedans\AMC@formulaire@dedansfalse
59 \newif\ifAMC@zoneformulaire
60 \newif\ifAMC@pagelayout\AMC@pagelayouttrue
61 \newif\ifAMC@postcorrect\AMC@postcorrectfalse
62 \newif\ifAMC@automarks\AMC@automarksfalse
63 \newif\ifAMC@invisible\AMC@invisiblefalse
64 \newif\ifAMC@pdfform\AMC@pdfformfalse
65 \let\AMCcompleteMulti=\AMC@complete@multitrue
66 \let\AMCnoCompleteMulti=\AMC@complete@multifalse
```

`\AMCid@name` The package also defines command `\AMCid@name` to be the current question identifier key.
67 `\def\AMCid@name{}`

4.2 Dimensions

`\AMCformVSpace` The following dimensions can be modified by the user to adjust questions formatting:
`\AMCformHSpace` `\AMCformVSpace` is the amount of vertical space between two questions in a separate answer
`\AMCinterIrep` sheet.
`\AMCinterBrep` `\AMCformHSpace` is the amount of horizontal space between two answers boxes in a separate
answer sheet.
`\AMCinterIrep` is the amount of vertical space to be added between two answers.
`\AMCinterBrep` is the amount of vertical space between two boxed answers (see `\AMCBoxedAnswers`
and `\ifAMC@rbloc`).
`\AMCinterIquest` is the amount of vertical space left after a question, in standard mode (with-
out package option `box`).
`\AMCinterBquest` is the amount of vertical space left after a question, in 'boxed' mode (with
package option `box`).
`\AMCpostNquest` is the amount of vertical space left after a numeric question.
`\AMCpostOquest` is the amount of vertical space left after an open question.
68 `\newdimen\AMCformVSpace\AMCformVSpace=1.2ex`
69 `\newdimen\AMCformHSpace\AMCformHSpace=.3em`
70 `\newdimen\AMCinterIrep\AMCinterIrep=\z@`
71 `\newdimen\AMCinterBrep\AMCinterBrep=.5ex`
72 `\newdimen\AMCinterIquest\AMCinterIquest=\z@`
73 `\newdimen\AMCinterBquest\AMCinterBquest=3ex`
74 `\newdimen\AMCpostNquest\AMCpostNquest=1.5ex`
75 `\newdimen\AMCpostOquest\AMCpostOquest=7mm`

4.3 Human readable sheet ID position

`\AMCidsPosition` The position of the human readable sheet ID, near the corresponding binary boxes, is set with the
`\AMCidsPosition` command, in the form `\AMCidsPosition{pos=<position>,width=<width>,height=<height>}`,
where *<position>* is one of `side` (default), `top` and `none`, *<width>* is the width of the box enclosing
the ID (default value is 4cm), and *<height>* is the height of the box enclosing the ID (default value
is 3ex).

```

76 \newif\ifAMCids@top
77 \newif\ifAMCids@side
78 \newdimen\AMCids@width
79 \newdimen\AMCids@height
80 \define@choicekey*{AMCids}{pos}{\AMCidsVar\AMCidsVarN}{none,top,side}{%
81   \ifcase\AMCidsVarN\relax
82     \AMCids@topfalse\AMCids@sidefalse
83   \or
84     \AMCids@toptrue\AMCids@sidefalse
85   \or

```

```

86 \AMCids@topfalse\AMCids@sidetrue
87 \fi
88 }
89 \define@key{AMCids}{width}{\AMCids@width=#1}
90 \define@key{AMCids}{height}{\AMCids@height=#1}
91 \def\AMCidsPosition#1{\setkeys{AMCids}{#1}}
92 \AMCidsPosition{pos=side,width=4cm,height=3ex}

```

4.4 Localisation

In this section, some localised strings or commands are defined, for English, French and Spanish languages.

\AMCtext To modify these texts, you can use command **\AMCtext**. For example, **\AMCtext{draft}{*<text>*}** sets the text to be printed behind each page of a draft exam.

```

93 \def\AMCtext#1#2{\expandafter\def\csname AMC@loc@#1\endcsname{#2}}
94 \def\AMClocalized#1{\csname AMC@loc@#1\endcsname}

```

4.4.1 English

Text indicating draft exams:

```

95 \def\AMC@loc@draft{DRAFT}

```

Message at page bottom when compiled out of AMC gui:

```

96 \def\AMC@loc@message{For your examination, preferably print
97 documents compiled from auto-multiple-choice.}

```

Announcing a question in a separate sheet (parameter #1 is the question number):

```

98 \def\AMC@loc@qf#1{\textbf{Question #1:}}

```

Announcing a question (parameter #1 is the question number and parameter #2 can be the multiple question symbol, or be empty):

```

99 \def\AMC@loc@q#1#2{\textbf{Question #1} #2}

```

Headers for corrected version and catalog:

```

100 \def\AMC@loc@corrected{Corrected}
101 \def\AMC@loc@catalog{Catalog}

```

Localization text for Explanation

```

102 \def\AMC@loc@explain{\textit{\textbf{Explanation: }}}

```

Last choice added at the end for multiple questions when option **completemulti** is used:

```

103 \def\AMC@loc@none{None of these answers are correct.}

```

Word for 'question', singular and plural forms:

```

104 \def\AMC@loc@question{question}
105 \def\AMC@loc@questions{questions}

```

Default text to write in the students' name box:

```

106 \def\AMC@loc@namesurname{Name and surname:}

```

4.4.2 Catalan

Catalan localisation is called with option `lang=CA`.

```
107 \def\AMC@loc@CA{
108   \def\AMC@loc@draft{PROJECTE}
109   \def\AMC@loc@message{Pel vostre examen, imprimiu preferiblement
110     els documents compilats amb l'ajuda de auto-multiple-choice.}
111   \def\AMC@loc@qf##1{\textbf{Pregunta ##1 :}}
112   \def\AMC@loc@q##1##2{\textbf{Pregunta ##1} ##2}
113   \def\AMC@loc@corrected{Correcci\'}o}
114   \def\AMC@loc@catalog{Cat\'aleg}
115   \def\AMC@loc@explain{\textit{\textbf{Explicaci\'}o : }}}
116   \def\AMC@loc@none{Cap de les respostes \'es correcta.}
117   \def\AMC@loc@question{pregunta}
118   \def\AMC@loc@questions{preguntes}
119   \def\AMC@loc@namesurname{Nom i cognoms:}
120 }
```

4.4.3 Dutch

Dutch localisation is called with option `lang=NL`.

```
121 \def\AMC@loc@NL{
122   \def\AMC@loc@draft{Ontwerp}
123   \def\AMC@loc@message{Gebruik bij uw proefwerk bij voorkeur die
124     documenten welke door auto-multiple-choice zijn aangemaakt.}
125   \def\AMC@loc@qf##1{\textbf{Vraag ##1 :}}
126   \def\AMC@loc@q##1##2{\textbf{Vraag ##1} ##2}
127   \def\AMC@loc@corrected{Correctie}
128   \def\AMC@loc@catalog{Catalogus}
129   \def\AMC@loc@none{Geen van de antwoorden is juist.}
130   \def\AMC@loc@question{vraag}
131   \def\AMC@loc@questions{vragen}
132   \def\AMC@loc@namesurname{Achternaam en voornaam:}
133 }
```

4.4.4 French

French localisation is called with option `francais`, or `lang=FR`.

```
134 \def\AMC@loc@FR{
135   \def\AMC@loc@draft{PROJET}
136   \def\AMC@loc@message{Pour votre examen, imprimez de pr\'ef\'erence
137     les documents compil\'es \'a l'aide de auto-multiple-choice.}
138   \def\AMC@loc@qf##1{\textbf{Question ##1 :}}
139   \def\AMC@loc@q##1##2{\textbf{Question ##1} ##2}
140   \def\AMC@loc@corrected{Correction}
141   \def\AMC@loc@catalog{Catalogue}
142   \def\AMC@loc@explain{\textit{\textbf{Explication : }}}
143   \def\AMC@loc@none{Aucune de ces r\'eponses n'est correcte.}
144   \def\AMC@loc@question{question}
145   \def\AMC@loc@questions{questions}
146   \def\AMC@loc@namesurname{Nom et pr\'enom :}
147 }
```

4.4.5 German

German localisation is called with option `lang=DE`.

```
148 \def\AMC@loc@DE{
149   \def\AMC@loc@draft{ENTWURF}
150   \def\AMC@loc@message{Benutzen Sie f\"ur Ihre Pr\"ufung bevorzugt Dokumente die mit
151     auto-multiple-choice erstellt wurden.}
152   \def\AMC@loc@qf##1{\textbf{Frage ##1 :}}
153   \def\AMC@loc@q##1##2{\textbf{Frage ##1} ##2}
154   \def\AMC@loc@corrected{Korrektur}
155   \def\AMC@loc@catalog{Katalog}
156   \def\AMC@loc@explain{\textit{\textbf{Erkl\"arung : }}}
157   \def\AMC@loc@none{Keine dieser Antworten ist korrekt.}
158   \def\AMC@loc@question{Frage}
159   \def\AMC@loc@questions{Fragen}
160   \def\AMC@loc@namesurname{Vor- und Nachname:}
161 }
```

4.4.6 Italian

Italian localisation is called with option `lang=IT`.

```
162 \def\AMC@loc@IT{
163   \def\AMC@loc@draft{BOZZA}
164   \def\AMC@loc@message{Per l'esame, \e preferibile stampare i documenti
165     a partire da auto-multiple-choice.}
166   \def\AMC@loc@qf##1{\textbf{Domanda ##1:}}
167   \def\AMC@loc@q##1##2{\textbf{Domanda ##1} ##2}
168   \def\AMC@loc@corrected{Correzione}
169   \def\AMC@loc@catalog{Catalogo}
170   \def\AMC@loc@none{Nessuna risposta \e giusta.}
171   \def\AMC@loc@question{domanda}
172   \def\AMC@loc@questions{domande}
173   \def\AMC@loc@namesurname{Nome e cognome:}
174 }
```

4.4.7 Norwegian

Norwegian localisation is called with option `lang=NO`.

```
175 \def\AMC@loc@NO{
176   \def\AMC@loc@draft{UTKAST}
177   \def\AMC@loc@message{Det anbefales {\aa} skrive ut dokumentet
178     for gjennomgang \direkte fra auto-multiple-choice.}
179   \def\AMC@loc@qf##1{\textbf{Oppgave ##1 :}}
180   \def\AMC@loc@q##1##2{\textbf{Oppgave ##1} ##2}
181   \def\AMC@loc@corrected{Rettet}
182   \def\AMC@loc@catalog{Katalog}
183   \def\AMC@loc@none{Ingen svar er riktige.}
184   \def\AMC@loc@question{oppgave}
185   \def\AMC@loc@questions{oppgave}
186   \def\AMC@loc@namesurname{Etternavn og fornavn:}
187 }
```

4.4.8 Portuguese

Portuguese localisation is called with option `lang=PT`.

```
188 \def\AMC@loc@PT{
189   \def\AMC@loc@draft{RASCUNHO}
190   \def\AMC@loc@message{Para o seu exame, use preferencialmente documentos compilados do auto-multiple-choice}
191   \def\AMC@loc@qf##1{\textbf{Quest\~ao ##1:}}
192   \def\AMC@loc@q##1##2{\textbf{Quest\~ao ##1} ##2}
193   \def\AMC@loc@corrected{Corrigido}
194   \def\AMC@loc@catalog{Cat\'alogo}
195   \def\AMC@loc@explain{\textit{\textbf{Justifique: }}}
196   \def\AMC@loc@none{Nenhuma das respostas apresentadas est\'a correta.}
197   \def\AMC@loc@question{Quest\~ao}
198   \def\AMC@loc@questions{Quest\~oes}
199   \def\AMC@loc@namesurname{Nome e apelido:}
200 }
```

4.4.9 Spanish

Spanish localisation is called with option `lang=ES`.

```
201 \def\AMC@loc@ES{
202   \def\AMC@loc@draft{BORRADOR}
203   \def\AMC@loc@message{Para revisi\'on, preferentemente imprimir documentos compilados
204     desde auto-multiple-choice.}
205   \def\AMC@loc@qf##1{\textbf{Pregunta ##1 :}}
206   \def\AMC@loc@q##1##2{\textbf{Pregunta ##1} ##2}
207   \def\AMC@loc@corrected{Correcci\'on}
208   \def\AMC@loc@catalog{Cat\'alogo}
209   \def\AMC@loc@none{Ninguna de estas preguntas son correctas.}
210   \def\AMC@loc@question{pregunta}
211   \def\AMC@loc@questions{preguntas}
212   \def\AMC@loc@namesurname{Nombre y apellidos:}
213 }
```

4.4.10 Japanese

Japanese localisation is called with option `lang=JA`. It includes UTF8 encoded Japanese characters which are shown as $\diamond$ here (look at the `.sty` file to see them).

```
214 \def\AMC@loc@JA{
215   \def\AMC@loc@draft{\diamond\diamond\diamond\diamond}
216   \def\AMC@loc@message{\diamond\diamond\diamond\diamondauto-multiple-choice\diamond\diamond\diamond\diamond\diamond\diamond\diamond\diamond\diamond\diamond}
217   \def\AMC@loc@qf##1{\textbf{\diamond##1:}}
218   \def\AMC@loc@q##1##2{\textbf{\diamond##1} ##2}
219   \def\AMC@loc@corrected{\diamond\diamond\diamond\diamond}
220   \def\AMC@loc@catalog{\diamond\diamond\diamond\diamond}
221   \def\AMC@loc@explain{\textit{\textbf{\diamond: }}}
222   \def\AMC@loc@none{\diamond\diamond\diamond\diamond}
223   \def\AMC@loc@question{\diamond}
224   \def\AMC@loc@questions{\diamond}
225 }
```

4.4.11 Other languages

Other languages can be integrated to automultiplechoice package upon request to the author.

4.5 Interaction with other packages

4.5.1 cleveref

For references to questions:

```
226 \AtBeginDocument{\@ifpackageloaded{cleveref}{%
227   \message{AMC/cleveref integration loaded^^J}%
228   \crefalias{AMCquestionaff}{question}%
229   \crefname{question}{\AMC@loc@question}{\AMC@loc@questions}%
230 }{}}%
```

`\AMCrefs` In some cases, some questions can be used or not depending on the student copy. The macro `\AMCrefs{<macroname>}{<questions IDs list>}` selects the used questions before passing the list to the command specified as the first argument (for example `cref`, `cpageref` or other variants).

```
231 \ExplSyntaxOn
232
233 \seq_new:N \amc_refs_a_seq
234 \seq_new:N \amc_refs_b_seq
235
236 \cs_new:Npn \amc_refs_filter:n #1 {
237   \seq_set_from_clist:Nn \amc_refs_a_seq { #1 }
238   \seq_set_map:NNn \amc_refs_b_seq \amc_refs_a_seq { \AMCstudentlabel { ##1 } }
239   \seq_set_filter:NNn \amc_refs_a_seq \amc_refs_b_seq {
240     \cs_if_exist_p:c { r@##1 }
241   }
242   \seq_if_empty:NTF \amc_refs_a_seq { \seq_put_right:Nn \amc_refs_a_seq { NONE } } { }
243 }
244
245 \cs_new_eq:NN \AMCfilterRefs \amc_refs_filter:n
246
247 \cs_new:Npn \amc_func_refs:Nn #1 #2 {
248   \amc_refs_filter:n { #2 }
249   \exp_args:Nx #1 { \seq_use:Nn \amc_refs_a_seq { , } }
250 }
251
252 \cs_generate_variant:Nn \amc_func_refs:Nn { cn }
253
254 \cs_new_eq:NN \AMCrefs \amc_func_refs:cn
255
256 \ExplSyntaxOff
```

4.6 Random

4.6.1 Random pseudo-generator

The package uses the pseudo-random bit generator from *TuGBoat* 1994, vol 15:1:

```
257 \ifx\AMC@SR\undefined\newcount\AMC@SR\fi
258 \providecommand\AMC@SRconst{2097152}
259 \providecommand\AMC@SRset[i]{\global\AMC@SR#1 \ignorespaces}
260 \providecommand\AMC@SRadvance{%
```

```

261 \begingroup%
262 \ifnum\AMC@SR<\AMC@SRconst\relax\AMC@SR@count\z@\else\AMC@SR@count\@ne\fi%
263 \ifodd\AMC@SR\advance\AMC@SR@count\@ne\fi%
264 \global\divide\AMC@SR\tw%
265 \ifodd\AMC@SR@count\global\advance\AMC@SR\AMC@SRconst\relax\fi%
266 \endgroup}
267 \providecommand\AMC@SRbit{\AMC@SRadvance\ifodd\AMC@SR1\else0\fi}
268 \providecommand\AMC@SRtest[2]{\AMC@SRadvance%
269 \ifodd\AMC@SR#2\else#1\fi\ignorespaces}
270 \providecommand\AMC@SRvalue{\number\AMC@SR}

```

`\AMCrandomseed` The seed of this generator is set to 1515, but another value can be given using the command `\AMCrandomseed{<seed>}`.

```

271 \AMC@SRset{1515}
272 \def\AMCrandomseed#1{\AMC@SRset{#1}}

```

4.6.2 Uniform random deviates

`\AMC@SRnextByte` This generator is used to build first a 20-bit uniform integer generator (macro `\AMC@SRnextByte`).
`\AMC@SRmax` Then, using modulo, a (nearly) uniform generator on $\{0, \dots, n - 1\}$ is built: command `\AMC@SRmax{n}` puts in `\AMC@SR@count` the random deviate.

```

273 \newcount\AMC@SR@count
274 \def\AMC@SR@time{\AMC@SRset{\time}}
275 \newcount\AMC@SRnum
276 \def\AMC@SRnextByte{\AMC@SRnum=\z@%
277 \AMC@SR@count=20%
278 \loop\multiply\AMC@SRnum\tw%
279 \AMC@SRtest{\advance\AMC@SRnum\@ne}{}%
280 \ifnum\AMC@SR@count>\@ne\advance\AMC@SR@count\m@ne\repeat%
281 }
282 \newcommand\AMC@SRmax[1]{\AMC@SRnextByte%
283 \AMC@SR@count=\AMC@SRnum%
284 \divide\AMC@SR@count by #1\relax%
285 \multiply\AMC@SR@count by #1\relax%
286 \advance\AMC@SRnum by -\AMC@SR@count%
287 }

```

4.6.3 Tokens shuffling

`\AMCsw@p` The package defines the macro `\AMCsw@p` to swap the values of two token registers given as
`\AMC@shuffletoks` parameters.

After defining n token registers `\foo@i`, `\foo@ii`, `\foo@iii`, `\foo@iv` and so on, you can shuffle them using `\AMC@shuffletoks[<a>]{<n>}{<foo>}`. With optional argument $\langle a \rangle$, registers are shuffled from number $\langle a \rangle$ to $\langle n \rangle$ (default value for $\langle a \rangle$ is 1).

```

288 \newcount\AMC@sti
289 \newcount\AMC@stil
290 \newtoks\AMCsw@p@
291 \newcommand\AMCsw@p[2]{%
292 \global\AMCsw@p@=#1%
293 \global#1=#2%
294 \global#2=\AMCsw@p@}
295 \newcommand{\AMC@shuffletoks}[3][\@ne]{%

```

```

296 \AMC@sti=#2\relax%
297 \AMC@stil=#2\relax%
298 \advance\AMC@stil\@ne%
299 \advance\AMC@stil -#1\relax%
300 \@whilenum\AMC@sti>#1\do{%
301   \AMC@SRmax{\AMC@stil}\advance\AMC@SRnum #1\relax%
302   \AMCsw@p{\csname #3\romannumeral\AMC@SRnum\endcsname}%
303     {\csname #3\romannumeral\AMC@sti\endcsname}%
304   \advance\AMC@sti\m@ne\relax%
305   \advance\AMC@stil\m@ne\relax%
306 }}

```

4.7 Keys numbering

`\AMC@unnumero` This package allocates a unique integer ID to each question key from the questionnaire.
`\AMC@affecte` The counter `\AMC@numerotation` keeps track of the number of keys which already had an ID. Command `\AMC@definitnumero{n}{key}` allocates ID *n* to the key *key*. Command `\AMC@prepare{key}` looks if an ID had already been associated to *key*, and, if not, makes a new ID allocation for *key*. Command `\AMC@unnumero{key}` returns the ID associated with *key* (creating one if necessary). Command `\AMC@affecte{key}{\cnt}` give to counter `\cnt` the value of the ID associated to *key* (creating one if necessary).

```

307 \newcount\AMC@numerotation\AMC@numerotation=\z@%
308 \def\AMC@definitnumero#1#2{\AMCmessage{NUM=#1=#2}}%
309 \expandafter\global\expandafter\def\csname AMC@numtab@#2\endcsname{#1}}
310 \def\AMC@prepare#1{\expandafter\ifx\csname AMC@numtab@#1\endcsname\relax%
311   \global\advance\AMC@numerotation\@ne%
312   \expandafter\AMC@definitnumero\expandafter{\the\AMC@numerotation}{#1}\fi}
313 \def\AMC@unnumero#1{\AMC@prepare{#1}\csname AMC@numtab@#1\endcsname}
314 \def\AMC@affecte#1#2{\AMC@prepare{#1}\global#2=\csname AMC@numtab@#1\endcsname}

```

4.8 Boxes

4.8.1 Character logging

`\AMC@logchar` The command `\AMC@logchar{<char>}{<key>}` logs the character written in the box referenced as *<key>* in the .amc file. This is used in catalog mode, to get understandable references to answers from the statistics tables of the ODS export.

```

315 \def\AMC@logchar#1#2{%
316   \protected@write\AMC@logfile{}{%
317     \string\answer%
318     {\the\AMCid@etud/\thepage:#2}%
319     {#1}}%
320 }

```

4.8.2 Position logging

`\AMC@tracebox` Command `\AMC@tracebox{<trace>}{<key>}{<content>}` makes a L^AT_EX box around *<content>*,
`\AMC@pagepos` and, if *<trace>* is not empty, logs to the .xy file informations to be able to compute exact location of this box on the page, attached to the box identification *<key>*.

Command `\AMC@pagepos` logs page and page size informations at the beginning of each page.

```

321 \def\AMC@shapename{\ifAMC@invisible none\else\AMC@shapename\fi}

```

```

322 \def\AMC@tracepos#1#2{%
323   \ifAMC@calibration\ifx\@empty#1\@empty\else%
324   \pdfsavepos\protected@write\AMC@XYFILE{}\{%
325     \string\tracepos%
326     {\the\AMCid@etud/\thepage:#2}%
327     {\noexpand\number\pdflastxpos sp}%
328     {\noexpand\number\pdflastypos sp}%
329     {\AMC@shapename}}%
330   \fi\fi}
331 \def\AMC@traceposx#1#2{%
332   \ifAMC@calibration\ifx\@empty#1\@empty\else%
333   \pdfsavepos\protected@write\AMC@XYFILE{}\{%
334     \string\tracepos%
335     {\the\AMCid@etud/\thepage:#2}%
336     {\noexpand\number\pdflastxpos sp}%
337     {0sp}%
338     {\AMC@shapename}}%
339   \fi\fi}
340 \def\AMC@traceposy#1#2{%
341   \ifAMC@calibration\ifx\@empty#1\@empty\else%
342   \pdfsavepos\protected@write\AMC@XYFILE{}\{%
343     \string\tracepos%
344     {\the\AMCid@etud/\thepage:#2}%
345     {0sp}%
346     {\noexpand\number\pdflastypos sp}%
347     {\AMC@shapename}}%
348   \fi\fi}
349 \newcommand\AMC@tracebox[3]{%
350   \vbox{\AMC@traceposy{#1}{#2}%
351     \hbox{\AMC@traceposx{#1}{#2}#3\AMC@traceposx{#1}{#2}}%
352     \AMC@traceposy{#1}{#2}}
353 \def\AMC@pagepos{%
354   \ifAMC@calibration\protected@write\AMC@XYFILE{}\{%
355     \string\page%
356     {\the\AMCid@etud/\thepage/\the\AMCid@check}%
357     {\the\paperwidth}{\the\paperheight}%
358     {\the\pdfpagewidth}{\the\pdfpageheight}}\fi}

```

\AMCdontScan The commands \AMCdontScan, \AMCdontAnnotate and \AMCReTick write into the xy file instructions related to the current question.

```

\AMCReTick 359 \newcommand{\AMCdontScan}{\ifAMC@calibration\immediate\write\AMC@XYFILE{\string\dontscan{\the\AMCid@etud
360 \newcommand{\AMCdontAnnotate}{\ifAMC@calibration\immediate\write\AMC@XYFILE{\string\dontannotate{\the\AM
361 \newcommand{\AMCReTick}{\ifAMC@calibration\immediate\write\AMC@XYFILE{\string\retick{\the\AMCid@etud,\th
362 %

```

\AMC@tracechar The macro \AMC@tracechar{<char>}{<unused>}{<trace>}{<key>} is used to log (for further processing with AMC), into to .xy file, the character used to identify the box.

```

363 \newcommand\AMC@tracechar[4]{%
364   \ifAMC@calibration\ifx\@empty#3\@empty\else%
365     \protected@write\AMC@XYFILE{}\{%
366       \string\boxchar{\the\AMCid@etud/\thepage:#4}{#1}%
367     }%
368   \fi\fi%

```

369 }

`amcxyfile` (*env.*) The following lines defines an environment to tag positions outputs for a particular part of the document. This is used mainly for documentation or testing.

```
370 \newenvironment{amcxyfile}[1]{%
371   \protected@write\AMC@XYFILE{}\string\xyopen{#1}}%
372 }{%
373   \protected@write\AMC@XYFILE{}\string\xyclose{}}%
374 }
```

`\AMCzone` The `\AMCzone[flags]{zone name}{zone content}` is a simple call to `\AMC@tracebox`:

```
375 \newcommand{\AMCzone}[3][\AMC@tracebox{1}{__zone:#1:#2}{#3}]
```

`\namefield` The `\namefield{name field content}` is a simple call to `\AMCzone`:

```
376 \newcommand{\namefield}[2][id]{\AMCzone[#1]{__n}{#2}}
```

It is used to enclose the page region where students are to write their names, so as to retrieve it easily from the scans.

`\namefielddots` The command `\namefielddots` can be used to fill a line with dots (printed sheets) or use a text field in PDF forms:

```
377 \newcommand{\namefielddots}{%
378   \noindent%
379   \ifAMC@pdfform%
380     \hspace*{\fill}%
381     \TextField[name={\the\AMCid@etud:namefield},width=.95\linewidth,bordercolor=0 0 0]{}%
382     \hspace*{\fill}
383   \else%
384     \dotfill
385   \fi%
386 }
```

As an example,

```
\namefield{\fbox{%
  \begin{minipage}{5cm}
    Name:

    \vspace*{.5cm}
    \namefielddots
    \vspace{2mm}
  \end{minipage}}}
```

produces the following box:

Name:

and outputs information about the position of the box in the `.xy` file, as seen in section 5.1.

4.8.3 Boxes to be checked by students

`\AMC@answerBox@` There are two styles for boxes to be checked by the students. The first one is an empty box, printed beside the answer. The second is a box with a character in it. It is mainly used when answers are to be given on a separate answer sheet.

These boxes can be drawn using command `\AMC@answerBox@{<char>}{<answer>}{<trace>}{<key>}`: `<char>` is the character to print inside the box, `<trace>` is non-empty if you want to log the box position in the .xy file, `<key>` is the box identification, and `<answer>` is an answer to be written in the box (or `\AMC@checkbox` for filling the box).

Depending on the required shape for the boxes, the corresponding

`\AMC@shape@xxx{<char>}{<answer>}{<trace>}{<key>}`

command is used.

- `\AMC@answerBox@{K}{1}{test}` produce the box $\boxed{K}$, writing the lines in the .xy file shown in section 5.2.
- `\AMC@answerBox@{K}{\AMC@checkbox}{}` produces $\blacksquare$
- `\AMC@answerBox@{}{8}{}` produces $\boxed{8}$
- `\AMC@answerBox@{K}{8}{1}{testb}` produces $\textcircled{8}$ with `\AMCboxStyle{shape=oval,color=red}`

```
387 \def\AMC@checkbox{}
388 \let\AMC@new@savebox=\newsavebox
389 \let\AMC@save@box=\savebox
390 \let\AMC@use@box=\usebox
391 \newif\ifAMC@draw@cross
```

The `\AMC@smashcentered{<text>}` command shows the `<text>` centered at point.

```
392 \newbox\AMC@smashbox
393 \newdimen\AMC@smashboxheight
394 \newcommand{\AMC@smashcentered}[1]{%
395   \setbox\AMC@smashbox\hbox{#1}%
396   \AMC@smashboxheight=\ht\AMC@smashbox%
397   \advance\AMC@smashboxheight by \dp\AMC@smashbox%
398   \vfuzz=\AMC@smashboxheight\hfuzz=\wd\AMC@smashbox%
399   \hspace*{-.5\wd\AMC@smashbox}\hbox to .5\wd\AMC@smashbox{%
400     \vbox to 0pt{%
401       \vspace*{-.5\AMC@smashboxheight}\vbox to .5\AMC@smashboxheight{%
402         \box\AMC@smashbox}}}%
403 }
```

`\AMC@setcolors@{<trace>}{<answer>}` sets colours `\AMC@boxcolor@` and `\AMC@fillcolor@` according to its arguments. It also sets the `\ifAMC@draw@cross` switch if AMC should draw a cross instead of filling the box.

```
404 \newcommand\AMC@setcolors@[2]{%
405   \def\AMC@boxcolor@{\AMC@boxcolor}%
406   \ifx\@empty#1\@empty \def\AMC@boxcolor@{black}\fi%
407   \ifAMC@correc\def\AMC@boxcolor@{black}\fi%
408   \def\AMC@fillcolor@{\ifx #2\AMC@checkbox%
409     \AMC@boxcolor@\else white\fi}%
410   \AMC@draw@crossfalse%
411   \ifKV@AMCdim@cross\ifx #2\AMC@checkbox%
```

```

412 \AMC@draw@crosstrue\fi\fi%
413 }
414 \newcommand\AMC@answerBox@[4]{%
415 \ifAMC@catalog%
416 \AMC@logchar{#1}{#4}%
417 \fi%
418 \AMC@LR{\hspace{0pt}}%
419 \lower\AMC@boxeddown\hbox{\csname AMC@shape@\AMC@shapename@\endcsname%
420 {AMC@choiceLabelFormat{#1}}{#2}{#3}{#4}}}%
421 }
422 \newcommand\AMC@shapeprepare@square{%
423 \newcommand\AMC@shape@square[4]{%
424 \fboxsep=\z@\fboxrule=\AMC@boxedrule%
425 \AMC@setcolors@{#3}{#2}%
426 \ifKV@AMCdim@cross\def\AMC@fillcolor@{white}\fi%
427 \fcolorbox{\AMC@boxcolor@}{\AMC@fillcolor@}%
428 {%
429 \boxput*(0,0){%
430 \ifAMC@draw@cross\AMC@crosschar\fi%
431 }{%
432 \vbox to \AMC@boxedheight{%
433 \AMC@tracepos{#3}{#4}%
434 \vfill%
435 \hbox to \AMC@boxedwidth{\hfill%
436 \AMC@smashcentered{\textcolor{\AMC@boxcolor@}{#1}}%
437 \AMC@smashcentered{#2}%
438 \hfill}\vfill}}%
439 \AMC@tracepos{#3}{#4}}%
440 }

```

`\AMC@makeovalbox{<trace>}{<answer>}{<box>}` prepares an oval frame in the L^AT_EX box `<box>`.

```

441 \newcommand\AMC@makeovalbox[3]{%
442 \AMC@setcolors@{#1}{#2}%
443 \ifKV@AMCdim@cross\def\AMC@fillcolor@{white}\fi%
444 \AMC@save@box{#3}{%
445 \begin{tikzpicture}%
446 \useasboundingbox (-0.5\AMC@boxedwidth-0.5\AMC@boxedrule,0.5\AMC@boxedheight+0.5\AMC@boxedrule)
447 rectangle (0.5\AMC@boxedwidth+0.5\AMC@boxedrule,-0.5\AMC@boxedheight-0.5\AMC@boxedrule);
448 \draw[\AMC@boxcolor@,fill=\AMC@fillcolor@,line width=\AMC@boxedrule,rounded corners=\AMC@oval@radi
449 (-0.5\AMC@boxedwidth,0.5\AMC@boxedheight)
450 rectangle (0.5\AMC@boxedwidth,-0.5\AMC@boxedheight);
451 \ifAMC@draw@cross
452 \draw[\AMC@boxcolor@,line width=\AMC@crossrule]
453 (-0.5\AMC@boxedwidth,0.5\AMC@boxedheight) -- (0.5\AMC@boxedwidth,-0.5\AMC@boxedheight)
454 (0.5\AMC@boxedwidth,0.5\AMC@boxedheight) -- (-0.5\AMC@boxedwidth,-0.5\AMC@boxedheight);
455 \fi
456 \end{tikzpicture}}%
457 }
458 \newcommand\AMC@shapeprepare@oval{%
459 \ifx\AMC@ovalbox@R\undefined\else%
460 \AMC@makeovalbox{1}{-}{\AMC@ovalbox@R}%
461 \AMC@makeovalbox{1}{-}{\AMC@checkedbox}{\AMC@ovalbox@RF}%
462 \AMC@makeovalbox{-}{-}{\AMC@ovalbox@}%
463 \AMC@makeovalbox{-}{-}{\AMC@checkedbox}{\AMC@ovalbox@F}%

```

```

464 \fi%
465 }
466 \newcommand\AMC@shape@oval[4]{%
467 \AMC@setcolors@{#3}-{#2}%
468 \AMC@tracebox{#3}{#4}{\boxput*(0,0){%
469 \AMC@smashcentered{\textcolor{\AMC@boxcolor@}{#1}}}%
470 \AMC@smashcentered{#2}%
471 }{%
472 \ifx\@empty#3\@empty%
473 \ifx #2\AMC@checkbox%
474 \AMC@use@box{\AMC@ovalbox@F}%
475 \else%
476 \AMC@use@box{\AMC@ovalbox@}%
477 \fi%
478 \else%
479 \ifx #2\AMC@checkbox%
480 \AMC@use@box{\AMC@ovalbox@RF}%
481 \else%
482 \AMC@use@box{\AMC@ovalbox@R}%
483 \fi%
484 \fi%
485 }}%
486 }
487 \newcommand\AMC@shape@prepare@form{}
488 \newcommand\AMC@shape@form@base[5]{%
489 \ifx #2\AMC@checkbox%
490 \def\AMC@shape@form@ticked{true}%
491 \else%
492 \def\AMC@shape@form@ticked{false}%
493 \fi%
494 \AMC@tracebox{#3}{#4}{%
495 \CheckBox[checked=\AMC@shape@form@ticked,%
496 checkboxsymbol=\ding{110},name={#5},%
497 bordercolor=0 0 0,%
498 width=\AMC@boxedwidth,height=\AMC@boxedheight]{#5}}%
499 }%
500 }
501 \newcommand\AMC@shape@form[4]{%
502 \AMC@shape@form@base{#1}{#2}{#3}{#4}{\the\AMCid@etud:#4}%
503 }
504 \newcommand\AMC@shape@prepare@none{}
505 \newcommand\AMC@shape@none[4]{ #1 }

```

\AMC@answerBox Command \AMC@answerBox is the same as \AMC@answerBox@, but if $\langle char \rangle$ is empty, it is replaced by an arabic or alphabetical counter, depending on the use of the `digits` package option.

\AMCchoiceLabel To use another way to label the choices boxes, the user can redefine the \AMCchoiceLabel macro, which takes as argument the name of the counter used to number the choices. One can for example use `\def\AMCchoiceLabel#1{\alph{#1}}` to ask for lowercase letters.

To write these labels with another font, size, or so, the user can redefine the \AMCchoiceLabelFormat macro, which takes as argument the label. One can for example get sans serif bold labels with `\def\AMCchoiceLabelFormat#1{\textsf{\textsf{#1}}}`.

```

506 \def\AMCchoiceLabel#1{%
507 \ifAMC@inside@digit\arabic{#1}%

```

```

508 \else\Alph{#1}\fi%
509 }
510 \def\AMCchoiceLabelFormat#1{#1}
511 \newcounter{AMC@ncase}
512 \setcounter{AMC@ncase}{0}
513 \newcommand\AMC@answerBox[4]{%
514 \AMC@answerBox@{\ifx\@empty#1\@empty%
515 \AMCchoiceLabel{AMC@ncase}%
516 \else #1\fi}{#2}{#3}{#4}}

```

`\AMCboxStyle` The dimensions of these box are managed by `\AMCboxDimensions{<sizes>}`, where `<sizes>` is a comma separated list of `<name>=<dimension>` constructs. Here, `<name>` can be `size` for the box size, `rule` for the box rule width, `down` for moving the box down, `color` for the box color and `outsidesep` for the distance between the box and the letter (when outside the box).

The `<color>` value given to `color` is a color that should be defined for the `xcolor` package. This color is used only in the case the box will be used for data capture: it is not used on the corrected answer sheet (`answers` or `indivanswers` package option), and not used on the subject part of an exam with a separate answer sheet (`separateanswersheet` package option).

The `\AMCboxColor{<color>}` command is defined as an alias to `\AMCboxStyle{color=<color>}`, and `\AMCboxDimensions` as an alias to `\AMCboxStyle`, for backward compatibility.

```

517 \newlength\AMC@boxedrule
518 \newlength\AMC@crossrule
519 \newlength\AMC@boxeddown
520 \newlength\AMC@boxedwidth
521 \newlength\AMC@boxedheight
522 \newlength\AMC@oval@radius
523 \newlength\AMC@outside@sep
524 \define@choicekey{AMCdim}{shape}{square,oval,form,none}{\def\AMC@shapename{#1}}
525 \define@key{AMCdim}{size}{\AMC@boxedwidth=#1\AMC@boxedheight=#1}
526 \define@key{AMCdim}{height}{\AMC@boxedheight=#1}
527 \define@key{AMCdim}{width}{\AMC@boxedwidth=#1}
528 \define@key{AMCdim}{rule}{\AMC@boxedrule=#1}
529 \define@key{AMCdim}{outsidesep}{\AMC@outside@sep=#1}
530 \define@key{AMCdim}{down}{\AMC@boxeddown=#1}
531 \define@key{AMCdim}{color}{\def\AMC@boxcolor{#1}}
532 \define@boolkey{AMCdim}{cross}{false}{}
533 \define@key{AMCdim}{crosschar}{\textbf{\textsf{X}}}{\def\AMC@crosschar{#1}}
534 \define@key{AMCdim}{crossrule}[1.5pt]{\AMC@crossrule=#1}
535 \def\AMC@shapeprepare{\csname AMC@shapeprepare@\AMC@shapename@ \endcsname}
536 \def\AMCboxStyle#1{%
537 \setkeys{AMCdim}{#1}%
538 \ifnum\AMC@boxedwidth<\AMC@boxedheight%
539 \AMC@oval@radius=\AMC@boxedwidth\divide\AMC@oval@radius\tw@%
540 \else%
541 \AMC@oval@radius=\AMC@boxedheight\divide\AMC@oval@radius\tw@%
542 \fi%
543 \AMC@shapeprepare%
544 }
545 \AMCboxStyle{shape=square,size=2.5ex,down=.4ex,rule=.5pt,outsidesep=.1em,color=black,cross,crosschar,crossrule}
546 \newcommand\AMCboxColor[1]{\AMCboxStyle{color=#1}}
547 \let\AMCboxDimensions=\AMCboxStyle

```

`\AMCboxOutsideLetter` Command `\AMC@box{<char>}{<answer>}` prints a box with character `<char>` inside, showing an-

```

\AMC@box
\AMC@formBox@
\AMC@formBox
outsideLabelFormat

```

swer $\langle answer \rangle$ (`\AMC@checkbox` to get a filled box), using global variables to identify the box (question and choice).

It calls `\AMC@formBox@{ $\langle char \rangle$ }{ $\langle answer \rangle$ }{ $\langle trace \rangle$ }{ $\langle key \rangle$ }` to actually render the box.

Command `\AMC@formBox` simply sets the first argument when empty before calling `\AMC@formBox@`.

The command `\AMCboxOutsideLetter{ $\langle box \rangle$ }{ $\langle char \rangle$ }` is called to print the box *and* the character $\langle char \rangle$ outside (and next to) it. The character is formatted using `\AMCoutsideLabelFormat` first: if you need bold characters, redefine it with `\def\AMCoutsideLabelFormat#1{\textbf{#1}}`

`\AMC@keyBox@` is used instead of `\AMC@formBox@` when the text that corresponds to the answer is the letter/character inside the box itself (see `\AMCcodeGrid` and `\AMCnumericChoices`).

```

548 \def\AMCoutsideLabelFormat#1{#1}
549 \newcommand\AMCboxOutsideLetter[2]{#1\nobreak\hspace{.1em}\AMCoutsideLabelFormat{#2}}
550 \newif\ifAMC@printformoutside@%
551 \newcommand\ifAMC@printformoutside{%
552   \AMC@printformoutside@false%
553   \ifAMC@ensemble\ifAMC@outside@box%
554     \ifAMCformulaire@dedans\AMC@printformoutside@true\fi%
555     \ifAMC@zoneformulaire\AMC@printformoutside@true\fi%
556   \fi\fi%
557   \ifAMC@printformoutside@%
558 }
559 \newcommand\AMC@formBox@[4]{%
560   \ifAMC@printformoutside% letter to be written outside the box
561     \AMCboxOutsideLetter{\AMC@answerBox@{#2}{#3}{#4}}{#1}%
562   \else%
563     \AMC@answerBox@{#1}{#2}{#3}{#4}%
564   \fi%
565   \AMC@tracechar{#1}{#2}{#3}{#4}%
566 }
567 \newif\ifAMC@printkeyoutside@%
568 \newcommand\ifAMC@printkeyoutside{%
569   \AMC@printkeyoutside@false%
570   \ifAMC@ensemble%
571     \ifAMC@outside@box\AMC@printkeyoutside@true\fi%
572   \else%
573     \ifAMC@inside@box\else\AMC@printkeyoutside@true\fi%
574   \fi%
575   \ifAMC@printkeyoutside@%
576 }
577 \newcommand\AMC@keyBox@[4]{%
578   \ifAMC@printkeyoutside%
579     \AMCboxOutsideLetter{\AMC@answerBox@{#2}{#3}{#4}}{#1}%
580   \else%
581     \AMC@answerBox@{#1}{#2}{#3}{#4}%
582   \fi%
583   \AMC@tracechar{#1}{#2}{#3}{#4}%
584 }
585 \newcommand\AMC@formBox[4]{%
586   \AMC@formBox@{\ifx\@empty#1\@empty%
587     \AMCchoiceLabel{AMC@ncase}%
588     \else #1\fi}{#2}{#3}{#4}%
589 }
590 \newcommand{\AMC@box}[2]{%

```

```

591 \ifAMC@ensemble%
592 \ifAMC@zoneformulaire% for codes inside form sheet
593 \protect\AMC@formBox{#1}{#2}{1}{case:\AMCid@name:\the\AMCid@quest,\the\AMCrep@count}%
594 \else%
595 \ifAMC@formulaire@dedans% for answer boxes inside form sheet
596 \protect\AMC@formBox{#1}{#2}{1}{case:\AMCid@name:\the\AMCid@quest,\the\AMCrep@count}%
597 \else% outside form sheet: not to be read during data capture
598 \AMC@formBox{#1}{#2}{1}{casequestion:\AMCid@name:\the\AMCid@quest,\the\AMCrep@count}%
599 \fi\fi%
600 \else% no separate sheet for answers: always read
601 \ifAMC@inside@box%
602 \AMC@formBox{#1}{#2}{1}{case:\AMCid@name:\the\AMCid@quest,\the\AMCrep@count}%
603 \else%
604 \AMC@formBox{}{#2}{1}{case:\AMCid@name:\the\AMCid@quest,\the\AMCrep@count}%
605 \fi%
606 \fi%
607 }

```

4.8.4 Scoring zones

`\AMCscoreZone` The source file can define zones that will be used to print scores when annotating the completed answer sheets. The command `\AMCscoreZone{<zone>}` logs these zones positions on the page.

```

608 \newif\ifAMCsz@logged\AMCsz@loggedfalse
609 \newcommand{\AMCscoreZone}[1]{%
610 \ifAMC@ensemble%
611 \ifAMC@formulaire@dedans%
612 \AMC@tracebox{1}{score::\the\AMCid@quest,-1}{#1}%
613 \else%
614 \AMC@tracebox{1}{scorequestion::\the\AMCid@quest,-1}{#1}%
615 \fi%
616 \else%
617 \AMC@tracebox{1}{score::\the\AMCid@quest,-1}{#1}%
618 \fi%
619 \ifAMCsz@logged\else%
620 \AMCmessage{VAR:scorezones=1}%
621 \global\AMCsz@loggedtrue%
622 \fi%
623 }

```

4.8.5 Binary boxes

The package prints on each page some boxes that code (like binary digits) student sheet number, page number and a check number, so as to be read easily from scans after exam.

`\AMCid@checkmax` The check number is just decreased each page. Its maximum value is `\AMCid@checkmax`.
`\AMC@NCBetud` The number of binary digits used to print student sheet number, page and check number are `\AMC@NCBetud`, `\AMC@NCBpage` and `\AMC@NCBcheck`. The number of the first page is `\AMC@NCBcheck`.
`\AMC@premierecopie`

The length of zone reserved for binary boxes is `\AMC@CBtaille`.

```

624 \def\AMCid@checkmax{60}
625 \def\AMC@NCBetud{12}
626 \def\AMC@NCBpage{6}
627 \def\AMC@NCBcheck{6}

```

```

628 \newlength{\AMC@CBtaille}\setlength{\AMC@CBtaille}{5cm}
629 \def\AMC@premierecopie{1}

```

`\AMC@binaryCode` The command `\AMC@binaryCode{<options>}{<n>}` prints boxes to represent the number $\langle n \rangle$ in its binary form. Options from $\langle options \rangle$ include:

`ndigits=<ndigits>` for the number of digits to be shown.

`id=<id>` for an ID of the number role (1 for the student number, 2 for the page number, 3 for the checking value).

`hsep=<hsep>` for the space between boxes.

`style=<style>` for some box style options.

`\AMCbin@one` and `\AMCbin@zero` print individual digit-boxes.

For example, `\AMC@binaryCode{ndigits=12}{367}` shows $367 = 000101101111_2$ using 12 boxes:



```

630 \newtoks\AMCbin@sequence
631 \newcount\AMCbin@number
632 \newcount\AMCbin@digit
633 \newcount\AMCbin@id
634 \newcount\AMCbin@did
635 \newcount\AMCbin@endigits
636 \newdimen\AMCbin@hsep
637 \define@key{AMCbin}{ndigits}{\AMCbin@endigits=#1}
638 \define@key{AMCbin}{id}{\AMCbin@id=#1}
639 \define@key{AMCbin}{hsep}{\AMCbin@hsep=#1}
640 \define@key{AMCbin}{style}[]{\def\AMCbin@style{#1}}
641 \def\AMCbin@one{%
642   \ifnum\AMCbin@did>\z@%
643     \hspace{\AMCbin@hsep}%
644     \fi%
645     \advance\AMCbin@did\@ne%
646   \ifnum\AMCbin@id>0%
647     \AMC@answerBox@{}{\AMC@checkedbox}{1}{chiffre:\the\AMCbin@id,\the\AMCbin@did}%
648     \else%
649     \AMC@answerBox@{}{\AMC@checkedbox}{1}{}%
650     \fi}
651 \def\AMCbin@zero{%
652   \ifnum\AMCbin@did>\z@%
653     \hspace{\AMCbin@hsep}%
654     \fi%
655     \advance\AMCbin@did\@ne%
656   \ifnum\AMCbin@id>0%
657     \AMC@answerBox@{}{1}{chiffre:\the\AMCbin@id,\the\AMCbin@did}%
658     \else%
659     \AMC@answerBox@{}{1}{}%
660     \fi}
661 \newcommand{\AMC@binaryCode}[2]{%
662   \setkeys{AMCbin}{ndigits=1,hsep=0pt,style}\setkeys{AMCbin}{#1}%
663   \AMCbin@did=\z@%

```

```

664 {\AMCboxDimensions{shape=square,size=.32cm,down=0pt,rule=.2pt,cross=false}\expandafter\AMCboxDimensions\
665 \AMCbin@digit=\z@%
666 \loop%
667 \ifnum\AMCbin@number>\z@%
668 \advance\AMCbin@digit\@ne%
669 \ifodd\AMCbin@number\AMCbin@sequence=\expandafter{\expandafter\AMCbin@one\the\AMCbin@sequence}%
670 \else\AMCbin@sequence=\expandafter{\expandafter\AMCbin@zero\the\AMCbin@sequence}\fi%
671 \divide\AMCbin@number\tw@%
672 \repeat%
673 \loop\relax%
674 \ifnum\AMCbin@digit<\AMCbin@ndigits\advance\AMCbin@digit\@ne%
675 \AMCbin@sequence=\expandafter{\expandafter\AMCbin@zero\the\AMCbin@sequence}\repeat%
676 \the\AMCbin@sequence%
677 \ifnum\AMCbin@digit>\AMCbin@ndigits\PackageError{automultiplechoice}{Too low AMC@NCB value (got \the\AMC
678 }

```

The commands `\AMCbin@begin` and `\AMC@binaryBoxes` are now unused and are defined for backward compatibility.

```

679 \def\AMCbin@begin#1{\setkeys{AMCbin}{id=#1}}
680 \newcommand{\AMC@binaryBoxes}[2][1]{%
681 \AMC@binaryCode{ndigits=#1}{#2}%
682 }

```

4.9 Checking Environment

`\AMCcurrentenv` Sets the current environment as document.

```

683 \def\AMCcurrentenv{document}

```

`\AMCif@env` Checks for the current environment.

```

684 \def\AMCif@env#1{
685   \def\AMC@tempenv{#1}%
686   \ifx\AMC@tempenv\AMCcurrentenv
687     \expandafter\@firstoftwo
688   \else
689     \expandafter\@secondoftwo
690   \fi
691 }

```

4.10 Handling groups of questions

The package allows to handle groups of questions, so as to be able to shuffle them before printing them to the sheets.

`\nouveaugroupe` Command `\nouveaugroupe{<group-name>}{<n>}` creates a new (empty) group with name `<group-name>` (argument `<n>` is present only for compatibility reasons and is ignored). Command `\element{<group-name>}{<text>}` adds to group `<group-name>` a new element that contains `<text>`. `<text>` can be a `question` environment, ore two successive `questions` to be kept together, or anything else. Calling command `\nouveaugroupe` is not compulsory, as `\element` calls it if necessary.

```

692 \newcount\AMCtok@k
693 \newcount\AMCtok@max
694 \newcount\AMCtok@size

```

```

695 \newcommand{\nouveaugroupe}[2]{%
696   \expandafter\ifx\csname #1@k\endcsname\relax%
697   \expandafter\newcount\csname #1@k\endcsname%
698   \expandafter\newcount\csname AMC#1@j\endcsname%
699   \csname #1@k\endcsname=\z@\relax%
700   \csname AMC#1@j\endcsname=\z@\relax%
701   \setgroupmode{#1}{\AMCdefault@groupmode}%
702   \fi%
703 }
704 \newcommand\AMC@prepare@element[1]{%
705   \nouveaugroupe{#1}{}%
706   \global\advance\csname #1@k\endcsname\@ne\relax%
707   \AMCtok@k=\csname #1@k\endcsname%
708   \expandafter\ifx\csname #1@romannumeral\AMCtok@k\endcsname\relax%
709   \expandafter\newtoks\csname #1@romannumeral\AMCtok@k\endcsname\fi%
710 }
711 \newcommand{\element}[2]{%
712   \AMC@prepare@element{#1}%
713   \global\csname #1@romannumeral\AMCtok@k\endcsname={#2}%
714 }

```

`\setgroupmode` Command `\setgroupmode{<group-name>}{<mode>}` sets the group mode to `<mode>` for group `<group-name>`. This mode setup the behaviour of `\insertgroup` and `\copygroup` for this group:

1. With mode `fixed`, group's elements will be taken from the beginning.
2. With mode `cyclic`, the elements will be taken from the group following the last call group's use, recycling if necessary.
3. Mode `withreplacement` is the same as `fixed`, but the group is shuffled before each use.
4. Mode `withoutreplacement` is like `cyclic`, adding some shuffling when coming back to the beginning of the group.

The command `\setdefaultgroupmode{<mode>}` sets the group mode to be used for the following created groups (a group is created at the first `\element{<group>}` call). When no `\setdefaultgroupmode` is used, `fixed` is the default mode.

```

715 \def\AMCdefault@groupmode{fixed}
716 \newcommand{\setdefaultgroupmode}[1]{\def\AMCdefault@groupmode{#1}}
717 \newcommand{\setgroupmode}[2]{%
718   \expandafter\ifx\csname AMCgrouppre@#2\endcsname\relax%
719   \PackageError{automultiplechoice}{Unknown group mode for #1 : #2}%
720     {You asked to set group '#1' mode to '#2',
721      but '#2' is not a valid group mode}%
722   \else%
723   \expandafter\global\expandafter\def\csname AMC#1@mode\endcsname{#2}%
724   \fi%
725 }

```

The functions `\AMCgrouppre@xxx{<group-name>}{<n>}{<i>}` are called before using `<n>` elements from group `<group-name>` starting from index `<i>` (negative value for `<i>` stands for the current value of the group index), either with `\insertgroup` or `\copygroup`.

For mode `fixed`, the group index is set to `<i>`, or 0 if `<i>` is negative (take elements from the beginning).

```

726 \newcommand{\AMCgrouppre@fixed}[3]{%
727   \ifnum#3<\z@%
728     \csname AMC#1@j\endcsname=\z@%
729   \else%
730     \csname AMC#1@j\endcsname=#3%
731   \fi%
732 }

```

For mode **withreplacement**, the group is shuffled and the group index is set to $\langle i \rangle$ or 0 (take elements from the beginning) if negative.

```

733 \newcommand{\AMCgrouppre@withreplacement}[3]{%
734   \ifnum#3<\z@%
735     \csname AMC#1@j\endcsname=\z@%
736   \else%
737     \csname AMC#1@j\endcsname=#3%
738   \fi%
739   \shufflegroup{#1}%
740 }

```

For mode **withoutreplacement**, the group index is set to $\langle i \rangle$, or left unchanged if $\langle i \rangle$ is negative. If there is not enough elements left in the group, the elements before the index and the elements after the index are shuffled.

```

741 \newcount\AMC@imax
742 \newcommand{\AMCgrouppre@withoutreplacement}[3]{%
743   \ifnum#3<\z@%
744   \else%
745     \csname AMC#1@j\endcsname=#3%
746   \fi%
747   \ifnum\AMCtok@ik=\AMCloop@k%
748     \AMCtok@ik=\z@%
749   \fi%
750   \ifnum\AMCtok@ik=\z@%
751     \shufflegroup{#1}%
752   \else%
753     \AMC@imax=\AMCloop@k%
754     \advance\AMC@imax -#2\relax%
755     \ifnum\AMCtok@ik>\AMC@imax%
756       \shufflegroupslicel{#1}{\@ne}{\AMCtok@ik}%
757       \ifnum\AMCtok@ik<\AMCloop@k%
758         \advance\AMCtok@ik\@ne%
759       \shufflegroupslicel{#1}{\AMCtok@ik}{\AMCloop@k}%
760     \fi%
761   \fi%
762 \fi%
763 }

```

For mode **cyclic**, nothing has to be done, except setting the group index if non-negative.

```

764 \newcommand{\AMCgrouppre@cyclic}[3]{%
765   \ifnum#3<\z@%
766   \else%
767     \csname AMC#1@j\endcsname=#3%
768   \fi%
769 }

```

The function `\AMCgroup@pre{<mode>}{<group-name>}{<n>}{<i>}` calls the right `\AMCgroup@pre@xxx` command.

```
770 \newcommand{\AMCgroup@pre}[4]{%
771   \csname AMCgroup@pre@#1\endcsname{#2}{#3}{#4}%
772 }
```

`\shufflegroup` Command `\shufflegroup{<group-name>}` shuffles the elements of group `<group-name>`, and

`\insertgroup` `\shufflegroupslices{<group-name>}{<a>}{<b>}` shuffles elements `<a>` to `<b>` from group `<group-name>`.

`\insertgroupfrom` It can be called at each student sheet in order to get different student sheets and avoid cheating.

Command `\insertgroup[<n>]{<groupname>}` inserts all the elements of group `<groupname>`, or only the first `<n>` elements if `<n>` is given. `\insertgroupfrom[<n>]{<groupname>}{<i>}` inserts all the elements of group `<groupname>` starting from index `<i>` (the index of the first element is 0), or only the first `<n>` elements if `<n>` is given.

```
773 \newcommand{\shufflegroup}[1]{%
774   \ifAMC@shuffleG{\AMC@shuffletoks{\number\csname #1@k\endcsname}{#1@}}\fi%
775 }
776 \newcommand{\shufflegroupslices}[3]{%
777   \ifAMC@shuffleG{\AMC@shuffletoks[#2]{#3}{#1@}}\fi%
778 }
779 \newcount\AMCtok@ik
780 \newcount\AMCloop@k
781 \newcommand{\AMCgrouploop@prep}[3]{%
782   \AMCtok@size=#1\relax%
783   \ifAMC@fullGroups\AMCtok@size=\m@ne\fi%
784   \ifnum\AMCtok@size<\z@%
785     \AMCtok@size=\csname #2@k\endcsname%
786   \fi%
787   \AMCtok@ik=\csname AMC#2@j\endcsname%
788   \AMCloop@k=\csname #2@k\endcsname%
789   \expandafter\ifx\csname AMC#2@mode\endcsname\relax%
790     \PackageError{automultiplechoice}{No group mode for #2}%
791     {No mode has been defined for group '#2'. This should not occur...}%
792   \fi%
793   \AMCgroup@pre{\csname AMC#2@mode\endcsname}{#2}{\the\AMCtok@size}{#3}%
794 }
795 \newcommand{\AMCgrouploop@next}[1]{%
796   \global\advance\csname AMC#1@j\endcsname\@ne\relax%
797   \expandafter\ifnum\csname AMC#1@j\endcsname>\AMCloop@k\relax%
798     \global\csname AMC#1@j\endcsname=\@ne%
799   \fi%
800   \AMCtok@ik=\csname AMC#1@j\endcsname%
801   \advance\AMCtok@size\m@ne%
802 }
803 \newcommand{\insertgroupfrom}[3][-1]{%
804   \ifnum#1=0%
805     \else%
806       \AMCgrouploop@prep{#1}{#2}{#3}%
807       {\loop%
808         \AMCgrouploop@next{#2}%
809         {\the\csname #2@romannumeral\AMCtok@ik\endcsname}%
810         \ifnum\AMCtok@size>\z@\repeat}%
811       \fi%
812 }
```

```

813 \newcommand{\insertgroup}[2][-1]{%
814   \insertgroupfrom[#1]{#2}{-1}%
815 }

```

`\cleargroup` The commands `\cleargroup` and `\copygroup` can also be used to make more complex questions combinations in the exams, allowing for example to ask the package to shuffle 3 questions taken at random from group `groupa` and 5 questions taken at random from group `groupb`.

`\cleargroup{<group>}` clears the group `<group>`, erasing all of its elements.

`\copygroup[<n>]{<from>}{<to>}` copies `<n>` elements from group `<from>` to group `<to>`. If optional parameter `<n>` is not given, all the questions from group `<from>` are copied. `\copygroupfrom[<n>]{<from>}{<to>}{<i>}` copies `<n>` elements from group `<from>` to group `<to>`, starting from element at index `<i>` (the index of the first element is 0). If optional parameter `<n>` is not given, all the questions from group `<from>` are copied.

See section 3.4 for an illustration for these commands.

```

816 \newcommand{\cleargroup}[1]{%
817   \nouveau groupe{#1}{}%
818   \csname #1@k\endcsname=\z@\relax%
819   \csname AMC#1@j\endcsname=\z@\relax%
820 }
821 \newcommand{\copygroupfrom}[4][-1]{%
822   \ifnum#1=0%
823     \else%
824       \AMCgrouploop@prep{#1}{#2}{#4}%
825       {\loop%
826         \AMCgrouploop@next{#2}%
827         \AMC@prepare@element{#3}%
828         \global\csname #3@romannumeral\AMCtok@k\endcsname=\csname #2@romannumeral\AMCtok@ik\endcsname%
829         \ifnum\AMCtok@size>\z@\repeat}%
830       \fi%
831 }
832 \newcommand{\copygroup}[3][-1]{%
833   \copygroupfrom[#1]{#2}{#3}{-1}%
834 }

```

4.11 Questions

To manage multiple choice questions, first set some counters and token registers to handle answers. Token registers `\reponse@i`, `\reponse@ii` and so on will be used for answers – we restrict the number of answers of a single questions to `\AMCload@counter = 199`.

```

835 \newcount\AMCrep@count
836 \newcount\AMCrep@nn
837 \newcount\AMCrep@nnmax
838 \AMCload@counter=199
839 \@whilenum\AMCload@counter>0\do{%
840   \expandafter\newtoks\csname reponse@\romannumeral\AMCload@counter\endcsname%
841   \advance\AMCload@counter\m@ne%
842 }

```

`\AMCload@reponse` Command `\AMCload@reponse{<n>}{<text>}` will be used to add answer number `<n>` with text `<text>` (`<text>` will include the box to be ticked and all the layout commands) to the set of answers (in a token register `\reponse@xxx` – counter `\AMCload@counter` keeps track of the number of answers), in order to shuffle them when all answers will be loaded.

When answers are not to be shuffled, command `\AMCrien@deux{<n>}{<text>}` will be used instead, only printing `<text>`.

```

843 \newcommand\AMCload@reponse[2]{%
844   \global\advance\AMCload@counter\@ne\relax%
845   \global\csname reponse@\romannumeral\AMCload@counter\endcsname%
846   =\expandafter{\expandafter\AMCrep@count\expandafter=#2 #1}%
847 }
848 \newcommand\AMCrien@deux[2]{#1}

```

`\shuffle@it` After loading all answers, commands `\shuffle@it` will be used to shuffle them, and `\AMCdump@reponses` to print them.

```

849 \def\shuffle@it{\AMC@shuffletoks{\number\AMCload@counter}{reponse@}}
850 \newcount\AMCnum@questions
851 \newcommand\AMCdump@reponses{%
852   \global\AMCnum@questions=\AMCload@counter%
853   \@whilenum\AMCload@counter>0\do{%
854     \the\csname reponse@\romannumeral\AMCload@counter\endcsname%
855     \advance\AMCload@counter\m@ne}}

```

4.11.1 Managing answers

`\lastchoices` Command `\AMCrep@init{<mode>}` is called for each question before reading answers. `<mode>` `\AMCrep@init` is `r` for shuffled answers, and `o` if answers are not to be shuffled. It sets the number of answers `\AMC@fin@rep` counter to zero, and calls `\AMCrep@o` or `\AMCrep@r` depending on `<mode>`. These commands sets `\AMCload@@reponse` and `\AMCrep@fini` that will be called for each answer and after the last answer respectively, depending on `<mode>`:

- If `<mode>=r`, `\AMCload@@reponse` is `\AMCload@reponse` (loads answer to token register) and `\AMCrep@fini` calls `\shuffle@it` and `\AMCdump@reponses`;
- If `<mode>=o`, `\AMCload@@reponse` is `\AMCrien@deux` (prints answer directly) and `\AMCrep@fini` does nothing.

Command `\lastchoices` is called before giving answers that are to be printed at the end (even when shuffling answers). It closes the answers list calling `\AMCrep@fini` and opens another one in ordered mode. Note that it also saves the value of `\AMCrep@count`, which is the number of the current answer among all answers given in the subject source for the current question.

Command `\AMC@fin@rep` is to be called after the last answer: it adds a “None of these answers are correct.” answer if necessary (package option `completemulti`) with answer number zero, and calls `\AMCrep@fini`.

```

856 \newcommand\AMCrep@init[1]{%
857   \ifAMC@ordre\AMCrep@o\else%
858     \csname AMCrep@#1\endcsname\fi\AMCload@counter=\z@}
859 \newcommand\AMCrep@o{%
860   \def\AMCload@@reponse{\AMCrien@deux}\def\AMCrep@fini{}}
861 \newcommand\AMCrep@r{%
862   \def\AMCload@@reponse{\AMCload@reponse}%
863   \def\AMCrep@fini{\shuffle@it\AMCdump@reponses}}
864 \newcount\AMCrep@count
865 \newcommand\lastchoices{%
866   \AMCrep@count=\AMCrep@count%
867   \AMCrep@fini\AMCrep@init{o}%

```

```

868 \AMCrep@count=\AMCrep@count}
869 \newcommand\@aucune{\emph{\AMC@loc@none}}
870 \newcommand\AMC@fin@rep{%
871 \ifAMCcomplete@multi\ifAMCtype@multi%
872 \lastchoices\AMCrep@count=-1%
873 \ifAMCune@bonne\wrongchoice{\@aucune}\else%
874 \ifAMC@postcorrect\wrongchoice{\@aucune}\else\correctchoice{\@aucune}\fi%
875 \fi\fi\fi\AMCrep@fini}

```

4.11.2 Separate answer sheet

This package needs some memory to print questions/answers boxes again on a separate answer sheet.

`\AMCformQuestion` First define commands that will announce questions and answers on the separate answer sheet
`\AMCformAnswer` (these commands can be modified by the user): `\AMCformQuestion{<number>}` is responsible for announcing question, and `\AMCformAnswer{<box>}` is responsible for printing the box to be ticked, given as argument `<box>`.

Commands `\AMCformQuestionA` and `\AMCformAnswerA` set up counter `\AMC@ncase` value before calling their counterparts.

```

876 \def\AMCformBeforeQuestion{\vspace{\AMCformVSpace}\par}
877 \def\AMCformAfterQuestion{\ifAMC@asqbloc\egroup\fi}
878 \def\AMCformQuestion#1{\AMC@loc@qf{#1}}
879 \def\AMCformQuestionN{\AMCformQuestion{\AMC@qaff}}
880 \def\AMCformQuestionA{%
881 \setcounter{AMC@ncase}{0}%
882 \AMCformBeforeQuestion%
883 \ifAMC@asqbloc\vbox\bgroup\fi%
884 \ifx\@empty\AMC@sza@callout\@empty\else%
885 \csname\AMC@sza@callout\endcsname%
886 \fi%
887 \AMCformQuestionN%
888 \ifx\@empty\AMC@sza@callin\@empty\else%
889 \csname\AMC@sza@callin\endcsname%
890 \fi%
891 }
892 \def\AMCformAnswer#1{\hspace{\AMCformHSpace} #1}
893 \def\AMCformAnswerA#1{\addtocounter{AMC@ncase}{1}\AMCformAnswer{#1}}

```

`\AMC@mem@add@ifneeded` These are commands to manage memory for separate answer sheet. `\AMC@mem@add@ifneeded{<code>}`

`\AMCformBegin` adds `<code>` to this memory. `\AMC@mem@answer{<code>}` adds to memory answer code `<code>`, and
`\AMCform` `\AMC@mem@openQuestion` adds to memory question code to announce current question.

`\AMCformS` The command `\AMCformBegin` defines the beginning of the separate answer sheet for the current student sheet, and `\AMCform` prints the whole memory: questions and answers boxes.

`\AMCformS` is a `\AMCform` variant that does not clear the list of answer boxes. It can be used to make the same exact subject for all students, displaying the questions before (outside) `onecopy`, so that `onecopy` contains only the answer sheet.

```

894 \ExplSyntaxOn
895
896 \prg_set_conditional:Nnn \amc_if_separate_question: { p , T } {
897 \ifAMC@ensemble

```

```

898     \ifAMC@zoneformulaire
899         \prg_return_false:
900     \else
901         \prg_return_true:
902     \fi
903 \else
904     \prg_return_false:
905 \fi
906 }
907 \cs_new_eq:NN \AMC@if@separate@question \amc_if_separate_question:T
908
909 \int_new:N \amc_memory_elts_count
910
911 \cs_new:Nn \amc_clear_memory: { \int_gzero:N \amc_memory_elts_count }
912 \cs_new_eq:NN \AMC@mem@clear \amc_clear_memory:
913
914 \cs_new:Npn \amc_memory_elt_i:n #1 {
915     amc_memory_elts_ \int_to_alph:n { #1 }
916 }
917 \cs_new:Nn \amc_memory_current_elt: {
918     \amc_memory_elt_i:n \amc_memory_elts_count
919 }
920 \cs_new:Npn \amc_memory_vars_i:n #1 {
921     amc_memory_vars_ \int_to_alph:n { #1 }
922 }
923 \cs_new:Nn \amc_memory_current_vars: {
924     \amc_memory_vars_i:n \amc_memory_elts_count
925 }
926
927 \cs_new:Nn \amc_add_memory_elt: {
928     \int_gincr:N \amc_memory_elts_count
929     \tl_gclear_new:c { \amc_memory_current_elt: }
930     \tl_gclear_new:c { \amc_memory_current_vars: }
931 }
932 \cs_new_eq:NN \AMC@mem@next \amc_add_memory_elt:
933
934 \cs_new:Npn \amc_add_to_memory:n #1 {
935     \tl_gput_right:cn { \amc_memory_current_elt: } { #1 }
936 }
937 \cs_new_eq:NN \AMC@mem@add \amc_add_to_memory:n
938
939 \cs_new:Npn \amc_add_to_vars:n #1 {
940     \tl_gput_right:cn { \amc_memory_current_vars: } { #1 }
941 }
942 \cs_new_eq:NN \AMC@mem@addvar \amc_add_to_vars:n
943
944 \cs_new:Npn \amc_add_qidaffname:nnn #1#2#3 {
945     \amc_add_to_vars:n {\AMCid@quest=#1\setcounter{AMCquestionaff}{#2}%
946         \global\def\AMCid@name{#3}}
947 }
948 \cs_generate_variant:Nn \amc_add_qidaffname:nnn { xxx }
949 \cs_new_eq:NN \AMC@mem@qidaffname \amc_add_qidaffname:xxx
950

```

```

951 \cs_new:Npn \amc_mem_elt_cat:n #1 {
952   \amc_add_to_vars:n { \def\AMCmem@elt@cat{ #1 } }
953 }
954 \cs_generate_variant:Nn \amc_mem_elt_cat:n { x }
955 \cs_new_eq:NN \AMC@mem@category \amc_mem_elt_cat:x
956
957 \cs_new:Npn \amc_add_aid:n #1 {
958   \amc_add_to_memory:n {\AMCrep@count=#1}
959 }
960 \cs_generate_variant:Nn \amc_add_aid:n { x }
961 \cs_new_eq:NN \AMC@mem@aid \amc_add_aid:x
962
963 \cs_new:Npn \amc_if_category_is_p:n #1 {
964   \str_if_eq_p:on { \AMCmem@elt@cat } { #1 }
965 }
966 \cs_new:Npn \amc_use_memory:n #1 {
967   \int_step_inline:nnnn { 1 } { 1 } \amc_memory_elts_count {
968     \def\AMCmem@elt@cat{ plain }
969     \tl_use:c { \amc_memory_vars_i:n { ##1 } }
970     \bool_if:nTF { #1 } {
971       \tl_use:c { \amc_memory_elt_i:n { ##1 } }
972     } { }
973   }
974 }
975 \cs_new:Nn \amc_use_memory: { \amc_use_memory:n { \c_true_bool } }
976 \cs_new_eq:NN \AMC@mem@show \amc_use_memory:
977 \cs_new_eq:NN \AMC@mem@show@filter \amc_use_memory:n
978 \cs_new_eq:NN \AMC@if@category \amc_if_category_is_p:n
979
980 \ExplSyntaxOff
981 \newcommand\AMC@mem@add@ifneeded[1]{%
982   \AMC@if@separate@question{%
983     \AMC@mem@add{#1}%
984   }%
985 }
986 \newcommand\AMC@mem@addsingle@ifneeded[2]{%
987   \AMC@if@separate@question{%
988     \AMC@mem@next%
989     \AMC@mem@category{#2}%
990     \AMC@mem@add{#1}%
991   }%
992 }
993 \newcommand\AMC@mem@answer[1]{%
994   \addtocounter{AMC@ncase}{1}%
995   \AMC@if@separate@question{%
996     \AMC@mem@aid{\the\AMCrep@count}%
997     \AMC@mem@add{\AMCformAnswerA{#1}}%
998   }%
999 }
1000 \newcommand\AMC@mem@openQuestion{%
1001   \AMC@if@separate@question{%
1002     \AMC@mem@next%
1003     \AMC@mem@qidaffname{\the\AMCid@quest}{\arabic{AMCquestionaff}}{\AMCid@name}%

```

```

1004 \AMC@mem@add{\AMCformQuestionA}%
1005 }%
1006 }
1007 \def\AMCformBegin{%
1008 \AMC@zoneformulairetrue\setcounter{section}{0}%
1009 \ifAMC@ensemble\ifAMC@automarks\pagestyle{AMCpageFull}\fi\fi%
1010 }
1011 \newcommand\AMCform{%
1012 \ifAMC@ensemble\AMCformulaire@dedanstrue%
1013 \AMC@mem@show%
1014 \fi}
1015 \newcommand\AMCformFilter[1]{%
1016 \ifAMC@ensemble\AMCformulaire@dedanstrue%
1017 \AMC@mem@show@filter{#1}%
1018 \fi}
1019 \newif\ifAMC@keepmemory
1020 \newcommand\AMCformS{%
1021 \ifAMC@ensemble\AMCformulaire@dedanstrue%
1022 \AMCmessage{BR=0}\AMC@mem@show%
1023 \global\AMC@keepmemorytrue%
1024 \fi}

```

`\AMCtableForm` `\AMCtableForm[<options>]` is a variant of `\AMCform` that displays the boxes as a multi-column table.

The argument *<options>* is a key-value list, where:

- `nanswers=<n>` gives the number of answers that are labeled in the table (defaults to the maximal number of answers of the subject).
- `ncols=<n>` gives the number of columns to use (defaults to the largest possible number of columns).
- `idtext=<text>` gives a text to be inserted before each question number.
- `idtitle=<text>` gives a text to be used as a column title for question numbers.
- `columnsep=<dim>` and `columnseprule=<dim>` are passed to the `multicols` environment.
- `headers=<bool>` tells if the headers with boxes letters are to be added at the top of the columns (defaults to true).
- `inside=<bool>` tells if letters are to be written inside the boxes (defaults to false).

```

1025 \newcounter{AMC@specs}
1026 \def\AMC@formspecs#1{%
1027 \noindent\hbox to \AMCformTH{\hspace*{\fill}\textbf{\AMC@tf{idtitle}}\hspace{\AMCformHSpace}}%
1028 \setcounter{AMC@specs}{0}%
1029 \loop%
1030 \addtocounter{AMC@specs}{1}%
1031 \AMCformAnswer{\bf\AMCchoiceLabel{AMC@specs}}%
1032 \ifnum\value{AMC@specs}<#1\repeat%
1033 }
1034 \newcount\AMC@coli
1035 \def\AMC@formcolspecs#1#2{%
1036 \columnseprule=0pt%

```

```

1037 \begin{multicols}{#1}
1038 \AMC@coli=\z@%
1039 \@whilenum\AMC@coli<#1\do{
1040   \advance\AMC@coli\@ne%
1041   \AMC@formspecs{#2}\par
1042 }
1043 \end{multicols}
1044 }}
1045 \newcount\AMC@tf@ncols
1046 \newdimen\AMCformTH
1047 \newdimen\AMC@tf@colw
1048 \newdimen\AMC@tf@faw
1049 \def\AMC@tf@idtext{}
1050 \def\AMC@tf@idtitle{}
1051 \newbox\AMC@tf@box
1052 \define@key{AMCtf}{nanswers}[0]{\def\AMC@tf@nanswers{#1}}
1053 \define@key{AMCtf}{ncols}[0]{\AMC@tf@ncols=#1}
1054 \define@key{AMCtf}{idtext}{\def\AMC@tf@idtext{#1}}
1055 \define@key{AMCtf}{idtitle}{\def\AMC@tf@idtitle{#1}}
1056 \define@key{AMCtf}{idwidth}[Opt]{\AMCformTH=#1}
1057 \define@key{AMCtf}{columnsep}[0.5em]{\columnsep=#1}
1058 \define@key{AMCtf}{columnseprule}[0.5pt]{\columnseprule=#1}
1059 \define@boolkey{AMCtf}{headers}[true]{}
1060 \define@boolkey{AMCtf}{inside}[false]{}
1061 \setkeys{AMCtf}{nanswers,ncols,idwidth,headers,inside}
1062 \newcommand\AMCtableForm[1][{}]{%
1063   \setkeys{AMCtf}{columnsep,columnseprule}
1064   \setkeys{AMCtf}{#1}%
1065   \ifnum\AMC@tf@nanswers=0%
1066     \def\AMC@tf@nanswers{\the\AMCrep@nnmax}%
1067   \fi%
1068   \newdimen\AMC@tf@colW\AMC@tf@colW=\AMCformHSpace%
1069   \advance\AMC@tf@colW by \AMC@boxedwidth%
1070   \def\AMCformBeforeQuestion{\vspace{\AMCformVSpace}\par}%
1071   \def\AMCformQuestion##1{\noindent\hbox to \AMCformTH{\hspace*{\fill}\textbf{\AMC@tf@idtext{##1}}\hspace*{\fill}}}%
1072   \def\AMCformAnswer##1{\hbox to \AMC@tf@colW{\hspace*{\fill}##1\hspace*{\fill}}}%
1073   \ifnum\AMCformTH=0%
1074     \setbox\AMC@tf@box=\hbox{\textbf{\AMC@tf@idtext{999}}}%
1075     \AMCformTH=\wd\AMC@tf@box%
1076   \fi%
1077   \ifnum\AMC@tf@ncols=0%
1078     \AMC@tf@colw=\AMC@tf@nanswers\AMC@tf@colW%
1079     \advance\AMC@tf@colw by \AMCformTH%
1080     \advance\AMC@tf@colw by \columnsep%
1081     \AMC@tf@faw=\linewidth%
1082     \loop%
1083       \ifnum\AMC@tf@faw>\AMC@tf@colw%
1084         \advance\AMC@tf@faw by -\AMC@tf@colw%
1085         \advance\AMC@tf@ncols\@ne%
1086       \repeat%
1087   \fi%
1088   \ifKV@AMCtf@headers%
1089     \AMC@formcolspecs{\the\AMC@tf@ncols}{\AMC@tf@nanswers}%

```

```

1090 \vspace{\AMCformVSpace}\vspace{-2\multicolsep}
1091 \fi%
1092 {\raggedcolumns
1093 \begin{multicols}{\the\AMC@tf@ncols}
1094 \ifKV@AMCtf@inside\else\def\AMCchoiceLabel##1{}\fi%
1095 \AMCform
1096 \end{multicols}}
1097 }

```

`\AMCsection` and `\AMCsubsection` The `\AMCsection` and `\AMCsubsection` commands issue their standard counterparts (`\section` and `\subsection` with the same argument, both in the subject *and* in the separate answer sheet.

```

1098 \newcommand{\AMCsectionNumbered}[1]{%
1099 \section{#1}\AMC@mem@addsingle@ifneeded{\section{#1}}{section}}
1100 \newcommand{\AMCsubsectionNumbered}[1]{%
1101 \subsection{#1}\AMC@mem@addsingle@ifneeded{\subsection{#1}}{subsection}}
1102 \newcommand{\AMCsectionStar}[1]{%
1103 \section*{#1}\AMC@mem@addsingle@ifneeded{\section*{#1}}{section}}
1104 \newcommand{\AMCsubsectionStar}[1]{%
1105 \subsection*{#1}\AMC@mem@addsingle@ifneeded{\subsection*{#1}}{subsection}}
1106 \def\AMCsection{\@ifstar\AMCsectionStar\AMCsectionNumbered}
1107 \def\AMCsubsection{\@ifstar\AMCsubsectionStar\AMCsubsectionNumbered}

```

4.11.3 Formatting answers

`choices` (*env.*) Answers have to be included in an environment `choices` (standard), `choiceshoriz` (answers on one line) or `choicescustom` (user defined) depending on the desired formatting.

`choicescustom` (*env.*) Use `\AMCBoxedAnswers` to request all answers to be included in L^AT_EX boxes; this can be useful for example when using multicolumn answers formatting.

```

tikz-multi (env.) 1108 \def\AMCBoxedAnswers{\AMC@rbloctrue}
\AMCBoxedAnswers 1109 \newcommand{\start@Answers}{%
1110 \global\AMCrep@count=\z@%
1111 \global\AMCrep@nn=\z@%
1112 }
1113 \newenvironment{choices}[1][r]{%
1114 \def\une@rep{\AMCrep@itemize}%
1115 \ifAMC@rbloc\def\une@rep{\AMCrep@bloc}%
1116 \else\begin{itemize}\setlength{\itemsep}{\AMCinterIrep}\fi%
1117 \AMCrep@init{#1}}%
1118 {\AMC@fin@rep\ifAMC@rbloc\else\end{itemize}\fi}
1119 \newenvironment{choiceshoriz}[1][r]{%
1120 \def\une@rep{\AMCrep@ligne}\AMCrep@init{#1}%
1121 \par\begin{center}}%
1122 {\AMC@fin@rep\end{center}}
1123 \newenvironment{choicescustom}[1][r]{%
1124 \def\une@rep{\AMCrep@perso}\AMCrep@init{#1}%
1125 \AMCbeginAnswer\ignorespaces}%
1126 {\AMC@fin@rep\AMCendAnswer}
1127 \newenvironment{tikz-single}[1][r]{
1128 \def\une@rep{\AMCrep@tikz}\AMCrep@init{#1}%
1129 \begin{tikzpicture}}{\AMC@fin@rep\end{tikzpicture}}
1130 \newenvironment{tikz-multi}[1][r]{
1131 \def\une@rep{\AMCrep@tikzmat}\AMCrep@init{#1}%
1132 \begin{tikzpicture}[remember picture]}{\AMC@fin@rep\end{tikzpicture}}

```

`\AMCrep@bloc` For each of these styles, a corresponding `\AMCrep@xxx{⟨box⟩}{⟨text⟩}` is defined, which will
`\AMCrep@tikz` format the answer with a box given in `⟨box⟩` and text `⟨text⟩`. `\AMCrep@bloc` is also defined and
`\AMCrep@tikzmat` used in standard formatting when the user wants to put answers inside a L^AT_EX box.
`\AMCrep@itemize` 1133 `\newcommand\AMCrep@bloc[2]{\AMC@mem@answer{#1}%`
`\AMCrep@ligne` 1134 `\par%`
`\AMCrep@perso` 1135 `\ifAMC@textPos\ vbox\bgroup\AMC@tracepos{1}{atext:\AMCid@name:\the\AMCid@quest,\the\AMCrep@count}\hbox%`
1136 `\noindent\begin{minipage}{\linewidth}%`
1137 `\begin{itemize}\item{#1} #2\end{itemize}\end{minipage}%`
1138 `\ifAMC@textPos\AMC@tracepos{1}{atext:\AMCid@name:\the\AMCid@quest,\the\AMCrep@count}\egroup\AMC@tra`
1139 `\vspace{\AMCinterBrep}}`
1140 `\newcommand\AMCrep@tikz[5]{\AMC@mem@answer{#1}\node[#4] (lab\thecsvrow) at (#3) {#2} node[#5] (box\the`
1141 `\newcommand\AMCrep@tikzmat[5]{\AMC@mem@answer{#1}\node[#5] (box\thecsvrow) at (#3) {#1} node[#4] (lab\th`
1142 `\newcommand\AMCrep@itemize[2]{\AMC@mem@answer{#1}\item{#1} #2}`
1143 `\newlength\AMChorizAnswerSep`
1144 `\setlength{\AMChorizAnswerSep}{3em plus 4em}`
1145 `\newlength\AMChorizBoxSep`
1146 `\setlength{\AMChorizBoxSep}{1em}`
1147 `\newcommand\AMCrep@ligne[2]{\AMC@mem@answer{#1}%`
1148 `\ifAMC@textPos%`
1149 `\mbox{\AMC@tracebox{1}{atext:\AMCid@name:\the\AMCid@quest,\the\AMCrep@count}{#1}\hspace*{\AMChorizBoxSe`
1150 `\else%`
1151 `\mbox{#1}\hspace*{\AMChorizBoxSep}#2}%`
1152 `\fi\hspace{\AMChorizAnswerSep}}`
1153 `\newcommand\AMCrep@perso[2]{\AMC@mem@answer{#1}\AMCanswer{#1}{#2}}`

`\AMCbeginAnswer` The custom style will use user-defined commands to format answers: `\AMCbeginAnswer` is called
`\AMCendAnswer` once before answers, `\AMCanswer{⟨box⟩}{⟨text⟩}` is called for each answer (`⟨box⟩` being the box
`\AMCanswer` to be ticked and `⟨text⟩` the text associated with the proposed answer), and `\AMCendAnswer` is
called after all answers.
1154 `\def\AMCbeginAnswer{}`
1155 `\def\AMCanswer#1#2{#1 #2}`
1156 `\def\AMCendAnswer{}`

`\answer` The commands `\correctchoice` and `\wrongchoice` are used inside `choices`-like environments
`\correctchoice` to give the proposed answers and specify if they are to be ticked by the students or not.
`\wrongchoice` 1157 `\newcommand{\next@Answer}{%`
1158 `\global\advance\AMCrep@count\@ne\relax%`
1159 `\global\advance\AMCrep@nn\@ne\relax%`
1160 `\ifnum\AMCrep@nn>\AMCrep@nnmax%`
1161 `\global\AMCrep@nnmax=\AMCrep@nn%`
1162 `\fi%`
1163 `}`
1164 `\newcommand{\correctchoice}[2] []{%`
1165 `\next@Answer%`
1166 `\ifAMC@calibration\AMCmessage{REP=\the\AMCrep@count:B}\fi%`
1167 `\global\AMCune@bonnettrue%`
1168 `\AMCload@@reponse{\une@rep{\ifAMC@correc\AMC@box{#1}{\AMC@checkedbox}}%`
1169 `\else\AMC@box{#1}{\fi}{#2}}{\the\AMCrep@count}\ignorespaces}`
1170 `\newcommand{\wrongchoice}[2] []{%`
1171 `\next@Answer%`
1172 `\ifAMC@calibration\AMCmessage{REP=\the\AMCrep@count:M}\fi%`
1173 `\AMCload@@reponse{\une@rep{\AMC@box{#1}{\fi}{#2}}{\the\AMCrep@count}}%`
1174 `\ignorespaces}`

4.11.4 Score zones

`\AMCscoreZone` The position of the scores on the annotated answer sheets can be defined in the L^AT_EX source file using `\AMCsetScoreZone{<options>}` (or `\AMCsetScoreZoneAnswerSheet{<options>}` for the answer sheets when the separate answer sheet option is used).

First begin with some helpers: `\AMCemptybox{<width>}{<height>}{<depth>}` draws an empty box with specified dimensions, and `\AMCmarginNote{<note>}` (code from one of `sgmoye`'s comments on `tex.stackexchange.com`) prints a marginal note in the left or right margin, depending on current the position (usefull in `multicols` environment).

```

1175 \newcommand{\AMCemptybox}[3]{%
1176   \sbox0{} \wd0=#1\ht0=#2\dp0=#3\relax\box0}%
1177 \newlength\AMC@mn@test
1178 \newlength\AMC@mn@sep\AMC@mn@sep=4mm
1179 \newlength\AMC@mn@leftmargin
1180 \newlength\AMC@mn@rightmargin
1181 \newcommand\AMCmarginNote[1]{%
1182   \begin{tikzpicture}[remember picture,overlay]%
1183     \coordinate (here) at (0,0);%
1184     \pgfextractx{\AMC@mn@test}{\pgfpointdiff{\pgfpointorigin}%
1185       {\pgfpointanchor{current page}{center}}}%
1186     \ifodd\thepage%
1187       \AMC@mn@leftmargin=\oddsidemargin%
1188       \AMC@mn@rightmargin=\evensidemargin%
1189     \else
1190       \AMC@mn@leftmargin=\evensidemargin%
1191       \AMC@mn@rightmargin=\oddsidemargin%
1192     \fi
1193     \ifdim\AMC@mn@test < 1cm%
1194       \draw (current page.east |- here)+(-\AMC@mn@rightmargin-1in+\AMC@mn@sep,0pt) node[anchor=text,align=right]{#1}%
1195     \else%
1196       \draw (current page.west |- here)+(0cm,0pt) node[anchor=text,align=right,text width=\AMC@mn@leftmargin]{#1}%
1197     \fi%
1198   \end{tikzpicture}%
1199 }
```

Define now different ways to place the score zone:

`none` nowhere

`question` right after the question heading

`margin` in the margin, using `marginpar` (this does not work with `multicols` environment)

`margins` in the left or right margin, depending on the current position (needs `tikz` package)

```

1200 \newcommand{\AMC@sz@box}{\AMCemptybox{\AMC@sz@width}{\AMC@sz@height}{\AMC@sz@depth}}
1201 %
1202 \newcommand{\AMC@sz@callin@question}{\AMCscoreZone{\AMC@sz@box}}
1203 %
1204 \newcommand{\AMC@sz@callout@margin}{\hspace{0pt}\marginpar{\AMCscoreZone{\AMC@sz@box}}}
1205 %
1206 \newcommand{\AMC@sz@init@margins}{\PackageWarning{automultiplechoice}{Please run twice to get proper margins}}
1207 \newcommand{\AMC@sz@callout@margins}{\hspace{0pt}\AMCmarginNote{\AMCscoreZone{\AMC@sz@box}}}
```

Let us now set up options handling.

```

1208 \newlength\AMC@sz@width
1209 \newlength\AMC@sz@height
1210 \newlength\AMC@sz@depth
1211 \def\AMC@sz@callout{}
1212 \def\AMC@sz@callin{}
1213 \define@key{AMCsz}{width}{\AMC@sz@width=#1}
1214 \define@key{AMCsz}{height}{\AMC@sz@height=#1}
1215 \define@key{AMCsz}{depth}{\AMC@sz@depth=#1}
1216 \define@key{AMCsz}{calloutside}{\def\AMC@sz@callout{#1}}
1217 \define@key{AMCsz}{callinside}{\def\AMC@sz@callin{#1}}
1218 \define@choicekey{AMCsz}{position}{none,question,margin,margins}{%
1219   \ifcsname AMC@sz@callout@#1\endcsname%
1220     \def\AMC@sz@callout{AMC@sz@callout@#1}%
1221   \else%
1222     \def\AMC@sz@callout{}%
1223   \fi%
1224   \ifcsname AMC@sz@callin@#1\endcsname%
1225     \def\AMC@sz@callin{AMC@sz@callin@#1}%
1226   \else%
1227     \def\AMC@sz@callin{}%
1228   \fi%
1229   \ifcsname AMC@sz@init@#1\endcsname%
1230     \csname AMC@sz@init@#1\endcsname%
1231   \fi%
1232 }
1233 \newcommand{\AMCsetScoreZone}[1]{\setkeys{AMCsz}{#1}}
1234 \AMCsetScoreZone{width=1.5em,height=1.5ex,depth=.5ex,position=none}

```

And do the same for \AMCsetScoreZoneAnswerSheet...

```

1235 \newcommand{\AMC@sza@box}{\AMCemptybox{\AMC@sza@width}{\AMC@sza@height}{\AMC@sza@depth}}
1236 %
1237 \newcommand{\AMC@sza@init@none}{}
1238 \newcommand{\AMC@sza@callout@none}{}
1239 \newcommand{\AMC@sza@callin@none}{}
1240 %
1241 \newcommand{\AMC@sza@init@question}{}
1242 \newcommand{\AMC@sza@callout@question}{}
1243 \newcommand{\AMC@sza@callin@question}{\AMCscoreZone{\AMC@sza@box}}
1244 %
1245 \newcommand{\AMC@sza@init@margin}{}
1246 \newcommand{\AMC@sza@callout@margin}{\hspace{Opt}\marginpar{\AMCscoreZone{\AMC@sza@box}}}
1247 \newcommand{\AMC@sza@callin@margin}{}
1248 %
1249 \newcommand{\AMC@sza@init@margins}{\PackageWarning{automultiplechoice}{Please run twice to get proper ma}}
1250 \newcommand{\AMC@sza@callout@margins}{\hspace{Opt}\AMCmarginNote{\AMCscoreZone{\AMC@sza@box}}}
1251 \newcommand{\AMC@sza@callin@margins}{}
1252 %
1253 \newlength\AMC@sza@width
1254 \newlength\AMC@sza@height
1255 \newlength\AMC@sza@depth
1256 \def\AMC@sza@callout{}
1257 \def\AMC@sza@callin{}

```

```

1258 \define@key{AMCsza}{width}{\AMC@sza@width=#1}
1259 \define@key{AMCsza}{height}{\AMC@sza@height=#1}
1260 \define@key{AMCsza}{depth}{\AMC@sza@depth=#1}
1261 \define@key{AMCsza}{calloutsideside}{\def\AMC@sza@callout{#1}}
1262 \define@key{AMCsza}{callinsideside}{\def\AMC@sza@callin{#1}}
1263 \define@choicekey{AMCsza}{position}{none,question,margin,margins}{%
1264   \ifcsname AMC@sza@callout@#1\endcsname%
1265     \def\AMC@sza@callout{AMC@sza@callout@#1}%
1266   \else%
1267     \def\AMC@sza@callout{}%
1268   \fi%
1269   \ifcsname AMC@sza@callin@#1\endcsname%
1270     \def\AMC@sza@callin{AMC@sza@callin@#1}%
1271   \else%
1272     \def\AMC@sza@callin{}%
1273   \fi%
1274   \ifcsname AMC@sza@init@#1\endcsname%
1275     \csname AMC@sza@init@#1\endcsname%
1276   \fi%
1277 }
1278 \newcommand{\AMCsetScoreZoneAnswerSheet}[1]{\setkeys{AMCsza}{#1}}
1279 \AMCsetScoreZoneAnswerSheet{width=1.5em,height=1.5ex,depth=.5ex,position=none}
1280 \newcommand{\AMCnoScoreZone}{\AMCsetScoreZone{position=none}\AMCsetScoreZoneAnswerSheet{position=none}}

```

4.11.5 Formatting questions

`\AMCquestionaff` The counter `\AMCquestionaff` keeps track of the current question number. It can be redefined by the user, for example to print several questions without a number, and then print questions with a number starting at one.

`\AMC@stepQuestion` will increase this counter and `\AMC@qaff` will format the question number out.

```

1281 \newcounter{AMCquestionaff}
1282 \newcommand{\AMCnumero}[1]{\setcounter{AMCquestionaff}{#1}\addtocounter{AMCquestionaff}{-1}}
1283 \AtBeginDocument{%
1284   \ifx\@skiphyperreftrue\@undefined%
1285     \expandafter\newif\csname if@skiphyperref\endcsname%
1286   \fi%
1287 }
1288 \newcommand\AMC@stepQuestion{\ifAMCquestionNumber\@skiphyperreftrue\refstepcounter{AMCquestionaff}\@skip
1289 \newcommand\AMC@qaff{\arabic{AMCquestionaff}}

```

`\AMCbeforeQuestion` The command `\AMCbeforeQuestion` opens a new question. The command `\AMCbeginQuestion{<n>}{<sign>}` will format the question header, where `<n>` is the question number and `<sign>` being `\multiSymbole` in case of a multiple question, and empty in case of a simple one. `\AMCbeforeQuestion`, `\AMCbeginQuestion` and `\multiSymbole` can be user-redifined.

```

1290 \def\AMCbeforeQuestion{\ifAMC@qbloc\else\par\noindent\fi}
1291 \def\AMCbeginQuestion#1#2{\noindent\AMC@loc@q{#1}{#2}%
1292   \ifx\@empty\AMC@sz@callin\@empty\hspace*{1em}\fi%
1293 }
1294 \def\multiSymbole{$\clubsuit$}

```

`question (env.)` Environment `{question}{<key>}` encloses a simple question (with one and only one correct choice) with associated unique key `<key>` and the proposed answers.

`questionmult (env.)`

`variable-single (env.)`

`variable-multi (env.)`

`questionouverte (env.)`

`\ouverte@vs`

Environment `{questionmult}{\langle key \rangle}` is the same for multiple questions (with none, one or several correct choices).

Environment `{questionmultx}{\langle key \rangle}` is the same as `questionmult`, but with no use of `\multiSymbole`.

Environment `{questionouverte}[\langle width \rangle]` is used for open questions (that won't be marked automatically!), with width given as an optional argument (defaults to 3 cm).

The command `\AMCexternalQuestion{\langle id \rangle}{\langle maxscore \rangle}` allows to declare a question that will be scored outside AMC, with a maximal score $\langle maxscore \rangle$. When you use this command, you can manage the question number and question text freely (AMC won't handle this).

```

1295 \ifx\question\undefined\else\let\question\undefined\fi
1296 \def\AMCnobloc{\AMC@qblocfalse}
1297 \def\AMCbloc{\AMC@qbloctrue}
1298 \newcommand\AMCstartWithQuestion[1]{%
1299   \global\def\AMCid@name{#1}\AMC@affecte{#1}{\AMCid@quest}%
1300   \ifAMC@calibration%
1301     \AMCmessage{Q=\the\AMCid@quest}%
1302     \immediate\write\AMC@XYFILE{\string\question{\the\AMCid@quest}{\AMCid@name}}%
1303   \fi%
1304   \start@Answers%
1305 }
1306 \newcommand\AMCexternalQuestion[2]{%
1307   \AMCstartWithQuestion{#1}%
1308   \ifAMC@calibration%
1309     \AMCmessage{B=MAX=#2}%
1310     \AMCmessage{MULT}%
1311     \AMCmessage{FQ}%
1312   \fi%
1313 }
1314 \newenvironment{question}[2][{}]{%
1315   \def\AMCcurrentenv{question}%
1316   \AMC@stepQuestion%
1317   \AMCstartWithQuestion{#2}%
1318   \AMCbeforeQuestion%
1319   \ifx\@empty\AMC@sz@callout\@empty\else%
1320     \csname\AMC@sz@callout\endcsname%
1321   \fi%
1322   \AMCtype@multifalse\ifAMC@qbloc\ifAMC@textPos\ vbox\ bgroup\AMC@tracemos{1}{qtext:#2:\the\AMCid@quest,0}
1323   \ifAMC@affichekeys\index{\texttt{#2}}\ifAMC@keyline[\texttt{#2}]\newline\fi\fi%
1324   \AMCbeginQuestion{\ifAMC@affichekeys\ifAMC@ensemble\AMC@qaff\ \fi\ifAMC@keyline\else[\texttt{#2}]\fi}
1325   \ifAMC@calibration\immediate\write\AMC@XYFILE{\string\questionnum{\the\AMCid@etud}{\the\AMCid@quest}{\the\AMCid@score}}
1326   \ifx\@empty\AMC@sz@callin\@empty\else%
1327     \csname\AMC@sz@callin\endcsname%
1328   \fi%
1329   \AMCformulaire@dedansfalse\setcounter{AMC@ncase}{0}%
1330   \AMC@mem@openQuestion}%
1331 {\ifAMC@qbloc\end{minipage}\ifAMC@textPos\AMC@tracemos{1}{qtext:\AMCid@name:\the\AMCid@quest,0}\egroup\AMC@tracemos{2}{a}}
1332 \newenvironment{questionmult}[1]{%
1333   \AMC@un@bonnefalse\begin{question}[{\multiSymbole}]{#1}%
1334   \AMCtype@multitrue\ifAMC@calibration%
1335     \AMCmessage{MULT}\fi%
1336 }{\end{question}}
1337 \newif\ifSurveySingleAnswer\SurveySingleAnswerfalse

```

```

1338 \newenvironment{variable-single}[2]
1339 {\def\AMCbeginQuestion##1##2{}
1340 \begin{question}{#1}\scoring{v=#2}\QuestionIndicative\ifSurveySingleAnswer\else\AMCmessage{MULT}\fi
1341 \begin{tikz-single}[o]}
1342 {\end{tikz-single}
1343 \end{question}}
1344 \newenvironment{variable-multi}[4]
1345 {\def\AMCbeginQuestion##1##2{}
1346 \begin{question}{#1}\scoring{v=#4}\QuestionIndicative\ifSurveySingleAnswer\else\AMCmessage{MULT}\fi
1347 \begin{tikz-multi}[o]
1348 \node[#3] (var) at (0,0) {#2};}
1349 {\end{tikz-multi}
1350 \end{question}}
1351 \newenvironment{questionmultx}[1]{%
1352 \begingroup\def\multiSymbole{}\begin{questionmult}{#1}}%
1353 {\end{questionmult}\endgroup}
1354 \newdimen\ouverte@vs
1355 \newenvironment{questionouverte}[1][3cm]{%
1356 \AMC@stepQuestion%
1357 \AMCtype@multifalse\ouverte@vs=#1%
1358 \ifAMC@qbloc\noindent\begin{minipage}{\linewidth}\fi%
1359 \AMCbeginQuestion{\AMC@qaff}{}}%
1360 {\vspace*{\ouverte@vs}\ifAMC@qbloc\end{minipage}\vspace{3ex}\fi}

```

4.11.6 Explanations

`\explain` The command `\explain{<text>}` is used inside question-like environments to give the explanation for the answers of a question. The command `\explaincontext{<text>}` inserts its argument only in the corrected paper.

```

1361 \newcommand{\explain}[1]{%
1362 \ifAMC@correc%
1363 \AMCif@env{question}{\par\noindent\AMC@loc@explain #1}{\AMC@error@explain}\vspace{1ex}%
1364 \else%
1365 \AMCif@env{question}{}{\AMC@error@explain}%
1366 \fi%
1367 }
1368 \newcommand{\explaincontext}[1]{%
1369 \ifAMC@correc%
1370 #1%
1371 \fi%
1372 }

```

4.12 Scoring

`\scoring` Scoring strategies are simply transmitted to the `.amc` file for later analysis.

`\scoringDefaultS` `\scoring{<score>}` details the scoring strategy for current question or current answer, `\scoringDefaultM` `\scoringDefaultS{<score>}` and `\scoringDefaultM{<score>}` gives default scoring strategy for simple and multiple questions, and `\QuestionIndicative` tells that the current question is not to be taken into account in the global mark.

```

1373 \def\scoring#1{\ifAMC@calibration\AMCmessage{B=#1}\fi\ignorespaces}
1374 \def\scoringDefaultS#1{\ifAMC@calibration\AMCmessage{BDS=#1}\fi}
1375 \def\scoringDefaultM#1{\ifAMC@calibration\AMCmessage{BDM=#1}\fi}

```

```
1376 \def\QuestionIndicative{\ifAMC@calibration\AMCmessage{INDIC}\fi}
```

4.13 Numerical data

4.13.1 Codes

`\AMCcodeGrid` Students can code some numerical information (such as student number) through special questions, which can be formatted easily with the command `\AMCcodeGrid[⟨opts⟩]{⟨key⟩}{⟨descr⟩}`, where `⟨key⟩` is a key prefix and `⟨descr⟩` is a coma-separated list of character pools to offer. The characters entered by the student will be available through the questions `⟨key⟩[1], …, ⟨key⟩[⟨length(descr)⟩]`.

As an example,

`\AMCcodeGrid{code}{ABCD,012345,012345,012345,012345}` produces the opposite boxes (two results are show here: without or with `separateanswersheet` option), and trace positions of all the boxes in the .xy file with the `code` identifier: the first digit is represented by question with key `code[6]`, the second by question with key `code[5]`, and so on.

Positions of the boxes are logged in the .xy file, as shown in section 5.3 for the first set of boxes (without `separateanswersheet`, with digits outside boxes).

	0		0		0		0
	1		1		1		1
A	2		2		2		2
B	3		3		3		3
C	4		4		4		4
D	5		5		5		5

0	0	0	0
1	1	1	1
A	2	2	2
B	3	3	3
C	4	4	4
D	5	5	5

The “horizontal” version can also be considered using option `h`, especially with a small number of digits. See opposite for the result of

`\AMCcodeGrid[h]{code}{ABCDEF,0123456789,0123456789}`.

The `\AMCcodeGridInt[⟨opts⟩]{⟨key⟩}{⟨n⟩}` is a shortcut for calling `\AMCcodeGrid` with `⟨n⟩` digits from 0 to 9. This allows to create grids for `⟨n⟩`-digits integers easily.

These two commands supports the following options (given as a comma-separated list optional argument `⟨opts⟩`):

- `vertical=true` or `false` to indicate the direction to be used (default is `true`);
- `h` is a shortcut for `vertical=false`;
- `v` is a shortcut for `vertical=true`;
- `top` to request top-aligned columns in vertical direction.
- `multi` for codes that are repeated on each page.

```
1377 \newcount\AMC@chiffres
1378 \newdimen\AMCcodeHspace\AMCcodeHspace=.5em
1379 \newdimen\AMCcodeVspace\AMCcodeVspace=.5em
1380 \newcommand\AMCcodeID@squarebrackets[2]{#1[#2]}
1381 \newcommand\AMCcodeID@dot[2]{#1.#2}
1382 \newcommand\AMCcodeID@@[1]{%
1383 \expandafter\def\expandafter\AMCcodeID\expandafter{\csname AMCcodeID@#1\endcsname}%
```

```

1384 \def\AMCcodeID@mode{#1}%
1385 }
1386 \AMCcodeID@@{squarebrackets}
1387 \ExplSyntaxOn
1388
1389 \clist_new:N \amc_code_descr_clist
1390 \seq_new:N \amc_code_digits_seq
1391 \int_new:N \amc_code_digit_n_int
1392 \bool_new:N \amc_code_vertical_bool
1393 \bool_new:N \amc_code_top_bool
1394 \bool_new:N \amc_code_multi_bool
1395 \clist_new:N \amc__multi_clist
1396
1397 \cs_new:Npn \amc_code_init:N #1 {
1398   \def\AMCbeginQuestion##1##2{}
1399   \def\AMCbeforeQuestion{}
1400   \AMCnoScoreZone
1401   \AMCquestionNumberfalse
1402   \setlength{\parindent}{0pt}
1403   \AMCnobloc
1404   \int_set:Nn \amc_code_digit_n_int { \clist_count:N #1 }
1405 }
1406
1407 \cs_new:Nn \amc_code_digit_init: {
1408   \QuestionIndicative
1409   \global\AMCrep@count=\z@
1410 }
1411
1412 \cs_new:Npn \amc_code_digit:n #1 {
1413   \global\advance\AMCrep@count\@ne\relax
1414   \ifAMC@calibration\AMCmessage{ REP = \the\AMCrep@count : M }\fi
1415   \hbox{\AMC@keyBox@{#1}{1}{case : \AMCid@name : \the\AMCid@quest , \the\AMCrep@count}}
1416   \bool_if:NTF \amc_code_vertical_bool {
1417     \vspace{\AMCcodeVspace}
1418   }{
1419     \hspace{\AMCcodeHspace}
1420   }
1421 }
1422
1423 \keys_define:nn { amccode } {
1424   vertical .bool_set:N = \amc_code_vertical_bool,
1425   vertical .initial:n = { true },
1426   vertical .default:n = { true },
1427   v .code:n = { \bool_set_true:N \amc_code_vertical_bool },
1428   h .code:n = { \bool_set_false:N \amc_code_vertical_bool },
1429   top .bool_set:N = \amc_code_top_bool,
1430   top .initial:n = { false },
1431   top .default:n = { true },
1432   multi .bool_set:N = \amc_code_multi_bool,
1433   multi .initial:n = { false },
1434   multi .default:n = { true }
1435 }
1436

```

```

1437 \cs_new_nopar:Nn \amc_multi_report: {
1438   \ifAMC@calibration
1439     \immediate\write\AMC@XYFILE{\string\with{multi=\clist_use:Nn\amc__multi_clist{,}}}
1440   \fi
1441 }
1442 \cs_new_eq:NN \AMC@multi@report \amc_multi_report:
1443 \int_new:N \amc_multi_count_int
1444 \cs_new_nopar:Nn \amc_multi_clear: {
1445   \int_gzero:N \amc_multi_count_int
1446 }
1447 \cs_new_eq:NN \AMC@multiclear \amc_multi_clear:
1448
1449 \cs_new:Npn \amc_code_generate:nNn #1#2#3 {
1450   { \keys_set:nn { amccode } { #3 }
1451     \bool_if:NTF \amc_code_multi_bool {
1452       \clist_gset:Nn \amc__multi_clist { #1 }
1453     } {}
1454     \bool_if:NTF \amc_code_multi_bool { \int_gincr:N \amc_multi_count_int } {}
1455     \amc_code_init:N #2
1456     \clist_map_inline:Nn #2 { % iterates over 'digits'
1457       \begin{question}{
1458         \AMCcodeID{ #1 } \bool_if:NTF
1459           \amc_code_multi_bool
1460           { * \int_use:N \amc_multi_count_int } {} }
1461         { \int_use:N \amc_code_digit_n_int }
1462       }
1463       \amc_code_digit_init:
1464       \seq_set_split:Nnn \amc_code_digits_seq {} { ##1 }
1465       \bool_if:NTF \amc_code_vertical_bool {
1466         \hspace{0pt}
1467         \bool_if:NTF \amc_code_top_bool { \vtop } { \vbox }
1468       } \bgroup
1469     }{
1470       \hbox\bgroup
1471     }
1472     \seq_map_inline:Nn \amc_code_digits_seq {
1473       % iterates over available characters for 'digit'
1474       \amc_code_digit:n { ####1 }
1475     }
1476     \bool_if:NTF \amc_code_vertical_bool {
1477       \vspace{-\AMCcodeVspace}\egroup
1478       \hspace{\AMCcodeHspace}
1479     }{
1480       \egroup\vspace{\AMCcodeVspace}
1481     } \par
1482   }
1483   \end{question}
1484   \int_decr:N \amc_code_digit_n_int
1485 }
1486 }
1487 }
1488
1489 \cs_new:Npn \amc_code_generate:nnn #1#2#3 {

```

```

1490 \clist_set:Nn \amc_code_descr_clist { #2 }
1491 \amc_code_generate:nNn { #1 } \amc_code_descr_clist { #3 }
1492 }
1493 \cs_generate_variant:Nn \amc_code_generate:nnn { xxx }
1494 \newcommand{\AMCcodeGrid}[3][[]]{
1495   \amc_code_generate:xxx { #2 } { #3 } { #1 }
1496 }
1497
1498 \cs_new:Npn \amc_code_generate_integer:nnn #1#2#3 {
1499   \clist_clear:N \amc_code_descr_clist
1500   \prg_replicate:nn { #2 } { \clist_put_right:Nn \amc_code_descr_clist { 0123456789 } }
1501   \amc_code_generate:nNn { #1 } \amc_code_descr_clist { #3 }
1502 }
1503 \cs_generate_variant:Nn \amc_code_generate_integer:nnn { xxx }
1504 \newcommand{\AMCcodeGridInt}[3][[]]{
1505   \amc_code_generate_integer:xxx { #2 } { #3 } { #1 }
1506 }
1507
1508 \cs_new:Npn \amc_code_generate_integer_v:nn #1#2 {
1509   \amc_code_generate_integer:nnn { #1 } { #2 } { v }
1510 }
1511 \cs_new:Npn \amc_code_generate_integer_h:nn #1#2 {
1512   \amc_code_generate_integer:nnn { #1 } { #2 } { h }
1513 }
1514 \cs_generate_variant:Nn \amc_code_generate_integer_v:nn { xx }
1515 \cs_generate_variant:Nn \amc_code_generate_integer_h:nn { xx }
1516 \cs_new_eq:NN \AMCcode \amc_code_generate_integer_v:xx
1517 \cs_new_eq:NN \AMCcodeH \amc_code_generate_integer_h:xx
1518
1519 \ExplSyntaxOff

```

4.13.2 Numerical questions

`\AMCnumericChoices` The command `\AMCnumericChoices{<correct>}{<options>}` can be used as a replacement for the `choices` environment when the questions asks for a numeric value to code on the answer sheet.

As an example,

```

\begin{question}{product}
  What is the value of  $7 \times 5$ ?
  \AMCnumericChoices{35}{digits=2,sign=false}
\end{question}

```

produces (in correction mode):

Question 11	What is the value of 7×5 ?
☐0 ☐1 ☐2 ☒3 ☐4 ☐5 ☐6 ☐7 ☐8 ☐9 ☐0 ☐1 ☐2 ☐3 ☐4 ☒5 ☐6 ☐7 ☐8 ☐9	

and these boxes are only shown on the separate answer sheet if the `separateanswersheet` option is used.

This command uses the `\AMCformatChoices{<showcommand>}{<hidecommand>}{<arg1>}{<arg2>}` command, that calls either `<hidecommand>{<arg1>}{<arg2>}` if the `separateanswersheet` option is used and if we are currently in the question part (not in the answer sheet), or `<showcommand>{<arg1>}{<arg2>}` when all the boxes are to be produced.

```

1520 \newcommand\AMCformatChoices[4]{%
1521   \global\AMCrep@count=\z@%
1522   \AMC@if@separate@question{%
1523     \AMC@mem@add{\global\AMCrep@count=\z@%
1524               #1{#3}{#4}}%
1525   }%
1526   \ifAMC@ensemble%
1527     #2{#3}{#4}%
1528     \AMCmessage{QPART}%
1529   \else%
1530     #1{#3}{#4}%
1531   \fi%
1532 }
```

Some computation commands are now defined. The command `\amc_fp_decompose:NNn{<fp var>}{<int var>}{<x>}` sets `<fp var>` to be the *mantissa* and `<int var>` the *exponent* of the floating point number `<x>`. For example, `\amc_fp_decompose:NNn\mant_fp\expo_int{123.456}` give the value 1.23456 to `\mant_fp` and 2 to `\expo_int` (because $123.456 = 1.23456 \times 10^2$).

The command `\amc_fp_to_digits:Nnn{<clist>}{<x>}{<n digits>}{<base>}` rounds the floating point number `<x>` and populates the comma separated list `<clist>` with its `<n digits>` digits in base `<base>`. An error is issued if `<x>` would have required more digits.

```

1533 \ExplSyntaxOn
1534
1535 \cs_generate_variant:Nn \tl_replace_once:Nnn { Nxn }
1536
1537 \tl_new:N \amc_ee_tl
1538 \seq_new:N \amc_ee_seq
```

Note that with some versions of `l3fp-convert` (prior to 2017-09-18), `\fp_to_scientific` leads to a ‘e’ with catcode 12 (*other*). We convert it to catcode *letter* before splitting.

```

1539 \group_begin:
1540 \char_set_catcode_other:N E
1541 \tex_lowercase:D
1542 {
1543   \cs_new:Npn \amc_read_scientific:NNn #1 #2 #3 {
1544     \tl_set:Nn \amc_ee_tl { #3 }
1545     \tl_replace_once:Nxn \amc_ee_tl { E } { e }
1546     \seq_set_split:NnV \amc_ee_seq e \amc_ee_tl
1547     \fp_set:Nn #1 { \seq_item:Nn \amc_ee_seq 1 }
1548     \int_set:Nn #2 { \seq_item:Nn \amc_ee_seq 2 }
1549   }
1550 }
1551 \group_end:
1552
1553 \cs_generate_variant:Nn \amc_read_scientific:NNn { NNf, NNx }
1554
1555 \fp_new:N \amc_fulls_fp
1556 \cs_new:Npn \amc_fp_decompose:NNn #1 #2 #3 {
1557   \fp_set:Nn \amc_fulls_fp { #3 }
```

Note that with some versions of 13fp-convert, the exponent part is omitted for some values, so that we add e 0.

```

1558 \amc_read_scientific:NNx #1 #2
1559 { \fp_to_scientific:N \amc_fulls_fp e 0 }
1560 }
1561 \cs_generate_variant:Nn \amc_fp_decompose:NNn { NNx }
1562
1563 \fp_new:N \amc_num_mantissa_fp
1564 \int_new:N \amc_num_exponent_int
1565 \cs_new:Npn \amc_fp_n_significant_digits:Nnn #1 #2 #3 {
1566   \amc_fp_decompose:NNn \amc_num_mantissa_fp \amc_num_exponent_int
1567   { #2 }
1568   \fp_set:Nn #1
1569   { round(\amc_num_mantissa_fp * 10^((#3)-1)) }
1570   \fp_compare:nTF { abs(#1) >= 10^(#3) }
1571   {
1572     \fp_set:Nn #1 { #1 / 10 }
1573   } { }
1574 }
1575
1576 \fp_new:N \amc_num_nsig_fp
1577 \cs_new:Npn \amc_fp_show_n_significant_digits:nn #1 #2 {
1578   \amc_fp_n_significant_digits:Nnn \amc_num_nsig_fp { #1 } { #2 }
1579 }
1580 \cs_new_eq:NN \AMCsignificantDigits \amc_fp_show_n_significant_digits:nn
1581
1582 \cs_new:Npn \amc_fp_show_significant_digits: {
1583   \fp_use:N \amc_num_nsig_fp
1584 }
1585 \cs_new_eq:NN \AMCshowSignificantDigits \amc_fp_show_significant_digits:
1586
1587 \cs_new:Npn \amc_fp_n_digits:Nnn #1 #2 #3 {
1588   \fp_set:Nn #1
1589   { round((#2) * \amc_num_base_int^(#3)) }
1590 }
1591
1592 \int_new:N \amc_todigits_int
1593 \cs_new:Npn \amc_fp_to_digits:Nnnn #1 #2 #3 #4 {
1594   \clist_clear:N #1
1595   \int_set:Nn \amc_todigits_int { \fp_eval:n { abs(round(#2)) } }
1596   \prg_replicate:nn { #3 } {
1597     \clist_put_left:Nx #1 { \int_mod:nn \amc_todigits_int { #4 } }
1598     \int_set:Nn \amc_todigits_int
1599     { \int_div_truncate:nn \amc_todigits_int { #4 } }
1600   }
1601   \int_compare:nNnTF \amc_todigits_int = 0 { } {
1602     \message{^^J!~Error:~number~too~large,
1603       ~some~digits~will~be~discarded^^J}
1604   }
1605 }
1606
1607 \cs_new:Npn \amc_invalid_digits:Nn #1 #2 {
1608   \clist_clear:N #1

```

```

1609 \prg_replicate:nn { #2 } { \clist_put_left:Nx #1 { -1 } }
1610 }
1611
1612 \cs_new:Npn \amc_get_fp_sign:Nn #1 #2 {
1613   \fp_compare:nNnTF #2 < 0 {
1614     \int_set:Nn #1 { -1 }
1615   }{
1616     \fp_compare:nNnTF #2 > 0 {
1617       \int_set:Nn #1 { 1 }
1618     }{
1619       \int_set:Nn #1 { 0 }
1620     }
1621   }
1622 }
1623
1624 \cs_new:Npn \amc_get_int_sign:Nn #1 #2 {
1625   \int_compare:nNnTF #2 < 0 {
1626     \int_set:Nn #1 { -1 }
1627   }{
1628     \int_compare:nNnTF #2 > 0 {
1629       \int_set:Nn #1 { 1 }
1630     }{
1631       \int_set:Nn #1 { 0 }
1632     }
1633   }
1634 }
1635
1636 \ExplSyntaxOff

```

The command `\AMCnumericShow{<value>}{<opts>}` is called to draw all necessary boxes to code a numerical value `<value>` with options given as a comma separated list `<opts>`. `\AMCnumericOpts{<opts>}` can be used to set some default values for these options.

Begin with the available options:

```

1637 \def\AMCnntextGoto{
1638 \def\AMCnntextVHead#1{\emph{b#1}}
1639 \newdimen\AMCnumeric@Hspace\AMCnumeric@Hspace=.5em
1640 \newdimen\AMCnumeric@Vspace\AMCnumeric@Vspace=1ex
1641 \ExplSyntaxOn
1642
1643 \keys_define:nn { amcnumeric } {
1644   Tsign .code:n = {\def\AMCnntextSign{#1}},
1645   Tsign .initial:n = {},
1646   Tpoint .code:n = {\def\AMCdecimalPoint{#1}},
1647   Tpoint .initial:n = { \raisebox{1ex}{\bf .} },
1648   Texponent .code:n = {\def\AMCexponent{#1}},
1649   Texponent .initial:n = { $\times 10^{\textasciicircum{#1}}$ },
1650   vspace .code:n = {\AMCnumeric@Vspace=#1},
1651   hspace .code:n = {\AMCnumeric@Hspace=#1},
1652   arraybordercol .code:n = {\def\AMCnarray@Border{#1}},
1653   arraybordercol .initial:n = { black ! 20 },
1654   arrayborderwidth .code:n = {\def\AMCnarray@BorderWidth{#1}},
1655   arrayborderwidth .initial:n = { .5mm },
1656   bordercol .code:n = {\def\AMCncol@Border{#1}},
1657   bordercol .initial:n = { lightgray },

```

```

1658 borderwidth .code:n = {\def\AMCncol@BorderWidth{#1}},
1659 borderwidth .initial:n = { 1mm },
1660 backgroundcol .code:n = {\def\AMCncol@Background{#1}},
1661 backgroundcol .initial:n = { white },
1662 digits .int_set:N = \amc_num_ndigits_int,
1663 digits .initial:n = { 3 },
1664 digitcols .int_set:N = \amc_num_digitcols_int,
1665 digitcols .initial:n = { 1 },
1666 decimals .int_set:N = \amc_num_decd_int,
1667 decimals .initial:n = { 0 },
1668 exponent .int_set:N = \amc_num_expo_int,
1669 exponent .initial:n = { 0 },
1670 base .int_set:N = \amc_num_base_int,
1671 base .initial:n = { 10 },
1672 sign .bool_set:N = \amc_num_sign_bool,
1673 sign .initial:n = { true },
1674 sign .default:n = { true },
1675 plussign .bool_set:N = \amc_num_plussign_bool,
1676 plussign .initial:n = { true },
1677 plussign .default:n = { true },
1678 exposign .bool_set:N = \amc_num_exposign_bool,
1679 exposign .initial:n = { true },
1680 exposign .default:n = { true },
1681 strict .bool_set:N = \amc_num_strict_bool,
1682 strict .initial:n = { false },
1683 strict .default:n = { true },
1684 scoring .bool_set:N = \amc_num_scoring_bool,
1685 scoring .initial:n = { true },
1686 scoring .default:n = { true },
1687 ignoreblank .bool_set:N = \amc_num_ignoreblank_bool,
1688 ignoreblank .initial:n = { false },
1689 ignoreblank .default:n = { true },
1690 vertical .bool_set:N = \amc_num_vertical_bool,
1691 vertical .initial:n = { false },
1692 vertical .default:n = { true },
1693 expovertical .bool_set:N = \amc_num_expoververtical_bool,
1694 expovertical .initial:n = { false },
1695 expovertical .default:n = { true },
1696 reverse .bool_set:N = \amc_num_reverse_bool,
1697 reverse .initial:n = { false },
1698 reverse .default:n = { true },
1699 vhead .bool_set:N = \amc_num_vhead_bool,
1700 vhead .initial:n = { false },
1701 vhead .default:n = { true },
1702 Tvhead .code:n = {\clist_set:Nx \amc_tvhead_clist {\clist_reverse:n {#1}}},
1703 Tvhead .initial:n = {}, % \c_empty_clist does not work with \clist_reverse:n
1704 vheadunitindex .int_set:N = \amc_vheadunitindex_int,
1705 vheadunitindex .initial:n = 0,
1706 nozero .bool_set:N = \amc_num_nozero_bool,
1707 nozero .initial:n = { false },
1708 nozero .default:n = { true },
1709 significant .bool_set:N = \amc_num_significant_bool,
1710 significant .initial:n = { false },

```

```

1711 significant .default:n = { true },
1712 scoreexact .code:n = {\def\AMC@numeric@scoreexact{#1}},
1713 scoreexact .initial:n = { 2 },
1714 scoreapprox .code:n = {\def\AMC@numeric@scoreapprox{#1}},
1715 scoreapprox .initial:n = { 1 },
1716 scorewrong .code:n = {\def\AMC@numeric@scorewrong{#1}},
1717 scorewrong .initial:n = { 0 },
1718 exact .int_set:N = \amc_num_exact_int,
1719 exact .initial:n = { 0 },
1720 approx .int_set:N = \amc_num_approx_int,
1721 approx .initial:n = { 0 },
1722 keepas .code:n = {\def\AMC@numeric@keepas{#1}},
1723 keepas .initial:n = {},
1724 alsocorrect .code:n = {\def\AMC@numeric@alsocorrect{#1}},
1725 alsocorrect .initial:n = {}
1726 }
1727
1728 \cs_new:Npn \amc_num_setopts #1 {
1729   \keys_set:nn { amcnumeric } { #1 }
1730 }
1731
1732 \cs_new_nopar:Nn \amc_num_check_score_opts: {
1733   \bool_if:NTF \amc_num_ignoreblank_bool {
1734     \int_compare:nNnTF \amc_num_base_int = { 10 } { } {
1735       \message{^^J!~Error:~ignoreblank~can~only~be~used~with~number~base~10^^J}
1736     }
1737   } {}
1738 }
1739
1740 \cs_new_eq:NN \AMCnumericOpts \amc_num_setopts
1741

```

The command `\amc_num_char:nn{<inside>}{<answer>}` draw a box with content *<inside>* (only if needed), where *<answer>* is `\AMC@checkbox` if the corresponding choice is correct and empty if not.

```

1742 \cs_new:Npn \amc_num_char:nn #1 #2 {
1743   \global\advance\AMCrep@count\@ne\relax
1744   \AMCmessage{REP= \the\AMCrep@count :
1745     \ifx#2\AMC@checkbox B\else M\fi }
1746   \ifAMC@correc
1747     \protect\AMC@keyBox@{#1}{#2}{1}{case : \AMCid@name :
1748       \the\AMCid@quest , \the\AMCrep@count}
1749   \else
1750     \protect\AMC@keyBox@{#1}{}{1}{case : \AMCid@name :
1751       \the\AMCid@quest , \the\AMCrep@count}
1752   \fi
1753 }

```

The command `\amc_num_digit_box:nn{<i>}{<j>}` draws a box for current digit value *<i>*, where *<j>* is the correct value for the current digit. If *<i>* is greater than 9, it is converted to a character from the English alphabet (A for 10, B for 11...)

```

1754 \int_new:N \amc_num_digit_value_int
1755 \tl_new:N \amc_num_digit_value_tl
1756 \cs_new:Npn \amc_num_digit_box:nn #1 #2 {

```

```

1757 \int_set:Nn \amc_num_digit_value_int { #1 }
1758 \tl_set:Nn \amc_num_digit_value_tl {
1759   \int_compare:nNnTF { \amc_num_digit_value_int } < { 10 }
1760     { \int_to_arabic:n { \amc_num_digit_value_int } }
1761     { \int_to_Alph:n { \amc_num_digit_value_int - 9 } }
1762 }
1763 \int_compare:nNnTF { #1 } = { #2 } {
1764   \amc_num_char:nn{ \tl_use:N \amc_num_digit_value_tl }
1765     {\AMC@checkbox}
1766 } {
1767   \amc_num_char:nn{ \tl_use:N \amc_num_digit_value_tl }
1768     {}
1769 }
1770 }

```

The command `\amc_num_sign_boxes:Nn{<sign>}{<prefix>}` draws two boxes for the students to code the sign (with a right value given by the boolean `<negative>`).

```

1771 \cs_new:Npn \amc_num_sign_boxes:Nn #1 #2 {
1772   \int_case:nn { #1 } {
1773     { -1 } {
1774       \bool_if:NTF \amc_num_plussign_bool {
1775         \hbox{\amc_num_char:nn{+}{}}
1776         \vspace{\AMCnumeric@Vspace}
1777         \AMCmessage{B=set. sign #2 =1}
1778       } { }
1779       \hbox{\amc_num_char:nn{-}{\AMC@checkbox}}
1780       \AMCmessage{B=set. sign #2 =-1}
1781     }
1782     { 1 } {
1783       \bool_if:NTF \amc_num_plussign_bool {
1784         \hbox{\amc_num_char:nn{+}{\AMC@checkbox}}
1785         \vspace{\AMCnumeric@Vspace}
1786         \AMCmessage{B=set. sign #2 =1}
1787       } { }
1788       \hbox{\amc_num_char:nn{-}{}}
1789       \AMCmessage{B=set. sign #2 =-1}
1790     }
1791     { 0 } {
1792       \bool_if:NTF \amc_num_plussign_bool {
1793         \hbox{\amc_num_char:nn{+}{}}
1794         \vspace{\AMCnumeric@Vspace}
1795         \AMCmessage{B=set. sign #2 =1}
1796       } { }
1797       \hbox{\amc_num_char:nn{-}{}}
1798       \AMCmessage{B=set. sign #2 =-1}
1799     }
1800   }
1801 }

```

The command `\amc_num_digit_boxes_h:nnn{<varname>}{<correct>}{<maxdigit>}` draws a serie of boxes for all possible values of a digit (from 0 to `<maxdigit>`), where the correct value is `<correct>`, transmitting scoring data to AMC so that the variable `<varname>` will be set to the value chosen by the student.

```

1802 \cs_new:Npn \amc_num_digit_boxes_h:nnn #1 #2 #3 {

```

```

1803 \int_step_inline:nnnn
1804 { \bool_if:NTF \amc_num_nozero_bool { 1 } { 0 } }
1805 { 1 } { #3 - 1 } {
1806   \amc_num_digit_box:nn { ##1 } { #2 }
1807   \AMCmessage{B= set. #1 = ##1}
1808   \hspace{\AMCnumeric@Hspace}
1809 }
1810 \hspace{-\AMCnumeric@Hspace}
1811 }
1812

```

The command `\amc_num_digit_boxes_v:nnn{<varname>}{<correct>}{<maxdigit>}` does the same as `\amc_num_digit_boxes_h:nnn`, with a vertical disposition.

```

1813 \cs_new:Npn \amc_num_digit_boxes_v:nnn #1 #2 #3 {
1814   \int_step_inline:nnnn
1815   { \bool_if:NTF \amc_num_nozero_bool { 1 } { 0 } }
1816   { 1 } { #3 - 1 } {
1817     \vbox{\hbox{
1818       \amc_num_digit_box:nn { ##1 } { #2 }
1819     }}
1820     \AMCmessage{B= set. #1 = ##1}
1821     \int_compare:nNnTF { ##1 } < { #3 - 1 } {
1822       \vspace{\AMCnumeric@Vspace}
1823     } {}
1824   }
1825 }
1826

```

The command `\amc_num_digit_boxes_a:nnn{<varname>}{<correct>}{<maxdigit>}` does the same as `\amc_num_digit_boxes_h:nnn`, with an array disposition with `\amc_num_digitcols_int` columns.

```

1827 \int_new:N \amc_num_array_int
1828 \int_new:N \amc_num_array_col_int
1829 \int_new:N \amc_num_array_row_int
1830 \int_new:N \amc_num_array_nrows_int
1831 \int_new:N \amc_num_array_i_int
1832 \tl_new:N \amc_num_array_tl
1833
1834 \cs_new:Npn \amc_tabular_defs:nn #1 #2 {
1835   \begin{tabular}[#1]{#2}
1836 }
1837 \cs_generate_variant:Nn \amc_tabular_defs:nn { xx }
1838
1839 \cs_new:Npn \amc_num_digit_boxes_a:nnn #1 #2 #3 #4 {
1840   \tl_set:Nn \amc_num_array_tl l
1841   \int_step_inline:nnnn 2 1 \amc_num_digitcols_int {
1842     \tl_put_right:Nn \amc_num_array_tl { |l }
1843   }
1844   \fboxrule=\AMCnarray@BorderWidth
1845   \fboxsep=1pt
1846   \fcolorbox{\AMCnarray@Border}{\AMCncol@Background}{\hspace*{-.2em}
1847     \arrayrulecolor{\AMCnarray@Border}\setlength{\tabcolsep}{4pt}
1848     \hbox{\amc_tabular_defs:xx { b } { \tl_use:N \amc_num_array_tl }
1849       \int_gzero:N \amc_num_array_int

```

```

1850
1851 \int_gzero:N \amc_num_array_row_int
1852 \int_gset:Nn \amc_num_array_nrows_int
1853 { \int_div_truncate:nn { #4 - #3 + \amc_num_digitcols_int - 1 }
1854   \amc_num_digitcols_int }
1855 \int_do_while:nNnn \amc_num_array_row_int < \amc_num_array_nrows_int {
1856   \int_gzero:N \amc_num_array_col_int
1857   \int_do_while:nNnn \amc_num_array_col_int < \amc_num_digitcols_int {
1858
1859     \int_set:Nn \amc_num_array_i_int
1860     { #3 + \amc_num_array_row_int +
1861       \amc_num_array_col_int * \amc_num_array_nrows_int }
1862
1863     \int_compare:nNnTF \amc_num_array_i_int < #4 {
1864       \vbox{\hbox{
1865         \amc_num_digit_box:nn { \int_use:N \amc_num_array_i_int }{ #2 }
1866       }}
1867       \AMCmessage{B= set. #1 = \int_use:N \amc_num_array_i_int}
1868     } { }
1869
1870     \int_gincr:N \amc_num_array_col_int
1871
1872     \int_compare:nNnTF \amc_num_array_col_int < \amc_num_digitcols_int { & } { }
1873   }
1874   \int_gincr:N \amc_num_array_row_int
1875
1876   \int_compare:nNnTF \amc_num_array_row_int < \amc_num_array_nrows_int { \\ } { }
1877 }
1878
1879 \end{tabular}}\hspace*{-.2em}}
1880 }
1881
1882 \int_new:N \amc_num_first_digit_int
1883 \cs_new:Npn \amc_num_digit_boxes_vr:nnn #1 #2 #3 {
1884   \int_set:Nn \amc_num_first_digit_int
1885   { \bool_if:NTF \amc_num_nozero_bool { 1 } { 0 } }
1886   \int_step_inline:nnnn { #3 - 1 } { -1 }
1887   \amc_num_first_digit_int {
1888     \vbox{\hbox{
1889       \amc_num_digit_box:nn { ##1 }{ #2 }
1890     }}
1891     \AMCmessage{B= set. #1 = ##1}
1892     \int_compare:nNnTF { ##1 } > \amc_num_first_digit_int {
1893       \vspace{\AMCnumeric@Vspace}
1894     } {}
1895   }
1896 }

The command \amc_num_integer_boxes_v:Nnn{<correct digits>}{<prefix>}{<decimals>} draws
boxes for integer entry, without the sign.
1897 \cs_new:Npn \amc_num_integer_boxes_v:Nnn #1 #2 #3 {
begin a loop over all digits,
1898   \int_set_eq:NN \amc_num_digit_int { \clist_count:N #1 }

```

```

1899 \clist_map_inline:Nn #1 {
place the decimal point if necessary,
1900 \int_compare:nNnTF \amc_num_digit_int = { #3 } {
1901 \hbox{ \AMCdecimalPoint }\hspace{\AMCnumeric@Hspace}
1902 } { }
draw the box for this digit,
1903 \hbox{\vbox{
1904 \bool_if:NTF \amc_num_vhead_bool {
1905 \vbox{\hbox to \AMC@boxedwidth{\hfill\AMCncontextVHead{ \int_eval:n
1906 { \amc_num_digit_int - 1 } }\hfill}}
1907 \vspace{\AMCnumeric@Vspace}
1908 } { }
1909 \int_compare:nNnTF \amc_num_digitcols_int = 1 {
1910 \bool_if:NTF \amc_num_reverse_bool {
1911 \amc_num_digit_boxes_vr:nnn { #2
1912 \int_to_Alph:n \amc_num_digit_int }
1913 { ##1 } { \amc_num_base_int }
1914 } {
1915 \amc_num_digit_boxes_v:nnn { #2
1916 \int_to_Alph:n \amc_num_digit_int }
1917 { ##1 } { \amc_num_base_int }
1918 }
1919 } {
1920 \hbox{
1921 \amc_num_digit_boxes_a:nnn { #2
1922 \int_to_Alph:n \amc_num_digit_int }
1923 { ##1 } { \bool_if:NTF \amc_num_nozero_bool { 1 } { 0 } }
1924 \amc_num_base_int
1925 }
1926 }
1927 }}

```

and end the loop over digits, adding space if this is not the last one.

```

1928 \int_compare:nNnTF \amc_num_digit_int > 1 {
1929 \hspace{\AMCnumeric@Hspace}
1930 } { }
1931 \int_decr:N \amc_num_digit_int
1932 }
1933 }
1934

```

The command `\amc_num_integer_boxes_h:Nnn{<correct digits>}{<prefix>}{<decimals>}` does the same, in horizontal mode.

```

1935
1936 \cs_new:Npn \amc_num_integer_boxes_h:Nnn #1 #2 #3 {
1937 \vbox{
1938 \int_set_eq:NN \amc_num_digit_int { \clist_count:N #1 }
1939 \clist_map_inline:Nn #1 {
1940 \int_compare:nNnTF
1941 \amc_num_digit_int = { #3 } {
1942 \hbox{ \AMCdecimalPoint }
1943 } { }
1944 \int_compare:nNnTF \amc_num_digitcols_int = 1 {

```

```

1945     \hbox{
1946         \amc_num_digit_boxes_h:nnn { #2
1947             \int_to_Alph:n \amc_num_digit_int }
1948         { ##1 } \amc_num_base_int
1949     }
1950 } {
1951     \hbox{
1952         \amc_num_digit_boxes_a:nnn { #2
1953             \int_to_Alph:n \amc_num_digit_int }
1954         { ##1 } { \bool_if:NTF \amc_num_nozero_bool { 1 } { 0 } } \amc_num_base_int
1955     }
1956 }
1957 \int_compare:nNnTF \amc_num_digit_int > 1 {
1958     \vspace{\AMCnumeric@Vspace}
1959 } { }
1960 \int_decr:N \amc_num_digit_int
1961 }}
1962 }
1963
1964 \cs_new:Npn \amc_num_sign_boxes:NnN #1 #2 #3 {
1965     \vbox{
1966         \ifx\AMCnntextSign\@empty\@empty\else
1967             \hbox{\AMCnntextSign}\vspace{\AMCnumeric@Vspace}\fi
1968         \bool_if:NTF \amc_num_strict_bool {
1969             \int_compare:nNnTF { #3 } = 0 {
1970                 \amc_num_sign_boxes:Nn { 1 } { #2 }
1971             }{
1972                 \amc_num_sign_boxes:Nn { #3 } { #2 }
1973             }
1974         }{
1975             \amc_num_sign_boxes:Nn { #3 } { #2 }
1976         }
1977     }
1978 }
1979

```

Finally, `\amc_num_integer_boxes:NnnNN{<correct digits>}{<prefix>}{<decimals>}{<sign bool>}{<sign>}` draws boxes for integer entry, including the sign if `<sign bool>` is true. When using the `strict` option, check the `+` box for a null value.

```

1980 \cs_new:Npn \amc_num_integer_boxes:NnnNN #1 #2 #3 #4 #5 {
1981     \hbox{
1982         \bool_if:NTF { #4 } {
1983             \int_compare:nNnTF \amc_num_digitcols_int = 1 {
1984                 \amc_num_sign_boxes:NnN { #1 } { #2 } { #5 }
1985                 \hspace{\AMCnumeric@Hspace}
1986                 \vrule
1987                 \hspace{\AMCnumeric@Hspace}
1988             } {
1989                 \fboxrule=\AMCnarray@BorderWidth
1990                 \fboxsep=1pt
1991                 \fcolorbox{\AMCnarray@Border}{\AMCncol@Background}{
1992                     \amc_num_sign_boxes:NnN { #1 } { #2 } { #5 }
1993                 }
1994                 \hspace{\AMCnumeric@Hspace}

```

```

1995     }
1996   } { }
1997   \hbox{
1998     \bool_if:NTF \amc_num_vertical_bool
1999     \amc_num_integer_boxes_v:Nnn \amc_num_integer_boxes_h:Nnn
2000     #1 { #2 } { #3 }
2001   }
2002 }
2003 }
2004

```

The command `\amc_num_build_integer_scoring:Nnnnn{<tl var>}{<sign bool>}{<prefix>}{<n>}{<decimals>}` builds a scoring to compute an integer from a serie of $\langle n \rangle$ -digits boxes (from which $\langle decimals \rangle$ are for decimals), with name prefix $\langle prefix \rangle$, using a sign variable if $\langle sign bool \rangle$ is true.

```

2005
2006 \cs_new:Npn \amc_num_build_integer_scoring:Nnnnn #1 #2 #3 #4 #5 {
2007   \amc_num_check_score_opts:
2008   \tl_clear:N #1
2009   \int_set_eq:NN \amc_num_digit_int { #4 }
2010   \int_while_do:nNnn \amc_num_digit_int > 0 {
2011     \bool_if:NTF \amc_num_strict_bool {
2012       \AMCmessage{B=requires. #3
2013         \int_to_Alph:n \amc_num_digit_int = 1}
2014     } {
2015       \AMCmessage{B=default. #3
2016         \int_to_Alph:n \amc_num_digit_int =
2017         \bool_if:NTF \amc_num_ignoreblank_bool { } { 0 }
2018       }
2019     }
2020     \int_compare:nNnTF \amc_num_digit_int = #4 { } {
2021       \bool_if:NTF \amc_num_ignoreblank_bool {
2022         \tl_put_right:Nx #1 { ~.~ }
2023         \int_compare:nNnTF \amc_num_digit_int = #5 {
2024           \tl_put_right:Nx #1 { "." ~.~ }
2025         } { }
2026       } {
2027         \tl_put_left:Nn #1 { ( }
2028         \tl_put_right:Nx #1 { ) *
2029         \int_use:N \amc_num_base_int + }
2030       }
2031     }
2032     \tl_put_right:Nx #1
2033     { #3 \int_to_Alph:n \amc_num_digit_int }
2034     \int_decr:N \amc_num_digit_int
2035   }
2036   \bool_if:NTF \amc_num_ignoreblank_bool {
2037     \tl_put_left:Nn #1 { ( 0 + ( }
2038     \tl_put_right:Nn #1 { ) ) }
2039     \int_compare:nNnTF \amc_num_decd_int > 0 {
2040       \tl_put_right:Nx #1 { * ( \int_use:N \amc_num_base_int ** \int_eval:n { #5 } ) }
2041     } { }
2042   } {
2043     \tl_put_left:Nn #1 { ( }
2044     \tl_put_right:Nn #1 { ) }

```

```

2045 }
2046 \bool_if:NTF { #2 } {
2047   \bool_if:NTF \amc_num_strict_bool {
2048     \AMCmessage{B=requires. sign #3 =1}
2049   } {
2050     \AMCmessage{B=default. sign #3 =1}
2051   }
2052   \tl_put_right:Nx #1 { * ( sign #3 ) }
2053 } { }
2054 }
2055

```

Then the command `\AMCnumericShow{<x>}{<options>}` itself:

```

2056
2057 \fp_new:N \amc_num_result_fp
2058 \fp_new:N \amc_num_correct_fp
2059 \clist_new:N \amc_num_digits_clist
2060 \clist_new:N \amc_num_expo_digits_clist
2061 \int_new:N \amc_num_digit_int
2062 \int_new:N \amc_num_sign_int
2063 \int_new:N \amc_num_expo_sign_int
2064 \tl_new:N \amc_num_compute_tl
2065 \tl_new:N \amc_num_expo_tl
2066 \int_new:N \amc_num_correct_expo_int
2067
2068 \cs_new:Npn \amc_numeric_show:nn #1 #2 {

```

We have to tell AMC that the scoring we will give concerns this question:

```

2069 \ifAMC@ensemble\ifAMCformulaire@dedans
2070   \AMCmessage{Q=\the\AMCid@quest}
2071 \fi\fi

```

Then we parse the options from `<opts>`:

```

2072 {\keys_set:nn { amcnumeric } { #2 }

```

if `Tvhead` is set, we adapt the `AMCncontextVHead` macro

```

2073 \int_compare:nTF {\amc_vheadunitindex_int = 0}
2074 {\int_set:Nn \amc_vheadunitindex_int {\amc_num_decd_int + 1}}
2075 {}
2076
2077 \clist_if_empty:NTF \amc_tvhead_clist
2078 {}
2079 {
2080   \def\AMCncontextVHead##1{
2081     \int_set:Nn \l_tmpa_int
2082       {\int_max:nn
2083         {(##1) - \amc_num_decd_int + \amc_vheadunitindex_int}
2084         {0}}
2085     \emph{\clist_item:Nn \amc_tvhead_clist {\l_tmpa_int}}}}
2086
2087   \bool_if:nTF { \bool_if_p:N\amc_num_significant_bool
2088     && \int_compare_p:n { \amc_num_base_int != 10 } } {
2089     \message{^^J!~AMCnumeric~Error:~significant=true~can't~be~used~with~base!=10.^^J}
2090   } {}
2091   \bool_if:nTF { \int_compare_p:n { \amc_num_expo_int != 0 }

```

```

2092     && \int_compare_p:n { \amc_num_base_int != 10 } } {
2093     \message{^^J!~AMCnumeric~Error:~scientific~notation~can't~be~used~with~base!=10.^^J}
2094 } {}

```

Convert the floating point correct value to integer, taking into account the parameters significant, exponent and decimals:

```

2095 \ifx\@empty#1\@empty
2096   \fp_set:Nn \amc_num_correct_fp { 0 }
2097   \fp_set:Nn \amc_num_mantissa_fp { 0 }
2098   \int_set:Nn \amc_num_correct_expo_int { 0 }
2099 \else
2100 \bool_if:NTF \amc_num_significant_bool {
2101   \amc_fp_n_significant_digits:Nnn \amc_num_correct_fp { #1 } \amc_num_ndigits_int
2102 } {
2103   \int_compare:nNnTF \amc_num_expo_int > 0 {
2104     \amc_fp_decompose:NnN \amc_num_mantissa_fp \amc_num_correct_expo_int { #1 }
2105     \int_compare:nNnTF { \amc_num_ndigits_int - \amc_num_decd_int } > 1 {
2106       \fp_set:Nn \amc_num_mantissa_fp {
2107         \amc_num_mantissa_fp * \amc_num_base_int^( \amc_num_ndigits_int - \amc_num_decd_int - 1 )
2108       }
2109       \int_set:Nn \amc_num_correct_expo_int {
2110         \amc_num_correct_expo_int - ( \amc_num_ndigits_int - \amc_num_decd_int - 1 )
2111       }
2112     } {}
2113     \amc_fp_n_digits:Nnn \amc_num_correct_fp \amc_num_mantissa_fp \amc_num_decd_int
2114   } {
2115     \amc_fp_n_digits:Nnn \amc_num_correct_fp { #1 } \amc_num_decd_int
2116   }
2117 }
2118 \fi

```

Now extracts the required digits:

```

2119 \ifx\@empty#1\@empty
2120   \amc_invalid_digits:Nn \amc_num_digits_clist \amc_num_ndigits_int
2121   \amc_invalid_digits:Nn \amc_num_expo_digits_clist \amc_num_expo_int
2122   \int_set:Nn \amc_num_sign_int { 0 }
2123   \int_set:Nn \amc_num_expo_sign_int { 0 }
2124 \else
2125   \amc_fp_to_digits:Nnnn \amc_num_digits_clist \amc_num_correct_fp
2126   \amc_num_ndigits_int \amc_num_base_int
2127   \amc_get_fp_sign:Nn \amc_num_sign_int \amc_num_correct_fp
2128   \int_compare:nNnTF \amc_num_expo_int > 0 {
2129     \amc_fp_to_digits:Nnnn \amc_num_expo_digits_clist \amc_num_correct_expo_int
2130     \amc_num_expo_int \amc_num_base_int
2131     \amc_get_int_sign:Nn \amc_num_expo_sign_int \amc_num_correct_expo_int
2132   } {}
2133 \fi

```

The question scoring is given to AMC (if requested by the `scoring=true` option). Note that the variable `intV` refers to the correct value, and `intX` to the value entered by the student.

```

2134 \fp_set:Nn \amc_num_result_fp { #1 }
2135 \AMCmessage{B=numval=\fp_to_scientific:N \amc_num_result_fp ,
2136   numex=\int_use:N \amc_num_exact_int,
2137   numapp=\int_use:N \amc_num_approx_int,
2138   numsex=\AMC@numeric@scoreexact,

```

```

2139     numsapp=\AMC@numeric@scoreapprox
2140 }
2141 \bool_if:NTF \amc_num_scoring_bool {
2142   \AMCmessage{B=haut=mz=d=undef,p=undef,
2143     formula=(Vdifference <= \int_use:N \amc_num_exact_int ?
2144     \AMC@numeric@scoreexact :
2145     \int_compare:nNnTF \amc_num_approx_int = 0 {
2146       \AMC@numeric@scorewrong
2147     } {
2148       (Vdifference <= \int_use:N \amc_num_approx_int ?
2149       \AMC@numeric@scoreapprox : \AMC@numeric@scorewrong)
2150     }
2151   )}
2152 } {}
2153 \amc_num_build_integer_scoring:Nnnnn
2154   \amc_num_compute_tl \amc_num_sign_bool { digit } \amc_num_ndigits_int
2155   \amc_num_decd_int
2156 \int_compare:nNnTF \amc_num_expo_int > 0 {
2157   \amc_num_build_integer_scoring:Nnnnn
2158   \amc_num_expo_tl \amc_num_exposign_bool { expo } \amc_num_expo_int { 0 }
2159   \AMCmessage{B= set. intE = \amc_num_expo_tl}
2160 } {}
2161 \AMCmessage{B= set.intV = \fp_to_int:N \amc_num_correct_fp ,
2162   set.intXX = \amc_num_compute_tl }
2163 \int_compare:nNnTF \amc_num_expo_int > 0 {
2164   \AMCmessage{B= set.intX = intXX * \int_use:N \amc_num_base_int ** ( intE - (\int_use:N \amc_num_correc
2165 }{
2166   \AMCmessage{B= set.intX = intXX}
2167 }
2168 \int_compare:nNnTF \amc_num_expo_int > 0 {
2169   \AMCmessage{B= set.valueX = intXX * \int_use:N \amc_num_base_int ** (intE - \int_use:N \amc_num_decd
2170 }{
2171   \AMCmessage{B= set.valueX = intXX * \int_use:N \amc_num_base_int ** (- \int_use:N \amc_num_decd_int))
2172 }
2173 \ifx\@empty\AMC@numeric@keepas\@empty\else
2174 \AMCmessage{B= setglobal.\AMC@numeric@keepas = valueX}
2175 \fi
2176 \ifx\@empty#1\@empty
2177 \bool_if:NTF \amc_num_significant_bool {
2178   \AMCmessage{B=set.Vdifference=0}
2179 }{
2180   \ifx\@empty\AMC@numeric@alsocorrect\@empty
2181     \AMCmessage{B=set.Vdifference=0}
2182   \else
2183     \AMCmessage{B="set.Vdifference =
2184       amcvdifference( \AMC@numeric@alsocorrect, valueX, \int_use:N \amc_num_decd_int, \int_use:N \amc_r
2185       "}
2186   \fi
2187 }
2188 \else
2189 \bool_if:NTF \amc_num_significant_bool {
2190   \AMCmessage{B=set.Vdifference="min( abs((intV)-(intX)) ,
2191     abs(\int_use:N \amc_num_base_int * (intV) - (intX)) ,

```

```

2192      abs((intV) - \int_use:N\amc_num_base_int * (intX)) )"}
2193    } {
2194      \ifx\@empty\AMC@numeric@alsocorrect\@empty
2195        \AMCmessage{B=set.Vdifference=abs((intV)-(intX))}
2196      \else
2197        \AMCmessage{B="set.Vdifference =
2198          min( amcvdifference( \AMC@numeric@alsocorrect, valueX, \int_use:N\amc_num_decd_int, \int_use:N\am
2199            abs((intV)-(intX)) )"}
2200      \fi
2201    }
2202    \fi

```

Begin now with the frame around all the boxes:

```

2203    \ifAMC@extractOnly\else
2204    \vspace{1.5ex}\par{
2205      \fboxrule=\AMCncol@BorderWidth
2206      \fcolorbox{\AMCncol@Border}{\AMCncol@Background}{
2207        \bool_if:NTF \amc_num_expovertical_bool {
2208          \hbox{\vbox{
2209            \vbox{\amc_num_integer_boxes:NnnNN
2210              \amc_num_digits_clist { digit } \amc_num_decd_int \amc_num_sign_bool
2211              \amc_num_sign_int}
2212            \int_compare:nNnTF \amc_num_expo_int > 0 {
2213              \vspace{\AMCnumeric@Vspace}
2214              \vbox{\hbox{\AMCexponent}}
2215              \vspace{\AMCnumeric@Vspace}
2216              \vbox{\amc_num_integer_boxes:NnnNN
2217                \amc_num_expo_digits_clist { expo } { 0 } \amc_num_exposign_bool
2218                \amc_num_expo_sign_int}
2219            } {}
2220          }}
2221        } {
2222          \amc_num_integer_boxes:NnnNN
2223          \amc_num_digits_clist { digit } \amc_num_decd_int \amc_num_sign_bool
2224          \amc_num_sign_int
2225          \int_compare:nNnTF \amc_num_expo_int > 0 {
2226            \hspace{\AMCnumeric@Hspace}\AMCexponent\hspace{\AMCnumeric@Hspace}
2227            \amc_num_integer_boxes:NnnNN
2228            \amc_num_expo_digits_clist { expo } { 0 } \amc_num_exposign_bool
2229            \amc_num_expo_sign_int
2230          } {}
2231        }
2232      }
2233    }
2234    \fi

```

And tell AMC that we finished with this question:

```

2235    \ifAMC@ensemble\else\vspace{\AMCpostNquest}\par\fi
2236    \ifAMC@ensemble\ifAMCformulaire@dedans
2237      \AMCmessage{FQ}
2238    \fi\fi
2239  }
2240 }
2241

```

```

2242 \cs_new_eq:NN \AMCnumericShow \amc_numeric_show:nn
2243

```

`\AMCnumericHide` is called when the boxes are not to be drawn (in the question sheets for separate answer sheet layout), and `\AMCnumericChoices{⟨value⟩}{⟨options⟩}` is the function to be used in the LaTeX source code of the exam.

```

2244 \cs_new:Npn \amc_numeric_hide:nn #1 #2 {
2245   \keys_set:nn { amcnumeric } { #2 }
2246   \AMCncontextGoto
2247   \ifAMC@qbloc\else\vspace{1.5ex}\par\fi
2248 }
2249
2250 \cs_new_eq:NN \AMCnumericHide \amc_numeric_hide:nn
2251
2252 \ExplSyntaxOff
2253 \def\AMCnumericChoicesPlain{%
2254   \AMC@if@separate@question{\AMC@mem@category{numeric}}{%
2255     \AMCformatChoices{\AMCnumericShow}{\AMCnumericHide}%
2256   }

```

The `{⟨value⟩}` argument is often given as a macro, that is to be expanded before calling `\AMCnumericChoicesPlain`, so that its value will be the same in the separate answer sheet...

```

2257 \ExplSyntaxOn
2258
2259 \cs_new:Npn \amc_numeric_choices:nn #1#2 {
2260   \AMCnumericChoicesPlain{#1}{#2}
2261 }
2262 \cs_generate_variant:Nn \amc_numeric_choices:nn { xn }
2263 \cs_new_eq:NN \AMCnumericChoices \amc_numeric_choices:xn
2264
2265 \ExplSyntaxOff

```

4.13.3 Intervals

`\AMCIntervals` The command `\AMCIntervals{⟨x⟩}{⟨x0⟩}{⟨x1⟩}{⟨delta⟩}` can be used to present answers as intervals $[x_i, x_i + \delta[$ covering $[\langle x0 \rangle, \langle x1 \rangle]$, such that the only interval containing $\langle x \rangle$ is declared as `\correctchoice`, and the other as `\wrongchoice`.

For this command to work, one has to load package `fp`.

As an example,

```

\begin{question}{quarter}
  In which interval falls  $1/4$ ?
  \begin{multicols}{5}
    \begin{choices}[o]
      \AMCIntervals{0.25}{0}{1}{0.1}
    \end{choices}
  \end{multicols}
\end{question}

```

produces (in correction mode):

Question 12 In which interval falls $1/4$?

☐ [0, 0.1[	☒ [0.2, 0.3[	☐ [0.4, 0.5[	☐ [0.6, 0.7[	☐ [0.8, 0.9[
☐ [0.1, 0.2[	☐ [0.3, 0.4[	☐ [0.5, 0.6[	☐ [0.7, 0.8[	☐ [0.9, 1[

Note that the interval formatting can be changed redefining the `\AMCintervalFormat` command, which is originally defined as

```
2266 \def\AMCIntervalFormat#1#2{[#1,\,#2]}
```

to follow local conventions (writting $[a, b]$ instead of $[a, b[$ is for example a common usage).

```
2267 \ExplSyntaxOn
```

```
2268
```

```
2269 \fp_new:N \amc_interv_a
```

```
2270 \fp_new:N \amc_interv_b
```

```
2271 \cs_new:Npn \amc_intervals:nnnn #1 #2 #3 #4 {
```

```
2272   \fp_set:Nn \amc_interv_a { #2 }
```

```
2273   \fp_do_while:nn { \amc_interv_a < #3 } {
```

```
2274     \fp_set:Nn \amc_interv_b { \amc_interv_a + #4 }
```

```
2275     \fp_compare:nTF { \amc_interv_a <= #1 < \amc_interv_b }
```

```
2276       \correctchoice \wrongchoice
```

```
2277       {\AMCIntervalFormat{\fp_use:N \amc_interv_a}{\fp_use:N \amc_interv_b}}
```

```
2278       \fp_set:Nn \amc_interv_a \amc_interv_b
```

```
2279   }
```

```
2280 }
```

```
2281 \cs_new_eq:NN \AMCIntervals \amc_intervals:nnnn
```

```
2282
```

```
2283 \ExplSyntaxOff
```

4.14 Open questions

`\AMCOpen` The command `\AMCOpen{<options>}{<choices>}` can be used as a replacement for the `choices` environment when asking the student to write some answer by hand. The teacher will correct and mark this answer either on the paper before scanning, or with manual data capture, thanks to the scoring boxes.

As an example,

```
\begin{question}{Linux}
```

```
  What is the first name of the person who started working on the Linux kernel?
```

```
  \AMCOpen{}{\wrongchoice[w]{w}\scoring{0}\correctchoice[c]{c}\scoring{2}}
```

```
\end{question}
```

shows:

Question 13 What is the first name of the person who started working on the Linux kernel?

☐ w ☐ c

.....

The teacher will have to tick the ‘w’ box for wrong answers, and the ‘c’ box for correct answers.

Begin with the options definitions:

```

2284 \def\AMCotextGoto{}
2285 \def\AMCotextReserved{}
2286 \def\AMCocol@Background{lightgray}
2287 \def\AMCocol@BoxFrameRule{white}
2288 \def\AMCocol@FrameRule{black}
2289 \def\AMCocol@Foreground{}
2290 \def\AMCopen@answer{}
2291 \def\AMCopen@question{}
2292 \def\AMCopen@lineuptext{}
2293 \define@key{AMCopen}{backgroundcol}{\def\AMCocol@Background{#1}}
2294 \define@key{AMCopen}{foregroundcol}{\def\AMCocol@Foreground{#1}}
2295 \define@key{AMCopen}{Treserved}{\def\AMCotextReserved{#1}}
2296 \define@key{AMCopen}{question}{\AMCid@name}{\def\AMCopen@question{#1}}
2297 \define@key{AMCopen}{answer}{\def\AMCopen@answer{#1}}
2298 \define@key{AMCopen}{contentcommand}{AMCopen@lines}{\def\AMCopen@contentcommand{#1}}
2299 \newdimen\AMCopen@Hspace\AMCopen@Hspace=.5em
2300 \define@key{AMCopen}{hspace}{\AMCopen@Hspace=#1}
2301 \def\AMCopen@Width{.95\linewidth}
2302 \define@key{AMCopen}{width}{\def\AMCopen@Width{#1}}
2303 \newdimen\AMCopen@LineHeight\AMCopen@LineHeight=1cm
2304 \define@key{AMCopen}{lineheight}{\AMCopen@LineHeight=#1}
2305 \newcount\AMCopen@Lines\AMCopen@Lines=1
2306 \define@key{AMCopen}{lines}{\AMCopen@Lines=#1}
2307 \newdimen\AMCopen@boxmargin\AMCopen@boxmargin=3pt
2308 \define@key{AMCopen}{boxmargin}{\AMCopen@boxmargin=#1}
2309 \newdimen\AMCopen@boxframerule\AMCopen@boxframerule=1pt
2310 \define@key{AMCopen}{boxframerule}{\AMCopen@boxframerule=#1}
2311 \define@key{AMCopen}{boxframerulecol}{\def\AMCocol@BoxFrameRule{#1}}
2312 \define@key{AMCopen}{framerulecol}{\def\AMCocol@FrameRule{#1}}
2313 \newdimen\AMCopen@framerule\AMCopen@framerule=1pt
2314 \define@key{AMCopen}{framerule}{\AMCopen@framerule=#1}
2315 \define@key{AMCopen}{lineuptext}{\def\AMCopen@lineuptext{#1}}
2316 \define@boolkey{AMCopen}{dots}[true]{}
2317 \define@boolkey{AMCopen}{scan}[true]{}
2318 \define@boolkey{AMCopen}{retick}[true]{}
2319 \define@boolkey{AMCopen}{annotate}[false]{}
2320 \define@boolkey{AMCopen}{lineup}[false]{}
2321 \setkeys{AMCopen}{dots,scan,retick,annotate,lineup,contentcommand}
2322 \newcommand\AMCopenOpts[1]{\setkeys{AMCopen}{#1}}

```

The command \AMCopen is similar to \AMCnumericChoices, calling either \AMCopenShow or \AMCopenHide.

```

2323 \newcommand\AMCopen@lines{%
2324   \begin{minipage}{\AMCopen@Width}%
2325     \loop\vspace{\AMCopen@LineHeight}
2326     \hspace*{.5em}\ifAMC@correc\smash{\AMCopen@answer}\def\AMCopen@answer{}\fi%
2327     \ifKV@AMCopen@dots%
2328       \dotfill\hspace*{.5em}
2329     \fi
2330     \ifnum\AMCopen@Lines>\@ne\par\advance\AMCopen@Lines\@ne\repeat%
2331   \end{minipage}
2332 }
2333 \newcommand\AMCopenShow[2]{
2334   \ifAMC@ensemble\ifAMC@formulaire@dedans%

```

```

2335 \AMCmessage{Q=\the\AMCid@quest}%
2336 \fi\fi%
2337 {\setkeys{AMCOpen}{#1}%
2338 \ifKV@AMCOpen@lineup%
2339 \ifAMC@ensemble\else%
2340 \ifx\@empty\AMCOpen@lineuptext\@empty\fi%
2341 \fi%
2342 \ifAMC@correc\smash{\AMCOpen@answer}\fi%
2343 \ifx\@empty\AMCOpen@lineuptext\@empty%
2344 \dotfill%
2345 \else%
2346 \AMCOpen@lineuptext\hfill%
2347 \fi%
2348 \else%
2349 \hspace*{.5em}\linebreak[1]\hspace*{\fill}%
2350 \fi%
2351 {\AMCnoCompleteMulti%
2352 \def\AMCbeginAnswer{}\def\AMCendAnswer{}%
2353 \def\AMCanswer##1##2{\ifAMC@ensemble ##1\else%
2354 \ifAMC@inside@box ##1\else\AMCboxOutsideLetter{##1}{##2}}\fi\fi%
2355 \hspace{\AMCOpen@Hspace}}%
2356 \fboxsep=\AMCOpen@boxmargin%
2357 \fboxrule=\AMCOpen@boxframerule%
2358 \fcolorbox{\AMCocol@BoxFrameRule}{\AMCocol@Background}{%
2359 \ifAMC@ensemble\AMCOpen@question%
2360 \ifx\@empty\AMCOpen@question\@empty\else\hspace{\AMCOpen@Hspace}\fi%
2361 \fi%
2362 \begin{choicescustom}[o]%
2363 \ifx\AMCocol@Foreground\@empty\@empty\else%
2364 \def\AMC@boxcolor{\AMCocol@Foreground}%
2365 \fi%
2366 #2%
2367 \ifKV@AMCOpen@scan\else\AMCdontScan\fi%
2368 \ifKV@AMCOpen@retick\AMCreTick\fi%
2369 \ifKV@AMCOpen@annotate\else\AMCdontAnnotate\fi%
2370 \end{choicescustom}}%
2371 \ifx\@empty\AMCotextReserved\@empty%
2372 \hspace{-\AMCOpen@Hspace}%
2373 \else%
2374 \ifx\AMCocol@Foreground\@empty\@empty%
2375 \AMCotextReserved%
2376 \else%
2377 \textcolor{\AMCocol@Foreground}{\AMCotextReserved}%
2378 \fi%
2379 \fi%
2380 }}%
2381 \ifKV@AMCOpen@lineup\else%
2382 \par\nobreak\noindent%
2383 \hspace*{\fill}{%
2384 \fboxrule=\AMCOpen@framerule%
2385 \fcolorbox{\AMCocol@FrameRule}{white}{%
2386 \csname\AMCOpen@contentcommand\endcsname
2387 }%

```

```

2388     \vspace{\AMCpostQuest}\par%
2389     \fi%
2390   }%
2391   \ifAMC@ensemble\ifAMCformulaire@dedans%
2392   \AMCmessage{FQ}%
2393   \fi\fi%
2394 }
2395 \newcommand\AMCOpenHide[2]{%
2396   \AMCotextGoto%
2397   \ifAMC@qbloc\else\vspace{1.5ex}\par\fi%
2398 }
2399 \def\AMCOpen{%
2400   \AMC@if@separate@question{\AMC@mem@category{open}}}%
2401   \AMCformatChoices{\AMCOpenShow}{\AMCOpenHide}%
2402 }
2403 \ExplSyntaxOn
2404 \cs_new:Npn \amc_open_question:nn #1#2 {
2405   \AMCOpen{#1}{#2}
2406 }
2407 \cs_generate_variant:Nn \amc_open_question:nn { xn }
2408 \cs_new_eq:NN \AMCOpenX \amc_open_question:xn
2409 \ExplSyntaxOff

```

4.15 Boxes with letters only

`\AMCBoxOnly` Sometimes the letters printed in the boxes (or just after them) are enough to describe the answers. In such cases, printing the boxes both on the question and on the answer sheet is not necessary. The `\AMCBoxOnly{<options>}{<choices>}` can be used as a replacement for the `choices` environment:

```

\begin{question}{arm}
  Which letter shows the \textit{arm} on the diagram?
  \AMCBoxOnly{ordered=true}{\wrongchoice[A]{}\correctchoice[B]{}%
    \wrongchoice[C]{}\wrongchoice[D]{}%
  }
\end{question}

2410 \def\AMCbotextGoto{}
2411 \def\AMCbo@help{}
2412 \define@key{AMCBoxOnly}{help}{\def\AMCbo@help{#1}}
2413 \define@boolkey{AMCBoxOnly}{ordered}[false]{}
2414 \setkeys{AMCBoxOnly}{ordered}
2415 \newcommand\AMCboOpts[1]{\setkeys{AMCBoxOnly}{#1}}
2416 \newcommand\AMCboShow[2]{%
2417   \ifAMC@ensemble\ifAMCformulaire@dedans%
2418     \AMCmessage{Q=\the\AMCid@quest}%
2419     \fi\fi%
2420   {\setkeys{AMCBoxOnly}{#1}%
2421     \def\AMCbeginAnswer{}\def\AMCendAnswer{}%
2422     \def\AMCanswer##1##2{\hspace{\AMCformHSpace} \ifAMC@ensemble ##1\else%
2423       \ifAMC@inside@box ##1\else\AMCboxOutsideLetter{##1}{##2}}\fi\fi%
2424     }%
2425     \ifAMC@ensemble\AMCbo@help\fi%
2426     \ifKV@AMCBoxOnly@ordered%

```

```

2427     \begin{choicescustom}[o]%
2428     \else%
2429     \begin{choicescustom}%
2430     \fi%
2431     #2
2432     \end{choicescustom}%
2433 }%
2434 \ifAMC@ensemble\ifAMCformulaire@dedans%
2435 \AMCmessage{FQ}%
2436 \fi\fi%
2437 }
2438 \newcommand\AMCboHide[2]{
2439 \AMCbotextGoto%
2440 \ifAMC@qbloc\else\vspace{1.5ex}\par\fi%
2441 }
2442 \def\AMCBoxOnly{%
2443 \AMC@if@separate@question{\AMC@mem@category{box}}%
2444 \AMCformatChoices{\AMCboShow}{\AMCboHide}%
2445 }

```

4.16 Page formatting

4.16.1 Watermark

`\AMCw@termark` These commands are used to print a grey “DRAFT” under each page, so as to prevent from
`\AMCw@terprint` printing old versions of the subject.

```

2446 \DeclareFontShape{OT1}{cmr}{b}{n}{<35->cmr17}{-}
2447 \def\AMC@watertext{\AMC@loc@draft}
2448 \newcommand\AMCw@termark{%
2449 \setlength{\@tempdimb}{.5\paperwidth}%
2450 \setlength{\@tempdimc}{-.5\paperheight}%
2451 \put(\strip@pt\@tempdimb,\strip@pt\@tempdimc){%
2452 \makebox(0,0){\rotatebox{45}{\AMC@LR{%
2453 \textcolor[gray]{0.8}{
2454 \fontencoding{OT1}\fontfamily{cmr}
2455 \fontseries{b}\fontshape{n}
2456 \fontsize{90pt}{120pt}
2457 \selectfont
2458 \AMC@watertext}}}}}
2459 \newcommand\AMCw@terprint[1]{%
2460 \setbox\@tempboxa\vbox to \z@{%
2461 \vbox{%
2462 \hbox to \z@{%
2463 #1\hss}}\vss}
2464 \dp\@tempboxa\z@
2465 \box\@tempboxa}

```

4.16.2 Signs for scan analysis

The following code sets up all the signs to be printed on the pages so as to be able to recognize the position of the boxes on the scans. Four circles ● are printed on the corners (see `\m@rqueCalage`), and binary boxes show the student sheet number (see `\AMCIDBoxesA`), the page (see `\AMCIDBoxesB`) and a checking number (see `\AMCIDBoxesC`).

\AMC@intituleHead is the title to be printed at the beginning (used for corrected sheet, and empty on subject). \AMC@note is printed at the bottom of each page. You can change its value using \AMCsetFoot{\foot}.

```

2466 \def\AMCccercle#1#2{%
2467   {\setlength{\unitlength}{1mm}%
2468     \begin{picture}(\#1,\#1)(-#2,-#2)\thinlines\circle*{\#1}\end{picture}}
2469 \def\m@rqueCalage{\AMCccercle{3.6}{1.8}}
2470 \def\m@rque#1{\AMC@tracebox{1}{\#1}{\m@rqueCalage}}
2471 \def\he@dtaille#1{% \par cancels the \leavevmode
2472   % introduced by https://github.com/pietvo/fancyhdr/commit/6b1ad10eeb5bc3d804f3cd2cf193e6440d0229e6
2473   \par\vbox to 1cm{\#1}}
2474 \def\he@dbas#1{\he@dtaille{\vspace*{\fill}\#1}}
2475 \def\he@dhaut#1{\he@dtaille{\#1\vspace*{\fill}}}
2476 \def\AMC@intituleHead{\AMC@loc@corrected}
2477 \def\AMC@note{}
2478 \def\AMCsetFoot#1{\def\AMC@note{\#1}}
2479 \newcommand\AMCStudentNumber{\the\AMCid@etud}
2480 \newcommand\AMCIDBoxesA{\AMC@binaryCode{id=1,ndigits=\AMC@NCBetud}{\the\AMCid@etud}}
2481 \newcommand\AMCIDBoxesB{\AMC@binaryCode{id=2,ndigits=\AMC@NCBpage}{\thepage}}
2482 \newcommand\AMCIDBoxesC{\AMC@binaryCode{id=3,ndigits=\AMC@NCBcheck}{\the\AMCid@check}}
2483 \newcommand\AMCIDBoxesABC{%
2484   \hbox{\vbox{\noindent\AMCIDBoxesA\
2485     \noindent\AMCIDBoxesB\AMCIDBoxesC}}}%
2486 }
2487 \def\AMC@pageHook{%
2488   \AMC@pagepos%
2489   \ifAMC@pagelayout\global\advance\AMCid@check\m@ne%
2490   \ifnum\AMCid@check<1\global\AMCid@check=\AMCid@checkmax\fi%
2491   \ifAMC@watermark\ifAMC@correthead\else\AMCwaterprint{\AMCwatermark}%
2492     \fi\fi\fi}
2493 \@ifl@t@r{fmtversion}{2020/10/01}
2494   {\AddToHook{shipout/background}{\put(0in,0in){\AMC@pageHook}}}
2495   {\AtBeginShipout{\AtBeginShipoutUpperLeft{\AMC@pageHook}}}
2496 \fancypagestyle{AMCpageHeadOnly}{%
2497   \fancyhf{} \fancyhead[C]{\textsc{\AMC@intituleHead}}%
2498   \renewcommand{\headrulewidth}{0pt}%
2499   \renewcommand{\footrulewidth}{0pt}%
2500 }
2501 \fancypagestyle{AMCpageFull}{%
2502   \fancyhf{}%
2503   \fancyhead[L]{\AMC@LR{\he@dbas{\leavevmode\m@rque{positionHG}}}}%
2504   \fancyhead[R]{\AMC@LR{\he@dbas{\leavevmode\m@rque{positionHD}}}}%
2505   \fancyfoot[L]{\AMC@LR{\leavevmode\m@rque{positionBG}}}%
2506   \fancyfoot[R]{\AMC@LR{\leavevmode\m@rque{positionBD}}}%
2507   \fancyhead[C]{\AMC@LR{\he@dhaut{%
2508     \begin{minipage}[b]{\AMC@CBtaille}\AMCboxColor{black}%
2509       \ifAMCids@top\vbox to \AMCids@height{\texttt{+\the\AMCid@etud/\thepage/\the\AMCid@check+}}\fi%
2510       \AMCIDBoxesABC
2511     \end{minipage}}%
2512     \ifAMCids@side\hbox to \AMCids@width{\hspace*\fill}%
2513     \texttt{+\the\AMCid@etud/\thepage/\the\AMCid@check+}}\fi%
2514   }}}%
2515   \fancyhfoffset[EOLR]{5mm}%

```

```

2516 \fancyfoot[C]{\AMC@note}%
2517 \renewcommand{\headrulewidth}{0pt}%
2518 \renewcommand{\footrulewidth}{0pt}%
2519 }
2520 \newcommand\AMCsubjectPageTag{%
2521 \fbox{\texttt{\the\AMCid@etud:\thepage}}%
2522 }
2523 \fancypagestyle{AMCpageNoMarks}{%
2524 \fancyhf{}%
2525 \fancyhead[R]{\AMCsubjectPageTag}%
2526 \fancyfoot[C]{\AMC@note}%
2527 \renewcommand{\headrulewidth}{0pt}%
2528 \renewcommand{\footrulewidth}{0pt}%
2529 }
2530 \fancypagestyle{AMCpageEmpty}{%
2531 \fancyhf{}%
2532 \renewcommand{\headrulewidth}{0pt}%
2533 \renewcommand{\footrulewidth}{0pt}%
2534 }
2535 \AtBeginDocument{%
2536 \ifAMC@pagelayout%
2537 \ifAMC@correthead
2538 \pagestyle{AMCpageHeadOnly}
2539 \else
2540 \pagestyle{AMCpageFull}
2541 \fi
2542 \fi
2543 }

```

4.17 Defining a single exam copy content

`\onecopy` The command `\onecopy[ $\langle n \rangle$ ]{ $\langle code \rangle$ }` generates $\langle n \rangle$ copies of the subject that is described in $\langle code \rangle$. The L^AT_EX code $\langle code \rangle$ that generates a single copy can be a little long, so that the environment `examcopy` is often preferred.

```

2544 \newcommand{\onecopy}[2]{%
2545 \ifx\AMCNombreCopies\undefined\AMCnum@copies=#1%
2546 \else\AMCnum@copies=\AMCNombreCopies\fi%
2547 \AMCmessage{TOTAL=\the\AMCnum@copies}%
2548 \message{^^JAMC:copies:total=\the\AMCnum@copies^^J}%
2549 \AMCid@etud=\AMCid@etudstart%
2550 \ifnum\AMCid@etud=0\AMCid@etud=\AMC@premierecopie\fi%
2551 \AMCid@etudfin=\AMCnum@copies%
2552 \advance\AMCid@etudfin\AMCid@etud\relax%
2553 \ifAMC@correthead\AMCid@etudfin=\AMC@premierecopie%
2554 \message{^^JAMC:copies:total=1^^J}%
2555 \fi
2556 \ifAMC@pdfform\begin{Form}\fi%
2557 \loop{%
2558 \global\AMCrep@nnmax=0%
2559 \ifAMC@calibration\protected@write\AMC@XYFILE{}{%
2560 \string\rngstate{\the\AMCid@etud}{\the\AMC@SR}%
2561 }\fi%
2562 \AMC@zoneformulairefalse\setcounter{page}{1}\setcounter{section}{0}%

```

```

2563 \ifAMC@ensemble\ifAMC@automarks\pagestyle{AMCpageNoMarks}\fi\fi%
2564 \AMCnumero{1}%
2565 \ifAMC@calibration\AMCmessage{ETU=\the\AMCid@etud}\fi%
2566 \AMC@multiclear%
2567 \global\AMC@keepmemoryfalse%
2568 #2%
2569 \ifAMC@keepmemory\else\AMC@mem@clear\fi%
2570 \clearpage}%
2571 \message{^^JAMC:copies:add=1^^J}%
2572 \advance\AMCid@etud\@one\ifnum\AMCid@etud<\AMCid@etudfin\repeat%
2573 \global\AMCid@etudstart=\AMCid@etud%
2574 \ifAMC@pdfform\end{Form}\fi%
2575 \AMC@multi@report%
2576 }

```

\AMCaddpagesto In some situations, one needs all question sheets to have the same number of pages. The command **\AMCaddpagesto{<n>}** adds enough (white) pages to get at least <n> pages in the current question sheet.

```

2577 \newcount\AMC@addpages
2578 \newcommand{\AMCaddpagesto}[1]{%
2579 \AMC@addpages=#1\advance\AMC@addpages\@one%
2580 \clearpage%
2581 \@whilenum\thepage<\AMC@addpages\do{%
2582 \ifAMC@automarks\pagestyle{AMCpageEmpty}\fi%
2583 \hbox{}\clearpage%
2584 }%
2585 }

```

\AMCcleardoublepage If you want to print the subject all at one time in duplex mode, it is necessary to end each subject with an even number of pages. This can be achieved using **\AMCcleardoublepage** at the end of the copy definition. This command is also useful inserted before the separate answer sheet (if any).

```

2586 \def\AMCcleardoublepage{%
2587 \clearpage%
2588 \ifodd\thepage\else%
2589 \ifAMC@automarks\pagestyle{AMCpageEmpty}\fi%
2590 \hbox{}\clearpage%
2591 \fi%
2592 }

```

\exemplairepair To make some differences in the copies, checking if the student sheet number is odd, with **\exemplairepair** construct, can be useful.

```

2593 \def\exemplairepair{\ifodd\AMCid@etud}

```

\AMClabel Commands **\AMClabel**, **\AMCref** and **\AMCpageref** replaces L^AT_EX's **\label**, **\ref** and **\pageref** **\AMCref** to be able to use different labels for different sheets.

```

\AMCref
2594 \newcommand\AMCstudentlabel[1]{\the\AMCid@etud-#1}
2595 \def\AMClabel#1{\expandafter\label{\AMCstudentlabel{#1}}}
2596 \def\AMCref#1{\expandafter\ref{\AMCstudentlabel{#1}}}
2597 \def\AMCpageref#1{\expandafter\pageref{\AMCstudentlabel{#1}}}

```

`\AMCqlabel` A label can be created for current question with `\AMCqlabel{<label>}`. This label can be used with `\AMCref` and `\AMCpageref`. This command is defined for backward compatibility only, since `\AMClabel` can also be used.

```
2598 \newcommand{\AMCqlabel}[1]{%
2599   \AMClabel{#1}%
2600 }
```

4.18 Pre-association

`\AMCassociation` Association between sheets and students can be made before the exam with the `\AMCassociation[<filename>]{<id>}` command. The optional argument `<filename>` will be used when printing student sheets to files.

```
2601 \newcommand{\AMCassociation}[2][]{%
2602   \ifAMC@calibration%
2603     \immediate\write\AMC@XYFILE{\string\association{\the\AMCid@etud}{#2}{#1}}%
2604   \fi%
2605 }
```

`\AMCstudentslistfile` You can also pass AMC the path to the CSV file with students, and the unique key that can be used, with `\AMCstudentslistfile{<path>}{<key>}`.

```
2606 \newcommand{\AMCstudentslistfile}[2]{%
2607   \ifAMC@calibration%
2608     \immediate\write\AMC@XYFILE{\string\with{studentslistfile=#1}}%
2609     \immediate\write\AMC@XYFILE{\string\with{studentslistkey=#2}}%
2610   \fi%
2611 }
```

4.19 Package options

See section 3.1 for the options descriptions.

```
2612 \def\AMC@lang@code{}
2613 \DeclareOptionX{noshuffle}{\AMC@ordretrue}
2614 \DeclareOptionX{noshufflegroups}{\AMC@shuffleGfalse}
2615 \DeclareOptionX{fullgroups}{\AMC@fullGroupstrue}
2616 \DeclareOptionX{answers}{\AMC@corretheadtrue\AMC@correcttrue}
2617 \DeclareOptionX{indivanswers}{\AMC@correcttrue}
2618 \DeclareOptionX{textpos}{\AMC@textPostrue}
2619 \DeclareOptionX{extractonly}{\AMC@extractOnlytrue\AMC@textPostrue\AMC@boxStyle{shape=none}\AMC@boxedAnswer}
2620 \DeclareOptionX{box}{\AMC@qbloctrue}
2621 \DeclareOptionX{asbox}{\AMC@asqbloctrue}
2622 \DeclareOptionX{separateanswersheet}{\AMC@ensembletrue}
2623 \DeclareOptionX{digits}{\AMC@inside@digittrue}
2624 \DeclareOptionX{ordre}{\AMC@ordretrue}
2625 \DeclareOptionX{correc}{\AMC@corretheadtrue\AMC@correcttrue}
2626 \DeclareOptionX{modele}{\AMC@corretheadtrue\AMC@correcfalse\AMC@ordretrue}
2627 \DeclareOptionX{correcindiv}{\AMC@correcttrue}
2628 \DeclareOptionX{init}{\ifx\NoWatermarkExterne\undefined\relax\AMC@SR@time\fi}
2629 \DeclareOptionX{bloc}{\AMC@qbloctrue}
2630 \DeclareOptionX{completemulti}{\AMC@complete@multitrue}
2631 \DeclareOptionX{insidebox}{\AMC@inside@boxtrue}
2632 \DeclareOptionX{ensemble}{\AMC@ensembletrue}
2633 \DeclareOptionX{chiffres}{\AMC@inside@digittrue}
2634 \DeclareOptionX{outsidebox}{\AMC@outside@boxtrue}
```

```

2635 \DeclareOptionX{calibration}{\AMC@calibrationtrue}
2636 \DeclareOptionX{nowatermark}{\AMC@watermarkfalse}
2637 \newcommand\AMC@keys@next{\AMC@keyslinefalse}
2638 \newcommand\AMC@keys@line{\AMC@keyslinetrue}
2639 \DeclareOptionX{catalog}{\AMC@catalogtrue}
2640 \DeclareOptionX{keys}[next]{\csname AMC@keys@#1\endcsname{}}
2641 \DeclareOptionX{francais}{\def\AMC@lang@code{FR}\AMC@loc@FR}
2642 \DeclareOptionX{lang}{\def\AMC@lang@code{#1}\csname AMC@loc@#1\endcsname}
2643 \DeclareOptionX{versionA}{%
2644   \def\AMCid@checkmax{31}\def\AMC@NCBetud{9}\def\AMC@NCBpage{4}%
2645   \def\AMC@NCBcheck{5}\setlength{\AMC@CBtaille}{4cm}%
2646   \def\AMC@premierecopie{100}}
2647 \DeclareOptionX{plain}{\AMC@plaintrue}
2648 \DeclareOptionX{nopage}{\AMC@pagelayoutfalse}
2649 \DeclareOptionX{postcorrect}{\AMC@postcorrecttrue}
2650 \DeclareOptionX{automarks}{\AMC@automarkstrue}
2651 \newif\ifAMCneeds@storebox\AMCneeds@storeboxfalse
2652 \DeclareOptionX{storebox}{\AMCneeds@storeboxtrue}
2653 \DeclareOptionX{pdfform}{\AMC@pdfformtrue}
2654 \DeclareOptionX{codedigit}{\AMC@codeID@{#1}}
2655 \newif\ifAMC@survey\AMC@surveyfalse
2656 \DeclareOptionX{survey}{\AMC@surveytrue}
2657 \ifx\AMCPackageOptionsExterne\undefined\else%
2658   \expandafter\ExecuteOptionsX\expandafter{\AMCPackageOptionsExterne}\fi
2659 \ProcessOptionsX
2660 \ifAMCneeds@storebox
2661   \RequirePackage{storebox}\AtBeginDocument{{}}%
2662 \fi
2663 \ifAMC@pdfform
2664   \AMCmessage{VAR:project:pdfform=1}%
2665   \AMCboxStyle{shape=form}%
2666   \RequirePackage[pageanchor=false]{hyperref}%
2667 \else%
2668   \AMCmessage{VAR:project:pdfform=0}%
2669 \fi
2670 \AtBeginDocument{%
2671   \ifAMCneeds@storebox%
2672     \let\AMC@new@savebox=\newstorebox%
2673     \let\AMC@save@box=\storebox%
2674     \let\AMC@use@box=\usestorebox%
2675   \fi%
2676   \AMC@new@savebox{\AMC@ovalbox@R}%
2677   \AMC@new@savebox{\AMC@ovalbox@RF}%
2678   \AMC@new@savebox{\AMC@ovalbox@}%
2679   \AMC@new@savebox{\AMC@ovalbox@F}%
2680   \AMC@shapeprepare%
2681 }

```

4.20 Survey add-on

Some code and *tikz* settings to help handling surveys, see https://survey.codes/pdf/surveyamc_manual.pdf for more details. This survey add-on is originally written by Claudia Saalbach.

```

questionnaires (env.)
  auto (env.) 2682 \ifAMC@survey
question-auto (env.) 2683 \NewEnviron{Questionnaires}[1]{
  values (env.) 2684 \onecopy{#1}{
  values-auto (env.) 2685 \BODY
variable-auto (env.) 2686 }
  \answer 2687 }
  2688 \NewEnviron{auto}[1]{
  2689 \csvreader[head to column names, separator=tab]{#1}{}{
  2690 \BODY
  2691 }
  2692 }
  2693 \NewEnviron{question-auto}[3]{
  2694 \csvreader[head to column names, separator=tab]{#1}{}{
  2695 \ifcsvstrcmp{#2}{#3}{\BODY \\\}
  2696 }
  2697 }
  2698 \newenvironment{values}{}{}
  2699 \NewEnviron{values-auto}[5]{
  2700 \csvreader[head to column names, separator=tab]{#1}{}{
  2701 \ifcsvstrcmp{#2}{#3}{
  2702 \ifcsvstrcmp{#4}{#5}{\BODY \\\}
  2703 }{}
  2704 }{}
  2705 }
  2706 }
  2707 \NewEnviron{variable-auto}[3]{
  2708 \foreach \x in {#3}{
  2709 \csvreader[head to column names, separator=tab]{#1}{}{
  2710 \ifcsvstrcmp{#2}{\x}{\BODY}{}
  2711 }
  2712 }
  2713 }
  2714 \newcommand{\answer}[5][\global\advance\AMCrep@count\@ne\relax%
  2715 \ifAMC@calibration\AMCmessage{REP=\the\AMCrep@count:B}\fi%
  2716 \global\AMCune@bonnettrue%
  2717 \AMCload@@reponse{\une@rep{\ifAMC@correc\AMC@box{#1}{\AMC@checkbox}%
  2718 \else\AMC@box{#1}{\fi}{#2}{#3}{#4}{#5}}{\the\AMCrep@count}\ignorespaces}
  2719 \RequirePackage{tikz}
  2720 \usetikzlibrary{positioning, shapes, arrows, tikzmark, decorations.pathreplacing}
  2721 \tikzset{
  2722 checkbox-sc/.style={
  2723 right=of lab\thecsvrow
  2724 },
  2725 vallab-sc/.style={
  2726 text width=4cm,
  2727 align=left,
  2728 },
  2729 checkbox-mc/.style={
  2730 },
  2731 vallab-mc/.style={
  2732 above=of box\thecsvrow,
  2733 text width=1.4cm,

```

```

2734     align=center,
2735   },
2736   varlab-mc/.style={
2737     text width=4cm,
2738     align=left,
2739   },
2740   node distance= 0mm,
2741 }
2742 \fi

```

4.21 Package Errors

`\AMC@error@explain` Error to display if `\explain` command is used outside question like environments

```

2743 \def\AMC@error@explain{\PackageError{automultiplechoice}{
2744   Command \protect\explain\space can only be used inside\MessageBreak question like environments}{Some
2745 }}

```

4.22 Optional features

This package tries to see if optional packages `environ` and `etex` are loadable, and load them if possible. This behaviour can be cancelled by using `plain` option.

```

2746 \ifAMC@plain
2747 \else
2748   \IfFileExists{environ.sty}{\RequirePackage{environ}}{}
2749   \ifx\etexversion\@undefined
2750   \else
2751     \RequirePackage{etex}
2752   \fi
2753 \fi

```

`examcopy` (*env.*) Then, if `environ` package is loaded and defines command `\NewEnviron`, environment `examcopy` is defined.

Environment `{examcopy}[\langle n \rangle]` does the same as command `onecopy`: it encloses `LATEX` code which makes *one* exam copy. Optional argument $\langle n \rangle$ gives the number of desired copies – this can also be modified redefinig `\AMCNombreCopies`.

```

2754 \@ifpackageloaded{environ}{%
2755   \ifx\NewEnviron\undefined\PackageWarning{automultiplechoice}%
2756     {Package environ loaded but too old version:
2757     environnement examcopy/copieexamen will NOT be defined.}%
2758   \else\NewEnviron{examcopy}[1][5]{\onecopy{#1}{\BODY}}\fi}%
2759 {\PackageWarning{automultiplechoice}%
2760   {Package environ not loaded: environnement
2761   examcopy/copieexamen will NOT be defined.}}

```

4.23 Use with recent LuaTeX versions

In recent LuaTeX versions, the commands `pdfsavepos`, `pdflastxpos` and `pdflastypos` has been renamed, stripping the `pdf` part. The following code tries to detect this situation and make the bindings between the old and new command names.

```

2762 \ExplSyntaxOn
2763

```

```

2764 \cs_if_exist:NTF \pdfsavepos { } {
2765   \cs_if_exist:NTF \savepos { \cs_new_eq:NN \pdfsavepos \savepos } { }
2766 }
2767 \cs_if_exist:NTF \pdflastxpos { } {
2768   \cs_if_exist:NTF \lastxpos { \cs_new_eq:NN \pdflastxpos \lastxpos } { }
2769 }
2770 \cs_if_exist:NTF \pdflastypos { } {
2771   \cs_if_exist:NTF \lastypos { \cs_new_eq:NN \pdflastypos \lastypos } { }
2772 }

```

In some situations, the *page* dimensions are different from the *paper* dimensions. This must be taken into account when computing coordinates.

```

2773
2774 \cs_if_exist:NTF \pdfpagewidth { } {
2775   \cs_new_eq:NN \pdfpagewidth \paperwidth
2776 }
2777 \cs_if_exist:NTF \pdfpageheight { } {
2778   \cs_new_eq:NN \pdfpageheight \paperheight
2779 }
2780
2781 \ExplSyntaxOff

```

4.24 External control

```

\SujetExterne Some of the package options can be controlled defining \xxxExterne commands. For example,
\ScoringExterne the following command will format the subject document, whatever options are used in the LATEX
\CorrigeExterne file:
\CorrigeIndivExterne pdfLaTeX '\nonstopmode\def\SujetExterne{1}\def\NoWatermarkExterne{1}\input{mcq.tex}'
\NoWatermarkExterne

2782 \def\AMC@randomseeds#1{%
2783   \ifx\pgfmath@rnd@z\undefined\relax
2784     \AMCmessage{VAR:pgfseed:#1=NONE}%
2785   \else%
2786     \pgfmathparse{\pgfmath@rnd@z}%
2787     \AMCmessage{VAR:pgfseed:#1=\pgfmathresult}%
2788   \fi%
2789 }
2790 \def\AMC@randomseeds#1{%
2791   \AtBeginDocument{\AMC@randomseeds@{#1}}%
2792 }
2793 \ifx\SujetExterne\undefined\else
2794   \message{***SUJET***^J}\AMC@randomseeds{subject}
2795   \AMC@catalogfalse\AMC@calibrationtrue\AMC@correcfalse\AMC@corretheadfalse\AMC@watermarkfalse
2796   \fi
2797 \ifx\ScoringExterne\undefined\else
2798   \message{***SCORING***^J}\AMC@randomseeds{scoring}
2799   \AMC@catalogfalse\AMC@calibrationtrue\AMC@correcfalse\AMC@corretheadfalse\AMC@watermarkfalse\AMC@invisib
2800   \fi
2801 \ifx\CorrigeExterne\undefined\else
2802   \message{***CORRIGE***^J}
2803   \AMC@catalogfalse\AMC@calibrationfalse\AMC@corretheadtrue\AMC@correcttrue\AMC@watermarkfalse
2804   \fi
2805 \ifx\CorrigeIndivExterne\undefined\else

```

```

2806 \message{***CORRIGE***^^J}\AMC@randomseeds{indivanswer}
2807 \AMC@catalogfalse\AMC@calibrationtrue\AMC@corretheadfalse\AMC@correcttrue\AMC@watermarkfalse
2808 \fi
2809 \ifx\CatalogExterne\undefined\else
2810 \message{***CATALOG***^^J}
2811 \AMC@catalogtrue
2812 \fi
2813 \ifx\NoWatermarkExterne\undefined\else
2814 \AMC@watermarkfalse
2815 \fi
2816 \ifx\codeDigitExterne\undefined\else
2817 \AMC@codeID@@{\codeDigitExterne}
2818 \fi
2819 \ifAMC@catalog
2820 \AMC@watermarkfalse\AMC@corretheadtrue%
2821 \AMC@correcttrue\AMC@ordretrue\AMC@shuffleGfalse%
2822 \AMC@fullGroupstrue%
2823 \def\AMC@intituleHead{\AMC@loc@catalog}\AMC@affichekeystrue
2824 \fi

```

4.25 Page layout

The following code sets the correct page layout to have room for signs for scan analysis, and prepares watermark printing:

```

2825 \@ifpackageloaded{geometry}{\usepackage{geometry}}
2826 \ifAMC@pagelayout
2827 \ifAMC@correthead
2828 \geometry{hmargin=3cm,vmargin={1cm,1cm},includeheadfoot,headheight=1cm,footskip=1cm}
2829 \else
2830 \geometry{hmargin=3cm,headheight=2cm,headsep=.3cm,footskip=1cm,top=3.5cm,bottom=2.5cm}
2831 \fi
2832 \ifAMC@watermark
2833 \ifAMC@correthead\else
2834 \def\AMC@note{\begin{minipage}{0.65\linewidth}
2835 \AMC@LR{\textcolor{blue}{\AMC@loc@message}}
2836 \end{minipage}}
2837 }
2838 \fi
2839 \fi
2840 \fi

```

4.26 Initialisation

Initialisation of the check counter:

```

2841 \AMCid@check=\AMCid@checkmax

```

Telling outside if separate answer sheet, and boxes labelling, are requested:

```

2842 \ifAMC@ensemble\AMCmessage{VAR:ensemble=1}\fi
2843 \ifAMC@inside@box\AMCmessage{VAR:insidebox=1}\fi
2844 \ifAMC@outside@box\AMCmessage{VAR:outsidebox=1}\fi
2845 \ifAMC@postcorrect\AMCmessage{VAR:postcorrect=1}\fi

```

Preparing writing to .xy file :

```

2846 \ifAMC@calibration
2847 \newwrite\AMC@XYFILE%
2848 \immediate\openout\AMC@XYFILE\jobname.xy%
2849 \immediate\write\AMC@XYFILE{\string\version{\AMC@VERSION}}
2850 \immediate\write\AMC@XYFILE{\string\with{codedigit=\AMCcodeID@mode}}
2851 \immediate\write\AMC@XYFILE{\string\with{version=\AMC@VERSION}}
2852 \immediate\write\AMC@XYFILE{\string\with{ensemble=\ifAMC@ensemble yes\else no\fi}}
2853 \immediate\write\AMC@XYFILE{\string\with{insidebox=\ifAMC@inside@box yes\else no\fi}}
2854 \immediate\write\AMC@XYFILE{\string\with{outsidebox=\ifAMC@outside@box yes\else no\fi}}
2855 \immediate\write\AMC@XYFILE{\string\with{postcorrect=\ifAMC@postcorrect yes\else no\fi}}
2856 \immediate\write\AMC@XYFILE{\string\with{extractonly=\ifAMC@extractOnly yes\else no\fi}}
2857 \immediate\write\AMC@XYFILE{\string\with{lang=\AMC@lang@code}}
2858 \ifx\AMCNombreCopies\undefined%
2859 \immediate\write\AMC@XYFILE{\string\with{ncopies=default}}}%
2860 \else%
2861 \immediate\write\AMC@XYFILE{\string\with{ncopies=\AMCNombreCopies}}}%
2862 \fi%
2863 \fi

```

4.27 French command names

For backward compatibility, a lot of commands have their french counterpart:

```

2864 \let\reponses=\choices\let\endreponses=\endchoices
2865 \let\reponseshoriz=\choiceshoriz\let\endreponseshoriz=\endchoiceshoriz
2866 \let\reponsesperso=\choicescustom\let\endreponsesperso=\endchoicescustom
2867 \let\bonne=\correctchoice
2868 \let\mauvaise=\wrongchoice
2869 \let\bareme=\scoring
2870 \let\baremeDefaultM=\scoringDefaultM
2871 \let\baremeDefaultS=\scoringDefaultS
2872 \def\exemplaire{\AMC@loc@FR\onecopy}
2873 \@ifpackageloaded{environ}{%
2874   \let\copieexamen=\examcopy\let\endcopieexamen=\endexamcopy}{%
2875   \let\melangegroupe=\shufflegroup
2876   \let\restituegroupe=\insertgroup
2877   \let\alafin=\lastchoices
2878   \let\formulaire=\AMCform
2879   \let\AMCdebutFormulaire=\AMCformBegin
2880   \let\champnom=\namefield
2881   \let\choixIntervalles=\AMCIntervals

```

5 Outputs

In the .xy file, $0/\langle n \rangle$ means student sheet number 0 (there is only one “student sheet” numbered 0 for this document as we did not use `\onecopy`) and page number $\langle n \rangle$ inside this student sheet. Then, each instance of the `\tracepos` command shows x and y positions as arguments #2 and #3 (unit is `sp`, such that $65536 \times 72.27\text{ sp}$ is one inch). One has to take min and max of the x -values to determine the left and right position of the box, and min and max values of y -values to determine top and bottom position of the box.

5.1 namefield command

Lines in the .xy file from a \namefield command:

```
\tracepos{0/35:--zone:id:--n}{0sp}{15446557sp}{square}  
\tracepos{0/35:--zone:id:--n}{5873801sp}{0sp}{square}  
\tracepos{0/35:--zone:id:--n}{15861297sp}{0sp}{square}  
\tracepos{0/35:--zone:id:--n}{0sp}{12461379sp}{square}
```

5.2 AMCboxedchar command

Lines in the .xy file from a \AMCboxedchar command:

```
\tracepos{0/36:test}{22855914sp}{38025531sp}{square}  
\tracepos{0/36:test}{23561334sp}{37320111sp}{square}
```

5.3 AMCcode command

Lines in the .xy file from a \AMCcode command. Here, `code[⟨n⟩]:⟨q⟩,⟨v⟩` relates to digit number ⟨n⟩ from the right (⟨n⟩=1 for units, ⟨n⟩=2 for tens, ⟨n⟩=3 for hundreds and so on), question number ⟨q⟩ (\AMCcode uses a fake question; this number can be ignored), and value ⟨v⟩-1 (box number ⟨v⟩ for the digit).

```
\tracepos{0/61:case:code[5]:16,1}{24875504sp}{41571962sp}{square}  
\tracepos{0/61:case:code[5]:16,1}{25580924sp}{40866542sp}{square}  
\boxchar{0/61:case:code[5]:16,1}{A}  
\tracepos{0/61:case:code[5]:16,2}{24875504sp}{40457850sp}{square}  
\tracepos{0/61:case:code[5]:16,2}{25580924sp}{39752430sp}{square}  
\boxchar{0/61:case:code[5]:16,2}{B}  
\tracepos{0/61:case:code[5]:16,3}{24875504sp}{39343738sp}{square}  
\tracepos{0/61:case:code[5]:16,3}{25580924sp}{38638318sp}{square}  
\boxchar{0/61:case:code[5]:16,3}{C}  
\tracepos{0/61:case:code[5]:16,4}{24875504sp}{38229626sp}{square}  
\tracepos{0/61:case:code[5]:16,4}{25580924sp}{37524206sp}{square}  
\boxchar{0/61:case:code[5]:16,4}{D}  
\tracepos{0/61:case:code[4]:17,1}{26540303sp}{43800186sp}{square}  
\tracepos{0/61:case:code[4]:17,1}{27245723sp}{43094766sp}{square}  
\boxchar{0/61:case:code[4]:17,1}{0}  
\tracepos{0/61:case:code[4]:17,2}{26540303sp}{42686074sp}{square}  
\tracepos{0/61:case:code[4]:17,2}{27245723sp}{41980654sp}{square}  
\boxchar{0/61:case:code[4]:17,2}{1}  
\tracepos{0/61:case:code[4]:17,3}{26540303sp}{41571962sp}{square}  
\tracepos{0/61:case:code[4]:17,3}{27245723sp}{40866542sp}{square}  
\boxchar{0/61:case:code[4]:17,3}{2}  
\tracepos{0/61:case:code[4]:17,4}{26540303sp}{40457850sp}{square}  
\tracepos{0/61:case:code[4]:17,4}{27245723sp}{39752430sp}{square}  
\boxchar{0/61:case:code[4]:17,4}{3}  
\tracepos{0/61:case:code[4]:17,5}{26540303sp}{39343738sp}{square}  
\tracepos{0/61:case:code[4]:17,5}{27245723sp}{38638318sp}{square}  
\boxchar{0/61:case:code[4]:17,5}{4}  
\tracepos{0/61:case:code[4]:17,6}{26540303sp}{38229626sp}{square}
```

```

\tracepos{0/61:case:code[4]:17,6}{27245723sp}{37524206sp}{square}
\boxchar{0/61:case:code[4]:17,6}{5}
\tracepos{0/61:case:code[3]:18,1}{28032160sp}{43800186sp}{square}
\tracepos{0/61:case:code[3]:18,1}{28737580sp}{43094766sp}{square}
\boxchar{0/61:case:code[3]:18,1}{0}
\tracepos{0/61:case:code[3]:18,2}{28032160sp}{42686074sp}{square}
\tracepos{0/61:case:code[3]:18,2}{28737580sp}{41980654sp}{square}
\boxchar{0/61:case:code[3]:18,2}{1}
\tracepos{0/61:case:code[3]:18,3}{28032160sp}{41571962sp}{square}
\tracepos{0/61:case:code[3]:18,3}{28737580sp}{40866542sp}{square}
\boxchar{0/61:case:code[3]:18,3}{2}
\tracepos{0/61:case:code[3]:18,4}{28032160sp}{40457850sp}{square}
\tracepos{0/61:case:code[3]:18,4}{28737580sp}{39752430sp}{square}
\boxchar{0/61:case:code[3]:18,4}{3}
\tracepos{0/61:case:code[3]:18,5}{28032160sp}{39343738sp}{square}
\tracepos{0/61:case:code[3]:18,5}{28737580sp}{38638318sp}{square}
\boxchar{0/61:case:code[3]:18,5}{4}
\tracepos{0/61:case:code[3]:18,6}{28032160sp}{38229626sp}{square}
\tracepos{0/61:case:code[3]:18,6}{28737580sp}{37524206sp}{square}
\boxchar{0/61:case:code[3]:18,6}{5}
\tracepos{0/61:case:code[2]:19,1}{29524017sp}{43800186sp}{square}
\tracepos{0/61:case:code[2]:19,1}{30229437sp}{43094766sp}{square}
\boxchar{0/61:case:code[2]:19,1}{0}
\tracepos{0/61:case:code[2]:19,2}{29524017sp}{42686074sp}{square}
\tracepos{0/61:case:code[2]:19,2}{30229437sp}{41980654sp}{square}
\boxchar{0/61:case:code[2]:19,2}{1}
\tracepos{0/61:case:code[2]:19,3}{29524017sp}{41571962sp}{square}
\tracepos{0/61:case:code[2]:19,3}{30229437sp}{40866542sp}{square}
\boxchar{0/61:case:code[2]:19,3}{2}
\tracepos{0/61:case:code[2]:19,4}{29524017sp}{40457850sp}{square}
\tracepos{0/61:case:code[2]:19,4}{30229437sp}{39752430sp}{square}
\boxchar{0/61:case:code[2]:19,4}{3}
\tracepos{0/61:case:code[2]:19,5}{29524017sp}{39343738sp}{square}
\tracepos{0/61:case:code[2]:19,5}{30229437sp}{38638318sp}{square}
\boxchar{0/61:case:code[2]:19,5}{4}
\tracepos{0/61:case:code[2]:19,6}{29524017sp}{38229626sp}{square}
\tracepos{0/61:case:code[2]:19,6}{30229437sp}{37524206sp}{square}
\boxchar{0/61:case:code[2]:19,6}{5}
\tracepos{0/61:case:code[1]:20,1}{31015874sp}{43800186sp}{square}
\tracepos{0/61:case:code[1]:20,1}{31721294sp}{43094766sp}{square}
\boxchar{0/61:case:code[1]:20,1}{0}
\tracepos{0/61:case:code[1]:20,2}{31015874sp}{42686074sp}{square}
\tracepos{0/61:case:code[1]:20,2}{31721294sp}{41980654sp}{square}
\boxchar{0/61:case:code[1]:20,2}{1}
\tracepos{0/61:case:code[1]:20,3}{31015874sp}{41571962sp}{square}
\tracepos{0/61:case:code[1]:20,3}{31721294sp}{40866542sp}{square}
\boxchar{0/61:case:code[1]:20,3}{2}
\tracepos{0/61:case:code[1]:20,4}{31015874sp}{40457850sp}{square}
\tracepos{0/61:case:code[1]:20,4}{31721294sp}{39752430sp}{square}

```

```

\boxchar{0/61:case:code[1]:20,4}{3}
\tracepos{0/61:case:code[1]:20,5}{31015874sp}{39343738sp}{square}
\tracepos{0/61:case:code[1]:20,5}{31721294sp}{38638318sp}{square}
\boxchar{0/61:case:code[1]:20,5}{4}
\tracepos{0/61:case:code[1]:20,6}{31015874sp}{38229626sp}{square}
\tracepos{0/61:case:code[1]:20,6}{31721294sp}{37524206sp}{square}
\boxchar{0/61:case:code[1]:20,6}{5}

```

Contents

1	Introduction	1
2	Samples	1
2.1	Standard layout	4
2.2	Separate answer sheet	5
2.3	Without markers	6
3	Usage	10
3.1	Package options	10
3.2	Questions and answers	11
3.3	Scoring	13
3.4	Groups of questions	14
3.5	Students identification	15
3.6	Separate answer sheet	16
3.7	Random computation questions	17
3.8	French command names	20
3.9	Customisation	21
3.9.1	Boxes	21
3.9.2	Codes	22
3.9.3	Answers	22
4	Implementation	23
4.1	Variables	23
4.2	Dimensions	26
4.3	Human readable sheet ID position	26
4.4	Localisation	27
4.4.1	English	27
4.4.2	Catalan	28
4.4.3	Dutch	28
4.4.4	French	28
4.4.5	German	29
4.4.6	Italian	29
4.4.7	Norwegian	29
4.4.8	Portuguese	30
4.4.9	Spanish	30
4.4.10	Japanese	30
4.4.11	Other languages	31
4.5	Interaction with other packages	31
4.5.1	cleveref	31
4.6	Random	31
4.6.1	Random pseudo-generator	31
4.6.2	Uniform random deviates	32
4.6.3	Tokens shuffling	32
4.7	Keys numbering	33
4.8	Boxes	33
4.8.1	Character logging	33
4.8.2	Position logging	33
4.8.3	Boxes to be checked by students	36

4.8.4	Scoring zones	41
4.8.5	Binary boxes	41
4.9	Checking Environment	43
4.10	Handling groups of questions	43
4.11	Questions	47
4.11.1	Managing answers	48
4.11.2	Separate answer sheet	49
4.11.3	Formatting answers	54
4.11.4	Score zones	56
4.11.5	Formatting questions	58
4.11.6	Explanations	60
4.12	Scoring	60
4.13	Numerical data	61
4.13.1	Codes	61
4.13.2	Numerical questions	64
4.13.3	Intervals	80
4.14	Open questions	81
4.15	Boxes with letters only	84
4.16	Page formatting	85
4.16.1	Watermark	85
4.16.2	Signs for scan analysis	85
4.17	Defining a single exam copy content	87
4.18	Pre-association	89
4.19	Package options	89
4.20	Survey add-on	90
4.21	Package Errors	92
4.22	Optional features	92
4.23	Use with recent LuaTeX versions	92
4.24	External control	93
4.25	Page layout	94
4.26	Initialisation	94
4.27	French command names	95
5	Outputs	95
5.1	<code>namefield</code> command	96
5.2	<code>AMCboxedchar</code> command	96
5.3	<code>AMCcode</code> command	96

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined> refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

Symbols	1493,	1495,	1498,	1884,	1885,	1887,
\"	1499,	1500,	1501,	1889,	1892,	1897,
\@aucune	1503,	1505,	1508,	1898,	1900,	1904,
\@firstoftwo	1509,	1511,	1512,	1906,	1909,	1910,
\@ifl@t@r	1514,	1515,	1516,	1911,	1912,	1913,
\@ifstar	1517,	1537,	1538,	1915,	1916,	1917,
\@secondoftwo	1543,	1544,	1545,	1921,	1922,	1923,
\@skiphyperreffalse	1546,	1547,	1548,	1924,	1928,	1931,
\@skiphyperreftrue	1553,	1555,	1556,	1936,	1938,	1941,
\@tempboxa	1557,	1558,	1559,	1944,	1946,	1947,
\@tempdimb	1561,	1563,	1564,	1948,	1952,	1953,
\@tempdimc	1565,	1566,	1569,	1954,	1957,	1960,
_	1576,	1577,	1578,	1964,	1968,	1970,
\~	1580,	1582,	1583,	1972,	1975,	1980,
	1585,	1587,	1589,	1983,	1984,	1992,
	1592,	1593,	1595,	1998,	1999,	2006,
	1597,	1598,	1599,	2007,	2009,	2010,
	1601,	1607,	1612,	2011,	2013,	2016,
	1624,	1662,	1664,	2017,	2020,	2021,
	1666,	1668,	1670,	2023,	2029,	2033,
	1672,	1675,	1678,	2034,	2036,	2039,
	1681,	1684,	1687,	2040,	2047,	2057,
	1690,	1693,	1696,	2058,	2059,	2060,
	1699,	1702,	1704,	2061,	2062,	2063,
	1706,	1709,	1718,	2064,	2065,	2066,
	1720,	1728,	1732,	2068,	2073,	2074,
	1733,	1734,	1740,	2077,	2083,	2085,
	1742,	1754,	1755,	2087,	2088,	2091,
	1756,	1757,	1758,	2092,	2096,	2097,
	1759,	1760,	1761,	2098,	2100,	2101,
	1764,	1767,	1771,	2103,	2104,	2105,
	1774,	1775,	1779,	2106,	2107,	2109,
	1783,	1784,	1788,	2110,	2113,	2115,
	1792,	1793,	1797,	2120,	2121,	2122,
	1802,	1804,	1806,	2123,	2125,	2126,
	1813,	1815,	1818,	2127,	2128,	2129,
	1827,	1828,	1829,	2130,	2131,	2134,
	1830,	1831,	1832,	2135,	2136,	2137,
	1834,	1837,	1839,	2141,	2143,	2145,
	1840,	1841,	1842,	2148,	2153,	2154,
	1848,	1849,	1851,	2155,	2156,	2157,
	1852,	1853,	1854,	2158,	2159,	2161,
	1855,	1856,	1857,	2162,	2163,	2164,
	1859,	1860,	1861,	2168,	2169,	2171,
	1863,	1865,	1867,	2177,	2184,	2189,
	1870,	1872,	1874,	2191,	2192,	2198,
	1876,	1882,	1883,	2207,	2209,	2210,

A

\aa	177
\AddToHook	2494
\alafin	21, 2877
\amc	233, 234, 236, 237, 238,
	239, 242, 245, 247,
	248, 249, 252, 254,
	896, 907, 909, 911,
	912, 914, 917, 918,
	920, 923, 924, 927,
	928, 929, 930, 932,
	934, 935, 937, 939,
	940, 942, 944, 945,
	948, 949, 951, 952,
	954, 955, 957, 958,
	960, 961, 963, 966,
	967, 969, 971, 975,
	976, 977, 978, 1389,
	1390, 1391, 1392,
	1393, 1394, 1395,
	1397, 1404, 1407,
	1412, 1416, 1424,
	1427, 1428, 1429,
	1432, 1437, 1439,
	1442, 1443, 1444,
	1445, 1447, 1449,
	1451, 1452, 1454,
	1455, 1459, 1460,
	1461, 1463, 1464,
	1465, 1467, 1472,
	1474, 1476, 1484,
	1489, 1490, 1491,

2211, 2212, 2216, 2217, 2218, 2222, 2223, 2224, 2225, 2227, 2228, 2229, 2242, 2244, 2250, 2259, 2262, 2263, 2269, 2270, 2271, 2272, 2273, 2274, 2275, 2277, 2278, 2281, 2404, 2407, 2408	\AMC@fillcolor@ 408, 426, 427, 443, 448	\AMC@loc@none . . 103, 116, 129, 143, 157, 170, 183, 196, 209, 222, 869
\AMC@addpages 2577, 2579, 2581	\AMC@fin@rep . . 856, 1118, 1122, 1126, 1129, 1132	\AMC@loc@PT 188
\AMC@affiche 307, 1299	\AMC@formBox 548	\AMC@loc@q 99, 112, 126, 139, 153, 167, 180, 192, 206, 218, 1291
\AMC@amclog 19	\AMC@formBox@ 548	\AMC@loc@qf 98, 111, 125, 138, 152, 166, 179, 191, 205, 217, 878
\AMC@answerBox 506	\AMC@formcolspecs 1035, 1089	\AMC@loc@question 104, 117, 130, 144, 158, 171, 184, 197, 210, 223, 229
\AMC@answerBox@ . . . 387, 514, 561, 563, 579, 581, 647, 649, 657, 659	\AMC@formspecs . . 1026, 1041	\AMC@loc@questions 105, 118, 131, 145, 159, 172, 185, 198, 211, 224, 229
\AMC@binaryBoxes 680	\AMC@fullGroupsfalse . . . 36	\AMC@logchar 315, 416
\AMC@binaryCode . . . 630, 681, 2480, 2481, 2482	\AMC@fullGroupstrue 2615, 2822	\AMC@logfile . 19, 20, 21, 316
\AMC@box 548, 1168, 1169, 1173, 2717, 2718	\AMC@if@separate@question 907, 982, 987, 995, 1001, 1522, 2254, 2400, 2443	\AMC@LR 23, 418, 2452, 2503, 2504, 2505, 2506, 2507, 2835
\AMC@boxcolor 405, 531, 2364	\AMC@imax . 741, 753, 754, 755	\AMC@makeovalbox 441, 460, 461, 462, 463
\AMC@boxcolor@ 405, 406, 407, 409, 427, 436, 448, 452, 469	\AMC@intituleHead 2476, 2497, 2823	\AMC@mem@add 937, 983, 990, 997, 1004, 1523
\AMC@boxeddown 419, 519, 530	\AMC@keepmemoryfalse . . 2567	\AMC@mem@add@ifneeded 894, 1331
\AMC@boxedheight 432, 446, 447, 449, 450, 453, 454, 498, 521, 525, 526, 538, 541	\AMC@keepmemorytrue . . . 1023	\AMC@mem@addsingle@ifneeded 986, 1099, 1101, 1103, 1105
\AMC@boxedrule 424, 446, 447, 448, 517, 528	\AMC@keyBox@ 577, 1415, 1747, 1750	\AMC@mem@addvar 942
\AMC@boxedwidth 435, 446, 447, 449, 450, 453, 454, 498, 520, 525, 527, 538, 539, 1069, 1905	\AMC@keys@line 2638	\AMC@mem@aid 961, 996
\AMC@CBtaille 628, 2508, 2645	\AMC@keys@next 2637	\AMC@mem@answer 993, 1133, 1140, 1141, 1142, 1147, 1153
\AMC@checkbox 387, 408, 411, 461, 463, 473, 479, 489, 647, 649, 1168, 1745, 1765, 1779, 1784, 2717	\AMC@lang@code 2612, 2641, 2642, 2857	\AMC@mem@category . 955, 989, 2254, 2400, 2443
\AMC@chiffres 1377	\AMC@loc@CA 107	\AMC@mem@clear . . . 912, 2569
\AMC@coli 1034, 1038, 1039, 1040	\AMC@loc@catalog 101, 114, 128, 141, 155, 169, 182, 194, 208, 220, 2823	\AMC@mem@next 932, 988, 1002
\AMC@crosschar 430, 533	\AMC@loc@corrected 100, 113, 127, 140, 154, 168, 181, 193, 207, 219, 2476	\AMC@mem@openQuestion 1000, 1330
\AMC@crossrule 452, 518, 534	\AMC@loc@DE 148	\AMC@mem@qidaffname 949, 1003
\AMC@definitnumero . 308, 312	\AMC@loc@draft . . 95, 108, 122, 135, 149, 163, 176, 189, 202, 215, 2447	\AMC@mem@show 976, 1013, 1022
\AMC@draw@crossfalse . . 410	\AMC@loc@ES 201	\AMC@mem@show@filter 977, 1017
\AMC@draw@crosstrue . . . 412	\AMC@loc@explain 102, 115, 142, 156, 195, 221, 1363	\AMC@mn@leftmargin 1179, 1187, 1190, 1196
\AMC@error@explain 1363, 1365, 2743	\AMC@loc@FR . . 134, 2641, 2872	\AMC@mn@rightmargin 1180, 1188, 1191, 1194
	\AMC@loc@IT 162	\AMC@mn@sep . 1178, 1194, 1196
	\AMC@loc@JA 214	\AMC@mn@test 1177, 1184, 1193
	\AMC@loc@message 96, 109, 123, 136, 150, 164, 177, 190, 203, 216, 2835	
	\AMC@loc@namesurname 106, 119, 132, 146, 160, 173, 186, 199, 212	
	\AMC@loc@NL 121	
	\AMC@loc@NO 175	

\AMC@multi@report	1442, 2575	\AMC@setcolors@		\AMC@sz@callin	
\AMC@multiclear	1447, 2566		404, 425, 442, 467	..	1212, 1217, 1225,
\AMC@NCBcheck	624, 2482, 2645	\AMC@shape@form		1227, 1292, 1326, 1327	
\AMC@NCBetud	624, 2480, 2644	\AMC@shape@form@base	488, 502	\AMC@sz@callin@question	1202
\AMC@NCBpage	624, 2481, 2644	\AMC@shape@form@ticked		\AMC@sz@callout	
\AMC@new@savebox			490, 492, 495		1211, 1216,
.....	388, 2672,	\AMC@shape@none		1220, 1222, 1319, 1320	
2676, 2677, 2678, 2679		\AMC@shape@oval		\AMC@sz@callout@margin	1204
\AMC@note	 2477,	\AMC@shape@square		\AMC@sz@callout@margin	1207
2478, 2516, 2526, 2834		\AMC@shapename		\AMC@sz@depth	1200, 1210, 1215
\AMC@numeric@alsocorrect			321, 329, 338, 347, 524	\AMC@sz@height	
.....	1724,	\AMC@shapename@	321, 419, 535		1200, 1209, 1214
2180, 2184, 2194, 2198		\AMC@shapeprepare		\AMC@sz@init@margin	1206
\AMC@numeric@keepas			535, 543, 2680	\AMC@sz@width	1200, 1208, 1213
.....	1722, 2173, 2174	\AMC@shapeprepare@form	487	\AMC@sza@box	1235, 1243, 1246
\AMC@numeric@scoreapprox		\AMC@shapeprepare@none	504	\AMC@sza@callin	888, 889,
.....	1714, 2139, 2149	\AMC@shapeprepare@oval	458	1257, 1262, 1270, 1272	
\AMC@numeric@scoreexact		\AMC@shapeprepare@square	422	\AMC@sza@callin@margin	1247
.....	1712, 2138, 2144	\AMC@shuffletoks		\AMC@sza@callin@margin	1251
\AMC@numeric@scorewrong			288, 774, 777, 849	\AMC@sza@callin@none	1239
.....	1716, 2146, 2149	\AMC@smashbox	.. 392, 395,	\AMC@sza@callin@question	
\AMC@numeration		396, 397, 398, 399, 402			1243
.....	307, 311, 312	\AMC@smashboxheight		\AMC@sza@callout	884, 885,
\AMC@outside@sep	.. 523, 529		393, 396, 397, 398, 401	1256, 1261, 1265, 1267	
\AMC@oval@radius		\AMC@smashcentered		\AMC@sza@callout@margin	1246
.....	448, 522, 539, 541		394, 436, 437, 469, 470	\AMC@sza@callout@margin	
\AMC@ovalbox@	462, 476, 2678	\AMC@SR			1250
\AMC@ovalbox@F	463, 474, 2679		257,	\AMC@sza@callout@none	1238
\AMC@ovalbox@R			259, 262, 263, 264,	\AMC@sza@callout@question	
.....	459, 460, 482, 2676	\AMC@SR@count			1242
\AMC@ovalbox@RF	461, 480, 2677		262,	\AMC@sza@depth	
\AMC@pageHook	2487, 2494, 2495		263, 265, 273, 277,		1235, 1255, 1260
\AMC@pagepos	 321, 2488		280, 283, 284, 285, 286	\AMC@sza@height	
\AMC@premierecopie		\AMC@SR@time			1235, 1254, 1259
..	629, 2550, 2553, 2646	\AMC@SR@advance	260, 267, 268	\AMC@sza@init@margin	1245
\AMC@prepare	.. 310, 313, 314	\AMC@SR@bit		\AMC@sza@init@margin	1249
\AMC@prepare@element	...	\AMC@SR@const	.. 258, 262, 265	\AMC@sza@init@none	1237
.....	704, 712, 827	\AMC@SR@max		\AMC@sza@init@question	1241
\AMC@printf@outside@false		\AMC@SR@nextByte		\AMC@sza@width	
.....	552	\AMC@SR@num	275, 276, 278,		1235, 1253, 1258
\AMC@printf@outside@true		279, 283, 286, 301, 302		\AMC@tempenv	
.....	554, 555	\AMC@SR@set	259, 271, 272, 274	\AMC@tf@colW	
\AMC@printf@key@outside@false		\AMC@SR@test		..	1068, 1069, 1072, 1078
.....	569	\AMC@SR@value		\AMC@tf@idtext	
\AMC@printf@key@outside@true		\AMC@stepQuestion		..	1049, 1054, 1071, 1074
.....	571, 573		1281, 1316, 1356	\AMC@tf@idtitle	
\AMC@qaff	 879,	\AMC@sti	288, 296, 300, 303, 304		1027, 1050, 1055
1281, 1324, 1325, 1359		\AMC@stil		\AMC@tf@nanswers	1052,
\AMC@randomseeds			297, 298, 299, 301, 305	1065, 1066, 1078, 1089	
..	2790, 2794, 2798, 2806	\AMC@surveyfalse		\AMC@tf@ncols	1045, 1053,
\AMC@randomseeds@	2782, 2791	\AMC@surveytrue		1077, 1085, 1089, 1093	
\AMC@save@box	389, 444, 2673	\AMC@sz@box		\AMC@tfaw	
		1202, 1204, 1207, 1250		..	1048, 1081, 1083, 1084

\AMC@tfbox . 1051, 1074, 1075	\AMCbin@zero . . 651, 670, 675	\AMCformAfterQuestion . .
\AMC@tfcolw . . 1047, 1078,	\AMCbloc 1297	 877, 1331
1079, 1080, 1083, 1084	\AMCbo@help . 2411, 2412, 2425	\AMCformAnswer 876, 1031, 1072
\AMC@tracebox	\AMCboHide 2438, 2444	\AMCformAnswerA . . . 893, 997
. 321, 375, 468, 494,	\AMCboOpts 2415	\AMCformatChoices
612, 614, 617, 1149, 2470	\AMCboShow 2416, 2444	. 1520, 2255, 2401, 2444
\AMC@tracechar 363, 565, 583	\AMCbotextGoto . . 2410, 2439	\AMCformBeforeQuestion .
\AMC@tracepos	\AMCboxColor 546, 2508	 876, 882, 1070
. 322, 433, 439,	\AMCboxDimensions . 547, 664	\AMCformBegin . 16, 894, 2879
1135, 1138, 1322, 1331	\AMCBoxedAnswers 1108, 2619	\AMCformFilter 1015
\AMC@traceposx . . . 331, 351	\AMCBoxOnly 2410	\AMCformHSpace . . 68, 892,
\AMC@traceposy 340, 350, 352	\AMCboxOutsideLetter . .	1027, 1068, 1071, 2422
\AMC@unnumero 307	 548, 2354, 2423	\AMCformQuestion . 876, 1071
\AMC@use@box 390,	\AMCboxStyle	\AMCformQuestionA 880, 1004
474, 476, 480, 482, 2674	 21, 517, 2619, 2665	\AMCformQuestionN . 879, 887
\AMC@VERSION 2849, 2851	\AMCccircle 2466, 2469	\AMCformS 894
\AMC@watertext . . 2447, 2458	\AMCchoiceLabel	\AMCformTH
\AMC@XYFILE 324, 333, 342,	. . . 506, 587, 1031, 1094	. . 1027, 1046, 1056,
354, 359, 360, 361,	\AMCchoiceLabelFormat . .	1071, 1073, 1075, 1079
365, 371, 373, 1302,	 420, 506	\AMCformVSpace
1325, 1439, 2559,	\AMCcleardoublepage 16, 2586	 68, 876, 1070, 1090
2603, 2608, 2609,	\AMCcode 1516	\AMCgroup@pre 770, 793
2847, 2848, 2849,	\AMCcodeGrid 15, 1377	\AMCgrouploop@next
2850, 2851, 2852,	\AMCcodeGridInt . . 15, 1377	 795, 808, 826
2853, 2854, 2855,	\AMCcodeH 1517	\AMCgrouploop@prep
2856, 2857, 2859, 2861	\AMCcodeHspace	 781, 806, 824
\AMCaddpagesto 2577	 1378, 1419, 1478	\AMCgrouppre@cyclic . . 764
\AMCanswer	\AMCcodeID 1383, 1458	\AMCgrouppre@fixed . . . 726
. 1153, 1154, 2353, 2422	\AMCcodeID@@	\AMCgrouppre@withoutreplacement
\AMCassociation 2601	. 1382, 1386, 2654, 2817	 742
\AMCbeforeQuestion	\AMCcodeID@dot 1381	\AMCgrouppre@withreplacement
. 1290, 1318, 1399	\AMCcodeID@mode . 1384, 2850	 733
\AMCbeginAnswer	\AMCcodeID@squarebrackets	\AMChorizAnswerSep
. 1125, 1154, 2352, 2421	 1380	 1143, 1144, 1152
\AMCbeginQuestion	\AMCcodeVspace	\AMChorizBoxSep
. 1290, 1324,	. 1379, 1417, 1477, 1480	. 1145, 1146, 1149, 1151
1339, 1345, 1359, 1398	\AMCcompleteMulti . . 12, 65	\AMCid@check
\AMCbin@begin 679	\AMCcurrentenv 683, 686, 1315	29, 356, 2482, 2489,
\AMCbin@did 634, 642, 645,	\AMCdebutFormulaire 21, 2879	2490, 2509, 2513, 2841
647, 652, 655, 657, 663	\AMCdecimalPoint	\AMCid@checkmax
\AMCbin@digit	 1646, 1901, 1942	. . 624, 2490, 2644, 2841
. 632, 665, 668, 674, 677	\AMCdefault@groupmode . .	\AMCid@etud . 30, 318, 326,
\AMCbin@hsep 636, 639, 643, 653	 701, 715, 716	335, 344, 356, 359,
\AMCbin@id 633,	\AMCdontAnnotate . 359, 2369	360, 361, 366, 381,
638, 646, 647, 656, 657	\AMCdontScan 359, 2367	502, 325, 2479, 2480,
\AMCbin@endigits	\AMCdump@reponses . 849, 863	2509, 2513, 2521,
. . . . 635, 637, 674, 677	\AMCemptybox 1175, 1200, 1235	2549, 2550, 2552,
\AMCbin@number	\AMCendAnswer	2560, 2565, 2572,
. 631, 664, 667, 669, 671	. 1126, 1154, 2352, 2421	2573, 2593, 2594, 2603
\AMCbin@one 641, 669	\AMCexponent 1648, 2214, 2226	\AMCid@etudfin 32,
\AMCbin@sequence . . 630,	\AMCexternalQuestion . . 1306	2551, 2552, 2553, 2572
664, 669, 670, 675, 676	\AMCfilterRefs 245	\AMCid@etudstart
\AMCbin@style 640, 664	\AMCform . 16, 894, 1095, 2878	 31, 2549, 2573

\AMCid@name	1311, 1331, 1335,	\AMCnumericChoicesPlain	 2253, 2260
.. 67, 593, 596, 598,	1340, 1346, 1373,	\AMCnumericHide ..	2250, 2255
602, 604, 946, 1003,	1374, 1375, 1376,	\AMCnumericOpts	1740
1135, 1138, 1149,	1414, 1528, 1744,	\AMCnumericShow ..	2242, 2255
1299, 1302, 1331,	1777, 1780, 1786,	\AMCnumero	1282, 2564
1415, 1747, 1750, 2296	1789, 1795, 1798,	\AMCocol@Background	2286, 2293, 2358
\AMCid@quest	1807, 1820, 1867,	\AMCocol@BoxFrameRule ..	 2287, 2311, 2358
359, 360, 361, 593,	1891, 2012, 2015,	\AMCocol@Foreground	2289, 2294,
596, 598, 602, 604,	2048, 2050, 2070,	2363, 2364, 2374, 2377	
612, 614, 617, 945,	2135, 2142, 2159,	\AMCocol@FrameRule	2288, 2312, 2385
1003, 1135, 1138,	2161, 2164, 2166,	\AMCOpen	2284
1149, 1299, 1301,	2169, 2171, 2174,	\AMCopen@answer	2290, 2297, 2326, 2342
1302, 1322, 1325,	2178, 2181, 2183,	\AMCopen@boxframerule ..	 2309, 2310, 2357
1331, 1415, 1748,	2190, 2195, 2197,	\AMCopen@boxmargin	2307, 2308, 2356
1751, 2070, 2335, 2418	2237, 2335, 2392,	\AMCopen@contentcommand	 2298, 2386
\AMCIDBoxesA	2418, 2435, 2547,	\AMCopen@framerule	2313, 2314, 2384
\AMCIDBoxesABC ..	2565, 2664, 2668,	\AMCopen@Hspace ..	2299,
\AMCIDBoxesB	2715, 2784, 2787,	2300, 2355, 2360, 2372	
\AMCIDBoxesC	2842, 2843, 2844, 2845	\AMCopen@LineHeight	2303, 2304, 2325
\AMCids@height ..	79, 90, 2509	\AMCopen@Lines	2305, 2306, 2330
\AMCids@sidefalse ...	82, 84	\AMCopen@lines	2323
\AMCids@sidetrue	86	\AMCopen@lineuptext	2292,
\AMCids@topfalse	82, 86	2315, 2340, 2343, 2346	
\AMCids@toptrue	84	\AMCopen@question	2291, 2296, 2359, 2360
\AMCids@width ..	78, 89, 2512	\AMCopen@Width	2301, 2302, 2324
\AMCidsPosition	76	\AMCopenHide	2395, 2401
\AMCidsVar	80	\AMCopenOpts	2322
\AMCidsVarN	80, 81	\AMCopenShow	2333, 2401
\AMCif@env ..	684, 1363, 1365	\AMCOpenX	2408
\AMCifcategory	978	\AMCotextGoto ...	2284, 2396
\AMCinterBquest ...	73, 1331	\AMCotextReserved	2285,
\AMCinterBrep	68, 1139	2295, 2371, 2375, 2377	
\AMCinterIquest ...	72, 1331	\AMCoutsideLabelFormat	548
\AMCinterIrep	68, 1116	\AMCPackageOptionsExterne	 2657, 2658
\AMCIntervalFormat	2266, 2277	\AMCpageref	2597
\AMCIntervals	17, 2266, 2881	\AMCpostNquest	74, 2235
\AMClabel	2594, 2599	\AMCpostOquest	75, 2388
\AMCload@@reponse ..	860,	\AMCqlabel	2598
862, 1168, 1173, 2717			
\AMCload@counter			
.. 27, 838, 839, 840,			
841, 844, 845, 849,			
852, 853, 854, 855, 858			
\AMCload@reponse ..	843, 862		
\AMClocalized	94		
\AMCloop@k	747, 753,		
757, 759, 780, 788, 797			
\AMCmarginNote			
..... 1181, 1207, 1250			
\AMCmem@elt@cat	952, 964, 968		
\AMCmessage	19, 308,		
620, 1022, 1166, 1172,			
1301, 1309, 1310,			
\AMCnarray@Border	1652, 1846, 1847, 1991		
\AMCnarray@BorderWidth ..	 1654, 1844, 1989		
\AMCncol@Background	1660, 1846, 1991, 2206		
\AMCncol@Border ..	1656, 2206		
\AMCncol@BorderWidth ...	 1658, 2205		
\AMCneeds@storeboxfalse	2651		
\AMCneeds@storeboxtrue	2652		
\AMCnobloc	1296, 1403		
\AMCnoCompleteMulti	12, 66, 2351		
\AMCnombreCopies	2545, 2546, 2858, 2861		
\AMCnoScoreZone ..	1280, 1400		
\AMCnontextGoto ...	1637, 2246		
\AMCnontextSign	1644, 1966, 1967		
\AMCnontextVHead	1638, 1905, 2080		
\AMCnum@copies ..	33, 2545,		
2546, 2547, 2548, 2551			
\AMCnum@questions ..	850, 852		
\AMCnumeric@Hspace	1639, 1651, 1808,		
1810, 1901, 1929,			
1985, 1987, 1994, 2226			
\AMCnumeric@Vspace	1640, 1650,		
1776, 1785, 1794,			
1822, 1893, 1907,			
1958, 1967, 2213, 2215			
\AMCnumericChoices ..	18, 1520		

\ifAMC@fullGroups .. 36, 783	\ifcsname ... 1219, 1224,	2016, 2020, 2023,
\ifAMC@inside@box	1229, 1264, 1269, 1274	2029, 2033, 2034,
..... 54, 573, 601,	\ifcsvstrcmp	2039, 2040, 2061,
2354, 2423, 2843, 2853	. 2695, 2701, 2702, 2710	2062, 2063, 2066,
\ifAMC@inside@digit . 57, 507	\ifdim	2073, 2074, 2081,
\ifAMC@invisible ... 63, 321	\ifKV@AMCBoxOnly@ordered	2082, 2088, 2091,
\ifAMC@keepmemory 1019, 2569	 2426	2092, 2098, 2103,
\ifAMC@keyline 39, 1323, 1324	\ifKV@AMCdim@cross	2105, 2109, 2122,
\ifAMC@ordre 34, 857	 411, 426, 443	2123, 2128, 2136,
\ifAMC@outside@box	\ifKV@AMCOpen@annotate 2369	2137, 2143, 2145,
55, 553, 571, 2844, 2854	\ifKV@AMCOpen@dots 2327	2148, 2156, 2163,
\ifAMC@pagelayout	\ifKV@AMCOpen@lineup ...	2164, 2168, 2169,
... 60, 2489, 2536, 2826	 2338, 2381	2171, 2184, 2191,
\ifAMC@pdfform	\ifKV@AMCOpen@retick .. 2368	2192, 2198, 2212, 2225
64, 379, 2556, 2574, 2663	\ifKV@AMCOpen@scan 2367	
\ifAMC@plain 50, 2746	\ifKV@AMCtf@headers ... 1088	K
\ifAMC@postcorrect	\ifKV@AMCtf@inside 1094	\keys 1423, 1450,
.... 61, 874, 2845, 2855	\ifSurveySingleAnswer ..	1643, 1729, 2072, 2245
\ifAMC@printformoutside	 1337, 1340, 1346	keys (option) 10
..... 551, 560	indivanswers (option) . 6, 10	
\ifAMC@printformoutside@	init (option) 10	L
..... 550, 557	\InputIfFileExists 17	\l 2081, 2085
\ifAMC@printkeyoutside .	\insertgroup .. 14, 773, 2876	\lastchoices 856, 2877
..... 568, 578	\insertgroupfrom ... 14, 773	\lastxpos 2768
\ifAMC@printkeyoutside@	insidebox (option) 10	\lastypos 2771
..... 567, 575	\int 909, 911, 915, 921, 928,	\linebreak 2349
\ifAMC@qbloc ... 43, 1290,	967, 1391, 1404, 1443,	M
1322, 1331, 1358,	1445, 1454, 1460,	\m@rque 2470,
1360, 2247, 2397, 2440	1461, 1484, 1548,	2503, 2504, 2505, 2506
\ifAMC@rbloc . 45, 1115, 1118	1564, 1592, 1595,	\m@rqueCalage ... 2469, 2470
\ifAMC@shuffleG 35, 774, 777	1597, 1598, 1599,	\marginpar 1204, 1246
\ifAMC@survey ... 2655, 2682	1601, 1614, 1617,	\mauvaise 21, 2868
\ifAMC@textPos . 41, 1135,	1619, 1625, 1626,	\melangegroupe 21, 2875
1138, 1148, 1322, 1331	1628, 1629, 1631,	\MessageBreak 2744
\ifAMC@watermark	1734, 1754, 1757,	\multicolsep 1090
..... 53, 2491, 2832	1759, 1760, 1761,	\multiSymbole 1290, 1333, 1352
\ifAMC@zoneformulaire ..	1763, 1772, 1803,	
..... 59, 555, 592, 898	1814, 1821, 1827,	N
\ifAMCcomplete@multi 46, 871	1828, 1829, 1830,	\namefield ... 15, 376, 2880
\ifAMCformulaire@dedans	1831, 1841, 1849,	\namefielddots 377
..... 58, 554,	1851, 1852, 1853,	\newbox 392, 1051
595, 611, 2069, 2236,	1855, 1856, 1857,	\newline 1323
2334, 2391, 2417, 2434	1859, 1863, 1865,	\newsavebox 388
\ifAMCids@side 77, 2512	1867, 1870, 1872,	\newstorebox 2672
\ifAMCids@top 76, 2509	1874, 1876, 1882,	\next@Answer 1157, 1165, 1171
\ifAMCneeds@storebox ...	1884, 1886, 1892,	\nobreak 549, 2382
..... 2651, 2660, 2671	1898, 1900, 1905,	\node 1140, 1141, 1348
\ifAMCquestionNumber 47, 1288	1909, 1912, 1916,	nopage (option) 6, 11
\ifAMCsz@logged ... 608, 619	1922, 1928, 1931,	noshuffle (option) 10
\ifAMCtype@multi ... 52, 871	1938, 1940, 1944,	noshufflegroups (option) . 10
\ifAMCune@bonne 51, 873	1947, 1953, 1957,	\nouveau groupe 692, 817
\ifcase 81	1960, 1969, 1983,	nowatermark (option) .. 4, 10
	2009, 2010, 2013,	

\NoWatermarkExterne	 1185	\shufflegroup	 14, 739, 751, 773, 2875
..... 2628, 2782	\pgfpointdiff	 1184	
O	\pgfpointorigin	 1184	\shufflegroupslice
\oddsidemargin .. 1187, 1191	plain (option)	 11	 756, 759, 776
\onecopy 2544, 2684, 2758, 2872	postcorrect (option)	 11	\smash
options:	\prg	 896, 899, 901, 904, 1500, 1596, 1609	 2326, 2342
answers	 10		\space
asbox	 10		 2744
automarks	 11	Q	\start@Answers .. 1109, 1304
bloc	 21	\question	 1295, 1302
box	 10	question (env.)	 11, 1295
calibration	 5, 10	question-auto (env.)	 2682
catalog	 10	\QuestionIndicative	 13, 1340, 1346, 1373, 1408
chiffres	 21	questionmult (env.)	 11, 1295
completemulti	 10	Questionnaires (env.)	 2682
correc	 21	\questionnum	 1325
correcindiv	 21	questionnouverte (env.)	 1295
digits	 10		
ensemble	 21	R	
francais	 10	\raggedcolumns	 1092
fullgroups	 11	\raisebox	 1647
indivanswers	 6, 10	\refstepcounter	 1288
init	 10	\reponses	 2864
insidebox	 10	reponses (env.)	 21
keys	 10	\reponseshoriz	 2865
nopage	 6, 11	reponseshoriz (env.)	 21
noshuffle	 10	\reponsesperso	 2866
noshufflegroups	 10	reponsesperso (env.)	 21
nowatermark	 4, 10	\restituegroupe	 21, 2876
ordre	 21	\retick	 361
outsidebox	 10	\rngstate	 2560
pdfform	 11		
plain	 11	S	
postcorrect	 11	\savebox	 389
separateanswersheet	 5, 10, 16	\savepos	 2765
storebox	 11	\sbox	 1176
\or	 83, 85	\scoring	 13, 1340, 1346, 1373, 2869
ordre (option)	 21	\scoringDefaultM	 13, 1373, 2870
outsidebox (option)	 10	\scoringDefaultS	 13, 1373, 2871
\ouverte@vs	 1295	\ScoringExterne	 2782
P		\section	 1099, 1103
\PackageError	 677, 719, 790, 2743	separateanswersheet (op-	 5, 10, 16
\pageref	 2597	tion)	 5, 10, 16
pdfform (option)	 11	\seq	 233, 234, 237, 238, 239, 242, 249, 1390, 1464, 1472, 1538, 1546, 1547, 1548
\pdfpageheight	358, 2777, 2778	\setdefaultgroupmode	 715
\pdfpagewidth	358, 2774, 2775	\setgroupmode	 701, 715
\pgfextractx	 1184	\shuffle@it	 849, 863
\pgfmath@rnd@z	 2783, 2786		
\pgfmathparse	 2786	V	
\pgfmathresult	 2787	\value	 1032
		values (env.)	 2682

values-auto (env.)	2682	\vtop	1467	\wrongchoice	13 ,
variable-auto (env.) . . .	2682				873 , 874 , 1157 , 2276 , 2868
variable-multi (env.) . .	1295	W			
variable-single (env.) .	1295	\wd	398 , 399 , 1075 , 1176		
\version	2849	\with . . .	1439 , 2608 , 2609 ,	X	
\vfuzz	398		2850 , 2851 , 2852 ,	\x	2708 , 2710
\vrule	1986		2853 , 2854 , 2855 ,	\xyclose	373
			2856 , 2857 , 2859 , 2861	\xyopen	371